

# A Brief Review of Nature-Inspired Algorithms for Optimization

Iztok Fister Jr.<sup>1</sup>, Xin-She Yang<sup>2</sup>, Iztok Fister<sup>1</sup>, Janez Brest<sup>1</sup>, Dušan Fister<sup>1</sup>

<sup>1</sup>University of Maribor

Faculty of electrical engineering and computer science, Smetanova 17, 2000 Maribor, Slovenia

E-mail: iztok.fister@guest.arnes.si

<sup>2</sup>University of Middlesex

School of Science and Technology, Middlesex University, London NW4 4BT, United Kingdom

E-mail: xy227@cam.ac.uk

**Abstract.** Swarm-intelligence-based and bio-inspired algorithms form a hot topic in the developments of new algorithms inspired by nature. These nature-inspired metaheuristic algorithms can be based on swarm intelligence, biological systems, physical and chemical systems. Therefore, these algorithms can be called swarm-intelligence-based, bio-inspired, physics- and chemistry-based, depending on the sources of inspiration. Though not all of them are efficient, a few algorithms have proved to be very efficient and thus have become popular tools for solving real-world problems. Some of the algorithms have been insufficiently studied. The purpose of this review is to present a relatively comprehensive list of all the algorithms in the literature, so as to inspire further research.

**Keywords:** swarm intelligence, bio-inspired algorithms, physics/chemistry algorithms, optimization

## Kratki pregled algoritmov po vzoru iz narave za optimizacijo

Inteligenca rojev (angl. Swarm Intelligence, krajše SI) in algoritmi po vzoru iz biologije ponujajo nove smernice v razvoju novih algoritmov po vzoru iz narave. Ti metahevrstični algoritmi lahko bazirajo na inteligenci rojev, bioloških sistemih ter fizikalnih in kemijskih sistemih. Glede na njihov vzor, ki ga posnemajo, te delimo na algoritme z inteligenco rojev, algoritme na osnovi bioloških sistemov, in algoritme na osnovi fizikalnih oz. kemijskih sistemov. Čeprav vsi algoritmi te vrste niso učinkoviti, pa nekateri izmed njih kažejo ravno obratno in zato je z njimi moč reševati realne probleme. Nekateri izmed njih nimajo teoretične podlage. V članku želimo predstaviti širok seznam vseh današnjih algoritmov po vzoru iz narave, da bi vspodbudili njihov nadaljni razvoj.

## 1 INTRODUCTION

Real-world optimization problems are often very challenging to solve, and many applications have to deal with the NP-hard problems. To solve such problems, optimization tools have to be used, though there is no guarantee that the optimal solution can be obtained. In fact, for the NP-problems, there are no efficient algorithms at all. As a result, many problems have to be solved by trial and errors using various optimization techniques. In addition, new algorithms have been developed to see if they can cope with these challenging optimization problems.

Among these new algorithms, many algorithms such as particle swarm optimization, cuckoo search and firefly algorithm, have gained popularity due to their high efficiency. In the current literature, there are about 40 different algorithms. It is really a challenging task to classify these algorithms systematically. Obviously, the classifications can largely depend on the criteria, and there is no easy guideline to set out the criteria in the literature. As criteria may vary, detailed classifications can be an impossible task for a research paper. However, in this short paper, we only attempt to focus on one aspect of the characteristics of these algorithms. That is, we will focus on the source of inspiration when developing algorithms.

Therefore, the rest of this paper is organized as follows: Section 2 analyzes the sources of inspiration, Section 3 provides a brief and yet comprehensive list of algorithms and, Section 4 concludes the paper with some suggestions.

## 2 SOURCES OF INSPIRATION

Nature has inspired many researchers in many ways and thus is a rich source of inspiration. Nowadays, most new algorithms are nature-inspired, because they have been developed by drawing inspiration from nature. Even with the emphasis on the source of inspiration, we can still have different levels of classifications, depending on how details and how many subsources we will wish to use. For the sake of simplicity, we will use the highest level

sources such as biology, physics or chemistry.

In the most generic term, the main source of inspiration is nature. Therefore, almost all the new algorithms can be referred to as nature-inspired. By far the majority of the nature-inspired algorithms are based on some successful characteristics of the biological system. Therefore, the largest fraction of the nature-inspired algorithms are biology-inspired, or bio-inspired for short.

Among the bio-inspired algorithms, a special class of algorithms have been developed by drawing inspiration from swarm intelligence. Therefore, some of the bio-inspired algorithms can be called swarm-intelligence-based. In fact, algorithms based on swarm intelligence are among the most popular. Good examples are ant colony optimization [1], particle swarm optimization [2], cuckoo search [3], bat algorithm [4], and firefly algorithm [5], [6].

Obviously, not all the algorithms have been based on biological systems. Many algorithms have been developed by using inspiration from physical and chemical systems. Some may even be based on music [7]. In the rest of the paper, we will briefly divide all the algorithms into different categories without claiming this categorization to be unique. This is a good attempt to provide sufficiently detailed references.

### 3 CLASSIFICATION OF ALGORITHMS

Based on the above discussions, we can divide all the existing algorithms into four major categories: swarm-intelligence (SI)-based, bio-inspired (but not SI-based), physics/chemistry-based, and others. We will summarize them briefly in the rest of this paper. However, we will focus here on the relatively new algorithms. The Well-established algorithms such as genetic algorithms are so well known that there is no need to introduce them in this brief paper.

It is worth pointing out the classifications given here are not unique as some of the algorithms can be classified into several categories at the same time. Loosely speaking, classifications depend largely on what the focus or emphasis and the perspective may be. For example, if the focus and perspective are about the trajectory of the search path, the algorithms can be classified as trajectory- and population-based. Simulated annealing is a good example of the trajectory-based algorithms, while particle swarm optimization and firefly algorithms are the population-based algorithms. If our emphasis is placed on the interaction of the multiple agents, the algorithms can be classified as attraction-based or non-attraction-based. The Firefly algorithm (FA) is a good example of the attraction-based algorithms because FA uses the attraction of light and attractiveness of fireflies, while the genetic algorithms are non-attraction-based since there is no explicit attraction

used. On the other hand, if the emphasis is placed on the updating equations, the algorithms can be divided into rule- and equation-based. For example, particle swarm optimization and cuckoo search are the equation-based algorithms for using explicit updating equations, while the genetic algorithms do not have explicit equations for crossover and mutation. However, in this case, the classifications are not unique. For example, FA uses three explicit rules that can be converted explicitly into a single updating equation which is nonlinear [5], [6]. This clearly shows that classifications depend on the actual perspective and motivations. Therefore, the classifications here are just one possible attempt, though the emphasis is placed on the sources of inspiration.

#### 3.1 Swarm-intelligence-based algorithms

Swarm intelligence (SI) concerns the collective, emerging behaviour of multiple, interacting agents who follow some simple rules. While each agent may be considered as unintelligent, the whole system of the multiple agents may show some self-organization behaviour and thus can behave like some sort of collective intelligence. Many algorithms have been developed by drawing inspiration from the swarm-intelligence systems in nature.

All the SI-based algorithms use multi-agents inspired by the collective behaviour of social insects, like ants, termites, bees, and wasps, as well of other animal societies like flocks of birds or fish. A list of the SI algorithms is presented in Table 1. The classical particle swarm optimization (PSO) uses the swarming behaviour of fish and birds, while the firefly algorithm (FA) uses the flashing behaviour of swarming fireflies. Cuckoo search (CS) is based on the brooding parasitism of some cuckoo species, while the bat algorithm uses the echolocation of foraging bats. Ant-colony optimization uses the interaction of social insects (e.g., ants), while the class of the bee algorithms is all based on the foraging behaviour of the honey bees.

The SI-based algorithms are among the most popular and widely used. There are many reasons for such popularity. One of them is that the SI-based algorithms usually share information among the multiple agents, so that self-organization, co-evolution and learning during iterations may help to provide the high efficiency of most SI-based algorithms. Another reason is that the multiple agent can be parallelized easily so that large-scale optimization becomes more practical from the implementation point of view.

#### 3.2 Bio-inspired, but not SI-based algorithms

Obviously, the SI-based algorithms belong to a wider class of the algorithms, called the bio-inspired algorithms. In fact, the bio-inspired algorithms form a majority of all the nature-inspired algorithms. From the set theory point of view, the SI-based algorithms are

a subset the of bio-inspired algorithms, while the bio-inspired algorithms are a subset of the nature-inspired algorithms. That is

$$\text{SI-based} \subset \text{bio-inspired} \subset \text{nature-inspired}.$$

Conversely, not all the nature-inspired algorithms are bio-inspired, and some are purely physics- and chemistry- based algorithms as we will see below.

Many bio-inspired algorithms do not use directly the swarming behaviour. Therefore, it is better to call them bio-inspired, but not SI-based. For example, the genetic algorithms are bio-inspired, but not SI-based. However, it is not easy to classify certain algorithms such as differential evolution (DE). Strictly speaking, DE is not bio-inspired because there is no direct link to any biological behaviour. However, as it has some similarity with the genetic algorithms and also has a key word ‘evolution’, we tentatively put it in the category of bio-inspired algorithms. These algorithms are listed in Table 1.

For example, the flower algorithm [8], or flower pollination algorithm [9], developed by Xin-She Yang in 2012, is a bio-inspired algorithm, but it is not an SI-based algorithm because the flower algorithm tries to mimic the pollination characteristics of flowering plants and the associated flower consistency of some pollinating insects.

### 3.3 Physics- and Chemistry-Based algorithms

Not all the metaheuristic algorithms are bio-inspired, because their sources of inspiration often come from physics and chemistry. For the algorithms that are not bio-inspired, most have been developed by mimicking certain physical and/or chemical laws, including electrical charges, gravity, river systems, etc. As different natural systems are relevant to this category, we could even subdivide them into many subcategories which is not necessary. A list of these algorithms is given in Table 1.

Schematically, we can present the relationship between the physics- and chemistry based algorithms as follows:

$$\left. \begin{array}{l} \text{Physics algorithms} \\ \text{Chemistry algorithms} \end{array} \right\} \begin{array}{l} \notin \text{bio-inspired algorithms} \\ \in \text{nature-inspired algorithms} \end{array}$$

Though physics and chemistry are two different subjects, however, it is not useful to subdivide this subcategory further into the physics- and chemistry-based algorithms. After all, many fundamental laws are the same. So we simply group them as the physics- and chemistry-based algorithms.

### 3.4 Other algorithms

When researchers develop new algorithms, some may look for inspiration away from nature. Consequently, as some algorithms are not bio-inspired or

physic/chemistry-based, it is sometimes difficult to put some algorithms in the above three categories, because these algorithms have been developed by using various characteristics from different sources, such as social, emotional, etc. In this case, it is better to put them in some other category, as listed in Table 1.

### 3.5 Some Remarks

Though the sources of inspiration are very diverse, the algorithm designed from such inspiration may be equally diverse. However, care should be taken, as a true novelty is a rare thing. For example, though there are about 28,000 living species of fish, this cannot mean that researchers should develop 28,000 different fish-based algorithms. Therefore, they cannot call their algorithms trout algorithm, squid algorithm, ..., shark algorithm.

As a matter of fact, researchers try to look for some efficient formulas as summarized by Yang [10] in the following generic scheme:

$$[x_1, x_2, \dots, x_n]^{t+1} = A\{[x_1, x_2, \dots, x_n]^t, \dots; (p_1, p_2, \dots, p_k); (w_1, w_2, \dots, w_m)\},$$

which attempts to generate better solutions (a population of  $n$  solutions) at iteration  $t+1$  from the current iteration  $t$  and its solution set  $x_i, (i = 1, 2, \dots, n)$ . This iterative algorithmic engine (i.e. algorithm  $A$ ) also uses some algorithm-dependent parameters  $(p_1, \dots, p_k)$  and some random variables  $(w_1, \dots, w_m)$ . This schematic representation can include all the algorithms listed in this paper. However, this does not mean it is easy to analyze the behaviour of an algorithm because this formula can be highly nonlinear. Though the Markov chains theory and dynamic-system theory can help providing some limited insight into some algorithms, a detailed mathematical framework is still yet to be developed.

On the other hand, it is worth pointing out that studies show that some algorithms are better than others. It is still not quite understood why. However, if one looks at the intrinsic part of the algorithm design closely, some algorithms are badly designed; they lack certain basic capabilities such as mixing and diversity among the solutions. In contrast, good algorithms have both mixing and diversity control so that the algorithms can explore the vast search space efficiently, while they converge relatively quickly when necessary. Good algorithms, such as particle swarm optimization, differential evolution, cuckoo search and FAs all have both global search and intensive local search capabilities, which may be partly why they are so efficient.

Swarm intelligence based algorithms		Bio-inspired (not SI-based) algorithms	
Algorithm	Author	Algorithm	Author
Accelerated PSO	Yang et al.	Atmosphere clouds model	Yan and Hao
Ant colony optimization	Dorigo	Biogeography-based optimization	Simon
Artificial bee colony	Karaboga and Basturk	Brain Storm Optimization	Shi
Bacterial foraging	Passino	Differential evolution	Storn and Price
Bacterial-GA Foraging	Chen et al.	Dolphin echolocation	Kaveh and Farhoudi
Bat algorithm	Yang	Japanese tree frogs calling	Hernández and Blum
Bee colony optimization	Teodorović and Dell'Orco	Eco-inspired evolutionary algorithm	Parpinelli and Lopes
Bee system	Lucic and Teodorovic	Egyptian Vulture	Sur et al.
BeeHive	Wedde et al.	Fish-school Search	Lima et al.
Wolf search	Tang et al.	Flower pollination algorithm	Yang
Bees algorithms	Pham et al.	Gene expression	Ferreira
Bees swarm optimization	Drias et al.	Great salmon run	Mozaffari
Bumblebees	Comellas and Martinez	Group search optimizer	He et al.
Cat swarm	Chu et al.	Human-Inspired Algorithm	Zhang et al.
Consultant-guided search	Iordache	Invasive weed optimization	Mehrabian and Lucas
Cuckoo search	Yang and Deb	Marriage in honey bees	Abbass
Eagle strategy	Yang and Deb	OptBees	Maia et al.
Fast bacterial swarming algorithm	Chu et al.	Paddy Field Algorithm	Premaratne et al.
Firefly algorithm	Yang	Roach infestation algorithm	Havens
Fish swarm/school	Li et al.	Queen-bee evolution	Jung
Good lattice swarm optimization	Su et al.	Shuffled frog leaping algorithm	Eusuff and Lansay
Glowworm swarm optimization	Krishnanand and Ghose	Termite colony optimization	Hedayatzadeh et al.
Hierarchical swarm model	Chen et al.	<i>Physics and Chemistry based algorithms</i>	
Krill Herd	Gandomi and Alavi	Big bang-big Crunch	Zandi et al.
Monkey search	Mucherino and Seref	Black hole	Hatamlou
Particle swarm algorithm	Kennedy and Eberhart	Central force optimization	Formato
Virtual ant algorithm	Yang	Charged system search	Kaveh and Talatahari
Virtual bees	Yang	Electro-magnetism optimization	Cuevas et al.
Weightless Swarm Algorithm	Ting et al.	Galaxy-based search algorithm	Shah-Hosseini
		Gravitational search	Rashedi et al.
		Harmony search	Geem et al.
Anarchic society optimization	Shayeghi and Dadashpour	Intelligent water drop	Shah-Hosseini
Artificial cooperative search	Civicioglu	River formation dynamics	Rabanal et al.
Backtracking optimization search	Civicioglu	Self-propelled particles	Vicsek
Differential search algorithm	Civicioglu	Simulated annealing	Kirkpatrick et al.
Grammatical evolution	Ryan et al.	Stochastic diffusion search	Bishop
Imperialist competitive algorithm	Atashpaz-Gargari and Lucas	Spiral optimization	Tamura and Yasuda
League championship algorithm	Kashan	Water cycle algorithm	Eskandar et al.
Social emotional optimization	Xu et al.		

Table 1. A list of algorithms

## 4 CONCLUSION

The sources of inspiration for algorithm development are very diverse, and consequently the algorithms are equally diverse. In this paper, we briefly summarized all the algorithms into four categories. This can be a comprehensive source of information to form a basis or point of reference for further research. It is worth noting that the algorithm classifications may not be unique, and the presented table should be used for the purpose of information only.

Based on many studies in the literature, some algorithms are more efficient and popular than others. It would be helpful to carry out more studies, but this does not mean that we should encourage researchers to develop more algorithms such as grass, sky, or ocean algorithms.

Currently, there may be some confusion and distraction in the research of metaheuristic algorithms. On one hand, researchers have focused on important novel ideas for solving difficult problems. On the other hand, some researchers, have artificially invented new algorithms for the sake of publications with little improvement and no novelty. Researchers should be encouraged to carry out truly novel and important studies that would really be useful in solving hard problems. Therefore, our aim is to inspire more research to gain a better insight into the efficient algorithms to be used in solving large-scale real-world problems.

## REFERENCES

- [1] Marco Dorigo. Optimization, learning and natural algorithms. *Ph. D. Thesis, Politecnico di Milano, Italy*, 1992.
- [2] James Kennedy and Russell Eberhart. Particle swarm optimization. In *Neural Networks, 1995. Proceedings., IEEE International Conference on*, volume 4, pages 1942–1948. IEEE, 1995.
- [3] Xin-She Yang and Suash Deb. Cuckoo search via lévy flights. In *Nature & Biologically Inspired Computing, 2009. NaBIC 2009. World Congress on*, pages 210–214. IEEE, 2009.
- [4] Xin-She Yang. A new metaheuristic bat-inspired algorithm. *Nature Inspired Cooperative Strategies for Optimization (NICSO 2010)*, pages 65–74, 2010.
- [5] Xin-She Yang. *Nature-Inspired Metaheuristic Algorithms*. Luniver Press, UK, 2008.
- [6] Iztok Fister, Iztok Fister Jr., Xin-She Yang, and Janez Brest. A comprehensive review of firefly algorithms. *Swarm and Evolutionary Computation*, 2013.
- [7] Zong Woo Geem, Joong Hoon Kim, and GV Loganathan. A new heuristic optimization algorithm: harmony search. *Simulation*, 76(2):60–68, 2001.
- [8] Xin-She Yang. Flower pollination algorithm for global optimization. *Unconventional Computation and Natural Computation*, pages 240–249, 2012.
- [9] Xin-She Yang, Mehmet Karamanoglu, and Xingshi He. Multi-objective flower algorithm for optimization. *Procedia Computer Science*, 18:861–868, 2013.
- [10] Xin-She Yang, Zhihua Cui, Renbin Xiao, Amir Hossein Gandom, and Mehmet Karamanoglu. *Swarm Intelligence and Bio-inspired Computation: Theory and Applications*. Elsevier, 2013.
- [11] Xin-She Yang. *Nature-Inspired Metaheuristic Algorithms, 2nd Edition*. Luniver Press, 2010.
- [12] GAO-WEI YAN and ZHAN-JU HAO. A novel optimization algorithm based on atmosphere clouds model. *International Journal of Computational Intelligence and Applications*, 2013.
- [13] Dan Simon. Biogeography-based optimization. *Evolutionary Computation, IEEE Transactions on*, 12(6):702–713, 2008.
- [14] Dervis Karaboga and Bahriye Basturk. A powerful and efficient algorithm for numerical function optimization: artificial bee colony (abc) algorithm. *Journal of global optimization*, 39(3):459–471, 2007.
- [15] Yuhui Shi. An optimization algorithm based on brainstorming process. *International Journal of Swarm Intelligence Research (IJSIR)*, 2(4):35–62, 2011.
- [16] Kevin M Passino. Biomimicry of bacterial foraging for distributed optimization and control. *Control Systems, IEEE*, 22(3):52–67, 2002.
- [17] Rainer Storn and Kenneth Price. Differential evolution—a simple and efficient heuristic for global optimization over continuous spaces. *Journal of global optimization*, 11(4):341–359, 1997.
- [18] Tai-Chen Chen, Pei-Wei Tsai, Shu-Chuan Chu, and Jeng-Shyang Pan. A novel optimization approach: bacterial-ga foraging. In *Innovative Computing, Information and Control, 2007. ICI-CIC'07. Second International Conference on*, pages 391–391. IEEE, 2007.
- [19] A Kaveh and N Farhoudi. A new optimization method: Dolphin echolocation. *Advances in Engineering Software*, 59:53–70, 2013.
- [20] Hugo Hernández and Christian Blum. Distributed graph coloring: an approach based on the calling behavior of japanese tree frogs. *Swarm Intelligence*, 6(2):117–150, 2012.
- [21] Dušan Teodorović and Mauro Dell’Orco. Bee colony optimization—a cooperative learning approach to complex transportation problems. In *Advanced OR and AI Methods in Transportation: Proceedings of 16th Mini-EURO Conference and 10th Meeting of EWGT (13-16 September 2005)—Poznan: Publishing House of the Polish Operational and System Research*, pages 51–60, 2005.
- [22] RS Parpinelli and HS Lopes. An eco-inspired evolutionary algorithm applied to numerical optimization. In *Nature and Biologically Inspired Computing (NaBIC), 2011 Third World Congress on*, pages 466–471. IEEE, 2011.
- [23] P Lucic and D Teodorovic. Bee system: modeling combinatorial optimization transportation engineering problems by swarm intelligence. In *Preprints of the TRISTAN IV triennial symposium on transportation analysis*, pages 441–445, 2001.
- [24] Chiranjib Sur, Sanjeev Sharma, and Anupam Shukla. Egyptian vulture optimization algorithm—a new nature inspired metaheuristics for knapsack problem. In *The 9th International Conference on Computing and Information Technology (IC2IT2013)*, pages 227–237. Springer, 2013.
- [25] H.F. Wedde, M. Farooq, and Y. Zhang. Beehive: An efficient fault-tolerant routing algorithm inspired by honey bee behavior. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 3172 LNCS:83–94, 2004.
- [26] FB de Lima Neto, AJCC Lins, Antônio IS Nascimento, Marília P Lima, et al. A novel search algorithm based on fish school behavior. In *Systems, Man and Cybernetics, 2008. SMC 2008. IEEE International Conference on*, pages 2646–2651. IEEE, 2008.
- [27] Carmelo JA Bastos Filho, Fernando B de Lima Neto, Anthony JCC Lins, Antônio IS Nascimento, and Marília P Lima. Fish school search. In *Nature-Inspired Algorithms for Optimisation*, pages 261–277. Springer, 2009.
- [28] Rui Tang, S. Fong, Xin-She Yang, and S. Deb. Wolf search algorithm with ephemeral memory. In *Digital Information Management (ICDIM), 2012 Seventh International Conference on*, pages 165–172, 2012.
- [29] DT Pham, A Ghanbarzadeh, E Koc, S Otri, S Rahim, and M Zaidi. The bees algorithm—a novel tool for complex optimization problems. In *Proceedings of the 2nd Virtual International Conference on Intelligent Production Machines and Systems (IPROMS 2006)*, pages 454–459, 2006.
- [30] Candida Ferreira. Gene expression programming: a new adaptive

- algorithm for solving problems. *arXiv preprint cs/0102027*, 2001.
- [31] Habiba Drias, Souhila Sadeg, and Safa Yahi. Cooperative bees swarm for solving the maximum weighted satisfiability problem. In *Computational Intelligence and Bioinspired Systems*, pages 318–325. Springer, 2005.
- [32] Ahmad Mozaffari, Alireza Fathi, and Saeed Behzadipour. The great salmon run: a novel bio-inspired algorithm for artificial system design and optimisation. *International Journal of Bio-Inspired Computation*, 4(5):286–301, 2012.
- [33] Francesc de Paula Comellas Padró, Jesús Martínez Navarro, et al. Bumblebees: a multiagent combinatorial optimization algorithm inspired by social insect behaviour. 2011.
- [34] S He, QH Wu, and JR Saunders. Group search optimizer: an optimization algorithm inspired by animal searching behavior. *Evolutionary Computation, IEEE Transactions on*, 13(5):973–990, 2009.
- [35] S.-A. Chu, P.-W. Tsai, and J.-S. Pan. Cat swarm optimization. *Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)*, 4099 LNAI:854–858, 2006. cited By (since 1996) 8.
- [36] Luna Mingyi Zhang, Cheyenne Dahmann, and Yanqing Zhang. Human-inspired algorithms for continuous function optimization. In *Intelligent Computing and Intelligent Systems, 2009. ICIS 2009. IEEE International Conference on*, volume 1, pages 318–321. IEEE, 2009.
- [37] Serban Iordache. Consultant-guided search: a new metaheuristic for combinatorial optimization problems. In *Proceedings of the 12th annual conference on Genetic and evolutionary computation*, pages 225–232. ACM, 2010.
- [38] A Reza Mehrabian and C Lucas. A novel numerical optimization algorithm inspired from weed colonization. *Ecological Informatics*, 1(4):355–366, 2006.
- [39] Hussein A Abbass. Mbo: Marriage in honey bees optimization—a haplometrosis polygynous swarming approach. In *Evolutionary Computation, 2001. Proceedings of the 2001 Congress on*, volume 1, pages 207–214. IEEE, 2001.
- [40] Xin-She Yang and Suash Deb. Eagle strategy using lévy walk and firefly algorithms for stochastic optimization. In *Nature Inspired Cooperative Strategies for Optimization (NICSO2010)*, pages 101–111. Springer, 2010.
- [41] Renato Dourado Maia, Leandro Nunes de Castro, and Waldir Matos Caminhas. Bee colonies as model for multimodal continuous optimization: The optbees algorithm. In *Evolutionary Computation (CEC), 2012 IEEE Congress on*, pages 1–8. IEEE, 2012.
- [42] Ying Chu, Hua Mi, Huilian Liao, Zhen Ji, and QH Wu. A fast bacterial swarming algorithm for high-dimensional function optimization. In *Evolutionary Computation, 2008. CEC 2008. (IEEE World Congress on Computational Intelligence). IEEE Congress on*, pages 3135–3140. IEEE, 2008.
- [43] Upeka Premaratne, Jagath Samarabandu, and Tarlochan Sidhu. A new biologically inspired optimization algorithm. In *Industrial and Information Systems (ICIS), 2009 International Conference on*, pages 279–284. IEEE, 2009.
- [44] Xin-She Yang. Firefly algorithm, stochastic test functions and design optimisation. *International Journal of Bio-Inspired Computation*, 2(2):78–84, 2010.
- [45] Timothy C Havens, Christopher J Spain, Nathan G Salmon, and James M Keller. Roach infestation optimization. In *Swarm Intelligence Symposium, 2008. SIS 2008. IEEE*, pages 1–7. IEEE, 2008.
- [46] X.-L. Li, Z.-J. Shao, and J.-X. Qian. Optimizing method based on autonomous animats: Fish-swarm algorithm. *Xitong Gongcheng Lilun yu Shijian/System Engineering Theory and Practice*, 22(11):32, 2002.
- [47] Sung Hoon Jung. Queen-bee evolution for genetic algorithms. *Electronics letters*, 39(6):575–576, 2003.
- [48] Shoubao Su, Jiwen Wang, Wangkang Fan, and Xibing Yin. Good lattice swarm algorithm for constrained engineering design optimization. In *Wireless Communications, Networking and Mobile Computing, 2007. WiCom 2007. International Conference on*, pages 6421–6424. IEEE, 2007.
- [49] M.M. Eusuff and K.E. Lansey. Optimization of water distribution network design using the shuffled frog leaping algorithm. *Journal of Water Resources Planning and Management*, 129(3):210–225, 2003. cited By (since 1996) 297.
- [50] KN Krishnanand and D Ghose. Detection of multiple source locations using a glowworm metaphor with applications to collective robotics. In *Swarm Intelligence Symposium, 2005. SIS 2005. Proceedings 2005 IEEE*, pages 84–91. IEEE, 2005.
- [51] KN Krishnanand and D Ghose. Glowworm swarm optimisation: a new method for optimising multi-modal functions. *International Journal of Computational Intelligence Studies*, 1(1):93–119, 2009.
- [52] Ramin Hedayatzadeh, Foad Akhavan Salmassi, Manijeh Keshtgari, Reza Akbari, and Koorush Ziarati. Termite colony optimization: A novel approach for optimizing continuous problems. In *Electrical Engineering (ICEE), 2010 18th Iranian Conference on*, pages 553–558. IEEE, 2010.
- [53] Hanning Chen, Yunlong Zhu, Kunyuan Hu, and Xiaoxian He. Hierarchical swarm model: a new approach to optimization. *Discrete Dynamics in Nature and Society*, 2010, 2010.
- [54] Amir Hossein Gandomi and Amir Hossein Alavi. Krill herd: a new bio-inspired optimization algorithm. *Communications in Nonlinear Science and Numerical Simulation*, 2012.
- [55] Z Zandi, E Afjei, and M Sedighzadeh. Reactive power dispatch using big bang-big crunch optimization algorithm for voltage stability enhancement. In *Power and Energy (PECon), 2012 IEEE International Conference on*, pages 239–244. IEEE, 2012.
- [56] Antonio Mucherino and Onur Seref. Monkey search: a novel metaheuristic search for global optimization. In *Data Mining, Systems Analysis and Optimization in Biomedicine*, volume 953, pages 162–173, 2007.
- [57] Abdolreza Hatamlou. Black hole: A new heuristic optimization approach for data clustering. *Information Sciences*, 2012.
- [58] Richard A Formato. Central force optimization: A new metaheuristic with applications in applied electromagnetics. *Progress In Electromagnetics Research*, 77:425–491, 2007.
- [59] Xin-She Yang, Janet M Lees, and Chris T Morley. Application of virtual ant algorithms in the optimization of cfrp shear strengthened precracked structures. In *Computational Science—ICCS 2006*, pages 834–837. Springer, 2006.
- [60] A Kaveh and S Talatahari. A novel heuristic optimization method: charged system search. *Acta Mechanica*, 213(3-4):267–289, 2010.
- [61] X.-S. Yang. Engineering optimizations via nature-inspired virtual bee algorithms. volume 3562, pages 317–323, 2005.
- [62] Erik Cuevas, Diego Oliva, Daniel Zaldivar, Marco Pérez-Cisneros, and Humberto Sossa. Circle detection using electromagnetism optimization. *Information Sciences*, 182(1):40–55, 2012.
- [63] TO Ting, Ka Lok Man, Sheng-Uei Guan, Mohamed Nayel, and Kaiyu Wan. Weightless swarm algorithm (wsa) for dynamic optimization problems. In *Network and Parallel Computing*, pages 508–515. Springer, 2012.
- [64] Hamed Shah-Hosseini. Principal components analysis by the galaxy-based search algorithm: a novel metaheuristic for continuous optimisation. *International Journal of Computational Science and Engineering*, 6(1):132–140, 2011.
- [65] Esmat Rashedi, Hossein Nezamabadi-Pour, and Saeid Saryazdi. Gsa: a gravitational search algorithm. *Information sciences*, 179(13):2232–2248, 2009.
- [66] H Shayeghi and J Dadashpour. Anarchic society optimization based pid control of an automatic voltage regulator (avr) system. *Electrical and Electronic Engineering*, 2(4):199–207, 2012.
- [67] P. Civicioglu. Artificial cooperative search algorithm for numerical optimization problems. *Information Sciences*, 229:58–76, 2013.
- [68] Hamed Shah-Hosseini. Problem solving by intelligent water drops. In *Evolutionary Computation, 2007. CEC 2007. IEEE Congress on*, pages 3226–3231. IEEE, 2007.
- [69] Pinar Civicioglu. Backtracking search optimization algorithm for numerical optimization problems. *Applied Mathematics and Computation*, 219(15):8121–8144, 2013.

- [70] Pablo Rabanal, Ismael Rodríguez, and Fernando Rubio. Using river formation dynamics to design heuristic algorithms. In *Unconventional Computation*, pages 163–177. Springer, 2007.
- [71] Pinar Civiciglu. Transforming geocentric cartesian coordinates to geodetic coordinates by using differential search algorithm. *Computers & Geosciences*, 46:229–247, 2012.
- [72] Tamás Vicsek, András Czirók, Eshel Ben-Jacob, Inon Cohen, and Ofer Shochet. Novel type of phase transition in a system of self-driven particles. *Physical Review Letters*, 75(6):1226–1229, 1995.
- [73] Conor Ryan, JJ Collins, and Michael O Neill. Grammatical evolution: Evolving programs for an arbitrary language. In *Genetic Programming*, pages 83–96. Springer, 1998.
- [74] Scott Kirkpatrick, D. Gelatt Jr., and Mario P Vecchi. Optimization by simulated annealing. *Science*, 220(4598):671–680, 1983.
- [75] Esmaeil Atashpaz-Gargari and Caro Lucas. Imperialist competitive algorithm: an algorithm for optimization inspired by imperialistic competition. In *Evolutionary Computation, 2007. CEC 2007. IEEE Congress on*, pages 4661–4667. IEEE, 2007.
- [76] JM Bishop. Stochastic searching networks. In *Artificial Neural Networks, 1989., First IEE International Conference on (Conf. Publ. No. 313)*, pages 329–331. IET, 1989.
- [77] Ali Husseinzadeh Kashan. League championship algorithm: a new algorithm for numerical function optimization. In *Soft Computing and Pattern Recognition, 2009. SOCPAR'09. International Conference of*, pages 43–48. IEEE, 2009.
- [78] Kenichi Tamura and Keiichiro Yasuda. Spiral dynamics inspired optimization. *Journal of Advanced Computational Intelligence and Intelligent Informatics*, 15(8):1116–1122, 2011.
- [79] Yuechun Xu, Zhihua Cui, and Jianchao Zeng. Social emotional optimization algorithm for nonlinear constrained optimization problems. In *Swarm, Evolutionary, and Memetic Computing*, pages 583–590. Springer, 2010.
- [80] Hadi Eskandar, Ali Sadollah, Ardeshir Bahreininejad, and Mohd Hamdi. Water cycle algorithm—a novel metaheuristic optimization method for solving constrained engineering optimization problems. *Computers & Structures*, 2012.

**Janez Brest** received his B.S., M.Sc., and Ph.D. degrees in computer science from the University of Maribor, Maribor, Slovenia, in 1995, 1998 and 2000, respectively. He is currently a full professor at the Faculty of Electrical Engineering and Computer Science, University of Maribor.

**Dušan Fister** is a student at the Faculty of Electrical Engineering and Computer Science of the University of Maribor. His research activities encompass GPS solutions, swarm intelligence and operating systems.

**Iztok Fister Jr.** received his B.Sc. degree in Computer Science in 2011 from the Faculty of Electrical Engineering and Computer Science of the University of Maribor, Slovenia. Currently, he is working towards his M.Sc. degree. His research activities encompass swarm intelligence, pervasive computing and programming languages.

**Xin-She Yang** received his Ph.D. degree in Applied Mathematics from University of Oxford, UK. Now he is a Reader in Modelling and Simulation at Middlesex University, UK, an Adjunct Professor at Reykjavik University, Iceland, and a Distinguished Guest Professor at Xi'an Polytechnic University, China. He is also the IEEE CIS Chair for the Task Force on Business Intelligence and Knowledge Management, and the Editor-in-Chief of International Journal of Mathematical Modelling and Numerical Optimisation (IJMMNO).

**Iztok Fister** graduated in computer science from the University of Ljubljana in 1983. He received his Ph.D. degree from the Faculty of Electrical Engineering and Computer Science, University of Maribor, in 2007. He works as teaching assistant in the Computer Architecture and Languages Laboratory at the same faculty. His research interests include program languages, operational researches and evolutionary algorithms.