June 1970

NASA TECH BRIEF

NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Division, NASA, Code UT, Washington, D.C. 20546.



Audio Signal Processor

The signal-processing system diagrammed above provides automatic volume control for an audio amplifier or a voice communication system without introducing noise surges during pauses in the input, and without losing the initial signal when the input resumes.

The preamplifier output is fed through a variablegain amplifier to a conventional automatic volume control (AVC) circuit, and also through an audio switch, which detects the presence of a signal and controls the variable-gain amplifier. When the system input halts for more than a moment the audio switch reduces the gain of the amplifier at approximately the same rate as the AVC circuit increases its gain. Thus, the increased AVC gain is nullified, and no noise surge occurs. When the signal resumes, the audio switch returns the amplifier gain to normal, at a rate approximately equal to the decay of the AVC gain, in order to maintain overall gain at a constant level.

False noise triggering is controlled by setting the detection threshold of the switch slightly above the ambient noise level. A short delay is provided in the switch turn-on time to furnish even greater protection against false triggering by high-amplitude, short-duration impulses.

Note:

Requests for further information may be directed to: Technology Utilization Officer

> Manned Spacecraft Center, Code BM7 Houston, Texas 77058 Reference: TSP70-10180

> > (continued overleaf)

This document was prepared under the sponsorship of the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States Government assumes any liability resulting from the use of the information contained in this document, or warrants that such use will be free from privately owned rights.

Patent status:

This invention is owned by NASA, and a patent application has been filed. Royalty-free, nonexclusive licenses for its commercial use will be granted by NASA. Inquiries concerning license rights should be made to NASA, Code GP, Washington, D.C. 20546.

Source: R. Hymer Manned Spacecraft Center (MSC-12223)

Category 01