

1-1-1975

Automatic Classification of Aircraft and Satellite Images Using Mixed Integer Programming

M. Rebollo

L. F. Escudero

Follow this and additional works at: http://docs.lib.purdue.edu/lars_symp

Rebollo, M. and Escudero, L. F., "Automatic Classification of Aircraft and Satellite Images Using Mixed Integer Programming" (1975).
LARS Symposia. Paper 59.
http://docs.lib.purdue.edu/lars_symp/59

This document has been made available through Purdue e-Pubs, a service of the Purdue University Libraries. Please contact epubs@purdue.edu for additional information.

Reprinted from

Symposium on

Machine Processing of

Remotely Sensed Data

June 3 - 5, 1975

The Laboratory for Applications of
Remote Sensing

Purdue University
West Lafayette
Indiana

IEEE Catalog No.
75CH1009-0 -C

Copyright © 1975 IEEE
The Institute of Electrical and Electronics Engineers, Inc.

Copyright © 2004 IEEE. This material is provided with permission of the IEEE. Such permission of the IEEE does not in any way imply IEEE endorsement of any of the products or services of the Purdue Research Foundation/University. Internal or personal use of this material is permitted. However, permission to reprint/republish this material for advertising or promotional purposes or for creating new collective works for resale or redistribution must be obtained from the IEEE by writing to pubs-permissions@ieee.org.

By choosing to view this document, you agree to all provisions of the copyright laws protecting it.

AN INCISIVE NEIGHBORHOOD DISCERNING
ITERATIVELY AGGREGATING NOMENCLATOR
(INDIAN) SYSTEM FOR PATTERN RECOGNITION
IN UNSUPERVISED ENVIRONMENTS

Belur V. Dasarathy
Computer Sciences Corporation
Huntsville, Alabama 35802

ABSTRACT

A novel system for pattern recognition in unsupervised environments, which combines the conceptual elegance of clustering schemes based on inter-sample distance measures with the computational simplicity of histogram approaches, is presented in this study. The multi-dimensional histogram of the entire data set is first derived and by scanning this histogram space, the significant hills therein are identified. The centroids of these hills are deemed to be representative of the given input sample set. This representative pseudo-sample set is then input to the CURRY system (International Journal of System Science, Vol. 6, No. 1, January 1975, pp 23-32), which has the innovative capability of self learning the number of clusters inherent in the environment, to derive the nuclei of these inherent clusters. The total input data set is then clustered with these cluster nuclei as prototypes. The two major advantages of this new approach are:

- The conceptual satisfaction of lessening the sensitivity, of the clustering approaches based on inter-sample distance measures, to individual outliers of the sample distributions through selection of a representative pseudo-sample set.
- The computational economy achieved in processing large data sets, such as those arising in remote sensing environments, through the choice of a significantly smaller but representative subset of pseudo-samples.

AUTOMATIC CLASSIFICATION OF AIRCRAFT
AND SATELLITE IMAGES USING
MIXED INTEGER PROGRAMMING

M. Rebollo and L. F. Escudero

IBM Center
IBM Espana
International Business Machines, S. A. E.
Madrid, Spain