

Competition between recombination and extraction of free charges determines the fill-factor of organic solar cells

Davide Bartesaghi,^{1,2} Irene del Carmen Pérez,¹ Juliane Kniepert,³ Steffen Roland,³ Mathieu Turbiez,⁴ Dieter Neher,³ L. Jan Anton Koster¹

1) Zernike Institute for Advanced Materials
University of Groningen
Nijenborgh 4
9747 AG Groningen

2) Dutch Polymer Institute, P. O. Box 902, 5600AX Eindhoven, The Netherlands

3) Institute of Physics and Astronomy
University of Potsdam
Karl-Liebknecht-Str. 24–25, 14476, Potsdam, Germany

4) BASF Schweiz AG, Schwarzwaldallee 215, CH-4002 Basel, Switzerland

ABSTRACT

Of the parameters that characterize a solar cell, the fill-factor (FF) is the least well understood, making targeted improvement difficult. Here, we show that the FF of bulk heterojunction solar cells is determined by the competition between charge extraction and recombination. Moreover, we empirically demonstrate the precise relationship between this competition and the FF for a wide variety of donor/acceptor combinations. Our finding is supported by experimental measurements on 15 different donor:acceptor combinations as well as by drift-diffusion simulations of organic solar cells in which charge carrier mobilities, recombination rate, light intensity, energy levels, and active layer thickness were all varied over wide ranges to reproduce typical experimental conditions. The results apply to polymer/fullerene and polymer/polymer combinations of different thicknesses, composition, temperatures, and light intensities. For the whole range of 0.26-0.74, all FF s follow from the competition between extraction and recombination.

We measure charge carrier mobilities and bimolecular recombination rates using a combination of steady-state and transient extraction techniques. These quantities are used to estimate the extraction and recombination times. The ratio between the extraction and recombination times, which we call θ , indicates whether the majority of charge carriers recombine or can be extracted from the solar cell. If all the FF s of the solar cells studied are plotted versus θ , the data collapse onto one universal curve. This shows that the main determinant of the FF is the balance between bimolecular recombination and charge extraction.

To explain the observed trend of FF versus θ , we perform drift-diffusion simulations of organic solar cells. Charge carrier mobilities, recombination rate, light intensity, energy levels, and active layer thickness were all varied over wide ranges to reproduce the experimental conditions. Again, when the resulting FF are plotted versus θ a universal curve is obtained that is in quantitative agreement with the experimental data.

The results presented here provide new insights into the physical phenomena governing the fill-factor of organic solar cells and help explain why the FF s change significantly with materials properties, light intensity and thickness. The relationship between FF and theta shown by this work offers an approach for targeted improvements of FF . In particular, this relationship can be used to rationalise the effect on FF of simultaneously changing multiple parameters. Additionally, we indicate in which way recombination and transport properties of a blend should be modified for a device with given thickness, generation rate and internal voltage in order to optimize its FF .