

Received December 1, 2019, accepted December 25, 2019, date of publication December 30, 2019, date of current version January 16, 2020.

Digital Object Identifier 10.1109/ACCESS.2019.2963092

# **Deep Learning-Based Intelligent Fault Diagnosis Methods Toward Rotating Machinery**

### SHENGNAN TANG<sup>1</sup>, SHOUQI YUAN<sup>1</sup>, AND YONG ZHU<sup>1,2</sup>

<sup>1</sup>National Research Center of Pumps, Jiangsu University, Zhenjiang 212013, China

Corresponding authors: Shouqi Yuan (shouqiy@ujs.edu.cn) and Yong Zhu (zhuyong@ujs.edu.cn)

This work was supported in part by the National Natural Science Foundation of China under Grant 51779107 and Grant 51805214, in part by the China Postdoctoral Science Foundation under Grant 2019M651722, in part by the Open Foundation of the State Key Laboratory of Fluid Power and Mechatronic Systems under Grant GZKF-201905, in part by the Natural Science Foundation of Jiangsu Province under Grant BK20170548, in part by the Youth Talent Development Program of Jiangsu University, and in part by the National Key Research and Development Program of China under Grant 2019YFB2005200.

**ABSTRACT** Fault diagnosis of rotating machinery plays a significant role in the industrial production and engineering field. Owing to the drawbacks of traditional fault diagnosis methods, such as heavily dependence on human knowledge and professional experience, intelligent fault diagnosis based on deep learning (DL) has aroused the interest of researchers. DL achieves the desirable automatic feature learning and fault classification. Therefore, in this review, DL and DL-based intelligent fault diagnosis techniques are overviewed. DL-based fault diagnosis approaches for rotating machinery are summarized and discussed, primarily including bearing, gear/gearbox and pumps. Finally, with respect to modern intelligent fault diagnosis, the existing challenges and possible future research orientations are prospected and analyzed.

**INDEX TERMS** Deep learning, deep neural network, intelligent fault diagnosis, rotating machinery.

### I. INTRODUCTION

As an essential part and one of the most representative of mechanical equipment, the rotating machinery relies on rotation for purpose of a specific function. It has been widely used in the field of mechanical transmission, including aircraft engines, pump, wind turbine generator systems, gas turbine engine, and power plants [1], [2]. Owing to unavoidable malfunction and downtime of the mechanical equipment in the process of operation, fault diagnosis is of great significance for rotating machinery in order to ensure the reliability and safety [3]–[6].

In general, fault diagnosis methods are divided into the followings, model-based methods, signal-based methods, knowledge-based methods and composite methods [7]. In view of traditional fault diagnosis methods, they are primarily based on mechanism, feature frequency or fault feature extraction [8]. On account of dependence on the practical experience and professional knowledge, it is difficult to detect the fault of rotating machinery with complex structure by the use of traditional subjective fault diagnosis methods [9], [10]. Some improvement and achievement have been made on fault diagnosis with respect to the model-based methods and

The associate editor coordinating the review of this manuscript and approving it for publication was Zhen Qin.

signal-based methods. A kalman filter was improved and used to evaluate the state of hydraulic actuator and leakage of hydraulic system by An and Sepehri [11], [12]. Du and Goharrizi et al. analyzed and estimated vibration signal of hydraulic pump, pressure signal of hydraulic cylinder and actuator via wavelet transform [13], [14]. The doubly iterative empirical mode decomposition (EMD) and adaptive multifractal detrended fluctuation analysis were employed to analyze fault diagnosis of the bearing, the gear and the piston pump [15]. Although the shortages of artificial data statistics have been compensated by the methods discussed above to some extent, there are still some limitations in fault diagnosis of rotating machinery owing to the difficulty in feature extraction and complicate mathematical model.

With the implement of "Industry 4.0" and "Internet +", artificial intelligence (AI) has been quickly integrated into the various traditional industries [16]. Intelligent fault diagnosis, which is combined with other feature extraction methods, AI as the main body, has attracted more and more attention. It is considered to be a powerful tool for big data processing and fault diagnosis of mechanical equipment, which provides a new exploration path for fault diagnosis and health management of rotating machinery [17], [18].

Great success has been achieved in fault diagnosis of rotating machinery with traditional machine learning methods,

<sup>&</sup>lt;sup>2</sup>State Key Laboratory of Fluid Power and Mechatronic Systems, Zhejiang University, Hangzhou 310027, China



such as support vector machine (SVM) and artificial neural network (ANN) [19]-[22]. Wavelet packet decomposition and EMD were combined and used to feature extraction, moreover, ANN was utilized to preliminary fault diagnosis by Bin et al. [23]. In order to achieve fault diagnosis of hydraulic pipe, an integrated method including principal component analysis (PCA), ANN and multiple adaptive neural fuzzy inference system was proposed by Saeed et al. [24]. On account of on-line intelligent diagnosis based on neural network, Schlechtingen et al. used it to fault diagnosis of wind turbine generator [25]. In order to realize fault identification of bearing, many various efforts have been made on the exploration of novel methods. Amar et al. proposed a neural network based on vibrational spectra [26], Jiang et al. combined improved singular value decomposition (SVD) and hidden markov model [27], and Zeng et al. used a maximum interval classification method based on flexible convex hull [28]. A novel diagnosis method for bearing was proposed by Li et al., thereinto, the geometry of input data was taken into account [29]. In addition, intelligent diagnosis method was proposed based on firefly neural network by Li et al. [30]. However, there are still some limitations and deficiencies in traditional intelligent diagnosis methods. On the one hand, in consideration of feature extraction, a large number of signal processing technologies requires to be grasped and rich experience in engineering practice needs to be possessed; additionally, feature extraction and intelligent diagnosis are treated separately, the relationship between them could not be taken into account. On the other hand, with regard to model training, the shallow model is used to characterize the complex mapping relationship between signals and health status, which leads to the obvious deficiency in diagnostic ability and generalization performance of the model in the face of mechanical big data [31], [32].

Modern intelligent fault diagnosis technology is based on the new theory and method of AI. In 2006, Hinton et al. first proposed the deep learning (DL) theory in Science [33], which triggered a wave of research on many different fields. DL was ranked as the top 10 breakthrough technologies of 2013 by MIT Technology Review. In 2015, Hinton et al. indicated that DL was thought to be one of machine leaning, and breakthrough was analyzed and discussed in the respects of image, video, audio and text processing [34]. It has been adequately demonstrated that DL presents the broad prospects on research and application. Through multilayer nonlinear network training, potential features of samples have been learned and classification or prediction ability have been improved with DL. DL methods that are widely studied usually include deep belief network (DBN) [35], stacked self-encoders (SAE) [36], convolutional neural network (CNN) [37] and recurrent neural network (RNN) [38]. Based on multivariate encoder information, a CNN was designed to intelligently identify the failure of planetary gear box by Lin et al. Not only did the deficiency of traditional vibration analysis overcome, but also a potential intelligent tool was provided to obtain the expected diagnosis towards rotating machinery [39]. In accordance with multi-domain features, an integrated kernel extreme learning machine was proposed and used to gear box, rotor and motor bearing, effective diagnosis was achieved by visualization with the method [40].

Presently, on account of the wide use of DL in many pattern recognition fields, intelligent fault diagnosis based on DL has attracted much more attention of professional researchers in machinery field. Therefore, this review will focus the efforts on fault diagnosis of rotating machinery. It will place an emphasis on fault diagnosis integrated with deep neural network technology. Furthermore, a summary of the applications will be given towards commonly used rotating machinery such as bearing, gear and pump. Finally, the above discussions are concluded and the possible research directions are provided to inspire more researches in this field

#### II. DL BASED FAULT DIAGNOSIS

### A. ARTIFICIAL INTELLIGENCE

As a new and interdisciplinary science, AI is aiming at simulating some of human thinking processes and intelligent behavior by the use of computer. It can be achieved in computer by the following two different ways, one is engineering approach which adopts traditional programming technique; the other is modeling approach, such as generic algorithm and ANN.

From SIRI to AlphaGo, rapid development of AI has been supposed to be interesting, surprising and outstanding [41], [42]. AI approaches have been integrated into many various fields, great achievements have been obtained in man-machine game, pattern recognition, automatic engineering and knowledge engineering [43]–[45]. Because of the increase of machinery data and complication of fault which result in high uncertainty during diagnosis process, AI based methods will outperform traditional methods on diagnosis efficiency. AI-based approaches can be divided into the following two categories, knowledge-driven methods and data-driven approaches [46].

### B. DL

As a distinguished development of AI, DL can be understood as feature learning or representation-learning, which possesses multiple and high levels representations of data, concretely, through DL, low-level features from simple and nonlinear modules were composed to form more abstract high-level representations in terms of categories or features, complex functions and distributed feature representations of data can be obtained [47]. Very deep neural networks can be considered to be typical DL model. DNN plays an essential role in deep models, mainly including DBN, SAE, CNN, RNN and GAN. As one of unsupervised learning ways, DBN is a DNN which possesses the stacked structure and consists of multiple Restricted Boltzmann Machines. Similarly, SAE is used to deal with high-dimensional data by means of



unsupervised learning. It is composed of multiple autoencoders, which presents a three-layer neural network including both encoding and decoding processes. CNN is a supervised learning network, whose structure seems to be more complex with convolution layers, sample layers and full connected layers. With especial ring structure, RNN represents a unique advantage in settling learning problems with sequential data via unsupervised learning. It is interesting that GAN is comprised by generally both non-linear function models, that is, a generative model and a discriminative model respectively [48]. In order to overcome the deficiency of insufficient training data, deep transfer learning (TL) has achieved that the learning from the source domain is employed to the target domain [49]. Compared with traditional machine learning, it should be noted that the key advantage of DL is layers of features are automatically learned from raw data through a general-purpose learning procedure, not dependent on engineering skills and domain expertise [34].

In view of the advantages of DL, it has been applied to many different fields such as language processing, automatic speech recognition, and audio recognition [50], [51]. Meanwhile, this has aroused the interest of researchers in the field of mechanical engineering, making it play an essential role in intelligent fault diagnosis combined with other methods and technologies [52], [53].

### C. OVERVIEW OF DL BASED FAULT DIAGNOSIS

Intelligent fault diagnosis is the combination of AI and fault diagnosis, which expresses comprehensive use of domain expertise and AI technology and strong capability of processing considerable mechanical data [54], [55].

Three different steps are included in traditional intelligent fault diagnosis, namely, signal collection, feature extraction and fault classification. Since some exhausted and handcrafted signal feature extraction technologies could be required in those methods, diagnosis results will finally be affected. Moreover, the ability to learn the complex nonlinear relationships between features and patterns will be hindered with the shallow structures such as SVM [56]. With respect to new intelligent fault diagnosis, in place of feature extraction and selection, the features can be automatically learned from raw signals, which presents more intelligent than conventional approaches [57], [58].

Some good results have been achieved in applications to gear, gearbox, bearing, rolling, pump, wind turbine and nuclear power plant with modern intelligent fault diagnosis [59]–[62]. Xu and his colleagues proposed a new intelligent diagnosis method based on elaborately designed deep neural network for failure detection of wind turbine, which solved the problem of unbalanced distribution with regard to SCADA data [63]. Combined a CNN with a Naïve Bayes data fusion proposal, Chen et al. applied DL theory to nuclear power plant inspection [62]. Zhang et al. constructed a new unsupervised learning method called general normalized sparse filtering, which was used for fault diagnosis of rolling bearing and planetary gearbox [64].

### III. APPLICATIONS OF DL TOWARD FAULT DIAGNOSIS IN ROTATING MACHINERY

Combined with the above analysis, it can be proved that it has acquired some improvements and achievements for machinery fault diagnosis illuminated from the applications of DL technique in other fields. As shown in Table 1, the applications of DL-based methods in machinery fault diagnosis have been summarized. In order to evaluate the diagnosis performance of methods, the following evaluation indicators are employed, including the diagnosis accuracy, the training accuracy, the average testing accuracy, the prediction accuracy, the clustering effect from visualization.

This review will play an emphasis on intelligent fault diagnosis of typical rotating machinery, including bearing, gear and pump. Furthermore, DL-based approaches for improving diagnosis accuracy will be analyzed and discussed in the following.

### A. INTELLIGENT FAULT DIAGNOSIS OF BEARING

As one of well-known and widely-used rotary machinery, bearing is of great significance but its brokendown occupies nearly 45-55% of equipment fault, which will lead to accidents, downtime, even severe damage and economic loss [93], [94]. Therefore, it is of vital importance to investigate intelligent fault diagnosis methods of bearing, especially the DL technique.

In order to overcome the imbalanced distribution of machinery health conditions, a new learning method called deep normalized CNN (DNCNN) was investigated to classify the faults of bearing by Jia *et al.* [95]. Three bearing datasets are employed to validate the diagnosis accuracy of the proposed methods, in which single faults and compound faults with various imbalanced degrees are taken into account. In Figure 1(a-c), it can be seen that DNCNN presents the superiority than S-CNN and R-CNN in terms of learning features from the vibration signals, in which the features cluster well. By the use of the confusion matrices, the imbalanced classification results were successfully obtained, that is, 95.4% of the samples were correctly classified by the proposed method, and only 4% of the samples were misclassified.

As one method of machine learning, TL makes it possible that one pretrained model is employed again to another task with the purpose of reducing the distribution discrepancy and enhancing the predictive performance [96].

Generally, both developing model and pretraining model are included, moreover, the latter is widely used in machine learning. Through the integration of auto-balanced high-order Kullback-Leibler divergence, smooth conditional distribution alignment and weighted joint distribution alignment, a novel TL framework was designed for fault diagnosis of rotator bearing and gearbox under varied conditions [97]. Inspired by the idea of TL, a deep CNN was proposed to be used for fault diagnosis of unlabeled data by Lei et al., which made it possible that labeled data from one machine after being



TABLE 1. Summary of DL-based methods for machinery fault diagnosis.

Technique	Applications	Diagnosis Effect	(Ref.)
CNN with first-layer kernel dropout	Bearing fault diagnosis	99.77% accuracy	[65]
CNN and second	U	•	
generation wavelet	Motor bearing	99.63%	[66]
transform	fault diagnosis	accuracy	[]
CNN and wavelet	Spindle bearing	99.8%	F 4 = 3
packet energy	fault diagnosis	accuracy	[67]
CNN with hierarchical	Bearing fault	desirable	
structure	diagnosis	performance	[37]
Structure	Bearing fault		
CNN	diagnosis	99.75%	[68]
	Bearing fault	100%	
CNN	diagnosis		[69]
	diagnosis	accuracy 100.00%	
	Rotor and		
CNN	bearing fault	accuracy for	[70]
	diagnosis	rotor; 93.33%	
	<u> </u>	for bearing	
CNN	Bearing fault	99.89%	[71]
	diagnosis	accuracy	[]
DBN and sparse	Bearing fault	97.82%	
autoencoder	diagnosis	average	[72]
	_	accuracy	
RNN-based	Bearing fault	99.85%	[72]
autoencoders	diagnosis	accuracy	[73]
Autoencoder and	Dagwing for to		
particle swarm	Bearing fault	94.34%	[74]
optimization-SVM	diagnosis		L
SAE and softmax	Bearing fault		
regression	diagnosis	95.26%	[75]
Deep convolutional	Bearing fault		
auto-encoding NN	diagnosis	99.7%	[76]
Kernel auto-encoder	diagnosis	95.95%	
	Bearing fault		[77]
based on firefly	diagnosis	average	[77]
optimization	0.10	accuracy	
D	Self-priming	98.845 and	
Deep convolution	centrifugal	97.62%	[70]
variational autoencoder	pump and	average	[78]
network	bearing fault	accuracy	
	diagnosis	respectively	
	Bearing fault	93.17%	
DBN	diagnosis	average	[79]
	Ü	accuracy	
DBN and singular	Bearing fault	100%	[80]
value decomposition	diagnosis		[00]
DBN and Hilbert	Bearing fault	99.55%	[81]
envelope spectrum	diagnosis	accuracy	[01]
	Bearings fault	99.93%	
DBN	pattern		[82]
	recognition	accuracy	
DBN based on multi-	Gearbox fault	98.1 %	[927
layer neural networks	diagnosis	<b>90.1</b> 70	[83]
CNN	Gearbox fault	96.8% mean	[0.47
CININ	diagnosis	accuracy	[84]
SAE, dropout	Cond. C. 1		
technique and ReLU	Gearbox fault	99.34%	[85]
activation function	diagnosis		
GAN and stacked	Gearbox fault	98.4%	50.63
denoising autoencoders	diagnosis	accuracy	[86]
	Gearbox and		1
TL	bearing fault	100%	[87]
IL	diagnosis	10070	[ [0,]
Multimodal deep	Gearbox fault		
	diagnosis	97.08%	[88]
support vector			<u> </u>
Support tensor machine	Gear fault	99.50%	[89]
- *	diagnosis		- 1
	Bearings and	1000/	F0 **
DATA			
DNN	gears fault diagnosis	100%	[36]

**TABLE 1.** (Continued.) Summary of DL-based methods for machinery fault diagnosis.

CNN	Bearing, self- priming centrifugal pump, and axial piston hydraulic pump fault diagnosis	99.79%, 99.481%, 100% prediction accuracy	[90]
SAE	Spacecraft fault diagnosis	98.35%	[91]
Refrigerant charge fault detection-based CNN	Heat pump system	99.9%	[92]




FIGURE 1. The visualization of learned features for Dataset A: (a) S-CNN, (b) R-CNN, (c) DNCNN. S-CNN represents the convolutional neural networks (CNN) using sigmoid function, R-CNN represents the CNN using ReLU, DNCNN represents deep normalized convolutional neural network, respectively [95].

trained could effectively classify the unlabeled data from other machines [98]. Furthermore, as one of CNN, a transfer neural network based on feature was explored for state identification of bearings. In comparison to the other methods such as CNN and multi-layer adaptation CNN, the average classification accuracy of the proposed method was the highest one which achieved 84.32%. It has been demonstrated that more desirable transfer results and transfer performance were obtained with FTNN. Seen from Figure 2(f), in consideration of the learned transferable features, the distribution was adapted efficaciously, furthermore, the among-class distance was expanded [99]. In order to overcome the limitations in training and the performance degradation, a new deeper 1D CNN based on the residual learning was developed for fault diagnosis of wheelset bearings, and the effectiveness was approved by visualization Figure 3 [71].






FIGURE 2. The visualization of the learned features on the dataset B (source domain) and the dataset D (target domain): (a) CNN, (b) TCA, (c) DAFD, (d) DDC, (e) MACNN, and (f) FTNN. CNN represents convolutional neural networks, TCA represents transfer component analysis, DAFD represents, DDC represents, MACNN represents multi-layer adaptation CNN, and FTNN represents feature-based transfer neural network [99].




FIGURE 3. Visualization of these five methods in noise environment (SNR = -16 dB). ADCNN represents adaptive deep CNN, Wen-CNN represents CNN proposed by Wen et al, MSCNN represents multiscale CNN, WDCNN represents deep convolutional neural networks with wide first-layer kernels, Der-1DCNN represents deeper 1D CNN [71].

A new deep TL with three-layer sparse encoder was investigated by Wen et al, which was validated by the use of motor bearing dataset. Compared with other traditional methods, such as DBN, ANN, sparse filter, and SVM, this proposed method presents good performance and the prediction accuracy achieved 99.82% [100].

He et al. presented a composite deep signal processing approach, which integrated vibration analysis and deep learning [101]. Vibration analysis was embedded into the discrete Fourier transform - inverse discrete Fourier transform autoencoder, which achieved that time-frequency characteristics were learned adaptively and effective convergence was obtained in view of learning procedure. Real bearing data was employed to validate the performance of the proposed method, which presented obviously higher diagnosis accuracy compared with those of popular deep neural

network (DNN), CNN and SVM. Specifically, the testing accuracy reached 100.00% while below 95.50% in other methods when shaft speeds were set as 45 and 60.

Motivated by the thought of enhancing the generalization ability and robustness of diagnosis model through utilizing the structural domain information among multiple bearing fault types, a new deep output kernel learning was presented in order to overcome the randomness of some deep learning methods [102]. In comparison to one the-state-of-the-art signal analysis method, four shallow models and four deep models, it showed higher accuracy of 100.00% and shorter training time of less than 7 s.

Combined compressed sensing with a convolutional DBN, a new improved deep model with powerful feature learning ability was constructed to analyze the single fault and compound faults of rolling bearing by Shao *et al.* [103]. It should be pointed that the analysis efficiency was enhanced by compressed sensing and the generalization performance was enhanced via exponential moving average technique. The average testing accuracy of the proposed method achieved 94.80%, which was be superior to other traditional methods of no more than 90.00%, including the standard DBN, CNN, deep auto-encoder (DAE), BP neural network and SVM. From the visualization of PCA (Figure 4), it can be proved that the better clustering result was obtained from the proposed method, which expressed the superiority in capturing potential features.




FIGURE 4. Three dimensional visualization of different features using PCA. (a) Compressed data features, (b) extracted 22 features, and (c) deep features [103].

In regard to the diversity of the fault data distribution and the data reconstruction ability, a sparse stacked denoising autoencoder is developed for the fault diagnosis of rolling bearings [104]. With the introduction of optimized transfer learning algorithm, the problem of the domain adaption was solved, and the accuracy of the target domain achieved 96.70% in one of motor loads. It was demonstrated that the quality of the target domain was influenced by the performance of the source domain algorithm, however, it is limited to only depend on the enhancement of the source domain.

In consideration of unlabled data in practical engineering, combined with Gath-Geva clustering algorithm, a stacked denoising autoencoder was investigated for roller bearing fault diagnosis without principal component analysis and data mark [105]. The proposed method presented the superior clustering effect. Moreover, its classification accuracy was higher compared to those of the other combination models, and the highest one reaches up to 100.00%.






FIGURE 5. The structure of the proposed CNN-ELM model for fault diagnosis [107].

## B. INTELLIGENT FAULT DIAGNOSIS OF GEAR AND GEARBOX

It was indicated that the gearbox failure was the primary contributor to equipment fault, which took up nearly 40% in mechanical transmission field according to the investigation performed under the assistance of the Institute of Electrical and Electronic Engineers (IEEE) [106]. Hence, in view of the fault diagnosis for gear and gearbox, the methods based on DL will be highlighted in the following.

Combined CNN and extreme learning machine, a new model without any extra training and fine tuning was established by Chen et al., gearbox dataset and motor bearing dataset were selected to verify the effectiveness of the proposed method, as depicted in Figure 5 [107]. It was demonstrated that the feature learning capability was improved by the CNN employed as an automatic feature extractor, and the classification performance and the learning speed were promoted through the extreme learning machine. In view of gearbox, the results indicated that the training accuracy and average test accuracy reached  $100.00\% \pm 0.00$  and  $99.83\% \pm$ 0.24 respectively, which achieved the superiority in contrast to the other methods such as standard CNN. With regard to motor bearing, the training accuracy and average test accuracy gained  $100.00\% \pm 0.00$  and  $99.92\% \pm 1.24$  respectively, which exhibits the better classification performance.

With respect to signal processing-based methods, a wavelet packet transform, a distance evaluation technique and a support vector regression (SVR)-based generic multi-class solver were combined for fault diagnosis of bearing and gearbox [1]. The proposed method presented the superior representative capability and the higher diagnosis accuracy, which was mainly attributed to the influences of wavelet basis functions on the proposed whole framework.

Motivated by the idea of TL, a new intelligent fault diagnosis scheme named deep transfer network with joint distribution adaptation was exploited to overcome the applicability limitations for the traditional diagnosis methods [108]. Three datasets including wind turbine, bearing and gearbox fault dataset, were employed to verify the performance of the proposed framework, which displayed some good results in accordance to various working conditions, the types and severities of fault. In order to demonstrate the performance of the proposed method, the average diagnosis accuracy, missing alarm rate, and false alarm rate were chosen as evaluation indicators, meanwhile, eight state-of-the-art intelligent

diagnosis approaches were used as comparisons. With regard to gearbox, the average diagnosis accuracy of the proposed scheme outbalanced those of other methods, which reached up to more than 96%. Similarly, a working condition-robust fault diagnosis method based on an improved joint distribution adaptation was exploited to achieve the acquisition of more useful samples and reduction of the input dimension [109]. The vibration signal datasets of roller bearings and a gearbox were used to validate the fault diagnosis performance of the proposed method, which obviously demonstrated its effectiveness although its computational time was completely unsatisfactory.

In consideration of unexpected diagnostic results via utilizing the spectrum signal, modern spectrum signals through preprocessing current signals was incorporated into DNN by Li *et al.* [110]. Compared with SVM and BPNN, the proposed method represented superior diagnostic results for faults detection in planetary gears, the testing accuracy rate of which achieved 96.69% with standard deviation of 1.05%. Furthermore, the diagnosis advantage of the proposed method was proved by the visualization of fault characteristics from PCA, as shown in Figure 6(d), which presented better clustering effect and little overlapping than those of others.




FIGURE 6. Scatterplot of the main characteristic components: (a) signals in the time domain, (b) direct spectrum signals, (c) spectrum signals without the power frequency, and (d) modified spectrum signals.

Reprinted with permission from ref. [110].

A new DL method was developed for fault diagnosis of planetary gear through combining power spectral entropy of variational mode decomposition and DNN, which was trained through unsupervised training and supervised fine tuning [111]. It is beneficial to fault classification via the reduction of raw signals by the use of BP. Compared with other methods such as SVM and BP, the proposed method exhibited the higher overall recognition rate of 100%.

Based on time-frequency analysis and DNN, a deep residual learning was constructed for fault diagnosis in



planetary gearbox [112]. Its performance was demonstrated under nonstationary running conditions, which implied admirable results for the incipient fault detection, especially when rotating speed was variable. The proposed scheme presented the higher diagnosis accuracy, which reached up to 95.4% under faulty condition.

A deep CNN was constructed for gearbox fault diagnosis under different operating conditions, which was compared with different SVM classifiers optimized by the use of a grid search technique [113]. With regard to vibration signals of different directions, the proposed method showed the superiority to other traditional methods. The identification accuracy achieved 93.6% and the computational cost was reduced.

By the use of the maximum correntropy and artificial fish swarm algorithm, a new deep autoencoder feature learning method was designed and optimized by Shao et al. for the fault diagnosis of gearbox and electrical locomotive roller bearing [114]. Compared with other approaches such as standard deep autoencoder, BP and SVM, the proposed method possessed the admirable diagnosis effectiveness including robustness, and the average testing accuracy reached 94.05% with a smaller standard deviation of 1.34.

In order to overcome the dependence on numerable labelled data and time consuming of handcrafted feature extraction in traditional supervised diagnosis, a new deep semi-supervised method of multiple association layers networks was investigated by Zhang et al. [115]. As shown in Figure 7, the wavelet packet transform was employed to preprocess raw signals, moreover, the labeled and unlabeled data was together used to train the model and method. It can be concluded that the recognition accuracy of the proposed method presented the advantage in comparison to SAE and DBN with less labeled data. The recognition rate increased from 78.58% to 93.26% with the increase of the labeled samples from 2% to 100%. Additionally, it is worth to note that the optimization of the hyper-parameter may be a key challenge and have a great influence on the performance of the neural networks.




FIGURE 7. The framework of the proposed method for fault diagnosis of planetary gearbox [115].

### C. INTELLIGENT FAULT DIAGNOSIS OF PUMPS

With the function diversity and structural complexity of hydraulic system, it seems to be more challenging for fault identification and classification [116]–[118]. As power source of hydraulic system, hydraulic pump plays an indispensable role in reflecting the working state of the system [119], [120]. Meanwhile, with respect to the wide use of centrifugal pump, whose operating state directly affects production and safety. According to the statistics on the mechanical and electrical equipment defects, more than 50% are connected with pump failures [121], [122]. Therefore, it is of great significance to diagnose pump faults accurately and effectively in order to ensure the safety and reliability of the system. Although some researches have achieved admirable results on machinery intelligent fault diagnosis, there are still little investigations on pumps.

As an essential and famous DL, DNN has aroused great attention in intelligent fault diagnosis, which has also stimulated interest in research for pumps. A new data-driven method based on CNN with LeNet-5 was developed by Wen et al. [90]. In regard to axial piston hydraulic pump, two fault conditions were taken into account, and the piston shoes and swashplate wearing and valve plate wearing were included. The prediction accuracy achieved 100%. As for self-priming centrifugal pump, four faults conditions were analyzed, including bearing roller wearing, inner race wearing, outer race wearing, and impeller wearing fault condition. From the results of confusion matrix, it can be observed that the prediction accuracy of 99.481% was obtained, moreover, the most misclassification was 0.4%. Similarly, a simple improved CNN was proposed for fault diagnosis of hydraulic pump by Yang et al. [123]. Two operating conditions including stable and variable pump speeds were investigated, the accuracy rate exceeded 95% and 90% in view of the worst

Based on image-processing technique, a probabilistic neural network was introduced by Lu et al, and it was achieved that the feature was automatically extracted in a two-dimensional space [124]. The speeded-up robust features and t-Distributed Stochastic Neighbor Embedding (SNE) were employed to automatic feature extraction and dimensionality reduction respectively. By the use of t-SNE, the feature information was more clustered and presented the potent capability of separability (Figure 8(A)). It can be concluded from the cross-validation results that the proposed method presented the high diagnosis accuracy. The classification accuracy was more than 96% for the self-priming centrifugal pump. For the axial piston hydraulic pump, the average classification accuracy achieved as high as 98.71%.

Through introducing data indicator containing time and frequency, Wang et al. investigated a DBN for multiple faults diagnosis of the axial piston hydraulic pump, which achieved the advantageous classification accuracy of 97.40% in comparison to SVM and ANN [125]. It deserved to be mentioned that the restricted Boltzmann machine was used to realize the automatic learning of fault features.




FIGURE 8. The first three features extracted using t-SNE (A) and without using t-SNE (B) [124].

In consideration of the complex dynamic behavior for rotary machinery, symbolic analysis plays an essential role [126]. In combination with hierarchical symbolic analysis (HSA), a CNN was used for fault diagnosis of centrifugal pump [127]. The diagnosis accuracy improved as the number of hierarchical layers increased, moreover, the computation time admirably reduced after using HSA. It achieved the maximum of 98.50% when hierarchical layer was 3. By means of data fusion which achieved the transformation of multisensor-signals to images, another improved CNN was proposed by Wang et al., and the prediction accuracy reached up to 99.47%. It presented the obvious better diagnosis effectiveness in comparison with other intelligent methods [128].

Owing to the long operating time and computing complication, a novel intelligent fault diagnosis scheme was developed combined deep structure with SVM, which realized the learning of the hidden features [129]–[131]. The similar conclusions were obtained that the accuracy rate increased with the number of network layers. In contrast to other methods, the proposed method exhibited the superior diagnosis performance. In consideration of the accuracy rate and computing time, the optimum result achieved up to 97.75% with standard deviation of 0.20.

### IV. CONCLUSIONS AND PERSPECTIVES

Relevant studies on fault recognition methods have been performed by our research group [132], [133]. Additionally, PCA and XGBoost were integrated to diagnose hydraulic valves. It is worth noting that we have conducted many investigations on fault diagnosis and signal processing for hydraulic pumps and centrifugal pumps, which mainly concentrate on conventional intelligent methods [134]–[137]. Furthermore, we gradually begin to study intelligent fault diagnosis methods such as SVM for hydraulic pumps [138], which provides a theoretical foundation for the following researches on DL-based fault diagnosis approaches. In the present and future, we will put emphasis on the DNN-based methods and explore multi-information fusion technique with well generalization capability, moreover, remote diagnosis system will be exploited and constructed.

In accordance with the analysis and discussions above, the methods based on DL can not only adaptively extract the hidden complex and changeable fault information, but also overcoming the reliance on diagnostic knowledge and engineering experience of traditional methods. Although these methods have achieved some expected results in rotary machinery, there are still some challenges in the current researches and the corresponding future research directions are as follows:

- (a) A large number of studies only used experiments or existing datasets to validate the effectiveness of the proposed methods, and the underlying mechanism of improved diagnostic accuracy has not been analyzed in details.
- (b) Many researches primarily focus on the single physical source information, diagnosis accuracy requires to be improved owing to small data size. It is significant to pay more attention to multi-source information, which can comprehensively reflect the state of equipment. But multi-source signal has diversity and complexity problems, which need to be further studied.
- (c) The commonly used single marker system has interpreted fault information out of context, and the introduction of multi-marker system could be promising to explore the identification of multiple faults.
- (d) On account of many present methods, only the diagnosis accuracy is improved. However, in the face of the fault with more coupled and concurrency characteristics, it is urgent for further exploring the identification of complex faults and the generalization performance of the method.

Based on the thinking of DL, intelligent fault diagnosis strategies are overviewed in this review. The applications of DL-based techniques in fault diagnosis of rotating machinery are thoroughly analyzed and discussed, mainly bearing, gears and pumps. The diagnosis performance of these emerged methods is highlighted, which provides ideas and guidance for the exploration and applications of novel intelligent fault diagnosis in rotary machinery extending to other machineries.

### **REFERENCES**

- C. Shen, D. Wang, F. Kong, and P. W. Tse, "Fault diagnosis of rotating machinery based on the statistical parameters of wavelet packet paving and a generic support vector regressive classifier," *Measurement*, vol. 46, no. 4, pp. 1551–1564, May 2013.
- [2] B. Ebrahimi, J. Faiz, and M. Roshtkhari, "Static-, dynamic-, and mixed-eccentricity fault diagnoses in permanent-magnet synchronous motors," *IEEE Trans. Ind. Electron.*, vol. 56, no. 11, pp. 4727–4739, Nov. 2009.
- [3] Y. Lei, J. Lin, Z. He, and M. J. Zuo, "A review on empirical mode decomposition in fault diagnosis of rotating machinery," *Mech. Syst. Signal Process.*, vol. 35, nos. 1–2, pp. 108–126, Feb. 2013.
- [4] S. Yin and O. Kaynak, "Big data for modern industry: Challenges and trends [point of view]," *Proc. IEEE*, vol. 103, no. 2, pp. 143–146, Feb. 2015.
- [5] W. Qiao and D. Lu, "A survey on wind turbine condition monitoring and fault diagnosis—Part I: Components and subsystems," *IEEE Trans. Ind. Electron.*, vol. 62, no. 10, pp. 6536–6545, Oct. 2015.
- [6] Y. Lei, J. Lin, M. J. Zuo, and Z. He, "Condition monitoring and fault diagnosis of planetary gearboxes: A review," *Measurement*, vol. 48, pp. 292–305, Feb. 2014.
- [7] Z. Gao, C. Cecati, and S. X. Ding, "A survey of fault diagnosis and fault-tolerant techniques—Part I: Fault diagnosis with model-based and signal-based approaches," *IEEE Trans. Ind. Electron.*, vol. 62, no. 6, pp. 3757–3767, Jun. 2015.



- [8] Y. Tian, C. Lu, and Z. L. Wang, "Approach for hydraulic pump fault diagnosis based on WPT-SVD and SVM," Appl. Mech. Mater., vols. 764–765, pp. 191–197, May 2015.
- [9] Y. Lei, "A deep learning-based method for machinery health monitoring with big data," J. Mech. Eng., vol. 51, no. 21, p. 49, Nov. 2015.
- [10] K. Worden, W. J. Staszewski, and J. J. Hensman, "Natural computing for mechanical systems research: A tutorial overview," *Mech. Syst. Signal Process.*, vol. 25, no. 1, pp. 4–111, Jan. 2011.
- [11] L. An and N. Sepehri, "Hydraulic actuator circuit fault detection using extended Kalman filter," in *Proc. Amer. Control Conf.*, Jan. 2004, vol. 5, no. 1, pp. 4261–4266.
- [12] L. An and N. Sepehri, "Leakage fault identification in a hydraulic positioning system using extended Kalman filter," in *Proc. Amer. Control Conf.*, vol. 4, 2004, pp. 3088–3093.
- [13] W. Du, Z. Zhou, and X. Huang, "The application of wavelet analysis to hydraulic cylinder leakage detection," *Mach. Tools Hydraulic Pressure*, vol. 6, pp. 318–319, Jun. 2003.
- [14] A. Y. Goharrizi and N. Sepehri, "A wavelet-based approach to internal seal damage diagnosis in hydraulic actuators," *IEEE Trans. Ind. Elec*tron., vol. 57, no. 5, pp. 1755–1763, May 2010.
- [15] W. Du, M. Kang, and M. Pecht, "Fault diagnosis using adaptive multifractal detrended fluctuation analysis," *IEEE Trans. Ind. Electron.*, vol. 67, no. 3, pp. 2272–2282, Mar. 2020.
- [16] S. Zhou and S. Wang, Innovative Thinking and Methods. Beijing, China: China Railway Publishing House, Sep. 2016, p. 42.
- [17] S. L. Chan, Y. Lu, and Y. Wang, "Data-driven cost estimation for additive manufacturing in cybermanufacturing," *J. Manuf. Syst.*, vol. 46, pp. 115–126, Jan. 2018.
- [18] J. Wang, Y. Ma, L. Zhang, R. X. Gao, and D. Wu, "Deep learning for smart manufacturing: Methods and applications," *J. Manuf. Syst.*, vol. 48, pp. 144–156, Jul. 2018.
- [19] B. Samanta, "Gear fault detection using artificial neural networks and support vector machines with genetic algorithms," *Mech. Syst. Signal Process.*, vol. 18, no. 3, pp. 625–644, May 2004.
- [20] A. Hajnayeb, A. Ghasemloonia, S. Khadem, and M. Moradi, "Application and comparison of an ANN-based feature selection method and the genetic algorithm in gearbox fault diagnosis," *Expert Syst. Appl.*, vol. 38, no. 8, pp. 10205–10209, Aug. 2011.
- [21] X. Zhang, B. Wang, and X. Chen, "Intelligent fault diagnosis of roller bearings with multivariable ensemble-based incremental support vector machine," *Knowl.-Based Syst.*, vol. 89, pp. 56–85, Nov. 2015.
- [22] R. Jegadeeshwaran and V. Sugumaran, "Fault diagnosis of automobile hydraulic brake system using statistical features and support vector machines," *Mech. Syst. Signal Process.*, vols. 52–53, pp. 436–446, Feb. 2015.
- [23] G. Bin, J. Gao, X. Li, and B. Dhillon, "Early fault diagnosis of rotating machinery based on wavelet packets-empirical mode decomposition feature extraction and neural network," *Mech. Syst. Signal Process.*, vol. 27, pp. 696–711, Feb. 2012.
- [24] R. Saeed, A. Galybin, and V. Popov, "3D fluid-structure modelling and vibration analysis for fault diagnosis of Francis turbine using multiple ANN and multiple ANFIS," *Mech. Syst. Signal Process.*, vol. 34, nos. 1–2, pp. 259–276, Jan. 2013.
- [25] M. Schlechtingen and I. Ferreira Santos, "Comparative analysis of neural network and regression based condition monitoring approaches for wind turbine fault detection," *Mech. Syst. Signal Process.*, vol. 25, no. 5, pp. 1849–1875, Jul. 2011.
- [26] M. Amar, I. Gondal, and C. Wilson, "Vibration spectrum imaging: A novel bearing fault classification approach," *IEEE Trans. Ind. Electron.*, vol. 62, no. 1, pp. 494–502, Jan. 2015.
- [27] H. Jiang, J. Chen, G. Dong, T. Liu, and G. Chen, "Study on Hankel matrix-based SVD and its application in rolling element bearing fault diagnosis," *Mech. Syst. Signal Process.*, vols. 52–53, pp. 338–359, Feb. 2015.
- [28] M. Zeng, Y. Yang, J. Zheng, and J. Cheng, "Maximum margin classification based on flexible convex hulls for fault diagnosis of roller bearings," *Mech. Syst. Signal Process.*, vols. 66–67, pp. 533–545, Jan. 2016.
- [29] Y. Li, C. K. L. Lekamalage, T. Liu, P.-A. Chen, and G.-B. Huang, "Learning representations with local and global geometries preserved for machine fault diagnosis," *IEEE Trans. Ind. Electron.*, vol. 67, no. 3, pp. 2360–2370, Mar. 2020.
- [30] W. Li, "A firefly neural network and its application in bearing fault diagnosis," Chin. J. Mech. Eng., vol. 51, no. 7, p. 99, Apr. 2015.

- [31] Y. Lei, F. Jia, J. Lin, S. Xing, and S. X. Ding, "An Intelligent fault diagnosis method using unsupervised feature learning towards mechanical big data," *IEEE Trans. Ind. Electron.*, vol. 63, no. 5, pp. 3137–3147, May 2016.
- [32] H. Shao, H. Jiang, H. Zhang, and T. Liang, "Electric locomotive bearing fault diagnosis using a novel convolutional deep belief network," *IEEE Trans. Ind. Electron.*, vol. 65, no. 3, pp. 2727–2736, Mar. 2018.
- [33] G. E. Hinton, "Reducing the dimensionality of data with neural networks," *Science*, vol. 313, no. 5786, pp. 504–507, Jul. 2006.
- [34] Y. L. Cun, Y. Bengio, and G. E. Hinton, "Deep learning," *Nature*, vol. 521, no. 28, pp. 436–444, May 2015.
- [35] H. Shao, H. Jiang, X. Zhang, and M. Niu, "Rolling bearing fault diagnosis using an optimization deep belief network," *Meas. Sci. Technol.*, vol. 26, no. 11, Nov. 2015, Art. no. 115002.
- [36] F. Jia, Y. Lei, J. Lin, X. Zhou, and N. Lu, "Deep neural networks: A promising tool for fault characteristic mining and intelligent diagnosis of rotating machinery with massive data," *Mech. Syst. Signal Process.*, vols. 72–73, pp. 303–315, May 2016.
- [37] X. Guo, L. Chen, and C. Shen, "Hierarchical adaptive deep convolution neural network and its application to bearing fault diagnosis," *Measure-ment*, vol. 93, pp. 490–502, Nov. 2016.
- [38] H. R. Li and S. S. Gu, "A fast parallel algorithm for a recurrent neural network," Acta Automatica Sinica, vol. 30, no. 4, pp. 516–522, Jul. 2004.
- [39] J. Jiao, M. Zhao, J. Lin, and J. Zhao, "A multivariate encoder information based convolutional neural network for intelligent fault diagnosis of planetary gearboxes," *Knowl.-Based Syst.*, vol. 160, pp. 237–250, Nov. 2018.
- [40] S. Pang, X. Yang, X. Zhang, and X. Lin, "Fault diagnosis of rotating machinery with ensemble kernel extreme learning machine based on fused multi-domain features," ISA Trans., to be published.
- [41] Siri. Accessed: Apr. 20, 2017. [Online]. Available: https://en.wikipedia. org/wiki/Siri
- [42] AlphaGo. Accessed: Apr. 20, 2017. [Online]. Available: https://deepmind.com/research/alphago/
- [43] A. Graves, A.-R. Mohamed, and G. Hinton, "Speech recognition with deep recurrent neural networks," in *Proc. IEEE Int. Conf. Acoust., Speech Signal Process.*, May 2013, pp. 1–5.
- [44] K. Yan and D. Zhang, "Correcting instrumental variation and timevarying drift: A transfer learning approach with autoencoders," *IEEE Trans. Instrum. Meas.*, vol. 65, no. 9, pp. 2012–2022, Sep. 2016.
- [45] M. Oquab, L. Bottou, I. Laptev, and J. Sivic, "Learning and transferring mid-level image representations using convolutional neural networks," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit.*, Jun. 2014, pp. 1717–1724.
- [46] J. Lee, F. Wu, W. Zhao, M. Ghaffari, L. Liao, and D. Siegel, "Prognostics and health management design for rotary machinery systems—Reviews, methodology and applications," *Mech. Syst. Signal Process.*, vol. 42, nos. 1–2, pp. 314–334, Jan. 2014.
- [47] Z. Zhou, Machine Learning. Beijing, China: Tsinghua Univ. Press, 2016, p. 113.
- [48] J. Schmidhuber, "Deep learning in neural networks: An overview," *Neural Netw.*, vol. 61, pp. 85–117, Jan. 2015.
- [49] S. J. Pan and Q. Yang, "A survey on transfer learning," *IEEE Trans. Knowl. Data Eng.*, vol. 22, no. 10, pp. 1345–1359, Oct. 2010.
- [50] H. Venkateswara, S. Chakraborty, and S. Panchanathan, "Deep-learning systems for domain adaptation in computer vision," *IEEE Signal Process. Mag.*, vol. 34, no. 6, pp. 117–129, Nov. 2017.
- [51] G. Hinton, L. Deng, D. Yu, G. Dahl, A.-R. Mohamed, N. Jaitly, A. Senior, V. Vanhoucke, P. Nguyen, T. Sainath, and B. Kingsbury, "Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups," *IEEE Signal Process. Mag.*, vol. 29, no. 6, pp. 82–97, Nov. 2012.
- [52] H. V. Nguyen, H. T. Ho, V. M. Patel, and R. Chellappa, "DASH-N: Joint hierarchical domain adaptation and feature learning," *IEEE Trans. Image Process.*, vol. 24, no. 12, pp. 5479–5491, Dec. 2015.
- [53] L. Zhang, W. Zuo, and D. Zhang, "LSDT: Latent sparse domain transfer learning for visual adaptation," *IEEE Trans. Image Process.*, vol. 25, no. 3, pp. 1177–1191, Mar. 2016.
- [54] Y. Lei, Intelligent Fault Diagnosis and Remaining Useful Life Prediction of Rotating Machinery. London, U.K.: Butterworth-Heinemann, 2016.
- [55] F. Jia, Y. Lei, L. Guo, J. Lin, and S. Xing, "A neural network constructed by deep learning technique and its application to intelligent fault diagnosis of machines," *Neurocomputing*, vol. 272, pp. 619–628, Jan. 2018.



- [56] G. Jiang, H. He, P. Xie, and Y. Tang, "Stacked multilevel-denoising autoencoders: A new representation learning approach for wind turbine gearbox fault diagnosis," *IEEE Trans. Instrum. Meas.*, vol. 66, no. 9, pp. 2391–2402, Sep. 2017.
- [57] R. Zhang, H. Tao, L. Wu, and Y. Guan, "Transfer learning with neural networks for bearing fault diagnosis in changing working conditions," *IEEE Access*, vol. 5, pp. 14347–14357, 2017.
- [58] J. Dai, J. Tang, S. Huang, and Y. Wang, "Signal-based intelligent hydraulic fault diagnosis methods: Review and prospects," *Chin. J. Mech. Eng.*, vol. 32, p. 75, Dec. 2019.
- [59] W. Lu, B. Liang, Y. Cheng, D. Meng, J. Yang, and T. Zhang, "Deep model based domain adaptation for fault diagnosis," *IEEE Trans. Ind. Electron.*, vol. 64, no. 3, pp. 2296–2305, Mar. 2017.
- [60] J. Xie, L. Zhang, L. Duan, and J. Wang, "On cross-domain feature fusion in gearbox fault diagnosis under various operating conditions based on transfer component analysis," in *Proc. IEEE Int. Conf. Prognostics Health Manage. (ICPHM)*, Ottawa, ON, Canada, Jun. 2016, pp. 1–6.
- [61] G. Jiang, H. He, J. Yan, and P. Xie, "Multiscale convolutional neural networks for fault diagnosis of wind turbine gearbox," *IEEE Trans. Ind. Electron.*, vol. 66, no. 4, pp. 3196–3207, Apr. 2019.
- [62] F.-C. Chen and M. R. Jahanshahi, "NB-CNN: Deep learning-based crack detection using convolutional neural network and Naïve Bayes data fusion," *IEEE Trans. Ind. Electron.*, vol. 65, no. 5, pp. 4392–4400, May 2018.
- [63] L. Chen, G. Xu, Q. Zhang, and X. Zhang, "Learning deep representation of imbalanced SCADA data for fault detection of wind turbines," *Measurement*, vol. 139, pp. 370–379, Jun. 2019.
- [64] Z. Zhang, S. Li, J. Wang, Y. Xin, and Z. An, "General normalized sparse filtering: A novel unsupervised learning method for rotating machinery fault diagnosis," *Mech. Syst. Signal Process.*, vol. 124, pp. 596–612, Jun. 2019.
- [65] W. Zhang, C. Li, G. Peng, Y. Chen, and Z. Zhang, "A deep convolutional neural network with new training methods for bearing fault diagnosis under noisy environment and different working load," *Mech. Syst. Signal Process.*, vol. 100, pp. 439–453, Feb. 2018.
- [66] J. Pan, Y. Zi, J. Chen, Z. Zhou, and B. Wang, "LiftingNet: A novel deep learning network with layerwise feature learning from noisy mechanical data for fault classification," *IEEE Trans. Ind. Electron.*, vol. 65, no. 6, pp. 4973–4982, Jun. 2018.
- [67] X. Ding and Q. He, "Energy-fluctuated multiscale feature learning with deep ConvNet for intelligent spindle bearing fault diagnosis," *IEEE Trans. Instrum. Meas.*, vol. 66, no. 8, pp. 1926–1935, Aug. 2017.
- [68] D. Lee, V. Siu, R. Cruz, and C. Yetman, "Convolutional neural net and bearing fault analysis," in *Proc. Int. Conf. Data Mining Steering Committee World Congr. Comput. Sci., Comput. Eng. Appl. Comput.* (WorldComp), Jan. 2016, p. 194.
- [69] D.-T. Hoang and H.-J. Kang, "Rolling element bearing fault diagnosis using convolutional neural network and vibration image," *Cognit. Syst. Res.*, vol. 53, pp. 42–50, Jan. 2019.
- [70] S. Guo, T. Yang, W. Gao, and C. Zhang, "A novel fault diagnosis method for rotating machinery based on a convolutional neural network," *Sensors*, vol. 18, no. 5, p. 1429, May 2018.
- [71] D. Peng, Z. Liu, H. Wang, Y. Qin, and L. Jia, "A novel deeper onedimensional CNN with residual learning for fault diagnosis of wheelset bearings in high-speed trains," *IEEE Access*, vol. 7, pp. 10278–10293, Dec. 2019.
- [72] Z. Chen and W. Li, "Multisensor feature fusion for bearing fault diagnosis using sparse autoencoder and deep belief network," *IEEE Trans. Instrum. Meas.*, vol. 66, no. 7, pp. 1693–1702, Jul. 2017.
- [73] H. Liu, J. Zhou, Y. Zheng, W. Jiang, and Y. Zhang, "Fault diagnosis of rolling bearings with recurrent neural network-based autoencoders," *ISA Trans.*, vol. 77, pp. 167–178, Jun. 2018.
- [74] D. T. Hoang and H. J. Kang, "A bearing fault diagnosis method based on autoencoder and particle swarm optimization-support vector machine," in *Intelligent Computing Theories and Application*. Cham, Switzerland: Springer, 2018.
- [75] S. Tao, T. Zhang, J. Yang, X. Wang, and W. Lu, "Bearing fault diagnosis method based on stacked autoencoder and softmax regression," in *Proc.* 34th Chin. Control Conf. (CCC), Jul. 2015, pp. 6331–6335.
- [76] X. Zhang, X. Zhou, and C. Tang, "A deep convolutional auto-encoding neural network and its application in bearing fault diagnosis," *J. Xi'an Jiaotong Univ.*, vol. 52, no. 7, pp. 1–8 and 59, 2018.

- [77] F. Wang, "Application of kernel auto-encoder based on firefly optimization in intershaft bearing fault diagnosis," *JME*, vol. 55, no. 7, p. 58, Aug. 2019.
- [78] B. She, F. Tian, and W. Liang, "Fault diagnosis based on a deep convolution variational autoencoder network," *Chin. J. Sci. Instrum.*, vol. 39, no. 10, pp. 27–35, Oct. 2018.
- [79] J. Tao, Y. Liu, and D. Yang, "Bearing fault diagnosis based on deep belief network and multisensor information fusion," *Shock Vib.*, vol. 2016, pp. 1–9, Aug. 2016.
- [80] Y. Li, X. Wang, M. Zhang, and H. Zhu, "An approach to fault diagnosis of rolling bearing using SVD and multiple DBN classifiers," *J. Shanghai Jiaotong Univ.*, vol. 49, no. 5, pp. 681–686, 694, May 2015.
- [81] X. Wang, Y. Li, T. Rui, H. Zhu, and J. Fei, "Bearing fault diagnosis method based on Hilbert envelope spectrum and deep belief network," J. Vib., vol. 17, no. 3, pp. 1295–1308, May 2015.
- [82] M. Gan, C. Wang, and C. Zhu, "Construction of hierarchical diagnosis network based on deep learning and its application in the fault pattern recognition of rolling element bearings," *Mech. Syst. Signal Process.*, vols. 72–73, pp. 92–104, May 2016.
- [83] Z. Chen, C. Li, and R. V. Sánchez, "Multi-layer neural network with deep belief network for gearbox fault diagnosis," *J. Vibroeng.*, vol. 17, no. 5, pp. 2379–2392, Jul. 2015.
- [84] Z. Chen, C. Li, and R.-V. Sanchez, "Gearbox fault identification and classification with convolutional neural networks," *Shock Vib.*, vol. 2015, pp. 1–10, Oct. 2015.
- [85] G. Liu, H. Bao, and B. Han, "A stacked autoencoder-based deep neural network for achieving gearbox fault diagnosis," *Math. Problems Eng.*, vol. 2018, pp. 1–10, Jul. 2018.
- [86] Z. Wang, J. Wang, and Y. Wang, "An intelligent diagnosis scheme based on generative adversarial learning deep neural networks and its application to planetary gearbox fault pattern recognition," *Neurocomputing*, vol. 310, pp. 213–222, Oct. 2018.
- [87] H. Zheng, R. Wang, J. Yin, Y. Li, H. Lu, and M. Xu, "A new intelligent fault identification method based on transfer locality preserving projection for actual diagnosis scenario of rotating machinery," *Mech. Syst. Signal Process.*, vol. 135, Jan. 2020, Art. no. 106344.
- [88] C. Li, R.-V. Sanchez, G. Zurita, M. Cerrada, D. Cabrera, and R. E. Vásquez, "Multimodal deep support vector classification with homologous features and its application to gearbox fault diagnosis," *Neurocomputing*, vol. 168, pp. 119–127, Nov. 2015.
- [89] Z. He, H. Shao, J. Cheng, X. Zhao, and Y. Yang, "Support tensor machine with dynamic penalty factors and its application to the fault diagnosis of rotating machinery with unbalanced data," *Mech. Syst. Signal Process.*, Oct. 2019, Art. no. 106441, doi: 10.1016/j.ymssp.2019.106441.
- [90] L. Wen, X. Li, L. Gao, and Y. Zhang, "A new convolutional neural network-based data-driven fault diagnosis method," *IEEE Trans. Ind. Electron.*, vol. 65, no. 7, pp. 5990–5998, Jul. 2018.
- [91] K. Li and Q. Wang, "Study on signal recognition and diagnosis for spacecraft based on deep learning method," in *Proc. Prognostics Syst. Health Manage. Conf. (PHM)*, Oct. 2015.
- [92] Y. H. Eom, J. W. Yoo, S. B. Hong, and M. S. Kim, "Refrigerant charge fault detection method of air source heat pump system using convolutional neural network for energy saving," *Energy*, vol. 187, Nov. 2019, Art. no. 115877.
- [93] C. Lanham, "Understanding the tests that are recommended for electric motor predictive maintenance," Baker Instrum. Company, Fort Collins, CO, USA, Tech. Rep. 1, Jan. 2009.
- [94] S. Nandi, H. A. Toliyat, and X. Li, "Condition monitoring and fault diagnosis of electrical motors-a review," *IEEE Trans. Energy Convers.*, vol. 20, no. 4, pp. 719–729, Dec. 2005.
- [95] F. Jia, Y. Lei, N. Lu, and S. Xing, "Deep normalized convolutional neural network for imbalanced fault classification of machinery and its understanding via visualization," *Mech. Syst. Signal Process.*, vol. 110, pp. 349–367, Sep. 2018.
- [96] K. Weiss, T. M. Khoshgoftaar, and D. Wang, "A survey of transfer learning," J. Big Data, vol. 3, pp. 9–49, May 2016.
- [97] W. Qian, S. Li, and X. Jiang, "Deep transfer network for rotating machine fault analysis," *Pattern Recognit.*, vol. 96, Dec. 2019, Art. no. 106993.
- [98] L. Guo, Y. Lei, S. Xing, T. Yan, and N. Li, "Deep convolutional transfer learning network: A new method for intelligent fault diagnosis of machines with unlabeled data," *IEEE Trans. Ind. Electron.*, vol. 66, no. 9, pp. 7316–7325, Sep. 2019.



- [99] B. Yang, Y. Lei, F. Jia, and S. Xing, "An intelligent fault diagnosis approach based on transfer learning from laboratory bearings to locomotive bearings," *Mech. Syst. Signal Process.*, vol. 122, pp. 692–706, May 2019.
- [100] L. Wen, L. Gao, and X. Li, "A new deep transfer learning based on sparse auto-encoder for fault diagnosis," *IEEE Trans. Syst. Man Cybern, Syst.*, vol. 49, no. 1, pp. 136–144, Jan. 2019.
- [101] M. He and D. He, "A new hybrid deep signal processing approach for bearing fault diagnosis using vibration signals," *Neurocomputing*, to be published, doi: 10.1016/j.neucom.2018.12.088.
- [102] W. Mao, W. Feng, and X. Liang, "A novel deep output kernel learning method for bearing fault structural diagnosis," *Mech. Syst. Signal Pro*cess., vol. 117, pp. 293–318, Feb. 2019.
- [103] H. Shao, H. Jiang, H. Zhang, W. Duan, T. Liang, and S. Wu, "Rolling bearing fault feature learning using improved convolutional deep belief network with compressed sensing," *Mech. Syst. Signal Process.*, vol. 100, pp. 743–765, Feb. 2018.
- [104] M. Sun, H. Wang, P. Liu, S. Huang, and P. Fan, "A sparse stacked denoising autoencoder with optimized transfer learning applied to the fault diagnosis of rolling bearings," *Measurement*, vol. 146, pp. 305–314, Nov. 2010.
- [105] F. Xu, W. T. P. Tse, and Y. L. Tse, "Roller bearing fault diagnosis using stacked denoising autoencoder in deep learning and Gath–Geva clustering algorithm without principal component analysis and data label," *Appl. Soft Comput.*, vol. 73, pp. 898–913, Dec. 2018.
- [106] Z. Gao, S. X. Ding, and C. Cecati, "Real-time fault diagnosis and fault-tolerant control," *IEEE Trans. Ind. Electron.*, vol. 62, no. 6, pp. 3752–3756, Jun. 2015.
- [107] Z. Chen, K. Gryllias, and W. Li, "Mechanical fault diagnosis using convolutional neural networks and extreme learning machine," *Mech. Syst. Signal Process.*, vol. 133, Nov. 2019, Art. no. 106272.
- [108] T. Han, C. Liu, W. Yang, and D. Jiang, "Deep transfer network with joint distribution adaptation: A new intelligent fault diagnosis framework for industry application," ISA Trans., to be published.
- [109] W. Qian, S. Li, P. Yi, and K. Zhang, "A novel transfer learning method for robust fault diagnosis of rotating machines under variable working conditions," *Measurement*, vol. 138, pp. 514–525, May 2019.
- [110] F. Li, X. Pang, and Z. Yang, "Motor current signal analysis using deep neural networks for planetary gear fault diagnosis," *Measurement*, vol. 145, pp. 45–54, Oct. 2019.
- [111] Y. Li, G. Cheng, C. Liu, and X. Chen, "Study on planetary gear fault diagnosis based on variational mode decomposition and deep neural networks," *Measurement*, vol. 130, pp. 94–104, Dec. 2018.
- [112] S. Ma, F. Chu, and Q. Han, "Deep residual learning with demodulated time-frequency features for fault diagnosis of planetary gearbox under nonstationary running conditions," *Mech. Syst. Signal Process.*, vol. 127, pp. 190–201, Jul. 2019.
- [113] G. Qiu, Y. Gu, and Q. Cai, "A deep convolutional neural networks model for intelligent fault diagnosis of a gearbox under different operational conditions," *Measurement*, vol. 145, pp. 94–107, Oct. 2019.
- [114] H. Shao, H. Jiang, H. Zhao, and F. Wang, "A novel deep autoencoder feature learning method for rotating machinery fault diagnosis," *Mech. Syst. Signal Process.*, vol. 95, pp. 187–204, Oct. 2017.
- [115] K. Zhang, B. Tang, Y. Qin, and L. Deng, "Fault diagnosis of planetary gearbox using a novel semi-supervised method of multiple association layers networks," *Mech. Syst. Signal Process.*, vol. 131, pp. 243–260, Sep. 2019.
- [116] Y. Zhu, P. Qian, S. Tang, W. Jiang, W. Li, and J. Zhao, "Amplitude-frequency characteristics analysis for vertical vibration of hydraulic AGC system under nonlinear action," AIP Adv., vol. 9, no. 3, Mar. 2019, Art. no. 035019.
- [117] Y. Zhu, S. Tang, C. Wang, W. Jiang, J. Zhao, and G. Li, "Absolute stability condition derivation for position closed-loop system in hydraulic automatic gauge control," *Processes*, vol. 7, no. 10, p. 766, Oct. 2019.
- [118] Y. Zhu, S. Tang, C. Wang, W. Jiang, X. Yuan, and Y. Lei, "Bifurcation characteristic research on the load vertical vibration of a hydraulic automatic gauge control system," *Processes*, vol. 7, no. 10, p. 718, Oct. 2019.
- [119] J. Du, S. Wang, and H. Zhang, "Layered clustering multi-fault diagnosis for hydraulic piston pump," *Mech. Syst. Signal Process.*, vol. 36, no. 2, pp. 487–504, Apr. 2013.
- [120] J. Ma, H. Li, and B. Xu, "Fault model identification of hydraulic pump based on MLSE and extension theory," *Mach. Tool Hydraul.*, vol. 43, no. 11, pp. 182–187, Jun. 2015.

- [121] S. Kumar and J. Bergada, "The effect of piston grooves performance in an axial piston pumps via CFD analysis," *Int. J. Mech. Sci.*, vol. 66, pp. 168–179, Jan. 2013.
- [122] S. Kumar, J. Bergada, and J. Watton, "Axial piston pump grooved slipper analysis by CFD simulation of three-dimensional NVS equation in cylindrical coordinates," *Comput. Fluids*, vol. 38, no. 3, pp. 648–663, Mar. 2009.
- [123] X. Yang, J. Yan, H. Zhu, Y. Cao, and L. Shao, "Research on fault diagnosis of hydraulic pump using convolutional neural network," *J. Vibroeng.*, vol. 18, no. 8, pp. 5141–5152, Dec. 2016.
- [124] C. Lu, Y. Wang, M. Ragulskis, and Y. Cheng, "Fault diagnosis for rotating machinery: A method based on image processing," *PLoS ONE*, vol. 11, no. 10, Oct. 2016, Art. no. e0164111.
- [125] S. Wang, J. Xiang, Y. Zhong, and H. Tang, "A data indicator-based deep belief networks to detect multiple faults in axial piston pumps," *Mech. Syst. Signal Process.*, vol. 112, pp. 154–170, Nov. 2018.
- [126] Y. Li, Y. Yang, G. Li, M. Xu, and W. Huang, "A fault diagnosis scheme for planetary gearboxes using modified multi-scale symbolic dynamic entropy and mRMR feature selection," *Mech. Syst. Signal Process.*, vol. 91, pp. 295–312, Jul. 2017.
- [127] Y. Yang, H. Zheng, Y. Li, M. Xu, and Y. Chen, "A fault diagnosis scheme for rotating machinery using hierarchical symbolic analysis and convolutional neural network," *ISA Trans.*, vol. 91, pp. 235–252, Aug. 2019.
- [128] H. Wang, S. Li, L. Song, and L. Cui, "A novel convolutional neural network based fault recognition method via image fusion of multi-vibrationsignals," *Comput. Ind.*, vol. 105, pp. 182–190, Feb. 2019.
- [129] Z. Qi, B. Wang, Y. Tian, and P. Zhang, "When ensemble learning meets deep learning: A new deep support vector machine for classification," *Knowl.-Based Syst.*, vol. 107, pp. 54–60, Sep. 2016.
- [130] L. C. Jiao, J. Zhao, and S. Y. Yan, Deep Learning, Optimization and Recognition. Beijing, China: Tsinghua Univ. Press, 2017, pp. 116–117.
- [131] K. Li, R. Zhang, F. Li, L. Su, H. Wang, and P. Chen, "A new rotation machinery fault diagnosis method based on deep structure and sparse least squares support vector machine," *IEEE Access*, vol. 7, pp. 26571–26580, 2019
- [132] Y. Lei, W. Jiang, A. Jiang, Y. Zhu, H. Niu, and S. Zhang, "Fault diagnosis method for hydraulic directional valves integrating PCA and XGBoost," *Processes*, vol. 7, no. 9, p. 589, Sep. 2019.
- [133] W. Zheng, Z. Wang, Y. Zhu, S. Tang, and B. Wang, "Feature extraction method for hydraulic pump fault signal based on improved empirical wavelet transform," *Processes*, vol. 7, no. 11, p. 824, Nov. 2019.
- [134] C. Wang, X. Chen, N. Qiu, Y. Zhu, and W. Shi, "Numerical and experimental study on the pressure fluctuation, vibration, and noise of multistage pump with radial diffuser," *J. Brazilian Soc. Mech. Sci. Eng.*, vol. 40, no. 10, p. 481, Oct. 2018.
- [135] S. Tang, Y. Zhu, W. Li, and J. Cai, "Status and prospect of research in preprocessing methods for measured signals in mechanical systems," *J. Drainage Irrigation Machinery Eng.*, vol. 37, no. 9, pp. 822–828, 2019.
- [136] Y. Zhu, S. Tang, L. Quan, W. Jiang, and L. Zhou, "Extraction method for signal effective component based on extreme-point symmetric mode decomposition and Kullback-Leibler divergence," J. Brazilian Soc. Mech. Sci. Eng., vol. 41, no. 2, p. 100, 2019.
- [137] J. Pei, F. Zhang, D. Appiah, B. Hu, S. Yuan, K. Chen, and S. N. Asomani, "Performance prediction based on effects of wrapping angle of a side channel pump," *Energies*, vol. 12, no. 1, p. 139, Jan. 2019.
- [138] Z. Liu, W. Jiang, W. Tan, and Y. Zhu, "Fault identification method for hydraulic pumps based on multi-feature fusion and multiple kernel learning SVM," *Chin. Mech. Eng.*, vol. 27, no. 24, pp. 3355–3361, Dec. 2016.



**SHENGNAN TANG** received the master's degree from Yanshan University, Qinhuangdao, China, in 2013. She is currently pursuing the Ph.D. degree with Jiangsu University. She has participated in more than ten research projects at provincial or ministerial levels. She has authored or coauthored more than ten publication articles. Her current research interests include intelligent fault diagnosis based on deep learning and their application in rotating machinery.





**SHOUQI YUAN** received the master's and Ph.D. degrees from the Jiangsu Institute of Technology (currently Jiangsu University), Zhenjiang, China, in 1990 and 1995, respectively. He visited Cranfield University, from 1995 to 1996. He is currently a Professor and an Academic Leader of the National Key Discipline Fluid Machinery and Engineering. He has presided and completed more than 30 projects, including National Science Fund for Distinguished Young Scholars, National

Natural Science Foundation, and National 863 project. He has authored or coauthored more than 300 publication articles and 13 books and holds more than 11 PCT patents granted, including two U.S. patents. His research area mainly focused on fluid machinery and engineering. He is a member of the IEEE ITS and RS and a Senior Member of the IET. He received two national prizes for Progress in Science and Technology and two second prize of National Teaching Achievement.



**YONG ZHU** received the master's and Ph.D. degrees from Yanshan University, Qinhuangdao, China, in 2013 and 2017, respectively. Since 2017, he has been an Assistant Professor and a Master's Supervisor with Jiangsu University. He has presided over and participated in more than 20 research projects at provincial or ministerial levels. He has authored or coauthored more than 50 publication articles and 2 books and holds more than 20 patents granted. His research areas mainly

focused on prognostics and health management, intelligent information processing, and fault diagnosis of rotating machinery. He received the Science and Technology Progress Award of the Ministry.

. .