

ACCEPTED VERSION

Anton Bergant, Angus Ross Simpson, John Vitkovsky
Developments in unsteady pipe flow friction modelling
Journal of Hydraulic Research, 2001; 39(3):249-257

© International Association Of Hydraulic Engineering and Research

*This is an Accepted Manuscript of an article published by Taylor & Francis Group in **Journal of Hydraulic Research** on 01/04/2001, available online: <http://www.tandfonline.com/10.1080/00221680109499828>*

PERMISSIONS

<http://journalauthors.tandf.co.uk/copyright/sharingYourWork.asp>

As a Taylor & Francis author, you can post your Accepted Manuscript (AM) on your departmental or personal website at any point after publication of your article (this includes posting to Facebook, Google groups, and LinkedIn, and linking from Twitter).

To encourage citation of your work we recommend that you insert a link from your posted AM to the published article on [Taylor & Francis Online](#) with the following text:

"This is an Accepted Manuscript of an article published by Taylor & Francis in [JOURNAL TITLE] on [date of publication], available online: [http://www.tandfonline.com/\[Article DOI\]](http://www.tandfonline.com/[Article DOI])."

The AM is defined by the [National Information Standards Organization](#) as:

"The version of a journal article that has been accepted for publication in a journal."

This means the version that has been through peer review and been accepted by a journal editor. When you receive the acceptance email from the Editorial Office we recommend that you retain this article for future posting.

Embargoes apply (see [PDF](#) | [Excel](#) for applicable embargo periods) if you are posting the AM to an institutional or subject repository, or to academic social networks like Mendeley, ResearchGate, or Academia.edu.

Embargo for Journal of Hydraulic Research is 12 months.

2 March 2015

<http://hdl.handle.net/2440/997>

Developments in unsteady pipe flow friction modelling

by

Bergant, A., Simpson, A.R. and Vitkovsky, J.P.

Journal of Hydraulic Research

Citation:

Bergant, A., Simpson, A.R. and Vitkovsky, J.P. (2001). "Developments in unsteady pipe flow friction modelling." *Journal of Hydraulic Research*, International Association of Hydraulic Research. Vol. 39, No. 3, May-June, 249–257. (98 citations to Jan. 2013 – Scopus)

For further information about this paper please email Angus Simpson at angus.simpson@adelaide.edu.au

Developments in unsteady pipe flow friction modelling

Developpements dans la modelisation de frottement en ecoulement non permariente en conduite

ANTON BERGANT, *Litostroj E.I. d.o.o., Litostrojska 40, 1000 Ljubljana, Slovenia*

ANGUS ROSS SIMPSON and JOHN VITKOVSKY, *Department of Civil and Environmental Engineering, University of Adelaide, Adelaide 5005, Australia*

ABSTRACT

This paper reviews a number of unsteady friction models for transient pipe flow. Two distinct unsteady friction models, the Zielke and the Brunone models, are investigated in detail. The Zielke model, originally developed for transient laminar flow, has been selected to verify its effectiveness for "low Reynolds number" transient turbulent flow. The Brunone model combines local inertia and wall friction unsteadiness. This model is verified using the Vardy's analytically deduced shear decay coefficient C^* to predict the Brunone's friction coefficient k rather than use the traditional trial and error method for estimating k . The two unsteady friction models have been incorporated into the method of characteristics water hammer algorithm. Numerical results from the quasi-steady friction model and the Zielke and the Brunone unsteady friction models are compared with results of laboratory measurements for water hammer cases with laminar and low Reynolds number turbulent flows. Conclusions about the range of validity for the three friction models are drawn. In addition, the convergence and stability of these models are addressed.

RESUME

Le papier passe en revue un certain nombre de modeles de friction non permanente en ecoulement transitoire en conduite. Deux modeles de friction non permanente, celui de Zielke et celui de Brunone sont investigues en details. Le modele de Zielke, developpe a l'origine pour les ecoulements transitoires laminaires, a ete selectionne pour tester l'efficacite du modele pour les ecoulements transitoires turbulents a faible nombre de Reynolds. Le modele de Brunone combine la variation de l'inertie locale et de la friction de paroi. Ce modele est verifie en utilisant le coefficient C^* d'amortissement du cisaillement de Vardy d'duit analytiquement pour predire le coefficient de friction k de Brunone, plutot que la method traditionnelle par essais et erreurs pour estimer k . Les deux modeles de friction non permanente ont ete incorpores dans un algorithme de calcul du coup de belier par la methode des caracteristiques. Les resultats numeriques obtenus a partir d'un modele de friction quasi permanente et a partir des modeles non permanents de Zielke et de Brunone sont compares avec des resultats de mesures en laboratoire pour des ecoulements laminaires ou turbulents a faible nombre de Reynolds. Des conclusions sont tirees sur les domaines de validite des trois modeles de friction. En complement, la convergence et la stabilite des modeles sont abordees.

1 Introduction

Traditionally the steady or quasi-steady friction terms are incorporated into the standard water hammer algorithms. This assumption is satisfactory for slow transients where the wall shear stress has a quasi-steady behaviour. Experimental validation of steady friction models for rapid transients [1, 2, 3, 4, 5] previously has shown significant discrepancies in attenuation and phase shift of pressure traces when the computational results are compared to the results of measurements. The discrepancies are introduced by a difference in velocity profile, turbulence and the transition from laminar to turbulent flow. The magnitude of the discrepancies is governed by flow conditions (fast or slow transients, laminar or turbulent flow) and liquid properties (viscosity). The inaccuracies in numerical model results may lead to erroneous prediction of column separation and vaporous cavitation events [5, 6, 7, 8]. Real time monitoring and control of piping systems requires accurate prediction of the pressure time history [9]. To reduce uncertainty, the influences from fluid-structure interaction and gas release should be excluded in unsteady friction validation experiments.

This paper reviews a number of unsteady friction models for transient pipe flow that have been proposed in the literature. These include an early model developed by Daily et al. [10] in which the unsteady friction is dependent on instantaneous mean flow velocity and instantaneous local acceleration. Numerous similar models have also been proposed. Brunone et al. [11] deduced an improved version in which the convective acceleration is added to Golia's [4] version of the basic Daily model. The Brunone model is relatively simple and gives a good match between the computed and measured results using an empirically predicted (by trial and error) Brunone friction coefficient k . Zielke [12] has derived a model for frequency dependent friction in transient laminar flow. The friction term is related to the instantaneous mean flow velocity and to weighted past velocity changes. The advantage of this approach is that there is no need for empirical coefficients that are calibrated for certain flow conditions. The Zielke model has been modified by several researchers to improve computational efficiency and to develop weights for transient turbulent flow. Vardy and Brown [13] deduced weighting functions from a shear layer-uniform core approximation of turbulent flow. Furthermore, the authors linked their model to the Brunone model [14] and discovered a range of validity for the instantaneous acceleration approach. The instantaneous acceleration is approximately proportional to the unsteady shear stress when the highest frequencies of interest are smaller than the reciprocal of the rise time. The rise time characterizes the vorticity diffusion through shear layer. Apart from one-dimensional (1D) models, which in different ways indirectly incorporate the instantaneous cross-sectional velocity profile (by empirical coefficients or weighting functions), a number of 2D models have been proposed including an early boundary layer model developed by Wood and Funk [15]. The 2D models compute an actual velocity profile and corresponding energy losses continuously during the transient process. The CPU and memory requirements for these models are large.

Two distinct unsteady friction models, the Zielke and the Brunone models, are investigated in this paper in detail. The Zielke model, originally developed for transient laminar flow, has been selected to verify its effectiveness for 'low Reynolds number' transient turbulent flow. Engineers should have better tools to be able to predict rapid transient events accurately early in the design process of the piping systems. As a result, the Brunone model is tested using Vardy's analytically deduced shear decay coefficient C^* to compute the coefficient k [14] rather than to estimate k by trial and error. The two unsteady friction models have been incorporated into the method of characteristics water hammer algorithm.

Computational results from the numerical models are compared with results of measurements performed in a laboratory apparatus comprising of 37.2 m long constant-sloping copper pipe of 22.1 mm internal diameter and a 1.63 mm wall thickness connecting two pressurized tanks. A comparison is made for the rapid closure of a downstream end valve. The performance of the Zielke and the Brunone friction models is investigated for three water hammer cases with steady state flow velocities of $V_0 = \{0, 0.20, 0.30\}$ m/s (laminar and low Reynolds number turbulent flow). In addition, quasi-steady friction model results are also included in the paper. Conclusions about the range of validity for the unsteady friction models are drawn. Convergence and stability of the friction models are addressed.

2 Unsteady friction models

The unsteady friction terms can be classified into six groups:

- 1) The friction term is dependent on instantaneous mean flow velocity V (Hino et al. [16], Brekke [17], Cocchi [18]),
- 2) The friction term is dependent on instantaneous mean flow velocity V and instantaneous local acceleration $\delta V/\delta t$ (Daily et al. [10], Carstens and Roller [19], Safwat and van der Polder [20], Kurokawa and Morikawa [21], Shuy and Apelt [22], Golia [4], Kompere [23]),
- 3) The friction term is dependent on instantaneous mean flow velocity V , instantaneous local acceleration $\delta V/\delta t$ and instantaneous convective acceleration $\delta V/\delta x$ (Brunone et al. [11], Bughazem and Anderson [24]),
- 4) The friction term is dependent on instantaneous mean flow velocity V and diffusion $\delta^2 V/\delta x^2$ (Vennart [25], Svingen [26]),
- 5) The friction term is dependent on instantaneous mean flow velocity V and weights for past velocity changes $W(t)$ (Zielke [12], Trikha [27], Achard and Lespinard [28], Arlt [29], Kagawa et al. [30], Brown [31], Yigang and Jing-Chao [32], Suzuki et al. [33], Schohl [34], Vardy [35], Vardy et al. [36], Vardy and Brown [13, 14], Shuy [37], Zarzycki [38]),

- 6) The friction term is based on cross-sectional distribution of instantaneous flow velocity (Wood and Funk [15], Ohmi et al. [39], Bratland [40], Vardy and Hwang [41], Eichinger and Lein [42], Vennatr0 [43], Silva-Araya and Chaudhry [44], Pezzinga [45]).

2.1 Unsteady friction in a standard water hammer model

The method of characteristics transformation of the unsteady pipe flow equations gives the water hammer compatibility equations which are valid along the characteristic lines [46]:

- along the C^+ characteristic line ($\Delta x/\Delta t = a$):

$$H_{i,t} - H_{i-1,t-\Delta t} + \frac{a}{g}(V_{i,t} - V_{i-1,t-\Delta t}) + \frac{f\Delta x}{2gD}V_{i,t}|V_{i-1,t-\Delta t}| = 0 \quad (1)$$

- along the C^- characteristic line ($\Delta x/\Delta t = -a$):

$$H_{i,t} - H_{i+1,t-\Delta t} - \frac{a}{g}(V_{i,t} - V_{i+1,t-\Delta t}) - \frac{f\Delta x}{2gD}V_{i,t}|V_{i+1,t-\Delta t}| = 0 \quad (2)$$

in which H = piezometric head (head), V = flow velocity, Δx = reach length, t = time, Δt = time step, a = water hammer wave speed, g = gravitational acceleration, f = Darcy-Weisbach friction factor, D = pipe diameter and i = node number. At a boundary (reservoir, valve), the boundary equation replaces one of the water hammer compatibility equations [46]. The staggered grid in applying the method of characteristics is used in this paper.

A constant value of the Darcy-Weisbach friction factor f (steady-state friction factor) is used in most of commercial software packages for water hammer analysis. As an alternative the unsteady friction factor used in Eqs. 1 and 2 can be expressed as a sum of the quasi-steady part f_q and unsteady part f_u i.e. $f = f_q + f_u$. Setting $f_u = 0$ leads to the quasi-steady friction model. The quasi-steady friction factor f_q is based on updating the Reynolds number for each new computation. For turbulent flow the Haaland explicit formula [47] is used in this paper. The Zielke and the Brunone unsteady friction models have been explicitly incorporated into the staggered grid of the method of characteristics. A first order approximation of friction term $f\Delta x/(2gD)V_{t-\Delta t}|V_{t-\Delta t}|$ is used in the two unsteady friction models.

2.2 The Zielke model

The original version of Zielke's model [12] is used in this paper. The model was analytically developed for transient laminar flow. The unsteady part of friction term is related to the weighted past velocity changes at a computational section:

$$f_{i,k} = (f_q)_{i,k} + \frac{32\nu}{DV_{i,k}|V_{i,k}|} \sum_{j=1}^{k-1} (V_{i,j+1} - V_{i,j-1})W((k-j)\Delta t) \quad (3)$$

$$-\tau > 0.02: W(\tau) = \sum_{i=1}^5 e^{-n_i\tau} \quad (4)$$

$$-\tau \leq 0.02: W(\tau) = \sum_{i=1}^6 m_i\tau^{(i-2)/2} \quad (5)$$

$$\tau = \frac{4\nu}{D^2}(k-j)\Delta t \quad (6)$$

in which j and k = multiples of the time step Δt , W = weights for past velocity changes, ν = kinematic viscosity of the fluid, τ = dimensionless time, and coefficients $\{n_i, i = 1, \dots, 5\} = \{-26.3744, -70.8493, 135.0198, -218.9216, -322.5544\}$ and $\{m_i, i = 1, \dots, 6\} = \{0.282095, -1.25, 1.057855, 0.937500, 0.396696, -0.351563\}$.

The Zielke model requires large computer storage and has been modified by several researchers to improve the computational efficiency and/or to extend its application to the transient turbulent flow conditions [13, 14, 27 to 38]. A variable account of weights for past velocity changes is proposed in this paper to study the influence of past velocity changes for different time scales.

2.3 The original Brunone model and the Vitkovsky formulation of the model

The Brunone model [11] relates unsteady friction part f_u to the instantaneous local acceleration $\delta V/\delta t$ and instantaneous convective acceleration $\delta v/\delta x$:

$$f = f_q + \frac{kD}{V|V|} \left(\frac{\delta V}{\delta t} - a \frac{\delta V}{\delta x} \right) \quad (7)$$

in which k = Brunone's friction coefficient and x = distance.

Vitkovsky in 1998 investigated the original Brunone model for various flow situations. He found Eq. 7 failed to predict a correct sign of the convective term $-a\delta V/\delta x$ for particular flow and wave directions in acceleration and deceleration phases. For example, Eq. 7 fails to predict the correct sign in case of closure of the upstream end valve in a simple pipeline system with initial flow is in positive x direction. The original Brunone formulation performs correctly in case of closure of the downstream end valve [5], [8].

Vitkovsky deduced a new formulation of Eq. 7:

$$f = f_q + \frac{kD}{V|V|} \left(\frac{\delta V}{\delta t} + a \text{sign}(V) \left| \frac{\delta V}{\delta x} \right| \right) \quad (8)$$

in which $\text{sign}(V) = (+1$ for $V \geq 0$ or -1 for $V < 0$). Eq. 8 gives the correct sign of convective term for all possible flow and water hammer wave movement directions for either the acceleration or deceleration phases.

The Brunone friction coefficient defined for the head loss equation $h_f = fLV^2/(2gD)$ can be predicted either empirically by the trial and error method or analytically using Vardy's shear decay coefficient C^* (note: Vardy and Brown [14] are using British definition of the head loss equation $h_f = 4f_{BR}LV^2/(2gD)$ [48] for which k is 4 times larger ($f = 4f_{BR}$), C^* is identical):

$$k = \frac{\sqrt{C^*}}{2} \quad (9)$$

The Vardy's shear decay coefficient C^* from [14] is:

-laminar flow: $C^* = 0.00476$ (10)

-turbulent flow: $C^* = \frac{7.41}{Re^{\log(14.3/Re^{0.05})}}$ (11)

in which Re = Reynolds number ($Re = VD/\nu$).

The unknown flow velocity for time and space derivatives (Eqs. 7 and 8) in a simple finite-difference formulation (Eqs. 1 and 2) is:

$$V_{t-2\Delta t} = 0.5(V_{t-\Delta t} + V_{t-3\Delta t}) \quad (12)$$

3 Experimental apparatus

A flexible laboratory apparatus for investigating water hammer and column separation events in pipelines has been designed and constructed [49]. The apparatus comprises a straight 37.23 m ($U_x = \pm 0.01$ m) long sloping copper pipe of 22.1 mm ($U_x = \pm 0.1$ mm) internal diameter and 1.63 mm ($U_x = \pm 0.05$ mm) wall thickness connecting two pressurized tanks (Fig. 1). The uncertainty in a measurement U_x is expressed as a root-sum-square combination of bias and precision error [50]. The pipe slope is constant at 5.45% ($U_x = \pm 0.01\%$).

A specified pressure in each of the tanks ($H_{T,1}$ and $H_{T,2}$; $U_x = \pm 0.3\%$) is controlled by a computerized pressure control system. The net water volume in both tanks and the capacity of the air compressor limit the maximum steady state velocity to 1.5 m/s and maximum operating pressure (pressure head) in each tank to 400 kPa (40 m). Water hammer events in the apparatus are initiated by rapid closure of the ball valve. Fast closure of the valve is carried out either by a torsional spring actuator (the closure time (t_c) may be set from 5 to 10 milliseconds) or manually by hand. The actuator provides a constant and repeatable valve closure time.

Five pressure transducers (H_v , $H_{q,1}$, H_{mp} , $H_{q,2}$ and H_r ; $U_x = \pm 0.7\%$ for the piezoelectric type transducers) are located at equidistant points along the pipeline including as close as possible to the end points (Fig. 1). The water temperature in Tank 1 (T_w ; $U_x = \pm 0.5^\circ\text{C}$) is continuously monitored and the valve position during closure is measured using optical sensors ($U_x = \pm 0.0001$ s for the valve closing time). Data acquisition and processing were performed using a Concurrent real-time UNIX data acquisition computer.




Figure 1: Experimental apparatus layout

Each experiment using the apparatus consists of two phases. Firstly, an initial steady state velocity condition ($U_x = \pm 1\%$ for the volumetric method) is established. Secondly, a transient event is initiated by a rapid closure of the valve. The wave propagation velocity ($U_x = \pm 0.1\%$) is obtained from the time measured for a water hammer wave to travel between the closed valve and the quarter point nearest to the valve.

4 Numerical and experimental results

Numerical and measured results of three water hammer experimental runs, with steady state flow velocities of $V_0 = \{0.10, 0.20, 0.30\}$ m/s (laminar and low Reynolds number turbulent flow), are compared to verify the performance of the Zielke and the Brunone unsteady friction models. In addition, quasi-steady friction model results are included in the analysis.

Computational and experimental runs were performed for a rapid closure of the valve positioned at the downstream end of the upward sloping pipe (Fig. 1). The flow conditions, identical for the three runs, were:

- static head in an upstream end tank $H_{T,2} = 32$. m
- valve closure time $t_c = 0.009$ s
- water hammer wave speed $a = 1319$ m/s

The number of reaches selected for each computational run were:

- comparison analysis $N = 16$
- stability analysis $N = \{8, 16, 32\}$

Computational and experimental results for the three runs are compared at the valve (H_v) and at the midpoint (H_{mp}). The results of measurements at the two quarter points ($H_{q,1}$ and $H_{q,2}$) show similar behaviour as the results at the midpoint. The head adjacent to the Tank 2 (H_r) is the reservoir head.

4.1 Comparison of numerical and experimental results for transient laminar flow

The experimental run with How velocity $V_0 = 0.10$ m/s is the laminar flow case with Reynolds number $Re = 1870$ (water temperature $T_w = 15.4^\circ\text{C}$). Computational results from the three friction models are compared with results of measurements and are depicted in Fig. 2.




Figure 2: Comparison of heads at the valve (H_v) and at the midpoint (H_{mp}) in upward sloping pipe; $V_0 = 0.10$ m/s

Computational results obtained by the quasi-steady friction model (Figs. 2(a) and 2(b)) agree well for the first and the second pressure head rise. The discrepancies between the results are magnified for later times. Results from the Zielke model (Figs. 2(c) and 2(d)) show significant improvement in both attenuation and phase shift of pressure head traces. The magnitude of discrepancies in phase shift is larger than the magnitude of discrepancies in attenuation of the pressure head traces. Results from the Brunone model (Figs. 2(e) and 2(f)) exhibit the best fit. The model generates slightly excessive damping for the transient laminar flow case with analytically predicted Brunone's friction coefficient $k = 0.0345$ (for British definition $k = 0.138$). The match between the computed and measured results can be further improved by using an empirically estimated k (by trial and error) or by a more complex numerical grid (different approximation of discharges, complete method of characteristics transformation of basic equations) [5, 24]. However, the proposed explicit finite-difference scheme using k from Eq. 9 significantly improves the results and shows a significant potential for improving the Brunone model.

The ratio of CPU user time for the quasi-steady:Zielke: Brunone model is 1:45:1.2. The CPU user time for Zielke's model increases rapidly for a larger number of reaches. Decreasing the number of past velocity changes used in Zielke's analysis can increase the computational efficiency of the model. This provides a negligible loss of accuracy. For example, a $4L1a$ storage time decreases the CPU user time by a factor of three.

4.2 Comparison of numerical and experimental results for transient turbulent flow

Two experimental runs with initial flow velocities $V_0 = \{0.20, 0.30\}$ m/s represent low Reynolds number turbulent flows. The corresponding Reynolds numbers are $Re = \{3750, 5600$ at water temperature $T_w = \{15.4, 15.5\}$ °C}. The results from the three friction models are compared with measured results and are shown in Figs. 3 and 4 respectively.

The quasi-steady state friction results for the two velocity cases (Figs. 3(a) and 3(b) for $V_0 = 0.20$ m/s; Figs. 4(a) and 4(b) for $V_0 = 0.30$ m/s) show similar behaviour compared to the results for the laminar flow velocity case (Figs. 2(a) and 2(b) for $V_0 = 0.10$ m/s). Results from the Zielke model (Figs. 3(c) and 3(d) for $V_0 = 0.20$ m/s; Figs. 4(c) and 4(d) for $V_0 = 0.3$ m/s) show significant improvement both in attenuation and phase shift of pressure head traces when compared to the quasi-steady model results. Inclusion of weights for past velocity changes developed for transient laminar flow increase the rate of energy loss for low Reynolds number transient turbulent flow ($Re < 104$) [5,27]. The magnitude of discrepancies between computed and measured results for low Reynolds number turbulent flow (Figs. 3(c) and 3(d) for $V_0 = 0.20$ m/s; Figs. 4(c) and 4(d) for $V_0 = 0.30$ m/s) is similar to that for laminar flow (Figs. 2(c) and 2(d) for $V_0 = 0.10$ m/s). The results of the calculation can be further improved by inclusion of weighting functions for transient turbulent flow [13, 14]. Results from the Brunone model (Figs. 3(e) and 3(f) for $V_a = 0.20$ m/s; Figs. 4(e) and 4(f) for $V_a = 0.30$ m/s) show the best match with experimental results. The model generates slightly lesser attenuation with a minor phase shift of pressure pulses. The analytically predicted Brunone's friction coefficient (Eq. 9) for velocity $V_a = 0.20$ m/s is $k = 0.0245$ (for British definition $k = 0.098$) and for velocity $V_a = 0.30$ m/s is $k = 0.0209$ (for British definition $k = 0.0836$). The performance of the Brunone model, as for the case of transient laminar flow, can be improved by empirically estimating k or by using a more complex numerical grid [5, 24]. The comparison clearly shows the dependence of k on the Reynolds number [14]. The next step in research is to incorporate a variable $k = k(Re)$ into the Brunone model. A similar comparison analysis for a broad range of high Reynolds number turbulent flows (105 to 107) would be highly desirable. Construction of a new experimental apparatus for investigating high Reynolds number turbulent flows is planned in ongoing research.




Figure 3: Comparison of heads at the valve (H_v) and at the midpoint (H_{mp}) in upward sloping pipe; $V_0 = 0.20$ m/s




Figure 4: Comparison of heads at the valve (H_v) and at the midpoint (H_{mp}) in upward sloping pipe; $V_0 = 0.30$ m/s

1.3 Convergence and stability

The numerical solution of unsteady friction models incorporated into the method of characteristics computational grid should satisfy convergence and stability criteria. Convergence relates to behaviour of the solution as Δx and Δt tend to zero while stability is concerned with round-off error growth [51]. The performance of unsteady friction models is examined for a number different Δx and Δt sizes to determine each model's internal consistency.

Bughazem and Anderson [24] reported a numerically unstable solution using the explicit finite-difference form of the Brunone model on the rectangular grid of the method of characteristics. The solution was strongly dependent on the number of reaches (effecting Δx and Δt). A method of characteristics implementation of the Brunone model using a space-line representation performed consistently for a broad range of numbers of reaches N (4 to 20). No inconsistencies using quasi-steady and Zielke models have been reported in the literature.

The influence of different number of reaches ($N = 8, 16$ and 32) is investigated for the three friction models presented in this paper. Examination of computational results reveals numerically stable behaviour of all three models. Fig. 5 shows that the results for the Brunone model using the staggered grid of the method of characteristics are consistent for various numbers of reaches for the three velocity cases that are presented in comparison analysis.

Conclusions

Results from the quasi-steady friction model, the Zielke model and the Brunone model have been compared with results of measurements from a fast valve closure in a laboratory apparatus. A comparison analysis includes experimental runs for laminar flow and low Reynolds number turbulent flows ($Re < 104$). The Zielke model, developed originally for laminar flow, performs effectively for low Reynolds number turbulent flow. The best fit is given by the Brunone model even when using explicit

finite-difference scheme and an analytically predicted Brunone's friction coefficient k which was calculated from Vardy's shear decay coefficient C^* . These results clearly indicate the dependence of k on the Reynolds number. The influence of different number of reaches was also investigated. Examination of computational results reveals numerically stable behaviour for all three friction models.




Figure 5: Numerical analysis of Brunone's model

Notation

a	water hammer wave speed
C^*	Vardy's shear decay coefficient
D	pipe diameter
f	Darcy-Weisbach friction factor
g	gravitational acceleration
h_f	friction-head loss
H	piezometric head (head)
k	Brunone's friction coefficient
L	pipe length
m_i	coefficient in the Zielke model
N	number of computational reaches
n_i	coefficient in the Zielke model
Re	Reynolds number = VD/ν
T_w	water temperature
t	time
t_c	valve closure time
U_x	uncertainty in a measurement
V	flow velocity
W	weighting function
x	distance
Δt	time step
Δx	reach length

ν	kinematic viscosity
τ	dimensionless time

Subscripts

i	node number
j	multiple of the time step $t1t$
k	multiple of the time step M
mp	midpoint
q	quasi-steady part
r	reservoir
T	pressurized tank
U	unsteady part
V	valve
0	steady state

References

1. HOLOMBE, E.L., and ROULEAU, W.T. (1967). The effect of viscous shear on transients in liquid lines. *Journal of Basic Engineering*, ASME, 89(1), 174-180.
2. VARDY, A.E. (1980). Unsteady flows: fact and friction. *Proc., 3rd Int. Conf. on Pressure Surges*, BHRA, Canterbury, England, 15-26.
3. BRUNONE, B., and GRECO, M. (1990). Un modello per la ricostruzione di fenomeni di colpo d'ariete anche in presenza di cavitazione. Riscontro sperimentale. *Proc., 2nd Convengo Nazionale di Idraulica e Costruzioni Idrauliche*, Cosenza, Italy, Vol. 4, 147-160 (in Italian).
4. GOLIA, U.M. (1990). Sulla valutazione delle forze resistenti nel colpo d'ariete. *Report n. 639*, Dept. of Hydr. and Envir. Engrg., University of Naples, Naples, Italy (in Italian).
5. BERG ANT, A., and SIMPSON, A.R. (1994). Estimating unsteady friction in transient cavitating pipe flow. *Proc., 2nd Int. Conf. on Water Pipeline Systems*, BHR Group, Edinburg, Scotland, 333-342.
6. VAN DE SANDE, E., BELDE, A.P., HAMER, B.J.G., and HIEMSTRA, W. (1980). Velocity profiles in accelerating pipe flows started from rest. *Proc., 3rd Int. Conf. on Pressure Surges*, BHRA, Canterbury, England, 1-14.
7. SHUY, E.B., and APELT, C.J. (1983). Friction effects in unsteady pipe flows. *Proc., 4th Int. Conf. on Pressure Surges*, BHRA, Bath, England, 147-164.
8. BRUNONE, B., GOLIA, U.M., and GRECO, M. (1995). Effects of two-dimensionality on pipe transients modelling. *Journal of Hydraulic Engineering*, ASCE, 121(12), 906-912.
9. BRUNONE, B., and CARRAVETTA, A. (1994). Daily management of irrigation pipe networks. Water hammer pressure surges and happened damages. *Proc., 2nd Int. Conf. On Water Pipeline Systems*, BHR Group, Edinburg, Scotland, 451-458.
10. DAILY, W.L., HANKEY, W.L., OLIVE, R.W., and JORDAAN, I.M. (1956). Resistance coefficients for accelerated and decelerated flows through smooth tubes and orifices. *Transactions of AS ME*, 78(July), 1071-1077.
11. BRUNONE, B., GOLIA, U.M., and GRECO, M. (1991). Some remarks on the momentum equation for fast transients. *Int. Meeting on Hydraulic Transients with Column Separation, 9th Round Table*, IAHR, Valencia, Spain, 140-148.
12. ZIELKE, W. (1968). Frequency-dependent friction in transient pipe flow. *Journal of Basic Engineering*, ASME, 90(J), 109-115.
13. VARDY, A.E., and BROWN, J.M.B. (1995). Transient, turbulent, smooth pipe flow. *Journal of Hydraulic Research*, 256 IAHR, 33(4), 435-456.
14. VARDY, A.E., and BROWN, J.M.B. (1996). On turbulent, unsteady, smooth-pipe flow. *Proc., Int. Conf. on Pressure Surges and Fluid Transients*, BHR Group, Harrogate, England, 289-311.
15. WOOD, D.J., and FUNK, J.E. (1970). A boundary-layer theory for transient viscous losses in turbulent flow. *Journal of Basic Engineering*, ASME, 92(4), 865-873.
16. HINO, M., SAWAMOTO, M., and TAKASU, S. (1977). Study on the transition to turbulence and frictional coefficient in an oscillatory pipe flow. *Transactions of JSCE*, 9, 282-284.
17. BREKKE, H. (1984). *A stability study on hydropower plant governing including the influence from a quasi-nonlinear damping of oscillatory flow and from the turbine characteristics*. PhD Thesis, NTH, Trondheim, Norway.

18. COCCHI, G. (1988). Esperimento sulla resistenza al deflusso con moto vario in un tubo. *Affi della Accademia delle Scienze dell' Istituto di Bologna*, Bologna, Italy, 14(5), 203-210 (in Italian).
19. CARSTENS, M.R., and ROLLER, J.E. (1959). Boundary-shear stress in unsteady turbulent pipe flow. *Journal of the Hydraulics Division*, ASCE, 85(HY2), 67-81.
20. SAFWAT, H.H., and VAN DER POLDER, J. (1973). Friction-frequency dependence for oscillatory flows in circular pipes. *Journal of the Hydraulics Division*, ASCE, 99(HYII), 1933-1945.
21. KUROKAWA, J., and MORIKAWA, M. (1986). Accelerated and decelerated flows in a circular pipe. *Bulletin of JSME*, 29(249), 758-765.
22. SHUY, E.B., and APELT, C.J. (1987). Experimental studies of unsteady shear stress in turbulent flow in smooth round pipes. *Conf. on Hydraulics in Civil Engineering*, Melbourne, Australia, 137-141.
23. KOMPARE, B. (1995). *The use of artificial intelligence in ecological modelling*. PhD Thesis, University of Ljubljana, Ljubljana, Slovenia / Royal Danish School of Pharmacy, Copenhagen East, Denmark.
24. BUGHAZEM, M.B., and ANDERSON, A. (1996). Problems with simple models for damping in unsteady flow. *Proc., Int. Conf. on Pressure Surges and Fluid Transients*, BHR Group, Harrogate, England, 537-548.
25. VENNATRO, B. (1996). Unsteady friction in pipelines. *Proc., XVIII IAHR Symposium on Hydraulic Machinery and Cavitation*, Valencia, Spain, Vol. 2, 819-826.
26. SVINGEN, B. (1997). Rayleigh damping as an approximate model for transient hydraulic pipe friction. *Proc., 8th Int. Meet. on the Behaviour of Hydraulic Machinery under Steady Oscillatory Conditions*, IAHR, Chatou, France, Paper F-2.
27. TRIKHA, A.K. (1975). An efficient method for simulating frequency-dependent friction in transient liquid flow. *Journal of Fluids Engineering*, ASME, 97(1), 97-105.
28. ACHARD, I.L., and LESPINARD, G.M. (1981). Structure of the transient wall-law in one-dimensional models of laminar pipe flows, *Journal of Fluid Mechanics*, 113 (December), 283-298.
29. ARL T, H. (1983). Experimentelle Untersuchungen tiber des instationare, turbulente Reibungsverhalten bei aufgeprägten Druckimpulsen in einer Rohrleitung mit Kreisquerschnitt. *Mitteilungsheft Nr.102*, Institut fur Wasserbau und Wasser-wirtschaft, Technische Universitat Berlin, Berlin, Germany (in German).
30. KAGAWA, T., LEE, I., KITAGAWA, A., and TAKENAKA, T. (1983). High speed and accurate computing method of frequency-dependent friction in laminar pipe flow for characteristics method. *Transactions of JSME*, 49(447), 2638-2644 (in Japanese).
31. BROWN, ET. (1984). On weighting functions for the simulation of unsteady turbulent flow. *Forum on Unsteady Flow*, ASME, New Orleans, USA, FED-Vo.15, 26-28.
32. YIGANG, C., and JING-CHAO, S. (1989). An efficient approximate expression for transient flow of high viscous fluid in hydraulic pipelines. *Proc., 6th Int. Conf. on Pressure Surges*, BHRA, Cranfield, England, 349-356.
33. SUZUKI, K., TAKETOMJ, T., and SATO, S. (1991). Improving Zielke's method of simulating frequency-dependent friction in laminar liquid pipe flow. *Journal of Fluids Engineering*, ASME, 113(4), 569-573.
34. SCHOHL, G.A. (1993). Improved approximate method for simulating frequency-dependent friction in transient laminar flow. *Journal of Fluids Engineering*, ASME, 115(3), 420-424.
35. VARDY, A.E. (1992). Approximating unsteady friction at high Reynolds numbers. *Proc., Int. Conf. on Unsteady Flow and Fluid Transients*, Durham, England, 21-29.
36. VARDY, A.E., HWANG, K.L., and BROWN, J.M.B. (1993). A weighting function model of transient turbulent pipe flow. *Journal of Hydraulic Research*, IAHR, 31(4), 533-548.
37. SHUY, E.B. (1995). Approximate wall shear equation for unsteady laminar pipe flows. *Journal of Hydraulic Research*, IAHR, 33(4),457-469.
38. ZARZYCKI, Z. (1997). Hydraulic resistance of unsteady turbulent liquid flow in pipelines. *Proc., 3rd Int. Conf. on Water Pipeline Systems*, BHR Group, The Hague, the Netherlands, 163-178.
39. OHMI, M., KYOMEN, S., and USVI, T. (1985). Numerical analysis of transient turbulent flow in a liquid line. *Bulletin of JSME*, 28(239), 799-806.
40. BRATLAND, O. (1986). Frequency-dependent friction and radial kinetic energy variation in transient pipe flow. *Proc., 5th Int. Conf. on Pressure Surges*, BHRA, Hannover, Germany, 95-101.

41. VARDY, A.E., and HWANG, KL (1991). A characteristics model of transient friction in pipes. *Journal of Hydraulic Research*, IAHR, 29(5), 669-684.
42. EICHINGER, P., and LEIN, G. (1992). The influence of friction on unsteady pipe flow. *Proc., Int. Conf. on Unsteady Flow and Fluid Transients*, Durham, England, 41-50.
43. VENNATRO, B. (1998). Oscillating flow in pipelines. *Proc. XIX IAHR Symposium on Hydraulic Machinery and Cavitation*, Singapore, Vol. 2, 694-702.
44. SILVA-ARAYA, W.E and CHAUDHRY, M.H. (1997). Computation of energy dissipation in transient flow. *Journal of Hydraulic Engineering*, ASCE, 123(2), 108-115.
45. PEZZINGA, G. (1999). Quasi-2D model for unsteady flow in pipe networks. *Journal of Hydraulic Engineering*, ASCE, 125(7), 676-685.
46. WYLIE, E.B., and STREETER, Y.L. (1993). *Fluid transients in systems*. Prentice Hall, Englewood Cliffs, USA.
47. HAALAND, S.E. (1983). Simple and explicit formulas for the friction factor in turbulent pipe flow. *Journal of Fluids Engineering*, ASME, 105(1), 89-90.
48. Fox, J.A. (1989). *Transient flow in pipes, open channels and sewers*. Ellis Horwood Limited, Chichester, England.
49. BERGANT, A. and SIMPSON, A.R. (1995). Water hammer and column separation measurements in an experimental apparatus. *Report n. R128*, Dept. of Civil and Envir. Engrg., University of Adelaide, Adelaide, Australia.
50. COLEMAN, H.W. and STEELE, W.G. (1989). *Experimentation and uncertainty analysis for engineers*. John Wiley and Sons, New York, USA.
51. CHAUDHRY, M.H. (1987). *Applied hydraulic transients*. . Van Nostrand Reinhold Company, New York, USA.