

## Diffusive gradients in thin films: devices, materials and applications

— [Source link](#) 

[Cai Li](#), [Shiming Ding](#), [Liyuan Yang](#), [Yan Wang](#) ...+5 more authors

**Institutions:** [Chinese Academy of Sciences](#), [University of Jinan](#)

**Published on:** 01 Jun 2019 - [Environmental Chemistry Letters](#) (Springer International Publishing)

**Topics:** [Diffusive gradients in thin films](#)

Related papers:

- [In-situ speciation measurements of trace components in natural waters using thin-film gels.](#)
- [Performance Characteristics of Diffusion Gradients in Thin Films for the in Situ Measurement of Trace Metals in Aqueous Solution](#)
- [Progress in understanding the use of diffusive gradients in thin films \(DGT\) – back to basics](#)
- [Simultaneous measurements of cations and anions using diffusive gradients in thin films with a ZrO-Chelex mixed binding layer.](#)
- [A high-resolution dialysis technique for rapid determination of dissolved reactive phosphate and ferrous iron in pore water of sediments](#)

Share this paper:    

View more about this paper here: <https://typeset.io/papers/diffusive-gradients-in-thin-films-devices-materials-and-13smltk8c7>



## Diffusive gradients in thin films: devices, materials and applications

Cai Li, Shiming Ding, Liyuan Yang, Yan Wang, Mingyi Ren, Musong Chen,  
Xianfang Fan, Eric Lichtfouse

### ► To cite this version:

Cai Li, Shiming Ding, Liyuan Yang, Yan Wang, Mingyi Ren, et al.. Diffusive gradients in thin films: devices, materials and applications. *Environmental Chemistry Letters*, Springer Verlag, 2019, 17 (2), pp.801-831. 10.1007/s10311-018-00839-9 . hal-02142638

**HAL Id: hal-02142638**

**<https://hal.archives-ouvertes.fr/hal-02142638>**

Submitted on 28 May 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## REVIEW

## Diffusive gradients in thin films: devices, materials and applications

Cai Li<sup>1,2</sup> · Shiming Ding<sup>2</sup>  · Liyuan Yang<sup>1</sup> · Yan Wang<sup>2,4</sup> · Mingyi Ren<sup>1,2</sup> · Musong Chen<sup>2</sup> · Xianfang Fan<sup>2</sup> · Eric Lichtfouse<sup>3</sup> **Abstract**

A large number of ex situ sampling techniques have been used traditionally to investigate the impact and fate of pollutants in soil, sediment and waters. However, the distribution and form of chemical species present are often altered prior analysis, due to the alterations during sampling and transfer to the laboratory. Alternatively, a robust in situ passive sampling technique, diffusive gradients in thin films (DGT), has been developed for the measurement of labile concentrations, species and distribution of various solutes in soil, sediment and waters. Here we review the recent developments in DGT device configurations and components, e.g., binding agents, diffusive phases and filter membranes. We highlight new configurations for effectively reducing the measurement errors and the disturbance of environmental media. We discuss DGT applications for the analysis of soil, sediment and water, such as evaluation of bioavailability and toxicity, measurement of nutrients and organic substances, and assessment of relationships between multiple solutes. We also present the coupling of DGT with other in situ measurement techniques such as dialysis samplers (Peeper), diffusive equilibrium in thin films (DET) and planar optodes (PO).

**Keywords** Diffusive gradients in thin films (DGT) · Device · Passive sampling technique · Biogeochemical processes

**Abbreviations**

BPs	Bisphenols	PO	Planar optode
BPA	Bisphenol A	CID	Computer imaging densitometry
BPF	Bisphenol F	LA-ICP-MS	Laser ablation inductively coupled plasma mass spectrometry
BPB	Bisphenol B	ICP-MS	Inductively coupled plasma mass spectrometry
DBL	Diffusive boundary layer	ICP-OES	Inductively coupled plasma optical emission spectrophotometry
DGT	Diffusive gradients in thin films	GFAAS	Graphite flame atomic absorption spectroscopy
DIFS	DGT induced fluxes in sediments or soils	Zr-oxide	Zirconium oxide
DET	Diffusive equilibrium in thin films	SPR-IDA	Suspended particulate reagent-iminodiacetate
HR-Peeper	High-resolution Peeper	APA	Agarose cross-linked polyacrylamide
		MBL	Mixed binding layer
		SRP	Soluble reactive phosphorus
		SWI	Sediment–water interface
		DRP	Dissolved reactive phosphorous
		ROL	Radial oxygen loss
		1D, 2D	One-dimensional, two-dimensional
		EDCs	Endocrine disrupting chemicals
		HPCPs	Household and personal care products
		4-CP	4-chlorophenol
		PSS	Poly (4-styrenesulfonate)

✉ Shiming Ding  
smding@niglas.ac.cn

✉ Liyuan Yang  
youngliyuan@126.com

<sup>1</sup> School of Water Conservancy and Environment, University of Jinan, Jinan 250022, China

<sup>2</sup> State Key Laboratory of Lake Science and Environment, Nanjing Institute of Geography and Limnology, Chinese Academy of Sciences, Nanjing 210008, China

<sup>3</sup> CNRS, IRD, INRA, Coll France, CEREGE, Aix Marseille University, 13100 Aix-en-Provence, France

<sup>4</sup> Nanjing EasySensor Environmental Technology Co., Ltd, Nanjing 210018, China

PA	Polyacrylate
PEI	Poly (ethyleneimine)
Py-PEI	Polymer-bound Schiff base
SH-CNP	Thiol-modified carbon nanoparticle
Fe <sub>3</sub> O <sub>4</sub> NPs	Fe <sub>3</sub> O <sub>4</sub> nanoparticle aqueous suspensions
PQAS	Polyquaternary ammonium salt
PVDF	Polyvinylidene fluoride
CN	Cellulose nitrate
PES	Polyethersulfone

## Introduction

With industrial development and urbanization, increasing levels of discharge of environmental pollutants such as heavy metals, nutrients and organics, not only result in severe environmental problems, but also pose a great risk to human health (Henner et al. 1999; Dsikowitzky and Schwarzbauer 2014; Heim and Schwarzbauer 2013; Li et al. 2017). A large number of ex situ active sampling techniques have been used to investigate the impacts and fates of compounds in soils, sediments and water, such as direct sampling, centrifugation and filtration, and displacement (Henner et al. 1997; Gimbert et al. 2005; Wang et al. 2015). However, the distribution and form of the chemical species present are often altered prior to analysis, due to the processes involved in sampling and transfer to the laboratory. Traditional sampling and extraction techniques give access to the total extractable analyte concentrations, which usually include some biologically unavailable fractions of inert organic species and large colloids (Divis et al. 2005). However, full assessment of the potential risk of a target analyte requires analysis of the labile fraction rather than total analyte concentrations (de Paiva Magalhães et al. 2015; Divis et al. 2005; Fernandez-Gomez et al. 2011). It is crucial to understand the complex interaction of biogeochemical processes responsible for speciation and distribution of analytes, as well as the resupply kinetics from solid phase to solution phase in sediments or soils (Wu and Wang 2017).

In situ passive sampling techniques are considered an ideal alternative method to these conventional sampling techniques, with many advantages including low environmental disturbance, having low cost and time requirements, and avoiding the need for active media transport (Chen 2015; Zarrouk et al. 2013). Diffusive gradients in thin films (DGT) is an in situ passive sampling techniques commonly used in environmental chemistry, which has been applied to the detection of elements and compounds in natural environments, including water, sediment and soil. This technique uses a specially designed passive sampler that typically houses a binding layer and diffusive layer. Labile fractions, including free ions, labile complexes which can dissociate and mobile fractions released from solids, diffuse through




Fig. 1 Diffusive gradients in thin-film (DGT) device and mechanisms

diffusive layer and are then rapidly and irreversibly assimilated by the binding layer. Therefore, a diffusive gradient is established within the diffusive layer, between the internal medium and the binding layer interface (Fig. 1) (Ernstberger et al. 2002; Sun et al. 2013). Based on Fick's first law of diffusion, the time-weighted average concentration ( $C_{DGT}$ ) of labile species during the deployment time ( $t$ ) can be obtained using DGT, according to Eq. (1) (Davison and Zhang 1994):

$$C_{DGT} = \frac{M(\Delta g + \delta)}{DA t} \quad (1)$$

where  $\Delta g$  is the diffusion layer thickness;  $\delta$  is the diffusive boundary layer thickness, which calculated based on previously reported methods (Davison and Zhang 2012; Galceran and Puy 2015; Scally et al. 2003);  $A$  is the exposed surface area of the DGT device;  $M$  is the accumulated mass of analyte in the binding gel;  $D$  is the analyte diffusion coefficient in the diffusive layer, determined by diffusion cell or DGT time-series deployment methods (Ding et al. 2016c; Pan et al. 2015; Zhang and Davison 1999).

Furthermore, DGT induced fluxes in sediments or soils (DIFS) modeling was developed to investigate the kinetics resupply of solutes to porewater from soil/sediment solids (Harper et al. 1998, 2000; Sochaczewski et al. 2007). Resupply mechanisms were described and evaluated using the resupply parameter from solid phase to solution phase  $R$  ( $C_{DGT}/C_{SOL}$ ), the distribution coefficient between solid and porewater  $K_d$  ( $C_s/C_{SOL}$ ), the solid phase adsorption rate constant  $k_1$ , the desorption rate constant  $k_{-1}$  and the response time  $T_C$  needed for the perturbed system to reach a 63% equilibrium level. DGT and DIFS therefore pose a significant advantage as compared to traditional measurement methods, as they can reflect the mobility, bioavailability and resupply

kinetics of solutes in environmental media (Gu et al. 2017; Naylor et al. 2006; Xu et al. 2018).

The DGT technique was developed in 1994 by William Davison and Hao Zhang with use for the determination of trace metals in water most common, during the early stages of development (Davison and Zhang 1994; Zhang and Davison 1995). Since then, the DGT technique has been modified and expanded to allow measurement of a significant number of elements and compounds, including multiple metals (Altier et al. 2016; Gao et al. 2009; Gimpel et al. 2003; Yabuki et al. 2014), nutrients (Cai et al. 2017; Menzies et al. 2005), organic chemicals/compounds (Chen et al. 2012a, 2013; Dong et al. 2014), radioactive elements (Drozdak et al. 2015; Leermakers et al. 2009), oxyanions (Stockdale et al. 2008, 2010) and rare earth elements (Yuan et al. 2018). The simultaneous measurement of metals and oxyanions via DGT also provides an opportunity for analysis of the complex relationships between various elements (Mason et al. 2005; Panther et al. 2013; Wang et al. 2017a). Furthermore, the combination of DGT with other techniques has provided novel insight into different aspects of biogeochemical processes at high resolution, such as dialysis samplers (Peeper) (Xu et al. 2012a), diffusive equilibrium in thin films (DET) (Gao et al. 2007; Pradit et al. 2013) and planar optodes (PO) (Hoefler et al. 2017; Lehto et al. 2017). Obtaining a two-dimensional (2D) sub-mm high-resolution distribution of analytes in heterogeneous environments, such as sediments and the rhizosphere, is possible using laser ablation inductively coupled plasma mass spectrometry (LA-ICP-MS) (Stockdale et al. 2010; Warnken et al. 2004b) or computer imaging densitometry (CID) (Ding et al. 2013; Teasdale et al. 1999).

This study provides a comprehensive review of DGT development in recent years, including: device components, improved device configurations, and their application in soils, sediments and water. Moreover, the advantages and challenges of DGT technique are discussed.

## Devices and components of diffusive gradients in thin films

To date, two types of DGT samplers have been reported, solid binding phase devices and liquid binding phase devices, with both types having different holder configurations. Solid binding phase devices consist of four types, including the piston-type and dual-mode devices used for analysis of solutions and dry soils (Luo et al. 2014; Pan et al. 2015), and the traditional and new flat-type probes used for analysis of sediments and flooded soils (Ding et al. 2016b; Wu et al. 2014; Zhang et al. 2002). DGT devices typically contain a binding layer which rapidly and irreversibly accumulates the solute species, a diffusive gel layer which allows

solute species to pass through, a protective filter membrane which prevents adherence of particles to gels, and a front plate with a window which clips to the backing plate and holds all the layers firmly together. Recently, the improvements in traditional DGT device construction, as well as the developments in liquid binding phase device, have significantly expanded the potential applications.

## DGT configuration


### Measurement in solutions and dry soils

The piston-type device incorporates two components: the DGT piston and DGT cap (Fig. 2a). The binding gel, diffusive gel and filter membrane were sequentially laid together on the DGT piston and fixed by the DGT cap (exposure area: 3.14 cm<sup>2</sup>), and the surface of the filter membrane is exposed to waters or soils during measurements. The typical piston-type device can be deployed into soils by hand pressing after the soil is moistened (Luo et al. 2010; Oporto et al. 2008; Santner et al. 2010; Zhang et al. 2004). The density of the soil, different thicknesses of soil layers, and the diffusive characteristics of target analytes may be potentially altered during pressing, which may result in measurement errors (Ding et al. 2016b).

In order to reduce the potential artificial interference for DGT measurement in soils, Ding et al. (2016b) developed the dual-mode DGT device, which has two different forms (Fig. 2b), with installation of the core on the top of the base for the measurement in water, or with the core inserted into the base to form an open cavity for measurements in soil. The deployment setup of dual-mode device differs significantly for soil measurements, as compared with piston-type device. Soil samples filled up to the open cavity with a height of 10 mm (i.e., the thickness of the soil layer is unified to 10 mm) after soils have been moistened, with devices then gently shaken by hand, to ensure complete and homogeneous contact between the DGT exposure surface and soils. The accuracy and variability of dual-mode and piston-type DGT devices were evaluated by determining the amounts of P, As, Cd and Pd with each device. Results indicated that accumulated masses established by both devices were significantly similar with correlation coefficients  $R^2$  of 0.99 or 1.00. In addition, total measurement variability decreased from 5.57% in the piston-type DGT, to 3.37% in dual-mode DGT measurements (reduced by 42%).

### Measurement in sediment and flooded soils


The flat-type probe is composed of a flat base with raised bottom edge for accommodation of the binding gel, diffusive gel and filter membrane, fixed by windowed frame (exposure area: 27 cm<sup>2</sup>) (Fig. 3a), which is vertically deployed in



**Fig. 2** Structure of the piston-type diffusive gradients in thin-film (DGT) device **(a)** and the dual-mode DGT device **(b)**. **a** 1, the cap; 2, the piston and 3 their assembled form in the traditional holder system; **b** 1, the “O-shape” ring; 2, the recessed base of the DGT core in the new holder and 3, the hollow base (open cavity) for accom-

modation of the DGT core; 4 and 6 are the two different assembled forms of the DGT core and the open cavity for measurements in water and soil, respectively; 5 and 7 are sectional drawing of 4 and 6, respectively (Ding et al. 2016b). Reprinted with permission from Ding et al., Copyright (2016b), The Royal Society of Chemistry

**Fig. 3** Structure of the traditional flat-type diffusive gradients in thin-film (DGT) device **(a)** and the new flat-type DGT device **(b)**: 1, the flat base; 2, the flat base and 3, their assembled form for the two types of probes, respectively; 4 is a cutaway view of the bottom of 3 loaded with binding gel, diffusive gel and a filter membrane (Ding et al. 2016b). Reprinted with permission from Ding et al., Copyright (2016b), The Royal Society of Chemistry




sediments or soils. Due to raised bottom edge, the typical flat-type probe can cause larger particles from the top layer of sediments to be transported down the sample profile and deeper layers during the insertion process (Santner et al. 2015). Additionally, the gap formed between the surface of flat-type probe and sediments due to raised bottom edge has been found to induce increased exchange in the overlying water (Ding et al. 2016b).

Furthermore, the flat-type probe for sediment measurements have been improved, with the significant differences being the removal of the raised bottom edge, as well as ensuring the window frame is flat at the front and has a beveled back (Fig. 3b). The performances of new and traditional flat-type DGT were compared for S(II) measurement, combining with ZrO–AgI binding gel and CID technique, The similar S(II) distribution trends were observed with both

devices from the 2D distribution of S(II). However, the new flat-type probe without a raised bottom edge, induces much less disturbance of solid particulates and overlying water from sediment surfaces, reducing transfer into the deeper layers during deployment, as compared to the traditional design. The penetration depths of dissolved sulfide and sulfide-enriched sands in sediments have been reduced to 33% and 20% of those measured using the traditional holder. Because the seepage of oxic overlying water into the sediment has been effectively inhibited using new holder, the distribution of sulfide with low concentration appeared at a much shallower depth (2.5 mm vs. 6 mm). The improved dual-mode DGT and new flat-type DGT devices have been successfully used for the measurement of various solutes in soils and sediments (Lin et al. 2017a; Xu et al. 2017; Zhang et al. 2017a).

### Liquid binding phase device

The liquid binding phase device has mainly been applied to the measurement of solutes in water and soils, with a configuration similar to piston-type devices. As shown in Fig. 4, the typical liquid binding phase device is composed of two parts: the base with a reservoir for the placement of the binding phase solution; and the cap with a 29.5-mm open window which can be clipped onto the base (Liu et al. 2016; Wu et al. 2017). In order to avoid leakage of the liquid binding solution, a silica rubber spacer was fitted onto the base before the dialysis membrane was placed on the top of the spacer. As compared with solid binding phase DGT, liquid binding phase DGT provides excellent contact between the polymer solution and diffusive layer, overcoming fragility and swelling problems associated with solid gel. In addition, liquid binding phase DGT require simpler analytical procedures which directly measure analyte concentrations from polymer solution without complex elution steps (Chen



**Fig. 4** The construction of diffusive gradients in thin-film (DGT) devices for liquid binding phase systems, comprised of a base with reservoir, for the placement of the binding phase solution and a cap with a 29.5-mm open window which can be clipped onto the base (Liu et al. 2016). NP nanoparticles. Reprinted with permission from Liu et al., Copyright (2016), Elsevier. N

et al. 2011; Fan et al. 2009b). However, the measurement using this type of DGT cannot reflect the spatial change of the analyte in environmental medium, due to that the binding agent is mobile in the binding solution.

In summary, the development of DGT configuration, including new solid and liquid binding phase devices, has expanded the application of this technique and reduced the disturbances on environmental media and induced measurement errors.

### Binding agents

A large number of studies have suggested that labile species concentrations measured by different binding phases for same target analyte vary significantly (Ding et al. 2010b; Panther et al. 2011; Zhang et al. 2018a). Moreover, labile species concentrations are dependent on the binding strength and capability of the binding agent, providing possibility of using different DGT devices to determine the speciation and bioavailability of solutes, by choosing various suitable binding agents (Fan et al. 2013; Li et al. 2005a). To date, two different binding phases have been developed, including solid binding phases and liquid binding phases. Tables 1 and 2 summarize various solid binding agents and liquid binding agents, respectively, as well as their target analytes and applied conditions.

#### Single solid binding agents

Single solid binding phases are prepared by impregnating single binding agents (e.g., resin) into polyacrylamide or agarose gels (Guan et al. 2017; Zhang et al. 2004; Zheng et al. 2015). In addition, some ion exchange membranes are directly used as single solid binding phases for measuring metals with DGT (Li et al. 2002, 2006).

Chelex-100 resin is the most widely used solid binding adsorbent and has been applied for the measurement of trace metals in sediments, soils and waters (Divis et al. 2007; Song et al. 2018a; Zhang et al. 1998b). The most notable advantage of Chelex-100 resin is that it can determine a large number of metals, to date, the Chelex-100 is typically used to measure cationic metals with DGT, including Fe, Mn, Cd, Co, Cu, Ni, Pb, Zn and Al (Garmo et al. 2003; Leermakers et al. 2016; Song et al. 2018b; Turner et al. 2012; Wu et al. 2011). Other available materials have also been reported for the determination of metals, such as adsorbent suspended particulate reagent-iminodiacetate (SPR-IDA) and activated carbon (Davison et al. 1997; Lucas et al. 2012, 2014). SPR-IDA and activated carbon DGT can measure fewer analytes than Chelex-100 but activated carbon DGT can be applied for Au and bisphenols (BPs) measurement over a wide range of pH and ionic strength conditions (Guan et al. 2017; Lucas et al. 2012; Warnken et al. 2004a). Both

**Table 1** Binding agents for preparation of solid binding phases in diffusive gradients in thin films (DGT)

Solid binding agents	Target analytes	Analytical techniques	Applied condition	References
Chelex-100	Zn, Cd, Co, Ni, Cu, Al, Pb, Cr, Mn, Fe, As, Hg, U	ICP-MS <sup>b</sup> , ICP-AES <sup>c</sup> LA-ICP-MS	pH: 5.0–8.5; I: 0.01 mM–0.75 M NaNO <sub>3</sub>	Divis et al. (2007), Gao et al. (2009), Leermakers et al. (2016), Song et al. (2018a), Wu et al. (2011)
SPR-IDA <sup>a</sup>	Co, Ni, Cu, Zn, Cd, Pb	LA-ICP-MS <sup>d</sup>	pH: 4.0–8.0	Davison et al. (1997), Gao and Lehto (2012), Warnken et al. (2004a, b)
Activated carbon	Au, As, Sb, bisphenols (BPs)	ICP-MS, HPLC <sup>e</sup>	pH: 2.0–9.5 I: 0.001–0.5 M NaCl	Lucas et al. (2012, 2014), Zheng et al. (2015)
<i>Saccharomyces cerevisiae</i>	Cd, Pb, MeHg	CV-AFS, ICP-OES <sup>f</sup>	pH: 4.5–8.5I: ≥0.005 M NaNO <sub>3</sub>	Menegário et al. (2010), Pescim et al. (2012), Tafurt-Cardona et al. (2015)
Amberlite IRA 910	As, V	HG-AFS <sup>g</sup>	pH: 3–9 I: 0.001–0.05 M NaNO <sub>3</sub>	Rolisola et al. (2014), Luko et al. (2017)
Whatman P81 membrane	Cd, Cu, Pb, Zn, Co, Ni, Mn, Ba, Hg, U species	FAAS <sup>h</sup> , ICP-MS	pH: 4–9	Colaço et al. (2014), de Oliveira et al. (2012), Larner and Seen (2005), Pedrobom et al. (2017)
Whatman DE 81 membrane	Cr, U species	ICP-OES, ICP-MS	pH: 4–9 I: 0.01–0.5 M NaNO <sub>3</sub>	Li et al. (2006), Suárez et al. (2016)
AgI	S	CID <sup>i</sup>		DeVries and Wang (2003), Teasdale et al. (1999), Wid-erlund and Davison (2007)
Ferrihydrite	As, Mo, Sb, V, W, Se, P	ICP-SFMS <sup>j</sup>		Osterlund et al. (2010), Price et al. (2013), Zhang et al. (1998a)
Metsorb	As, V, Sb, Mo, W, Se, P, U, Glyphosate and Aminomethyl Phosphonic Acid	ICP-MS	pH: 4.0–8.3; I: 10 <sup>-3</sup> –0.7 M NaNO <sub>3</sub>	Bennett et al. (2010), Drozdak et al. (2015), Fau-velle et al. (2015), Panther et al. (2010, 2013), Price et al. (2013)
Zr-oxide	P, As, Cr, Mo, Sb, Se, V, W	ICP-MS, CID	pH: 3–10 I: 0.01–750 mM NaNO <sub>3</sub>	Ding et al. (2010b, 2011, 2016c), Guan et al. (2015), Sun et al. (2014)
MnO <sub>2</sub>	Ra	ICP-MS		Gao et al. (2010), Leermakers et al. (2016)
Spheron-Thiol	Hg	HPLC–ICP-MS <sup>k</sup>		Cattani et al. (2008), Doceka-lova and Divis (2005), Fernandez-Gomez et al. (2011)
Tulsion® CH-95	Hg, MeHg	CVA-FS <sup>l</sup>	pH: 4.10–10.03/4.10–8.10 I: 0.1 mM–1 M NaCl	Ren et al. (2018a)
3-mercaptopropyl function-alized silica gel	MeHg, MMHg	GC-ICP-MS <sup>m</sup> GC-Py-AFS <sup>n</sup>		Clarisse et al. (2009, 2012), Fernandez-Gomez et al. (2014), Liu et al. (2012)
Chelex–Metsorb	Mn, Co, Zn, Ni, Cu, Cd, Pb, V, As, Mo, Sb, W, P	ICP-MS	pH: 5.03–8.05 I: 0.001–0.7 M	Arsic et al. (2018), Panther et al. (2014)
Chelex–Ferrihydrite	Zn, Pb, Cd, Cu, Mn, Mo, P, As	ICP-MS	pH: 3–8 I: 0.001–0.01 M NaCl	Huynh et al. (2012), Mason et al. (2005)
AgI–Ferrihydrite	P, V, As, Mo, Sb, W and U	LA-ICP-MS		Stockdale et al. (2010)
ZrO–AgI	P, S, As	CID, HG-AFS <sup>o</sup>	pH: 4–9; I: 0.01–750 mM NaCl	Ding et al. (2012), Xu et al. (2017)
ZrO–SPR-IDA	P, As, Co, Cu, Mn, and Zn	LA-ICP-MS	pH 4–8 I: 1–100 mM NaNO <sub>3</sub>	Kreuzeder et al. (2013)



**Table 1** (continued)

Solid binding agents	Target analytes	Analytical techniques	Applied condition	References
ZrO–Chelex	Fe, Mn, Co, Ni, Cu, Zn, Pb, Cd, P, As, Cr, Mo, Sb, Se, V, W	CID, ICP-MS	pH: 5–9 I: 1–750 or 2/3–750 mM NaNO <sub>3</sub>	Ding et al. (2016a), Wang et al. (2016, 2017a)
Micro-sized zeolite	NH <sub>4</sub> <sup>+</sup> –N	ICP-AES	pH: 3–8 I: 0.001–10 mM NaNO <sub>3</sub>	Feng et al. (2015)
Microlite PrCH cation exchange resin	NH <sub>4</sub> <sup>+</sup> –N	Automated colorimetric method	pH: 3.5–8.5 I: ~0.012 M NaCl	Huang et al. (2016c)
Purolite A520E anion exchange resin	NO <sub>3</sub> –N	Automated colorimetric method	pH: 3.5–8.5 I: 0.0001–0.008 M NaCl	Huang et al. (2016a)
AMI-7001 anion exchange membrane	NO <sub>3</sub> –N	Automated colorimetric methods	pH: 3.5–8.5 I: 0.0001–0.014 M NaCl	Huang et al. (2016d)
CMI-7000 cation exchange membranes	NH <sub>4</sub> <sup>+</sup> –N	Automated colorimetric methods	pH: 3.5–8.5 I: 0.0003–0.012 M NaCl	Huang et al. (2016d)
SIR-100-HP	NO <sub>3</sub> –N	Flow injection analysis	pH: 3–8 I: 0–0.018 M Na <sub>2</sub> SO <sub>4</sub>	Cai et al. (2017)
XAD-18 resin	Antibiotics/drugs/perfluoroalkyl substances (PFASs)/endocrine disrupting chemicals	HPLC–UV <sup>p</sup> RRLC–MS/MS <sup>q</sup>	pH: 6–9/4–9 I: 0.001–0.1 M NaCl	Chen et al. (2012a, 2013, 2018c), Guan et al. (2018), Guo et al. (2017a)
XDA-1 resin	Antibiotics/endocrine disrupting chemicals (EDCs)	UPLC-MS/MS <sup>f</sup>	pH: 7–9 I: 0.5/0.4–0.8 M NaCl	Xie et al. (2018a, b)
Oasis <sup>®</sup> HLB or Oasis <sup>®</sup> MAX	Anionic pesticides/endocrine disrupting chemicals/polar organic contaminants	HPLC-TOF <sup>g</sup>	pH: 3–8 I: 0.01–1 M NaNO <sub>3</sub>	Challis et al. (2016), Chen et al. (2018c), Guibal et al. (2017)
Bondesil <sup>®</sup> C <sub>8</sub> silica particles	Organotin compounds	PTV-LVI-GC/MS <sup>l</sup>	pH: 4–9 I: 0.01–1 M, NaCl	Cole et al. (2018)
Hydrophilic–lipophilic-balanced	Household and personal care products (HPCPs)	LC-MS/MS <sup>u</sup>	pH: 3.5–9.5 I: 0.001–0.1 M NaCl	Chen et al. (2017b)

<sup>a</sup>Suspended particulate reagent-iminodiacetate (SPR-IDA)<sup>b</sup>Inductively coupled plasma mass spectrometry (ICP-MS)<sup>c</sup>Inductively coupled plasma atomic emission spectrometry (ICP-AES)<sup>d</sup>Laser ablation inductively coupled plasma mass spectrometry (LA-ICP-MS)<sup>e</sup>High-performance liquid chromatography (HPLC)<sup>f</sup>Inductively coupled plasma optical emission spectroscopy (ICP-OES)<sup>g</sup>Hydride generation-atomic fluorescence spectrometry (HG-AFS)<sup>h</sup>Flame atomic absorption spectrometry (FAAS)<sup>i</sup>Computer imaging densitometry (CID)<sup>j</sup>Inductively coupled plasma sector-field mass spectrometry (ICP-SFMS)<sup>k</sup>High-performance liquid chromatography inductively coupled plasma mass spectrometry (HPLC–ICP-MS)<sup>l</sup>Cold vapor atomic fluorescence spectrometry (CVA-FS)<sup>m</sup>Gas chromatography coupled inductively coupled plasma mass spectrometry (GC-ICP-MS)<sup>n</sup>Gas chromatography coupled to atomic fluorescence spectrometry via a pyrolytic reactor (GC-Py-AFS)<sup>o</sup>Hydride generation coupled with AFS (HG-AFS)<sup>p</sup>High-performance liquid chromatography ultraviolet (HPLC–UV)<sup>q</sup>Rapid resolution liquid chromatography-tandem mass spectrometry (RRLC–MS/MS)<sup>r</sup>Ultra-performance liquid chromatography-tandem mass spectrometry (UPLC-MS/MS)<sup>s</sup>High-performance liquid chromatography time-of-flight (HPLC-TOF)<sup>t</sup>Pressure temperature vaporization-large volume injection gas chromatography-mass spectrometry (PTV-LVI-GC/MS)<sup>u</sup>Liquid chromatography-tandem mass spectrometry (LC-MS/MS)

**Table 2** Binding agents used for preparation of the liquid binding phase in diffusive gradients in thin films (DGT)

Liquid binding phase	Target analyte	Analytical techniques	Applied condition	References
Poly(4-styrenesulfonate)	Cu, Cd, Co, Ni	FAAS <sup>a</sup> ICP-MS <sup>b</sup>	pH: 4–8 Not suitable for high ionic strength	Chen et al. (2012b), Li et al. (2003, 2005b)
Polyvinyl alcohol	Cu	FAAS	pH: 5.6–8.6 I: 10 <sup>-4</sup> –0.7 M NaNO <sub>3</sub>	Fan et al. (2009a)
Polyacrylate	Cu, Cd	FAAS	pH: 4–8 Not suitable for high ionic strength	Fan et al. (2009b)
Polymer-bound Schiff base	Cu, Cd, Pb	FAAS	pH: 4–8.5 I: 10 <sup>-4</sup> –0.1 M NaNO <sub>3</sub>	Fan et al. (2013)
Poly (ethyleneimine)	Cu, Cd Pb	FAAS	pH: 4–8 I: 10 <sup>-4</sup> –0.1 M NaNO <sub>3</sub>	Sui et al. (2013)
Thiol-modified carbon nanoparticle (SH-CNP)	Hg	ICP-MS	pH: neutral value I: 0.001–0.5 M NaNO <sub>3</sub>	Wu et al. (2017)
Fe <sub>3</sub> O <sub>4</sub> NPs	As/P	ICP-MS ICP-OES <sup>c</sup>	pH: 4.5–9/3–10 I: 0.001–0.5 M NaNO <sub>3</sub>	Liu et al. (2016), Zhang et al. (2018a)
Polyquaternary ammonium salt (PQAS)	P	AMS <sup>d</sup>	pH: 3–10 I: 10 <sup>-4</sup> –1 M NaNO <sub>3</sub>	Chen et al. (2014b)
Zr-based metal–organic frameworks	P		pH: 6.5–8.5 I: 10 <sup>-5</sup> –0.1 M NaNO <sub>3</sub>	Qin et al. (2018)

<sup>a</sup>Flame atomic absorption spectroscopy (FAAS)

<sup>b</sup>Inductively coupled plasma mass spectrometry (ICP-MS)

<sup>c</sup>Inductively coupled plasma optical emission spectrophotometry (ICP-OES)

<sup>d</sup>Ammonium molybdate spectrophotometry (AMS)

SPR-IDA (bead size 0.2 µm) and ground Chelex-100 resin (bead size ~ 10 µm) allow obtaining high-resolution imaging of trace metals in sediments and soils in combination with the analysis of LA-ICP-MS (Zhou et al. 2018). Taking the expensive prices and limited binding capacity of SPR-IDA into consideration, the ground Chelex-100 resin can become a promising binding material for high-resolution 2D imaging analysis. Menegário et al. (2010) fixed baker's yeast (*Saccharomyces cerevisiae*) in agarose gel to form a DGT binding phase, and the labile Cd(II) measured by this type of DGT showed excellent agreements with that of Chelex DGT. This type of DGT has been developed for measuring Pb and MeHg in seawaters and freshwaters (Pescim et al. 2012; Tafurt-Cardona et al. 2015). Rolisola et al. (2014) and Luko et al. (2017) immobilized Amberlite IRA 910 into polyacrylamide gel to form a DGT binding phase capable of measuring As(III) and V, and the DGT performance was independent of pH 5–9 and pH 3–9 for the two analytes, respectively.

In addition, several binding materials have been developed for the measurement of Hg species. Spheron-Thiol resins were developed to determine Hg(II) and MeHg, showing a stronger affinity for mercury species than Chelex-100 (Docekalova and Divis 2005; Fernandez-Gomez et al. 2011). Three-mercaptopropyl functionalized silica (Clarisse et al. 2012; Fernandez-Gomez et al. 2015), the ion exchange

resin Duolite GT73 and Ambersep GT74 as well as the novel functionalized macroporous cross-linked polystyrene (Tulsion® CH-95) can measure several mercury species (Pelcova et al. 2014, 2015; Ren et al. 2018a). Further, we found the Tulsion® CH-95 binding agent has higher adsorption capacity and elution efficiency for Hg(II) and MeHg than other adsorbents (Ren et al. 2018a).

The use of ion exchange membranes as DGT binding phases has advantages of excellent mechanical strength, flexibility, reuse and easy preparation, in comparison with other types of binding phases (Huang et al. 2016d; Li et al. 2002, 2005a). Li et al. (2002) utilized commercially available solid cellulose phosphate membranes (Whatman P81) as DGT binding phase to determine Cu and Cd, and this type of DGT has been extended to measurement of other metals, such as Cd, Cu, Pb, Zn, Co, Ni, Mn, Ba, Hg and U species (Colaço et al. 2014; de Oliveira et al. 2012; Larner and Seen 2005; Mengistu et al. 2012; Pedrobom et al. 2017). In addition, the Whatman DE 81 with amino functional groups has been applied for the measurement of U species and Cr(VI) in waters (Li et al. 2006; Pedrobom et al. 2017; Suárez et al. 2016).

Titanium dioxide-based adsorbent (Metsorb), iron oxyhydroxide-based adsorbents (Ferrihydrite) and zirconium oxide (Zr-oxide)-based adsorbents have been employed to measure anionic analytes. Metsorb DGT, Ferrihydrite DGT and

Zr-oxide DGT can measure similar anionic analytes including As, Mo, Sb, V, W, Se, P in a similar range of pH (Ding et al. 2016c; Osterlund et al. 2010; Panther et al. 2010, 2013; Zhang et al. 2017a, b). Compared with Ferrihydrite, the capacity of Metsorb DGT was higher, with superior results found when deployment times were greater than 1 day or in seawater deployment. Both Metsorb and Ferrihydrite DGTs were found to be independent of  $\text{Cl}^-$  and  $\text{SO}_4^-$  for the measurement of dissolved reactive phosphorous (DRP) in water, whereas Ferrihydrite DGT was more susceptible to the effects of  $\text{HCO}_3^-$  (Mason et al. 2008; Panther et al. 2011). A high phosphate binding capacity was observed for Zr-oxide DGT, up to  $223 \mu\text{g P cm}^{-2}$ , which was significantly higher than Ferrihydrite DGT ( $6.94 \mu\text{g P cm}^{-2}$ ), Metsorb DGT ( $12.7 \mu\text{g P cm}^{-2}$ ) (Ding et al. 2010b). The capacities of Zr-oxide DGT for oxyanions are  $\sim 29$  to  $> 2397$ -fold that of Metsorb and approximately 7.5 to 232-fold that of Ferrihydrite DGT in freshwater and seawater, respectively (Ding et al. 2016c). Teasdale et al. (1999) initially developed a new DGT method for 2D measurement of S(II), based on the use of AgI as DGT binding phase. S(II) reacts specifically with the pale yellow AgI to form black  $\text{Ag}_2\text{S}$  substance. Therefore, the accumulation amount of S(II) can be quantitatively related to the grayscale intensity of the gel surface measured by the computer imaging density (CID) (Robertson et al. 2008; Teasdale et al. 1999).

Recently, DGT methods have been widely developed to measure the inorganic nutrient P (Ding et al. 2010b; Price et al. 2013; Zhang et al. 1998a), while there were relatively few reports about N. Feng et al. (2015) determined  $\text{NH}_4\text{-N}$  concentrations using DGT, based on the use of a novel binding material containing micro-sized zeolite in natural waters, effective between pH 3–8 and 0.001–10 mM ionic strengths. Huang et al. (2016a, c) used Purolite A520E anion exchange resin and Microlite PrCH cation exchange resin and as DGT binding agents for measurement of  $\text{NO}_3\text{-N}$  and  $\text{NH}_4\text{-N}$  in freshwaters, respectively, with neither A520E DGT or PrCH DGT affected in the pH range of 3.5–8.5. Huang et al. (2016d) also used AMI-7001 and CMI-7000 cation exchange membranes as binding layers for DGT measurements of  $\text{NO}_3\text{-N}$  and  $\text{NH}_4\text{-N}$  in freshwaters, respectively. They have the advantages of easy preparation, low detection limits and the use of non-toxic chemicals (i.e., acrylamide) in comparison with the uses of A520E and PrCH, enable the two DGTs more promising for measurement of N. Moreover, a novel styrene divinylbenzene-based adsorbent with amine functional groups (SIR-100-HP) has been developed for the measurement of  $\text{NO}_3\text{-N}$  in soils, with performance found to be effective at a pH range of 3–8 and ionic strengths of 0–0.018 M (Cai et al. 2017).

The binding agents used for the measurement of metals, oxyanions and nutrients have been considerably developed, while there is a tendency for the development of DGT in

measurement of organic compounds. XAD-18 resin is to date, the most commonly used adsorbent for measuring antibiotics and it has been developed to simultaneously several drugs and perfluoroalkyl substances (PFASs) in water and soil (Chen et al. 2014a, 2015a; Guan et al. 2018; Guo et al. 2017a). Some studies have proven that XAD-18 DGT is effective in situ tools to monitor multiple antibiotics and illicit drugs in the wide range of pH 4–9, with ionic strengths of 0.001–0.1 M NaCl (Chen et al. 2015b; Zhang et al. 2018b). In addition, Xie et al. (2018a, b) used the novel XAD-1 resin as a binding phase for the determination of antibiotics and endocrine disrupting chemicals (EDCs) in seawater. Compared with XAD-18 resin, the XAD-1 resin was suitable for application in high ionic strength environments (0.4–0.8 M), such as seawater. Activated charcoal DGT has also been employed for the simultaneous determination of bisphenols in water and soil, with performance not affected by pH within the range of 5–8, or ionic strengths between 0.001 and 0.5 M (Guan et al. 2017; Zheng et al. 2015). Ren et al. (2018b) developed a novel binding phase using porous carbon material (PCM) as binding agent for measuring 20 antibiotics in water samples, and its measurement was independent of pH 4.2–8.4 and ionic strength 0.001–0.5 M NaCl. Guibal et al. (2017) utilized both Oasis<sup>®</sup> HLB and Oasis<sup>®</sup> MAX sorbent in DGT devices, to monitor anionic pesticides in rivers, with accuracies better than 30% found under the conditions of pH 3–8 and ionic strength 0.01–1 M  $\text{NaNO}_3$ . The application of hydrophilic–lipophilic-balanced (HLB) binding agents has been reported for the measurement of household and personal care products (HPCPs) in waters, being effective in the pH range of 3.5–9.5, and ionic strengths of 0.001–0.1 M, with dissolved organic matter levels of 0–20  $\text{mg L}^{-1}$  (Chen et al. 2017b). Chen et al. (2018c) further compared the performances of three different resins [HLB, XAD18 and Strata-XL-A (SXLA)] for measuring endocrine disrupting chemicals, showing that the measurements with HLB and XAD18 DGT were more stable than that of SXLA-DGT, with the tolerant pH range of 3.5–9.5 and ionic strength of 0.001–0.5 M. The use of DGT for measurement of organometallics have been optimized, with Cole et al. (2018) using Bondesil<sup>®</sup> C<sub>8</sub> silica particles as DGT sorbents for measurement of five organotin compounds in sediment, with performances effective within a range of pH 4–9 and ionic strength of 0.01–1 M NaCl.

### Hybrid solid binding agents

Both direct and indirect interactions occur between different analyte species in biogeochemical processes. Consequently, in order to further understand potential coupled relationships, the hybrid DGT incorporating different adsorbents in a single gel has been developed. The concentrations of Zn, Pb, Cd, Cu, Mn, Mo, P and As in water and soil, were

determined using mixed binding layer (MBL) DGT, consisting of Ferrihydrite and Chelex-100 (Ferrihydrite–Chelex DGT) (Huynh et al. 2012; Mason et al. 2005). The added Chelex-100 does not interfere with the absorption capacity of Ferrihydrite for As and P, although the coating of Ferrihydrite on to the surface of Chelex-100 can affect the capacity of Chelex-100 to absorb trace metals. In particular, Ferrihydrite–Chelex DGT cannot be used to measure Fe. The simultaneous measurement of six labile cations (Mn, Co, Ni, Cu, Cd, and Pb) and six oxyanions (V, As, Mo, Sb, W, and P) was performed using Metsorb–Chelex DGT both in freshwater and seawater (Arsic et al. 2018; Panther et al. 2014). Both the diffusion coefficients and the measurement concentrations of cations and oxyanions agreed well with Metsorb–Chelex DGT, compared with Metsorb DGT and Chelex DGT, respectively. Both the number of analyte species measured and the accuracy were higher with Metsorb–Chelex DGT than Ferrihydrite–Chelex DGT.

In addition, AgI–Ferrihydrite DGT (for simultaneous measurement of S and oxyanion), and ZrO–AgI (for As, S and P measurement) have been developed in combination with some high-resolution analyte techniques, such as computer imaging densitometry (CID) (Ding et al. 2012; Stockdale et al. 2008, 2010; Xu et al. 2017). ZrO–SPR-IDA DGT was developed for 2D imaging of P, As, Co, Cu, Mn, and Zn distributions in combination with LA-ICP-MS, by embedding Zr-oxide and SPR-IDA into an ether-based urethane polymer hydrogel (Kreuzeder et al. 2013). Furthermore, Wang et al. (2016, 2017a) obtained the concentrations and distributions for eight cations (Fe, Mn, Co, Ni, Cu, Zn, Pb, and Cd) and eight anions (P, As, Cr, Mo, Sb, Se, V, and W) in water and sediments, using ZrO–Chelex DGT. ZrO–Chelex DGT was shown to have high capacities for all analytes, and although the capacity for As was lower than Zr-oxide DGT, it still exhibits significantly better responses than other reported DGT (Sun et al. 2014).

The main disadvantage of MBL DGT is the limited binding capacity, due to having a single layer of mixed gel and therefore reduced amounts of adsorbents, as well as the mutual interference between different adsorbents (Huynh et al. 2012). It is to note, that adding increased concentration of binding agents into mixed gels were demonstrated to be useful for elevating the binding capacity of MBL DGT (Wang et al. 2017a).

### Liquid binding agents

Liquid binding phases are typically polymer solutions containing functional groups, with recent applications including homogeneous suspension solutions with nano-particulates, the homogeneous liquid binding phase with nano-particulates offers the advantages of a large surface area, rich in functional group, with high mobility (Liu et al. 2016).

The use of poly (4-styrenesulfonate) (PSS) and sodium polyacrylate (PA) as the liquid binding phase for DGT, have been developed for the measurement of Cu and Cd (Fan et al. 2009b; Li et al. 2003), but PSS DGT is not suitable for long-term deployment under high ionic strength condition (Li et al. 2003, 2005b). Several metals (Cu, Cd, Co and Ni) have also been measured simultaneously using PSS-E6 and PSS-7E4 DGTs (Chen et al. 2012b), respectively. The results showed that the use of large molecular weight PSS-E6 was more suitable than PSS-7E4 due to lower pretreatment depletion rate, and lower cost and pollution. In addition, polymer-bound Schiff base (Py-PEI) and poly (ethyleneimine) (PEI) were employed as DGT liquid binding agents for the measurement of labile Cu, Cd and Pb (Fan et al. 2013; Sui et al. 2013). Py-PEI DGT has higher uptake percentages for metals than PA DGT and PSS DGT. Labile Hg species were determined using thiol-modified carbon nanoparticle (SH-CNP) suspensions as the DGT liquid binding agent, with performance effective in ionic strength of independence of 0.001–0.5 M NaNO<sub>3</sub>, as well as other interfering ionic Cd, Cr, Cu and Pb (Wu et al. 2017). In addition, Fe<sub>3</sub>O<sub>4</sub> nanoparticle aqueous suspensions (Fe<sub>3</sub>O<sub>4</sub>NPs) have been applied as liquid binding phases in DGT measurement of DRP concentrations and As species (Liu et al. 2016; Zhang et al. 2018a). Furthermore, polyquaternary ammonium salt (PQAS) aqueous solutions have also been applied as the liquid binding phase in DGT systems, to monitor the concentration of DRP in water, with effective performance within pH range of 3–10 and at ionic strengths of 10<sup>-4</sup>–1 M (Chen et al. 2014b). Qin et al. (2018) used Zr-based metal–organic frameworks (MOFs, UiO-66) as liquid binding agent for DGT measurement of P (UiO-66 DGT), and good agreements were obtained between the concentrations measured by DGT and in waters ( $C_{DGT}/C_{sol}$ : 0.9–1.1). The capacities of different DGTs in measurement of P are in the order of Zr-oxide DGT (223 µg P cm<sup>-2</sup>) > UiO-66 DGT (20.8 µg P cm<sup>-2</sup>) > Fe<sub>3</sub>O<sub>4</sub>NPs DGT (15.4 µg P cm<sup>-2</sup>) > Metsorb DGT (12.7 µg P cm<sup>-2</sup>) > PQAS DGT (9.9 µg P cm<sup>-2</sup>) > Ferrihydrite DGT (6.94 µg P cm<sup>-2</sup>) (Qin et al. 2018; Zhang et al. 2018a).

In summary, a large number of binding agents have been developed, and their uses have made DGT to be a commonly used sampling technique for measurement of a wide range of analytes.

### Diffusive phase

A series of materials have been applied as the diffusive gel in DGT (Table 3), including agarose cross-linked polyacrylamide (APA) gel (Shiva et al. 2017; Zhang and Davison 1995), agarose gel (Colaço et al. 2012; Docekalova and Divis 2005; Wang et al. 2016), dialysis membranes (Li et al. 2003), nylon membranes (Panther et al. 2008) and

**Table 3** Types and characteristics of diffusive gels used in diffusive gradients in thin films (DGT)

Diffusive gel	Pore size	Thickness	Moisture content	Analytes	References
APA gel	> 5 nm	Typically 0.8 mm	> 95%	Oxyanions (including PO <sub>4</sub> <sup>3-</sup> ), trace metals except of Hg and NH <sub>4</sub> <sup>+</sup> , and organic pollutants	Chen et al. (2011), Wang et al. (2016), Zhang and Davison (1999)
Agarose gel	> 20 nm	Typically 0.8 mm	> 99%	Various cations and anions, organic pollutants, Hg, NH <sub>4</sub> <sup>+</sup> , and the analytes capable and incapable of measurements with the APA gel	Divis et al. (2005), Wang et al. (2016)
Dialysis membrane	< 5 nm	50–85 μm	–	Cu, Cd, Co, Ni and As	Chen et al. (2012b), Li et al. (2003, 2005b)
Nylon membrane	0.22 μm	0.18 mm	–	4-chlorophenol (4-CP)	Dong et al. (2014)
3MM chromatography paper		0.46 mm		Various cations	de Almeida et al. (2012), de Oliveira et al. (2012)

**Table 4** Some reported diffusion coefficients for Hg species, NH<sub>4</sub>-N and some organic species in agarose gel ( $D \pm$  standard deviations;  $\times 10^{-6}$  cm<sup>2</sup> s<sup>-1</sup>, 25 °C)

Element	$D$	References
Hg	9.07 ± 0.23/7.65 ± 0.60	Pelcova et al. (2014), Ren et al. (2018a)
MeHg	9.06 ± 0.30/9.94 ± 0.49	Pelcova et al. (2014), Ren et al. (2018a)
NH <sub>4</sub> -N	15.2/17.1	Feng et al. (2015), Huang et al. (2016c)
BPA/BPB/BPF	5.03/2.64/4.44	Zheng et al. (2015)
HPCPs	3.36–7.30	Chen et al. (2017b)
Anionic pesticides	2.7–4.6 (22 °C)	Guibal et al. (2017)
17β-estradiol (E2)	4.65 ± 0.37	Guo et al. (2017b)
Methcathinone/ephedrine	7.60/6.62	Zhang et al. (2018b)
Ketamine/methamphetamine/amphetamine	8.13 ± 0.12/8.55 ± 0.14/7.72 ± 0.18 (22 °C)	Guo et al. (2017a)

paper-based diffusion layer, such as 3MM chromatographic paper (de Almeida et al. 2012; de Oliveira et al. 2012) as well as chromatography paper grade 1 Chr and 17 Chr (Larner and Seen 2005).

APA gel is the most widely used diffusive layer and has been employed for the measurement of various cations and anions, with advantage of retaining stability in the range of pH 2–9 after hydrogel (Osterlund et al. 2010; Wu et al. 2014). Nevertheless, some studies have shown that the interactions between APA gel functional groups and target analytes, can result in inaccurate measurements, such as with Hg (Divis et al. 2005; Pelcova et al. 2015; Tafurt-Cardona et al. 2015), Cu (Garmo et al. 2008b), NH<sub>4</sub><sup>+</sup> (Huang et al. 2016c), and some organics (Guan et al. 2017). APA gel possesses positive charge, therefore electrostatic interactions can interfere with metal diffusion at low ionic strengths according to the Donnan potential (Warnken et al. 2005). In addition, APA gel has relatively poor mechanical resistance, poor reproducibility and sophisticated preparation processes (Fan et al. 2013). An alternative diffusive material agarose gel, had been applied for the measurement of almost all DGT

analytes, such as various cations, anions, organic pollutants, Hg and NH<sub>4</sub><sup>+</sup>, as well as many analytes which cannot be measured with APA gel (Chen et al. 2012a; Divis et al. 2005; Huang et al. 2016d; Tafurt-Cardona et al. 2015; Wang et al. 2016); and Table 4 summarizes some reported diffusion coefficients of these species in agarose gel. The main binding sites on agarose gel are negative charges, which have attractive and repulsive interactions with cations and anions, respectively. Compared with the APA gel, the agarose gel (typically containing 1.5% agarose) is more stable in gel thickness, showing no swelling on hydration (APA gel showed 3.2-fold swelling) (> 99%) (Wang et al. 2016). It was also found that the thickness of agarose gel remained stable after hydration and storage under 4–40 °C, 0–1.0 M ionic strength, and 2–11 pH conditions, with the storage time extending to 300 days.

The reported diffusion coefficients for cations and anions in APA gel and agarose gel determined by diffusion cells ( $D_{\text{cell}}$ ) and DGT time-series deployment methods ( $D_{\text{DGT}}$ ), respectively, are presented in Table 5. The results indicated a considerable variation of the diffusion coefficients in APA

**Table 5** Diffusion coefficients for some elements in agarose cross-linked polyacrylamide (APA) gel and agarose gel (1.5%) determined using diffusion cells  $D_{\text{cell}}$  and diffusive gradients in thin-film (DGT) time-series deployment methods  $D_{\text{DGT}}$ , respectively ( $D \pm$  standard deviations;  $\times 10^{-6} \text{ cm}^2 \text{ s}^{-1}$ , 25 °C)

Analyte	Agarose cross-linked polyacrylamide gel											Agarose gel	
	$D_{\text{cell}}^{\text{a}}$	$D_{\text{cell}}^{\text{b}}$	$D_{\text{cell}}^{\text{c}}$	$D_{\text{cell}}^{\text{d}}$	$D_{\text{DGT}}^{\text{e}}$	$D_{\text{DGT}}^{\text{f}}$	$D_{\text{DGT}}^{\text{g}}$	$D_{\text{DGT}}^{\text{h}}$	$D_{\text{DGT}}^{\text{i}}$	$D_{\text{DGT}}^{\text{j}}$	$D^{\text{k}}$	RSD <sup>l</sup> (%)	$D^{\text{m}}$
As	5.26	5.36	5.54	5.21	6.02	8.13	5.96		6.78	5.54	6.09	<b>14.9</b>	6.38
Mo	5.18	5.58	6.28	5.96	6.33	6.43	7.24		6.81	5.70	5.94	9.9	6.53
Sb	4.90	5.50	6.04	5.55	6.22	6.16	6.74		6.86	5.25	6.23	<b>10.7</b>	6.59
V	3.75	3.88	7.14	6.72	7.98	8.13	8.92		8.02	6.69	5.85	<b>26.3</b>	5.91
W	6.22	4.28	6.89	5.45	6.88	7.06	6.50		6.26	5.82	5.77	<b>13.7</b>	6.54
Cd	5.52	5.36			5.56	5.72	5.56	5.50			8.03	<b>16.1</b>	8.41
Co	5.17	5.03			5.29	5.38	5.88	5.80			6.08	7.2	6.89
Cu	5.75	5.27			5.61	5.47	5.34	5.50			5.50	2.9	6.56
Mn	4.88	4.95			4.68	4.44	5.11	6.40			6.00	<b>13.8</b>	6.90
Ni	5.21	5.13			5.13	5.29	5.65	6.00			5.50	6.0	6.69
Pb	7.75	6.80			8.03	8.17	7.70	9.40			6.70	<b>11.7</b>	8.64
Zn	5.47	5.39			6.22	6.37	5.78	4.60			5.50	<b>10.5</b>	7.47

<sup>a</sup>Conditions: 0.01 M NaNO<sub>3</sub>, pH 4.01 (Panther et al. 2014)

<sup>b</sup>0.01 M NaNO<sub>3</sub>, pH 4.00 (Shiva et al. 2015)

<sup>c</sup>0.01 M NaNO<sub>3</sub>, pH 7.1 (Panther et al. 2013)

<sup>d</sup>0.01 M NaNO<sub>3</sub>, pH 6.4 (Osterlund et al. 2010)

<sup>e</sup>0.01 M NaNO<sub>3</sub>/0.004 M Mg(NO<sub>3</sub>)<sub>2</sub>, pH 6.06, using Chelex–Metsorb DGT (Panther et al. 2014)

<sup>f</sup>0.01 M NaNO<sub>3</sub>/0.004 M Mg(NO<sub>3</sub>)<sub>2</sub>, pH 6.06, using Chelex DGT for anions and Metsorb DGT for cations

<sup>g</sup>0.01 M NaNO<sub>3</sub>/0.004 M Mg(NO<sub>3</sub>)<sub>2</sub>, pH 4.01, using Chelex–Metsorb DGT (Shiva et al. 2015)

<sup>h</sup>pH=5.90, using Chelex DGT (Garmo et al. 2003)

<sup>i</sup>0.01 M NaNO<sub>3</sub>, pH 7.1; using Metsorb DGT (Panther et al. 2013)

<sup>j</sup>0.01 M NaNO<sub>3</sub>, pH 6.2, using ferrihydrite DGT (Osterlund et al. 2010)

<sup>k</sup>Obtained from DGT Research Ltd.

<sup>l</sup>Relative standard error (RSD%) of the diffusion coefficients in APA gel using the data of a–k, with the error > 10% marked in bold

<sup>m</sup>The analyte diffusion coefficients in agarose gel 0.01 M NaNO<sub>3</sub>, pH 5.50 for cations, Ph 6 for anions, using ZrO–Chelex DGT, obtained from EasySensor Ltd.

gel for the same analytes, even that the detection was performed in similar measurement conditions, using the same methods or by the same persons. Except for Cu, the errors (RSD%) of all other elements exceed 5%, and the errors of 8 elements even exceed 10%. These different reports have caused confusion to the users in calculation of DGT concentration and the difficulty in comparing the measuring results in different studies. The errors should be caused by differences in raw materials and production batches in preparation of the diffusion gel and binding gel. The diffusion coefficients measured by diffusion cells and DGT time-series deployment methods are also different, and the  $D_{\text{DGT}}$  are slightly higher than  $D_{\text{cell}}$  (Table 5). The reason is likely the presence of a diffusive boundary layer on each side of the diffusion gel in diffusion cell, even under fast stirring rate condition (Shiva et al. 2015). The measurement conditions of DGT time-series deployment method are closer to that of DGT deployment, compared to diffusion cell method. In addition, the diffusion coefficients for analytes in agarose gel are higher than that in APA gel, possibly due to the larger

pore size of agarose gel (> 20 nm) than APA gel (> 5 nm) (Zhang and Davison 1995).

Dialysis membranes and nylon membranes have widely been employed in liquid binding phase DGT for the measurement of heavy metals. No strong interactions exist between metals and dialysis membranes; therefore dialysis membranes do not concentrate Cd and Cu ions from solutions in a wide range of ionic concentrations (Li et al. 2003). Moreover, the diffusive boundary layer is not significant when using dialysis membranes as compared with APA hydrogel or agarose gel, even in poorly mixed waters. The nylon membrane presents excellent mechanical strength and flexibility and has been developed to determine 4-chlorophenol (4-CP) concentration; due to its inertness with organic compounds (Dong et al. 2014).

In addition, ultra-thin diffusion layer has been applied for DGT measurements, such as the use of a 0.01-mm Nuclepore membrane or a 0.1-mm Durapore® PVDF membrane (Ding et al. 2016a; Lehto et al. 2012). It is of note that the measured  $C_{\text{DGT}}$  level was significantly lower than the pore water concentration when using a thin diffusion layer

(10–100  $\mu\text{m}$  thicknesses). Therefore, to avoid erroneous date-interpretation, DGT-measured result should be interpreted as the time-averaged flux  $F_{\text{DGT}}$  (Teasdale et al. 1999; Widerlund et al. 2012):

$$F_{\text{DGT}} = \frac{M}{At} \quad (2)$$

Compared with the conventional 0.80 mm thickness APA gel and agarose diffusive gel, ultra-thin diffusion layers can reduce the diffusion distance, diffusion time and vertical diffusion of analytes in diffusive layer. Therefore, they are suitable for investigating the distribution of mobile chemical species in soils and sediments at extremely high spatial resolutions.

In summary, the considerable variation in diffusion coefficients in APA gel is worthy of concern. The uses of agarose gel and ultra-thin membrane have improved the performance of DGT in expanding the range of analytes and increasing the spatial resolution. Particularly, the agarose gel can be used as a promising standard diffusive layer in DGT measurements of various inorganic and organic analytes.

### Filter membrane

Filter membranes (usually 0.45  $\mu\text{m}$  pore sizes) have been applied as protective layer, preventing some large particles from contaminating or damaging diffusive gels outer surface. Polyvinylidene fluoride (PVDF) membranes, cellulose nitrate membranes (CN), cellulose acetate membrane and hydrophilic polyethersulfone filter membranes (PES) are commonly used as DGT filter membrane (Desautly et al. 2017; Kalkhajeh et al. 2018; Rolisola et al. 2014; Wang et al. 2016; Yabuki et al. 2014). Scally et al. (2006) reported the diffusion coefficients obtained by diffusion gels plus filter membranes were higher than those determined by the diffusion gel alone. Wang et al. (2016) further demonstrated that different filter membranes had a significant effect on the diffusion rates of anions and cations, showing the ranked order of diffusion rates to be: agarose < agarose plus PVDF < agarose plus PES < agarose plus CN. Compared the agarose gel, the larger pore size of filter membrane may be a reason for the increased diffusion rates. Some studies have indicated that different filter membranes have different affinities for solutes; and therefore, different filter membranes could result in alteration of diffusion coefficients (Garmo et al. 2008a, b; Weltje et al. 2003). In addition, the filter membrane thickness can also affect diffusion coefficients, while this aspect is rarely considered in DGT research.

A long deployment time is typically required for DGT deployment when measuring trace metals and other analytes with low concentrations in natural waters. However, the biofilm attachment on the surface of filter membrane after long deployment time could alter the diffusional properties

of the DGT device (Li et al. 2005a). To overcome this problem, Pichette et al. (2007) utilized antibiotics, copper and silver to pretreat the filter membrane, respectively. The results showed that copper and silver could prevent algal colonization within 14 days after DGT deployment. Pichette et al. (2009) also suggested an optimized deployment time of 4 days, since good measurement results and reduced biofilm effects were obtained. Other treatment methods have been applied, including the uses of additional polycarbonate membrane on the surface of DGT devices to limit biofilm growth (Uher et al. 2012), corrected diffusion coefficient to revise the DGT measurement (Feng et al. 2016). For the liquid binding phase, the dialysis membrane can be replaced by a fresh membrane regularly, which can reduce the biofouling effects without disturbing the liquid binding phase (Li et al. 2005a).


### DGT deployment and sample analysis

In general, DGT measurement needs to undergo four setups, including diffusive and binding gels preparation, DGT assembly and storage, DGT deployment and retrieval, and sample analysis and date treatment. For assembly of the DGT device, the binding gel is placed on DGT base bottom, which is covered in order by a diffusion gel and a filter membrane and fixed in the DGT holder. The DGT device is generally sealed in a clean plastic bag contains a small volume of 0.01 M NaCl/NaNO<sub>3</sub> solution, to keep a humid and ionic strength condition. Prior to deployment in anoxic soils and sediments, the loaded DGT device must be put into certain concentration of NaCl/NaNO<sub>3</sub> solution, with nitrogen gas filled into the solution for at least 16 h to remove the oxygen in the probe. This avoids oxygenation of the sediments or soils and the changes in the lability of solutes during deployment.

### DGT deployment in sediments

The flat-type probe is usually deployed in flooded soils and sediments (Fig. 3). In laboratory, the flat-type probe can be inserted vertically and slowly into the sediment in a core or other containers by hands, with 2–4 cm length left in the overlying water (the probe has a totally 15 cm effective length). When applying in the field, some researchers have inserted the flat-type probes into sediments by diver or lander (Brodersen et al. 2017). The lander has relatively big volume and needs additional equipment (camera) to identify the sediment–water interface (SWI). Ding et al. (2015) developed a man-pack, small volume releasing device. The probe can be inserted into the sediment vertically utilizing the gravity of releasing device. After that, the device can be retrieved from the water column, leaving the DGT probe in the sediment. The releasing device can be applied in shallow

**Fig. 5** Operational procedures for in situ deployment of the flat-type diffusive gradients in thin-film (DGT) device in sediment and treatment for analysis



water bodies (< 10 m depth of water). Ding et al. (2015) further developed a new method to identify the sediment–water interface after retrieval of the DGT probe. The back of the flat-type probe is attached by a sheet of sponge. There are numerous small holes on the surface of the sponge where the sediment particles will be squeezed in when inserting the probe, giving a clear mark of the sediment–water interface position on the sponge. Meanwhile, a sheet of plastic membrane is fixed on the top of the device prior to deployment. Once the probe is pulled out from the sediment, the plastic membrane will immediately cover both the front and back sides of the probe. This measure can preserve the sediment–water interface mark from water flow impact during pulling out the probe. The deployment of flat-type DGT and sample analysis is summarized in Fig. 5.

### DGT deployment in soils

Dryland soil must be moisturized prior to DGT deployment, but the water content has not been standardized in the literature (Kalkhaje et al. 2018; Luo et al. 2014). Some researchers adjusted the water content at a high level (over 90% of the maximum water holding capacity) (Guan et al. 2016; Gao et al. 2017; Kalkhaje et al. 2018; Zhang et al. 2004). This may result in anoxic condition in soils and cause the bias of the measurement from the field. Other researchers adjusted the water content to around 70% of the maximum water holding capacity (Zhang et al. 2017a). This content approaches the level in the field dryland soils, while the deployment operation can be preceded smoothly under most cases. The water content can be increased step-by-step on



a 5% interval if it is difficult to operate the deployment for some types of soils containing high content of organic matter or calcite. Adjustment of the water content is traditionally made using a glass rod by hands. It is tedious if a large number of samples are treated. Another good method is that using an electric non-metallic stirrer to mix the soil sample after addition of deionized water ([www.easysensor.net](http://www.easysensor.net)). This method can significantly save in labor, while the mixing efficiency can be greatly improved comparing to the use by hands. After adjustment of the water content, the soil sample is incubated at a certain temperature for 48 h for sufficiently moist prior to DGT deployment. For flooded soils, the DGT device can be directly deployed with the soils without adjustment of the water content. They can also be dried after sample collection and treated according to the procedure of dryland soil. It is of note, that air drying of flooded soil should be avoided prior to DGT deployment because that the properties of the soil may be changed (Zhang et al. 2017a).

The deployment procedure is different between using the piston-type and cavity-type (dual-mode) DGT device. For the use of piston-type DGT device, the device is deployed into wetted soil sample by hand pressing, a good contact should be ensured between the filter membrane and soil sample. For the use of cavity-type DGT device, the wetted soil sample is filled up to the open cavity of the device directly, and the device is gently shaken to ensure good contact between the filter membrane and soil sample. Then, DGT device is transferred to semi-closed zip lock bag pre-filled with a small amount of deionized water for 24 h. The deployment of DGT and sample analysis in soil is summarized in Fig. 6.

### DGT deployment in waters

The piston-type DGT device can be deployed in freshwater, seawater, and wastewaters for obtaining time-averaged concentrations of solutes, including organic chemicals/compounds, nutrients and multiple cations and anions (Guo et al. 2017a, b; Huang et al. 2016c; Wang et al. 2016; Xie et al. 2018a). The piston-type DGT device has been in situ deployed in water by several ways. The DGT devices can be attached to a buoy with fishing line (Pichette et al. 2007); multiple devices can be fixed into a polyhedral structure (the device exposure windows outward) (Guo et al. 2017a; Zheng et al. 2015); the devices can be fixed on plastic mesh strips or in the middle of two plexiglass plate (Lucas et al. 2014; Uher et al. 2017).

Many studies used a constant thickness diffusion layer to directly measure the time-averaged concentrations of solutes in water (Gimpel et al. 2003; Zheng et al. 2015). However, a thin solution layer is adjacent on the surface of DGT device to form a diffusive boundary layer when the device is deployed in water, which can affect the solute diffusive

rate (Warnken et al. 2006; Zhang et al. 1998a). The diffusive boundary layer thickness ( $\delta$ ) in water can be calculated by simultaneously using various thicknesses of diffusive gel layer (Garmo et al. 2006; Scally et al. 2006; Zhang et al. 1998a):

$$\frac{1}{M} = \frac{\Delta g}{DC_{\text{DGT}}At} + \frac{\delta}{DC_{\text{DGT}}At} \quad (3)$$

where  $\Delta g$  is the thickness of diffusive layer;  $C_{\text{DGT}}$  is the solute concentration measured by DGT;  $A$  is the exposed surface area of the DGT device;  $M$  is the accumulated mass of analyte in the binding gel;  $D$  is the analyte diffusion coefficient in the diffusive layer;  $t$  is the deployment time.


Davison and Zhang (2012) have reviewed that the thickness of diffusive boundary layer is typically  $\sim 0.2$  mm in well-stirred solutions, and varies from 0.26 mm in fast-flowing waters, 0.31 mm in lake epilimnion, to 0.39 mm in stagnant pond. Huang et al. (2016b) recently found that the thickness of diffusive boundary layer in some pond and wetland sites are approximately 100% of the standard DGT diffusive layer thickness ( $\Delta g = 0.09$  cm). Therefore, a substantial error will be introduced in DGT concentration calculation if ignoring the diffusive boundary layer thickness.

### Analysis of DGT sample

The DGT samples from the use of liquid binding phases can be determined directly without elution step. In comparison, the sample analysis from the use of solid binding phases generally requires an elution step. The elution agencies vary with the types of binding gels. The elution steps of common used binding gels are summarized in Table 6.

For sample analysis, the eluent containing target analytes can be determined by multiple analysis methods, such as inductively coupled plasma mass spectrometry (ICP-MS), inductively coupled plasma optical emission spectrophotometry (ICP-OES) or graphite flame atomic absorption spectroscopy (GFAAS). For the measurements in sediments and flooded soils, the 1D solute profile distributions with the use of flat-type DGT probes can be obtained by section-elution-analysis procedure. Several cutting tools have been applied for the section of the binding gel, including Teflon coated razor blade (Zhang et al. 2002), Plexiglass gel cutter (Gao et al. 2006) and multi-bladed ceramic cutter (Ding et al. 2015). Compared with other cutting tools, the use of multi-bladed ceramic cutter not only greatly increases the sample treatment efficiency, but also avoids the risk of metal contamination during the cutting. Furthermore, the spatial resolution of the cutting can be varied from 1.0 mm to 5.0 mm through adjusting the interval between the adjacent single ceramic blades.

**Fig. 6** Operational procedures for piston-type and dual-mode diffusive gradients in thin-film (DGT) deployment and treatment



In addition, some high-resolution techniques have been developed to obtain 2D solute distributions at sub-mm resolution, including 2D slicing-elution-microcolorimetric method for the determination of P (Ding et al. 2011, 2012), the staining technique coupled with computer imaging densitometry (CID) for the measurement of S(II), P and Cr(VI) (Ding et al. 2013; Teasdale et al. 1999; Yao et al. 2016), as well as laser ablation inductively coupled plasma mass spectrometry (LA-ICP-MS) for the determination of cations and anions (Kreuzeder et al. 2013; Stockdale et al. 2010; Warnken et al. 2004b). The CID technique is established

based on a relationship between the solute accumulation mass and the grayscale intensity, which simplifies the analysis procedures, improves the analysis efficiency and spatial resolution compared with traditional section-elution-analysis method. In comparison, the LA-ICP-MS requires a sophisticated instrument, complex analytical and expensive cost.

**Table 6** Elution steps for some commonly used binding gels

Binding gel types	Elution steps	References
Chelex-100	1 M or 2 M HNO <sub>3</sub> for 24 h to extract any metals	Song et al. (2018a), Zhang and Davison (1995)
Ferrihydrite	1.4 M HNO <sub>3</sub> and 0.1 M HF or 1 M HNO <sub>3</sub> for 24 h to extract anions	Osterlund et al. (2010), Panther et al. (2013)
Metsorb	1 M NaOH or the mixture of 1 M NaOH and 1 M H <sub>2</sub> O <sub>2</sub> for 24 h to extract anions	Bennett et al. (2010), Panther et al. (2013)
Zr-oxide	The mixture of 0.2 M NaOH and 0.5 M H <sub>2</sub> O <sub>2</sub> for 3–5 h to extract anions at 4 °C	Ding et al. (2016c)
Chelex–Metsorb	First 1 M HNO <sub>3</sub> for 24 h to extract cations, then wash the binding gel surface by deionized water, followed by elution in 1 M NaOH for 24 h to extract anions	Panther et al. (2014)
Chelex–Ferrihydrite	3 M HNO <sub>3</sub> for 24 h to extract for any analytes	Huynh et al. (2012)
ZrO–Chelex	First 1 M HNO <sub>3</sub> for 16 h to extract cations, then add deionized water to rinse for 2 h, finally mixture of 0.2 M NaOH and 0.5 M H <sub>2</sub> O <sub>2</sub> for 3–5 h to extract anions at 4 °C	Wang et al. (2017a)

## Application of the diffusive gradients in thin films

The measurement of concentration, speciation and distribution of analytes in soil, sediment and water using DGT, has been widely developed, since DGT was initially developed for the measurement of Zn concentrations in environmental water (Davison and Zhang 1994). A large number of studies have demonstrated the superiority of DGT for the measurement of species distribution and bioavailability, concentrations of nutrients and organics, and multiple elements, compared with other traditional chemical extractions methods (Dai et al. 2018; Uher et al. 2017). Moreover, the research progresses in chemical fractionation, speciation and bioavailability of analytes using DGT measurement and analysis, have been discussed in detail in the literature (Davison 2016; Menegario et al. 2017; Zhang and Davison 2015). Here, we review the recent advances in the application of DGT to the analysis of soil, sediment and water environments.

## Evaluation of bioavailability and toxicity

Currently, DGT techniques have been successfully applied for assessing the bioavailability and toxicity of solutes in soils and sediments. Zhang et al. (2014) provided an overview of the DGT assessment of P bioavailability in sediments and soils; therefore, this review focused on the recent development of DGT for assessing bioavailability and toxicity of metals. The bioavailability of As in different soil types were evaluated, comparing DGT and other traditional techniques (Dai et al. 2018; Zhang et al. 2017a), and the results indicated that the concentration of As measured by DGT exhibited a better correlation with the concentration absorbed by plants than those measured by other conventional extraction methods. Song et al. (2018a) demonstrated the potential application of DGT techniques for

evaluating the bioavailability of heavy metals in sediments of land–freshwater interfaces, compared with the sequential extraction method. A significant positive correlation was observed between  $C_{DGT}$  and exchangeable and weak acid soluble fraction of Cd, as well as a significant negative correlation between  $C_{DGT}$  and residual Cd fraction, which confirmed the DGT technique is a suitable method to assess the bioavailability of metals.

Plant uptake mechanisms for metals were explored using DGT, with results suggesting that the uptake of Ni by (*Raphanus sativus*) was controlled by diffusion and plant limiting uptake mechanisms, while the uptake of Cd was mainly controlled by plant limiting uptake mechanisms (Luo et al. 2014). Peng et al. (2017) further used DGT to prove that the distribution and bioavailability of Se and plant uptake processes were associated with plant species, growth cycles and differences in soil fractions. Song et al. (2018b) predicted the level of metal bioaccumulation and bioavailability in river sediments using DGT, and the accuracy of results was verified by comparing the DGT-measured results, to the results of direct sediment analysis and plant sample analysis, respectively. The strong correlation in bioaccumulation concentrations of Cr, Cu, Zn, and Cd and the DGT measurements, suggests that DGT can be an effective tool for the assessment of metal bioaccumulation and bioavailability in plants. However, a weak correlation for As, as well as negative correlation observed between Ni and both measured concentrations by DGT and measured levels in plant tissues. This may be because that the DGT measurement is limited to a thin layer (a few millimeters thickness) from the surface of the DGT device, while plant uptake covers a much larger volume of soils in the field (Tian et al. 2018; Williams et al. 2012). Therefore, the uptake and accumulation mechanisms of metals in plants need to be further explored in combination with other analysis techniques.

DGT has been proved to be a useful monitoring tool to reflect the accumulation extent of toxic elements in living organisms (Luider et al. 2004; Tusseau-Vuillemin et al. 2004). Gu et al. (2017) mimicked the biological responses of *Eisenia fetida* to Cd in soils using DGT. The results indicated that DGT measurement results can be more powerful for prediction of the accumulation of Cd in *Eisenia fetida*, as well as the induced adverse effects in comparison with total Cd concentration in soils. He et al. (2018) utilized DGT to predict trace metal bioavailability to chironomids (*C. tentans*) in sediments, and strong correlations were obtained between DGT-measured metal fluxes in the surficial sediment and metal bioaccumulation in *C. tentans*. Therefore, DGT-measured fluxes provide new surrogate to assess bioavailable fraction of toxic element accumulation in benthic invertebrates in sediments. In addition, Philipps et al. (2018) verified the performance of the DGT for predicting the Cu bioaccumulation in fish in waters containing low concentrations of natural organic matter.

### Measurement of time-averaged concentrations

An important application of DGT is to measure DGT-labile concentrations of nutrients, metal(loid)s and organics in environment. Menegario et al. (2017) have summarized and discussed this application by focusing on metal(loid)s in waters. Therefore, this review paid attention to nutrients and organics. The high level of agreement has been observed between the  $\text{NH}_4\text{-N}$  concentrations obtained by DGT and those measured in bulk solution ( $C_{\text{DGT}}: C_{\text{SOL}} = 0.922 \pm 0.070\text{--}1.030 \pm 0.060$ ) (Feng et al. 2015). Huang et al. (2016a, b) compared labile concentrations determined by DGT and grab sample for  $\text{NH}_4\text{-N}$  and  $\text{NO}_3\text{-N}$  concentrations in freshwater, respectively. Results showed  $C_{\text{DGT}}: C_{\text{SOL}} = 0.83\text{--}1.3$  for  $\text{NH}_4\text{-N}$ , and  $C_{\text{DGT}}: C_{\text{SOL}} = 1.03\text{--}1.04$  for  $\text{NO}_3\text{-N}$ . Huang et al. (2017) further measured dissolved inorganic nitrogen (PrCH resin for  $\text{NH}_4\text{-N}$  and A520E resin for  $\text{NO}_3\text{-N}$ ) and phosphorus (Metsorb for  $\text{PO}_4\text{-P}$ ) simultaneously in freshwater using a hybrid DGT. The ratio  $C_{\text{DGT}}/C_{\text{SOL}}$  was  $0.83\text{--}1.3$  for  $\text{NH}_4\text{-N}$ ,  $\text{NO}_3\text{-N}$  and  $\text{PO}_4\text{-P}$ , which demonstrated a high level of measurement accuracy for the new DGT. In addition, Cai et al. (2017) have applied DGT techniques to the determination of  $\text{NO}_3\text{-N}$  concentrations in soil, showing excellent agreement with pore water concentrations. Moreover, the heterogeneity of  $\text{NO}_3\text{-N}$  distribution in soil can be clearly observed from 2D distribution plots.

The toxicity and potential risk of organics are of wide global concern; therefore numerous studies have applied DGT techniques to the in situ measurement of organics in various environments (Cizmas et al. 2015). Chen et al. (2013, 2014a, 2015a, b) used XAD-18 as a DGT sorbent for the in situ sampling of multiple antibiotics in water and soil, combined with the DIFS model to investigate the supply

kinetics of antibiotics from soil solid phase into solution. Estrogenic activity was measured by XAD-18 DGT and conventional grab sampling, with good agreement between conventional sampling methods and DGT sampling results (Guo et al. 2017b). However, the DGT method provided the additional benefits of being in situ technique and more efficient in terms of cost, time, and labor. Moreover, XAD-18 DGT has been employed to measure the concentration of illicit drugs in wastewater and rivers, showing no significant difference in detected concentrations between DGT and active sampling methods; although the concentrations obtained by DGT were slightly lower than with active sampling (Guo et al. 2017b; Zhang et al. 2018b). Xie et al. (2018a) found that antibiotics concentrations in seawater were significantly different using XAD-1 DGT and active sampling. This difference may be due to the fact that active sampling missed the effects of discharge, tide and dilution. The ratio of EDCs concentrations obtained by XDA-1 DGT and direct sampling in seawater, were all between 0.8 and 1.2, which demonstrates that XDA-1 DGT is suitable for in situ measurement of EDCs in seawater (Xie et al. 2018b). In addition, the concentration of household and personal care product (HPCP) compounds in water, were measured using DGT, in comparison with auto and grab sampling methods (Chen et al. 2017b). Results suggested that concentrations of most HPCPs obtained by DGT are similar to those measured by auto sampling; however, they were not always consistent with the results of grab sampling, due to the grab sampling method ignoring some peak, point source, rain or discharge events.

Dong et al. (2014) used a novel molecularly imprinted polymer (MIP) as the binding agent for DGT sampling of 4-chlorophenol (4-CP) in water, with performances of MIP DGT tested. The concentration of free form 4-chlorophenol obtained by MIP DGT decreased with the increasing concentration of dissolved organic carbon due to electrostatic interaction between 4-chlorophenol dissolved organic carbons. The concentrations of bisphenols (BPs) bisphenol A (BPA), bisphenol B (BPB) and bisphenol F (BPF) were measured in water and soils (Guan et al. 2017; Zheng et al. 2015). After 7 days of deployment, the BPs concentrations in water obtained by DGT were in good agreement with active sampling results. Results also showed almost all free 4-chlorophenol was sampled by DGT with a  $C_{\text{DGT}}: C_{\text{SOL}}$  ratio of around  $1.01 \pm 0.05$  in synthetic solutions, while only 39.1% of the total concentration of 4-chlorophenol was collected by DGT in intermediate untreated industrial wastewater, due to the high concentrations of iron oxyhydroxide colloids and organic matter in the wastewater. It is worth noting that the toxicity of organometallics tended to be higher than inorganic metals, therefore accurate measurement of organometallics is critical. Fernandez-Gomez et al. (2015) measured and predicted the concentration and

bioavailability of MeHg in water using thiol-functionalized resin gel DGT, confirming the DOM can enhance the MeHg photodegradation process. DGT based on silica-bound sorbents was successfully employed for the measurement of five organotin compounds in sediments (Cole et al. 2018). The obtained 1D profile distributions demonstrated spatial distribution heterogeneity for five organotin compounds, with DGT fluxes ranging between  $4.3 \times 10^{-8}$  and  $1.6 \times 10^{-5}$  ng cm<sup>2</sup> s<sup>-1</sup> in sediments.

### Investigation of coupled relationship between different elements

DGT simultaneously determinates the concentrations of multiple metals and oxyanions and has been recently used to further understand the potentially coupled relationships between different elements. Wu et al. (2014) used Chelex-100 DGT to measure 14 metals (Fe, Mn, Cd, Co, Cu, Ni, Pb, Zn, Al, As, Sr, V, Cr and Sb) at the sediment–water interface (SWI). The coupled relationships between metals were observed, such as the similarities in concentration distributions between Cd, Co, V, Sb, Cu, Pb, As, Sr, Cr, Al and Fe, as well as Ni, As, Sr, Zn and Mn. Wang et al. (2017a) simultaneously measured eight cations (Fe, Mn, Co, Ni, Cu, Zn, Cd and Pb) and eight oxyanions (P, V, Cr, As, Se, Mo, Sb and W) in sediments using ZrO–Chelex DGT. Similar distributions were observed between six elemental groups: Fe, Mn, P, and As (1), Co and Ni (2), Zn and Pb (3), V and Cr (4), Se and Mo (5), and Sb and W (6). The coupled relationship and co-remobilization observed between trace metals and Fe/Mn was verified using DGT, where the redox cycle of Fe/Mn played an important role in the distribution and speciation of some trace elements (Parker et al. 2017). Naylor et al. (2004, 2006) simultaneously measured sulfide with Fe, Cu, Mn, Ni and Zn concentrations using DGT–CID techniques in marine sediments, while the simultaneous release of sulfide with Fe, Mn, Ni and Zn has been observed from distribution imaging. The coupled relationship between P and Fe(II) was observed at a millimeter scale by ZrO–Chelex DGT, with the mechanism identified for Fe-redox controlled P release from Fe-bound P in sediments (Ding et al. 2016a; Wu and Wang 2017; Xu et al. 2013). The phenomenon of simultaneous release of DRP and dissolved sulfide from the SWI was initially established by combining ZrO–AgI DGT and CID technique (Ding et al. 2012). Furthermore, the 2D distribution of DRP and dissolved sulfide, as well as the corresponding Fe(II) distribution, provided high-resolution information on the mechanism of microbial iron reduction (MIR) dominated sulfate reduction and Fe-coupled P mobilization, using ZrO–Chelex DGT, and AgI DGT, combined with CID analysis techniques (Ma et al. 2017).

### Combined use of DGT with DIFS

DIFS models were applied to describe the resupply capacity from solid phase to solution phase, when analytes were transferred to or consumed by DGT. The principles of DIFS and calculation methods have been well established, and DIFS has been widely applied in soil and sediment analysis, to investigate resupply processes (Harper et al. 1998, 2000; Sochaczewski et al. 2007). Zhang et al. (2017a) compared the As availability and release capacity from solids to soil solutions by DGT–DIFS in different soil types, showing greater availability of As in flooded soils, with higher values of  $R$ ,  $K_d$ ,  $k_1$ ,  $k_{-1}$  and lower  $T_C$  values than dry soils. The resupply capacities of three BPs (BPA, BPB and BPF) from soil solids to solutions were evaluated, with  $K_d$  values obtained by DIFS indicating that most BPs in soils could participate in labile exchange (Guan et al. 2017). Gao et al. (2018) predicted the Ni mobilization and release capacity from solid phases in riparian reservoir soil by DGT–DIFS. The small  $R$  ( $< 0.25$ ) and obviously high  $K_b$  suggested a slow rate of resupply of Ni from the solid phase. The lower Ni resupply capacity may be caused by the adsorption of Fe/Mn oxides and organic matter, according to the positive correlations between Ni concentrations and Fe, Mn and TOC concentrations. Xu et al. (2018) combined DGT and DIFS model to evaluate the dynamic release mechanism of Zn in the riparian soils. The results showed that labile Zn can irreversibly and rapidly release into soil solution from solid phase, indicating the release and pollution risk of Zn in riparian reservoir soils.

In addition, DIFS models can be applied to the prediction of resupply capacities from sediment solids to porewater. Chen et al. (2018a) studied the P resupply kinetics from sediment solids to porewater using DIFS, after dredging for 6 years. Simulation results indicated that the P release capacity decreased after sediment dredging in April, due to increased  $R$ ,  $K_d$  and  $k_1$  values. Moreover, DIFS was used to evaluate the resupply capacities of P in sediments after aluminum sulfate (ALS) and lanthanum modified bentonite amendment, respectively (Lin et al. 2017a; Wang et al. 2017b). Both the increase in  $K_d$  and  $k_1$ , as well as the decrease in  $T_C$ , suggested that release of P from sediment solids was difficult after amendment. Lin et al. (2017b) combined with DGT and DIFS to demonstrate that ALS could also effectively immobilize As in sediments.  $K_d$  and  $k_1$  consistently increased, indicating the As release capacity from sediment solids was reduced by ALS amendment. Moreover, the transfer, uptake and bioavailability of P, Cu, Cd, Pb, and Zn were assessed in the macrophyte rhizosphere in sediments using DGT and DIFS (Wang et al. 2018; Wu et al. 2018). It verified that the diffusion and resupply characteristics of metals at the rhizosphere interface were controlled by multiple factors, including the solid phase resupply capacity

and the labile pool size in the sediments. Furthermore, the observed depletion of labile P pool size in rhizosphere sediments indicated the essential role of macrophyte in controlling the release of P from sediments.

### Combined use of DGT with DET

The combination of DGT and other in situ passive sampling techniques has become a recent focus in DGT research and development. The diffusive equilibrium in thin films (DET), contained only the diffusive gel and the membrane, with a similar device setup to DGT, relying on the diffusion equilibrium established between DET gel and pore water (Davison et al. 1991; Ding et al. 2010a; Harper et al. 1997). DET measured the total dissolved species concentration, while DGT obtained information on labile species concentration; therefore, the concentrations acquired from DET were often higher than DGT (Gao et al. 2006, 2007).

The reported application of combined DGT and DET systems, have involved insertion of both devices in sediments in a back-to-back manner (Gao et al. 2012; Gregusova and Docekal 2013; Lesven et al. 2008). The 1D distribution profiles of Fe, Mn, Co, Cd, Cu and Zn in sediment have also been obtained using back-to-back DGT and DET probes (Yang et al. 2012). The concentration distributions of Fe, Mn and Co were in good agreement for both DGT and DET measurement. In addition, the ratio  $R$ : DGT/DET or DGT/centrifugation was applied to assess the supply capacity from the solid phase into solution, showing that Mn and Fe were more readily released from the solid phase. Various coupling relationships have been observed between Fe and As, Co, Ni and Mn, using the DGT and DET technique (Pradit et al. 2013). The maximum concentration of Cu, Zn, Cd and Pb detected at the SWI, was probably the result of organic matter degradation and similar results were also observed by Yang et al. (2012). The As concentration in soil porewater was measured using direct sampling, DGT and DET (Garnier et al. 2015). Results suggested that profile distributions obtained by all three sampling methods were similar in magnitude and pattern of concentrations. In addition, Menezes-Blackburn et al. (2016) established the P mobility and resupply capacity in soil, using DGT and DET combined with the DIFS model, showing that DGT induced inorganic P flux, occurred mainly from soil solids resupply.

In addition, DGT and DET have also been combined into a single device. Briefly, the DET–DGT probe consisted of three layers: the membrane filter, the DET gel as a diffusive gel and a DGT binding gel (Robertson et al. 2008, 2009). The relationship between Fe(II) and S(II), P, as well as the high-resolution (sub-mm) 2D imaging of the distributions of these species in seagrass sediments, were obtained using the hybrid probes (Pages et al. 2011). The heterogeneity distributions of Fe(II) and S(II), P, as well as the coupled


relationships between Fe(II) and P, as well as Fe(II) and S(II) were observed from 2D distribution images. Furthermore, Cesbron et al. (2014) developed a hyperspectral imaging method combined with a DET–DGT probe for the measurement of S(II), Fe(II) and DRP, at a sub-mm resolution in sediments, with iron and sulfide interactions in deeper sediment profiles. Moreover, the co-distribution of dissolved Fe(II) and DRP was obtained, providing evidence for Fe-coupled mobilization of P, with Pages et al. (2014) further confirming the results using a DET–DGT probe.

Pages et al. (2012) used a DET–DGT probe to measure S(II) and Fe(II) at high-resolution (sub-mm) and P and  $\text{NH}_4^+$  at low-resolution (mm), in the rhizosphere of *Zostera capricorni* under both light and dark conditions. Under light conditions, low S(II) and Fe(II) concentrations were observed around the rhizosphere; in contrast, high Fe(II) was observed in the near-surface sediment and high S(II) concentrations in the deep sediment. In addition, the effects of photosynthetic activity and radial oxygen loss (ROL) on the regulation of plant uptake of P and  $\text{NH}_4^+$  were demonstrated. Arsic et al. (2018) compared the speciation and distributions of Fe, As and Sb under oxic and anoxic conditions using a DET–DGT probe. Results suggested that Fe(II), As(III) and As(V) were more mobile under anoxic conditions, while Sb(III) and Sb(V) were released into water from sediments under oxic conditions. In addition, a decoupling relationship was observed between the Fe(II) cycle and Sb mobilization, which indicated that other processes may play a more important role in Sb mobilization, such as sulfur and/or organic carbon mechanisms.

### Combined use of DGT with dialysis sampler (Peeper)

Dialysis sampler (Peeper) systems are an in situ passive sampling technique, that rely on a diffusive equilibrium between porewater and the Peeper sampler, which is similar to DET in principle (Azcue et al. 1996). Peeper probe measures the concentration of total dissolved species; however, the significant difference with DET was the sampling medium for Peeper, which was a solution instead of a hydrogel. The Peeper sampler incorporates two fractions: with a chamber containing equilibrium solution and a dialysis membrane covered chamber. A high-resolution Peeper (HR-Peeper) sampler commonly has a total length of 15 cm with 75 chambers on a base plate (18 mm (length)  $\times$  1 mm (width)  $\times$  1 mm (height)) and a volume in each chamber of about 15  $\mu\text{L}$ , with each pair of two adjacent chambers separated vertically by a 1-mm-thick wall, allowing a vertical resolution of 2 mm. Xu et al. (2012b) used a Peeper device to collect pore water samples for the simultaneous analysis of DRP and soluble Fe. The HR-Peeper was further developed to enable measurement of more analytes, enlarging the chamber column and decreasing the vertical resolution to 4 or 5 mm (Fig. 7)

**Fig. 7** Schematic representation of the high-resolution (HR) Peeper device, **a** 1, the flat base to support the Peeper chambers (2); 3 and 4 the window and fixed strip to fix the Peeper chambers and dialysis membrane; **b** 1 and 2, the side and front of HR-Peeper device



(Ding et al. 2018b). Moreover, the combination of DGT and HR-Peeper devices provides insight into biogeochemical processes for P (Ding et al. 2018a; Lin et al. 2017a).

Chen et al. (2015c, 2016a, b) investigated the effects of different levels of bioturbation on P release and kinetics in sediments, with the relationship between Fe(II) and P mobilization investigated using HR-Peeper and DGT at a millimeter resolution. Results suggest that macrozoobenthos bioturbation resulted in a decrease in the concentrations of soluble/labile P in sediments, with labile P concentrations being much lower around the worm burrow. In contrast, bivalve bioturbation increased the concentrations of soluble/labile P. These different results may be caused by different biological types. Macrozoobenthos induced an increase in DO in worm borrows, causing Fe(II) to be oxidized to Fe(III) oxyhydroxides, which increased the adsorption for P and further inhibited P release. However, bivalve bioturbation shortened the O<sub>2</sub> penetration depth and caused the depletion of O<sub>2</sub> in sediments, resulting in the reduction of Fe(III) oxyhydroxides and an increase in soluble/labile Fe(II), as well as P release from sediment. The effects of elevated P in water on the release of heavy metals from sediments were investigated in a microcosm experiment, using DGT and HR-Peeper (Chen et al. 2017a). Results showed that DGT-labile metal concentrations decreased from the 10th to 20th days and dissolved metal concentrations decreased on the 20th day of incubation with elevated phosphorus levels in the water, due to the metal-P precipitate; on the 40th day, the degree of decrease in DGT-labile metals was reduced. In addition, Sun et al. (2017) combined the DGT and HR-Peeper technique, with the DIFS model to investigate the competitive effect of P on As mobility in sediments. Results indicated that soluble/labile P and As increased, while the

soluble/labile Fe(II) fraction decreased with rising P content in water, due to competitive effects of P and As. DIFS simulation results showed an increased As resupply capacity from the solid phase to pore water, with elevated P concentrations in water.

Using DGT and Peeper systems, the mechanisms of P release during algal blooms were investigated on an hourly scale (Chen et al. 2018b). Both the occurrence of algal blooms and their decomposition were found to increase the concentration of SRP in porewater. During algal blooms, increasing soluble Fe(II) concentrations were the main reason for the release of SRP, suggesting Fe-redox cycling controlled P mobilization. Furthermore, Ding et al. (2018b) verified the same Fe–P coupling mechanism in sediments, providing further insights into the contribution of internal P loading to N limitation. During the pre-bloom and bloom period, TP concentrations increased and significantly negatively correlated with sediment SRP flux and water column TN/TP concentrations, which demonstrates the contribution of internal P to N limitation. Liu et al. (2018) studied the effects of temperature on the release of P using DGT and Peeper, which simultaneously determined labile P/Fe and soluble P/Fe concentrations at different temperatures. Results showed that concentrations of DGT-labile P and SRP increased with rising temperatures, which may be caused by the increase in the microbial reduction of Fe(III) oxyhydroxides and algal degradation. Xing et al. (2018) utilized DGT to measure DGT-labile P and HR-Peeper techniques to measure soluble Fe(II), SRP in the rhizosphere. Exploring further plant uptake mechanisms for P in sediments, it was established that root-mediated radial O<sub>2</sub> loss processes caused the formation of Fe plaques on the root surface, with Fe plaques absorbing and accumulating P from

sediments and porewater adjacent to the roots. Finally, the root excreted oxalic acid and other LMWOAs, which were found to increase the release of P in Fe plaques and absorption by the root. Similar mechanisms of plant-mediated P uptake have been obtained by combining DGT and PO techniques (Brodersen et al. 2017).

### Combined use of DGT with planar optode

Some changes in physicochemical parameters, such as pH and O<sub>2</sub>, are associated with changes in metal species dynamics and distributions. Nevertheless, sophisticated experimental setups and complex data analysis processes have provided only a limited understanding of these processes. Planar optode (PO) is a robust 2D imaging technique that has been widely applied for the measurement of pH, O<sub>2</sub>, pCO<sub>2</sub> and temperature in sediments and soils (Möbhammer et al. 2016; Santner et al. 2015). Both DGT and planar optode are in situ measurement techniques that can provide high-resolution information on analyte fluxes and distributions (Davison and Zhang 1994; Glud et al. 1996). Hoefler et al. (2015) studied the effects of sulfur (S<sup>0</sup>) application on metal solubility in the rhizosphere of *Salix smithiana*, with the 2D distribution of Mn, Zn and Cd fluxes obtained by DGT–LA-ICP-MS and the O<sub>2</sub> 2D distribution by planar optode imaging. Results indicated that S<sup>0</sup> oxidation caused depletion of O<sub>2</sub> and local acidification along single roots, inducing an increase in Mn, Zn and Cd solubility at the root–soil interface. To investigate seagrass-derived phosphorus and Fe(II) solubilization, Brodersen et al. (2017) utilized DGT–LA-ICP-MS for assessment of the 2D distribution of Fe(II) and Ca<sup>2+</sup>, DGT–CID for 2D distribution of sulfide and phosphate and planar optode for 2D distribution of O<sub>2</sub> and pH, demonstrating the relationship between nutrient mobilization and radial O<sub>2</sub> loss. Kreuzeder et al. (2018) combined the DGT and planar optode techniques to study the biogeochemistry of P and metals in the rhizosphere of three plants (wheat, buckwheat and white lupine). The results showed that the root apices were more active for P solubilization, and plants could respond to P deficiency by inducing acidification or alkalization in the rhizosphere.

Furthermore, DGT–PO hybrid sensor has been developed for simultaneous 2D imaging of O<sub>2</sub>/pH and trace metal species dynamics at a sub-mm resolution. Stahl et al. (2012) used a novel DGT–PO hybrid sensor to simultaneously obtain 2D imaging distributions of O<sub>2</sub> dynamics and trace metal fluxes. As shown by the 2D imaging distribution of O<sub>2</sub> and corresponding metals, irrigated burrows induced enhanced O<sub>2</sub> levels, resulting in highly localized mobilization of Ni, Cu and Pb, as well as a decrease in dissolved Fe(II) around the burrow system. Lehto et al. (2017) used a DGT–PO sensor to investigate the influence of deposition of particulate organic matter (POM) on O<sub>2</sub> dynamics and

metals mobilization at SWI. Results indicated that the deposition of POM resulted in the depletion of O<sub>2</sub> concentrations, with anoxic conditions at the SWI also increasing mobilization of Fe and Mn, while decreasing Zn, Ni and Co mobilization. The combined single-layer gel consisted of the DGT with PO applied for analysis of rhizosphere biogeochemical processes (Hoefler et al. 2017; Williams et al. 2014). Results showed that ROL-derived acidification of the local rhizosphere environment, resulted in elevated mobilization of trace metals, such as Al, Co, Cu, Fe, Mn, Ni and Pb. In addition, 2D imaging of O<sub>2</sub>/pH and trace metals showed that Fe-redox cycles regulate the plant uptake of trace metals.

In summary, the combination of DGT with other high-resolution, imaging techniques allows the simultaneous measurement of multiple elements, enhancing our understanding of the relationship between labile species and dissolved species. This has greatly broadened the application scope of DGT and allows its function in revealing the biogeochemical processes for various solutes. In terms of analysis of the heterogeneous nature of sediments and flooded soils, the combined method looks very promising for future application.

## Advantages and challenges

### Advantages of DGT development

Over the last two decades, DGT has developed into an important measurement method, because of its notable advantages: (1) DGT can perform in situ measurements, with accurate interpretation of the measurement results possible. Furthermore, DGT measurements do not ignore certain events, such as discharge, rain and tide episodes, and are independent of soil properties and water flow conditions; (2) DGT can measure a great number of labile metal species, oxyanions, organics and other solutes, even at low concentrations due to pre-concentration capacity; (3) DGT can be applied to the measurement and evaluation of concentrations, distributions, speciation and bioavailability of analytes, allowing interpretation and prediction of resupply mechanisms from sediment and soil solid phase to solution phase, in combination with DIFS; (4) DGT can provide high-resolution (mm and sub-mm) information in combination with other in situ measurement techniques, such as DET, Peeper and PO.

### DGT development challenges

The DGT technique has been continually developed for more than 20 years, and its effective application in sediments, soils and water have been well established. However, significant challenges remain for the future development of DGT.



1. Overcoming environmental interference to DGT measurement. In addition to biofilms which could affect analyte diffusion, electrostatic interactions and ion competition can also interfere with solute diffusion in the diffusive layer, affecting the adsorption performance of the binding gel. Besides, the adsorption of organics by the filter membranes could affect the DGT measurement of organics. There are currently no effective methods to resolve these problems.
2. Expanding the capability of DGT measurement. With development of the mixed binding layer, hybrid DGT devices have provided new insights into the complex relationships between trace metals and oxyanions in various environments. The measurement of multiple targets using a mixed binding layer is required, such as for the simultaneous measurement of heavy metals and organics, or nutrient. Furthermore, in order to study the biogeochemical processes for a specific target under heavily polluted conditions, highly selective binding agents need to be further developed. The currently available DGT binding agents are too large (mm– $\mu$ m size) to match the combined use of other 2D imaging techniques, such as PO. Smaller binding agents in the nano-size range should be developed and applied in the future.
3. Unify the DGT operational procedure. To date, many researchers have applied the DGT technique to the measurement of various solutes in sediment, soil and water using different operational procedures. The use of varying operational procedures results in a greater potential for error, as well as reducing the comparability among measurement results. Therefore, the unification of operational procedures for DGT device assembly, deployment and sample treatment is required. Standardized systems, such as types of diffusion gel and filter membrane would significantly facilitate comparison among different studies. Furthermore, water content should be optimized to a similar level for the measurement of dryland soils.
4. Improvement of the interpretation of DGT measurement results. DGT has been demonstrated to be a useful tool to indicate the lability and bioavailability of nutrients and metals in soils and sediments. It has the potential to be applied in environmental quality and ecological risk assessments. However, the uptake of solutes by organisms are not only controlled by diffusive mechanism in soils or sediments, but also influenced by organism types and other factors. It is still far away from establishing environmental criteria based on DGT measurement. More research should be performed in this aspect. Furthermore, DIFS modeling has been successfully employed for the evaluation and prediction of the resupply capacity from soil or sediment solid phase. Further development of the interpretation of liquid–solid interactions is required, in combination with other models.

## Conclusion

A great number of studies have demonstrated that the DGT technique is not only a versatile in situ passive sampling tool for the measurement of metals and oxyanions, but also a potential tool for the determination of inorganic nutrients and organics. In this paper, the principles of DGT technique and research progress are described, with the performances of tradition DGT devices and improved DGT devices reviewed, as well as commonly used binding and diffusion materials discussed in detail. The novel applications and development of DGT techniques in recent years are discussed, as well as the potential capabilities of DGT, that have yet to be fully exploited. Overall, more research attention should be given to the investigation of biogeochemical processes by DGT.

**Acknowledgements** This research work was financially supported by the National Natural Science Foundation of China (41571465, 41701570, and 41621002), The Natural Science Foundation of Shandong Province (ZR2016DM10).

## References

- Altier A, Jimenez-Piedrahita M, Rey-Castro C, Cecilia J, Galceran J, Puy J (2016) Accumulation of Mg to diffusive gradients in thin films (DGT) devices: kinetic and thermodynamic effects of the ionic strength. *Anal Chem*. <https://doi.org/10.1021/acs.analchem.6b02961>
- Arsic M, Teasdale PR, Welsh DT, Johnston SG, Burton ED, Hockmann K et al (2018) Diffusive gradients in thin films reveals differences in antimony and arsenic mobility in a contaminated wetland sediment during an oxic–anoxic transition. *Environ Sci Technol* 52:1118–1127. <https://doi.org/10.1021/acs.est.7b03882>
- Azcue JM, Rosa F, Lawson G (1996) An improved dialysis sampler for the in situ collection of larger volumes of sediment pore waters. *Environ Technol* 17:95–100. <https://doi.org/10.1080/09593331708616365>
- Bennett WW, Teasdale PR, Panther JG, Welsh DT, Jolley DF (2010) New diffusive gradients in a thin film technique for measuring inorganic arsenic and selenium(IV) using a titanium dioxide based adsorbent. *Anal Chem* 82:7401–7407. <https://doi.org/10.1021/ac101543p>
- Brodersen KE, Koren K, Mosshammer M, Ralph PJ, Kuhl M, Santner J (2017) Seagrass-mediated phosphorus and iron solubilization in tropical sediments. *Environ Sci Technol* 51:14155–14163. <https://doi.org/10.1021/acs.est.7b03878>
- Cai C, Williams PN, Li H, Davison W, Wei TJ, Luo J et al (2017) Development and application of the diffusive gradients in thin films technique for the measurement of nitrate in soils. *Anal Chem* 89:1178–1184. <https://doi.org/10.1021/acs.analchem.6b03609>
- Cattani I, Spalla S, Beone GM, Del Re AA, Boccelli R, Trevisan M (2008) Characterization of mercury species in soils by HPLC–ICP-MS and measurement of fraction removed by diffusive gradient in thin films. *Talanta* 74:1520–1526. <https://doi.org/10.1016/j.talanta.2007.09.029>
- Cesbron F, Metzger E, Launeau P, Deflandre B, Delgard ML, Thibault de Chanvalon A et al (2014) Simultaneous 2D imaging of

- dissolved iron and reactive phosphorus in sediment porewaters by thin-film and hyperspectral methods. *Environ Sci Technol* 48:2816–2826. <https://doi.org/10.1021/es404724r>
- Challis JK, Hanson ML, Wong CS (2016) Development and calibration of an organic-diffusive gradients in thin films aquatic passive sampler for a diverse suite of polar organic contaminants. *Anal Chem* 88:10583–10591. <https://doi.org/10.1021/acs.analchem.6b02749>
- Chen CE (2015) Go greener with passive sampler and beyond. *J Environ Health Sci* 1:15–16. <https://doi.org/10.15436/2378-6841.15.008>
- Chen H, Sun T, Sui D, Dong J (2011) Effective concentration difference model to study the effect of various factors on the effective diffusion coefficient in the dialysis membrane. *Anal Chim Acta* 698:27–35. <https://doi.org/10.1016/j.aca.2011.04.056>
- Chen CE, Zhang H, Jones KC (2012a) A novel passive water sampler for in situ sampling of antibiotics. *J Environ Monit* 14:1523–1530. <https://doi.org/10.1039/c2em30091e>
- Chen H, Liu Y, Jiang Y, Gu J, Sun T (2012b) Application of large molecular weight poly (4-styrenesulfonate) as a binding phase of the diffusive gradients in thin films technique. *Desalin Water Treat* 50:125–131. <https://doi.org/10.1080/19443994.2012.708557>
- Chen CE, Zhang H, Ying GG, Jones KC (2013) Evidence and recommendations to support the use of a novel passive water sampler to quantify antibiotics in wastewaters. *Environ Sci Technol* 47:13587–13593. <https://doi.org/10.1021/es402662g>
- Chen CE, Jones KC, Ying GG, Zhang H (2014a) Desorption kinetics of sulfonamide and trimethoprim antibiotics in soils assessed with diffusive gradients in thin-films. *Environ Sci Technol* 48:5530–5536. <https://doi.org/10.1021/es500194f>
- Chen H, Zhang MH, Gu JL, Zhao G, Zhang Y, Li JR (2014b) Measurement of dissolved reactive phosphorus in water with polyquaternary ammonium salt as a binding agent in diffusive gradients in thin-films technique. *J Agric Food Chem* 62:12112–12117. <https://doi.org/10.1021/jf5040702>
- Chen CE, Chen W, Ying GG, Jones KC, Zhang H (2015a) In situ measurement of solution concentrations and fluxes of sulfonamides and trimethoprim antibiotics in soils using o-DGT. *Talanta* 132:902–908. <https://doi.org/10.1016/j.talanta.2014.08.048>
- Chen CE, Zhang H, Ying GG, Zhou LJ, Jones KC (2015b) Passive sampling: a cost-effective method for understanding antibiotic fate, behaviour and impact. *Environ Int* 85:284–291. <https://doi.org/10.1016/j.envint.2015.10.001>
- Chen M, Ding S, Liu L, Xu D, Han C, Zhang C (2015c) Iron-coupled inactivation of phosphorus in sediments by macrozoobenthos (chironomid larvae) bioturbation: evidences from high-resolution dynamic measurements. *Environ Pollut* 204:241–247. <https://doi.org/10.1016/j.envpol.2015.04.031>
- Chen M, Ding S, Liu L, Wang Y, Xing X, Wang D et al (2016a) Fine-scale bioturbation effects of tubificid worm (*Limnodrilus hoffmeisteri*) on the lability of phosphorus in sediments. *Environ Pollut* 219:604–611. <https://doi.org/10.1016/j.envpol.2016.06.023>
- Chen M, Ding S, Liu L, Xu D, Gong M, Tang H et al (2016b) Kinetics of phosphorus release from sediments and its relationship with iron speciation influenced by the mussel (*Corbicula fluminea*) bioturbation. *Sci Total Environ* 542:833–840. <https://doi.org/10.1016/j.scitotenv.2015.10.155>
- Chen M, Ding S, Zhang L, Li Y, Sun Q, Zhang C (2017a) An investigation of the effects of elevated phosphorus in water on the release of heavy metals in sediments at a high resolution. *Sci Total Environ* 575:330–337. <https://doi.org/10.1016/j.scitotenv.2016.10.063>
- Chen W, Li Y, Chen CE, Sweetman AJ, Zhang H, Jones KC (2017b) DGT passive sampling for quantitative in situ measurements of compounds from household and personal care products in waters. *Environ Sci Technol* 51:13274–13281. <https://doi.org/10.1021/acs.est.7b03940>
- Chen M, Cui J, Lin J, Ding S, Gong M, Ren M et al (2018a) Successful control of internal phosphorus loading after sediment dredging for 6 years: a field assessment using high-resolution sampling techniques. *Sci Total Environ* 616–617:927–936. <https://doi.org/10.1016/j.scitotenv.2017.10.227>
- Chen M, Ding S, Chen X, Sun Q, Fan X, Lin J et al (2018b) Mechanisms driving phosphorus release during algal blooms based on hourly changes in iron and phosphorus concentrations in sediments. *Water Res* 133:153–164. <https://doi.org/10.1016/j.watres.2018.01.040>
- Chen W, Pan S, Cheng H, Sweetman AJ, Zhang H, Jones KC (2018c) Diffusive gradients in thin-films (DGT) for in situ sampling of selected endocrine disrupting chemicals (EDCs) in waters. *Water Res* 137:211–219. <https://doi.org/10.1016/j.watres.2018.03.029>
- Cizmas L, Sharma VK, Gray CM, McDonald TJ (2015) Pharmaceuticals and personal care products in waters: occurrence, toxicity, and risk. *Environ Chem Lett* 13:381–394. <https://doi.org/10.1007/s10311-015-0524-4>
- Clarisse O, Foucher D, Hintelmann H (2009) Methylmercury speciation in the dissolved phase of a stratified lake using the diffusive gradient in thin film technique. *Environ Pollut* 157:987–993. <https://doi.org/10.1016/j.envpol.2008.10.012>
- Clarisse O, Lotufo GR, Hintelmann H, Best EP (2012) Biomonitoring and assessment of monomethylmercury exposure in aqueous systems using the DGT technique. *Sci Total Environ* 416:449–454. <https://doi.org/10.1016/j.scitotenv.2011.11.077>
- Colaço CD, Yabuki LNM, Alcântara AL, Menegário AA (2012) Diffusion coefficients of metals in non-conventional materials (agarose and cellulose acetate) used in the diffusive gradients in thin films technique. *Quim Nova* 35:1360–1364. <https://doi.org/10.1590/s0100-40422012000700014>
- Colaço CD, Yabuki LNM, Rolisola AM, Menegário AA, Almeida ED, Suárez CA et al (2014) Determination of mercury in river water by diffusive gradients in thin films using P81 membrane as binding layer. *Talanta* 129:417–421
- Cole RF, Mills GA, Hale MS, Parker R, Bolam T, Teasdale PR et al (2018) Development and evaluation of a new diffusive gradients in thin-films technique for measuring organotin compounds in coastal sediment pore water. *Talanta* 178:670–678. <https://doi.org/10.1016/j.talanta.2017.09.081>
- Dai Y, Nasir M, Zhang Y, Gao J, Lv Y, Lv J (2018) Comparison of DGT with traditional extraction methods for assessing arsenic bioavailability to *Brassica chinensis* in different soils. *Chemosphere* 191:183–189. <https://doi.org/10.1016/j.chemosphere.2017.10.035>
- Davison W (2016) Diffusive gradients in thin-films for environmental measurements. Cambridge Environmental Chemistry, Cambridge
- Davison W, Zhang H (1994) In situ speciation measurements of trace components in natural waters using thin-film gels. *Nature* 367:546–548. <https://doi.org/10.1038/367546a0>
- Davison W, Zhang H (2012) Progress in understanding the use of diffusive gradients in thin films (DGT)-back to basics. *Environ Chem* 9:1. <https://doi.org/10.1071/en11084>
- Davison W, Grime GW, Morgan JAW, Clarke K (1991) Distribution of dissolved iron in sediment pore waters at submillimetre resolution. *Nature* 352:323–325. <https://doi.org/10.1038/352323a0>
- Davison W, Fones GR, Grime GW (1997) Dissolved metals in surface sediment and a microbial mat at 100- $\mu$ m resolution. *Nature* 387:885–888. <https://doi.org/10.1038/43147>
- de Almeida E, Nascimento Filho VF, do Menegário AA (2012) Paper-based diffusive gradients in thin films technique coupled to energy dispersive X-ray fluorescence spectrometry for the determination of labile Mn, Co, Ni, Cu, Zn and Pb in river water.

- Spectrochim Acta B 71–72:70–74. <https://doi.org/10.1016/j.sab.2012.05.006>
- de Oliveira W, de Carvalho Mde F, de Almeida E, Menegario AA, Naves Domingos R, Brossi-Garcia AL et al (2012) Determination of labile barium in petroleum-produced formation water using paper-based DGT samplers. *Talanta* 100:425–431. <https://doi.org/10.1016/j.talanta.2012.08.013>
- de Paiva Magalhães D, da Costa Marques MR, Baptista DF, Buss DF (2015) Metal bioavailability and toxicity in freshwaters. *Environ Chem Lett* 13:69–87. <https://doi.org/10.1007/s10311-015-0491-9>
- Desautly A-M, Méheut M, Guerrot C, Berho C, Millot R (2017) Coupling DGT passive samplers and multi-collector ICP-MS: a new tool to measure Pb and Zn isotopes composition in dilute aqueous solutions. *Chem Geol* 450:122–134. <https://doi.org/10.1016/j.chemgeo.2016.12.023>
- DeVries CR, Wang F (2003) In situ two-dimensional high-resolution profiling of sulfide in sediment interstitial waters. *Environ Sci Technol* 37:792–797. <https://doi.org/10.1021/es026109j>
- Ding S, Sun Q, Xu D (2010a) Development of the DET technique for high-resolution determination of soluble reactive phosphate profiles in sediment pore waters. *Int J Environ Anal Chem* 90:1130–1138. <https://doi.org/10.1080/03067310903434733>
- Ding S, Xu D, Sun Q, Yin H, Zhang C (2010b) Measurement of dissolved reactive phosphorus using the diffusive gradients in thin films technique with a high-capacity binding phase. *Environ Sci Technol* 44:8169–8174. <https://doi.org/10.1021/es1020873>
- Ding S, Jia F, Xu D, Sun Q, Zhang L, Fan C et al (2011) High-resolution, two-dimensional measurement of dissolved reactive phosphorus in sediments using the diffusive gradients in thin films technique in combination with a routine procedure. *Environ Sci Technol* 45:9680–9686. <https://doi.org/10.1021/es202785p>
- Ding S, Sun Q, Xu D, Jia F, He X, Zhang C (2012) High-resolution simultaneous measurements of dissolved reactive phosphorus and dissolved sulfide: the first observation of their simultaneous release in sediments. *Environ Sci Technol* 46:8297–8304. <https://doi.org/10.1021/es301134h>
- Ding S, Wang Y, Xu D, Zhu C, Zhang C (2013) Gel-based coloration technique for the submillimeter-scale imaging of labile phosphorus in sediments and soils with diffusive gradients in thin films. *Environ Sci Technol* 47:7821–7829. <https://doi.org/10.1021/es400192j>
- Ding S, Han C, Wang Y, Yao L, Wang Y, Xu D et al (2015) In situ, high-resolution imaging of labile phosphorus in sediments of a large eutrophic lake. *Water Res* 74:100–109. <https://doi.org/10.1016/j.watres.2015.02.008>
- Ding S, Wang Y, Wang D, Li YY, Gong M, Zhang C (2016a) In situ, high-resolution evidence for iron-coupled mobilization of phosphorus in sediments. *Sci Rep* 6:24341. <https://doi.org/10.1038/srep24341>
- Ding S, Wang Y, Zhang L, Xu L, Gong M, Zhang C (2016b) New holder configurations for use in the diffusive gradients in thin films (DGT) technique. *RSC Adv* 6:88143–88156. <https://doi.org/10.1039/c6ra19677b>
- Ding S, Xu D, Wang Y, Wang Y, Li Y, Gong M et al (2016c) Simultaneous measurements of eight oxyanions using high-capacity diffusive gradients in thin films (Zr-oxide DGT) with a high-efficiency elution procedure. *Environ Sci Technol* 50:7572–7580. <https://doi.org/10.1021/acs.est.6b00206>
- Ding S, Chen M, Cui J, Wang D, Lin J, Zhang C et al (2018a) Reactivation of phosphorus in sediments after calcium-rich mineral capping: implication for revising the laboratory testing scheme for immobilization efficiency. *Chem Eng J* 331:720–728. <https://doi.org/10.1016/j.cej.2017.09.010>
- Ding S, Chen M, Gong M, Fan X, Qin B, Xu H et al (2018b) Internal phosphorus loading from sediments causes seasonal nitrogen limitation for harmful algal blooms. *Sci Total Environ* 625:872–884. <https://doi.org/10.1016/j.scitotenv.2017.12.348>
- Divis P, Leermakers M, Docekalova H, Gao Y (2005) Mercury depth profiles in river and marine sediments measured by the diffusive gradients in thin films technique with two different specific resins. *Anal Bioanal Chem* 382:1715–1719. <https://doi.org/10.1007/s00216-005-3360-8>
- Divis P, Docekalova H, Brulik L, Pavlis M, Hekera P (2007) Use of the diffusive gradients in thin films technique to evaluate (bio)available trace metal concentrations in river water. *Anal Bioanal Chem* 387:2239–2244. <https://doi.org/10.1007/s00216-006-0996-y>
- Docekalova H, Divis P (2005) Application of diffusive gradient in thin films technique (DGT) to measurement of mercury in aquatic systems. *Talanta* 65:1174–1178. <https://doi.org/10.1016/j.talanta.2004.08.054>
- Dong J, Fan H, Sui D, Li L, Sun T (2014) Sampling 4-chlorophenol in water by DGT technique with molecularly imprinted polymer as binding agent and nylon membrane as diffusive layer. *Anal Chim Acta* 822:69–77. <https://doi.org/10.1016/j.aca.2014.03.015>
- Drozdak J, Leermakers M, Gao Y, Phrommavanh V, Descostes M (2015) Evaluation and application of diffusive gradients in thin films (DGT) technique using Chelex<sup>®</sup>-100, Metsorb<sup>™</sup> and Diphonix<sup>®</sup> binding phases in uranium mining environments. *Anal Chim Acta* 889:71–81. <https://doi.org/10.1016/j.aca.2015.07.057>
- Dsikowitzky L, Schwarzbauer J (2014) Industrial organic contaminants: identification, toxicity and fate in the environment. *Environ Chem Lett* 12:371–386. <https://doi.org/10.1007/s10311-014-0467-1>
- Ernstberger H, Zhang H, Davison W (2002) Determination of chromium speciation in natural systems using DGT. *Anal Bioanal Chem* 373:873–879. <https://doi.org/10.1007/s00216-002-1370-3>
- Fan H, Bian Y, Sui D, Tong G, Sun T (2009a) Measurement of free copper(II) ions in water samples with polyvinyl alcohol as a binding phase in diffusive gradients in thin-films. *Anal Sci* 25:1345. <https://doi.org/10.2116/analsci.25.1345>
- Fan H, Sun T, Li W, Sui D, Jin S, Lian X (2009b) Sodium polyacrylate as a binding agent in diffusive gradients in thin-films technique for the measurement of Cu<sup>2+</sup> and Cd<sup>2+</sup> in waters. *Talanta* 79:1228–1232. <https://doi.org/10.1016/j.talanta.2009.04.049>
- Fan HT, Liu JX, Sui DP, Yao H, Yan F, Sun T (2013) Use of polymer-bound Schiff base as a new liquid binding agent of diffusive gradients in thin-films for the measurement of labile Cu<sup>2+</sup>, Cd<sup>2+</sup> and Pb<sup>2+</sup>. *J Hazard Mater* 260:762–769. <https://doi.org/10.1016/j.jhazmat.2013.05.049>
- Fauvelle V, Nhu-Trang TT, Feret T, Madarassou K, Randon J, Mazzella N (2015) Evaluation of titanium dioxide as a binding phase for the passive sampling of glyphosate and aminomethyl phosphonic acid in an aquatic environment. *Anal Chem* 87:6004–6009. <https://doi.org/10.1021/acs.analchem.5b00194>
- Feng Z, Guo T, Jiang Z, Sun T (2015) Sampling of ammonium ion in water samples by using the diffusive-gradients-in-thin-films technique (DGT) and a zeolite based binding phase. *Microchim Acta* 182:2419–2425. <https://doi.org/10.1007/s00604-015-1576-7>
- Feng Z, Zhu P, Fan H, Piao S, Xu L, Sun T (2016) Effect of biofilm on passive sampling of dissolved orthophosphate using the diffusive gradients in thin films technique. *Anal Chem* 88:6836–6843. <https://doi.org/10.1021/acs.analchem.6b01392>
- Fernandez-Gomez C, Bayona JM, Díez S (2011) Laboratory and field evaluation of diffusive gradient in thin films (DGT) for monitoring levels of dissolved mercury in natural river water. *Int J Environ Anal Chem* 92:1689–1698. <https://doi.org/10.1080/03067319.2011.581369>
- Fernandez-Gomez C, Bayona JM, Díez S (2014) Comparison of different types of diffusive gradient in thin film samplers for

- measurement of dissolved methylmercury in freshwaters. *Talanta* 129:486–490. <https://doi.org/10.1016/j.talanta.2014.06.025>
- Fernandez-Gomez C, Bayona JM, Diez S (2015) Diffusive gradients in thin films for predicting methylmercury bioavailability in freshwaters after photodegradation. *Chemosphere* 131:184–191. <https://doi.org/10.1016/j.chemosphere.2015.02.060>
- Galceran J, Puy J (2015) Interpretation of diffusion gradients in thin films (DGT) measurements: a systematic approach. *Environ Chem* 12:112. <https://doi.org/10.1071/en14068>
- Gao Y, Lehto N (2012) A simple laser ablation ICPMS method for the determination of trace metals in a resin gel. *Talanta* 92:78–83. <https://doi.org/10.1016/j.talanta.2012.01.043>
- Gao Y, Leermakers M, Gabelle C, Divis P, Billon G, Ouddane B et al (2006) High-resolution profiles of trace metals in the pore waters of riverine sediment assessed by DET and DGT. *Sci Total Environ* 362:266–277. <https://doi.org/10.1016/j.scitotenv.2005.11.023>
- Gao Y, Leermakers M, Elskens M, Billon G, Ouddane B, Fischer JC et al (2007) High resolution profiles of thallium, manganese and iron assessed by DET and DGT techniques in riverine sediment pore waters. *Sci Total Environ* 373:526–533. <https://doi.org/10.1016/j.scitotenv.2006.11.047>
- Gao Y, Lesven L, Gillan D, Sabbe K, Billon G, De Galan S et al (2009) Geochemical behavior of trace elements in sub-tidal marine sediments of the Belgian coast. *Mar Chem* 117:88–96. <https://doi.org/10.1016/j.marchem.2009.05.002>
- Gao Y, Baeyens W, De Galan S, Poffijn A, Leermakers M (2010) Mobility of radium and trace metals in sediments of the Winterbeek: application of sequential extraction and DGT techniques. *Environ Pollut* 158:2439–2445. <https://doi.org/10.1016/j.envpol.2010.03.022>
- Gao Y, Leermakers M, Pede A, Magnier A, Sabbe K, Lourino Cabana B et al (2012) Response of diffusive equilibrium in thin films (DET) and diffusive gradients in thin films (DGT) trace metal profiles in sediments to phytodetritus mineralisation. *Environ Chem* 9:41. <https://doi.org/10.1071/en11075>
- Gao L, Gao B, Zhou Y, Xu D, Sun K (2017) Predicting remobilization characteristics of cobalt in riparian soils in the Miyun Reservoir prior to water retention. *Ecol Indic* 80:196–203. <https://doi.org/10.1016/j.ecolind.2017.05.024>
- Gao L, Gao B, Yin S, Xu D, Gao J (2018) Predicting Ni dynamic mobilization in reservoir riparian soils prior to water submergence using DGT and DIFS. *Chemosphere* 195:390–397. <https://doi.org/10.1016/j.chemosphere.2017.12.090>
- Garmo Ø, Røyset Oddvar, Steinnes Eiliv, Flaten TP (2003) Performance study of diffusive gradients in thin films for 55 elements. *Anal Chem* 75:3573–3580. <https://doi.org/10.1021/ac026374n>
- Garmo Ø, Lehto N, Zhang H, Davison W, Røyset O, Eiliv S (2006) Dynamic aspects of DGT as demonstrated by experiments with lanthanide complexes of a multidentate ligand. *Environ Sci Technol* 40:4754–4760
- Garmo Ø, Davison W, Zhang H (2008a) Effects of binding of metals to the hydrogel and filter membrane on the accuracy of the diffusive gradients in thin films technique. *Anal Chem* 80:9220–9225. <https://doi.org/10.1021/ac801437j>
- Garmo Ø, Davison W, Zhang H (2008b) Interactions of trace metals with hydrogels and filter membranes used in DET and DGT techniques. *Environ Sci Technol* 42:5682–5687. <https://doi.org/10.1021/es800143r>
- Garnier JM, Garnier J, Jezequel D, Angeletti B (2015) Using DET and DGT probes (ferrihydrite and titanium dioxide) to investigate arsenic concentrations in soil porewater of an arsenic-contaminated paddy field in Bangladesh. *Sci Total Environ* 536:306–315. <https://doi.org/10.1016/j.scitotenv.2015.07.065>
- Gimbert LJ, Haygarth PM, Beckett R, Worsfold PJ (2005) Comparison of centrifugation and filtration techniques for the size fractionation of colloidal material in soil suspensions using sedimentation field-flow fractionation. *Environ Sci Technol* 39:1731–1735. <https://doi.org/10.1021/es049230u>
- Gimpel J, Zhang H, Davison W, Edwards AC (2003) In situ trace metal speciation in lake surface waters using DGT, dialysis, and filtration. *Environ Sci Technol* 37:138–146. <https://doi.org/10.1021/es0200995>
- Glud RN, Ramsing NB, Gundersen JK, Klimant I (1996) Planar optodes: a new tool for fine scale measurements of two-dimensional O<sub>2</sub> distribution in benthic communities. *Mar Ecol Prog Ser* 140:217–226. <https://doi.org/10.3354/meps140217>
- Gregusova M, Docekal B (2013) High resolution characterization of uranium in sediments by DGT and DET techniques ACA-S-12-2197. *Anal Chim Acta* 763:50–56. <https://doi.org/10.1016/j.aca.2012.12.001>
- Gu X, Liu Z, Wang X, Luo J, Zhang H, Davison W et al (2017) Coupling biological assays with diffusive gradients in thin-films technique to study the biological responses of *Eisenia fetida* to cadmium in soil. *J Hazard Mater* 339:340–346. <https://doi.org/10.1016/j.jhazmat.2017.06.049>
- Guan DX, Williams PN, Luo J, Zheng JL, Xu HC, Cai C et al (2015) Novel precipitated zirconia-based DGT technique for high-resolution imaging of oxyanions in waters and sediments. *Environ Sci Technol* 49:3653–3661. <https://doi.org/10.1021/es505424m>
- Guan DX, Williams PN, Xu HC, Li G, Luo J, Ma LQ (2016) High-resolution measurement and mapping of tungstate in waters, soils and sediments using the low-disturbance DGT sampling technique. *J Hazard Mater* 316:69–76. <https://doi.org/10.1016/j.jhazmat.2016.05.026>
- Guan DX, Zheng JL, Luo J, Zhang H, Davison W, Ma LQ (2017) A diffusive gradients in thin-films technique for the assessment of bisphenols desorption from soils. *J Hazard Mater* 331:321–328. <https://doi.org/10.1016/j.jhazmat.2017.02.053>
- Guan DX, Li Y-Q, Yu N-Y, Yu G-H, Wei S, Zhang H et al (2018) In situ measurement of perfluoroalkyl substances in aquatic systems using diffusive gradients in thin-films technique. *Water Res* 144:162–171. <https://doi.org/10.1016/j.watres.2018.07.031>
- Guibal R, Buzier R, Charriau A, Lissalde S, Guibaud G (2017) Passive sampling of anionic pesticides using the diffusive gradients in thin films technique (DGT). *Anal Chim Acta* 966:1–10. <https://doi.org/10.1016/j.aca.2017.02.007>
- Guo C, Zhang T, Hou S, Lv J, Zhang Y, Wu F et al (2017a) Investigation and application of a new passive sampling technique for in situ monitoring of illicit drugs in waste waters and rivers. *Environ Sci Technol* 51:9101–9108. <https://doi.org/10.1021/acs.est.7b00731>
- Guo W, Van Langenhove K, Denison MS, Baeyens W, Elskens M, Gao Y (2017b) Estrogenic activity measurements in water using diffusive gradients in thin-film coupled with an estrogen bioassay. *Anal Chem* 89:13357–13364. <https://doi.org/10.1021/acs.analchem.7b03537>
- Harper MP, William Davison A, Tych W (1997) Temporal, spatial, and resolution constraints for in situ sampling devices using diffusional equilibration: dialysis and DET. *Environ Sci Technol* 31:3110–3119. <https://doi.org/10.1021/es9700515>
- Harper MP, Davison W, Zhang H, Tych W (1998) Kinetics of metal exchange between solids and solutions in sediments and soils interpreted from DGT measured fluxes. *Geochim Cosmochim Acta* 62:2757–2770. [https://doi.org/10.1016/s0016-7037\(98\)00186-0](https://doi.org/10.1016/s0016-7037(98)00186-0)
- Harper MP, Davison W, Tych W (2000) DIFS—a modelling and simulation tool for DGT induced trace metal remobilisation in sediments and soils. *Environ Model Softw* 15:55–66. [https://doi.org/10.1016/s1364-8152\(99\)00027-4](https://doi.org/10.1016/s1364-8152(99)00027-4)
- He Y, Guo C, Lv J, Hou S, Zhang Y, Zhang Y et al (2018) Predicting trace metal bioavailability to chironomids in sediments by

- diffusive gradients in thin films. *Sci Total Environ* 636:134–141. <https://doi.org/10.1016/j.scitotenv.2018.04.285>
- Heim S, Schwarzbauer J (2013) Pollution history revealed by sedimentary records: a review. *Environ Chem Lett* 11:255–270. <https://doi.org/10.1007/s10311-013-0409-3>
- Henner P, Schwartz C, Lichtfouse E (1997) Pipette Pasteur extraction: a fast, convenient, exhaustive and environmentally friendly method for the extraction of solid samples. *Analisis* 25(9–10):M51–M52. <https://hal.archives-ouvertes.fr/hal-00193272>
- Henner P, Schiavon M, Druelle V, Lichtfouse E (1999) Phytotoxicity of ancient gaswork soils. Effect of polycyclic aromatic hydrocarbons (PAHs) on plant germination. *Org Geochem* 30:963–969. [https://doi.org/10.1016/S0146-6380\(99\)00080-7](https://doi.org/10.1016/S0146-6380(99)00080-7)
- Hoefler C, Santner J, Puschenreiter M, Wenzel WW (2015) Localized metal solubilization in the rhizosphere of *Salix smithiana* upon sulfur application. *Environ Sci Technol* 49:4522–4529. <https://doi.org/10.1021/es505757j>
- Hoefler C, Santner J, Borisov SM, Wenzel WW, Puschenreiter M (2017) Integrating chemical imaging of cationic trace metal solutes and pH into a single hydrogel layer. *Anal Chim Acta* 950:88–97. <https://doi.org/10.1016/j.aca.2016.11.004>
- Huang J, Bennett WW, Teasdale PR, Gardiner S, Welsh DT (2016a) Development and evaluation of the diffusive gradients in thin films technique for measuring nitrate in freshwaters. *Anal Chim Acta* 923:74–81. <https://doi.org/10.1016/j.aca.2016.04.006>
- Huang J, Bennett WW, Welsh DT, Li T, Teasdale PR (2016b) “Diffusive gradients in thin films” techniques provide representative time-weighted average measurements of inorganic nutrients in dynamic freshwater systems. *Environ Sci Technol* 50:13446–13454. <https://doi.org/10.1021/acs.est.6b02949>
- Huang J, Bennett WW, Welsh DT, Li T, Teasdale PR (2016c) Development and evaluation of a diffusive gradients in a thin film technique for measuring ammonium in freshwaters. *Anal Chim Acta* 904:83–91. <https://doi.org/10.1016/j.aca.2015.11.022>
- Huang J, Bennett WW, Welsh DT, Teasdale PR (2016d) Determining time-weighted average concentrations of nitrate and ammonium in freshwaters using DGT with ion exchange membrane-based binding layers. *Environ Sci Process Impacts* 18:1530–1539. <https://doi.org/10.1039/c6em00260a>
- Huang J, Bennett WW, Teasdale PR, Kankanamge NR, Welsh DT (2017) A modified DGT technique for the simultaneous measurement of dissolved inorganic nitrogen and phosphorus in freshwaters. *Anal Chim Acta* 988:17–26. <https://doi.org/10.1016/j.aca.2017.08.024>
- Huynh T, Zhang H, Noller B (2012) Evaluation and application of the diffusive gradients in thin films technique using a mixed-binding gel layer for measuring inorganic arsenic and metals in mining impacted water and soil. *Anal Chem* 84:9988–9995. <https://doi.org/10.1021/ac302430b>
- Kalkhajah YK, Sorensen H, Huang B, Guan DX, Luo J, Hu W et al (2018) DGT technique to assess P mobilization from greenhouse vegetable soils in China: a novel approach. *Sci Total Environ* 630:331–339. <https://doi.org/10.1016/j.scitotenv.2018.02.228>
- Kreuzeder A, Santner J, Prohaska T, Wenzel WW (2013) Gel for simultaneous chemical imaging of anionic and cationic solutes using diffusive gradients in thin films. *Anal Chem* 85:12028–12036. <https://doi.org/10.1021/ac403050f>
- Kreuzeder A, Santner J, Scharsching V, Oburger E, Hoefler C, Hann S et al (2018) In situ observation of localized, sub-mm scale changes of phosphorus biogeochemistry in the rhizosphere. *Plant Soil* 424:573–589. <https://doi.org/10.1007/s11104-017-3542-0>
- Larner BL, Seen AJ (2005) Evaluation of paper-based diffusive gradients in thin film samplers for trace metal sampling. *Anal Chim Acta* 539:349–355. <https://doi.org/10.1016/j.aca.2005.03.007>
- Leermakers M, Gao Y, Navez J, Poffijn A, Croes K, Baeyens W (2009) Radium analysis by sector field ICP-MS in combination with the diffusive gradients in thin films (DGT) technique. *J Anal At Spectrom* 24:1115. <https://doi.org/10.1039/b821472g>
- Leermakers M, Phrommavanh V, Drozdak J, Gao Y, Nos J, Descostes M (2016) DGT as a useful monitoring tool for radionuclides and trace metals in environments impacted by uranium mining: case study of the Sagnes wetland in France. *Chemosphere* 155:142–151. <https://doi.org/10.1016/j.chemosphere.2016.03.138>
- Lehto NJ, Davison W, Zhang H (2012) The use of ultra-thin diffusive gradients in thin-films (DGT) devices for the analysis of trace metal dynamics in soils and sediments: a measurement and modelling approach. *Environ Chem* 9:415–423. <https://doi.org/10.1071/en12036>
- Lehto NJ, Larsen M, Zhang H, Glud RN, Davison W (2017) A mesocosm study of oxygen and trace metal dynamics in sediment microniches of reactive organic material. *Sci Rep* 7:11369. <https://doi.org/10.1038/s41598-017-10179-3>
- Lesven L, Gao Y, Billon G, Leermakers M, Ouddane B, Fischer J et al (2008) Early diagenetic processes aspects controlling the mobility of dissolved trace metals in three riverine sediment columns. *Sci Total Environ* 407:447–459. <https://doi.org/10.1016/j.scitotenv.2008.08.033>
- Li W, Zhao H, Teasdale PR, John R, Zhang S (2002) Application of a cellulose phosphate ion exchange membrane as a binding phase in the diffusive gradients in thin films technique for measurement of trace metals. *Anal Chim Acta* 464:331–339. [https://doi.org/10.1016/S0003-2670\(02\)00492-0](https://doi.org/10.1016/S0003-2670(02)00492-0)
- Li W, Teasdale PR, Zhang S, John R, Zhao H (2003) Application of a poly(4-styrenesulfonate) liquid binding layer for measurement of Cu<sup>2+</sup> and Cd<sup>2+</sup> with the diffusive gradients in thin-films technique. *Anal Chem* 75:2578–2583. <https://doi.org/10.1021/ac020658q>
- Li W, Zhao H, Teasdale PR, John R, Wang F (2005a) Metal speciation measurement by diffusive gradients in thin films technique with different binding phases. *Anal Chim Acta* 533:193–202. <https://doi.org/10.1016/j.aca.2004.11.019>
- Li W, Zhao H, Teasdale PR, Wang F (2005b) Trace metal speciation measurements in waters by the liquid binding phase DGT device. *Talanta* 67:571–578. <https://doi.org/10.1016/j.talanta.2005.03.018>
- Li W, Zhao J, Li C, Kiser S, Jack Cornett R (2006) Speciation measurements of uranium in alkaline waters using diffusive gradients in thin films technique. *Anal Chim Acta* 575:274–280. <https://doi.org/10.1016/j.aca.2006.05.092>
- Li H, Kang X, Li X, Li Q, Song J, Jiao N et al (2017) Heavy metals in surface sediments along the Weihai coast, China: distribution, sources and contamination assessment. *Mar Pollut Bull* 115:551–558. <https://doi.org/10.1016/j.marpolbul.2016.12.039>
- Lin J, Sun Q, Ding S, Wang D, Wang Y, Chen M et al (2017a) Mobile phosphorus stratification in sediments by aluminum immobilization. *Chemosphere* 186:644–651. <https://doi.org/10.1016/j.chemosphere.2017.08.005>
- Lin J, Sun Q, Ding S, Wang D, Wang Y, Tsang DCW (2017b) First observation of labile arsenic stratification in aluminum sulfate-amended sediments using high resolution Zr-oxide DGT. *Sci Total Environ* 609:304–310. <https://doi.org/10.1016/j.scitotenv.2017.07.165>
- Liu J, Feng X, Qiu G, Anderson CW, Yao H (2012) Prediction of methyl mercury uptake by rice plants (*Oryza sativa* L.) using the diffusive gradient in thin films technique. *Environ Sci Technol* 46:11013–11020. <https://doi.org/10.1021/es302187t>
- Liu S, Qin N, Song J, Zhang Y, Cai W, Zhang H et al (2016) A nanoparticulate liquid binding phase based DGT device for aquatic arsenic measurement. *Talanta* 160:225–232. <https://doi.org/10.1016/j.talanta.2016.06.064>
- Liu Q, Ding S, Chen X, Sun Q, Chen M, Zhang C (2018) Effects of temperature on phosphorus mobilization in sediments in

- microcosm experiment and in the field. *Appl Geochem* 88:158–166. <https://doi.org/10.1016/j.apgeochem.2017.07.018>
- Lucas A, Rate A, Zhang H, Salmon SU, Radford N (2012) Development of the diffusive gradients in thin films technique for the measurement of labile gold in natural waters. *Anal Chem* 84:6994–7000. <https://doi.org/10.1021/ac301003g>
- Lucas AR, Reid N, Salmon SU, Rate AW (2014) Quantitative assessment of the distribution of dissolved Au, As and Sb in groundwater using the diffusive gradients in thin films technique. *Environ Sci Technol* 48:12141–12149. <https://doi.org/10.1021/es502468d>
- Luidner CD, Crusius J, Playle RC, Curtis PJ (2004) Influence of natural organic matter source on copper speciation as demonstrated by Cu binding to fish gills, by ion selective electrode, and by DGT gel sampler. *Environ Sci Technol* 38:2865–2872. <https://doi.org/10.1021/es030566y>
- Luko KS, Menegário AA, Suárez CA, Tafurtcardona M, Pedrobom JH, Rolisola AM et al (2017) In situ determination of V(V) by diffusive gradients in thin films and inductively coupled plasma mass spectrometry techniques using amberlite IRA-410 resin as a binding layer. *Anal Chim Acta* 950:32–40. <https://doi.org/10.1016/j.aca.2016.11.031>
- Luo J, Zhang H, Santner J, Davison W (2010) Performance characteristics of diffusive gradients in thin films equipped with a binding gel layer containing precipitated ferrihydrite for measuring arsenic(V), selenium(VI), vanadium(V), and antimony(V). *Anal Chem* 82:8903–8909. <https://doi.org/10.1021/ac101676w>
- Luo J, Cheng H, Ren J, Davison W, Zhang H (2014) Mechanistic insights from DGT and soil solution measurements on the uptake of Ni and Cd by radish. *Environ Sci Technol* 48:7305–7313. <https://doi.org/10.1021/es500173e>
- Ma WW, Zhu MX, Yang GP, Li T (2017) In situ, high-resolution DGT measurements of dissolved sulfide, iron and phosphorus in sediments of the East China Sea: insights into phosphorus mobilization and microbial iron reduction. *Mar Pollut Bull* 124:400–410. <https://doi.org/10.1016/j.marpolbul.2017.07.056>
- Mason S, Hamon R, Nolan A, Zhang H, Davison W (2005) Performance of a mixed binding layer for measuring anions and cations in a single assay using the diffusive gradients in thin films technique. *Anal Chem* 77:6339–6346. <https://doi.org/10.1021/ac0507183>
- Mason S, Hamon R, Zhang H, Anderson J (2008) Investigating chemical constraints to the measurement of phosphorus in soils using diffusive gradients in thin films (DGT) and resin methods. *Talanta* 74:779–787. <https://doi.org/10.1016/j.talanta.2007.07.005>
- Menegario AA, Yabuki LNM, Luko KS, Williams PN, Blackburn DM (2017) Use of diffusive gradient in thin films for in situ measurements: a review on the progress in chemical fractionation, speciation and bioavailability of metals in waters. *Anal Chim Acta* 983:54–66. <https://doi.org/10.1016/j.aca.2017.06.041>
- Menegário AA, Tonello PS, Durrant SF (2010) Use of *Saccharomyces cerevisiae* immobilized in agarose gel as a binding agent for diffusive gradients in thin films. *Anal Chim Acta* 683:107–112. <https://doi.org/10.1016/j.aca.2010.10.016>
- Menezes-Blackburn D, Zhang H, Stutter M, Giles CD, Darch T, George TS et al (2016) A holistic approach to understanding the desorption of phosphorus in soils. *Environ Sci Technol* 50:3371–3381. <https://doi.org/10.1021/acs.est.5b05395>
- Mengistu H, Roeyset O, Tessema A, Abiye TA, Demlie MB (2012) Diffusive gradient in thin-films (DGT) as risk assessment and management tools in the Central Witwatersrand Goldfield, South Africa. *Water SA* 38:15–22. <https://doi.org/10.4314/wsa.v38i1.3>
- Menzies NW, Kusumo B, Moody PW (2005) Assessment of P availability in heavily fertilized soils using the diffusive gradient in thin films (DGT) technique. *Plant Soil* 269:1–9. <https://doi.org/10.1007/s11104-004-1725-y>
- Moßhammer M, Strobl M, Kühl M, Klimant I, Borisov SM, Koren K (2016) Design and application of an optical sensor for simultaneous imaging of pH and dissolved O<sub>2</sub> with low cross-talk. *ACS Sens* 1:681–687. <https://doi.org/10.1021/acssensors.6b00071>
- Naylor C, Davison W, Motelica-Heino M, Van Den Berg GA, Van Der Heijdt LM (2004) Simultaneous release of sulfide with Fe, Mn, Ni and Zn in marine harbour sediment measured using a combined metal/sulfide DGT probe. *Sci Total Environ* 328:275–286. <https://doi.org/10.1016/j.scitotenv.2004.02.008>
- Naylor C, Davison W, Motelica-Heino M, Van Den Berg GA, Van Der Heijdt LM (2006) Potential kinetic availability of metals in sulphidic freshwater sediments. *Sci Total Environ* 357:208–220. <https://doi.org/10.1016/j.scitotenv.2005.04.034>
- Oporto C, Smolders E, Degryse F, Verheyen L, Vandecasteele C (2008) DGT-measured fluxes explain the chloride-enhanced cadmium uptake by plants at low but not at high Cd supply. *Plant Soil* 318:127–135. <https://doi.org/10.1007/s11104-008-9823-x>
- Osterlund H, Chlot S, Faarinen M, Widerlund A, Rodushkin I, Ingri J et al (2010) Simultaneous measurements of As, Mo, Sb, V and W using a ferrihydrite diffusive gradients in thin films (DGT) device. *Anal Chim Acta* 682:59–65. <https://doi.org/10.1016/j.aca.2010.09.049>
- Pages A, Teasdale PR, Robertson D, Bennett WW, Schafer J, Welsh DT (2011) Representative measurement of two-dimensional reactive phosphate distributions and co-distributed iron(II) and sulfide in seagrass sediment porewaters. *Chemosphere* 85:1256–1261. <https://doi.org/10.1016/j.chemosphere.2011.07.020>
- Pages A, Welsh DT, Robertson D, Panther JG, Schäfer J, Tomlinson RB et al (2012) Diurnal shifts in co-distributions of sulfide and iron(II) and profiles of phosphate and ammonium in the rhizosphere of *Zostera capricorni*. *Estuar Coast Shelf Sci* 115:282–290. <https://doi.org/10.1016/j.ecss.2012.09.011>
- Pages A, Welsh DT, Teasdale PR, Grice K, Vacher M, Bennett WW et al (2014) Diel fluctuations in solute distributions and biogeochemical cycling in a hypersaline microbial mat from Shark Bay, WA. *Mar Chem* 167:102–112. <https://doi.org/10.1016/j.marchem.2014.05.003>
- Pan Y, Guan DX, Zhao D, Luo J, Zhang H, Davison W et al (2015) Novel speciation method based on diffusive gradients in thin-films for in situ measurement of Cr(VI) in aquatic systems. *Environ Sci Technol* 49:14267–14273. <https://doi.org/10.1021/acs.est.5b03742>
- Panther JG, Stillwell KP, Powell KJ, Downard AJ (2008) Perfluorosulfonated ionomer-modified diffusive gradients in thin films: tool for inorganic arsenic speciation analysis. *Anal Chem* 80:9806–9811. <https://doi.org/10.1021/ac801678u>
- Panther JG, Teasdale PR, Bennett WW, Welsh DT, Zhao H (2010) Titanium dioxide-based DGT technique for in situ measurement of dissolved reactive phosphorus in fresh and marine waters. *Environ Sci Technol* 44:9419–9424. <https://doi.org/10.1021/es1027713>
- Panther JG, Teasdale PR, Bennett WW, Welsh DT, Zhao H (2011) Comparing dissolved reactive phosphorus measured by DGT with ferrihydrite and titanium dioxide adsorbents: anionic interferences, adsorbent capacity and deployment time. *Anal Chim Acta* 698:20–26. <https://doi.org/10.1016/j.aca.2011.04.049>
- Panther JG, Stewart RR, Teasdale PR, Bennett WW, Welsh DT, Zhao H (2013) Titanium dioxide-based DGT for measuring dissolved As(V), V(V), Sb(V), Mo(VI) and W(VI) in water. *Talanta* 105:80–86. <https://doi.org/10.1016/j.talanta.2012.11.070>
- Panther JG, Bennett WW, Welsh DT, Teasdale PR (2014) Simultaneous measurement of trace metal and oxyanion concentrations in water using diffusive gradients in thin films with a Chelex–Metsorb mixed binding layer. *Anal Chem* 86:427–434. <https://doi.org/10.1021/ac402247j>

- Parker R, Bolam T, Barry J, Mason C, Kroger S, Warford L et al (2017) The application of diffusive gradients in thin films (DGT) for improved understanding of metal behaviour at marine disposal sites. *Sci Total Environ* 575:1074–1086. <https://doi.org/10.1016/j.scitotenv.2016.09.183>
- Pedrobom JH, Eismann CE, Menegário AA, Galhardi JA, Luko KS, Dourado TdA et al (2017) In situ speciation of uranium in treated acid mine drainage using the diffusion gradients in thin films technique (DGT). *Chemosphere* 169:249–256. <https://doi.org/10.1016/j.chemosphere.2016.11.082>
- Pelcova P, Docekalova H, Kleckerova A (2014) Development of the diffusive gradient in thin films technique for the measurement of labile mercury species in waters. *Anal Chim Acta* 819:42–48. <https://doi.org/10.1016/j.aca.2014.02.013>
- Pelcova P, Docekalova H, Kleckerova A (2015) Determination of mercury species by the diffusive gradient in thin film technique and liquid chromatography–atomic fluorescence spectrometry after microwave extraction. *Anal Chim Acta* 866:21–26. <https://doi.org/10.1016/j.aca.2015.01.043>
- Peng Q, Wang M, Cui Z, Huang J, Chen C, Guo L et al (2017) Assessment of bioavailability of selenium in different plant-soil systems by diffusive gradients in thin-films (DGT). *Environ Pollut* 225:637–643. <https://doi.org/10.1016/j.envpol.2017.03.036>
- Pescim GF, Marrach G, Vannuci-Silva M, Souza LA, Menegario AA (2012) Speciation of lead in seawater and river water by using *Saccharomyces cerevisiae* immobilized in agarose gel as a binding agent in the diffusive gradients in thin films technique. *Anal Bioanal Chem* 404:1581–1588. <https://doi.org/10.1007/s00216-012-6248-4>
- Philipps RR, Xu X, Mills GL, Bringolf RB (2018) Impact of natural organic matter and increased water hardness on DGT prediction of copper bioaccumulation by yellow lampmussel (*Lampsilis cariosa*) and fathead minnow (*Pimephales promelas*). *Environ Pollut* 241:451–458. <https://doi.org/10.1016/j.envpol.2018.05.059>
- Pichette C, Zhang H, Davison W, Sauve S (2007) Preventing biofilm development on DGT devices using metals and antibiotics. *Talanta* 72:716–722. <https://doi.org/10.1016/j.talanta.2006.12.014>
- Pichette C, Zhang H, Sauvé S (2009) Using diffusive gradients in thin-films for in situ monitoring of dissolved phosphate emissions from freshwater aquaculture. *Aquaculture* 286:198–202. <https://doi.org/10.1016/j.aquaculture.2008.09.025>
- Predit S, Gao Y, Faiboon A, De Galan S, Baeyens W, Leermakers M (2013) Application of DET (diffusive equilibrium in thin films) and DGT (diffusive gradients in thin films) techniques in the study of the mobility of sediment-bound metals in the outer section of Songkhla Lake, Southern Thailand. *Environ Monit Assess* 185:4207–4220. <https://doi.org/10.1007/s10661-012-2862-z>
- Price HL, Teasdale PR, Jolley DF (2013) An evaluation of ferrihydrite– and Metsorb™–DGT techniques for measuring oxyanion species (As, Se, V, P): effective capacity, competition and diffusion coefficients. *Anal Chim Acta* 803:56–65. <https://doi.org/10.1016/j.aca.2013.07.001>
- Qin W, Gu Y, Wang G, Wu T, Zhang H, Tang X et al (2018) Zirconium metal organic frameworks-based DGT technique for in situ measurement of dissolved reactive phosphorus in waters. *Water Res* 147:223–232. <https://doi.org/10.1016/j.watres.2018.10.003>
- Ren M, Wang Y, Ding S, Yang L, Sun Q, Zhang L (2018a) Development of a new diffusive gradients in thin films (DGT) method for the simultaneous measurement of  $\text{CH}_3\text{Hg}^+$  and  $\text{Hg}^{2+}$ . *New J Chem* 42:7976–7983. <https://doi.org/10.1039/c8nj00211h>
- Ren S, Tao J, Tan F, Cui Y, Li X, Chen J et al (2018b) Diffusive gradients in thin films based on MOF-derived porous carbon binding gel for in situ measurement of antibiotics in waters. *Sci Total Environ* 645:482–490. <https://doi.org/10.1016/j.scitotenv.2018.07.013>
- Robertson D, Teasdale PR, Welsh DT (2008) A novel gel-based technique for the high resolution, two-dimensional determination of iron (II) and sulfide in sediment. *Limnol Oceanogr Methods* 6:502–512. <https://doi.org/10.4319/lom.2008.6.502>
- Robertson D, Welsh DT, Teasdale PR (2009) Investigating biogenic heterogeneity in coastal sediments with two-dimensional measurements of iron(II) and sulfide. *Environ Chem* 6:60–69. <https://doi.org/10.1071/en08059>
- Rolisola AMCM, Suárez CA, Menegário AA, Gastmans D, Kiang CH, Colaço CD et al (2014) Speciation analysis of inorganic arsenic in river water by Amberlite IRA 910 resin immobilized in a polyacrylamide gel as a selective binding agent for As(v) in diffusive gradient thin film technique. *Analyst* 139:4373. <https://doi.org/10.1039/c4an00555d>
- Santner J, Prohaska T, Luo J, Zhang H (2010) Ferrihydrite containing gel for chemical imaging of labile phosphate species in sediments and soils using diffusive gradients in thin films. *Anal Chem* 82:7668–7674. <https://doi.org/10.1021/ac101450j>
- Santner J, Larsen M, Kreuzeder A, Glud RN (2015) Two decades of chemical imaging of solutes in sediments and soils: a review. *Anal Chim Acta* 878:9–42. <https://doi.org/10.1016/j.aca.2015.02.006>
- Scally S, Davison W, Zhang H (2003) In situ measurements of dissociation kinetics and labilities of metal complexes in solution using DGT. *Environ Sci Technol* 37:1379–1384. <https://doi.org/10.1021/es0202006>
- Scally S, Davison W, Zhang H (2006) Diffusion coefficients of metals and metal complexes in hydrogels used in diffusive gradients in thin films. *Anal Chim Acta* 558:222–229. <https://doi.org/10.1016/j.aca.2005.11.020>
- Shiva AH, Teasdale PR, Bennett WW, Welsh DT (2015) A systematic determination of diffusion coefficients of trace elements in open and restricted diffusive layers used by the diffusive gradients in a thin film technique. *Anal Chim Acta* 888:146–154. <https://doi.org/10.1016/j.aca.2015.07.027>
- Shiva AH, Teasdale PR, Welsh DT, Bennett WW (2017) Evaluation of the DGT technique for selective measurement of aluminium and trace metal concentrations in an acid drainage-impacted coastal waterway. *Environ Sci Proc Impacts* 19:742–751. <https://doi.org/10.1039/c6em00276e>
- Sochaczewski L, Tych W, Davison B, Zhang H (2007) 2D DGT induced fluxes in sediments and soils (2D DIFS). *Environ Model Softw* 22:14–23. <https://doi.org/10.1016/j.envsoft.2005.09.008>
- Song Z, Dong L, Shan B, Tang W (2018a) Assessment of potential bioavailability of heavy metals in the sediments of land–freshwater interfaces by diffusive gradients in thin films. *Chemosphere* 191:218–225. <https://doi.org/10.1016/j.chemosphere.2017.10.048>
- Song Z, Shan B, Tang W (2018b) Evaluating the diffusive gradients in thin films technique for the prediction of metal bioaccumulation in plants grown in river sediments. *J Hazard Mater* 344:360–368. <https://doi.org/10.1016/j.jhazmat.2017.10.049>
- Stahl H, Warnken KW, Sochaczewski L, Glud RN, Davison W, Zhang H (2012) A combined sensor for simultaneous high resolution 2-D imaging of oxygen and trace metals fluxes. *Limnol Oceanogr Methods* 10:389–401. <https://doi.org/10.4319/lom.2012.10.389>
- Stockdale A, Davison W, Zhang H (2008) High-resolution two-dimensional quantitative analysis of phosphorus, vanadium and arsenic, and qualitative analysis of sulfide, in a freshwater sediment. *Environ Chem* 5:143. <https://doi.org/10.1071/en07096>
- Stockdale A, Davison W, Zhang H (2010) 2D simultaneous measurement of the oxyanions of P, V, As, Mo, Sb, W and U. *J Environ Monit* 12:981–984. <https://doi.org/10.1039/b925627j>
- Suárez CA, de Simone TV, Menegário AA, Rolisola AMCM, Luko KS, Gastmans D et al (2016) In situ redox speciation analysis of chromium in water by diffusive gradients in thin films using a

- DE81 anion exchange membrane. *Talanta* 154:299–303. <https://doi.org/10.1016/j.talanta.2016.03.085>
- Sui DP, Fan HT, Li J, Li Y, Li Q, Sun T (2013) Application of poly (ethyleneimine) solution as a binding agent in DGT technique for measurement of heavy metals in water. *Talanta* 114:276–282. <https://doi.org/10.1016/j.talanta.2013.05.027>
- Sun Q, Chen Y, Xu D, Wang Y, Ding S (2013) Investigation of potential interferences on the measurement of dissolved reactive phosphate using zirconium oxide-based DGT technique. *J Environ Sci* 25:1592–1600. [https://doi.org/10.1016/s1001-0742\(12\)60140-5](https://doi.org/10.1016/s1001-0742(12)60140-5)
- Sun Q, Chen J, Zhang H, Ding S, Li Z, Williams PN et al (2014) Improved diffusive gradients in thin films (DGT) measurement of total dissolved inorganic arsenic in waters and soils using a hydrous zirconium oxide binding layer. *Anal Chem* 86:3060–3067. <https://doi.org/10.1021/ac404025e>
- Sun Q, Ding S, Zhang L, Chen M, Zhang C (2017) A millimeter-scale observation of the competitive effect of phosphate on promotion of arsenic mobilization in sediments. *Chemosphere* 180:285–294. <https://doi.org/10.1016/j.chemosphere.2017.04.010>
- Tafurt-Cardona M, Eismann CE, Suarez CA, Menegario AA, Silva Luko K, Sargentini Junior E (2015) In situ selective determination of methylmercury in river water by diffusive gradient in thin films technique (DGT) using baker's yeast (*Saccharomyces cerevisiae*) immobilized in agarose gel as binding phase. *Anal Chim Acta* 887:38–44. <https://doi.org/10.1016/j.aca.2015.07.035>
- Teasdale PR, Hayward S, Davison W (1999) In situ, high-resolution measurement of dissolved sulfide using diffusive gradients in thin films with computer-imaging densitometry. *Anal Chem* 71:2186–2191. <https://doi.org/10.1021/ac981329u>
- Tian K, Xing Z, Liu G, Wang H, Jia M, Hu W et al (2018) Cadmium phytoavailability under greenhouse vegetable production system measured by diffusive gradients in thin films (DGT) and its implications for the soil threshold. *Environ Pollut* 241:412–421. <https://doi.org/10.1016/j.envpol.2018.05.086>
- Turner GS, Mills GA, Teasdale PR, Burnett JL, Amos S, Fones GR (2012) Evaluation of DGT techniques for measuring inorganic uranium species in natural waters: interferences, deployment time and speciation. *Anal Chim Acta* 739:37–46. <https://doi.org/10.1016/j.aca.2012.06.011>
- Tusseau-Vuillemin MH, Gilbin R, Bakkaus E, Garric J (2004) Performance of diffusion gradient in thin films to evaluate the toxic fraction of copper to *Daphnia magna*. *Environ Toxicol Chem* 23:2154–2161. <https://doi.org/10.1897/03-202a>
- Uher E, Zhang H, Santos S, Tusseau-Vuillemin MH, Gourlay-France C (2012) Impact of biofouling on diffusive gradient in thin film measurements in water. *Anal Chem* 84:3111–3118. <https://doi.org/10.1021/ac2028535>
- Uher E, Besse J-P, Delaigue O, Husson F, Lebrun JD (2017) Comparison of the metal contamination in water measured by diffusive gradient in thin film (DGT), biomonitoring and total metal dissolved concentration at a national scale. *Appl Geochem* 88:247–257. <https://doi.org/10.1016/j.apgeochem.2017.05.003>
- Wang Y, Yang L, Kong L, Liu E, Wang L, Zhu J (2015) Spatial distribution, ecological risk assessment and source identification for heavy metals in surface sediments from Dongping Lake, Shandong, East China. *CATENA* 125:200–205. <https://doi.org/10.1016/j.catena.2014.10.023>
- Wang Y, Ding S, Gong M, Xu S, Xu W, Zhang C (2016) Diffusion characteristics of agarose hydrogel used in diffusive gradients in thin films for measurements of cations and anions. *Anal Chim Acta* 945:47–56. <https://doi.org/10.1016/j.aca.2016.10.003>
- Wang Y, Ding S, Shi L, Gong M, Xu S, Zhang C (2017a) Simultaneous measurements of cations and anions using diffusive gradients in thin films with a ZrO–Chelex mixed binding layer. *Anal Chim Acta* 972:1–11. <https://doi.org/10.1016/j.aca.2017.04.007>
- Wang Y, Ding S, Wang D, Sun Q, Lin J, Shi L et al (2017b) Static layer: a key to immobilization of phosphorus in sediments amended with lanthanum modified bentonite (Phoslock®). *Chem Eng J* 325:49–58. <https://doi.org/10.1016/j.cej.2017.05.039>
- Wang S, Wu Z, Luo J (2018) Transfer mechanism, uptake kinetic process, and bioavailability of P, Cu, Cd, Pb, and Zn in macrophyte rhizosphere using diffusive gradients in thin films. *Environ Sci Technol* 52:1096–1108. <https://doi.org/10.1021/acs.est.7b01578>
- Warnken KW, Zhang H, Davison W (2004a) Performance characteristics of suspended particulate reagent-iminodiacetate as a binding agent for diffusive gradients in thin films. *Anal Chim Acta* 508:41–51. <https://doi.org/10.1016/j.aca.2003.11.051>
- Warnken KW, Zhang H, Davison W (2004b) Analysis of polyacrylamide gels for trace metals using diffusive gradients in thin films and laser ablation inductively coupled plasma mass spectrometry. *Anal Chem* 76:6077–6084. <https://doi.org/10.1021/ac0400358>
- Warnken KW, Zhang H, Davison W (2005) Trace metal measurements in low ionic strength synthetic solutions by diffusive gradients in thin films. *Anal Chem* 77:5440–5446. <https://doi.org/10.1021/ac050045o>
- Warnken KW, Zhang H, Davison W (2006) Accuracy of the diffusive gradients in thin-films technique: diffusive boundary layer and effective sampling area considerations. *Anal Chem* 78:3780–3787. <https://doi.org/10.1021/ac060139d>
- Weltje L, Hollander WD, Wolterbeek HT (2003) Adsorption of metals to membrane filters in view of their speciation in nutrient solution. *Environ Toxicol Chem* 22:265–271. <https://doi.org/10.1002/etc.5620220205>
- Widerlund A, Davison W (2007) Size and density distribution of sulfide-producing microniches in lake sediments. *Environ Sci Technol* 41:8044–8049. <https://doi.org/10.1021/es071510x>
- Widerlund A, Nowell GM, Davison W, Pearson DG (2012) High-resolution measurements of sulphur isotope variations in sediment pore-waters by laser ablation multicollector inductively coupled plasma mass spectrometry. *Chem Geol* 291:278–285. <https://doi.org/10.1016/j.chemgeo.2011.10.018>
- Williams PN, Zhang H, Davison W, Zhao S, Lu Y, Dong F et al (2012) Evaluation of in situ DGT measurements for predicting the concentration of Cd in chinese field-cultivated rice: impact of soil Cd:Zn ratios. *Environ Sci Technol* 46:8009–8016. <https://doi.org/10.1021/es301195h>
- Williams PN, Santner J, Larsen M, Lehto NJ, Oburger E, Wenzel W et al (2014) Localized flux maxima of arsenic, lead, and iron around root apices in flooded lowland rice. *Environ Sci Technol* 48:8498–8506. <https://doi.org/10.1021/es501127k>
- Wu Z, Wang S (2017) Release mechanism and kinetic exchange for phosphorus (P) in lake sediment characterized by diffusive gradients in thin films (DGT). *J Hazard Mater* 331:36–44. <https://doi.org/10.1016/j.jhazmat.2017.02.024>
- Wu Z, He M, Lin C (2011) In situ measurements of concentrations of Cd, Co, Fe and Mn in estuarine porewater using DGT. *Environ Pollut* 159:1123–1128. <https://doi.org/10.1016/j.envpol.2011.02.015>
- Wu Z, Wang S, He M, Wu F (2014) The measurement of metals by diffusive gradients in thin films (DGT) at sediment/water interface (SWI) of bay and remobilization assessment. *Environ Earth Sci* 73:6283–6295. <https://doi.org/10.1007/s12665-014-3851-z>
- Wu T, Wang G, Zhang Y, Kong M, Zhao H (2017) Determination of mercury in aquatic systems by DGT device using thiol-modified carbon nanoparticle suspension as the liquid binding phase. *New J Chem* 41:10305–10311. <https://doi.org/10.1039/c7nj02007d>
- Wu Z, Wang S, Luo J (2018) Transfer kinetics of phosphorus (P) in macrophyte rhizosphere and phytoremoval performance for lake sediments using DGT technique. *J Hazard Mater* 350:189–200. <https://doi.org/10.1016/j.jhazmat.2018.02.005>



- Xie H, Chen J, Chen Q, Chen CL, Du J, Tan F et al (2018a) Development and evaluation of diffusive gradients in thin films technique for measuring antibiotics in seawater. *Sci Total Environ* 618:1605–1612. <https://doi.org/10.1016/j.scitotenv.2017.09.330>
- Xie H, Chen Q, Chen J, Chen CL, Du J (2018b) Investigation and application of diffusive gradients in thin-films technique for measuring endocrine disrupting chemicals in seawaters. *Chemosphere* 200:351–357. <https://doi.org/10.1016/j.chemosphere.2018.02.096>
- Xing X, Ding S, Liu L, Chen M, Yan W, Zhao L et al (2018) Direct evidence for the enhanced acquisition of phosphorus in the rhizosphere of aquatic plants: a case study on *Vallisneria spiralis*. *Sci Total Environ* 616–617:386–396. <https://doi.org/10.1016/j.scitotenv.2017.10.304>
- Xu D, Ding S, Sun Q, Zhong J, Wu W, Jia F (2012a) Evaluation of in situ capping with clean soils to control phosphate release from sediments. *Sci Total Environ* 438:334–341. <https://doi.org/10.1016/j.scitotenv.2012.08.053>
- Xu D, Wu W, Ding S, Sun Q, Zhang C (2012b) A high-resolution dialysis technique for rapid determination of dissolved reactive phosphate and ferrous iron in pore water of sediments. *Sci Total Environ* 421–422:245–252. <https://doi.org/10.1016/j.scitotenv.2012.01.062>
- Xu D, Chen Y, Ding S, Sun Q, Wang Y, Zhang C (2013) Diffusive gradients in thin films technique equipped with a mixed binding gel for simultaneous measurements of dissolved reactive phosphorus and dissolved iron. *Environ Sci Technol* 47:10477–10484. <https://doi.org/10.1021/es401822x>
- Xu L, Sun Q, Ding S, Gong M, Zhang C (2017) Simultaneous measurements of arsenic and sulfide using diffusive gradients in thin films technique (DGT). *Environ Geochem Health*. <https://doi.org/10.1007/s10653-017-9968-8>
- Xu Q, Gao L, Peng W, Gao B, Xu D, Sun K (2018) Assessment of labile Zn in reservoir riparian soils using DGT, DIFS, and sequential extraction. *Ecotoxicol Environ Saf* 160:184–190. <https://doi.org/10.1016/j.ecoenv.2018.05.039>
- Yabuki LNM, Colaço CD, Menegário AA, Domingos RN, Chang HK, Pascoaloto D (2014) Evaluation of diffusive gradients in thin films technique (DGT) for measuring Al, Cd Co, Cu, Mn, Ni, and Zn in Amazonian rivers. *Environ Monit Assess* 186:961–969. <https://doi.org/10.1007/s10661-013-3430-x>
- Yang Z, Guo W, Fan Y, Lin C, He M (2012) High-resolution profiles of iron, manganese, cobalt, cadmium, copper and zinc in the pore water of estuarine sediment. *Int J Environ Sci Technol* 10:275–282. <https://doi.org/10.1007/s13762-012-0110-2>
- Yao Y, Wang C, Wang P, Miao L, Hou J, Wang T et al (2016) Zr oxide-based coloration technique for two-dimensional imaging of labile Cr(VI) using diffusive gradients in thin films. *Sci Total Environ* 566–567:1632–1639. <https://doi.org/10.1016/j.scitotenv.2016.06.065>
- Yuan Y, Ding S, Wang Y, Zhang L, Ren M, Zhang C (2018) Simultaneous measurement of fifteen rare earth. *Anal Chim Acta*. <https://doi.org/10.1016/j.aca.2018.05.067>
- Zarrouk S, Bermond A, Kolsi Benzina N, Sappin-Didier V, Denaix L (2013) Diffusive gradient in thin-film (DGT) models Cd and Pb uptake by plants growing on soils amended with sewage sludge and urban compost. *Environ Chem Lett* 12:191–199. <https://doi.org/10.1007/s10311-013-0431-5>
- Zhang H, Davison W (1995) Performance characteristics of diffusion gradients in thin films for the in situ measurement of trace metals in aqueous solution. *Anal Chem* 67:3391–3400. <https://doi.org/10.1021/ac00115a005>
- Zhang H, Davison W (1999) Diffusional characteristics of hydrogels used in DGT and DET techniques. *Anal Chim Acta* 398:329–340. [https://doi.org/10.1016/s0003-2670\(99\)00458-4](https://doi.org/10.1016/s0003-2670(99)00458-4)
- Zhang H, Davison W (2015) Use of diffusive gradients in thin-films for studies of chemical speciation and bioavailability. *Environ Chem* 12:85. <https://doi.org/10.1071/en14105>
- Zhang H, Davison W, Gadi R, Kobayashi T (1998a) In situ measurement of dissolved phosphorus in natural waters using DGT. *Anal Chim Acta* 370:29–38. [https://doi.org/10.1016/s0003-2670\(98\)00250-5](https://doi.org/10.1016/s0003-2670(98)00250-5)
- Zhang H, Davison W, Knight B, Steve M (1998b) In situ measurements of solution concentrations and fluxes of trace metals in soils using DGT. *Environ Sci Technol* 32:704–710. <https://doi.org/10.1021/es9704388>
- Zhang H, Davison W, Mortimer RJ, Krom MD, Hayes PJ, Davies IM (2002) Localised remobilization of metals in a marine sediment. *Sci Total Environ* 296:175–187. [https://doi.org/10.1016/s0048-9697\(02\)00078-5](https://doi.org/10.1016/s0048-9697(02)00078-5)
- Zhang H, Lombi E, Smolders E, McGrath S (2004) Kinetics of Zn release in soils and prediction of Zn concentration in plants using diffusive gradients in thin films. *Environ Sci Technol* 38:3608–3613. <https://doi.org/10.1021/es0352597>
- Zhang C, Ding S, Xu D, Tang Y, Wong MH (2014) Bioavailability assessment of phosphorus and metals in soils and sediments: a review of diffusive gradients in thin films (DGT). *Environ Monit Assess* 186:7367–7378. <https://doi.org/10.1007/s10661-014-3933-0>
- Zhang L, Sun Q, Ding S, Cheng X, Liu Q, Zhang C (2017a) Characterization of arsenic availability in dry and flooded soils using sequential extraction and diffusive gradients in thin films (DGT) techniques. *Environ Sci Pollut Res Int* 24:15727–15734. <https://doi.org/10.1007/s11356-017-9190-3>
- Zhang S, Williams PN, Zhou CY, Ma LQ, Luo J (2017b) Extending the functionality of the slurry ferrihydrite–DGT method: performance evaluation for the measurement of vanadate, arsenate, antimonate and molybdate in water. *Chemosphere* 184:812–819. <https://doi.org/10.1016/j.chemosphere.2017.06.062>
- Zhang Y, Song J, Zhou H, Zhang Y, Wang G (2018a) Novel Fe<sub>3</sub>O<sub>4</sub> nanoparticles-based DGT device for dissolved reactive phosphate measurement. *New J Chem* 42:2874–2881. <https://doi.org/10.1039/c7nj04464j>
- Zhang Y, Zhang T, Guo C, Hou S, Hua Z, Lv J et al (2018b) Development and application of the diffusive gradients in thin films technique for simultaneous measurement of methcathinone and ephedrine in surface river water. *Sci Total Environ* 618:284–290. <https://doi.org/10.1016/j.scitotenv.2017.11.068>
- Zheng JL, Guan DX, Luo J, Zhang H, Davison W, Cui XY et al (2015) Activated charcoal based diffusive gradients in thin films for in situ monitoring of bisphenols in waters. *Anal Chem* 87:801–807. <https://doi.org/10.1021/ac503814j>
- Zhou C, van de Velde S, Baeyens W, Gao Y (2018) Comparison of Chelex based resins in diffusive gradients in thin-film for high resolution assessment of metals. *Talanta* 186:397–405. <https://doi.org/10.1016/j.talanta.2018.04.085>