

POSTER PRESENTATION

Open Access

DrugScorePPI for scoring protein-protein interactions: improving a knowledge-based scoring function by atomtype-based QSAR

Dennis M Krüger*, Holger Gohlke

From 5th German Conference on Cheminformatics: 23. CIC-Workshop
Goslar, Germany. 8-10 November 2009

Protein-protein complexes are known to play key roles in many cellular processes. Therefore, knowledge of the three-dimensional structure of protein-complexes is of fundamental importance. A key goal in protein-protein docking is to identify near-native protein-complex structures. In this work, we address this problem by deriving a knowledge-based scoring function from protein-protein complex structures and further fine-tuning of the statistical potentials against experimentally determined alanine-scanning results.

Based on the formalism of the DrugScore approach¹, distance-dependent pair potentials are derived from 850 crystallographically determined protein-protein complexes². These DrugScorePPI potentials display quantitative differences compared to those of DrugScore, which was derived from protein-ligand complexes. When used as an objective function to score a non-redundant dataset of 54 targets with “unbound perturbation” solutions, DrugscorePPI was able to rank a near-native solution in the top ten in 89% and in the top five in 65% of the cases. Applied to a dataset of “unbound docking” solutions, DrugscorePPI was able to rank a near-native solution in the top ten in 100% and in the top five in 67% of the cases. Furthermore, Drugscore-PPI was used for computational alanine-scanning of a dataset of 18 targets with a total of 309 mutations to predict changes in the binding free energy upon mutations in the interface. Computed and experimental values showed a correlation of $R^2 = 0.34$. To improve the predictive power, a QSAR-model was built based on 24 residue-specific atom types that improves the correlation coefficient to a value of 0.53, with a root mean

square deviation of 0.89 kcal/mol. A Leave-One-Out analysis yields a correlation coefficient of 0.41. This clearly demonstrates the robustness of the model. The application to an independent validation dataset of alanine-mutations was used to show the predictive power of the method and yields a correlation coefficient of 0.51. Based on these findings, Drugscore-PPI was used to successfully identify hotspots in multiple protein-interfaces. These results suggest that DrugscorePPI is an adequate method to score protein-protein interactions.

Published: 4 May 2010

References

1. Gohlke H, Hendlich M, Klebe G: Knowledge-based scoring function to predict protein-ligand interactions. *J Mol Biol* 2000, **295**(2):337-356.
2. Huang SY, Zou X: An iterative knowledge-based scoring function for protein-protein recognition. *Proteins* 2008, **72**(2):557-579.

doi:10.1186/1758-2946-2-S1-P20

Cite this article as: Krüger and Gohlke: DrugScorePPI for scoring protein-protein interactions: improving a knowledge-based scoring function by atomtype-based QSAR. *Journal of Cheminformatics* 2010 **2**(Suppl 1):P20.

Publish with **ChemistryCentral** and every scientist can read your work free of charge

“Open access provides opportunities to our colleagues in other parts of the globe, by allowing anyone to view the content free of charge.”

W. Jeffery Hurst, The Hershey Company.

- available free of charge to the entire scientific community
- peer reviewed and published immediately upon acceptance
- cited in PubMed and archived on PubMed Central
- yours — you keep the copyright

Submit your manuscript here:
<http://www.chemistrycentral.com/manuscript/>



ChemistryCentral

Heinrich-Heine-University, Computational Pharmaceutical Chemistry, 40225 Düsseldorf, Germany

