

Public Works Management & Policy

Early Bill-of-Quantities estimation of concrete road bridges:

| | |
|------------------|--|
| Journal: | <i>Public Works Management & Policy</i> |
| Manuscript ID | PWMP-17-007.R1 |
| Manuscript Type: | Research & Theory |
| Keywords: | Artificial Neural Networks, Bill-of-Quantities, Bridge, Construction cost estimate, Infrastructure: planning |
| | |

SCHOLARONE™
Manuscripts

Review

Early Bill-of-Quantities estimation of concrete road bridges:

An artificial intelligence-based application

Abstract

Accurate cost estimation in the preliminary stages of project development is critical for making informed planning decisions. However, such early estimates are typically restricted by limited information. In this paper, the widely recognised intelligence of Feed-Forward Artificial Neural Networks (FFANNs) is used to process actual data from 68 concrete road bridges and provide a surrogate model for the accurate estimation of the Bill-of-Quantities (BoQ). Specifically, two FFANNs are trained to estimate the superstructure and piers concrete and steelbased on the construction method and the bridge dimensions. As the relevant metrics demonstrate, the FFANNs capture very well the complex interrelations in the dataset and produce highly accurate estimates. Furthermore, their generalization capability is superior to the capability ofrespective linear regression models. As the data used to train the FFANNs is normally available early in the project lifecycle, the proposed model enables early, yet accurate cost estimates to be obtained.

Keywords: Artificial Neural Network, Bill of Quantities, Bridge, Construction Cost estimate, Infrastructure Planning.

Introduction

Providing accurate forecasts of construction costs in the preplanning phases of construction projects is vital (Dursun & Stoy, 2016) as cost estimation accuracy has decisive impact on strategies for asset development, potential project screening, and resource commitment for further project development (Oberlender & Trost, 2001). Estimates prepared at the initial stages of a project can play several important roles: they can form the basis of cost-benefit analysis, for selection of potential delivery partners, to support a to-build-or-not-to-build decision, and very often as a benchmark for future performance measure (Ahiaga-Dagbui & Smith, 2014). They are also typically used for the estimation of preconstruction costs as a fixed or sliding percentage (Hollar & Rasdorf, 2013).

The soaring urban and inter-urban traffic needs generate an ever-increasing pressure for allocation of funding towards the construction of motorway infrastructure. This is a critical issue which currently attracts significant debate and disagreement (Hollar et al., 2013). Gibson, Denison, Wallace and Kreis (2015) note that the fiscal developments of recent years make it difficult to plan appropriate policies and infrastructure projects that maintain transportation systems at current service levels as the available public funding does not necessarily meet the expanding transportation needs of citizens. In this context, as motorway projects require a substantial investment of funds, developing a reliable and accurate project cost estimate in the initial decision-making process is a task of critical importance to the sponsoring organisation and the project team.

Apparently, in times of resource scarcity, it is even more necessary for the decision makers to estimate the budget of high-cost, large-scale construction projects like road bridges with adequate accuracy, early in the planning process, in order for the national funds to be invested as

1
2
3 efficiently as possible. However, the required accuracy is notoriously difficult to be achieved as
4
5 the conceptual stage involves very limited project information. Yeung and Skitmore (2012) note
6
7 that in the very early stages of construction projects, there are situations where only such basic
8
9 information as project type, project size and preliminary project specification is known
10
11 concerning a new project and the client-owners' consultant estimators have to resort to using
12
13 either the price of a very similar project or the mean price of a (base) group of projects. Similarly,
14
15 Hyari, Al-Daraiseh and El-Mashaleh (2016) highlight the fact that detailed estimates are usually
16
17 possible not earlier than the stage of procurement, i.e. after completion of the detailed project
18
19 design and therefore, earlier cost estimates can only be based on historical data and cost
20
21 forecasting models. This unsurprisingly leads to early estimates being highly inaccurate with the
22
23 final actual cost exceeding in the vast majority of cases the initial estimate.
24
25
26
27
28
29

30 As Rosenfeld (2014) notes, cost overruns in construction are a worldwide phenomenon
31
32 with no geographical limits nor cultural associations. Flyvbjerg, Holm and Buhl (2003) highlight
33
34 the correlation between cost overruns and project size arguing that larger projects present higher
35
36 percentage cost escalations while other factors such as premature tender documents (Rosenfeld
37
38 2014) and procurement choices (Chen et al. 2016) have also been strongly associated with this
39
40 global problem. Especially in the field of transportation projects, Flyvbjerg, Holm and Buhl
41
42 (2003) note that the magnitude of cost overruns in highway projects and motorway bridges is
43
44 substantially high. Specifically, nine out of ten transport infrastructure projects fall victim to cost
45
46 escalation, which for fixed links (tunnels and bridges) and roads has an average value of 34% and
47
48 20% respectively. Furthermore, Lee's (2008) analysis of roads, rails, airports and ports projects
49
50 found that road and rail projects had a maximum cost overrun of 50%. Vidalis and Najafi (2002)
51
52
53
54
55
56
57
58
59
60

1
2
3 in their research on 708 highway projects for the Florida Department of Transportation found a
4
5 combined cost overrun of \$200 million.
6
7

8 This research paper introduces an Artificial Neural Network (ANN)-based model which,
9
10 utilising actual Bill of Quantities (BoQ) data from 68 road bridge projects, enables the reliable
11
12 estimation of the bridge superstructure and piers material quantities and by extension the more
13
14 accurate estimation of the relevant cost. This is achieved by multiplying the quantities predicted
15
16 by the model with the unit prices specified by the user. The use of material quantities as a means
17
18 to extract the cost instead of developing a model to directly predict the cost, enhances the
19
20 reliability of the estimation process. This results from the fact that the BoQ is based on final
21
22 designs compliant to international standards with wide acceptance and use across countries (e.g.
23
24 DIN, Eurocodes, AASHTO) while on the contrary, cost values are heavily influenced by country-
25
26 specific actors (e.g. tendering system, inflation rate) which need to be adjusted for the model to
27
28 be used more widely.
29
30
31
32
33

34 **Literature Review**

35 **Research in road bridge cost analysis and management**

36
37 The analysis of the construction cost of concrete bridges has been the aim for numerous
38
39 past research efforts. Menn (1990) used a small sample of 19 motorway bridges built in
40
41 Switzerland between 1958 and 1985 to investigate the cost of prestressed concrete bridges. He
42
43 broke down the bridge structure into four components, i.e. mobilization, substructure,
44
45 superstructure, and accessories and concluded that these factors' contribution to the total bridge
46
47 construction cost is 8.00%, 23.50%, 54.50%, and 14.00%, respectively. Fragkakis and
48
49 Lambropoulos (2004) collected actual cost information from a large sample of 119 concrete
50
51 bridges and overpasses constructed between 1999 and 2003 as part of the Egnatia Motorway in
52
53
54
55
56
57
58
59
60

1
2
3 Greece. They divided the actual bridge construction cost into earthworks, foundation,
4 substructure, superstructure and accessories and proposed the average cost values for four major
5 deck construction methods. For example, concerning bridges consisting of precast prestressed
6 beams and reinforced concrete slabs, the average cost percentages for the five elements above are
7 4.70, 26.70, 15.90, 34.40 and 18.30 % respectively.
8
9

10
11
12
13
14
15 The review of publications relating to cost estimation for road bridges reveals that very few
16 studies use actual as-built design and structural data in order to produce cost estimate models.
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

The review of publications relating to cost estimation for road bridges reveals that very few studies use actual as-built design and structural data in order to produce cost estimate models. Fragkakis, Lambropoulos and Tsiambaos (2011) developed a bridge database with complete data from 157 pier foundations and developed a parametric model for conceptual cost estimation of concrete bridge foundations. A database with design and structural data for 322 bridge piers was used from Fragkakis, Lambropoulos and Pantouvakis (2014) in order to develop a cost estimate model for piers with regression analysis. Furthermore, Fragkakis, Lambropoulos and Pantouvakis (2010) applied regression analysis on a database consisting of 68 structures and derived material estimating models for three widely used deck construction methods (cantilever construction, precast pre-stressed beams, cast-in-situ box girders). Bridge cost estimation guidelines, mostly based on historical bid data, have also been developed by Departments of Transportation (DoT) in U.S. Such examples are California (2011), New York (2016) and Florida (2017). Moreover, in Dimitriou and Charmpis (2015) and Charmpis and Dimitriou (2015) alternative optimisation formulations and algorithmic configurations have been tested on a realistic large-scale sample of nearly 15,000 bridges from NY, USA, exposing the gains of optimal selection mechanisms on budget utilisation, while highlighting the importance of accuracy in bridges rehabilitation cost appraisal.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

Most efforts on cost estimation of concrete bridges are constrained by design standards and codes and are based on a trial-and-error computer-aided process aiming to optimise the design from a technical or economical viewpoint. Sirca and Adeli (2005) addressed precast, prestressed concrete bridge systems consisting of type I beams and developed an optimization method for the superstructure cost. The general design process of the superstructure and the standard cross sections were based on the AASHTO specifications. The model addressed the superstructure as a single system and did not explore the superstructure components. Cohn and Lounis (1994) explored the optimal design of concrete motorway bridges through a three-level cost optimization approach. Their research concentrated only on the superstructure of prestressed bridges with span length between 10.00 and 15.00 m. and deck width between 8.00 and 16.00 m. They addressed superstructure systems with solid or voided slabs, single-cell box girders and precast prestressed beams with reinforced concrete composite slab. Lounis and Cohn (1993) proposed a method for bridges consisting of precast prestressed girders with reinforced concrete slab that enables the selection of the most economical girder type, optimal girder spacing, optimal prestressing force, and minimum superstructure cost per unit deck area. The specifications and constraints of the Ontario Bridge design standard were used. Aparicio, Casas and Ramos (1996) proposed a computer-aided design and cost estimating system addressing all elements of concrete highway bridges. The software package represents an expert system that uses specific design constraints to perform the complete bridge design. It produces the geometry and cost of all bridge elements and extracts design drawings. A thorough review of publications on cost optimisation of concrete bridge components and systems has been presented by Sarma and Adeli (1998) and Hassanain and Loov (2003). The aforementioned studies address only the bridge superstructure and use standard beam shapes and cross sections dictated by the American or Canadian design standards

1
2
3 and specifications. The research is characterized by the computer-intensive theoretical resolutions
4
5 that result in the optimization of the final design from both technical and economic viewpoints.
6
7 Although cost estimates based on computer-aided resolutions provide helpful insights, they fail to
8
9 address the designers' attitude and experience that influence the as-built structural quantities for
10
11 each project, as well as the structural changes that take place during the project's construction
12
13 and were not predicted during the design phases.
14
15
16

17 18 **Cost prediction at early design stages: challenges and methodological approaches** 19

20
21 According to Burke (1999) and Flyvbjerg, Holm and Buhl (2002), at each phase in the
22
23 project implementation (conception, tendering, design, construction) different levels of cost-
24
25 estimating accuracy can be achieved from the detail of information available. Specifically the
26
27 early cost estimates made at the conception phase are based on designs which only correspond to
28
29 a general idea about what the project will entail, at a completion level of about 30%. As a result,
30
31 many of the costs must be inferred from costs associated with past projects (Asmar, Hanna,
32
33 &Whited, 2011). Nicholas (2004) also refers to the lack of realistic and accurate estimates as a
34
35 result of inadequate information and highlights the fact that estimators have to rely largely on
36
37 their own experience and historical cost information when preparing initial estimates. Ahiaga-
38
39 Dagbui and Smith (2013) observe that an estimate can only be as good as the information it is
40
41 based on so that, *ceteris paribus*, the level of accuracy of the estimates produced also increases as
42
43 more information becomes available. However, despite their low level of accuracy, early cost
44
45 estimates are used as the basis for the comparative evaluation of different investments decisions,
46
47 design alternatives and eventually the selection of the most efficient technical solution. Odeck
48
49 (2004) discusses the risk of inefficient investment decisions resulting from unreliable early cost
50
51 estimations. He particularly highlights the fact that underestimated costs may be deceptive
52
53
54
55
56
57
58
59
60

1
2
3 as when the viability of the project is being evaluated, the decision maker probably makes
4
5 decisions based on larger values of Net Present Value than the actual ones. The end result may be
6
7 that non-viable projects are being implemented and resources are inefficiently allocated due to
8
9 inaccurate estimates.
10

11
12 In this context, the uncertainty which is inherent in the pre-construction phase of projects
13
14 has repeatedly been connected by the literature with the occurrence of cost overruns. Flyvbjerg,
15
16 Holm and Buhl (2002) note that the likelihood of actual costs being larger than estimated at a
17
18 randomly selected project reaches the impressive percentage of 86%. Durdyev, Ismail and Bakar
19
20 (2012) in their research for residential projects identified improper planning and inaccurate
21
22 project cost estimation among the factors affecting cost overruns. Similarly, in their analysis for
23
24 infrastructure projects, Lee (2008) examined 161 roads, rails, airports, and ports projects and
25
26 concluded changes in the scope and unreasonable cost estimation have substantial impact on cost
27
28 overruns. Similar conclusions for the impact of inaccurate cost estimates were also presented by
29
30 Le-Hoai, Lee and Lee (2008). Cantarelli, vanWee, Molin and Flyvbjerg (2012) also note that
31
32 road projects are particularly vulnerable to exceeding the estimated costs in the pre-construction
33
34 phase and argue that although this phase is significantly shorter than the construction phase, it has
35
36 the highest influence on cost overruns. Bridge construction in particular also presents substantial
37
38 budget overruns (Odeck, 2004; Flyvbjerg, Skamris, & Buhl 2004, 2007; Azhar, Farooqui, &
39
40 Ahmed, 2008).
41
42
43
44
45
46
47

48 Numerous models have been developed to support decision makers in the challenging task
49
50 of estimating construction project cost. Among the most popular and well-established modelling
51
52 techniques for this purpose are the ANNs. An ANN is an information-processing system that has
53
54 been developed as a generalization of mathematical models of human cognition or neural biology
55
56
57
58
59
60

1
2
3 and exhibits the ability to capture the nonlinear relationships between variables. ANNs are made
4
5 of simple processing units, called neurons, capable of storing experimental knowledge as a
6
7 natural propensity. The elementary backpropagation artificial neuron forms the base component
8
9 of the ANN. Typically the neuron is configured with a number of inputs, with each input having
10
11 an associated weight which multiplies the signal transmitted. An activation/transfer, often sigmoid
12
13 function is applied to convert the input of each neuron to
14
15 output. The ANN type most suited for developing predictive models is the Feed-Forward ANN
16
17 (FFANN) trained using a back-propagation algorithm that uses a gradient-descent approach for
18
19 adjusting the ANN weights (Attalla & Hegazy, 2003). Back-propagation ANNs consist of an
20
21 input layer, an output layer, and one or more hidden layers. The number of layers and the
22
23 numbers of neurons in each layer determine the capability of the network to figure out the
24
25 relationship between the independent variables and the dependent one. A single hidden layer is
26
27 sufficient for almost any problem (Setyawati, Sahirman, & Creese, 2002). An ANN is
28
29 feedforward if there exists a method which numbers all the nodes in the network such that there is
30
31 no connection from a node with a large number to a node with a smaller number. All the
32
33 connections are from nodes with small numbers to nodes with larger numbers (Yao, 1999).

34
35 The ANN gains its problem-solving capabilities through generalization of the knowledge gained
36
37 during its training. According to Zhang, Patuwo and Hu (1998) the training process is usually as
38
39 follows. First, examples of the training set are entered into the input nodes. The activation values
40
41 of the input nodes are weighted and accumulated at each node in the first hidden layer. The total
42
43 is then transformed by an activation function into the node's activation value. It in turn becomes
44
45 an input into the nodes in the next layer, until eventually the output activation values are found.
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
The training algorithm is used to find the weights that minimize some overall error measure such

1
2
3 as the sum of squared errors (SSE) or mean squared errors (MSE). Hence the network training is
4
5 actually an unconstrained nonlinear minimization problem. When supervised training is applied,
6
7 input and output parameters of training data are randomly presented to the network thousands of
8
9 times, called cycles or epochs. In each epoch, the network applies its training algorithm and
10
11 calculates its predicted output. The errors between the predicted and the actual outputs are
12
13 propagated backward to adjust the network's weighted connections so that the predicted output
14
15 matches or becomes as close as possible to the actual output. This process is mathematically
16
17 guaranteed to converge (Rumelhort, Hinton, & Williams, 1986). The distinct advantage of ANNs
18
19 over the nonlinear regression is that no exact knowledge of the nonlinear relationship between the
20
21 input and output variables is required as these relationships are determined implicitly by the ANN
22
23 and therefore do not need to be specified by the user. The error of the trained model is used as a
24
25 metric of its generalization capability. As Svozil, Kvasnicka, & Pospichal (1997) explain, a
26
27 network generalises well when the input-output relationship computed by network is correct (or
28
29 nearly correct) for input/output patterns never used in training the network. When the learning
30
31 process is repeated too many times, then, overfitting may occur due to the network memorising
32
33 the training data instead of capturing the underlying correlations among variables. In such case,
34
35 the network performs satisfactorily during the training process but fails with data from the test
36
37 set. Thus, the network has reduced generalization capability. The most commonly used method
38
39 for avoiding overfitting is early stopping. This involves dividing data into two sets, one for
40
41 training and one for validation, and computing the validation error periodically during training.
42
43 Training stops when the validation error rate starts to increase. However, the validation error is
44
45 not a good estimate of the generalization error, and thus, a third set of data, not used during the
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3 training process, is necessary to check the generalization performance of the ANN. This third set
4
5 is called test set.
6
7

8 ANNs' powerful capabilities for capturing and modelling complex interrelations in real-
9 world datasets have been widely identified in the literature (e.g. Marinelli, Lambropoulos,
10 & Petroutsatou, 2014; Dimitriou & Hassan, 2013; Karlaftis & Vlahogianni, 2011; Moselhi,
11 Hegazy, & Fazio, 1992) and their suitability for cost estimation of different kinds of construction
12 projects like buildings (Gunaydin & Dogan, 2004; Kim, An, & Kang, 2004), tunnels
13 (Petroutsatou, Georgopoulos, Lambropoulos, & Pantouvakis, 2012), highway projects (Hegazy &
14 Ayed, 1998; Al-Tabtabai, Alex, & Tantash, 1999; Xin-Zheng, Xiao-Chen, & Jing-Yan, 2010),
15 drainage projects (Alex, Al Hussein, Bouferguene, & Fernando, 2010), water projects (Shehab,
16 Farooq, Sandhu, Nguyen, & Nasr 2010, Chau & Sethi, 2012), hydroelectric power plant projects
17 (Gunduz & Sahin, 2015) has also been highlighted. Other applications of ANNs include financial
18 tools, electric load consumption prediction and intelligent manufacturing systems (Huang &
19 Zhang 1994, Zhang, Patuwo & Hu (1998). Frazer (1995) also investigates the use of computer
20 based techniques and models in the field of architecture.
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40

41 In the area of bridges, Creese and Li (1995) used data from 12 timber bridges to develop an
42 ANN capable for the estimation of the bridge cost from the volume of webs, the volume of the
43 bridge decks and the weight of steel. Similarly, Ugwu and Kumaraswamy (2004) used data of
44 location, pavement material and project configuration from 74 highway bridges in Hong Kong to
45 train an ANN to predict their construction cost. Furthermore, Morcous, Bakhom, Taha, & El-
46 Said (2001) used data from 22 pre-stressed concrete bridges constructed in Egypt to develop a
47 ANN capable of estimating the concrete volume and pre-stressed steel weight of bridge
48 superstructures. The input attributes selected for the training of the ANN model were: the
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3 maximum span length, the superstructure type, the structure system, the construction method, the
4 contract type, and the design type. Testing results with cross-validation experiments resulted in
5
6 average network errors smaller than 11.50% in both output variables.
7
8
9

10
11 The literature survey indicates that ANNs have been used efficiently for the preliminary
12 quantity estimate of highway bridges despite the difficulties emerging from the use of different
13 design codes as well as the reluctance of public clients to supply financial information regarding
14 constructed projects. Other methods frequently employed for project cost estimation include
15 regression analysis (e.g. Trost & Oberlender, 2003; Lowe, Emsley, & Harding, 2006; Wang &
16 Horner, 2007; Fragkakis, Lambropoulos, & Pantouvakis, 2010; Jafarzadeh, Wilkinson, González,
17 Ingham, & Ghodrati Amiri 2014) and case-based reasoning (e.g. Karshenas & Tse, 2002; Kim &
18 Kang, 2004; Doğan, Arditi, & Gunaydin, 2008; Koo, Hong, Hyun, & Koo, 2010). Kim, An, &
19 Kang (2004) provide comparison of all the 3 methods performance and advantages /
20 disadvantages. Their research based on the analysis of actual construction costs of 530 projects of
21 residential buildings, concluded that the best ANN model performed more effectively than the
22 other two approaches in estimating construction costs. Quite a number of other researchers have
23 also verified the performance superiority of ANNs over regression. For instance, Attalla and
24 Hegazy (2003) compared the two methods' performance in reconstruction cost prediction and
25 concluded that the ANN-based model was able to include a much greater number of variables.
26 Similarly, Shehab, Farooq, Sandhu, Nguyen and Nasr (2010) concluded that the ANN developed
27 for water projects cost prediction produced much more accurate results compared to the
28 regression one and thus demonstrated superior capabilities in mapping relationships between
29 inputs and outputs in limited data environments. Gunduz and Sahin (2015) also confirmed in
30 their research that the ANN that was trained on cost data from forty one hydroelectric power
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3 plant projects had substantially higher prediction accuracy than the respective regression model
4
5 developed. Similar performance superiority of the ANNs over linear regression has also been
6
7 reported by Creese and Li (1995) for their timber bridge cost prediction model.
8
9

10 11 **Development of FFANN-based model for Road Bridge BoQ estimation**

12 13 **Data collection**

14
15
16
17 The data used for the development of the model were collected from the final BoQs of 68
18
19 bridges of Egnatia Motorway, a 680-km-long motorway constructed in northern Greece between
20
21 1996 and 2008 as part of the trans-European Transport Network. The whole project includes 646
22
23 concrete bridges which account for the 20% of the total construction cost. The greatest overall
24
25 bridge length exceeds 1,000 m, and the longest single span reaches at 235 m. The designs were
26
27 carried out by Greek and international structural design firms following international
28
29 competitions. A thorough three-stage review process was applied to all designs before
30
31 construction.
32
33
34

35
36 For the collection of the characteristics of each construction project, a list of questions was
37
38 distributed to the construction managers/supervisors responsible for each project and the
39
40 contractor's civil engineers. These questions concerned general information (e.g. location,
41
42 highway section and design office), the bridge's fundamental design parameters (e.g. number of
43
44 spans, construction method used, length of each span, width, height of piers) and the quantities of
45
46 concrete and reinforcing steel for each span and pier. After scrutinising the replies, on-site visits
47
48 were held to check and confirm the validity and accuracy of the data provided.
49
50
51

52
53 The final dataset includes three different types of bridges, distinguished by the use of
54
55 different construction methods as dictated by the varying landscape (mountainous, flat terrains,
56
57
58
59
60

significant slopes, etc). Apart from the construction method, the dataset for each bridge also includes the superstructure material quantities i.e. concrete (V_c), reinforcing steel (B_s) and pre-stressed steel (B_p), as well as basic design parameters i.e. the length of the span or cantilever (l) and the deck width (b). Details of the bridge superstructure dataset are presented in Table 1.

In order to take into account the difference of deck width among the bridges of the data sample, an adjusted length of the span or cantilever was also defined (l_{adj}) as a function of the median value of the deck width for each construction method in the sample (b_{med}) as per equation 1. This value equals 13.10 m for superstructures with precast beams, 13.50 m for superstructure with cast-in-situ box girders and 14.00 m for cantilever construction.

$$l_{adj} = l * \frac{b}{b_{med}} \quad (1)$$

Similarly, the collected dataset for 321 piers included the height of each pier, H , the corresponding concrete volume, V_c' , and the reinforced steel weight, B_s' (relevant ranges included in Table 2). Additionally, the length of the deck supported by each pier, l' , was calculated as the average length of the spans situated on both sides of the pier and this value was adjusted as previously (equation 2) to give l'_{adj} . In the following section, a thorough investigation of the datasets' characteristics is presented.

$$l'_{adj} = l' * \frac{b}{b_{med}} \quad (2)$$

Multivariate data analysis

Multivariate analysis was undertaken to enable deeper understanding of the complexity of the interrelations between the variables of the datasets, i.e. the bridge type, b , l , V_c , B_s , B_p , l_{adj} for bridge superstructure and H , V_c' , B_s' and l'_{adj} for bridge piers. Initially, the correlation matrices

1
2
3 provided in Figure 1 and Figure 2 provide a better picture of how the variables co-relate. In
4
5 particular, Figure 1 demonstrates the correlations between the superstructure variables while
6
7 similarly Figure 2 concerns the variables of the piers. From Figure 1, it can be observed that there
8
9 are pairs with strong, mainly nonlinear correlations. In Figure 2, the most apparent correlation
10
11 lies unsurprisingly between the concrete volume V_c ' and the reinforcement steel B_s ', while other
12
13 correlations (e.g. between piers height, H and concrete volume V_c ') are much more stochastic.
14
15

16
17
18 For further investigation of the correlations in the available dataset, the multivariate
19
20 datasets were analysed based on Andrews plots (Andrews, 1972) (Figure 3). Andrews plots
21
22 depict multivariate datasets to enable insights on the existence of possible correlations but with
23
24 no indication of their exact nature. Further information about Andrews plot can be found in
25
26 Garcia-Osorio and Fyfe (2006). In the specific form of the Andrews plot used in the present
27
28 study, each observation i , is represented by a function $f(t)$ of a continuous dummy variable t over
29
30 the interval $[0,1]$. The Function $f(t)$ is defined for the i -th observation in the dataset X as per
31
32 equation 3.
33
34
35

$$36$$
$$37$$
$$38 f(t) = X(i,1) / \sqrt{2} + X(i,2) / \sin(2\pi t) + X(i,3) \cos(2\pi t) + \dots \quad (3)$$
$$39$$
$$40$$

41 In varying the value of t in equation 3, data points which are similar will behave similarly in that
42
43 the locus of their movement will be similar facilitating thus the identification of patterns as well as
44
45 outliers in the dataset. Figure 3 shows that at least four distinct clusters can be identified in the
46
47 superstructure's dataset.
48
49

50
51 On the other hand, no particular clusters can be exposed in the Andrews plot for the piers'
52
53 dataset (Figure 4), revealing the stochastic nature of the interrelations among the selected
54
55 variables and validating the initial evidence provided earlier by the correlation analysis.
56
57 Concentrating on the piers' dataset and aiming to gain some insight into the type of the
58
59
60

1
2
3 interrelations, the normality of each variable as well as their possible fitting to the Weibull and
4
5 Lognormal distribution was checked. The relevant tests showed that none of the variables seem to
6
7 follow any of the theoretical distributions.
8
9

10 These findings suggest that standard regression analysis may not be a suitable analytical
11
12 framework, since the datasets do not fit to a theoretical distribution and thus this fundamental
13
14 assumption of regression analysis cannot be fulfilled. Moreover, the underlying relation between
15
16 the dataset variables possibly is of non-linear nature and of complex structure. Given the above,
17
18 the BoQ estimation problem requires a modelling approach based on ANNs, known for their
19
20 ability to handle complex 'mappings' from inputs to outputs. The experimental setup of the
21
22 ANNs used is presented in the following section.
23
24
25
26

27 **Application of the Feed-Forward Artificial Neural Network on the BoQ estimation**

28
29
30 The estimation of a total BoQ for the superstructure and the piers of bridges is addressed by
31
32 combining the results of two suitably selected, trained and tested FFANNs. This combination is
33
34 able to adapt to the particularities of the two datasets, since the quality of ANN performance is
35
36 dependent on the quantity of training data and on how the data are presented to the network.
37
38 Therefore, several data-representation experiments with various network architectures, different
39
40 number of hidden layers, hidden nodes and transfer functions were conducted, resulting to the
41
42 structure presented in Figure 5.
43
44
45
46

47 It should be noted here that the current paper addresses the particularities of bridge cost
48
49 estimation through the following two methodological features:
50
51

- 52 i. The use of binary/class/integer variables in the model building which enable the
53
54 introduction of bridge class features like the type of a bridge, and
55
56
57
58
59
60

1
2
3 ii. The training of a different ANN for each main component (superstructure, piers) and
4 subsequent combination of the results.
5
6

7
8 These two elements ensure that the estimated models are accurate, robust and reliable, take
9 into consideration realistic features in estimating bridges' cost and are also useful in project
10 feasibility phase.
11
12
13

14
15 Starting from the configuration of the ANN corresponding to the superstructure, the deck
16 width in meters (b), the adjusted length of span or cantilever in meters (l_{adj}) and the categorical
17 variable representing the bridge type (Type) are the inputs to a hidden layer of 10 nonlinear
18 neurons each of which has a log-sigmoid transfer function. Three linear functions for estimating
19 the volume of concrete in m^3 (V_c), the weight of reinforcing steel in kg (B_s) and the weight of
20 pre-stressed steel in kg (B_p) form the output layer of the ANN. Additionally, for the piers, the
21 height (H) and the adjusted length of the span supported by each pier (l'_{adj}) are input into a
22 hidden layer with 20 nonlinear neurons while the output layer estimates the volume of concrete in
23 m^3 (V'_c) and the weight of reinforcing steel in kg (B'_s).
24
25
26
27
28
29
30
31
32
33
34
35
36
37

38 The respective datasets were for both cases divided in three parts, namely, for training,
39 validating and testing into typical proportions of 70%, 15% and 15% respectively. The training
40 set was used by the Levenberg-Marquardt optimisation routine to update the weights of the
41 connections between the layers with the aim to minimise the Mean Squared Error (MSE) between
42 observations and predictions. The validation set was used to monitor the performance of the
43 network during training against over-fitting /memorisation, while test set was used for unbiased
44 evaluation of the model's predictive capabilities after the training process was completed. This
45 type of FFANN has several advantages including being straightforward, powerful in mapping
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3 nonlinear and stochastic interrelations within datasets, able to treat both continuous and
4
5 categorical (integer) data and easy for coding and testing (Karlaftis and Vlahogianni, 2011).
6
7

8 The convergence diagrams for the training, validating and testing process of the
9
10 complementary FFANNs (Figures 6 and 7) demonstrate the capability of the trained FFANNs to
11
12 model the interrelations among the dataset variables (starting from a random state) with a
13
14 substantially improved error component (reduced to 10^8 from 10^{12}), as the relevant MSE metric
15
16 denotes. The magnitude of performance of the gradient and the number of validation checks are
17
18 used to terminate the training. The gradient becomes very small as the training reaches a
19
20 minimum of the performance. Training stops after a number of successive epochs where the
21
22 validation performance fails to decrease (epoch 17 and onwards in Figure 6). As it can be
23
24 observed from Figure 7, the training process for the piers' FFANN requires 28 iterations, an
25
26 element possibly indicative of the complexity of the relevant dataset.
27
28
29
30
31

32 The performance of the proposed FFANNs can be further exposed by the regression plots
33
34 for the three datasets (training, validating and testing). As can be observed in Figure 8, the
35
36 superstructure FFANN is capable of notably accurate BoQ estimations, since the correlation of
37
38 predictions and observations is very high for all sets ($R \sim 0.99$) and the linear regression function
39
40 almost coincides with the ideal line. This is a clear indication of the model's value for practical
41
42 purposes.
43
44
45

46 Similarly, the regression analysis of the correlation between the observations and
47
48 predictions made by the piers' FFANN is also very high (Figure 9) reaching an R value of
49
50 $R=0.99$ for training (Figure 9a). However, it can also be observed that the correlation diagram is
51
52 more scattered around the ideal correlation line for all sets (training, validation and testing), while
53
54 the correlation coefficient for the validation and especially for the testing set lies at 0.90 (Figure
55
56
57
58
59
60

1
2
3 9b) and 0.96 (Figure 9c) respectively. Although the results can be regarded as satisfactory, this is
4
5 an additional indication of the complexity of the interrelations between the variables of the piers.
6
7

8
9 An additional indication for the FFANNs' performance can be obtained by checking the
10
11 distribution of errors; unbiased models are ideally expected to have normally distributed errors
12
13 with mean equal to zero. The close-to-normal distribution of the errors for the three sets (training,
14
15 validation and test sets) for both FFANNs as depicted in Figures 10 and 11, further verifies the
16
17 reliability of the training process and suggests unbiased estimation capabilities for both models.
18
19

20
21 The above thorough evaluation of the developed FFANNs' capability to estimate the BoQ
22
23 for both the superstructure and piers of road bridges offers encouraging evidence on the
24
25 applicability and performance of such data-driven models in real-world problems. The final step
26
27 of the proposed methodological framework involves its comparison against parametric estimation
28
29 models. Such comparative analysis is provided in the next section.
30
31

32 33 **FFANNs' performance comparison to regression models**

34
35

36 In order to check the performance of the developed FFANNs, apart from the tests already
37
38 presented, comparative statistics with standard regression models were also performed.
39
40 Specifically, the performance of the developed FFANNs was compared against the performance
41
42 of parametric linear regression models developed for the same data. The same test subset i.e. the
43
44 15% of the complete dataset was used in both cases. Two metrics of goodness-of-fit were used to
45
46 provide a clear picture of the accuracy of the alternative models: the coefficient of determination
47
48 (R^2), which is a measure of the variability explained by the models and the Mean Absolute
49
50 Percentage Error (MAPE) which is an error metric. As presented in Table 3, the FFANN trained
51
52 to estimate the superstructure BoQ outperforms the respective linear regression model in all the
53
54 three construction methods and in both metrics.
55
56
57
58
59
60

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
The comparative results for the piers' FFANN constitute an even stronger indication of the model's strengths and robustness. As indicated in Table 4, the FFANN demonstrates superior performance compared to the statistical models both in terms of the R^2 and the MAPE. This is particularly evident for the estimation of the steel weight and can be attributed to the lack of data normality, which is a prerequisite for the development of reliable linear regression models. The difference observed in the MAPE value between the FFANN for the superstructure and the one for the piers is also worth noting; in the case of piers the MAPE is significantly higher compared to the equivalent values for the superstructure, an additional evidence of the prediction difficulty for the piers' dataset.

25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
The above presented results provide strong evidence on the FFANNs' potential on predicting bridges' BoQ when used as surrogate mechanisms early in the design stage. Given the complex interrelationships among the variables for BoQ estimation and taking into account the overall very satisfactory computational performance of the developed models, it can be concluded that in the context of road bridge projects, the developed FFANNs are capable to provide reliable estimates of the material quantities required which in turn, can be used to yield cost estimates of improved accuracy.

43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 **Conclusions**

Developing a reliable cost estimate for large-scale road transport projects is a challenge for any authority or organisation, especially at the preliminary design phase, where only a general idea exists about what the project will entail. Aiming to enhance the accuracy of such preliminary cost estimates, two FFANNs were trained and tested on actual data from 68 concrete road bridges with the aim to reliably predict the BoQ of bridge superstructure and piers (concrete, pre-stressed steel and reinforcing steel) based on variables normally known even in the early implementation

1
2
3 stages. Specifically, the variables used as input to the superstructure's FFANN were the deck
4 width, the adjusted length of span or cantilever and the type of the bridge (with precast beams,
5 with cast in situ deck or cantilever construction). Similarly, for the piers' FFANN, the input
6 variables were the height of the pier and the adjusted length of span supported. As the relevant
7 performance analysis demonstrates, the developed FFANN model captures very well the complex
8 interrelations in the dataset and as a result of its strong generalization capability, it provides
9 reliable estimations of the final material quantities. An accurate cost estimation can be then
10 achieved by multiplying the properly selected material unit prices with the predicted material
11 quantities. Furthermore, following comparison of the FFANNs' performance against the
12 performance of the respective linear regression models, it became apparent that the use of
13 artificial intelligence resulted in an improved level of accuracy. Therefore, the proposed cost
14 estimation model represents a useful and reliable tool for the construction industry as it enables
15 planners to reach informed, despite early, decisions for technical and economic planning of
16 concrete bridge projects. Furthermore, the proposed surrogate model provides evidence of the
17 potential usefulness of ANNs in civil infrastructure planning and design. Similar extended
18 databases could be developed to include the remaining bridge elements (e.g. foundations and
19 abutments), other road infrastructure elements (culverts, underpasses and overpasses) as well as
20 motorway bridges constructed with different materials (e.g. steel girders and reinforced-concrete
21 slabs) or construction methods (e.g. incremental launching) and lead to additional cost estimation
22 models utilizing FFANNs. This research also highlights potential future directions for the field of
23 construction software, as the artificial intelligence of this computational paradigm is also suitable
24 for integration in the currently available software for infrastructure design and management.
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

References

- Ahiaga-Dagbui, D.D., & Smith, S.D. (2013). My cost runneth over: data mining to reduce construction cost overruns. In S.D. Smith and D.D. Ahiaga-Dagbui (Eds.), *Procs 29th Annual ARCOM Conference*, Reading, UK (pp. 559-568).
- Ahiaga-Dagbui, D. & Smith, S.D. (2014). Dealing with construction cost overruns using data mining. *Construction Management and Economics*, 32(7), 692-694.
- Al-Tabtabai, H., Alex, P. A., & Tantash, M. (1999). Preliminary cost estimation of highway construction using neural networks. *Cost Engineering*, 41(3), 19–24.
- Alex, D., Al Hussein, M., Bouferguene, A., & Fernando, S. (2010). Artificial Neural Network Model for Cost Estimation: City of Edmonton's Water and Sewer Installation Services. *Journal of Construction Engineering and Management*, 136(7), 745–756.
- Andrews, D. F. (1972). Plots of High-Dimensional Data. *International Biometric Society*, 18(1), 125–136.
- Aparicio, A. C., Casas, J. R., & Ramos, G. (1996). Computer aided design of prestressed concrete highway bridges. *Computers & Structures*, 60(6), 957-969.
- Asmar, M., Hanna, A., & Whited, G. (2011). New Approach to Developing Conceptual Cost Estimates for Highway Projects. *Journal of Construction Engineering and Management*, 137(11), 942–949.
- Attalla, M., and Hegazy, T. (2003). Prediction cost deviation in reconstruction project: Artificial neural networks versus regression. *Journal of Construction Engineering and Management*, 129(4), 405–411.
- Azhar, N., Farooqui, R. U., & Ahmed, S. M. (2008). Cost overrun factors in construction industry of Pakistan. In S.H. Lodi, S.M. Ahmed, R.U. Farooqi, & M. Saqib (Eds.), *1st International Conference on Construction In Developing Countries (ICCIDC-I) Advancing and Integrating Construction Education, Research & Practice*, Karachi, Pakistan (pp. 499-508).
- Burke, R. (1999). *Project management: Planning and control techniques*. Chichester, England: Wiley.
- California Department of Transportation, Division of Engineering Services (2011). *Construction Statistics 2010*. Retrieved November 5, 2015, from http://www.dot.ca.gov/hq/esc/estimates/Construction_Stats_2010.pdf.
- Cantarelli, C.C., vanWee, B., Molin, E.J.E., & Flyvbjerg, B. (2012). Different cost performance: different determinants? The case of cost overruns in Dutch transport infrastructure projects. *Transport Policy*, 22, 88–95.

- 1
2
3
4
5 Charmpis, D., & Dimitriou, L. (2015). A Stress-Test of Alternative Formulations and Algorithmic
6 Configurations for the Binary Combinatorial Optimization of Bridges Rehabilitation
7 Selection. In N. Lagaros, & M. Papadrakakis (Eds.), *Engineering and Applied Sciences*
8 *Optimization, dedicated to the memory of Professor M.G. Karlaftis*. Springer Verlag.
9
10
11 Chen, Q., Jin, Z., Xia, B., Wu, P., & Skitmore, M. (2016). Time and Cost Performance of
12 Design-Build Projects. *Journal of Construction Engineering and Management*, 142(2),
13 04015074.
14
15
16 Cohn, M.Z., & Lounis, Z. (1994). Optimal design of structural concrete bridge systems. *Journal of*
17 *Structural Engineering*, 120(9), 2653-2674.
18
19
20 Creese, R., & Li, L. (1995). Cost estimation of timber bridges using neural networks. *Cost*
21 *Engineering*, 37(5), 17-22.
22
23
24 Dimitriou, L., & Charmpis, D.C. (2015). Programming the Upgrade of Road Bridges by
25 Sequential Combination of Binary Optimization Routines. *Transportation Research Board,*
26 *94th TRB Annual Meeting Proceedings*, Washington DC, USA.
27
28
29 Dimitriou, L., & Hassan, H.M. (2013). Dynamic Autoregressive Neural Networks for Spatially
30 Distributed Time Series Prediction of Car Crashes in Urban Networks. *92th TRB Annual*
31 *Meeting, Washington DC, USA*.
32
33
34 Doğan, S. Z., Arditı, D., & Gunaydin, H. M. (2008). Using decision trees for determining attribute
35 weights in a case-based model of early cost prediction. *Journal of Construction*
36 *Engineering and Management*, 134(2), 146–152.
37
38
39 Durdyev, S., Ismail, S., & Bakar, N.A. (2012). Factors causing cost overruns in construction of
40 residential projects; case study of Turkey. *International Journal of Science and*
41 *Management*, 1(1), 3-12.
42
43
44 Dursun, O. and Stoy, C. (2016). Conceptual Estimation of Construction Costs Using the
45 Multistep Ahead Approach. *Journal of Construction Engineering and Management*,
46 142(9), 04016038.
47
48 Florida Department of Transportation (2017). *Structures design guidelines*. Retrieved February
49 20, 2017, from
50 <http://www.fdot.gov/structures/StructuresManual/CurrentRelease/Vol1SDG.pdf>.
51
52
53 Flyvbjerg, B. (2007). Cost overruns and demand shortfalls in urban rail and other infrastructure.
54 *Transportation Planning and Technology*, 30(1), 9-30.
55
56
57 Flyvbjerg, B., Skamris, H., & Buhl, S. (2004). What causes cost overrun in transport
58 infrastructure projects? *Transport Reviews*, 24(1), 3-18.
59
60

- 1
2
3
4
5 Flyvbjerg, B., Holm, M. S., & Buhl, S. (2003). How common and how large are cost overruns in
6 transport infrastructure projects? *Transport Reviews*, 23(1), 71-88.
7
- 8 Flyvbjerg, B., Holm, M. S., & Buhl, S. (2002). Underestimating Costs in Public Works
9 Projects. Error or Lie? *Journal of the American Planning Association*, 68(3), 279-295.
10
- 11 Fragkakis, N., Lambropoulos, S., & Pantouvakis, J.P. (2014). A computer-aided conceptual cost
12 estimating system for prestressed concrete road bridges. *International Journal of*
13 *Information Technology Project Management*, 5(1), 1-13.
14
- 15
16 Fragkakis, N., Lambropoulos, S., & Tsiambaos, G. (2011). A Parametric Model for Conceptual
17 Cost Estimation of Concrete Bridge Foundations. *Journal of Infrastructure Systems*, 17(2),
18 66 – 74.
19
- 20
21 Fragkakis, N., Lambropoulos, S., & Pantouvakis, P. (2010). A cost estimate method for bridge
22 superstructures using regression analysis and bootstrap. *Organization, Technology and*
23 *Management in Construction*, 2(2), 182-190.
24
- 25
26 Fragkakis, N., & Lambropoulos, S. (2004). A quantity and cost estimate model for concrete road
27 bridges (in greek). *TechnikaChronika Science Journal*, 24(2-3), 141-154.
28
- 29
30 Frazer, J. (1995). An evolutionary architecture. John Frazer and the Architectural Association. 36
31 Bedford Square, London, ISBN 1 870890 47 7.
32
- 33
34 Garcia-Osorio, C., & Fyfe, C. (2005). Visualization of high-dimensional data via orthogonal
35 curves. *Journal of Universal Computer Science*, 11(11), 1806-1819.
36
- 37
38 Gibson, B., Denison, D., Wallace, C., & Kreis, D. (2015). A Four-Step Process to Assess the
39 Fiscal Performance and Sufficiency of State Road Funds: An Application to Kentucky.
40 *Public Works Management & Policy*, 20(3), 226 –247.
41
- 42
43 Gunaydin, H., & Dogan, S. (2004). A neural network approach for early cost estimation of
44 structural systems of buildings. *International Journal of Project Management*, 22(7), 595 –
45 602.
46
- 47
48 Gunduz, M., & Bayram Sahin, H. (2015). An early cost estimation model for hydroelectric power
49 plant projects using neural networks and multiple regression analysis. *Journal of Civil*
50 *Engineering and Management*, 21(4), 470-477.
51
- 52
53 Hassanain, M.A., & Loov, R.E. (2003). Cost Optimization of Concrete Bridge Infrastructure.
54 *Canadian Journal of Civil Engineering*, 30(5), 841-849.
55
- 56
57 Hegazy, T., & Ayed, A. (1998). Neural network model for parametric cost estimation of highway
58 projects. *Journal of Construction Engineering and Management*, 124(3), 210-218.
59
60

- 1
2
3
4
5 Hollar, D., & Rasdorf, W. (2013). Predictive Modeling for Transportation Infrastructure
6 Preconstruction Costs. *Public Works Management & Policy*, 18(4) 304–321.
7
- 8 Hollar, D., Rasdorf, W., Liu, M., Hummer, J., Arocho, I., & Hsiang, S. (2013). Preliminary
9 Engineering Cost Estimation Model for Bridge Projects. *Journal of Construction*
10 *Engineering and Management*, 139(9), 1259–1267.
11
- 12 Huang, S.H. & Zhang, H.C. (1994). Artificial neural networks in manufacturing: concepts,
13 applications, and perspectives. *IEEE Transactions on Components, Packaging, and*
14 *Manufacturing Technology: Part A*, 17(2), 212-228.
15
- 16 Hyari, K., Al-Daraiseh, A., & El-Mashaleh, M. (2016). Conceptual Cost Estimation Model for
17 Engineering Services in Public Construction Projects. *Journal of Management in*
18 *Engineering*, 32(1).doi: 10.1061/(ASCE)ME.1943-5479.0000381.
19
- 20 Jafarzadeh, R., Wilkinson, S., González, V, Ingham, J.M., & Ghodrati Amiri, G. (2014).
21 Predicting Seismic Retrofit Construction Cost for Buildings with Framed Structures Using
22 Multilinear Regression Analysis. *Journal of Construction Engineering and Management*,
23 140(3), 04013062.
24
- 25 Karlaftis, M.G., & Vlahogianni, E.I. (2011). Statistical methods versus neural networks in
26 transportation research: Differences, similarities and some insights. *Transportation*
27 *Research Part C*, 19(3), 387–399.
28
- 29 Karshenas, S., & Tse, J. (2002). A case-based reasoning approach to construction cost estimating.
30 *Computing in Civil Engineering*, 113–123. doi: 10.1061/40652(2003)10.
31
- 32 Kim, G.H., An, S.H., & Kang, K. I. (2004). Comparison of construction cost estimating models
33 based on regression analysis, neural networks and case-based reasoning. *Building and*
34 *Environment*, 39, 1235-1242.
35
- 36 Kim, G., & Kang, K. (2004). A study on predicting construction cost of apartment housing
37 projects based on case based reasoning technique at the early project stage. *Journal of*
38 *Architectural Institute of Korea*, 20(5), 83–92.
39
- 40 Koo, C., Hong, T., Hyun, C., & Koo, K. (2010). A CBR-based hybrid model for predicting a
41 construction duration and cost based on project characteristics in multi-family housing
42 projects. *Canadian Journal of Civil Engineering*, 37(5), 739–752.
43
- 44 Le-Hoai, L., Lee, Y. D., & Lee, J. Y. (2008). Delay and cost overruns in Vietnam large
45 construction projects: A comparison with other selected countries, *KSCE Journal of Civil*
46 *Engineering*, 12(6), 367-377.
47
48
49
50
51
52
53
54
55
56
57
58
59
60

- 1
2
3
4
5 Lee, J.K. (2008). Cost overrun and cause in Korean social overhead capital projects: roads, rails,
6 airports, and ports. *Journal of Urban Planning and Development*, 134(2), 59–62.
7
- 8 Lounis, Z., & Cohn, M.Z. (1993). Optimization of precast prestressed concrete bridge girder
9 systems. *PCI Journal*, 38(4),60-78.
10
- 11 Lowe, D. J., Emsley, M.W., & Harding, A. (2006). Predicting construction cost using multiple
12 regression techniques. *Journal of Construction Engineering and Management*, 132(7), 750
13 –758.
14
15
- 16
17 Marinelli, M., Lambropoulos, S., & Petrousatou, K. (2014). Earthmoving Trucks Condition
18 Level Prediction using Neural Networks. *Journal of Quality in Maintenance Engineering*,
19 20(2), 182-192.
20
- 21 Menn, C (1990). *Prestressed concrete bridges*. Basel, Switzerland: Birkhauser.
22
- 23
24 Morcous, G., Bakhoum, M. M., Taha, M.A., & El-Said, M. (2001). Preliminary quantity estimate
25 of highway bridges using neural networks. In B.H.V. Topping and B. Kumar (Eds.),*6th*
26 *international conference on Application of artificial intelligence to civil & structural*
27 *engineering*, Eisenstadt, Vienna(pp.51-52).
28
- 29
30 Moselhi, O., Hegazy, T., & Fazio, P. (1992).Potential applications of neural networks in
31 construction. *Canadian Journal of Civil Engineering*, 19(3), 521-529.
32
- 33
34 New York Department of Transportation, Engineering Division, Office of Structures
35 (2016).*Preliminary cost estimate worksheet for new and replacement bridges*. Retrieved
36 February20, 2017, from
37 <https://www.dot.ny.gov/divisions/engineering/structures/manuals/preliminary-cost>
38
39
- 40
41 Nicholas, J. M. (2004).*Project management for business and engineering: Principles and*
42 *practice* (2nded.). Oxford, UK: Elsevier Butterworth–Heinemann.
43
- 44
45 Oberlender, G., &Trost, S. (2001). Predicting Accuracy of Early Cost Estimates Based on
46 Estimate Quality. *Journal of Construction Engineering and Management*, 127(3), 173–182.
47
- 48
49 Odeck, J. (2004). Cost overruns in road construction-what are their sizes and determinants?
50 *Transport Policy*, 11, 43-53.
51
- 52
53 Petrousatou, K., Georgopoulos E., Lambropoulos S., & Pantouvakis J. P. (2012). Early Cost
54 Estimating of Road Tunnel Construction Using Neural Networks. *Journal of Construction*
55 *Engineering and Management*, 138(6), 679-687.
56
57
58
59
60

- 1
2
3 Rosenfeld, Y. (2014). Root-Cause Analysis of Construction-Cost Overruns. *Journal of*
4 *Construction Engineering and Management*, 140(1), 04013039.
5
6
7 Rumelhart, D., Hinton, G., & Williams, R. (1986). *Parallel distributed processing, Vol. 1,*
8 *Foundations*. Cambridge, MA: MIT Press.
9
10
11 Sarma, K.C., & Adeli, H. (1998). Cost optimization of concrete structures. *Journal of Structural*
12 *Engineering*, 124(5), 570-579.
13
14 Setyawati, B.R., Sahirman, S., & Creese, R.C. (2002). Neural networks for cost estimation, *AACE*
15 *International Transactions*, 13, 1-9.
16
17
18 Shehab, T., Farooq, M., Sandhu, S., Nguyen, T., & Nasr, E. (2010). Cost Estimating Models for
19 Utility Rehabilitation Projects: Neural Networks versus Regression. *Journal of Pipeline*
20 *Systems Engineering and Practice*, 1(3), 104–110.
21
22
23 Sirca, G.F., & Adeli, H. (2005). Cost optimization of prestressed concrete bridges. *Journal of*
24 *Structural Engineering*, 131(3), 380-388.
25
26
27 Svozil, D., Kvasnicka, V., & Pospichal, J. (1997). Introduction to multi-layer feed-forward neural
28 networks, *Chemometrics and Intelligent Laboratory Systems*, 39(1), 43–62.
29
30
31 Taormina, R., Chau, K.W. & Sethi, R. (2012). Artificial neural network simulation of hourly
32 groundwater levels in a coastal aquifer system of the Venice lagoon. *Engineering*
33 *Applications of Artificial Intelligence*, 25(8), 1670-1676.
34
35
36 Trost, S. M., & Oberlender, G.D. (2003). Prediction accuracy of early cost estimates using factor
37 analysis and multivariate regression. *Journal of Construction Engineering and*
38 *Management*, 129(2), 198–204.
39
40
41 Ugwu, O., & Kumaraswamy, M. (2004). Neural network based decision support for estimating
42 cost of highway bridges – A Hong Kong study. In R. Ellis and M. Bell (Eds.), *COBRA 2004 -*
43 *RICS Construction and Property Conference*, Yorkshire, UK.
44
45
46 Vidalis, S.M., & Najafi, F.T. (2002). Cost and time overruns in highway construction. In *Procs*
47 *4th Transportation Specification Conference of the Canadian Society for Civil Engineering*,
48 Montreal, Canada (pp. 2799–2808).
49
50
51 Wang, N., & Horner, M. (2007). CSI model for estimating road maintenance projects,
52 *Construction Management and Economics*, 25(12), 1269-1281.
53
54
55 Xin-Zheng, W., Xiao-Chen, D., & Jing-Yan, L. (2010). Application of neural network in the cost
56 estimation of highway engineering. *Journal of Computers*, 5(11), 1762–1766.
57
58
59
60

1
2
3 Yao, X. (1999). Evolving artificial neural networks. *Proceedings of the IEEE*, 87(9), 1423-1447.
4

5
6 Yeung, D., & Skitmore, M. (2012). A method for systematically pooling data in very early stage
7 construction price forecasting. *Construction Management and Economics*, 30(11), 929–
8 939.
9

10 Zhang, G., Patuwo, B.E. & Hu, M.Y. (1998). Forecasting with artificial neural networks: The
11 state of the art. *International journal of forecasting*, 14(1), 35-62.
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

For Peer Review

1
2
3 *Figure 1.* Correlation matrix for the variables of the superstructure dataset.
4

5
6 *Figure 2.* Correlation matrix for the variables of the pier dataset.
7

8
9 *Figure 3.* Andrews plot for the variables of the superstructure dataset.
10

11
12 *Figure 4.* Andrews plot for the variable of the pier dataset.
13

14
15 *Figure 5.* The selected FFANNs' structure.
16

17
18 *Figure 6.* Convergence diagram for the FFANN estimating the BoQ of superstructure.
19

20
21 *Figure 7.* Convergence diagram for the FFANN estimating the BoQ of piers.
22

23
24 *Figure 8.* Performance of the FFANN estimating the BoQ of superstructure.
25

26
27 *Figure 9.* Performance of the FFANN estimating the BoQ of piers.
28

29
30 *Figure 10.* Distribution of estimation errors from the FFANN estimating the BoQ of
31 superstructure.
32

33
34 *Figure 11.* Distribution of estimation errors from the FFANN estimating the BoQ of piers.
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3 Table 1.
4

5
6 *Bridge superstructure dataset.*
7
8
9
10

11
12 Table 2.
13

14
15 *Ranges of height and material quantities in the bridge pier dataset.*
16
17


18
19
20
21
22 Table 3.
23


24
25 *Comparative statistics for the superstructure regression model and FFANN.*
26
27

28
29 Table 4.
30

31
32 *Comparative statistics for the pier regression model and FFANN .*
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60







1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

For Peer Review

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60




Peer Review




Peer Review

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60




Peer Review




Peer Review

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60


1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60




Peer Review



1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60




For Peer Review



1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60



For Peer Review

| Construction Method | Number of bridges | Number of spans | Width, b (m) | Length, l (m) | Deck concrete volume, V_c (m ³) | Deck steel weight, B_s (kg) | Deck prestressed steel weight, B_p (kg) |
|-------------------------------------|-------------------|-----------------|---------------|---------------|---|-------------------------------|---|
| Precast pre-stressed beams and slab | 31 | 47 | 10.00 – 17.75 | 19.92 – 43.50 | 154 - 466 | 14,716 - 57,851 | 3,174 – 16,255 |
| Cast-in-situ deck | 22 | 47 | 11.95 – 16.50 | 17.0 – 65.0 | 184 - 801 | 22,717 – 85,146 | 4,234 – 42,627 |
| Cantilever construction | 15 | 33 | 12.78 – 14.20 | 100.0 – 220.4 | 1,102 - 4,609 | 173,396 – 1,021,463 | 49,131 – 339,493 |

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

| Pier height H (m) | Pier concrete volume V_c (m ³) | Pier steel weight B_s (kg) |
|----------------------|---|---------------------------------|
| 7.31 – 87.83 | 16.21 -1,411 | 4,169 – 280,720 |

For Peer Review

| | Precast Beams | | Cast-in-Situ | | Cantilever | |
|-------------------|---------------|----------|--------------|----------|------------|----------|
| | R2 | MAPE (%) | R2 | MAPE (%) | R2 | MAPE (%) |
| Linear Regression | 0.967 | 12.29 | 0.952 | 16.82 | 0.956 | 16.36 |
| FFANN | 0.979 | 11.48 | 0.995 | 13.94 | 0.981 | 16.12 |

For Peer Review

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60

| | Pier Concrete Volume | | Pier Steel weight | | Overall | |
|-------------------|----------------------|----------|-------------------|----------|---------|----------|
| | R2 | MAPE (%) | R2 | MAPE (%) | R2 | MAPE (%) |
| Linear Regression | 0.724 | 38 | 0.849 | 42 | 0.895 | 40 |
| FFANN | 0.962 | 37 | 0.974 | 31 | 0.982 | 34 |

For Peer Review