

## Efficient parametric amplification in micro-resonators with integrated piezoelectric actuation and sensing capabilities

O. Thomas,<sup>1,2</sup> F. Mathieu,<sup>3</sup> W. Mansfield,<sup>4</sup> C. Huang,<sup>4</sup> S. Trolier-McKinstry,<sup>4</sup> and L. Nicu<sup>3</sup>

<sup>1</sup>Structural Mechanics and Coupled Systems Laboratory, Conservatoire National des Arts et M\_etiers, 2 Rue Cont\_e, 75003 Paris, France

<sup>2</sup>Arts et M\_etiers ParisTech, LSIS, 8 boulevard Louis XIV, 59046 Lille, France

<sup>3</sup>CNRS, LAAS, 7 avenue du Colonel Roche, F-31077 Toulouse Cedex 4, France

<sup>4</sup>Materials Research Institute and Materials Science and Engineering Department, The Pennsylvania State University, University Park, Pennsylvania 16802, USA

(Received 4 February 2013; accepted 7 April 2013; published online 25 April 2013)

We report, in this work, on unprecedented levels of parametric amplification in microelectromechanical resonators, operated in air, with integrated piezoelectric actuation and sensing capabilities. The method relies on an analytical/numerical understanding of the influence of geometrical nonlinearities inherent to the bridge-like configuration of the resonators. We provide analytical formulae to predict the performances of the parametric amplifier below the nonlinearity threshold, in terms of gain and quality factor (Q) enhancement. The analysis explains how to overcome this nonlinearity threshold by controlling the drive signals. It predicts that in theory, any Q-factor enhancement can be achieved. Experimental validation demonstrates a Q-factor enhancement by up to a factor 14 in air.

© 2013 AIP Publishing LLC [<http://dx.doi.org/10.1063/1.4802786>]