



Hartmann, A., Gleeson, T., Wada, Y., & Wagener, T. (2017). Enhanced recharge rates by altered recharge sensitivity to climate variability through subsurface heterogeneity. *Proceedings of the National Academy of Sciences of the United States of America*, 114(11), 2842-2847. https://doi.org/10.1073/pnas.1614941114

Peer reviewed version

Link to published version (if available): 10.1073/pnas.1614941114

Link to publication record in Explore Bristol Research PDF-document

This is the author accepted manuscript (AAM). The final published version (version of record) is available online via PNAS at http://www.pnas.org/content/114/11/2842. Please refer to any applicable terms of use of the publisher.

# University of Bristol - Explore Bristol Research General rights

This document is made available in accordance with publisher policies. Please cite only the published version using the reference above. Full terms of use are available: http://www.bristol.ac.uk/red/research-policy/pure/user-guides/ebr-terms/

- 1 In Press with PNAS. Classification: Physical Sciences
- 2 Enhanced groundwater recharge rates and altered
- 3 recharge sensitivity to climate variability through
- 4 subsurface heterogeneity

6 A. Hartmann<sup>1, 2\*</sup>, Tom Gleeson<sup>3</sup>, Yoshihide Wada<sup>4,5,6,7</sup>, Thorsten Wagener<sup>2,8</sup>

7

- 8 [1] Institute of Earth and Environmental Sciences, University of Freiburg, Germany
- 9 [2] Department of Civil Engineering, University of Bristol, UK
- 10 [3] Department of Civil Engineering and School of Earth and Ocean Sciences, University of
- 11 Victoria, CA
- 12 [4] International Institute for Applied Systems Analysis, Schlossplatz 1, A-2361 Laxenburg, Austria
- 13 [5] NASA Goddard Institute for Space Studies, 2880 Broadway, New York, NY 10025, USA
- 14 [6] Center for Climate Systems Research, Columbia University, 2880 Broadway, New York, NY
- 15 10025, USA
- 16 [7] Department of Physical Geography, Utrecht University, Utrecht, The Netherlands, Heidelberglaan
- 17 2, 3584 CS Utrecht, The Netherlands
- 18 [8] Cabot Institute, University of Bristol, UK
- 19 Corresponding author:
- 20 Dr Andreas Hartmann
- 21 University of Freiburg | Faculty of Environment and Natural Resources
- Friedrichstraße 39, 79098 Freiburg, Germany
- 23 Phone +49.761.203.3520 | Fax +49.761.203.3594
- 24 Keywords
- 25 Groundwater recharge, subsurface heterogeneity, water resources, climate variability, climate
- 26 change

### Abstract

1

2 Our environment is heterogeneous. In hydrological sciences, the heterogeneity of subsurface 3 properties, such as hydraulic conductivities or porosities, exerts an important control on water 4 balance. This notably includes groundwater recharge, which is an important variable for 5 efficient and sustainable groundwater resources management. Current large-scale 6 hydrological models do not adequately consider this subsurface heterogeneity. Here we show 7 that regions with strong subsurface heterogeneity have enhanced present and future recharge 8 rates due to a different sensitivity of recharge to climate variability compared to regions with 9 homogeneous subsurface properties. Our study domain is comprised of the carbonate rock 10 regions of Europe, Northern Africa and the Middle East, which cover ~25% of the total land 11 area. We compare the simulations of two large-scale hydrological models, one of them 12 accounting for subsurface heterogeneity. Carbonate rock regions strongly exhibit 13 "karstification", which is known to produce particularly strong subsurface heterogeneity. 14 Aguifers from these regions contribute up to half of the drinking water supply for some 15 European countries. Our results suggest that water management for these regions cannot rely on most of the presently available projections of groundwater recharge because spatially 16 17 variable storages and spatial concentration of recharge result in actual recharge rates that are 18 up to 4 times larger for present conditions and changes up to 5 times larger for potential future 19 conditions than previously estimated. These differences in recharge rates for strongly 20 heterogeneous regions suggest a need for groundwater management strategies that are adapted 21 to the fast transit of water from the surface to the aquifers.

## Significance

22

23

24

25

26

27

28

29

30

31

Understanding the implications of climate changes on hydrology is crucial for water resources management. Widely-used global hydrological models generally assume simple homogeneous subsurface representations to translate climate signals into hydrological variables. We study groundwater recharge in the carbonate rock regions of Europe, Northern Africa and the Middle East, which are known to exhibit strong subsurface heterogeneity. We demonstrate that subsurface heterogeneity alters the sensitivity of recharge to climate variability and enhances recharge estimates resulting in potentially more available water per capita, than previously estimated. Our results are opposing previous modeling studies on future groundwater availability that assumed homogeneous subsurface properties everywhere.

- 1 We suggest that water management strategies in regions with heterogeneous subsurface
- 2 properties need to consider these revised estimates.
- 3 \body

## Introduction

5 Groundwater recharge is a crucial component of the global water balance, feeding the world's groundwater storages and thereby supplying fresh water to large parts of the global population 6 7 (1-4). Comparing groundwater recharge with groundwater use and ecological water demand 8 helps to distinguish between over-used aguifer systems and aguifer systems that still allow for 9 more abstraction in a sustainable way (5, 6). The importance of managing groundwater 10 sustainably will increase in the future given the growing dependence on this resource in many 11 parts of the world (7). Subsurface heterogeneity notably affects groundwater recharge (4), 12 especially in weathered carbonate rock regions (8). Spatially variable soil thickness and 13 hydraulic conductivity in the subsurface produce fast, localized vertical water movement, thereby enhancing groundwater recharge (9). Our study is the first to take into account the 14 impact of subsurface heterogeneity on present and potential future recharge rates at a 15 continental scale. Subsurface heterogeneity evolves for various reasons (10). In this paper, we 16 confine our modelling domain to carbonate rock regions. Such regions typically exhibit the 17 most extreme subsurface heterogeneity in terms of hydraulic conductivities and storage 18 19 capacities due to the weathering of carbonate rock, a process also referred to as 20 "karstification" (11, 12). We focus on Europe, Northern Africa and the Middle East, where 21 ~560 Million people depend on drinking water from karst aguifers (13, 14), and where 22 information on karst recharge is most available. 23 We simulate groundwater recharge (defined here as the simulated vertical downward flux 24 entering the saturated zone) using both a homogeneous and a heterogeneous subsurface representation (Figure 1). The global hydrological model PCR-GLOBWB (15) is used for the 25 26 homogeneous subsurface representation, while the karst recharge model VarKarst-R (16), which includes variable thickness of the soil, epikarst (the weathered interface of soil and 27 28 carbonate rock) and hydraulic conductivity, is used for the heterogeneous representation. The 29 structure of VarKarst-R is particularly adapted to the dominant hydrological processes of 30 carbonate regions allowing for focused preferential recharge and variable subsurface dynamics that are found in humid, Mediterranean, mountainous and desert karst regions (16). 31

These processes are not included in the PCR-GLOBWB model or other comparable large-1 2 scale hydrological models. We use the output of five general circulation models (GCMs of the 3 ISI-MIP model ensemble (17), 0.5x0.5 degree resolution) to simulate groundwater recharge with each of these two subsurface representations, from 1991 to 2099 under the highest 4 emission scenario (RCP8.5 (18), increasing radiative forcing, >8.5Wm<sup>-2</sup> by 2100, and 5 increasing atmospheric CO<sub>2</sub> concentrations, > 1,370 ppm. CO<sub>2</sub>-equiv. by 2100). In order to 6 avoid biasing our results by selecting one specific GCM, we use ensemble means for all our 7 8 interpretations after applying all five GCMs individually to both subsurface representations, 9 respectively.

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

We assess recharge sensitivity to climate variability using the statistical *elasticity* measure. Beyond a correlation analysis that simply evaluates the strength of relations between variables, elasticity quantifies "how responsive one variable is to change in another variable" or "the percentage change in a first variable to the percentage change in second variable, when the second variable has a causal influence on the first variable" (19, 20). Among several applications of elasticity on stream flow (21–23), we are one of the first in hydrology to apply elasticity to groundwater recharge. Here we define recharge sensitivity as the median ratio of inter-annual changes of recharge rates to the inter-annual changes of three climatic variables that drive recharge and evapotranspiration using a 20-year period: (1) Annual precipitation expresses general water availability, (2) mean annual temperature is used as proxy for potential evapotranspiration, and (3) the mean intensity of high-intensity events is used to account for the non-linear impact of strong rainfall events (24). Similar to (23) we preferred temperature over net radiation as a proxy for potential evapotranspiration because net radiation is temperature dependent and temperature is the best-understood and most common input variable to large-scale hydrological models. Recharge sensitivity with large positive or negative values indicates that recharge is highly sensitive to variations of these input variables. Values closer to 0 indicate a low sensitivity. Recharge sensitivity to precipitation and to high intensity events is calculated with changes normalized by their 20-year average (%%<sup>-1</sup>), while recharge sensitivity to temperature is expressed by normalized changes of recharge per absolute change of temperature (%°C<sup>-1</sup>). Further elaborations on the simulation models, the input variables and the recharge elasticity are provided in the Methods section.

# Realism of heterogeneity processes

1

24

25

26

27

28

29

30

31

32

2 A comparison with observations indicates that the heterogeneous model provides more realistic simulations of recharge than the homogeneous model because it includes 3 4 heterogeneity processes. For validation we compare the recharge simulations of the two models driven by the 5 climate models for the present period (1991-2010) with independent 5 6 recharge observations for 38 karst systems in Europe for which we could obtain recharge values from the literature ((16), Table S1). To better understand how far subsurface 7 8 heterogeneity is actually responsible for the differences of recharge estimations of the two 9 models, we additionally compare the observations from our literature review with simulations 10 of a version of the heterogeneous model where the heterogeneity processes are turned off (i.e., homogeneous subsurface, no lateral flow concertation but surface runoff leaves the grid cell). 11 12 We find that, although significant remains, the simulations of the heterogeneous model plot around the 1:1 line (average deviation 55.8 mma<sup>-1</sup>; Figure 2), while most of the homogeneous 13 models simulations tend to under-estimate recharge (average deviation -232.9 mma<sup>-1</sup>; Figure 14 15 2). When we turn off the heterogeneity processes of the heterogeneous model, its simulations 16 also fall in large parts below the 1:1 line, plotting closer to the simulations of the homogeneous model (average deviation -167.4 mma<sup>-1</sup>). These results do not mean that 17 subsurface heterogeneity is the only reason for the different simulated recharge rates of the 18 19 heterogeneous and homogeneous subsurface representations, since the models also differ with respect to other processes, such as interception or capillary rise of groundwater (see Methods 20 section). However, our comparison suggest that disregarding heterogeneity processes can 21 22 result in an overall under-estimation of recharge, at least for the 38 karst systems that we used 23 in our evaluation.

#### Recharge sensitivity to climate variability

We further find that the two subsurface representations exhibit different sensitivities to climate variability. We divide all carbonate rock areas into 4 regions defined by cluster analysis using climatic and topographic descriptors (16) (Figure 4): humid (HUM), mountains (MTN), Mediterranean (MED), and deserts (DES). Recharge sensitivities to climate variability are calculated for the time period of 1991-2010. Between the four regions, we find a mixed pattern of sensitivity values (Figure 3, Figure S1). We can see that recharge sensitivities to rainfall change from high to low values when moving from wet (humid) to dry (desert) regions for both model representations. The Mediterranean and desert regions mostly

1 exhibit a higher sensitivity to climate variability. The same gradient from wet to dry is found

2 for high-intensity events. We observe the opposite trend for recharge sensitivity to

3 temperature, which increases from humid towards the Mediterranean regions but decreases

4 again in the desert.

For the Mediterranean and desert regions, the heterogeneous representation shows higher sensitivity to changes in annual precipitation, mean annual temperature and high-intensity rainfall events. Recharge estimates of the homogeneous model tends to be more sensitive to changes in precipitation in the humid and mountain regions, as well as to changes in high-intensity rainfall events in the mountain regions. Sensitivities to temperature changes in the humid and mountain regions and to high-intensity rainfall events in the humid regions are similar for both subsurface representations. The general pattern of recharge sensitivities can be explained through the increased fractions of precipitation that become evapotranspiration (25, 26) when moving from the humid toward the desert regions. Water availability (precipitation) is the most important control on recharge sensitivities in the humid region, while temperature is the stronger control in the Mediterranean regions. In the desert region, recharge sensitivity generally decreases, as there is simply little water available for evapotranspiration.

The different recharge sensitivities with respect to climate variability for the two subsurface representations can be explained by the interplay of two different simulated processes. (1) Variable fractions of surface runoff, which dynamically increase or reduce infiltration and (2) different dynamics of evapotranspiration that change the amount of water available for downward percolation. The first explains the higher sensitivities of the homogeneous subsurface representation to humid and mountain region precipitation. The homogeneous model calculates fractions of surface runoff with a non-linear relationship to wetness that is more sensitive for the wet conditions prevailing in humid and mountain regions (Eq. (1) in Methods section). The same process explains the higher sensitivity of the homogeneous model to high-intensity rainfall events. No such partitioning takes place for the heterogeneous model, which produces focused recharge instead of surface runoff and therefore is less sensitive to changes in precipitation and high-intensity rainfall events in those wet regions (humid, mountain). On the other hand, the explicit calculation of soil storages with variable storage capacities in the heterogeneous subsurface representation (Figure 1b, Eq. (2) in Methods section) results in different evapotranspiration dynamics than found in the

- 1 homogeneous model. While soil compartments with small storage capacities saturate rapidly
- 2 and produce focused recharge even during small and moderate rainfall events, the uniform
- 3 soil storages of the homogeneous model (Figure 1a) remain unsaturated more often and
- 4 produce more evapotranspiration. This stronger pronunciation of evapotranspiration in the
- 5 homogeneous model is the reason why its simulated recharge is less sensitive to all three
- 6 input variables for the Mediterranean and the desert regions.

# Future groundwater recharge

- 8 The differences in recharge sensitivity to variability in climate result in different simulated
- 9 present and future recharge rates over Europe's carbonate rock regions. Compared to the
- 10 homogeneous subsurface representation, the heterogeneous subsurface representation shows
- enhanced and more variable recharge rates, for both present and future conditions (Figure 4,
- 12 Figure S3). In the present period (1991-2010), the simulated recharge rates of the
- heterogeneous subsurface representation are 2.1 to 4.3 times larger than the recharge rates of
- the homogeneous representation. Towards the end of the century (2080-2099), the five GCMs
- indicate that in the humid region, future annual precipitation will remain more or less the
- same (2% of absolute increase), while considerable decreases are projected for the mountain
- 17 (-14%), Mediterranean (-19%) and desert regions (-12%). Temperatures are predicted to
- 18 increase for all regions, by 2.0°C, 4.9°C, 5.2°C and 8.1°C in the humid, mountain,
- Mediterranean and desert regions, respectively. Future mean intensity of high-rainfall events
- is predicted to increase for the humid (11%), mountain (8%) and Mediterranean (7%) regions,
- while there is no trend for the desert region (1% increase) (Figure S2).
- 22 As result of the projected climatic change we find a general reduction of recharge rates for
- both subsurface representations, which is consistent with previous findings on the changes of
- 24 future stream flow during low-flow conditions (27). The relative decrease of the two
- subsurface representations is in the same direction. We find reductions of 7-32% and 11-44%
- 26 for the heterogeneous and the homogeneous representation, respectively (Figure 4; Figure
- S3). But the absolute reductions of simulated recharge rates of the heterogeneous
- 28 representation (3–138 mma<sup>-1</sup>) are 2.2 to 5.3 larger than the simulated reductions of the
- 29 homogeneous representation (2-79 mma<sup>-1</sup>). Inter-annual variability of recharge is also
- 30 becoming more pronounced for the heterogeneous representation. This variability increases
- 31 from the humid and mountain regions to the deserts, likely due to the increased variability of
- 32 rainfall events in dry regions (28). In particular, convective storm events are known to

- produce large fractions of preferential recharge in semi-arid or arid regions (9). While
- 2 recharge rates of both simulations are predicted to decrease in all regions, temporal variability
- 3 within the 20-year averages does not change significantly over the same time horizon. Hence,
- 4 with a general decrease of recharge rates, the inter-annual variability of groundwater recharge
- 5 in heterogeneous regions will gain more importance, especially in the Mediterranean, where
- 6 we expect an increase in impact of high-intensity events.

# Discussion

- 8 Focused recharge is known to be an important process of recharge generation in regions with
- 9 heterogeneous subsurface characteristics (4, 29) and its strong impact on overall groundwater
- 10 recharge amounts has been shown in several studies at the catchment scale (30-32). Our
- recharge sensitivity analysis reveals that accounting for this process and the variability of soil
- storages at a much larger spatial scale results in different recharge sensitivities compared to a
- 13 homogeneous subsurface representation that does not consider focused recharge. We
- 14 demonstrate that a heterogeneous recharge modeling approach is more consistent with
- independent recharge estimates of other studies for karst regions, and therefore more likely to
- be a reasonable representation of the water balance separation occurring across the study
- 17 region than current modelling approaches. Our subsequent findings indicate that the water
- balance of heterogeneous areas in the Mediterranean and desert regions will be less dominated
- by evapotranspiration, as compared to regions with homogeneous subsurface properties
- because water is rapidly passed downwards. The heterogeneous subsurface representation
- 21 also suggests smaller amounts of surface runoff than the homogeneous representation. On the
- 22 other hand, the presence of focused recharge and variable soil storage capacities generally
- 23 results in higher recharge rates, which are less affected by the variability of precipitation and
- high-intensity events in the humid and mountain regions.
- Hence, due to the presence of heterogeneity processes, a greater proportion of the water cycle
- is active in the subsurface, meaning the risk of overexploitation may be lower than previously
- 27 considered. Dividing the difference of recharge simulations of the heterogeneous model and
- 28 mean recharge simulations of the homogeneous model in the four regions by their population
- 29 (Figure S4) indicates that an additional ~1000-3300 m³ of groundwater per capita per year are
- 30 potentially available at the present (2900, 3300, 1500 and 950 m³ per capita per year for the
- 31 humid, mountain, Mediterranean and desert region, respectively). Especially in the
- 32 Mediterranean, where previous modeling studies expect significant groundwater stress (5), the

- additional future recharge of 1000 m<sup>3</sup> of groundwater per capita per year may potentially lead
- 2 to less future groundwater stress than previously expected.
- 3 However, estimated groundwater recharge volumes do not equal exploitable groundwater
- 4 fluxes since a number of factors can limit the use of this simulated surplus recharge. First,
- 5 groundwater pumping likely decreases groundwater discharge significantly, spring flow and
- 6 baseflow impacting environmental flow (1, 33). Second, groundwater recharge in carbonate
- 7 rock aquifers may quickly leave the aquifer through large conduit systems and springs (8).
- 8 Third, recharge that is stored within the aquifer may not be fully available for development as
- 9 abstraction wells are usually unable to access the entire volume of the aguifer (33). Forth, the
- 10 high temporal variability of recharge in heterogeneous regions, which is most pronounced at
- 11 the Mediterranean and desert regions (Figure 4), may prohibit continuous withdrawal of
- 12 groundwater. And finally, higher recharge rates imply an increased vulnerability to surface
- 13 contamination due to preferential recharge, which might reduce the value of the groundwater
- 14 resource (34).
- 15 Possible water management strategies include adapted water management plans that take into
- account the variable flow dynamics of these aquifers with heterogeneous recharge behavior.
- 17 For instance, groundwater pumping rates could be adapted to the temporally variable water
- availability (35). Additionally, temporal variability could be compensated for by artificially
- 19 recharging aquifers with longer residence times using water discharged from the more
- 20 heterogeneous regions (36, 37). Regardless, the requirements to sustain environmental flow
- 21 (1) and the increased vulnerability to contamination due to preferential recharge (34) have to
- be accounted for in any water management plan. The concerns are especially acute in the
- 23 Mediterranean region where the expected increase of rainfall intensity and the high inter-
- 24 annual variability of recharge will require adapted measures for water resources management
- and protection to finally use the potentially additional recharge that we found in our study.
- 26 Such management strategies are important since 116 million inhabitants and 80% of
- agriculture depend on irrigation (Figure S4) in the Mediterranean region.
- 28 This study focuses on how to represent subsurface heterogeneity in large-scale hydrological
- 29 models. Our results imply that subsurface heterogeneity significantly alters groundwater
- 30 recharge and its sensitivity to climate variability at large spatial scales. The explicit
- 31 consideration of variable storage capacities and focused recharge within the heterogeneous
- model is novel compared to previous large-scale modeling studies that considered their soil

layers to be homogenous (38, 39). Considering heterogeneity processes within our model produces less evapotranspiration and surface runoff and more groundwater recharge. This difference produces and potentially more available groundwater per capita than previously estimated (15). Current simulations of land surface-atmosphere coupling (26), drought occurrence (27, 40), flood frequency projections (41) or water scarcity assessment (42) are currently based on large-scale hydrological models with homogeneous subsurface representations. Our study shows that their results may have reduced utility for groundwater management for regions with pronounced subsurface heterogeneity. Through our parsimonious simulation approach, we also provide a promising direction to include subsurface heterogeneity evolved due to karstification into any large-scale hydrological model to obtain more realistic simulations.

1 2

# **Materials and Methods**

- 2 The homogeneous model PCR-GLOBWB
- 3 The PCR-GLOBWB model(15) simulates the terrestrial water balance on a 0.5° x 0.5° grid
- 4 using a daily temporal resolution. Soil water balance of two homogeneous soil layers and a
- 5 single underlying aquifer layer is calculated at each time step. Simulated hydrological
- 6 processes comprise infiltration of rainfall and snowmelt, evapotranspiration, interception,
- 7 downward percolation from the upper soil layer to the lower soil layer and from the lower soil
- 8 layer to the aquifer layer (which is the flux we consider the simulated recharge of the
- 9 homogeneous model in this study), and capillary rise from the groundwater up to the
- 10 unsaturated soil. The model parameters are found using prior information from public
- sources, e.g., the FAO Digital Soil Map of the World (43) or a simplified version of the
- 12 lithological map of the world (44). No calibration is performed.
- Like other global hydrological models (38, 45), PCR-GLOBWB uses a distribution function
- 14 to account for the impact of spatial variability of land-surface properties on the generation of
- 15 surface runoff:

16 
$$x(t) = 1 - \left(\frac{S(t)}{S_{\text{max}}}\right)^{\frac{b}{b+1}}$$
 (1)

- Where x(t) is the fraction of effective precipitation at time t that becomes surface runoff, S(t)
- is the total soil storage (layers 1+2) at time t,  $S_{max}$  is the maximum total soil storage, and b is a
- 19 dimensionless shape factor based on subgrid information on the distribution of land-cover
- 20 classes with tall and short vegetation, paddy and non-paddy irrigation, land and open water,
- and different soil types(46). The surface runoff calculated by Eq. (1) leaves the grid cell
- 22 towards the stream (Figure 1a in the research letter).
- 23 The heterogeneous model VarKarst-R
- 24 The VarKarst-R(16) also simulates terrestrial hydrological processes on a 0.5° x 0.5° grid and
- at a daily temporal resolution. Its structure considers infiltration of rainfall and snowmelt,
- evapotranspiration, downward percolation from the upper soil layer to a lower soil epikarst
- 27 layer and vertical percolation from the epikarst layer towards the groundwater (which is the
- 28 flux we defined as simulated recharge of the heterogeneous model in this study). The epikarst
- in the second layer is a typical feature of karst systems regarded as the hydrological unit that

- 1 controls the dynamic separation of focused and diffuse groundwater recharge (47, 48). In
- 2 general, the VarKarst-R model has a simpler structure (only 4 free parameters) compared to
- 3 PCR-GLOBWB (29 free parameters) as it uses less explicit representations of hydrological
- 4 processes, for instance it does not explicitly consider interception or capillary rise from the
- 5 groundwater.
- 6 The special feature of the VarKarst-R model is its assumption that even within the same
- 7 hydrological landscape type there is a distribution of subsurface properties. This variability is
- 8 expressed by distribution functions that allow for variability of soil and epikarst storage
- 9 capacities, as well as of epikarst hydraulic properties, over N horizontally parallel model
- 10 compartments (Figure 1b):

$$11 S_{\max,i} = S_{\max,N} \left(\frac{i}{N}\right)^a (2)$$

12 
$$K_{epi,i} = K_{epi,1} \left(\frac{N-i+1}{N}\right)^a$$
 (3)

- Where  $S_{max,i}$  [mm] is the soil or epikarst storage capacity of model compartment i,  $S_{max,N}$  [mm]
- 14 is the overall maximum storage capacity of the soil or the epikarst,  $K_{epi,i}$  [d] is the storage
- 15 constant of the epikarst at model compartment i,  $K_{epi,1}$  [d] is the storage constant of the
- epikarst at model compartment 1, and a [-] is a dimensionless shape factor. Using the
- 17 distributions from Eqs. (2) and (3) soil and epikarst water balance are simultaneously
- calculated at each time step and in each model compartment. The epikarst can only reach
- 19 saturation when infiltration exceeds vertical percolation (actual epikarst storage divided by
- 20  $K_{epi,i}$ ). The fraction of effective precipitation that exceeds soil and epikarst water deficit
- becomes surface runoff. However, in contrast to PCR-GLOBWB, surface runoff is not routed
- towards the streams but transferred laterally to the next model compartment (from i to i+1)
- 23 where it is added again to effective precipitation. Increasing epikarst permeability (Eq. (3))
- 24 therefore allows for lateral flow concentration along the model compartments (Figure 1b in
- 25 the research letter).
- 26 Since large-scale information on subsurface heterogeneity in carbonate rock regions is not
- 27 available, a new procedure to estimate the VarKarst-R model parameters was developed (16).
- 28 Based on cluster analysis and the concept of hydrological landscapes that includes climate
- and topographic information (16, 49), carbonate rock regions are divided into 4 regions:

- 1 humid (HUM), mountains (MTN), Mediterranean (MED), and deserts (DES). A large sample
- of initial model parameter sets (n=25,000) is iteratively reduced using prior information (e.g.,
- 3 the FAO Digital Soil Map of the World (43)), FLUXNET (50) latent heat flux observations
- 4 and soil moisture observations of the International Soil Moisture Network ISMN (51) in each
- of the regions. For each karst landscape, the reduced parameters ranges of acceptable latent
- 6 heat flux and soil moisture simulations directly express the remaining parameter uncertainty.
- 7 For this study, we sampled 250 parameter sets from these reduced ranges to obtain an
- 8 ensemble of 250 model realizations in each grid cell to quantify the uncertainty of the
- 9 VarKarst-R recharge simulations due to the parameter estimation process.
- 10 Climate change scenarios
- Both simulation models are driven by the same climate forcing derived from the bias-
- 12 corrected 5 GCMs of the ISI-MIP data (17). We chose the highest emission scenario of
- 13 available Representative Concentrations Pathways (RCP 8.5), with strongly increased
- radiative forcing and atmospheric CO<sub>2</sub> concentrations(18) to obtain the worst case scenario
- between current and future conditions. Similar to previous studies on climate change impacts
- 16 (26), we consider 20-year periods to analyze changes in climate and groundwater recharge.
- 17 By calculating running averages and their standard deviation of the GCM ensemble mean for
- each of the four sub-regions, we can assess average recharge and its sensitivity to climate
- variability, including their transitions towards the end of this century.
- 20 Elasticity calculations
- We define recharge elasticity  $E_R$  [-] as the median of the inter-annual changes of recharge
- rates R [mma<sup>-1</sup>] according to trans-annual changes of a controlling variable X, normalized by
- 23 their annual means over a pre-defined period (e.g. 20 years):

$$E_{R} = median\left(\frac{\Delta R}{\Delta X}\right) \tag{1}$$

- As in previous studies(19, 21) we prefer the median of trans-annual changes rather than their
- 26 mean so as to avoid bias due to outliers. As control variables, we consider annual
- 27 precipitation P [mm], temperature T [°C] and the annual mean of rainfall intensity of high
- 28 intensity events [mmd<sup>-1</sup>], defined as the mean intensity of the upper quartile of rainfall
- events. Hereby P represents the influence of the total annual water availability on recharge, T
- 30 is a proxy for the influence of energy available for evapotranspiration, and  $H_{INT}$  is an indicator

- 1 for the influence of strong rainfall events on recharge (also see elaborations in the letter
- 2 above). Similar to other studies (26), we consider 20 years long enough to reflect climatic
- 3 variability. While R, P and  $H_{INT}$  are normalized by their mean over this 20-year period, we do
- 4 not normalize T because temperature changes cannot be meaningfully represented as %.

# 5 Acknowledgements

- 6 This work was supported by a fellowship to Andreas Hartmann within the Postdoc
- 7 Programme of the German Academic Exchange Service (DAAD).

# 8 References

- 9 1. Gleeson T, Wada Y, Bierkens MF, van Beek LP (2012) Water balance of global aquifers revealed by groundwater footprint. *Nature* 488(7410):197–200.
- Taylor RG, et al. (2012) Ground water and climate change. *Nat Clim Chang* 3(4):322–329.
- Döll P, Fiedler K (2008) Global-scale modeling of groundwater recharge. *Hydrol Earth Syst Sci* 12(3):863–885.
- de Vries JJ, Simmers I (2002) Groundwater recharge: an overview of processes and challenges. *Hydrogeol J* 10(1):5–17.
- Wada Y, Van Beek LPH, Bierkens MFP (2012) Nonsustainable groundwater sustaining irrigation: A global assessment. *Water Resour Res* 48(1). doi:10.1029/2011WR010562.
- Aeschbach-Hertig W, Gleeson T (2012) Regional strategies for the accelerating global problem of groundwater depletion. *Nat Geosci* 5(12):853–861.
- 7. Gleeson T, et al. (2010) Groundwater sustainability strategies. *Nat Geosci* 3(6):378–379.
- 24 8. Ford DC, Williams PW (2013) *Karst Hydrogeology and Geomorphology* (John Wiley & Sons).
- 26 9. Scanlon BR, et al. (2006) Global synthesis of groundwater recharge in semiarid and arid regions. *Hydrol Process* 20(15):3335–3370.
- 28 10. McDonnell JJ, et al. (2007) Moving beyond heterogeneity and process complexity: A new vision for watershed hydrology. *Water Resour Res* 43(7):W07301.
- 30 11. Ford DC, Williams PW (2007) *Karst Hydrogeology and Geomorphology* (Wiley, 31 Chichester).
- Worthington SRH, Davies GJ, Alexander EC (2016) Enhancement of bedrock permeability by weathering. *Earth-Science Rev* 160:188–202.
- 34 13. Hartmann A, Goldscheider N, Wagener T, Lange J, Weiler M (2014) Karst water
- resources in a changing world: Review of hydrological modeling approaches. *Rev Geophys* 52(3):218–242.

- 1 14. COST (1995) COST 65: Hydrogeological aspects of groundwater protection in karstic areas, Final report (COST action 65). *Eur Comm Dir XII Sci Res Dev* Report EUR:446.
- Wada Y, Wisser D, Bierkens MFP (2014) Global modeling of withdrawal, allocation and consumptive use of surface water and groundwater resources. *Earth Syst Dyn* 5(1):15–40.
- Hartmann A, et al. (2015) A large-scale simulation model to assess karstic groundwater recharge over Europe and the Mediterranean. *Geosci Model Dev* 8(6):1729–1746.
- Hempel S, Frieler K, Warszawski L, Schewe J, Piontek F (2013) A trend-preserving bias correction the ISI-MIP approach. *Earth Syst Dyn* 4(2):219–236.
- 10 18. Moss RH, et al. (2010) The next generation of scenarios for climate change research and assessment. *Nature* 463(7282):747–756.
- 12 19. Schaake JC (1990) From climate to flow. *Climate Change and US Water Resources.*, ed Waggoner PE (John Wiley, New York), pp 177–206.
- 14 20. OECD (1993) Glossary of industrial organisation economics and competition law eds
  15 Khemani RS, Shapiro DM (Organisation for Economic Co-operation and
  16 Development,, commissioned by the Directorate for Financial, Fiscal and Enterprise
  17 Affairs).
- 18 21. Andréassian V, Coron L, Lerat J, Le Moine N (2015) Climate elasticity of streamflow revisited an elasticity index based on long-term hydrometeorological records. *Hydrol Earth Syst Sci Discuss* 12(4):3645–3679.
- 22. Berghuijs WR, Hartmann A, Woods RA (2016) Streamflow sensitivity to water storage changes across Europe. *Geophys Res Lett.* doi:10.1002/2016GL067927.
- 23. Vano J a., Das T, Lettenmaier DP (2012) Hydrologic Sensitivities of Colorado River 24. Runoff to Changes in Precipitation and Temperature\*. *J Hydrometeorol* 13(3):932– 25. 949.
- 24. Taylor RG, et al. (2012) Evidence of the dependence of groundwater resources on extreme rainfall in East Africa. *Nat Clim Chang* 3(4):374–378.
- 28 25. Prudhomme C, et al. (2014) Hydrological droughts in the 21st century, hotspots and uncertainties from a global multimodel ensemble experiment. *Proc Natl Acad Sci U S* 30 A 111(9):3262–7.
- 31 26. Seneviratne SI, Lüthi D, Litschi M, Schär C (2006) Land–atmosphere coupling and climate change in Europe. *Nature* 443(7108):205–209.
- Forzieri G, et al. (2014) Ensemble projections of future streamflow droughts in Europe. *Hydrol Earth Syst Sci* 18(1):85–108.
- 28. Lionello P (2012) The Climate of the Mediterranean Region: From the past to the future (Elsevier). first edit.
- 37 29. Scanlon B, Healy R, Cook P (2002) Choosing appropriate techniques for quantifying groundwater recharge. *Hydrogeol J* 10(1):18–39.
- 39 30. Malard A, Sinreich M, Jeannin P (2015) A novel approach for estimating karst groundwater recharge in mountainous regions and its application in. *Hydrol Process*:DOI: 10.1002/hyp.10765.

- 1 31. Andreo B, et al. (2008) Methodology for groundwater recharge assessment in carbonate aquifers: application to pilot sites in southern Spain. *Hydrogeol J* 16(5):911–925.
- 4 32. Allocca V, Manna F, De Vita P (2014) Estimating annual groundwater recharge coefficient for karst aquifers of the southern Apennines (Italy). *Hydrol Earth Syst Sci* 18(2):803–817.
- 7 33. Bredehoeft JD (2002) The water budget myth revisited: why hydrogeologists model. 8 Ground Water 40(4):340–345.
- 9 34. Andreo B, et al. (2006) Karst groundwater protection: First application of a Pan-10 European Approach to vulnerability, hazard and risk mapping in the Sierra de Líbar 11 (Southern Spain). *Sci Total Environ* 357(1–3):54–73.
- 12 35. Fleury P, Ladouche B, Conroux Y, Jourde H, Dörfliger N (2009) Modelling the hydrologic functions of a karst aquifer under active water management The Lez spring. *J Hydrol* 365(3–4):235–243.
- 15 36. Xanke J, Jourde H, Liesch T, Goldscheider N (2016) Numerical long-term assessment of managed aquifer recharge from a reservoir into a karst aquifer in Jordan. *J Hydrol* 540:603–614.
- 18 37. Valhondo C, et al. (2016) Tracer test modeling for local scale residence time 19 distribution characterization in an artificial recharge site. *Hydrol Earth Syst Sci* 20 *Discuss*:1–17.
- 21 38. Sood A, Smakhtin V (2015) Global hydrological models: a review. *Hydrol Sci J* 60(4):549–565.
- 23 39. Davie JCS, et al. (2013) Comparing projections of future changes in runoff from hydrological and biome models in ISI-MIP. *Earth Syst Dyn* 4(2):359–374.
- 25 40. Dai A (2012) Increasing drought under global warming in observations and models. 26 *Nat Clim Chang* 3(1):52–58.
- Hirabayashi Y, et al. (2013) Global flood risk under climate change. *Nat Clim Chang* 3(9):816–821.
- 29 42. Schewe J, et al. (2014) Multimodel assessment of water scarcity under climate change. 30 *Proc Natl Acad Sci U S A* 111(9):3245–3250.
- 31 43. FAO (2003) Digital Soil Map of the World (Rome).
- 32 44. Dürr HH, Meybeck M, Dürr SH (2005) Lithologic composition of the Earth's continental surfaces derived from a new digital map emphasizing riverine material transfer. *Global Biogeochem Cycles* 19(4):1–23.
- 35 45. Döll P, Kaspar F, Lehner B (2003) A global hydrological model for deriving water availability indicators: model tuning and validation. *J Hydrol* 270(1–2):105–134.
- Hagemann S, Gates LD (2003) Improving a subgrid runoff parameterization scheme for climate models by the use of high resolution data derived from satellite observations. *Clim Dyn* 21(3–4):349–359.
- 40 47. Hartmann A, Lange J, Weiler M, Arbel Y, Greenbaum N (2012) A new approach to model the spatial and temporal variability of recharge to karst aquifers. *Hydrol Earth*

- 1 *Syst Sci* 16(7):2219–2231.
- Williams PW (1983) The role of the Subcutaneous zone in karst hydrology. *J Hydrol* 61:45–67.
- 4 49. Winter TC (2001) The Concept of Hydrologic Landscapes. *JAWRA J Am Water Resour* 4ssoc 37(2):335–349.
- 6 50. Baldocchi D, et al. (2001) FLUXNET: A New Tool to Study the Temporal and Spatial Variability of Ecosystem–Scale Carbon Dioxide, Water Vapor, and Energy Flux Densities. *Bull Am Meteorol Soc* 82(11):2415–2434.
- Dorigo WA, et al. (2011) The International Soil Moisture Network: a data hosting facility for global in situ soil moisture measurements. *Hydrol Earth Syst Sci* 15(5):1675–1698.

# 12 Supplementary information

- 13 A table listing all references for the evaluation of the models, maps of model input, simulation
- results and calculated elasticities are provided in the supplementary information.

#### Author contributions

15

21

- 16 Andreas Hartmann performed the analysis and developed the manuscript. Tom Gleeson
- 17 provided guidance and advice during analysis and manuscript development. Yoshihide Wada
- provided the PCR-GLOBWB data, guidance and advice during analysis and manuscript
- 19 development. Thorsten Wagener provided guidance and advice during analysis and
- 20 manuscript development.


# Figure legends

1


7

- 2 Figure 1: A homogenoeus and a heterogeneous representation of the subsurface. Two different
- 3 representations of the subsurface of a simulation grid-cell (0.5x0.5 decimal degree); (a) homogeneous subsurface
- 4 representation by the PCR-GLOBWB global simulation model (15) and (b) heterogeneous subsurface
- 5 representation by the VarKarst-R large-scale karst recharge model (16).
- 6 Figure 2: Comparison of simulations and observations. Simulated recharge volumes of the heterogeneous
  - model (VarKarst-R), the homogeneous model (PCR-GLOBWB), and the heterogeneous model with subsurface
- 8 heterogeneity processes turned off plotted against observed recharge volumes (Table S 1); coloured and grey
- 9 whiskers indicate the simulation uncertainty (1 standard deviation) due to the 5 climate models and due to
- parameter uncertainty (only heterogeneous model and heterogeneous model with heterogeneity processes turned
- off, see Methods section), respectively. We find a significant difference (p ) between the heterogeneous
- model and the homogeneous model, as well as between the heterogeneous model and the heterogeneous model
- with heterogeneity processes turned off. There is no statistical difference (5% significance level) between the
- homogeneous model and the heterogeneous model with heterogeneity processes turned off, as well as between
- 15 the heterogeneous model and the observations.
- 16 Figure 3: Sensitivity to climate variability. Recharge sensitivity to (a) annual precipitation, (b) mean annual
- temperature and (c) high-intensity events (mean intensity of the upper quartile of rainfall events) for the four
- regions (HUM: humid, MTN: mountain, MED: Mediterranean, DES: desert) at the present (1991-2010);
- 19 uncertainty of simulated recharge sensitivities of the heterogeneous model due to parameter uncertainty (see
- Methods section) to annual precipitant, temperature and strong rainfall events vary by 0.13 -0.24 %%<sup>-1</sup>, 0.03-
- 21 0.18%°C<sup>-1</sup> and 0.18-0.37 %%<sup>-1</sup>, respectively (1 standard deviation, increasing from humid to desert regions).
- 22 Figure 4: Simulation of future groundwater recharge. Simulation results for the two subsurface
- representations for 4 regions; spatial variability within each region for the present (1991-2010) is presented by
- 24 the boxplots, temporal evolution of recharge rates is expressed by a 20-year moving average (centered around its
- mean year, for instance the year 2000 for the 1991-2010 average); temporal variability within each 20-year
- window is expressed by its standard deviation indicated by the grey shading round the mean (grey dashed line
- 27 represents lower boundary of the heterogeneous model temporal variability at the desert regions); simulation
- 28 uncertainty of the heterogeneous model due to parameter uncertainty (see Methods section) is indicated by the
- dashed lines around the mean recharge.


# Figures




**Figure 1: A homogenoeus and a heterogeneous representation of the subsurface.** Two different representations of the subsurface of a simulation grid-cell (0.5x0.5 decimal degree); (a) homogeneous subsurface representation by the PCR-GLOBWB global simulation model (15) and (b) heterogeneous subsurface representation by the VarKarst-R large-scale karst recharge model (16).



**Figure 2: Comparison of simulations and observations.** Simulated recharge volumes of the heterogeneous model (VarKarst-R), the homogeneous model (PCR-GLOBWB), and the heterogeneous model with subsurface heterogeneity processes turned off plotted against observed recharge volumes (Table S 1); coloured and grey whiskers indicate the simulation uncertainty (1 standard deviation) due to the 5 climate models and due to parameter uncertainty (only heterogeneous model and heterogeneous model with heterogeneity processes turned off, see Methods section), respectively. We find a significant difference (p< p<10<sup>-5</sup>) between the heterogeneous model and the homogeneous model, as well as between the heterogeneous model and the heterogeneous model with heterogeneous model and the heterogeneous model with heterogeneous model and the observations.



**Figure 3: Sensitivity to climate variability.** Recharge sensitivity to (a) annual precipitation, (b) mean annual temperature and (c) high-intensity events (mean intensity of the upper quartile of rainfall events) for the four regions (HUM: humid, MTN: mountain, MED: Mediterranean, DES: desert) at the present (1991-2010); uncertainty of simulated recharge sensitivities of the heterogeneous model due to parameter uncertainty (see Methods section) to annual precipitant, temperature and strong rainfall events vary by 0.13 -0.24 %%<sup>-1</sup>, 0.03-0.18%°C<sup>-1</sup> and 0.18-0.37 %%<sup>-1</sup>, respectively (1 standard deviation, increasing from humid to desert regions).



**Figure 4: Simulation of future groundwater recharge.** Simulation results for the two subsurface representations for 4 regions; spatial variability within each region for the present (1991-2010) is presented by the boxplots, temporal evolution of recharge rates is expressed by a 20-year moving average (centered around its mean year, for instance the year 2000 for the 1991-2010 average); temporal variability within each 20-year window is expressed by its standard deviation indicated by the grey shading round the mean (grey dashed line represents lower boundary of the heterogeneous model temporal variability at the desert regions); simulation uncertainty of the heterogeneous model due to parameter uncertainty (see Methods section) is indicated by the dashed lines around the mean recharge.