

UNCLASSIFIED

AD NUMBER
AD843585
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; Sep 1968. Other requests shall be referred to Aeronautical Systems Division, Directorate of Airframe Subsystems Engineering, Attn: ASNFL, Wright-Patterson AFB, OH 45433.
AUTHORITY
ASD USAF ltr, 1 May 1972

THIS PAGE IS UNCLASSIFIED

ASD-TR-68-34

AD 843585


**EVALUATION OF AIRCRAFT LANDING GEAR  
GROUND FLOTATION CHARACTERISTICS  
FOR OPERATION FROM  
UNSURFACED SOIL AIRFIELDS**

*DONALD H. GRAY*

*DONALD E. WILLIAMS*

TECHNICAL REPORT ASD-TR-68-34

SEPTEMBER 1968



This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Directorate of Airframe Subsystems Engineering (ASNFL), Aeronautical Systems Division, Wright-Patterson AFB, Ohio 45433.

DEPUTY FOR ENGINEERING  
AERONAUTICAL SYSTEMS DIVISION  
AIR FORCE SYSTEMS COMMAND  
WRIGHT-PATTERSON AIR FORCE BASE, OHIO

**Best Available Copy**



ASD-TR-68-34

**EVALUATION OF AIRCRAFT LANDING GEAR  
GROUND FLOTATION CHARACTERISTICS  
FOR OPERATION FROM  
UNSURFACED SOIL AIRFIELDS**

*DONALD H. GRAY*

*DONALD E. WILLIAMS*

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Directorate of Airframe Subsystems Engineering (ASNFL), Aeronautical Systems Division, Wright-Patterson AFB, Ohio 45433.

FOREWORD

The work reported here has evolved from a need to establish flotation requirements for several proposed systems and numerous flotation capability studies for existing aircraft in support of the ASD mission.

This report was submitted by the authors in May 1968.

This technical report is published for use, within the ASD environment, as a standard method in evaluating aircraft ground flotation capabilities of present and proposed air-vehicle designs operating from unsurfaced soil airfields.

Publication of this report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.

*William A. Hamilton*

WILLIAM A. HAMILTON  
Chief, Launching & Alighting Division  
Directorate of Airframe Subsystems  
Engineering

ABSTRACT

This report presents a theoretical method of evaluating aircraft landing gear ground flotation characteristics on unsurfaced soil airfields. Equations developed in AFFDL-TR-66-43, Part I, Aircraft Ground Flotation Investigation, form the basis for the method used in this report.

It contains a list of definitions of terms used in regard to ground flotation within ASD and presents a method of evaluating the ground flotation characteristics and capabilities of aircraft to operate from unsurfaced soil airfields. The method presented is relatively straightforward and is applicable to most aircraft having conventional landing gear configurations. A sample calculation is also presented.

(Distribution of this abstract is unlimited.)

TABLE OF CONTENTS

SECTION	PAGE
I INTRODUCTION	1
II AIRCRAFT GROUND FLOTATION ANALYSIS	2
III SAMPLE CALCULATIONS	5
APPENDIX PERTINENT DIAGRAMS AND CURVES	10
REFERENCES	18

ILLUSTRATIONS

FIGURE		PAGE
1.	Single Wheel Loads	12
2.	Equivalent Single-Wheel Load-Adjustment Curve for Unsurfaced Soils	13
3.	Equivalent Single-Wheel Load (1000 lb)	14
4.	$\frac{CBR}{CBR_1}$ vs Coverages	15
5.	Passes per Coverage	16
6.	Aircraft Passes	17



SYMBOLS

A	Single tire contact area (square inches)
AP	Aircraft passes
B	Lateral distance between centerlines of the most inboard and most outboard tires of one main landing gear assembly (inches)
b	Tire deflection (percent)
C	Coverage
CBR	California Bearing Ratio (percent)
CBR <sub>1</sub>	CBR required for one coverage
CP	Contact pressure - not inflation pressure (pounds per square inch)
D	Lateral distance between the centerlines of the most outboard tires of the nose landing gear assembly (inches)
DWL	Dynamic wheel loads (kips)
D <sub>F</sub>	Wheel flange diameter (inches) (bead dia. +2 times flange height)
D <sub>O</sub>	Tire outside diameter-nominal for new tires (inches)
d	Tire radial deflection (inches)
E	Lateral distance between centerlines of the left and right main landing gear assemblies (inches)
ESWL	Equivalent single wheel load (kips)
F	Forward to aft distance between the centerlines of the main and nose landing gear assemblies (inches)
GW	Gross weight of aircraft (pounds)
H	Aircraft passes correction factor due to main landing gear spacing
J	Height of CG (at gross weight under consideration)
K	Aircraft passes correction factor due to relative spacing of main and nose landing gear assemblies
L	Distance maximum forward CG (at gross weight under consideration) is aft of nose landing gear centerline (inches)
M	Distance maximum aft CG (at gross weight under consideration) is forward of main landing gear centerline (inches)

SYMBOLS (CONTD)

N	Number of tires of a landing gear assembly
P	Passes
P/C	Passes per coverage ratio
R	Tire contact area radius (inches) $R = .564 \sqrt{A}$
SWL	Single wheel load (kips)
W	Width of single tire contact area (inches) $W = .875 \sqrt{A}$
w	Tire section width - nominal for new tires (inches)

Subscript Symbols

M	Main landing gear factor
N	Nose landing gear factor

## DEFINITION OF TERMS

### Assembly Load

The landing gear assembly load used for ground flotation calculations shall be that static load which results from the specified aircraft gross weight condition.

### California Bearing Ratio (CBR)

A measure of the bearing capacity of soil. The CBR of a soil is expressed in terms of a percentage of the bearing capacity of a standard crushed limestone surface. Details of test procedures used to determine the CBR of a soil are contained in MIL-STD-621.

### Coverage (C)

This term when applied to a point means one movement of the wheel over that point. Coverage of an area is defined as the covering of every point in the area.

### Equivalent Single Wheel Load (ESWL)

The theoretical load which, if acting on a single tire, with a contact area equal to that of one tire of the assembly, will produce the same effect on the airfield as the multiple wheel assembly.

### Pass or Aircraft Pass (P) or (AP)

A movement or passage of the aircraft past a given lateral station.

### Single Wheel Load (SWL)

The calculated load on each tire of a landing gear assembly. It is computed by dividing the assembly load by the number of tires on the assembly.

### Tire Contact Area (A)

The calculated area of the tire footprint which is in contact with the airfield surface.

## SECTION I INTRODUCTION

This report is to provide an interim standard for evaluation of aircraft landing gear designs proposed for operation on unsurfaced soils. The report is published to give preliminary guidance for design of advanced systems.

The method contained herein may be used to evaluate relative ground flotation performance for aircraft operation in the conventional takeoff and landing (CTOL) or short field takeoff and landing (STOL) mode on unsurfaced soils. Ground flotation performance is expressed in terms of the number of operations that could be performed on a heavy clay soil prior to formation of permanent rutting to a depth of about three inches. The method allows consideration of single wheel loads in the range of 5000 to 75,000 pounds and tire contact pressures in the range of 20 to 300 pounds per square inch.

This report, when specified, supersedes the Theater of Operations airfield ground flotation evaluation procedures contained in AFSCM 80-1, Handbook of Instructions for Aircraft Design.

The general procedure for evaluation of landing gear flotation for operation from unsurfaced soils consists of computation of the number of passes that the aircraft should be able to perform on a specified strength airfield prior to attainment of a defined failure condition. The number of passes predicted is then compared with the required number of passes to determine if the landing gear is acceptable. Due to the many variables involved, it is essential that a standard calculation procedure be used.

## SECTION II

### AIRCRAFT GROUND FLOTATION ANALYSIS

The following has been developed as an interim standard procedure:

#### Determination of Single Wheel Load (SWL)

**Main Landing Gear Wheels** — Analyze the aircraft at the specified gross weight condition and the most critical center of gravity position (most critical for ground flotation), using Figure 1a to determine the individual landing gear assembly loads. Divide the assembly load by the number of tires per assembly to determine the single wheel load.

**Nose Landing Gear Wheels** — Analyze the aircraft at the specified gross weight condition and the most critical center of gravity position (most critical for overall aircraft ground flotation) to determine the dynamic load on the nose landing gear assembly due to braking at a deceleration rate of 10 feet/second/second. The procedure outlined in Figure 1b will be used. The assembly load is divided by the number of tires on the assembly to determine the single wheel load.

#### Tire Inflation Pressure

The tire inflation pressure used for ground flotation analysis should be the pressure required to support the most severe loading condition without exceeding the specified tire deflection limits. Therefore, in the following ground flotation analysis, loads resulting from a maximum forward center of gravity (CG) position will be used in nose landing gear tire inflation pressure calculations and, accordingly, the main landing gear tire inflation pressures will be based on main landing gear loads resulting from an aft CG position.

The following calculations should be made for both the main and nose gear assemblies.

Determination of Tire Contact Area (A)

Tire contact area shall be determined by use of the following relations:

$$A = 2.36d \sqrt{(D_o - d)(w - d)} \text{ and}$$

$$d = \frac{b(D_o - D_F)}{200}$$

where A = Tire contact area

d = Tire radial deflection in inches

$D_o$  = Tire outside diameter in inches

w = Tire section width in inches

b = Tire deflection under consideration in per cent

$D_F$  = Wheel flange diameter in inches

Tire Contact Pressure (CP)

Tire contact pressure is determined by dividing the single wheel load by the calculated contact area.

Equivalent Single Wheel Load (ESWL)

Figure 2 is used to determine the equivalent single wheel load. Determine the center to center spacing in radii by dividing the actual tire spacing by the radius of a circle of area equal to the single tire contact area. Increase the single wheel load for each adjacent wheel by the percentage indicated by Figure 2 to determine the equivalent single wheel load. This adjacent wheel may be "adjacent" by virtue of either a twin or tandem wheel arrangement. In either case, if it is more than 5 1/2 single tire contact area radii from the wheel under consideration, it will not be considered in determining the equivalent single wheel load. Note that in the case of a landing gear with a single isolated wheel, the equivalent single wheel load is equal to the single wheel load.

Coverages (C)

Enter Figure 3 with the equivalent single wheel load and tire contact pressure of the assembly in question to determine a value of  $CBR_1$ . The

ASD-TR-68-34

number of coverages to failure of the airfield is then determined by the following relation:

$$\text{Coverages} = \left( \frac{\text{C B R}}{\text{C B R}_1} \right)^6$$

Where CBR is the strength of the airfield under consideration.

(Figure 4 can be used to simplify this calculation.)

#### Passes Per Coverage Ratio (P/C)

Use the procedures of Figure 5 to determine the passes per coverage for the assembly under consideration.

#### Passes (P)

Multiply the number of coverages by the passes per coverage ratio to determine the number of passes that the assembly can accomplish prior to failure of the airfield.

#### Aircraft Passes (AP)

Use the procedures of Figure 6 to determine the number of passes of the aircraft that can be accomplished prior to failure of the airfield.

SECTION III

SAMPLE CALCULATIONS

EXAMPLE SITUATION

How many passes can an aircraft weighing 60,000 pounds and configured as below make on an unprepared airfield with CBR of 4 without failure of the surface provided the tires are allowed to operate 50% deflected.

Nose Tires - 9.50-16 Type III

Main Tires - 12.50-16 Type III

$D_o = 33.4''$

$D_o = 38.5''$

$D_F = 18.0''$


$D_F = 18.5''$

$b = 50\%$

$b = 50\%$

$w = 9.7''$

$w = 12.75''$



Example Configuration



a. Single Wheel Load Calculation (SWL) - Reference Figure 1

<p><u>Main Wheels:</u></p> $SWL_M = \frac{GW \times (F - M)}{F \times N_M}$ $= \frac{60,000 (275 - 55)}{275 \times 4}$ $= 12,000 \text{ lbs}$	<p><u>Nose Wheels:</u></p> $SWL_N = \frac{GW \times (F - L)}{F \times N_N} + \frac{10 \times GW \times J}{32.2 \times F \times N_N}$ $= \frac{60,000 (275 - 200)}{275 \times 2} + \frac{10 \times 60,000 \times 105}{32.2 \times 275 \times 2}$ $= 8,180 + 3,550$ $= 11,730 \text{ lbs}$
---	--

b. Single Tire Contact Area (A)

<p><u>Main Wheels:</u></p> $d = \frac{b (D_o - D_i)}{200}$ $= \frac{50 (38.5 - 18.5)}{200}$ $= 5.0'' \text{ deflection}$ $A = 2.36d \sqrt{(D_o - d)(w - d)}$ $= 2.36 \times 5 \sqrt{(38.5 - 5)(12.75 - 5)}$ $= 190 \text{ sq in}$	<p><u>Nose Wheels:</u></p> $d = \frac{b (D_o - D_i)}{200}$ $= \frac{50 (33.4 - 18)}{200}$ $= 3.85'' \text{ deflection}$ $A = 2.36d \sqrt{(D_o - d)(w - d)}$ $= 2.36 \times 3.85 \sqrt{(33.4 - 3.85)(9.7 - 3.85)}$ $= 119.5 \text{ sq in}$
---	---

c. Contact Pressure Calculation (CP)

<p><u>Main Wheels:</u></p> $P_M = \frac{SWL_M}{A_M}$ $= \frac{12,000}{190}$ $= 63 \text{ psi}$	<p><u>Nose Wheels:</u></p> $P_N = \frac{SWL_N}{A_N}$ $= \frac{11,730}{119.5}$ $= 98.1 \text{ psi}$
--	--

d. Equivalent Single Wheel Load Calculations (ESWL) - Reference Figure 2

Main Wheels:

Single tire contact area  
radius -

$$R_M = .564 \sqrt{A}$$

$$= .564 \sqrt{190}$$

$$= 7.78 \text{ inches}$$

$$\frac{B}{R_M} = \frac{24}{7.8} = 3.08 \text{ radii}$$

$$ESWL_M = SWL_M + (\text{Fig 2 Factor})$$

$$= 12,000 + 53 \%$$

$$= 18,350 \text{ lbs}$$

Nose Wheels:

Single tire contact area  
radius -

$$R_N = .564 \sqrt{A}$$

$$= .564 \sqrt{119.8}$$

$$= 6.17 \text{ inches}$$

$$\frac{D}{R_N} = \frac{18}{6.17} = 2.92 \text{ radii}$$

$$ESWL_N = SWL_N + (\text{Fig 2 Factor})$$

$$= 11,730 + 59 \%$$

$$= 18,650 \text{ lbs}$$

e. Coverages Calculations (C) - Reference Figures 3 and 4

Main Wheels:

From Fig 3 with

$$ESWL_M = 18,350 \text{ lbs}$$

$$P = 63 \text{ psi}$$

Obtain  $CBR_1 = 2.4$

$$C_M = \left( \frac{CBR}{CBR_1} \right)^6$$

$$= \left( \frac{4}{2.4} \right)^6$$

$$= (1.67)^6$$

$$= 21 \text{ coverages}$$

Nose Wheels:

From Fig 3 with

$$ESWL_N = 18,650 \text{ lbs}$$

$$P = 98 \text{ psi}$$

Obtain  $CBR_1 = 3.7$

$$C_N = \left( \frac{CBR}{CBR_1} \right)^6$$

$$= \left( \frac{4}{3.7} \right)^6$$

$$= (1.08)^6$$

$$= 1.6 \text{ coverages}$$

f. Passes per Coverage Ratio Calculations (P/C) - Reference Figure 5

Main Wheels:

$$\begin{aligned}
 P/C &= \frac{B + 80 + W_M}{.75 N_M W_M} \\
 &= \frac{24 + 80 + .874\sqrt{190}}{.75 \times 2 \times .874\sqrt{190}} \\
 &= \frac{116.0}{18.2} \\
 &= 6.4 \text{ P/C}
 \end{aligned}$$

Nose Wheels:

$$\begin{aligned}
 P/C &= \frac{D + 80 + W_N}{.75 N_N W_N} \\
 &= \frac{18 + 80 + .874\sqrt{119}}{.75 \times 2 \times .874\sqrt{119}} \\
 &= \frac{107}{14.3} \\
 &= 7.5 \text{ P/C}
 \end{aligned}$$

g. Passes Calculation (P)

Main Wheels:

$$P_M = 21 \times 6.4 = 134 \text{ passes}$$

NOSE Wheels:

$$P_N = 1.6 \times 7.5 = 12 \text{ passes}$$

Aircraft Passes Calculations (AP) - Reference Figure 6

$$\begin{aligned}
 X &= E - W_M - B \\
 &= 140 - 12.75 - 24 \\
 &= 103
 \end{aligned}$$

from Fig 6 (B)

$$H = 80$$

$$\begin{aligned}
 Y &= \frac{E - W_M - W_N - B - D}{2} \\
 &= \frac{140 - 12.75 - 9.7 - 24 - 18}{2}
 \end{aligned}$$

$$= 38$$

from Fig 6 (C)

$$K = 38$$

## h. Aircraft Passes Calculations (AP) (Continued)

Main Wheels:

$$\begin{aligned}
 AP_M &= \frac{80 P_M P_N}{80P_N + (80-H)P_N + (80-K)P_M} \\
 &= \frac{80 \times 134 \times 12}{(80 \times 12) + (80-80)12 + (80-38)134} \\
 &= \frac{128,640}{960 + 0 + 5628} \\
 &= \frac{128,640}{6,588} \\
 &= 19.5 \text{ aircraft passes}
 \end{aligned}$$


Nose Wheels:

$$\begin{aligned}
 AP_M &= \frac{80 P_M P_N}{80P_M + (80-H)P_N + (80-K)P_N} \\
 &= \frac{80 \times 134 \times 12}{(80 \times 134) + (80-80)12 + (80-38)12} \\
 &= \frac{128,640}{10,720 + 0 + 504} \\
 &= \frac{128,640}{11,224} \\
 &= 11.5 \text{ aircraft passes}
 \end{aligned}$$

## SOLUTION

Comparing the calculated values of  $AP_M$  and  $AP_N$ , paragraph h, it is indicated that the aircraft in question could make 11 passes on an unprepared surface having a CBR of 4.

APPENDIX  
PERTINENT DIAGRAMS AND CURVES



a. Main Gear - Single Wheel Static Load

$$SWL_M = \frac{GW \times (F-M)}{F \times N_M}$$

Where:

GW = Aircraft Gross Weight

$N_M$  = Number of main wheels on aircraft

b. Nose Gear - Single Wheel Dynamic Load


$$SWL_N = \frac{GW \times (F-L)}{F \times N_N} + \frac{10 \times GW \times J}{32.2 \times F \times N_N}$$

Where

GW = Aircraft Gross Weight

$N_N$  = Number of nose wheels

Figure 1. Single Wheel Loads



\* Increase in load on a single wheel of a multiple-wheel gear to account for effects of adjacent wheels of the Multiple-wheel gear in arriving at an equivalent single-wheel load.

Figure 2. Equivalent Single-Wheel Load-Adjustment Curve For Unsurfaced Soils




Figure 3. Equivalent Single Wheel Load (1000 lb)







Figure 4.  $\frac{CBR}{CBR_1}$  - Coverages



PROCEDURE


$$\text{Main Assembly: } P/C = \frac{B + 80 + W_M}{(0.75) (N_M) (W_M)}$$

$$\text{Nose Assembly: } P/C = \frac{D + 80 + W_N}{(0.75) (N_N) (W_N)}$$

SYMBOLS

- P/C Passes per coverage
- $N_M$  Number of tires per main gear assy
- $N_N$  Number of tires per nose gear assembly
- $W_M$  Width of main single tire contact area  $W_M = 0.874 \sqrt{A_M}$
- $W_N$  Width of nose single tire contact area  $W_N = 0.874 \sqrt{A_N}$
- $A_M$  Single tire contact area of main tires
- $A_N$  Single tire contact area of nose tires

Figure 5. Passes Per Coverage



PROCEDURE

1. Determine dimension

$$X = E - W_M - B$$

$$Y = \frac{E - W_M - W_N - B - D}{2}$$

2. Use figure (B) to determine "H" and figure (C) to determine "K"

3. Compute:

$$AP_M = \frac{80 P_M P_N}{80 P_N + (80 - H) P_N + (80 - K) P_M}$$

$$AP_N = \frac{80 P_M P_N}{80 P_M + (80 - H) P_N + (80 - K) P_N}$$

Where

$P_M$  = allowable passes for the main gear

$P_N$  = allowable passes for the nose gear

4. The allowable number of aircraft passes (AP) is then equal to the smaller value,  $AP_M$  or  $AP_N$ .

5. All dimensions are in inches.

Figure 6. Aircraft Passes

REFERENCES

1. D. Ladd and H. Ulery Jr., Aircraft Ground Flotation Investigation, Part I, AFFDL-TR-66-43, Part I, Wright-Patterson Air Force Base, Ohio Aug 1967.
2. Handbook of Instructions for Aircraft Design (HIAD), AFSCM 80-1.
3. "Subgrade, Subbase, and Test Method for Pavement Base-Course Materials," MIL-STD-621.

UNCLASSIFIED  
Security Classification

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1. ORIGINATING ACTIVITY (Corporate author) Deputy For Engineering Aeronautical Systems Division Wright-Patterson Air Force Base, Ohio		2a. REPORT SECURITY CLASSIFICATION Unclassified
		2b. GROUP
3. REPORT TITLE EVALUATION OF AIRCRAFT LANDING GEAR GROUND FLOTATION CHARACTERISTICS FOR OPERATION FROM UNSURFACED SOIL AIRFIELDS		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
5. AUTHOR(S) (Last name, first name, initial) Gray, Donald H. Williams, Donald E.		
6. REPORT DATE September 1968	7a. TOTAL NO. OF PAGES 27	7b. NO. OF REFS 3
8a. CONTRACT OR GRANT NO.	8b. ORIGINATOR'S REPORT NUMBER(S) ASD-TR-68-34	
b. PROJECT NO.		
c.	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d.		
10. AVAILABILITY/LIMITATION NOTICES This document is subject to special export controls, and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Directorate of Airframe Subsystems Engineering (ASNFL), Aeronautical Systems Division, Wright-Patterson AFB, Ohio 45433.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Deputy For Engineering Aeronautical Systems Division Wright-Patterson Air Force Base, Ohio 45433	
13. ABSTRACT This report presents a theoretical method of evaluating aircraft landing gear ground flotation characteristics on unsurfaced soil airfields. Equations developed in AFFDL-TR-66-43, Part I, Aircraft Ground Flotation Investigation, form the basis for the method used in this report. It contains a list of definitions of terms used in regard to ground flotation within ASD and presents a method of evaluating the ground flotation characteristics and capabilities of aircraft to operate from unsurfaced soil airfields. The method presented is relatively straightforward and is applicable to most aircraft having conventional landing gear configurations. A sample calculation is also presented.  (Distribution of this abstract is unlimited.)		

DD FORM 1473  
1 JAN 64

UNCLASSIFIED  
Security Classification

14. KEY WORDS  <p align="center"><b>Unsurfaced Soil Airfield Flotation Aircraft Flotation Evaluation</b></p>	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT

**INSTRUCTIONS**

**1. ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

**2a. REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

**2b. GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

**3. REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

**4. DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

**5. AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

**6. REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

**7a. TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

**7b. NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

**8a. CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

**8b, 8c, & 8d. PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

**9a. ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

**9b. OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

**10. AVAILABILITY LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

**11. SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

**12. SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

**13. ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

**14. KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical content. The assignment of links, rules, and weights is optional.