



Technical Report No. 2

EXTERNAL ELLIPTICAL CRACK IN ELASTIC SOLID

by
M.K. Kassir
G.C. Sih

INTERNATIONAL INFORMATION TO MECHANICAL ENGINEERS

FACILITY FORM 602

N 68-13943
(ACCESSION NUMBER)

November 1967

20
(PAGES)

(THRU)

CR-91667
(NASA CR OR TMX OR AD NUMBER)

(CODE)

32
(CATEGORY)

Department of Applied Mechanics
Lehigh University, Bethlehem, Pennsylvania

National Aeronautics
and
Space Administration

Grant NGR-39-007-025

Technical Report No. 2

EXTERNAL ELLIPTICAL CRACK IN ELASTIC SOLID

by

M. K. Kassir and G. C. Sih

Department of Applied Mechanics
Lehigh University
Bethlehem, Pennsylvania

~~October, 1967~~

EXTERNAL ELLIPTICAL CRACK IN ELASTIC SOLID¹

by

M. K. Kassir² and G. C. Sih³

ABSTRACT

Potential functions are developed for both symmetric and antisymmetric three-dimensional problems of an infinite elastic solid containing a flat crack covering the outside of an ellipse. The knowledge of these functions permits an examination of the stress and displacement fields everywhere in the cracked solid as well as in a toroidal region around the crack border. Stress-intensity factors k_j ($j=1,2,3$) corresponding to the three basic modes of fracture are obtained. The results of this paper, coupled with those found previously by the authors for the problem of internal elliptical crack, are essential in making approximate estimates of k_j - values for solids with arbitrarily-shaped planar cracks.

¹The work reported herein was supported by the National Aeronautics and Space Administration under Grant NGR-39-007-025 with Lehigh University.

²Lecturer, Department of Civil Engineering, The City College, New York, New York.

³Professor of Mechanics, Lehigh University, Bethlehem, Pennsylvania.

INTRODUCTION

In the examination of fracture failures of solids weakened by planar cracks, it is unlikely that the configuration of the initial starting crack would be an ellipse or any other idealized shape conforming to the existing curvilinear coordinate systems. Since the mathematical problem of cracks in three-dimensions involving complicated crack geometry prohibits any analytical solution, it is useful to solve some relatively simple, but basic, component crack problems whose solutions may provide rough estimates of the fracture behavior of irregularly-shaped cracks. The component problems may consist of an internal and external elliptical crack embedded in the solid. By varying the ellipticity of the internal and external crack, it is possible to approximate the periphery⁴ of an arbitrarily-shaped crack by joining a sequence of segments of the elliptical boundary.

Green and Sneddon [1]⁵ have discussed the symmetric problem of the internal elliptical crack while Kassir and Sih [2] have solved the antisymmetric problem dealing with the same geometry. In this paper, exact solutions to the problem of two half-spaces connected through an elliptically-shaped region are given. The two half-spaces are either pulled apart symmetrically or sheared

⁴It is assumed that the periphery of the crack is sufficiently smooth and contains no sharp edges.

⁵Numbers in brackets designate references at end of paper.

apart antisymmetrically with respect to the crack plane. With the help of the limiting forms of ellipsoidal to polar coordinates defined locally from the crack border as established by Kassir and Sih [2], stress-intensity factors are calculated and the results are presented graphically.

STATEMENT OF THE PROBLEM

In the formulation of boundary problems of elliptic crack, it is expedient to use ellipsoidal coordinates (ξ, η, ζ) which are defined as the roots of the equation in s as

$$\frac{x^2}{a^2+s} + \frac{y^2}{b^2+s} + \frac{z^2}{s} = 1$$

The restrictions placed on ξ, η, ζ are

$$-a^2 \leq \zeta \leq -b^2 \leq \eta \leq 0 \leq \xi < \infty$$

Referring to the work of Kassir and Sih [2-4], they have pointed out that a wide variety of three-dimensional problems involving discontinuity in the shape of an ellipse can be solved by making use of potentials (satisfying the Laplace equation in the variables x, y, z) in the form

$$I(x, y, z) = \int_{\xi}^{\infty} \lambda[\omega(s)] \frac{ds}{\sqrt{Q(s)}} \quad (1)$$

where

$$\omega(s) = 1 - \frac{x^2}{a^2+s} - \frac{y^2}{b^2+s} - \frac{z^2}{s}$$

and $Q(s) = s(s+a^2)(s+b^2)$. Without exception, harmonic functions

of the type shown in equation (1) will also be employed in the present treatment. In elastostatics, these functions are associated with the components u_x , u_y , u_z of the displacement vector \underline{u} such that \underline{u} satisfies the Navier equation

$$\nabla^2 \underline{u} + \frac{1}{1-2\nu} \nabla \nabla \cdot \underline{u} = 0 \quad (2)$$

Here, ν is Poisson's ratio and the body forces are assumed to be absent.

By an "external elliptical crack", it is meant the union of two half-spaces across a plane in the shape of an ellipse. Let this plane region Σ ($x^2/a^2 + y^2/b^2 = 1, z = 0$) be located in the xy -plane so that the z -axis is directed normally to Σ and the origin of the cartesian coordinate system coincides with the center of the ellipse. In terms of ellipsoidal coordinates, the point $(x,y,0)$ inside and outside the region Σ can be identified by $\xi = 0$ and $\eta = 0$, respectively. This problem will be split into two parts; one symmetric and the other antisymmetric with respect to the plane $z = 0$. In each case, the problem reduces to one of selecting the appropriate harmonic potentials that satisfy the prescribed boundary conditions.

SYMMETRIC PROBLEM

When the stress distribution is symmetric with respect to the plane $z = 0$, the equilibrium of the cracked solid can be considered under the following conditions

$$u_z = \sigma_{zx} = \sigma_{zy} = 0, \xi = 0 \quad (3)$$

$$\sigma_{xz} = \sigma_{yy} = \sigma_{zz} = 0, \eta = 0$$

The resultant normal force⁶ acting on the elliptical region Σ is designated by

$$P = \int_{\Sigma} \int (\sigma_{zz})_{\xi=0} dx dy \quad (4)$$

For this problem, Boussinesq's solution of the elastic equations of equilibrium, equation (2), can be employed. That is

$$\begin{aligned} u_x &= (1-2\nu) \frac{\partial f}{\partial x} + z \frac{\partial^2 f}{\partial x \partial z}, \\ u_y &= (1-2\nu) \frac{\partial f}{\partial y} + z \frac{\partial^2 f}{\partial y \partial z}, \\ u_z &= -2(1-\nu) \frac{\partial f}{\partial z} + z \frac{\partial^2 f}{\partial z^2}, \end{aligned} \quad (5)$$

in which the harmonic potential $f(x,y,z)$ satisfies the Laplace equation

$$\nabla^2 f(x,y,z) = 0$$

The relevant stress components corresponding to the displacements in equation (5) are

⁶The specification of uniform stress at infinity should be avoided since it leads to unbounded tensile force across the region Σ .

$$\frac{\sigma_{xz}}{2\mu} = z \frac{\partial^3 f}{\partial x \partial z^2}, \quad \frac{\sigma_{yz}}{2\mu} = z \frac{\partial^3 f}{\partial y \partial z^2}, \quad \frac{\sigma_{zz}}{2\mu} = -\frac{\partial^2 f}{\partial z^2} + z \frac{\partial^3 f}{\partial z^3} \quad (6)$$

with μ being the shear modulus of the elastic solid. On the plane $z = 0$, it is obvious that the shear stresses σ_{xz} and σ_{yz} vanish while the normal stress σ_{zz} becomes

$$\sigma_{zz} = -2\mu \frac{\partial^2 f}{\partial z^2}, \quad z = 0 \quad (7)$$

As a special case of equation (1) with $\lambda[\omega(s)] = A$ (const.), let $\partial f / \partial z$ be equal to

$$\frac{\partial f}{\partial z} = A \int_{\xi}^{\infty} \frac{ds}{\sqrt{Q(s)}} = \frac{2A}{a} u \quad (8)$$

In equation (8), u is a variable related to ξ by the relation

$$\xi = a^2 (\operatorname{sn}^{-2} u - 1)$$

and hence it takes the value of $K(k)$ at $\xi = 0$, where $K(k)$ is the complete elliptic integral of the first kind associated with the argument $k^2 = 1 - (b/a)^2$. In addition, since

$$\frac{\partial^2 f}{\partial z^2} = -\frac{2A[\eta\zeta(a^2+\xi)(b^2+\xi)]^{1/2}}{ab(\xi-\eta)(\xi-\zeta)} \quad (9)$$

σ_{zz} vanishes automatically for $\eta = 0$. The only remaining condition, $u_z = 0$ for $\xi = 0$, in equation (3) can be satisfied by rewriting u_z in equation (5) as

$$u_z = -2(1-\nu) \frac{\partial f}{\partial z} + 2(1-\nu) A \int_0^{\infty} \frac{ds}{\sqrt{Q(s)}} + z \frac{\partial^2 f}{\partial z^2}$$

The additional term corresponds to a rigid body displacement and will not affect the state of stress. Now, inserting equation (9) into (7) and the result subsequently into equation (4) yield

$$p = \frac{4\mu A}{ab} \int_{\Sigma} \int \frac{dxdy}{(1-x^2/a^2-y^2/b^2)^{1/2}} = 8\pi\mu A \quad (10)$$

and thus

$$A = \frac{P}{8\pi\mu}$$

The solution is essentially complete. Once $\partial f/\partial z$ is known, the stresses and displacements throughout the elastic solid can be calculated.

ANTISYMMETRIC PROBLEM

Suppose that the stresses in the solid are distributed antisymmetrically with respect to the plane $z = 0$, then

$$u_x = u_y = \sigma_{zz} = 0, \quad \xi = 0 \quad (11)$$

$$\sigma_{xz} = \sigma_{yz} = \sigma_{zz} = 0, \quad \eta = 0$$

In this case, the resultant shear forces transmitted across Σ in the x - and y -directions will be denoted by

$$Q = \int_{\Sigma} \int (\sigma_{xz})_{\xi=0} dxdy, \quad \text{and} \quad R = \int_{\Sigma} \int (\sigma_{yz})_{\xi=0} dxdy \quad (12)$$

A solution of Navier's equations that gives zero normal

stress σ_{zz} everywhere in the plane $z = 0$ can be written in terms of two harmonic potentials:

$$\begin{aligned} u_x &= 2 \frac{\partial g}{\partial z} - 2\nu \int_z^\infty \frac{\partial G}{\partial x} dz - z \frac{\partial G}{\partial x} \\ u_y &= 2 \frac{\partial h}{\partial z} - 2\nu \int_z^\infty \frac{\partial G}{\partial y} dz - z \frac{\partial G}{\partial y} \\ u_z &= (1-2\nu) G - z \frac{\partial G}{\partial z} \end{aligned} \quad (13)$$

The function $G(x,y,z)$ stands for

$$G = \frac{\partial g}{\partial x} + \frac{\partial h}{\partial y}$$

in which $g(x,y,z)$ and $h(x,y,z)$ satisfy

$$\nabla^2 g(x,y,z) = 0, \quad \nabla^2 h(x,y,z) = 0$$

From the stress-displacement relations, it is found that

$$\frac{\sigma_{xz}}{2\mu} = \frac{\partial^2 g}{\partial z^2} - z \frac{\partial^2 G}{\partial x \partial z}, \quad \frac{\sigma_{yz}}{2\mu} = \frac{\partial^2 h}{\partial z^2} - z \frac{\partial^2 G}{\partial y \partial z}, \quad \frac{\sigma_{zz}}{2\mu} = z \frac{\partial^2 G}{\partial z^2} \quad (14)$$

The stress components σ_{xx} , σ_{yy} , and σ_{xy} can be found in the same way.

First, let the elliptical connection Σ be sheared along the major axis with $R = 0$. In such a case, it is appropriate to set

$$\frac{\partial g}{\partial z} = B \int_\xi^\infty \frac{ds}{\sqrt{Q(s)}}, \quad h(x,y,z) = 0 \quad (15)$$

from which it can be readily verified that σ_{xz} and σ_{yz} vanish outside the region Σ at $z = 0$. As in the symmetric problem, the displacements u_x and u_y in equation (13) are modified into the forms

$$u_x = 2 \frac{\partial g}{\partial z} - 2B \int_0^{\infty} \frac{ds}{\sqrt{Q(s)}} - 2\nu \int_z^{\infty} \frac{\partial^2 g}{\partial x^2} dz + 2\nu \int_0^{\infty} \left(\frac{\partial^2 g}{\partial x^2} \right)_{\xi=0} dz - z \frac{\partial^2 g}{\partial x^2}, \quad (16)$$

$$u_y = - 2\nu \int_z^{\infty} \frac{\partial^2 g}{\partial x \partial y} dz + 2\nu \int_0^{\infty} \left(\frac{\partial^2 g}{\partial x \partial y} \right)_{\xi=0} dz - z \frac{\partial^2 g}{\partial x \partial y}$$

such that $u_x = u_y = 0$ for $\xi = 0$, and the stresses in equation (14) remain unchanged. Having satisfied all the boundary conditions, the constant B is evaluated from equation (12) with $\sigma_{yz} = 0$ for $\xi = 0$. The result is

$$B = - \frac{Q}{8\pi\mu} \quad (17)$$

If the action of shear is directed along the minor axis of the ellipse $x^2/a^2 + y^2/b^2 = 1$, then $Q = 0$ in equation (12), and

$$g(x,y,z) = 0, \quad \frac{\partial h}{\partial z} = C \int_{\xi}^{\infty} \frac{ds}{\sqrt{Q(s)}} \quad (18)$$

Similarly, expressions pertaining to rigid body motions may be added onto u_x and u_y so as to satisfy equation (11). The constant C is found to be

$$C = - \frac{R}{8\pi\mu} \quad (19)$$

It is clear that the two foregoing results may be superposed to render the complete solution to the problem of an external elliptical crack sheared in its own plane along any given direction.

CRACK-EXTENSION FORCE

To compute the strain-energy change for a small opening of the crack boundary or the force tending to cause crack extension, it is pertinent to obtain asymptotic expansions of the appropriate stress components about the crack border. In this way, the crack stress-field parameters k_j ($j=1,2,3$) can be determined and the crack-extension forces G_j ($j=1,2,3$) can then be found from the relationships⁷

$$G_1 = \frac{\pi(1-\nu^2)}{E} k_1^2, \quad G_2 = \frac{\pi(1-\nu^2)}{E} k_2^2, \quad G_3 = \frac{\pi(1+\nu)}{E} k_3^2 \quad (20)$$

where E is Young's modulus of elasticity.

The parameters k_j , commonly known as the stress-intensity factors, can be evaluated from the formulas

$$k_1 = \lim_{r \rightarrow 0} \sqrt{2r} (\sigma_{zz})_{\theta=0}$$

⁷Kassir and Sih [2] have shown that the combined state of plane strain and of anti-plane deformation always prevail near the border of an embedded crack under arbitrary loadings.

$$k_2 = \lim_{r \rightarrow 0} \sqrt{2r} (\sigma_{nz})_{\theta=0} \quad (21)$$

$$k_3 = \lim_{r \rightarrow 0} \sqrt{2r} (\sigma_{tz})_{\theta=0}$$

The shear stresses σ_{nz} and σ_{tz} act in the directions normal and tangent to the ellipse $x^2/a^2 + y^2/b^2 = 1$ and they can be associated with the rectangular components σ_{xz} and σ_{yz} by means of the following transformations [2]

$$\sigma_{nz} = (b\sigma_{xz} \cos \phi + a\sigma_{yz} \sin \phi)(a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-1/2} \quad (22)$$

$$\sigma_{tz} = (-a\sigma_{xz} \sin \phi + b\sigma_{yz} \cos \phi)(a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-1/2}$$

More precisely, the set of axes n , t , and z are always situated along the binormal, tangent, and principal normal of the crack boundary, respectively. The angle ϕ is referenced from the major axis of the ellipse as illustrated in Figures 1 and 2. In equation (21), the radial distance r is measured from the crack front in the nz -plane and the angle θ from the elliptical region Σ .

In view of equation (21), the evaluation of k_j requires only the $(1/\sqrt{2r})$ - terms of σ_{nz} , σ_{tz} , and σ_{zz} because the non-singular terms vanish in the limit as $r \rightarrow 0$. These singular terms can be found from a knowledge of the limiting forms of

(ξ, η, ζ) to (r, θ) ⁸:

$$\begin{aligned}\xi &= 2abr \left(\sin \frac{\theta}{2}\right)^2 (a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-1/2} \\ \eta &= -2abr \left(\cos \frac{\theta}{2}\right)^2 (a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-1/2} \\ \zeta &= -(a^2 \sin^2 \phi + b^2 \cos^2 \phi)\end{aligned}\quad (23)$$

(a) Opening Mode

With the aid of equation (23), equation (9) may be inserted into equation (7) to obtain

$$(\sigma_{zz})_{\theta=0} = \frac{P}{2\pi\sqrt{ab}} (a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-1/4} \frac{1}{\sqrt{2r}} + O(r^0) \quad (24)$$

From equation (21), the stress-intensity factor k_I for the opening mode is found⁹:

$$k_I = \frac{P}{2\pi\sqrt{ab}} (a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-1/4} \quad (25)$$

For a circular connection, $a = b$, and equation (25) simplifies to

⁸For details, refer to the paper by Kassir and Sih [2], equation (55). Their definition of the angle θ is equal to π minus that given in equation (23).

⁹This result was simply stated by Westmann [5] without any detailed derivations.

$$k_1 = \frac{P}{2\pi a^{3/2}}$$

The variations of k_1 in equation (25) with the angle ϕ for different values of a/b are plotted in Figure 1. Note that k_1 attains its maximum value at $\phi = 0, \pi$, where the crack boundary intersects the major axis of the ellipse. Based on the notion of brittle fracture theory, if the tension P is sufficiently large, the elliptical bond should spread inward and tend to produce a circular bond of radius b . Any further crack propagation will reduce the radius of the circular bond to the point of complete separation of the solid into two half-spaces.

This is contrary to the situation of an internal elliptical crack. It was shown by Irwin [6] that the maximum k_1 -value occurs at $\phi = \pm \pi/2$. Hence, an internal elliptical crack will propagate outward into the solid and tend to produce a penny-shaped crack of radius a , the major semiaxis of the ellipse. A graphical representation of Irwin's result is given by Kassir and Sih [2].

From the results of the elliptical crack and bond problems, estimates can be made for stress-intensity factor for quite arbitrary crack-front contours in solids under tensile loads.

(b) Shearing And Tearing Modes

The k_j -factors ($j=2,3$) for an elliptical connection sheared along the major axis can be computed by the same pro-

cedure. The results of combining equations (14), (15), (22), and (23) are

$$\sigma_{nz} = \frac{Q}{2\pi} \sqrt{\frac{b}{a}} \cos \phi (a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-3/4} \frac{1}{\sqrt{2r}} + O(r^0) \quad (26)$$

$$\sigma_{tz} = -\frac{Q}{2\pi} \sqrt{\frac{a}{b}} \sin \phi (a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-3/4} \frac{1}{\sqrt{2r}} + O(r^0)$$

from which k_j ($j=2,3$) in equation (21) can be deduced:

$$k_2 = \frac{Q}{2\pi} \sqrt{\frac{b}{a}} \cos \phi (a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-3/4} \quad (27)$$

$$k_3 = -\frac{Q}{2\pi} \sqrt{\frac{a}{b}} \sin \phi (a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-3/4}$$

If $a = b$, equation (27) reduces to the k_j -values of a penny-shaped connection given by

$$k_2 = \frac{Q \cos \phi}{2\pi a^{3/2}}, \quad k_3 = -\frac{Q \sin \phi}{2\pi a^{3/2}}$$

Figures 2 and 3 show the results of k_2 and k_3 in equation (27) in the form of curves. It is seen that k_2 decreases in magnitude as the angle ϕ is increased from 0° to 90° at which k_2 vanishes. On the other hand, since a state of pure shearing prevails at $\phi = 0^\circ$, $k_3 = 0$. At other points of the crack border, both k_2 and k_3 are present. However, their combined effect leading to brittle fracture is not known as a priori. For this reason,

the shape into which the elliptical bond would spread under the action of shear can only be determined experimentally by assuming that the function

$$f(k_2, k_3) = f_{cr}$$

reaches certain critical value at the onset of crack propagation.

When the elliptical bond is sheared along the minor axis with resultant force R, the same procedures may be employed to find the stress-intensity factors

$$k_2 = \frac{R}{2\pi} \sqrt{\frac{a}{b}} \sin \phi (a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-3/4} \quad (28)$$

$$k_3 = \frac{R}{2\pi} \sqrt{\frac{b}{a}} \cos \phi (a^2 \sin^2 \phi + b^2 \cos^2 \phi)^{-3/4}$$

Equation (28) is strictly analogous to equation (27) and thus no separate comment is required.

REFERENCES

1. Green, A. E. and Sneddon, I. N., "The Distribution of Stress in the Neighborhood of a Flat Elliptical Crack in an Elastic Solid", Proc. Cambridge Phil. Soc., Vol. 46, pp. 159-164, (1950).
2. Kassir, M. K. and Sih, G. C., "Three-Dimensional Stress Distribution Around an Elliptical Crack Under Arbitrary Loadings", J. Appl. Mech. Vol. 33, pp. 601-611, (1966).

3. Kassir, M. K. and Sih, G. C., "Geometric Discontinuities in Elastostatics", J. Math. Mech. Vol. 16, pp. 927-948, (1967).
4. Kassir, M. K. and Sih, G. C., "Some Three-Dimensional Inclusion Problems in Elasticity", Int. J. Engng. Sci. (in Press).
5. Westmann, R. A., "Note on Estimating Critical Stress for Irregularly-Shaped-Planar Cracks", Int. J. Fracture Mech. Vol. 2, pp. 561-563, (1966).
6. Irwin, G. R., "Crack-Extension Force for a Part-Through Crack in a Plate", J. Appl. Mech. Vol. 29, pp. 651-654, (1962).

TITLE OF FIGURES

Figure 1 - Stress-Intensity Factor For Opening Mode.

Figure 2 - Stress-Intensity Factor For Shearing Mode.

Figure 3 - Stress-Intensity Factor For Tearing Mode.





