

[< Back to results](#) | 1 of 1

[Export](#) [Download](#) [Print](#) [E-mail](#) [Save to PDF](#) [Add to List](#) [More... >](#)
[Full Text](#) | [View at Publisher](#)
Document type

Article

Source type


Journal

ISSN

00019240





DOI

10.1017/aer.2020.53


[View more](#) 

Aeronautical Journal • Volume 124, Issue 1281, Pages 1740 - 1760 • November 2020

Finite - element modelling of NiTi shape - memory wires for morphing aerofoils

Wan A. Hamid W.L.H. , Iannucci L. , Robinson P. 
 Save all to author list

Department of Aeronautics, Imperial College London, London, United Kingdom

Views count 
[View all metrics >](#)
[Abstract](#)[Author keywords](#)[Reaxys Chemistry database information](#)[Indexed keywords](#)[SciVal Topics](#)[Metrics](#)[Funding details](#)**Abstract**

This paper presents the development and implementation of a user-defined material (UMAT) model for NiTi Shape - Memory Alloy (SMA) wires for use in LS-DYNA commercial explicit finite - element analysis software. The UMAT focusses on the Shape - Memory Effect (SME), which could be used for actuation of aerostructural components. The actuation of a fundamental structure consisting of an SMA wire connected in series with a linear spring was studied first. The SMA thermomechanical behaviour obtained from the finite - element simulation was compared with that obtained from the analytical solution in MATLAB. A further comparison is presented for an SMA-actuated cantilever beam, showing excellent agreement in terms of the SMA stress and strain as well as the tip deflection of the cantilever beam. A mesh sensitivity study on the SMA wire indicated that one beam element was adequate to accurately predict the SMA thermomechanical behaviour. An analysis of several key parameters showed that, to achieve a high recovery strain, the stiffness of the actuated structure should be minimised while the cross-sectional area of the SMA wire should be maximised. The actuation of an SMA wire under a constant stress/load was also analysed. The SMA material model was finally applied to the design of morphing aluminium and composite aerofoils consisting of corrugated sections, resulting in the prediction of reasonably large trailing-edge deflections (7.8-65.9 mm). © 2020 Cambridge University Press. All rights reserved.



Author keywords

Keywords: Shape - memory alloy (SMA); LS-DYNA; morphing structures; shape - memory effect (SME); UMAT

[Reaxys Chemistry database information](#) 

Substances

View all substances (2)



Cited by 0 documents

Inform me when this document is cited in Scopus:

[Set citation alert >](#)
Related documents

Characterization of shape memory alloy micro-springs for application in morphing wings

 Emiliavaca, A. , De Araujo, C.J. , Souto, C.R. (2019) *Smart Materials and Structures*

Self-sensing-based deflection control of carbon fibre-reinforced polymer (CFRP)-based shape memory alloy hybrid composite beams

 Lee, S.-H. , Kim, S.-W. (2020) *Composite Structures*

Optimisation of composite corrugated skins for buckling in morphing aircraft

 Shaw, A.D. , Dayyani, I. , Friswell, M.I. (2015) *Composite Structures*

View all related documents based on references

Find more related documents in Scopus based on:

[Authors >](#) [Keywords >](#)

Engineering controlled terms

Binary alloys; Cantilever beams; MATLAB; Nanocantilevers; Shape - memory alloy; Titanium alloys; Wire

Engineering uncontrolled terms

Actuated structures; Cross sectional area; Explicit finite element analysis; Finite element modelling; Finite element simulations; Fundamental structures; NiTi shape memory alloys; Thermomechanical behaviour

Engineering main heading

Finite element method

**Topic name**

Morphing; Wing Camber; Ailerons

Prominence percentile

94.689

Scopus metrics

Views count Last updated on 19 May 2021

Views count 2021

Views count 2020

Views count 2012-2021

PlumX metrics

Captures

Readers

View PlumX details >

Funding sponsor	Funding number	Acronym
Ministry of Higher Education, Malaysia		MOHE
See opportunities by MOHE ↗		
International Islamic University Malaysia		IIUM
See opportunities by IIUM ↗		

Funding text

The research is funded by the Ministry of Education Malaysia and IIUM, which is hereby gratefully acknowledged.

References (33)

View in search results format >

 All
 Export
 Print
 E-mail
 Save to PDF
 Create bibliography

- 1 Buehler, W.J., Wiley, R.C.
 (1961) *The Properties of TiNi and Associated Phases, U.S. Naval Ordnance Laboratory NOLTR 61-75*
- 2 Frotscher, M., Nörtershäuser, P., Somsen, Ch., Neuking, K., Böckmann, R., Eggeler, G.
Microstructure and structural fatigue of ultra-fine grained NiTi-stents
 (2009) *Materials Science and Engineering A*, 503 (1-2), pp. 96-98. Cited 24 times.
 doi: 10.1016/j.msea.2008.02.059
[View at Publisher](#)
- 3 Petrini, L., Migliavacca, F.
 Biomedical applications of shape memory alloys
 (2011) *Journal of Metallurgy*, 501 (483), pp. 1-15. Cited 268 times.
- 4 Tobushi, H., Date, K., Miyamoto, K.
 Characteristics and development of shape-memory alloy heat engine
 (2010) *Journal of Solid Mechanics and Materials Engineering*, 4 (7), pp. 1094-1102. Cited 23 times.

- 5 Banks, R.
The Banks Engine
(1975) *Die Naturwissenschaften*, 62 (7), pp. 305-308. Cited 4 times.
doi: 10.1007/BF00608890
[View at Publisher](#)
-
- 6 Kim, H.-I., Han, M.-W., Song, S.-H., Ahn, S.-H.
Soft morphing hand driven by SMA tendon wire
(2016) *Composites Part B: Engineering*, 105, pp. 138-148. Cited 53 times.
doi: 10.1016/j.compositesb.2016.09.004
[View at Publisher](#)
-
- 7 Thill, C., Etches, J., Bond, I., Potter, K., Weaver, P.
Morphing skins
(2008) *Aeronautical Journal*, 112 (1129), pp. 117-139. Cited 434 times.
<http://journals.cambridge.org.ezlib.iium.edu.my/AER>
doi: 10.1017/S0001924000002062
[View at Publisher](#)
-
- 8 Barbarino, S., Bilgen, O., Ajaj, R.M., Friswell, M.I., Inman, D.J.
A review of morphing aircraft ([Open Access](#))
(2011) *Journal of Intelligent Material Systems and Structures*, 22 (9), pp. 823-877. Cited 817 times.
doi: 10.1177/1045389X11414084
[View at Publisher](#)
-
- 9 Iannucci, L., Evans, M., Irvine, R., Patoor, E., Osmont, D.
(2009) *Morphing Wing Design, MCM-ITP Conference*
Lille-Grand Palais
-
- 10 Jardine, A.Peter, Bartley-Cho, Jonathan, Flanagan, John
Improved design and performance of the SMA torque tube for the DARPA Smart Wing program
(1999) *Proceedings of SPIE - The International Society for Optical Engineering*, 3674, pp. 260-269. Cited 33 times.
[View at Publisher](#)
-
- 11 Dong, Y., Boming, Z., Jun, L.
A changeable aerofoil actuated by shape memory alloy springs
(2008) *Materials Science and Engineering A*, 485 (1-2), pp. 243-250. Cited 56 times.
doi: 10.1016/j.msea.2007.08.061
[View at Publisher](#)
-
- 12 Iannucci, L.
Fontanazza Design of morphing wing structures
(2008) *3rd SEAS DTC (System Engineering and Autonomous Systems Defence Technology Centre) Technical Conference*
-
- 13 Kang, W.-R., Kim, E.-H., Jeong, M.-S., Lee, I., Ahn, S.-M.
Morphing wing mechanism using an SMA wire actuator ([Open Access](#))
(2012) *International Journal of Aeronautical and Space Sciences*, 13 (1), pp. 58-63. Cited 38 times.
http://ijass.org/On_line/admin/files/6%29%28058-063%2912-010.pdf
doi: 10.5139/IJASS.2012.13.1.58
[View at Publisher](#)

- 14 Rim, M., Kim, E.-H., Kang, W.-R., Lee, I.
Development of a shape memory alloy wire actuator to operate a morphing wing
(2014) *Journal of Theoretical and Applied Mechanics (Poland)*, 52 (2), pp. 519-531. Cited 8 times.
<http://www.ptmts.org.pl/jtam/index.php/jtam/article/view/v52n2p519/1844>
-
- 15 de Almeida, T.C., Santos, O.S., Otubo, J.
Construction of a morphing rib actuated by a NiTi wire (Open Access)
(2015) *Journal of Aerospace Technology and Management*, 7 (4), pp. 454-464. Cited 10 times.
<http://www.jatm.com.br/ojs/index.php/jatm/article/download/532/457>
doi: 10.5028/jatm.v7i4.532
View at Publisher
-
- 16 Iannucci, L.
(2012) *Aerofoil Member*
US-Patent No. 8,186,631
-
- 17 Ruangjirakit, K.
(2013) *Polyurethane Corrugated Composites for Morphing Wing Applications*
PhD Thesis, Imperial College London, UK
-
- 18 Thill, C., Etches, J.A., Bond, I.P., Potter, K.D., Weaver, P.M.
Composite corrugated structures for morphing wing skin applications
(2010) *Smart Materials and Structures*, 19 (12), art. no. 124009. Cited 128 times.
http://iopscience.iop.org/0964-1726/19/12/124009/pdf/0964-1726_19_12_124009.pdf
doi: 10.1088/0964-1726/19/12/124009
View at Publisher
-
- 19 Terwagne, D., Brojan, M., Reis, P.M.
Smart morphable surfaces for aerodynamic drag control
(2014) *Advanced Materials*, 26 (38), pp. 6608-6611. Cited 71 times.
<http://www3.interscience.wiley.com.ezlib.iium.edu.my/journal/119030556/issue>
doi: 10.1002/adma.201401403
View at Publisher
-
- 20 Kudva, J.N.
Overview of the DARPA smart wing project
(2004) *Journal of Intelligent Material Systems and Structures*, 15 (4), pp. 261-267. Cited 271 times.
doi: 10.1177/1045389X04042796
View at Publisher
-
- 21 Gao, X., Qiao, R., Brinson, L.C.
Phase diagram kinetics for shape memory alloys: A robust finite element implementation
(2007) *Smart Materials and Structures*, 16 (6), pp. 2102-2115. Cited 42 times.
doi: 10.1088/0964-1726/16/6/013
View at Publisher
-
- 22 Birman, V.
Stability of functionally graded shape memory alloy sandwich panels (Open Access)
(1997) *Smart Materials and Structures*, 6 (3), pp. 278-286. Cited 61 times.
doi: 10.1088/0964-1726/6/3/006
View at Publisher

- 23 Cross, W.B., Kariotis, A.H., Stimler, F.J.
(1970) *Nitinol Characterization Study*. Cited 107 times.
NASA CR 1433
-
- 24 Alipour, A., Kadkhodaei, M., Ghaei, A.
Finite element simulation of shape memory alloy wires using a user material subroutine: Parametric study on heating rate, conductivity, and heat convection

(2015) *Journal of Intelligent Material Systems and Structures*, 26 (5), pp. 554-572. Cited 6 times.
<http://jim.sagepub.com/>
doi: 10.1177/1045389X14533431

View at Publisher
-
- 25 Solomou, A.G., MacHairas, T.T., Saravanos, D.A.
A coupled thermomechanical beam finite element for the simulation of shape memory alloy actuators

(2014) *Journal of Intelligent Material Systems and Structures*, 25 (7), pp. 890-907. Cited 13 times.
doi: 10.1177/1045389X14526462

View at Publisher
-
- 26 Tabesh, M., Lester, B., Hartl, D., Lagoudas, D.
Influence of the latent heat of transformation and thermomechanical coupling on the performance of shape memory alloy actuators

(2012) *ASME 2012 Conference on Smart Materials, Adaptive Structures and Intelligent Systems, SMASIS 2012*, 2, pp. 237-248. Cited 6 times.
ISBN: 978-079184510-3
doi: 10.1115/SMASIS2012-8188

View at Publisher
-
- 27 Okabe, Y., Sugiyama, H., Inayoshi, T.
Lightweight actuator structure with SMA honeycomb core and CFRP skins

(2011) *Journal of Mechanical Design, Transactions of the ASME*, 133 (1), art. no. 011006. Cited 5 times.
doi: 10.1115/1.4003139

View at Publisher
-
- 28 Turner, T.L., Cabell, R.H., Cano, R.J., Silcox, R.J.
Development of a preliminary model-scale adaptive jet engine chevron

(2008) *AIAA Journal*, 46 (10), pp. 2545-2557. Cited 7 times.
<http://pdf.aiaa.org/getfile.cfm?urlX=%2D%3CWI%277D%2FQKS%2B%28S%20%23JU%20%20%20%0A&urla=%26%2A%221%20%23%20%2AC%0A&urlb=%21%2A%20%20%20%0A&urlc=%21%2A0%20%20%0A&urld=%21%2A0%20%20%0A&urle=%27%2B%22T%23%22DU%20%20%20%0A>
doi: 10.2514/1.35939

View at Publisher
-
- 29 Barbarino, S., Pecora, R., Lecce, L., Concilio, A., Ameduri, S., Calvi, E.
A novel SMA-based concept for airfoil structural morphing

(2009) *Journal of Materials Engineering and Performance*, 18 (5-6), pp. 696-705. Cited 61 times.
doi: 10.1007/s11665-009-9356-3

View at Publisher

30 Sellitto, A., Riccio, A.
Overview and future advanced engineering applications for morphing surfaces by Shape Memory Alloy Materials ([Open Access](#))
(2019) *Materials*, 12 (5), art. no. 708. Cited 18 times.
<https://www.mdpi.com/1996-1944/12/5/708/pdf>
doi: 10.3390/ma12050708
[View at Publisher](#)

31 Tanaka, K., Hayashi, T., Itoh, Y., Tobushi, H.
Analysis of thermomechanical behavior of shape memory alloys
(1992) *Mechanics of Materials*, 13 (3), pp. 207-215. Cited 58 times.
doi: 10.1016/0167-6636(92)90003-V
[View at Publisher](#)

32 (2015) *Livermore Software Technology Corporation (Lstc), Ls-Dyna*. Cited 134 times.
Keyword User's Manual, Volume II Material Models, Version R8.0

33 Epps, J.J., Chopra, I.
In-flight tracking of helicopter rotor blades using shape memory alloy actuators
(2001) *Smart Materials and Structures*, 10 (1), pp. 104-111. Cited 90 times.
doi: 10.1088/0964-1726/10/1/310
[View at Publisher](#)

© Copyright 2021 Elsevier B.V., All rights reserved.

[Back to results](#) | 1 of 1

[Top of page](#)

About Scopus

[What is Scopus](#)
[Content coverage](#)
[Scopus blog](#)
[Scopus API](#)
[Privacy matters](#)

Language

[日本語に切り替える](#)
[切换到简体中文](#)
[切换到繁體中文](#)
[Русский язык](#)

Customer Service

[Help](#)
[Contact us](#)

ELSEVIER

[Terms and conditions](#) [Privacy policy](#)

Copyright © Elsevier B.V. All rights reserved. Scopus® is a registered trademark of Elsevier B.V.

We use cookies to help provide and enhance our service and tailor content. By continuing, you agree to the use of cookies.

RELX