alloy was anodized in a sulfuric acid bath it produced a very light beige color that was exactly what the architect, Minoro Yamasaki, wanted. He thought that the buildings would stand for 500 years! The special alloy, CJ43, was a thin layer on one side only of the old (pots and pans) alloy 3003. The clad sheet product (CJ43 on 3003) was designated as CJ44. The one-side clad sheet panels (12 ft. long) were formed into "column covers" that formed the exterior of the building and covered the steel columns. They extended essentially the full height of the buildings.

I was told that some time during construction of the buildings the company that formed and finished the panels by mistake formed some of them "wrong side out" so that the color and brightness did not match that of the properly formed pieces. It was decided that if these pieces were installed on the far upper stories the mismatch could not be detected by observers on the ground level, and in addition, it was made certain that the placement was to avoid the mismatch pieces being seen from the opposite tower.

Of course, these were only material things. The anguish of the victims' survivors, the suffering of the victims themselves, the effects on business and society far outweigh the mere destruction and loss of property. But for those of us that spent quite a few years of our lives working out the ways of providing materials that better answer the needs of buildings, vehicles (both flying and rail- or road-bound), cans, electrical equipment, and many more things, a catastrophe such as this has indeed a deep-seated meaning.

It was shattering to view (live) the demise of the twin towers since this special building material was developed in the division of Alcoa Labs which I managed. I later learned that the planes were Boeing 767s, which were the first to use the new structural alloy 7050, of which I am a co-patentee. Both alloy developments (for buildings and planes)



were done while I was chairman of Alcoa's Alloy Development Technical Committee.

> Harold Y. Hunsicker TMS Member since 1939

THE TRUTH ABOUT TRANSATLANTIC FLIGHT

Folks,

Your statement (p. 27 of the November



issue) ["Space-ShipOne, the Ansari X Prize, and the Materials of the Civilian Space Race,"November 2004, pp. 24–28] that the Orteig Prize, won by

Lindberg, was for the "first nonstop transatlantic flight" is inaccurate. Such a flight occurred eight years earlier. The following information was found at *http://msnbc.msn.com/id/5191763*.

1913: Daily Mail Trans-Atlantic Prize: Britain's Daily Mail offers 10,000 pounds for the first nonstop trans-Atlantic airplane crossing. The prize is won in 1919 by British Capt. John Alcock and Lt. Arthur Whitten Brown flying a Vickers Vimy airplane for 16 hours from Newfoundland to Ireland.

1919: Orteig Prize: New York hotel owner Raymond Orteig offers \$25,000 to the first aviator to cross the Atlantic from New York to Paris (or the shores of France), or vice versa, without a stop. The prize is won in 1927 by Missouri airmail pilot Charles Lindbergh, who completes the flight in a Ryan monoplane in 33 hours and 30 minutes.

J.W. Evans

Plato Malozemoff Chair in Mineral Engineering and Professor of Metallurgy University of California–Berkeley

- View hypertext-enhanced articles from JOM
- See the unabridged version of the TMS Meetings Calendar
- Read Material Matters articles dating from 1990 to today
- Review classified ads that have appeared in the past three issues

CORRECTIONS

In "High-Strength Metastable Beta-Titanium Alloys for Biomedical Applications" by J.I. Qazi, B. Marquardt, and H.J. Rack (JOM, 56 (11) (2004), pp. 49–51), the contents of Tables I and II were switched during editing. The corrected tables are as follows:

Table I. Tensile Properties of Ti-35Nb-7Zr-5Ta-0.06O							
Heat Treatment	YS (MPa)	UTS (MPa)	El. (%)	RA (%)			
Solution treated	530	590	21	69			
427°C/ 8 h	630	686	17	42			
482°C/ 8 h	503	534	20	46			
538°C/ 8 h	493	537	21	52			
593°C/ 8 h	508	549	26	63			
260°C/ 4 h/ 427°C/8 h	693	753	15	35			

Table II. Tensile Properties of Ti-35Nb-7Zr-5Ta-0.46O							
Heat Treatment	YS (MPa)	UTS (MPa)	El. (%)	RA (%)			
Solution treated 427°C/ 8 h 482°C/ 8 h 538°C/ 8 h 593°C/ 8 h 260°C/ 4 h/ 427°C/8 h	937 1,007 1,060 806 765 1,202	1,014 1,055 1,149 929 861 1,244	19 12 9 11 15 8	55 27 17 22 22 16			

Also, in "The Near-Net-Shape Manufacturing of Affordable Titanium Componentsforthe M777Lightweight Howitzer" by Kevin L. Klug, Ibrahim Ucok, Mehmet N. Gungor, Mustafa Guclu, Lawrence S. Kramer, Wm. Troy Tack. Larentiu Nastac, Nicholas R. Martin, Hao Dong, and Joseph R. Pickens (JOM, 56 (11) (2004), pp. 35–41) the name of Joseph R. Pickens was omitted from the list of authors in the byline. Also, the captions for Figure 5g and Figure 5h should have identified those images as flowformed tubes.

- Browse the *JOM* book reviews and consider becoming a reviewer
- Acquire articles from past issues of JOM, dating from 1997 to today, available for download in Portable Document Format (TMS members receive this benefit at no cost)
- Access the subject indexes on-line (1990-present)