 Open access • Journal Article • DOI:10.1061/(ASCE)HY.1943-7900.0000919

Hydraulics, Air Entrainment, and Energy Dissipation on a Gabion Stepped Weir

— [Source link](#) 

[Davide Wüthrich](#), [Hubert Chanson](#)

Institutions: [École Polytechnique Fédérale de Lausanne](#), [University of Queensland](#)

Published on: 17 Jun 2014 - [Journal of Hydraulic Engineering](#) (American Society of Civil Engineers)

Topics: [Gabion](#)

Related papers:

- [Hydraulics, air entrainment and energy dissipation on a](#)
- [Flow and Energy Dissipation Over Stepped Gabion Weirs](#)
- [Skimming Flow in Stepped Spillways](#)
- [Air–water flows down stepped chutes: turbulence and flow structure observations](#)
- [Hydraulics of Stepped Chutes and Spillways](#)

Share this paper:    

View more about this paper here: <https://typeset.io/papers/hydraulics-air-entrainment-and-energy-dissipation-on-a-35r2xm8py0>

HYDRAULICS, AIR ENTRAINMENT AND ENERGY DISSIPATION ON A GABION STEPPED WEIR

Davide Wüthrich ⁽¹⁾ and Hubert Chanson ⁽²⁾ (*)

⁽¹⁾ Research student, The University of Queensland, School of Civil Engineering, Brisbane QLD 4072, Australia (Present address: EPF ENAC IIC LCH, Lausanne, Switzerland)

⁽²⁾ Professor in Hydraulic Engineering, The University of Queensland, School of Civil Engineering, Brisbane QLD 4072, Australia, Ph.: (61 7) 3365 4163, Fax: (61 7) 3365 4599, E-mail: h.chanson@uq.edu.au

(*) Corresponding author

Abstract: In the last decades the design of stepped spillways regained some interest because of their suitability with new construction methods including gabions. The hydraulic performances of gabion stepped weirs were investigated experimentally in terms of the flow patterns, air-water flow properties and energy dissipation. A laboratory study was conducted in a 26.6° slope (1V:2H) and 0.10 m step height facility with both smooth impervious and gabion steps. The visual observations highlighted the seepage flow through the gabions, inducing a modification of the cavity flow, especially in the skimming flow regime. In skimming flows, higher velocities were measured at the downstream end of the gabion stepped chute, associated with smaller energy dissipation rates and lower friction factors, compared to the smooth impervious stepped chute data.

Keywords: Gabion weirs, Stepped spillways, Energy dissipation, Air entrainment, Physical modelling.

INTRODUCTION

Stepped spillways and weirs have been used for more than 3,500 years (Chanson 2001). The stepped chute design enhances the rate of energy dissipation on the spillway chute, thus reducing the size and cost of the downstream stilling structure. During the last three decades, research into the hydraulics of stepped spillways has been active with a focus on steep stepped spillways for concrete gravity dams (Chanson 1995,2000, Ohtsu and Yasuda 1998, Minor and Hager 2000). For a given concrete stepped chute, the spill flows as a nappe flow regime for small discharges. For a range of intermediate discharges, a transition flow regime may be observed. Most prototype spillways operate in the skimming flow regime for large flow rates per unit width. In skimming flows, the waters skim as a coherent stream over the pseudo-bottom formed by step edges and large form losses take place (Rajaratnam 1990).

Stepped spillway flows are characterised by strong flow aeration, very intense turbulence, and interactions between entrained air and turbulence (Chanson and Toombes 2002, Ohtsu et al. 2004). A few studies investigated the impact of macro-roughness and turbulence manipulation on skimming flow properties (Andre et al. 2004, Guenther et al. 2013). The effects of step roughness on the flow properties were specifically studied independently by Gonzalez et al. (2008) and Bung and Schlenkhoff (2010) with similar counter-intuitive results: i.e., both data sets showed faster flow motion and lesser energy dissipation on rough stepped chutes. Peyras et al. (1992) studied the flow patterns and energy dissipation of gabion stepped weirs, while Kells (1993,1995) discussed the interactions between seepage and free-surface flows on gabion weirs. Figure 1 shows two photographs of a gabion stepped weir. A wider literature encompasses the research on riprap overtopping, covering both loose and anchored materials (Judd and Peterson 1969, Knauss 1979, Gerodetti 1981).

It is the purpose of this contribution to study thoroughly the hydraulics of gabion stepped weirs, including their air-water flow properties and rate of energy dissipation. A key feature was the systematic comparison between gabion and smooth impervious stepped spillways for a range of flow rates. New measurements were conducted in laboratory with a focus on the transition and skimming flow regimes. The results provided a new understanding of the combined effects of seepage and step surface roughness on the overflow characteristics.

EXPERIMENTAL FACILITY AND INSTRUMENTATION

New experiments were conducted in a relatively large size stepped spillway model at the University of Queensland previously used by Guenther et al. (2013). The test section consisted of a broad-crested weir followed by ten steps with step height $h = 0.1$ m and step length $l = 0.2$ m. The stepped chute was 0.52 m wide. The water flow was supplied by a large upstream intake basin followed by a smooth sidewall

WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

convergent with a 4.23:1 contraction ratio. At the upstream end of the chute, the flow was controlled by a broad-crested weir equipped with an upstream rounded corner. A pump controlled with an adjustable frequency AC motor drive delivered the flow rate, allowing an accurate discharge adjustment. The water discharge was deduced from the measured upstream head above crest using the discharge calibration results of Felder and Chanson (2012). At the downstream end, the stepped chute was followed by a smooth horizontal channel ending with an overfall. The flow was supercritical in this horizontal tailwater raceway for all investigated flow conditions (Table 1).

Two stepped configurations were tested (Fig. 2). The smooth impervious stepped configuration consisted of flat horizontal steps made of marine ply (Fig. 2A). For the gabion chute, ten identical gabions were installed above the smooth impervious steps. Each gabion was 0.3 m long, 0.1 m high and 0.52 m wide, made of fine $12.7 \times 12.7 \text{ mm}^2$ galvanised metallic mesh and filled with natural river pebbles (Fig. 2B). The gravels (Cowra pearl) were sieved with 14 mm square sieve. Note that the ratio of stone size to mesh size was typical of construction practices for more economical cage filling and better adaptability of gabions to deformation (Agostini et al. 1987, Chanson 2001). The density of dry gravels was 1.6 tonnes/m^3 corresponding to a porosity of 0.35-0.4. The hydraulic conductivity of the gabions was estimated to be $K \approx 10^{-1} \text{ m/s}$ (Wüthrich and Chanson 2014).

INSTRUMENTATION

The air-water flow measurements were conducted with a dual-tip phase detection intrusive probe (inner tip $\varnothing = 0.25 \text{ mm}$). The probe was mounted on a trolley and the elevation in the direction perpendicular to the pseudo bottom formed by the step edges was controlled by a fine adjustment screw-drive mechanism equipped with a MitutoyoTM digital ruler (accuracy: 0.05 mm). The probe was excited by an electronic air bubble detector with a response frequency greater than 100 kHz. The probe signal output was sampled at 20 kHz per sensor for 45 s. The main parameters derived from the signal processing were the time-averaged void fraction C , bubble frequency F , interfacial velocity V and turbulence intensity $Tu = v'/V$. Further details on the signal post-processing were discussed in Chanson (2002,2013). All stepped weir performances, including energy dissipation rate and flow resistance, were calculated based upon the air-water flow measurements.

FLOW CONDITIONS

The experimental study was conducted systematically on the two stepped spillway configurations (Fig. 2). Flow visualisations were carried out for a wide range of discharges within $0.005 \leq Q \leq 0.114 \text{ m}^3/\text{s}$. The air-water flow properties were recorded in the transition and skimming flow regimes, for a range of dimensionless discharges between $0.02 \leq Q \leq 0.11 \text{ m}^3/\text{s}$ corresponding to dimensionless discharges $0.5 \leq d_c/h \leq 1.7$ and Reynolds numbers between 1.4×10^5 and 8.8×10^5 , where d_c is the critical flow depth: $d_c = (q^2/g)^{1/3}$, q is the overflow discharge per unit width measured at the weir crest, and Re is the Reynolds number defined in terms of the hydraulic diameter. The experimental flow conditions are summarised and compared with previous relevant studies in Table 1.

FLOW REGIMES

Visual observations indicated the three 'classical' flow regimes typically observed on stepped spillways for both configurations: nappe, transition and skimming flows with increasing flow rates. In addition a porous flow regime was observed on the gabion stepped weir for very low discharges. On the smooth impervious stepped spillway, a nappe flow regime was observed for $d_c/h < 0.5$. The flow consisted of a succession of free falling nappes from a step to the following one (Chamani and Rajaratnam 1994, Toombes and Chanson 2008). Below each falling nappe, a recirculating pool of water was formed with a distinctive air cavity above. For a range of intermediate discharges ($0.5 < d_c/h < 0.9$), strong hydrodynamic instabilities associated with a large amount of spray and splashes were observed. The step cavities were almost completely full, with a small air pocket under the step edge, while for larger discharges the cavities became filled with water (Chanson and Toombes 2004). For $d_c/h > 0.9$, the flow skimmed as a coherent stream above the pseudo-bottom formed by the step edges (Fig. 2A). Substantial air entrainment occurred downstream of the inception point of free surface aeration, and an energetic recirculation pattern was observed in the step cavities. Overall the flow pattern observations and flow conditions for the changes between flow regimes were in agreement with the literature (Chanson 2001, Boes and Hager 2003, Felder and Chanson 2009).

On the gabion stepped weir, a porous seepage flow regime was observed for $d_c/h < 0.3$. All the water seeped

through the gabion materials. On the first gabion box, some infiltration was observed as shown in Figure 3A. A short horizontal seepage face was observed on each step and there was no overflow past the step edges. In the porous material, the free-surface (i.e. water table) could be observed through the transparent sidewalls. For the smallest discharges, no vertical seepage was observed through the step vertical face. With increasing discharge, small water jets came out of the downstream face of the gabions. The transition between porous and nappe flow regime occurred once some overflow took place at the first gabion. For $0.3 < d_c/h < 0.6$, the nappe flow appeared as a succession of free falling nappes from one step edge to the next one. The cavity beneath the nappe was filled with a superposition of seepage jets coming out of the upstream gabion (Fig. 3B). In the lower part of the cavity an oscillating recirculation pool was observed. A transition flow regime was observed for $0.6 < d_c/h < 0.9$ (Fig. 2B). The flow instabilities and splashes appeared less intense than those observed on smooth impervious stepped spillway. For the largest discharges, a skimming flow was observed ($d_c/h > 0.9$). The flow pattern was generally similar to that observed on the smooth stepped configuration. However a different streamline pattern was seen next to the stagnation point on the horizontal step face (Fig. 3C). Some bubbly flow and air bubble entrainment into the gabions were observed, mostly in the upper corner of each gabion box downstream of the inception point of free-surface aeration. Visual observations were carried out in the cavity, including with dye injections and wool strings. A vertical flux of air bubbles was observed close to the vertical step face (Fig. 3C). Around the centre of the cavity, a clear water core was seen downstream of the inception point for all skimming flow discharges in all cavities. The existence of a similar clear water core was previously reported by Gonzalez et al. (2008) for rough impervious steps. Visually the recirculation motion appeared to be modified by the existence of the clear-water core and the interactions with the seepage flow, with the bubbly motion mostly reduced to the downstream end of the cavity as sketched in Figure. 3C.

At the chute upstream end, the water was clear. Further downstream, the inception point of free surface aeration was well defined as the location where the turbulence overcame surface tension and air was entrained within the flow. For a given discharge, the position of the inception point was observed to be nearly identical for both stepped configurations. A few air bubbles were seen intermittently up to one to two step cavities upstream of the inception point of free-surface aeration. But their numbers were small and their appearance was irregular. The locations of cavity aeration inception and gabion aeration inception were recorded for the gabion weir. Herein cavity aeration is defined as the aeration of the (water) cavities beneath the pseudo-bottom formed by the step edges, while gabion aeration means the air entrainment into the gabion material and is related to the air-water seepage motion. The data indicated that the inception of step cavity aeration and gabion aeration took place about one step cavity downstream of the inception point of free-surface aeration.

For comparison, Peyras et al. (1992) reported two types of flow on gabion stepped weirs: nappe and skimming flows, without a mention on seepage and transitions flow regimes. Their observations indicated nappe flows for $d_c/h < 0.6$ to 0.7 depending upon the chute slope, with skimming flows for larger flow rates (Peyras et al. 1991).

AIR-WATER FLOW PROPERTIES

Basic observations

The air concentration distributions for both smooth impervious and gabion stepped weirs exhibited shapes which were comparable to previous observations on stepped spillways (Chamani and Rajaratnam 1999, Boes and Hager 2003, Felder and Chanson 2009). Typical profiles are presented in Figure 4, in which y is the distance normal to the pseudo-bottom formed by the step edges, and Y_{90} is the characteristic air-water flow depth where the air concentration C equals 0.90. All the data showed substantial flow aeration. In the transition flow regime, the air concentration distributions were compared to a theoretical model (Chanson and Toombes 2002):

$$C = K'' \times \left[1 - \exp\left(-\lambda \times \frac{y}{Y_{90}}\right) \right] \quad (1)$$

where K'' and λ are dimensionless functions of the mean air concentration C_{mean} :

$$K'' = \frac{0.9}{1 - \exp(-\lambda)} \quad (2)$$

WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

$$\lambda = \frac{0.9}{K'' - C_{\text{mean}}} \quad (3)$$

Equation (1) is compared with experimental data in Figure 4A. The transition flows over gabion steps were observed to be slightly less aerated than the transition flow on the smooth impervious stepped configuration (e.g. Fig. 4A, steps 8 & 10). But the air concentration at $y = 0$ (i.e. at the gabion edge) was non-zero because of the bubbly flow inside the gabions. In the skimming flows, the air concentration data exhibited an inverted S-profile (Fig. 4B). The air concentration distributions were successfully compared with the advective diffusion equation developed by Chanson and Toombes (2002):

$$C = 1 - \tanh^2 \left[K' - \frac{y}{2 \times D_0} + \frac{\left(\frac{y}{Y_{90}} - \frac{1}{3} \right)^3}{3 \times D_0} \right] \quad (4)$$

where K' is an integration constant and D_0 is a function of the depth-averaged void fraction C_{mean}

$$K' = 0.0327 + \frac{1}{2 \times D_0} - \frac{8}{81 \times D_0} \quad (5)$$

$$D_0 = -\frac{1}{3.614} \times \text{Ln} \left(1.0434 - \frac{C_{\text{mean}}}{0.7622} \right) \quad (6)$$

The results showed a good self-similarity of the void fraction profiles (Fig. 4B) and little difference between the two stepped configurations. Equation (4) is compared with data in Figure 4B.

The bubble frequency distributions on both smooth impervious and gabion stepped spillways showed a marked maximum (Fig. 5) corresponding to a local void fraction between 0.4 and 0.5. The results were consistent with previous studies on stepped spillways with smooth impervious steps (Toombes 2002, Gonzalez 2005). In Figure 5, typical results are presented in terms of the dimensionless bubble frequency $F \times d_c / V_c$ where F is defined as the number of bubbles detected per unit time, and V_c is the critical flow velocity: $V_c = \sqrt{g \times d_c}$. For all discharges, the bubble frequency was consistently smaller on the gabion stepped weir compared to the smooth impervious stepped chute. In the skimming flows, some difference was noted between smooth and gabion stepped chutes in the lower part of the flow: namely, significantly less bubble counts were recorded in the gabion stepped configuration (Fig. 5B). This finding is still not fully understood although it is conceivable that the discharge seeping through the gabions altered the vortex shedding downstream of the step edges, leading to lesser turbulent stress levels.

The velocity distributions showed self-similar profiles. In skimming flows, the smooth impervious and gabion chute data compared favourably with a power law for $y < Y_{90}$ and an uniform profile above:

$$\frac{V}{V_{90}} = \left(\frac{y}{Y_{90}} \right)^{\frac{1}{N}} \quad 0 \leq \frac{y}{Y_{90}} \leq 1 \quad (7A)$$

$$\frac{V}{V_{90}} = 1 \quad \frac{y}{Y_{90}} \geq 1 \quad (7B)$$

where V_{90} is the interfacial velocity at $y = Y_{90}$ (i.e. $C = 0.9$). Typical velocity distributions are presented in Figure 6 and the data are compared with Equations (7A) and (7B) for $N = 8$. The same self-similar shape was observed on both configurations. But the gabion stepped chute flow exhibited faster velocities than the smooth impervious stepped chute flow, for the same discharge at the same location downstream of the inception point of free-surface aeration (Figure 6 and caption). Given the increased roughness of the gabion steps, the finding was counter-intuitive, although a similar trend was previously observed on rough impervious steps by Gonzalez et al. (2008) and Bung and Schlenkhoff (2010). It is plausible that, in skimming flows, the recirculation flow was altered by a combined effect of gabion seepage outflow into step cavities and step surface roughness. The former effect was documented in monophasic flow, sometimes termed (monophasic flow) ventilation (Wood 1964, Naudascher and Rockwell 1994), while the latter was linked to turbulence manipulation, for example observed with riblets and d-type roughness in developing boundary layer (Djenidi and Antonia 1995, Djenidi et al. 1999).

For both smooth impervious and gabion stepped configurations, the turbulence intensity distributions

WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

presented a local maximum at the elevation where the bubble count rate was maximum. Typical results are presented in Figure 7 in transition and skimming flows. Overall the level of turbulence was higher on the smooth impervious stepped chute for transition and skimming flows. The results suggested that the interactions between seepage and overflow contributed to some dampening of the free-surface flow turbulence.

Longitudinal air-water flow properties

The longitudinal distributions of selected characteristic air-water properties are presented in Figure 8, namely the characteristic flow depth Y_{90} , the depth averaged void fraction C_{mean} , and the characteristic air-water flow velocity V_{90} . The results are plotted in dimensionless form in terms of the step edge. The step edge 1 was the first step edge at the downstream end of the broad crest and the measurement location 11 was set in the horizontal tailrace channel at 0.2 m downstream of step edge 10. For all flow conditions, the results showed that the air-water flow height was lower on the gabion stepped weir and this was consistent with photographic observations. The depth-averaged void fraction data C_{mean} highlighted a lesser aeration of the flow on the gabion stepped configuration. At step edge 10, C_{mean} was between 1.0 and 1.4 times larger on the smooth impervious stepped chute than on the gabion stepped chute, and the difference increased monotonically with an increasing discharge (Fig. 8). The characteristic air-water velocity V_{90}/V_c data showed that, in the skimming flow regime, V_{90} was larger on the gabion weir. Although counter-intuitive, these results were similar to the findings on rough impervious steps (see above).

The porosity of gabion steps induced some seepage through the gabions, thus reducing the overflow discharge above the steps. The overflow discharge per unit width above the gabions q_w was estimated based upon the equation of conservation of mass using the measured air-water flow properties:

$$q_w = \int_0^{Y_{90}} (1 - C) \times V \times dy \quad (8)$$

The data showed that the proportion of seepage flow $(1 - q_w/q)$ was a function of the flow regime and flow rate. In nappe flow conditions, the seepage flow ratio was about 0.5 on average. In skimming flows, $(1 - q_w/q)$ was down to 0.05 to 0.15.

ENERGY DISSIPATION PERFORMANCES

The rate of energy dissipation and flow resistance above the stepped weir were calculated based upon the air-water flow measurements. For the smooth impervious stepped weir, all calculations were based upon the total discharge q measured at the weir crest. For the gabion stepped chute, the flow resistance calculations were performed using the overflow discharge q_w (Eq. (8)).

For design purposes, a key parameter is the residual head estimated as:

$$H_{res} = \int_0^{Y_{90}} (1 - C) \times dy \times \cos \theta + \frac{q^2}{2 \times g \times \left(\int_0^{Y_{90}} (1 - C) \times dy \right)^2} \quad (9)$$

The results are summarised in Figure 9, regrouping the data measured at the last step edge (step 10) and in the bottom tailrace channel 0.20 m downstream of step edge 10. The experimental results showed that the gabion stepped weir was the least efficient in terms of energy dissipation, except for the smallest discharge. The largest residual head was observed with the gabion stepped chute in skimming flows (Fig. 9). For the smallest flow rate, on the other hand, the gabion stepped chute flow presented the smallest residual head. Between the step edge 10 and the tailrace channel, some differences in terms of energy dissipation were seen for the gabion stepped chute which reflected likely the large energy dissipation rate of the seepage flow component (Stephenson 1979).

The flow resistance was evaluated in terms of the Darcy-Weisbach friction factor (Rajaratnam 1990, Chanson 2001). The friction factor was calculated based upon the air-water flow properties and total head line slope measurements:

$$f_e = \frac{8 \times g \times S_f \times \left(\int_0^{Y_{90}} (1 - C) \times dy \right)}{\left(q / \int_0^{Y_{90}} (1 - C) \times dy \right)^2} \quad (10)$$

where S_f is the total head line slope: $S_f = -\partial H / \partial x$, where H is the total head and x is the distance in flow direction. The present data are shown in Figure 10 as a function of the dimensionless step roughness height $h \times \cos\theta / D_H$ where D_H is the hydraulic diameter. The results indicated consistently that the smallest flow resistance was experienced on the gabion stepped chute (Fig. 10). On the smooth impervious stepped weir, the flow resistance was on average two times larger than that on the gabion stepped chute for the investigated flow conditions, and the results were within commonly accepted values for stepped spillways (Chanson 2006). In the skimming flow regime, the average Darcy-Weisbach friction factor was 0.23 for the smooth impervious steps and 0.11 for the gabion steps.

Although the gabion step faces were much rougher, the present results showed that, in skimming flows, the gabion stepped design was the least efficient in terms of energy dissipation performances and flow resistance. The finding was unexpected, but in qualitative agreement with the results of Gonzalez et al. (2008) and Bung and Schlenkhoff (2010) on rough impervious steps.

CONCLUSION

The hydraulic performances of a gabion stepped weir were investigated with a systematic comparison of the performances of gabion and smooth impervious stepped chutes with a slope of 26.6° (1V:2H) and step height of 0.1 m. For each configuration, the detailed flow properties were investigated for a wide range of discharges. The visual observations highlighted the seepage flow through the gabions. On the gabion stepped chute, a porous regime was observed for the smallest discharges: there was no overflow and the water seeped through the gabions. For larger discharges, the main overflow regimes included the nappe, transition and skimming flows with increasing discharges. The interactions between seepage flow and overflow were functions of the discharge, gabion configuration and flow regime, and they resulted in a modification of the step cavity flow and recirculation patterns. The seepage flow motion was observed to cause a modification of the cavity flow dynamics, while a substantial number of air bubbles were entrapped in the gabions.

The air-water flow measurements showed comparable trends for both stepped weirs, although with some quantitative differences. The gabion stepped chute was slightly less aerated, while the bubble count rate and turbulence intensity were lower on the gabion stepped weir. In skimming flows, larger velocities were measured at the downstream end of the gabion stepped weir. The rate of energy dissipation and residual head data showed that the rate of energy dissipation was the lowest on the gabion stepped weir. While the finding might appear counter-intuitive, it was consistent with earlier experimental results on rough impervious stepped chutes, highlighting the importance of sound physical modelling in the investigation of hydraulic structures. It is hypothesised that the cavity recirculation motion was altered by a combined effect of gabion seepage discharging into step cavities and step surface roughness, thus reducing the flow resistance and rate of energy dissipation above the gabion stepped chute. It may be added that the laboratory experiments were conducted with new gabion boxes. The weir structure was possibly more rigid than older gabion structures (Fig. 1B) and it was not affected by any form of settlement and damage.

ACKNOWLEDGEMENTS

The authors acknowledge the people who assisted with the experiments and the technical staff of the School of Civil Engineering at the University of Queensland. The financial support of the Australian Research Council (Grant DP120100481) is acknowledged.

REFERENCES

- Agostini, R., Bizzarri, A., Masetti, M., and Papetti, A. (1987). "Flexible Gabion and Reno Mattress Structures in River and Stream Training Works. Section One : Weirs." *Officine Maccaferri*, Bologna, Italy, 2nd edition.
- Andre, S., Boillat, J.L., Schleiss, A.J., and Matos, J. (2004). "Energy Dissipation and Hydrodynamic Forces of Aerated Flow over Macro-Roughness Linings for Overtopped Embankment Dams." *Proc. Intl Conf. on*

WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

Hydraulics of Dams and River Structures, Tehran, Iran, Balkema Publ., The Netherlands, pp. 189-196.

Boes, R.M., and Hager, W.H. (2003). "Two-Phase Flow Characteristics of Stepped Spillways." *Jl of Hyd. Engrg.*, ASCE, Vol. 129, No. 9, pp. 661-670.

Bung, D.B., and Schlenkhoff, A. (2010). "Self-aerated Flow on Embankment Stepped Spillways - The Effect of Additional Micro-roughness on Energy Dissipation and Oxygen Transfer." *Proc. 1st IAHR European Congress*, 4-6 May, Edinburgh, Scotland, 6 pages (CD-ROM).

Chamani, M.R., and Rajaratnam, N. (1994). "Jet Flow on Stepped Spillways." *Jl of Hyd. Engrg.*, ASCE, Vol. 120, No. 2, pp. 254-259.

Chamani, M.R., and Rajaratnam, N. (1999). "Characteristics of Skimming Flow over Stepped Spillways." *Jl of Hyd. Engrg.*, ASCE, Vol. 125, No. 4, pp. 361-368.

Chanson, H. (1995). "Hydraulic Design of Stepped Cascades, Channels, Weirs and Spillways." *Pergamon*, Oxford, UK, 292 pages.

Chanson, H. (2000). "Forum article. Hydraulics of Stepped Spillways: Current Status", *Jl of Hyd. Engrg.*, ASCE, Vol. 126, No. 9, pp. 636-637.

Chanson, H. (2001). "The Hydraulics of Stepped Chutes and Spillways." *Balkema*, Lisse, The Netherlands, 384 pages.

Chanson, H. (2002). "Air-Water Flow Measurements with Intrusive Phase-Detection Probes. Can we Improve their Interpretation?." *Jl of Hyd. Engrg.*, ASCE, Vol. 128, No. 3, pp. 252-255.

Chanson, H. (2006). "Hydraulics of Skimming Flows on Stepped Chutes: the Effects of Inflow Conditions?" *Journal of Hydraulic Research*, IAHR, Vol. 44, No. 1, pp. 51-60.

Chanson, H. (2013). "Hydraulics of Aerated Flows: Qui Pro Quo?" *Journal of Hydraulic Research*, IAHR, Invited Vision paper, Vol. 51, No. 3, pp. 223-243 (DOI: 10.1080/00221686.2013.795917).

Chanson, H. and Toombes, L. (2002). "Air-Water Flows down Stepped chutes: Turbulence and Flow Structure Observations." *International Journal of Multiphase Flow*, Vol. 28, No. 11, pp. 1737-1761.

Chanson, H. and Toombes, L. (2004). "Hydraulics of stepped chutes: The transition flow." *Journal of Hydraulic Research*, Vol. 42, No. 1, pp. 43-54.

Djenidi, L, and Antonia, R.A. (1995). "Riblet Modelling Using a Second-Moment Closure." *Applied Scientific Research*, Vol. 54, pp. 249-266.

Djenidi, L, Elavarasan, R., and Antonia, R.A. (1999). "The Turbulent Boundary Layer over Transverse Square Cavities." *Jl Fluid Mech.*, Vol. 395, pp. 271-294.

Felder, S., and Chanson, H. (2009). "Energy dissipation, flow resistance and gas-liquid interfacial area in skimming flows on moderate-slope stepped spillways." *Environmental Fluid Mechanics*, Vol. 9, No. 4, pp. 427-441.

Felder, S, and Chanson, H. (2012). "Free-surface Profiles, Velocity and Pressure Distributions on a Broad-Crested Weir: a Physical study." *Journal of Irrigation and Drainage Engineering*, ASCE, Vol. 138, No. 12, pp. 1068–1074 (DOI: 10.1061/(ASCE)IR.1943-4774.0000515).

Gerodetti, M. (1981). "Model studies of an overtopped rockfill dam." *Water Power & Dam Construction*, Vol. 34, No. 9, pp. 25-31.

Gonzalez, C. (2005). "Experimental Study of Free-surface Aeration on Embankment Stepped Chutes." *Ph.D. Thesis*, The University of Queensland, Department of Civil Engineering, Brisbane, Australia, 240 pages.

Gonzalez, C., Takahashi, M., and Chanson, H. (2008). "An experimental study of effects of step roughness in skimming flows on stepped chutes." *Journal of Hydraulic Research*, Vol. 46, No. 1, pp. 24-35.

Guenther, P., Felder, S., and Chanson, H. (2013). "Flow Aeration, Cavity Processes and Energy Dissipation on Flat and Pooled Stepped Spillways for Embankments." *Environmental Fluid Mechanics*, Vol. 13, No. 5, pp. 503-525 (DOI: 10.1007/s10652-013-9277-4).

Judd, H.E., and Peterson, D.F. (1969). "Hydraulics of Large Bed Element Channels." *UWRL Research Report*, PRWG 17-6, Utah State University, Logan, USA, 115 pages.

Kells, J.A. (1993). "Spatially varied flow over rockfill embankments." *Canadian Journal of Civil Engineering*, Vol. 20, pp. 820-827.

Kells, J.A. (1995). "Comparison of Energy Dissipation between Nappe and Skimming Flow Regimes on Stepped Chutes - Discussion." *Jl of Hyd. Res.*, IAHR, Vol. 33, No. 1, pp. 128-133.

Knauss, J. (1979). "Computation of Maximum Discharge at Overflow Rockfill Dams (a comparison of different model test results)." *Proc. 13th ICOLD Congress*, New Delhi, India, Q. 50, R. 9, pp. 143-159.

Minor, H.E., and Hager, W.H. (2000). "Hydraulics of Stepped Spillways." *Intl Workshop on Hydraulics of Stepped Spillways*, Zürich, Switzerland, Balkema Publ., Lisse, The Netherlands.

- WÜTHRICH, D., and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).
- Naudascher, E., and Rockwell, D. (1994). "Flow-Induced Vibrations. An Engineering Guide." *IAHR Hydraulic Structures Design Manual No. 7*, Hydraulic Design Considerations, Balkema Publ., Rotterdam, The Netherlands, 413 pages.
- Ohtsu, I., and Yasuda, Y. (1998). "Hydraulic Characteristics of Stepped Channel Flows." *Workshop on Flow Characteristics around Hydraulic Structures and River Environment*, University Research Center, Nihon University, Tokyo, Japan, 55 pages.
- Ohtsu, I., Yasuda, Y., and Takahashi, M. (2004). "Flow Characteristics of Skimming Flows in Stepped Channels." *Jl of Hyd. Engrg.*, ASCE, Vol. 130, No. 9, pp. 860-869. Discussion: Vol. 132, No. 5, pp. 527-542.
- Peyras, L., Royet, P., and Degoutte, G. (1991). "Ecoulement et Dissipation sur les Déversoirs en Gradins de Gabions." ('Flows and Dissipation of Energy on Gabion Weirs.') *Jl La Houille Blanche*, No. 1, pp. 37-47 (in French).
- Peyras, L., Royet, P. and Degoutte, G. (1992). "Flow and energy dissipation over stepped gabion weirs." *Journal of Hydraulic Engineering*, Vol. 118, No. 5, pp. 707-717.
- Rajaratnam, N. (1990). "Skimming Flow in Stepped Spillways." *Journal of Hydraulic Engineering*, ASCE, Vol. 116, No. 4, pp. 587-591.
- Stephenson, D. (1979). "Gabion Energy Dissipators." *Proc. 13th ICOLD Congress*, New Delhi, India, Q. 50, R. 3, pp. 33-43.
- Toombes, L. (2002). "Experimental Study of Air-Water Flow Properties on Low-Gradient Stepped Cascades." *Ph.D. Thesis*, University of Queensland, School of Civil Engineering, Brisbane, Australia, 304 pages.
- Toombes, L. and Chanson, H. (2008). "Flow Patterns in Nappe Flow Regime down Low Gradient Stepped Chutes." *Journal of Hydraulic Research*, Vol. 46, No. 1, pp. 4-14.
- Wood, C.J. (1964). "The Effect of Base Bleed on periodic Wake." *Jl Roy. Aeronautical Soc.*, Vol. 68, pp. 477-482.
- Wüthrich, D., and Chanson, H. (2014). "Aeration and Energy Dissipation over Stepped Gabion Spillways: a Physical Study." *Hydraulic Model Report No. CH92/13*, School of Civil Engineering, The University of Queensland, Brisbane, Australia, 171 pages and 5 video movies (ISBN 9781742720944).

NOTATION

- C air concentration, defined as the volume of air per unit volume;
- C_{mean} depth-averaged air concentration defined in terms of Y_{90} : $C_{\text{mean}} = 1 - d/Y_{90}$.
- D_H hydraulic diameter (m);
- D_o constant function of the mean void fraction in the advective diffusion equation (skimming flow);
- d equivalent clear water flow depth (m) defined as
- $$d = \int_{y=0}^{Y_{90}} (1 - C) \times dy$$
- d_c critical flow depth (m): $d_c = (q^2/g)^{1/3}$;
- F bubble frequency (Hz) defined as the number of detected air bubbles per unit time;
- g gravity constant (m/s^2): $g = 9.794 \text{ m/s}^2$ in Brisbane (Australia);
- H total head (m):
- $$H = z_o + \int_0^{Y_{90}} (1 - C) \times dy \times \cos \theta + \frac{q^2}{2 \times g \times \left(\int_0^{Y_{90}} (1 - C) \times dy \right)^2}$$
- H_{res} residual head of the flow (m);
- h vertical step height (m);
- K hydraulic conductivity of a porous medium (m/s);
- K' integration constant in the advective diffusion equation (skimming flow);
- K'' integration constant in the advective diffusion equation (transition flow);
- l horizontal step length (m);
- Q overflow discharge (m^3/s) measured at the weir crest;

WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

q overflow discharge per unit width (m²/s) measured at the weir crest, defined as $q = Q/W$;
 q_w water discharge per unit width (m²/s) calculated from the integration of the void ratio and velocity profiles:

$$q_w = \int_{y=0}^{Y_{90}} (1 - C) \times V \times dy$$

Re Reynolds number defined in terms of the hydraulic diameter;
 S_f friction slope defined as $S_f = -\partial H/\partial x$;
 Tu turbulence intensity: $Tu = u'/V$;
 u' root mean square of velocity fluctuations (m/s);
 V time-averaged interfacial velocity (m/s);
 V₉₀ characteristic interfacial velocity (m/s) where $C = 0.9$;
 V_c critical velocity of the flow (m/s) defined as: $V_c = (g \times d_c)^{1/2}$;
 W width of the stepped spillway (m);
 x longitudinal distance (m) measured along the pseudo-bottom formed by the step edges;
 Y₉₀ characteristic depth (m) where $C = 0.9$;
 y distance (m) measured perpendicular to the pseudo-bottom formed by the step edges;
 z_o bed elevation (m) above the tailwater channel invert;
 Δx streamwise distance between the probe tips (m);
 Δz transverse distance between the probe tips (m);
 θ chute slope: $\tan\theta = h/l$;
 λ dimensionless function of the mean air concentration (transition flow);
 Ø diameter of the probe sensor (m);

Subscript

c critical flow conditions;
 90 flow properties at the characteristic location where $C = 0.90$.

WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

Table 1 - Detailed experimental investigations on gabion and rough impervious stepped weirs

Reference (1)	θ ($^\circ$) (2)	Geometry (3)	Steps (4)	Flow conditions (5)	Instrumentation (6)
Gabion steps					
Peyras et. al (1991)	45 26.6 18.3	$h = 0.2$ m, $l = 0.4$ m, $W = 0.8$ m	Gabion steps (plain) Capped steps (layer cake) Upward steps Pooled steps (End Sill)	$Q = 0.05$ to 0.2 m ³ /s, $Re = 2.5 \times 10^5$ to 1.0×10^6	Pitot tube array (copper pipe with inlet holes every 5 cm)
Present Study	26.6	$h = 0.1$ m, $l = 0.2$ m, $W = 0.52$ m	Smooth and impervious steps Gabion and porous steps	$Q = 0.02$ to 0.11 m ³ /s, $Re = 1.4 \times 10^5$ to 8.8×10^5 (†)	Double tip conductivity probe ($\varnothing = 0.25$ mm, $\Delta x = 6.2$ mm, $\Delta z = 1.35$ mm)
Rough impervious steps					
Gonzalez et al. (2008)	21.8	$h = 0.1$ m, $l = 0.25$ m, $W = 1$ m	Rough impervious step faces Rough vertical faces Rough horizontal faces Smooth steps	$Q = 0.01$ to 0.22 m ³ /s, $Re = 5 \times 10^4$ to 7×10^5 (†)	Double tip conductivity probe ($\varnothing = 0.025$ mm)
Bung & Schlenkhoff (2010)	26.6	$h = 0.06$ m, $W = 0.30$ m	Rough impervious horizontal faces (in row) Rough impervious horizontal faces (shifted) Smooth steps	$Q = 0.021, 0.027$ & 0.33 m ³ /s, $Re = 2.7 \times 10^5, 3.6 \times 10^5$ & 4.4×10^5 (†)	Double-tip conductivity probe ($\varnothing = 0.13$ mm, $\Delta x = 5.1$ mm, $\Delta y = 1$ mm)

Notes: h: step height; l: step length; Q: water discharge, Re: Reynolds number defined in terms of hydraulic diameter; W: width of channel; \varnothing : probe diameter; Δx : streamwise distance between probe tips; Δy : vertical distance between probe tips; Δz : transverse distance between probe tips; θ : chute slope; (†): air-water flow measurements.

WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

Fig. 1 - Gabion stepped weir at Robina, Gold Coast (Australia) - $h = 0.6$ m, $l = 1.1$ to 2 m
(A) On 2 April 1997 shortly after completion



(B) On 25 April 2013



WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

Fig. 2 - Experimental stepped weir

(A) Skimming flow on the smooth impervious stepped configuration ($d_s/h = 1.3$)



(B) Transition flow on the gabion stepped configuration ($d_s/h \sim 0.9$)




WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

Fig. 3 - Porous, nappe and skimming flow regimes above a gabion stepped weir

(A) Porous flow at first gabion box located at end of broad-crest: $d_o/h = 0.20$, $Q = 0.005 \text{ m}^3/\text{s}$, $Re = 3.5 \times 10^4$



(B) Nappe flow



(C) Skimming flow





Fig. 4 - Air concentration distributions in transition and skimming flows on smooth impervious and gabion stepped weirs - $\theta = 26.6^\circ$, $h = 0.10$ m

(A) $d_c/h = 0.5$, $Q = 0.018$ m³/s, $Re = 1.40 \times 10^5$



(B) $d_c/h = 1.3$, $Q = 0.076$ m³/s, $Re = 5.9 \times 10^5$






Fig. 5 - Bubble count rate distributions in transition and skimming flows on smooth impervious and gabion stepped weirs - $\theta = 26.6^\circ$, $h = 0.10$ m
 (A) $d_c/h = 0.5$, $Q = 0.018$ m³/s, $Re = 1.40 \times 10^5$



(B) $d_c/h = 1.5$, $Q = 0.095$ m³/s, $Re = 7.3 \times 10^5$



WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

Fig. 6 - Velocity distributions in skimming flow on smooth impervious and gabion stepped weirs - $\theta = 26.6^\circ$, $h = 0.10$ m, $d_c/h = 1.3$, $Q = 0.076$ m³/s, $Re = 5.9 \times 10^5$ - Comparison with a 1/8th profile





Fig. 7 - Turbulence intensity distributions in transition and skimming flow in smooth impervious and gabion stepped weirs - $\theta = 26.6^\circ$, $h = 0.10$ m

(A) $d_c/h = 0.8$, $Q = 0.037$ m³/s, $Re = 2.83 \times 10^5$



(B) $d_c/h = 1.1$, $Q = 0.059$ m³/s, $Re = 4.57 \times 10^5$





Fig. 8 - Longitudinal distributions of characteristic air-water flow properties Y_{90}/d_c , C_{mean} , and V_{90}/V_c for smooth impervious and gabion stepped weirs ($\theta = 26.6^\circ$, $h = 0.10$ m) - Same legend applies to all graphs



WUTHRICH, D, and CHANSON, H. (2014). "Hydraulics, Air Entrainment and Energy Dissipation on Gabion Stepped Weir." *Journal of Hydraulic Engineering*, ASCE, Vol. 140, No. 9, Paper 04014046, 10 pages (DOI: 10.1061/(ASCE)HY.1943-7900.0000919) (ISSN 0733-9429).

Fig. 9 - Residual head at the downstream end of smooth impervious and gabion stepped chutes ($\theta = 26.6^\circ$, $h = 0.10$ m) - Gabion data measured at Step edge 10 and in bottom (tailrace) channel




Fig. 10 - Equivalent Darcy-Weisbach friction factor on smooth impervious and gabion stepped weirs ($\theta = 26.6^\circ$, $h = 0.10$ m)

