



REVIEW ARTICLE

10.1002/2015WR017096

Special Section:

The 50th Anniversary of Water Resources Research

Key Points:

- Land model development can benefit from recent advances in hydrology
- Accelerating modeling advances requires comprehensive benchmarking activities
- Stronger collaboration is needed between the hydrology and ESM modeling communities

Correspondence to:

M. P. Clark,
mclark@ucar.edu

Citation:

Clark, M. P., Y. Fan, D. M. Lawrence, J. C. Adam, D. Bolster, D. J. Gochis, R. P. Hooper, M. Kumar, L. R. Leung, D. S. Mackay, R. M. Maxwell, C. Shen, S. C. Swenson, and X. Zeng (2015), Improving the representation of hydrologic processes in Earth System Models, *Water Resour. Res.*, 51, 5929–5956, doi:10.1002/2015WR017096.

Received 13 FEB 2015

Accepted 19 JUL 2015

Accepted article online 22 JUL 2015

Published online 21 AUG 2015

Improving the representation of hydrologic processes in Earth System Models

Martyn P. Clark¹, Ying Fan², David M. Lawrence¹, Jennifer C. Adam³, Diogo Bolster⁴, David J. Gochis¹, Richard P. Hooper⁵, Mukesh Kumar⁶, L. Ruby Leung⁷, D. Scott Mackay⁸, Reed M. Maxwell⁹, Chaopeng Shen¹⁰, Sean C. Swenson¹, and Xubin Zeng¹¹

¹National Center for Atmospheric Research, Boulder, Colorado, USA, ²Department of Earth and Planetary Sciences, Rutgers University, New Brunswick, New Jersey, USA, ³Department of Civil and Environmental Engineering, Washington State University, Pullman, Washington, USA, ⁴Department of Civil & Environmental Engineering and Earth Sciences, University of Notre Dame, South Bend, Indiana, USA, ⁵The Consortium of Universities for the Advancement of Hydrologic Science, Inc., ⁶Nichols Schools of Environment, Duke University, Durham, North Carolina, USA, ⁷Pacific Northwest National Laboratory, Richland, Washington, USA, ⁸Department of Geography, University at Buffalo, State University of New York, Buffalo, New York, USA, ⁹Department of Geology and Geological Engineering, Colorado School of Mines, Golden, Colorado, USA, ¹⁰Department of Civil and Environmental Engineering, Pennsylvania State University, State College, Pennsylvania, USA, ¹¹Department of Atmospheric Sciences, University of Arizona, Tucson, Arizona, USA

Abstract Many of the scientific and societal challenges in understanding and preparing for global environmental change rest upon our ability to understand and predict the water cycle change at large river basin, continent, and global scales. However, current large-scale land models (as a component of Earth System Models, or ESMs) do not yet reflect the best hydrologic process understanding or utilize the large amount of hydrologic observations for model testing. This paper discusses the opportunities and key challenges to improve hydrologic process representations and benchmarking in ESM land models, suggesting that (1) land model development can benefit from recent advances in hydrology, both through incorporating key processes (e.g., groundwater-surface water interactions) and new approaches to describe multiscale spatial variability and hydrologic connectivity; (2) accelerating model advances requires comprehensive hydrologic benchmarking in order to systematically evaluate competing alternatives, understand model weaknesses, and prioritize model development needs, and (3) stronger collaboration is needed between the hydrology and ESM modeling communities, both through greater engagement of hydrologists in ESM land model development, and through rigorous evaluation of ESM hydrology performance in research watersheds or Critical Zone Observatories. Such coordinated efforts in advancing hydrology in ESMs have the potential to substantially impact energy, carbon, and nutrient cycle prediction capabilities through the fundamental role hydrologic processes play in regulating these cycles.

1. Introduction

The stores and fluxes of water near the land surface modulate nearly all processes at the land-atmosphere interface. For example, evapotranspiration affects weather and climate through its influence on boundary layer dynamics and thermal dynamics. The stores and fluxes of water on land also influence ecosystem structure and functioning, carbon, nutrient, and other biogeochemical cycles, and dictate freshwater availability for societies. Many of the scientific and societal challenges to understand and prepare for global environmental change rest upon our ability to understand and predict water cycle changes at large river basin, continent, and global scales [Eagleson, 1986].

Simulations of global environmental change are now performed using Earth System Models (ESMs), which are designed to capture the key interactions among the components of the Earth System including the atmosphere, ocean, land, and sea ice [Flato, 2011; Dunne *et al.*, 2012; Hurrell *et al.*, 2013]. ESMs build on global climate model platforms but substantially extend their capabilities by representing a diverse set of physical, chemical, and biological interactions across multiple space and time scales [Hurrell *et al.*, 2013]. Here we focus on the hydrologic processes in the so-called “land models”—the land component of ESMs. Because terrestrial water stores and fluxes are strong modulators of energy and biogeochemical stores on

land and their flux exchange with the atmosphere and the oceans, adequately capturing hydrologic processes in the ESM land models has important implications to our ability to predict global environmental change.

The last 50 years have seen remarkable advances in the capabilities of land models to simulate land surface influences on weather and climate. Since the very first attempt to incorporate land surface processes in climate models [Manabe *et al.*, 1965; Manabe, 1969], land models have evolved to include sophisticated representation of biogeophysical, biogeochemical, and hydrologic processes [Sellers *et al.*, 1997; Pitman, 2003; van den Hurk *et al.*, 2011]. Many hydrologists have been actively involved in, and contributed toward, water cycle advancement in ESMs, and several such land models have been applied to studying the water cycle change at large river basin, continent and global scales. This two-way flow of knowledge and tools have benefited both the ESM community and those hydrologists engaged in large-scale water cycle research. As *Water Resources Research* celebrates its Fiftieth anniversary, it is important to reflect on the past advances in water cycle representation in ESM land models, and consider if the collective wisdom and knowledge from the hydrologic sciences could be more fully utilized to inform and advance the representation of the terrestrial water cycle in ESMs.

In this paper, we juxtapose modeling advances in the land modeling community with advances in the hydrologic sciences to address the following two questions:

1. What are the hydrologic stores and fluxes that are known to be essential to predicting large-scale water, energy, and biogeochemical fluxes but not yet adequately accounted for in ESMs? Put differently, what are the key opportunities to improve the representation of hydrologic processes in land models?
2. How can we evaluate model improvements? What are the practical steps that our community can take so that we can meaningfully and transparently test, document, and benchmark model performance, and set milestones moving forward as a community?

We do not intend to fully answer these questions here, but to provide our perspective of the past progress and lessons learned, building on the extensive literature of Model Intercomparison Experiments and benchmarking activities (see van den Hurk *et al.* [2011] for a recent review), along with a recent synthesis of modeling approaches in the hydrologic sciences [Clark *et al.*, 2015a, 2015b]. We also do not intend to provide a comprehensive review of the representation of all terrestrial hydrologic processes in all models designed for many different applications. Our emphasis here is the hydrologic processes that are well recognized to be the most basic (e.g., lateral convergence, two-way groundwater-surface water exchange) and most relevant to the large-scale Earth System functioning (e.g., regulating the global carbon cycle). We also emphasize the critical need to represent hydrologic processes explicitly and mechanistically (not empirically) so that we can predict future water cycle changes forced by, and forcing, global energy and biogeochemical cycle changes. Lastly, we emphasize the need for parsimonious (parameter-wise) and efficient (computation-wise) ways to represent these essential hydrologic processes in the ESM context.

To keep the paper tractable, we focus primarily on below ground hydrologic processes and explicitly consider the representation of the storage and transmission of water in soils, infiltration, root water uptake, groundwater dynamics, stream-aquifer interactions, and channel/floodplain routing. These stores and fluxes are arguably among the weakest parts of current land models. We also review model representations of spatial heterogeneity and briefly discuss the impact of humans on the terrestrial water cycle. Important hydrologic processes, such as canopy and snow hydrology, the role of land cover and land use change on the water cycle, and interactions between hydrology and biogeochemistry, are not reviewed here.

The remainder of this paper is organized as follows. In section 2, we provide the scientific motivation for improving the representation of hydrologic processes in land models. In section 3, we contrast the current representation of hydrologic processes in modern land models (Table 1) with the modeling approaches used in the hydrologic sciences. Our goal for this (rather focused) review is to identify key opportunities to improve the representation of hydrologic processes in the land models of ESMs. In section 4, we discuss the work needed to accelerate modeling advances; in particular, we discuss the need for comprehensive hydrologic benchmarking activities that systematically evaluate competing modeling alternatives, understand model weaknesses, and prioritize model development needs. Finally, in section 5, we present concluding remarks.

Table 1. Land Models Reviewed in This Study

Model	Name	References
CABLE	The Community Atmosphere Biosphere Land Exchange model	<i>Kowalczyk et al.</i> [2006] and <i>Wang et al.</i> [2011]
Catchment	The Catchment model	<i>Ducharne et al.</i> [2000] and <i>Koster et al.</i> [2000]
CLM	The Community Land Model	<i>Niu et al.</i> [2007], <i>Zeng and Decker</i> [2009], <i>Oleson et al.</i> [2010], and <i>Lawrence et al.</i> [2011]
TESSEL	The Tiled ECMWF Scheme for Surface Exchanges over Land	<i>Balsamo et al.</i> [2009], <i>Balsamo et al.</i> [2011], <i>Pappenberger et al.</i> [2012], and <i>ECMWF</i> [2014]
JULES	The Joint UK Land Environment Simulator	<i>Cox et al.</i> [1999], <i>Gedney and Cox</i> [2003], <i>Clark and Gedney</i> [2008], and <i>Best et al.</i> [2011]
LEAF	The Land Ecosystem-Atmosphere Feedback model	<i>Walko et al.</i> [2000], <i>Fan et al.</i> [2007], <i>Miguez-Macho et al.</i> [2007], and <i>Miguez-Macho and Fan</i> [2012a,b]
LM3	Land Model 3	<i>Milly et al.</i> [2014] and <i>Subin et al.</i> [2014]
MATSIRO	The Minimal Advanced Treatments of Surface Interaction and Runoff	<i>Takata et al.</i> [2003], <i>Yeh and Eltahir</i> [2005a,b], and <i>Koirala et al.</i> [2014]
Noah	The Noah land surface model	<i>Chen et al.</i> [1996], <i>Schaake et al.</i> [1996], <i>Koren et al.</i> [1999], <i>Chen and Dudhia</i> [2001], and <i>Ek et al.</i> [2003]
ORCHIDEE	The Organizing Carbon and Hydrology in Dynamic Ecosystems model	<i>de Rosnay et al.</i> [2002], <i>Verant et al.</i> [2004], <i>Ngo-Duc et al.</i> [2007], <i>d'Orgeval et al.</i> [2008], and <i>Campoy et al.</i> [2013]
VIC	The Variable Infiltration Capacity model	<i>Liang et al.</i> [1994], <i>Liang et al.</i> [1996], <i>Lohmann et al.</i> [1998b], and <i>Nijssen et al.</i> [2001]

2. Scientific Motivation

The current rudimentary representation of hydrologic processes in ESM land models limits our capability to simulate land-atmosphere fluxes and biogeochemical cycles, which, in turn, limits our ability to predict land-atmosphere processes and feedbacks across multiple time (minutes to centuries) and space (points to continents) scales. Incomplete treatment of terrestrial hydrological processes also impedes our ability to properly constrain model performance using new observational capabilities such as groundwater and remotely sensed data. A concerted effort to improve the representation of hydrologic processes in land-surface models will accelerate science advances in a number of key areas. Some of the science questions that motivate the overarching ideas presented in this review include:

1. How does the space-time variability in hydrologic stores (canopy, snowpack, soil moisture, groundwater, rivers and floodplains, lakes and reservoirs, and wetlands) affect land-atmosphere fluxes on time scales from minutes to seasons? How does the hydrologic modulation of land-atmosphere fluxes affect weather and climate, including fronts, storm tracks, monsoons, and extremes? To what extent do advances in model representation of the land branch of the water cycle improve regional predictions of weather and climate across multiple time and space scales?
2. How will the hydrologic stores and fluxes respond to global environmental change under natural (e.g., climate variability) and anthropogenic (e.g., land use change, irrigation) forcings? How will the water cycle response affect biological productivity and functioning in terrestrial and aquatic ecosystems? How will the hydrologic and ecosystem responses feedback on the climate system, and through what physical-biogeochemical pathways? What are the globally salient mechanisms of these responses and feedbacks?
3. Given that groundwater and lateral flow are largely missing in ESM land models, what is the role of the groundwater, with its large storage and slow response to climate forcing, in buffering water stress in terrestrial and aquatic ecosystems and human societies? How will groundwater resources respond to climate change and mounting human pressure? How will the globally diminishing groundwater observed by GRACE affect dry-season streamflow, groundwater-supported ecosystem productivity, and water quality (e.g., stream temperature)?
4. What parts of the world will likely experience water stress, posing threats to ecosystem sustainability and water and food security for human populations? Can we quantify water resource vulnerability in the context of climate change and human development uncertainty?
5. How will warming affect the Pan-Arctic permafrost and peatlands? How will the projected large-scale thawing and draining affect Arctic hydrological conditions, thereby impacting how and when thawed organic matter is decomposed and released to the atmosphere as carbon dioxide or methane?

These critical science questions cannot be comprehensively addressed with the current generation of ESM land models. Addressing them requires additional targeted development, capitalizing on the progress in modeling capabilities in the hydrologic sciences. The next section outlines some key opportunities to advance representation of hydrologic processes in land models necessary to begin to address these critical science questions.

3. Opportunities to Improve the Representation of Hydrologic Processes in Land Models

The opportunities to improve the representation of hydrologic processes in land models fall into three main categories. First, there are opportunities to directly improve the model representation of individual hydrologic processes. Work in this area can improve simulations of soil moisture dynamics, groundwater dynamics, and, ultimately, the space-time variability of plant available water and its impact on biogeochemical cycles. Second, there are opportunities to improve representations of how interlinked hydrologic-biophysical-biogeochemical processes affect land-atmosphere fluxes at larger spatial scales. The key aspects of this second element are the approaches used to characterize spatial heterogeneity and hydrologic connectivity. Third, there are opportunities to substantially improve model representations of human impacts on the terrestrial hydrologic cycle. The following sections review model development opportunities in each of these three areas.

3.1. Representation of Hydrologic Processes

Table 2 summarizes the key differences in the representation of hydrologic processes among 11 current generation land models developed by different modeling groups, documenting the approaches used to represent the storage and transmission of water in soils, infiltration, root water uptake, groundwater dynamics, stream-aquifer interactions, and channel/floodplain routing. Appendix A reviews the similarities and differences among these land models, and contrasts the representation of hydrologic processes in land models with the modeling approaches used in the hydrologic sciences. The main inter-model differences in Table 2 are (1) the storage and transmission of water in soils is typically simulated using the moisture-form of Richards' equation; (2) infiltration is most commonly simulated as saturation-excess runoff, where saturated areas are parameterized either as a function of water table depth or soil moisture; (3) the lower boundary condition is often handled as free drainage or restricted drainage; (4) root water uptake is typically simulated using a macroscopic approach (i.e., ignoring hydraulic gradients between the roots and the soil); and (5) groundwater dynamics and stream-aquifer interactions are either neglected or simulated using overly simple methods.

Table 3 identifies candidate areas to improve the representation of hydrologic processes in land models. The key areas are (1) improve simulations of the storage and transmission of water in the soil matrix, obtained through (a) implementing the mixed form of Richards' equation [Celia *et al.*, 1990; Maxwell and Miller, 2005] and (b) explicitly representing macropore flow [Beven and Germann, 1982; Weiler, 2005; Nimmo, 2010; Yu *et al.*, 2014]; (2) improve representation of hydraulic gradients throughout the soil-plant-atmosphere continuum to improve simulations of root water uptake and evapotranspiration [Balocchi and Meyers, 1998; Mackay *et al.*, 2003; Bonan *et al.*, 2014]; (3) improve representation of groundwater dynamics across a hierarchy of spatial scales, including improving "among grid" and "within grid" groundwater representations [Famiglietti and Wood, 1994; Troch *et al.*, 2003; Miguez-Macho *et al.*, 2007]; and (4) improve simulations of streamflow, by explicitly representing stream-aquifer interactions and improving parameterizations of channel/floodplain routing [Qu and Duffy, 2007; Shen and Phanikumar, 2010; Miguez-Macho and Fan, 2012a; Pappenberger *et al.*, 2012]. Underpinning all of these areas is the need to improve data sets on geophysical attributes, especially data on bedrock depth and permeability [Tesfa *et al.*, 2009; Fan *et al.*, 2015] and data sets on the physical characteristics of rivers [Getirana *et al.*, 2013; Mersel *et al.*, 2013; Gleason and Smith, 2014].

The philosophy underlying the recommendations in Table 3 is the need to explicitly resolve dominant hydrologic processes. This approach differs from the approach often adopted in the hydrologic modeling community where the preference is to lump multiple processes (e.g., use a parsimonious catchment-average storage-discharge functions), and implicitly represent the aggregate impact of unresolved processes [e.g., Perrin *et al.*, 2003; Fenicia *et al.*, 2014]. We push for a mechanistic approach, even where the

Table 2. Representation of Hydrologic Processes in Different Land Models

Model	Storage/Transmission of Water Through Soils	Infiltration	Lower Boundary Condition	Root Water Uptake	Groundwater Dynamics	Routing
CABLE	Richards' equation (Clapp Hornberger functions)	Unlimited	Restricted drainage	Macroscopic approach	None	None
Catchment	Empirical approximation to 1-D Richards' equation	Saturation-excess runoff, $F_{sat} = f(z_{wt})$	Two-way flux between the root zone and water table	Macroscopic approach	Base flow computed using TOPMODEL concepts	None
CLM	Richards' equation (Clapp Hornberger functions)	Saturation-excess runoff, $F_{sat} = f(z_{wt})$	Free drainage	Explicitly represent the hydraulic gradients ^a	Base flow computed using TOPMODEL concepts	Linear storage-outflow relationship
TESSEL	Richards' equation (van Genuchten functions)	Saturation-excess runoff, $F_{sat} = f(\theta)$	Free drainage	Macroscopic approach	None	1-D diffusive wave
JULES	Richards' equation (either Clapp Hornberger or van Genuchten functions)	Saturation-excess runoff; options for $F_{sat} = f(\theta)$ or $F_{sat} = f(z_{wt})$	Options for free drainage and zero-flux boundary conditions (depends on groundwater dynamics)	Macroscopic approach	Includes the option to use TOPMODEL concepts to compute base flow	None
LEAF	Richards' equation (Clapp Hornberger functions)	Infiltration-excess and Saturation-excess runoff, $F_{sat} = f(\theta)$	Water table represented as a moving lower boundary	Macroscopic approach	Grid-to-grid lateral flow based on Darcy's Law	1-D diffusive wave
LM3	Richards' equation (Clapp Hornberger functions) ^b	Unlimited ^c	Zero flux	Explicitly represent the hydraulic gradients	Hillslope flow based on Darcy's Law	1-D diffusive wave in low slope reaches
MATSIRO	Richards' equation (Clapp Hornberger functions)	Saturation-excess runoff, $F_{sat} = f(z_{wt})$	Water table represented as a moving lower boundary	Macroscopic approach	Base flow computed using TOPMODEL concepts	None
Noah	Richards' equation (Clapp Hornberger functions)	Based on variability in infiltration and precipitation	Restricted drainage	Macroscopic approach	None	None
ORCHIDEE	Richards' equation (van Genuchten functions)	Saturation-excess runoff, $F_{sat} = f(\theta)$	Free drainage ^d	Macroscopic approach	None	Linear storage-outflow relationship
VIC	Richards' equation (Clapp Hornberger functions)	Saturation-excess runoff, $F_{sat} = f(\theta)$	Free drainage	Macroscopic approach	Conceptual bucket below the soil profile	Source-to-sink method

^aThe representation of hydraulic gradients throughout the soil-plant-atmosphere continuum [Bonan et al., 2014] is not yet incorporated in an official release of CLM.

^bLM3 has separate micropore and macropore domains; Richards' equation used for the micropore domain and water moves instantaneously through macropore domain.

^cLM3 computes surface runoff if the infiltration capacity of the soil exceeded – however, the would-be surface runoff enters macropores (if macropores are present).

^dCampoy et al. [2013] also experimented with options for (i) restricted drainage and (ii) imposing water table boundary condition at specific depths within the soil profile.

results compared to today's observations do not necessarily agree as well, because we cannot guarantee that the parsimonious lumped models will hold under a different climate regime [Vaze et al., 2010; Milly and Dunne, 2011].

An important issue is defining the appropriate balance between model complexity and model fidelity. We define model complexity as the number of model state variables and fluxes—in this definition model complexity describes the extent to which physical processes are represented explicitly as well as the discretization and connectivity of the physical landscape. We define model fidelity as the extent to which models faithfully represent observed processes. The trade-offs between complexity and fidelity bring up two central questions: first, to what extent is additional model complexity supported by the available information on geophysical attributes (topography, vegetation, soils, geology, and fine-scale meteorological data)? Or, put differently, does it make sense to include additional processes if there is limited information on the spatial variability of model parameters? Second, to what extent does the higher computational cost of more complex models limit their use, especially by constraining the application of continental-domain parameter estimation methods [Samaniego et al., 2010] and stochastic simulations [Maxwell and Kollet, 2008a]. We hence

Table 3. Opportunities for Future Land Surface Model Development

Model Development Opportunities	Expected Impact	References
Explicitly represent variably saturated flow using the mixed form of Richards' equation	Improve simulations of shallow groundwater dynamics and soil moisture	<i>Celia et al.</i> [1990], <i>Maxwell and Miller</i> [2005], and <i>Kumar et al.</i> [2009]
Explicitly represent vapor flow through soil	Improve simulations of evapotranspiration	<i>Parker et al.</i> [1987], <i>Painter</i> [2011], <i>Zeng et al.</i> [2011], and <i>Smits et al.</i> [2012]
Explicitly represent macropore and fracture flow	Improve simulations of soil moisture, evapotranspiration, groundwater dynamics, and runoff	<i>Beven and Germann</i> [1981, 1982], <i>SimunEk et al.</i> [2003], <i>Weiler</i> [2005], <i>McDonnell et al.</i> [2007], <i>Maxwell and Kollet</i> [2008a], <i>Maxwell</i> , [2010], <i>Nimmo</i> [2010], and <i>Yu et al.</i> [2014]
Explicitly represent infiltration of surface runoff as water moves across the landscape	Improve simulations of soil moisture and partitioning of precipitation into evapotranspiration and runoff	<i>Downer and Ogden</i> [2004], <i>Kollet and Maxwell</i> [2006], <i>Kumar et al.</i> [2009], and <i>Therrien et al.</i> [2010]
Explicitly represent hydraulic gradients throughout the soil-plant-atmosphere continuum	Improve simulations of root water uptake and evapotranspiration	<i>Baldocchi and Meyers</i> [1998], <i>Lai and Katul</i> [2000], <i>Williams et al.</i> [2001], <i>Mackay et al.</i> [2003], <i>Bonan et al.</i> [2014], and <i>Manoli et al.</i> [2014]
Explicitly represent "among-grid" groundwater flow, using 2-D or 3-D models	Improve simulations of groundwater dynamics and evapotranspiration	<i>Miguez-Macho et al.</i> [2007], <i>Kumar et al.</i> [2009], <i>Therrien et al.</i> [2010], <i>Miguez-Macho and Fan</i> [2012a,b], and <i>Maxwell et al.</i> [2015]
Explicitly (or implicitly) represent "within-grid" groundwater flow, using representative hillslopes	Improve simulations of groundwater dynamics and evapotranspiration	<i>Famiglietti and Wood</i> [1994], <i>Wigmosta and Lettenmaier</i> [1999], <i>Beven and Freer</i> [2001], <i>Paniconi et al.</i> [2003], <i>Troch et al.</i> [2003b], and <i>Subin et al.</i> [2014]
Explicitly represent stream-aquifer interactions	Improve simulations of groundwater dynamics and streamflow	<i>Panday and Huyakorn</i> [2004], <i>Kollet and Maxwell</i> [2006], <i>Qu and Duffy</i> [2007], <i>Shen and Phanikumar</i> [2010], <i>Miguez-Macho and Fan</i> [2012a], and <i>Niu et al.</i> [2014]
Improve simulations channel/floodplain routing by implementing 1-D diffusive wave models	Improve simulations of streamflow, especially backwater effects	<i>Yamazaki et al.</i> [2011], <i>Miguez-Macho and Fan</i> [2012a], <i>Pappenberger et al.</i> [2012], and <i>Yamazaki et al.</i> [2012]
Improve data sets on bedrock depth and bedrock permeability	Improve simulations of soil moisture and groundwater dynamics	<i>Tesfa et al.</i> [2009] and <i>Fan et al.</i> [2015]
Improve data sets on physical characteristics of rivers (e.g., slope, roughness, hydraulic geometry)	Improve simulations of streamflow and stream-aquifer interactions	<i>Getirana et al.</i> [2013], <i>Mersel et al.</i> [2013], and <i>Gleason and Smith</i> [2014]

propose careful analysis of the trade-offs between complexity and fidelity; we will return to this issue in section 4.3.

3.2. Heterogeneity and Scaling Behavior

A critical issue in land modeling is to understand and reliably simulate the impacts of heterogeneity in inter-linked hydrologic-biophysical-biogeochemical processes on land-atmosphere fluxes at larger spatial scales [*Giorgi and Avissar*, 1997; *Essery et al.*, 2003]. Model experiments show that heterogeneity in soil moisture can have profound impacts on regional meteorology [*Avissar and Pielke*, 1989; *Chen and Avissar*, 1994; *Mahrt*, 2000; *Huang and Margulis*, 2009], signifying that improved representation of the heterogeneity in soil moisture (and associated vegetation) can substantially improve simulations of land-atmosphere interactions [*Maxwell and Kollet*, 2008b].

The crux of the problem is to simulate how subgrid-scale heterogeneities are manifest in grid-average fluxes. This has received substantial attention in the land modeling community over the past several decades [*Shuttleworth*, 1988; *Entekhabi and Eagleson*, 1989; *Pitman et al.*, 1990; *Dolman and Gregory*, 1992; *Koster and Suarez*, 1992], and has been addressed in five main ways: (1) explicit representation of subgrid variability—this can be accomplished by configuring the land model with a finer mesh than the rest of the ESM [*Hahmann and Dickinson*, 2001], by using multiple tiles to represent subgrid heterogeneity [*Koster and Suarez*, 1992; *Bonan et al.*, 2002], or by explicitly representing the spatial variability for a subset of processes; e.g., separate stomatal conductance calculations for sunlit and shaded leaves [*Wang and Leuning*, 1998] or separate energy balance calculations for snow-covered and snow-free surfaces [*Takata et al.*, 2003; *Swenson and Lawrence*, 2012]; (2) statistical-dynamical models, which parameterize how subgrid variability in model state variables affects grid-average fluxes—for example, as discussed in section A1.1, the Probability Distributed Model [*Moore and Clarke*, 1981] and TOPMODEL [*Beven and Kirkby*, 1979] represent the impacts of

subgrid variability in soil moisture and water table depth on grid-average infiltration [e.g., Clark and Gedney, 2008]; (3) development of new parameterizations that represent the aggregate impact of subgrid heterogeneities on grid-average fluxes [e.g., Mahrt, 1987; Essery et al., 2008]; (4) application of reduced-order modeling to construct surrogate models for subgrid variability from fine-grid simulations [e.g., Pau et al., 2014; Riley and Shen, 2014]; and (5) development of “effective” parameter values through application of upscaling operators that are specifically designed to reflect the impact of fine-scale heterogeneity on large-scale fluxes [e.g., Samaniego et al., 2010].

A key missing link in the current generation of land models is representing how the spatial organization of soil moisture and groundwater [Western et al., 1999; Grant et al., 2004] affects land-atmosphere fluxes [Maxwell and Kollet, 2008b]. In particular, most of the land models reviewed in Table 2 have a simplistic representation of the topographic controls on fine-scale soil moisture heterogeneity and the associated heterogeneity in evapotranspiration. Many models use a variant of the mosaic approach to represent surface heterogeneity, where land-atmosphere fluxes are computed separately for different vegetation types within a model grid box [Koster and Suarez, 1992]. A variant of the mosaic approach is used in CLM [Bonan et al., 2002], TESSEL [Balsamo et al., 2009], LEAF [Walko et al., 2000], VIC [Liang et al., 1994], and ORCHIDEE [Campoy et al., 2013]. In other models, the representation of spatial heterogeneity is even more limited—the Noah model [Ek et al., 2003], MATSIRO [Takata et al., 2003], and CABLE [Kowalczyk et al., 2006] have a single vegetation type per grid box; spatial heterogeneity is represented in CABLE solely through separate stomatal resistance calculations for sunlit and shaded leaves [Dai et al., 2004] and in MATSIRO through different surface energy calculations for snow covered and snow-free surfaces [Takata et al., 2003]. Two standout models with more detailed representations of subgrid heterogeneity are the Catchment model [Koster et al., 2000] and the tiled hydrology implementation of the LM3 model [Subin et al., 2014]—the Catchment model explicitly disaggregates a grid cell into catchments, with further disaggregation into zones of variable evapotranspiration stress; the LM3 model explicitly calculates the lateral flux of water among a sequence of tiles in a subgrid hillslope, leading to higher water table (and consequently lower plant water stress) in areas of topographic convergence.

There are a number of opportunities to improve the representation of the topographic controls on subgrid heterogeneities. Specifically, several existing approaches can readily be implemented into land models: (1) the distributed TOPMODEL approach, differing from the lumped TOPMODEL approach implemented in many land models (Table 2)—in the distributed approach, grid cells are disaggregated into multiple tiles based on the topographic index, with the local water table for a given topographic index class imposed as a lower boundary condition for each subgrid tile [Famiglietti and Wood, 1994]; (2) Kinematic subsurface flow along a representative hillslope—assuming that the water table gradient can be approximated by the topographic gradient, the groundwater flow equation is reduced to a 1-D kinematic wave equation and can be applied to simulate the water table position for various tiles along the hillslope [Wigmosta and Lettenmaier, 1999; Beven and Freer, 2001]; (3) dynamic subsurface flow across a representative hillslope, where lateral flux depends on spatial water table gradients—this is the approach used in the Hillslope Boussinesq model [Troch et al., 2003; Paniconi et al., 2003], and can be applied to multiple hillslope tiles to represent spatially variable evapotranspiration stress as in the LM3-TiHy model [Subin et al., 2014]; and (4) a high-resolution spatial mesh of subgrid tiles [Hahmann and Dickinson, 2001], which can be extended to explicitly resolve hill-to-valley convergence, implementing the same large-scale, among-grid groundwater flow model to finer grids within an ESM grid box. All of these methods represent both the spatial variability in physical characteristics (meteorology, vegetation, soils) as well as hydrologic connectivity, which enables simulations of the spatial organization of soil moisture and groundwater and plant water stress.

An important consideration is multiscale modeling of energy and mass fluxes, where different physical processes are simulated at different spatial resolutions. Multiscale modeling has a long history in land models: examples include separate stomatal conductance calculations for sunlit and shaded leaves, to scale fluxes from the leaf scale to the canopy scale [Wang and Leuning, 1998]; multiple plant functional types embedded within a single soil column to represent the impacts of spatial variability in vegetation phenology on grid-scale fluxes [Bonan et al., 2002]; and, more generally, a high-resolution spatial mesh of subgrid tiles to represent the large-scale impact of landscape heterogeneity [Hahmann and Dickinson, 2001]. More recent multiscale capabilities include high-resolution subgrid spatial mesh for terrain routing (subsurface and overland flow) and complex spatial representations of the river network and the built environment

[Gochis *et al.*, 2013; Voisin *et al.*, 2013a, 2013b; Subin *et al.*, 2014; Clark *et al.*, 2015a; Li *et al.*, 2015]. The need for multiscale modeling capabilities introduces new software engineering requirements, including hierarchical data structures, unstructured grids, and more complex coupling procedures [Oleson *et al.*, 2010; Leonard and Duffy, 2014].

3.3. Human Impacts on the Terrestrial Water Cycle

Human actions comprise another area ripe for improvement in ESMs. While humans are indirectly impacting the hydrologic cycle a myriad of ways including through anthropogenic climate change, e.g., through changes in snowpack hydrology [Barnett *et al.*, 2005] and intensification of the water cycle [Huntington, 2006], humans are also impacting the water cycle directly. Construction of dams causes an increase of residence time on the land surface, fragments our waterways, and inundates river valleys [Marble and Lough, 1997]; surface water diversions distort our hydrologic regimes [Poff *et al.*, 1997]; groundwater extraction and tile drains lower the water table with impacts on connected surface water bodies [Zektser *et al.*, 2005]; irrigation mines surface and groundwater systems and increases evapotranspiration [Boucher *et al.*, 2004]; and other land use changes such as forest and cropland management impact the partitioning of precipitation into ET, runoff, and groundwater recharge and flow [Foley *et al.*, 2005].

Currently, many existing and new ESMs are being developed to resolve coupled human and natural systems, including representation of resource management activities [Pokhrel *et al.*, 2012; Adam *et al.*, 2014; Kraucunas *et al.*, 2014]. CLM has been developed to represent maize, soybean, and spring wheat including management practices such as fertilizer application, residue management, and harvest [Drewniak *et al.*, 2013]; irrigation from surface water [Sacks *et al.*, 2009; Leng *et al.*, 2013] and from groundwater [Leng *et al.*, 2014]. VIC [Liang *et al.*, 1994] has been fully coupled to a cropping system model (CropSyst), allowing for simulation of the interactions between large-scale hydrologic processes and crop growth, phenology, and management (including irrigation technology and management) [Stöckle *et al.*, 2014]; and it has been adapted to simulate reservoir operations [Haddeland *et al.*, 2006]. Other modeling frameworks that allow for representation of water management include WaterGap [Alcamo *et al.*, 2003] the Model for Scale Adaptive River Transport (MOSART), which is a streamflow routing model [Li *et al.*, 2013] that has been incorporated into an ESM framework [Li *et al.*, 2015] and coupled with a water management model [Voisin *et al.*, 2013a] and an integrated assessment model [Voisin *et al.*, 2013b] to simulate water demand consistent with the socioeconomic scenarios. Nazemi and Wheeler [2015a,b] provide a comprehensive review of the incorporation of water demand, supply, and allocation in ESM frameworks—they conclude that current models are limited in representing these processes, and that there is tremendous opportunity to improve models for understanding the role that water management plays in impacting earth system interactions.

3.4. Summary: Opportunities to Improve Representation of Hydrologic Processes in Land Models

The previous sections illustrate that the historical development of ESM land models can benefit from the advances in hydrologic research in the past decades. This is possible by improving the representation of key processes (e.g., groundwater dynamics), improving model representations of key aspects of spatial variability (e.g., bedrock depth, hydraulic geometry), improving model representations of the dominant features of the lateral flow of water above and below ground (e.g., infiltration of surface runoff, flow through macropores, river-aquifer interactions, and downstream controls on the flow of water through the river network), and improving model representations of the topographic controls on subgrid-scale heterogeneities in soil moisture and evapotranspiration fluxes.

To define a path forward, Table 3 summarizes key opportunities to improve the representation of hydrologic processes in land models. Active work on these topics is already underway in many modeling groups, and recent results prove that advances in the representation of hydrologic processes substantially improve the fidelity of simulations of land-atmosphere fluxes and biogeochemistry [e.g., Miguez-Macho and Fan, 2012a, 2012b; Pappenberger *et al.*, 2012; Milly *et al.*, 2014; Subin *et al.*, 2014; Swenson and Lawrence, 2014]. Table 3 and the discussion in this section define what needs to be done—the next section outlines some strategic research tasks and considerations on how to improve hydrologic processes in ESMs.

4. Hydrologic Benchmarking Activities to Accelerate Modeling Advances

The opportunities to improve land models listed in Table 3 are gleaned from a diverse set of model development activities, making it difficult to understand the relative merits of competing modeling alternatives.

Model intercomparison projects have typically not yielded specific insight into the causes of differences in output across models because the extensive structural differences among the models make it difficult to attribute inter-model differences to specific modeling decisions [Koster and Milly, 1997; Nijssen et al., 2003; Clark et al., 2011]. There is therefore a strong need for a systematic and controlled approach to model evaluation in order to both identify preferable modeling alternatives and understand model weaknesses and model development needs.

In our opinion, improving the representation of hydrologic processes in land models demands comprehensive hydrologic benchmarking activities in order to systematically evaluate competing modeling alternatives. This requires four main elements: (1) synthetic test problems; (2) process-based model evaluation, making extensive use of multivariate and multiscale data from research basins; (3) evaluating the interplay between predictive accuracy, computational efficiency, and transferability; and (4) understanding the information content in data and models, in order to improve how land models use the data that are available to them. We will discuss each of these elements in the following sections, building on the existing literature on benchmarking of hydrologic and land models [Abramowitz et al., 2008; Gupta et al., 2008; Blyth et al., 2011; Clark et al., 2011; Abramowitz, 2012; Gupta et al., 2012; Luo et al., 2012; Maxwell et al., 2014; Nearing and Gupta, 2014].

4.1. Synthetic Test Problems

Synthetic test cases are used to evaluate the implementation of the model equations, including impacts of the numerical approximations. For example, synthetic test problems have been used to evaluate different numerical solutions of Richards' equation [Celia et al., 1990; Boone and Wetzel, 1996; Tocci et al., 1997; Lee and Abriola, 1999; Vanderborght et al., 2005; Miller et al., 2006], different approaches to represent cyrosuction processes during soil freezing [Hansson et al., 2004; Noh et al., 2011; Painter, 2011], different approaches to simulate lateral subsurface flow [Wigmosta and Lettenmaier, 1999; Rupp and Selker, 2005, 2006; Bogaart et al., 2013; Troch et al., 2013], and different numerical approximations of overland flow [Parlange et al., 1981; Govindaraju et al., 1990; Mizumura, 2006; Mizumura and Ito, 2010, 2011]. Such synthetic test problems are not widely used in the land surface modeling community—yet there is a need to incorporate these synthetic test problems in model test suites in order to provide a rudimentary test of the model implementation and continually check if changes to the model corrupt the most basic model capabilities.

The synthetic test problems described above primarily focus on individual processes (e.g., infiltration into initially dry soil [Celia et al., 1990]), and there is a need to augment the simple synthetic test cases with numerical experiments that evaluate interlinked physical processes. This was recently done by Maxwell et al. [2014], who used five test problems to evaluate the differences among seven integrated hydrologic models. The test problems included (1) infiltration-excess runoff for an inclined hillslope (saturated hydraulic conductivity less than the rainfall rate); (2) saturation-excess runoff for an inclined hillslope (saturated hydraulic conductivity greater than the rainfall rate); (3) surface runoff over a tilted V-shaped catchment; (4) runoff generation on a heterogeneous 1-D slab; and (5) return flow for an inclined hillslope. The results of this experiment showed strong inter-model agreement, most pronounced for the first three test problems, with inter-model differences attributed to differences in the numerical approximation [Maxwell et al., 2014]. It will be important to include these “more advanced” test problems in land surface model test suites as the representation of hydrologic processes in land models continues to improve.

4.2. Process-Based Model Evaluation

The synthetic test problems described in section 4.1 are useful to evaluate the implementation of the model equations, but do not provide much insight on the more pressing need to evaluate the capability of different modeling approaches in real catchments. Synthetic test problems only provide the first (and the most basic) test of the model implementation. A systematic multivariate and multiscale evaluation of hydrologic modeling advances, making extensive use of data from research basins, is necessary to improve model representation of dominant processes [Gupta et al., 2008; Clark et al., 2011].

The process-based approach to evaluation has two related elements. First, it is important to minimize the number of differences between alternative model configurations so that it is possible to attribute differences in model behavior to individual modeling decisions. For example, in addition to comparing different channel routing models, it is important to evaluate the approximations/simplifications within a routing

model. This can be accomplished using the so-called “multiple hypothesis” approach to model evaluation [Clark *et al.*, 2011; Beven, 2012], through experimenting with different physics options, spatial configurations, and model parameter values, all within the same land surface model framework [Best *et al.*, 2011; Niu *et al.*, 2011; Clark *et al.*, 2015a, 2015b]. The second element of process-based model evaluation is to pull together multivariate and multiscale observations to diagnose specific reasons for model inadequacies and guide future model development efforts [Gupta *et al.*, 2008]. Multivariate and multiscale diagnostic metrics of model behavior should provide insight into both the individual processes within a model as well as how interlinked processes combine to produce the system-scale response at larger spatial scales [Clark *et al.*, 2011; Luo *et al.*, 2012]. For example, analysis of recession behavior can provide more information on model weaknesses than analysis of summary metrics of model performance such as the Nash-Sutcliffe score [Yilmaz *et al.*, 2008; Clark *et al.*, 2009]. Essentially, models need to reproduce both realistic temporal hydrologic behavior (i.e., high frequency and low frequency) and realistic spatial patterns of variability across a hierarchy of scales. As such, the process-based approach to model evaluation involves decomposing land models into a set of testable components (constituent hypotheses), and using multivariate and multiscale data to systematically evaluate individual model hypotheses and their interactions.

There are two main challenges in process-based evaluation of hydrologic modeling advances. The first challenge is a practical one: since land models must simulate processes in a myriad of different environments throughout the globe, there is a need to pull together the multivariate and multiscale data from a wide range of hydroclimatic regimes [Blyth *et al.*, 2011]. The research data must be compiled in a consistent format, be serially complete (at least for the model forcing data), and include estimates of the uncertainty and spatial representativeness of individual observations [Abramowitz, 2012]. Many of the emerging data papers from research basins cover these issues to varying degrees [e.g., Reba *et al.*, 2011; Landry *et al.*, 2014], but there is much more work to be done to pull together research data from a wide range of watersheds.

The second challenge is to devise meaningful ways to use research data for model evaluation, accounting for problems of data uncertainty and the incommensurability of models and measurements [Beven, 1993; Kuczera and Mroczkowski, 1998; Beven, 2001; Freer *et al.*, 2004; Beven, 2007; Kuczera *et al.*, 2010], and making use of qualitative insights from experimentalists to constrain model behavior [Seibert and McDonnell, 2002]. A key modeling problem is representing how interlinked physical processes affect the aggregate system-scale responses at larger spatial scales [Beven and Cloke, 2012; Wood *et al.*, 2012], and thus a key focal area for model evaluation is understanding the merits of different methods to represent spatial variability and hydrologic connectivity. Focus on these scaling issues will help identify the modeling approaches that can reliably represent the impacts of subgrid-scale heterogeneities on grid-average fluxes (see section 3.2). In a general sense, this second challenge can be addressed by pursuing the systematic and controlled approach to model evaluation detailed earlier [Clark *et al.*, 2011, 2015a, 2015b]; however, the specific details on defining meaningful diagnostic signatures, the extent to which it is possible to isolate individual modeling decisions, and designing/implementing methods to characterize model and data uncertainty, are all important issues that require substantial effort and debate [Beven *et al.*, 2012; Clark *et al.*, 2012].

The challenge of multivariate and multiscale model evaluation will require a substantial amount of determination. Concerted effort on model evaluation, especially systemizing the model evaluation approach, will help improve the representation of hydrologic processes in land models, will help understand differences in performance across models and across model versions, and enable assessment of how improved hydrologic process representation affects other aspects of the land model system.

4.3. Interplay Between Predictive Accuracy, Computational Efficiency, and Data Availability

A key issue to consider as part of model evaluation is the trade-off between predictive accuracy (or model fidelity) and computational efficiency. This is of critical importance as land models begin to include a bewilderingly large set of processes [Lawrence *et al.*, 2011]. For example, there is currently limited understanding of the cost-benefit trade-off of moving from single-layer canopy models to multilayer canopy models [Bonan *et al.*, 2014], the shift from noniterative to iterative solutions of Richards' equation [Zeng and Decker, 2009; De Rooij, 2010; Zeng and Decker, 2010] and the importance of kinematic versus diffusive models to simulate lateral subsurface flow [Beven and Freer, 2001; Paniconi *et al.*, 2003; Troch *et al.*, 2003]. The lack of understanding of accuracy-efficiency trade-offs is especially acute in the land modeling community, as

there is very little published work on how different numerical approximations of hydrologic processes affect the representation of land-atmosphere fluxes.

Another major issue is the tension between global applicability and data availability. For any parameterization to be implemented in an ESM, it has to be applicable globally (e.g., for all climate regimes, for all land cover types). For instance, while insights can be gained from detailed studies over specific river basins, a substantial amount of additional work is needed to extend such insights to all river basins (e.g., from tropical to polar river basins). To this end, effort is required to estimate important geophysical attributes on the global scale (e.g., soil information, bedrock depth, hydraulic geometry) [Tesfa *et al.*, 2009; Chaney *et al.*, 2014; Fan *et al.*, 2015; Allen and Pavelsky, 2015], and use the available geophysical information to estimate spatially variable model parameters [Samaniego *et al.*, 2010]. The broad applicability of modeling advances also requires a synthesis across catchment-scale observatories, to pull out processes and interactions that are common in a wide range of climatic-hydrologic-ecosystem regimes [McDonnell *et al.*, 2007; Wagener *et al.*, 2007]. As such, model benchmarking requires understanding the interplay between predictive accuracy, computational efficiency, and the availability of data to support competing modeling approaches.

4.4. Understanding the Information Content in Data and Models

Building on the synthetic test cases and process-based model evaluation, there is a need to advance the “science” of benchmarking through improving understanding of the information content in data and models. This issue relates to our expectations of model performance. Specifically, we ask the following related questions: how do we define a “good” model, and can we define meaningful benchmarks to evaluate the extent to which the model contains useful information [Kirchner *et al.*, 1996; Schaeffli and Gupta, 2007; Abramowitz *et al.*, 2008; Blyth *et al.*, 2011; Gupta *et al.*, 2012; Nearing and Gupta, 2014].

The benchmarking problem involves comparing a proposed model to a baseline alternative (i.e., the null hypothesis), and evaluating if the proposed model adds information [Nearing and Gupta, 2014]. For example, Abramowitz *et al.* [2008] compare the performance of land models to statistical models based on empirical relationships between model forcing data and model fluxes, effectively comparing the information in the land surface model to the information content in the model forcing data. This study actually showed that the statistical models consistently outperformed the state-of-the-art land models, suggesting that land models underutilize the information in the meteorological forcing data [Abramowitz *et al.*, 2008].

The value of these formal benchmarks is that they force us to take a step back from the traditional model development activities and ask, “What went wrong?” Or, more specifically, to ask why the complex models cannot make better use of the information that is available to them. One potential explanation is that the models have very strong a priori constraints—these constraints are evident in the choice of model parameter values, the choice of process parameterizations, the choice of spatial configurations, and the choice of the numerical schemes [Mendoza *et al.*, 2015]. Addressing these issues requires careful and systematic scrutiny of the model representation of physical processes [Gupta *et al.*, 2008; Clark *et al.*, 2011], along with dialog between modelers and observationalists [Seibert and McDonnell, 2002], to improve the fidelity of model simulations.

5. Concluding Remarks

As *Water Resources Research* reaches its half century milestone, we look back on the immense accumulation of knowledge by the hydrologic sciences community through decades of observations and synthesis, and as we look forward in anticipation of global-scale environmental change with great uncertainties, we ask ourselves: what are the major gaps in our understanding of large-scale fluxes of water, energy, and biogeochemical cycles, and how can we contribute this knowledge toward advancing Earth System Models (ESMs), that are arguably the only quantitative tools available to foresee possible futures?

In this contribution to the *Water Resources Research* 50 year special issue, we take the opportunity to reflect on these questions. Through examples of hydrologic stores and fluxes, we contrast how hydrologists

understand them and represent them in catchment-scale models versus how they are currently described in the large-scale land models in ESMs. This paper is not meant to be a comprehensive review of all aspects of terrestrial hydrology, but, rather, to identify opportunities to bridge between the catchment-scale focus in the hydrologic sciences and the global-scale focus in ESMs, and to propose some of the many paths forward that can be taken to incorporate the well-understood and large-scale hydrologic processes into the next generation of ESMs.

The examples presented in this paper point to the following general perspectives:

1. ESM land model development can benefit from recent advances in hydrology, both through incorporating key processes (e.g., groundwater-surface interactions) and new approaches to describe multiscale spatial variability and hydrologic connectivity;
2. Accelerating modeling advances requires comprehensive hydrologic benchmarking activities, in order to systematically evaluate competing modeling alternatives, understand model weaknesses, and prioritize model development needs; and
3. A stronger collaboration is needed between the hydrology and ESM modeling community, both through greater engagement of hydrologists in ESM land model development, and through rigorous evaluation of ESM hydrology performance in research watersheds or Critical Zone Observatories. Such coordinated efforts in advancing hydrology in ESMs have the potential to substantially impact energy, carbon, and nutrient cycle prediction capabilities through the fundamental role that hydrologic processes play in regulating these cycles.

We hope that the examples in this paper will motivate a series of detailed synthesis activities in the near future among the hydrologic and ESM communities, in order to create a comprehensive road map that will help accelerate advances in the representation of hydrologic processes in land models.

We conclude with a highly relevant and prescient quotation from a seminal paper by Peter Eagleson published in *Water Resources Research* in 1986 entitled "The emergence of global-scale hydrology" [Eagleson, 1986]:

Emerging problems of environmental change and of long range hydrologic forecasting demand knowledge of the hydrologic cycle at global rather than catchment scale. Changes in atmosphere and/or landscape characteristics modify the earth's metabolism through changes in its biogeochemical cycles. The most basic of these is the water cycle which directly affects the global circulation of both atmosphere and ocean and hence is instrumental in shaping weather and climate. Defining the spatial extent of the environmental impact of a local land surface change, or identifying, for forecasting purposes, the location and nature of climatic anomalies that may be causally linked to local hydrologic persistencies requires global scale dynamic modeling of the coupled ocean-atmosphere-landsurface. Development, evaluation, verification, and use of these models requires the active participation of hydrologists along with a wide range of other earth scientists [Eagleson, 1978, page 6S]. . . He who controls the future of global-scale models controls the direction of hydrology [Eagleson, 1986, page 13S].

Appendix A: Process Representations in Land Models

A1. Storage and Transmission Through Soils

Improving simulations of the storage and transmission of water through soils is critical in order to improve the representation of the soil moisture-climate/weather feedbacks. While there are many facets to land-atmosphere interaction mechanisms, the basic framework is that soil moisture affects the partitioning of surface net radiation into sensible and latent heat flux (evaporative fraction), which consequently affects surface temperature, boundary layer properties, cloud formation, and in some cases the initiation of convection leading to precipitation [Douville, 2004; Dirmeyer et al., 2006; Koster et al., 2006, 2011; Huang and Margulis, 2013].

As documented in Table 2, most models use one-dimensional Richards' equation to simulate the time evolution of volumetric liquid water content [Chen and Dudhia, 2001; de Rosnay et al., 2002; Milly et al., 2014; Clark et al., 2015b]

$$\frac{\partial \theta}{\partial t} = -\frac{\partial q}{\partial z} + S_{et} + S_{lf} \quad (A1)$$

where θ is the volumetric liquid water content, q is the vertical flux of liquid water (m s^{-1}), and S_{et} is the sink term for evapotranspiration (root water uptake) and S_{lf} is the source-sink term for the lateral flux of liquid water (s^{-1}). Note that in many models, $S_{lf}=0$. The vertical flux of liquid water q is formulated as a function of volumetric liquid water content (i.e., leading to the moisture-based form of Richards' equation)

$$q(z) = -K \frac{d\psi}{d\theta} \frac{\partial \theta}{\partial z} + K \quad (A2)$$

where $K=f(\theta)$ is the hydraulic conductivity (m s^{-1}) and $\psi=f(\theta)$ is the liquid water matric potential (m). The boundary conditions for equation (A1) are the fluxes at the soil surface (i.e., the infiltration of water into the soil profile, see section A1.1) and the fluxes at the bottom of the soil profile (section A1.2).

Ignoring differences in boundary conditions for the time being (see sections A1.1 and A1.2), the inter-model differences in Table 2 relate primarily to the details of the numerical implementation. The land models reviewed here use either the soil hydraulic functions of *Clapp and Hornberger* [1978] or *van Genuchten* [1980] for K and ψ (Table 2). Moreover, the different models use different numerical approximations in terms of the number of soil layers [*de Rosnay et al.*, 2000], the splitting methods used to separate the diffusive and gravity terms in Richards' equation [*Kowalczyk et al.*, 2006], the methods used to estimate diagnostic variables at layer interfaces [*Boone and Wetzel*, 1996; *Campoy et al.*, 2013], the choice of noniterative and iterative solution method [*Chen and Dudhia*, 2001; *Takata et al.*, 2003], and the ad hoc numerical fixes necessary in the moisture-based form of Richards' equation to account for supersaturated soil layers [*Boone and Wetzel*, 1996; *Chen and Dudhia*, 2001; *Yeh and Eltahir*, 2005a; *Best et al.*, 2011]. Other inter-model differences relate to the representation of soil freezing processes, especially the representation of supercooled liquid water and the migration of liquid water toward the freezing front [*Luo et al.*, 2003; *Niu and Yang*, 2006; *Swenson et al.*, 2012]. The outlier models in Table 2 are the Catchment model which uses an empirical approximation to Richards' equation to calculate the time evolution of bulk root zone soil moisture [*Koster et al.*, 2000; *Ducharne et al.*, 2000], and CLM which subtracts the hydrostatic equilibrium soil moisture distribution from the vertical soil moisture profile before solving Richards' equation [*Zeng and Decker*, 2009; *De Rooij*, 2010; *Zeng and Decker*, 2010].

All of these land models, however, treat the storage and transmission of soil water significantly differently than many of the physically motivated models used in the hydrologic modeling communities, which include a more comprehensive set of processes including lateral flow, interflow, lowland depression storage, and exchange with groundwater. Moving forward, there is an opportunity to improve representation of storage and transmission of soil water in land models, while maintaining computational efficiency in mind, by (1) explicitly representing variably saturated flow, as is possible in the mixed form of Richards' equation [*Celia et al.*, 1990; *Maxwell and Miller*, 2005; *Kumar et al.*, 2009], to improve simulations of shallow groundwater dynamics; (2) explicitly represent airflow (vapor diffusion) through the soil to improve simulations of bare soil evaporation [*Parker et al.*, 1987; *Painter*, 2011; *Zeng et al.*, 2011; *Smits et al.*, 2012]; and (3) explicitly represent macropore flow to simulate the nonuniform wetting of the soil matrix and the heterogeneity of flow paths at larger spatial scales [*Beven and Germann*, 1981, 1982; *SimunEk et al.*, 2003; *Weiler*, 2005; *McDonnell et al.*, 2007; *Maxwell and Kollet*, 2008a; *Nimmo*, 2010; *Yu et al.*, 2014]. Some integrated models have incorporated these processes—for example, the coupling of ParFlow and CLM represents three-dimensional variably saturated flow and has now been applied at continental scales [*Maxwell et al.*, 2015], CLM now parameterizes the diffusion of water vapor through a dry surface layer to improve simulations of bare soil evaporation [*Swenson and Lawrence*, 2014], and the LM3 model has a simple representation of macropores [*Milly et al.*, 2014].

A1.1. Infiltration and Surface Runoff

The upper boundary condition in equation (A1), i.e., the surface infiltration, is given as

$$q(z=0) = P_x - e_s - q_s \quad (A3)$$

where P_x is the flux of water incident at the soil surface ($\text{kg m}^{-2} \text{s}^{-1}$), including throughfall and canopy drip when the soil surface is free of snow and drainage from the bottom of the snowpack when snow

is present, e_s is the bare soil evaporation ($\text{kg m}^2 \text{s}^{-1}$), and q_s is the surface runoff ($\text{kg m}^2 \text{s}^{-1}$). Here we ignore canopy processes, snow processes, and evaporation processes (all of which are important), and focus on the differences in surface infiltration caused by differences in the parameterizations of surface runoff.

In contrast to their similarities in storage/transmission of water in soils, current land models include substantially different representations of surface runoff (Table 2) and therefore infiltration. Three main approaches are used:

$$q_s = 0 \tag{A4}$$

$$q_s = P_x F_{sat} + (1 - F_{sat}) \max(0, P_x - i_{max}) \tag{A5}$$

$$q_s = \frac{P_x^2}{P_x + I_c} \tag{A6}$$

where i_{max} is the maximum infiltration rate ($\text{kg m}^2 \text{s}^{-1}$), typically parameterized as a function of volumetric liquid water content or liquid water matric potential in the upper soil layer(s), F_{sat} is the saturated fraction of the catchment, and I_c is the infiltration capacity ($\text{kg m}^2 \text{s}^{-1}$), parameterized as a function of the soil moisture deficit and the saturated hydraulic conductivity (see *Schaake et al.* [1996] and *Chen and Dudhia* [2001] for specific details on the parameterization of I_c). Specific details are as follows:

1. The first approach of $q_s = 0$ is used in only a small number of models, including CABLE [*Wang et al.*, 2011] and LM3 [*Milly et al.*, 2014]. In LM3, the flux at the upper boundary is initially computed as $q(z=0) = P_x - e_s$, with surface runoff computed if the solution to equation (A1) yields positive matric head (meaning that the infiltration capacity of the soil exceeded). However, the would-be surface runoff enters the soil if macropores are present and pore space is available, meaning $q_s = 0$ in many situations.
2. The second approach, defined in equation (A5), combines saturation-excess runoff and infiltration-excess runoff. This approach is used in most land models (Table 2), though in some models the infiltration-excess runoff—the second term in equation (A5)—is set to zero [e.g., *Liang et al.*, 1994; *Verant et al.*, 2004].
 - a. Saturation-excess runoff depends on the parameterization of saturated fraction F_{sat} , where (i) F_{sat} is parameterized as a step function of soil moisture, with $F_{sat} = 1$ when the upper-most layer reaches capacity—this is the approach used in ORCHIDEE [*Verant et al.*, 2004]; (ii) F_{sat} is parameterized as a power law function of soil moisture, as used in VIC [*Liang et al.*, 1994], TESSEL [*Balsamo et al.*, 2009] and JULES [*Best et al.*, 2011]; and (iii) F_{sat} is parameterized as a function of the depth to the water table, as used in the Catchment model [*Koster et al.*, 2000], MATSIRO [*Takata et al.*, 2003], CLM [*Niu et al.*, 2007], and JULES [*Best et al.*, 2011]. Note that JULES has two options for saturation-excess runoff. The parameterization of the saturated fraction has a large impact on runoff dynamics—surface runoff can respond more rapidly to variations in soil moisture than to variations in water table depth, and associated differences in surface infiltration can affect base flow [*Boone et al.*, 2004; *Clark and Gedney*, 2008; *Clark et al.*, 2008].
 - b. Infiltration excess depends on the parameterization of the maximum infiltration rate i_{max} . In models where i_{max} is defined as the saturated hydraulic conductivity of the upper-most soil layer [e.g., *Takata et al.*, 2003] lead to the situation where i_{max} is typically much greater than P_x , meaning that infiltration-excess runoff is rather rare [*Balsamo et al.*, 2009].
3. The third approach, defined in equation (A6), is only used in the Noah model [*Ek et al.*, 2003], equation (A6) was formulated by *Schaake et al.* [1996] to represent the spatial variability in precipitation and infiltration capacity.

The similarity among models is their simplistic representation of the heterogeneity of flow paths. Runoff in most models is represented simply as the sum of surface runoff and base flow. Most models do not represent exfiltration, which is important to simulate return flow and wetland dynamics, and no allowance is made for the re-infiltration of surface runoff. Such simplifications can affect even the most basic hydrologic function such as the partitioning of precipitation among evapotranspiration and runoff.

A key issue here is identifying reliable methods to represent the impact of small-scale heterogeneity on the large-scale fluxes of infiltration and surface runoff, considering the merits of different modeling approaches

to represent heterogeneity and scaling behavior (section 3.2) and the interplay between predictive accuracy, computational efficiency, and data availability (section 4.3). The approaches typically used in land models parameterize the impacts of subgrid-scale heterogeneities on the grid-average infiltration flux (Table 2), considering the aggregate impacts of subgrid variability in soil moisture [Moore and Clarke, 1981; Wood et al., 1992; Clark and Gedney, 2008; Balsamo et al., 2009], or the aggregate impacts of subgrid variability in water table depth [Beven and Kirkby, 1979; Gedney and Cox, 2003; Niu et al., 2005]. This is typically known as the top-down modeling approach [Klemes, 1983; Dooge, 1986]. By contrast, large-scale infiltration in physically based hydrologic models is represented as the spatial average across a high-resolution spatial mesh [VanderKwaak and Loague, 2001; Downer and Ogden, 2004; Kollet and Maxwell, 2006; Qu and Duffy, 2007; Kumar et al., 2009; Therrien et al., 2010]. This approach is typically known as the bottom-up approach to hydrologic modeling, and is elegantly presented in a blueprint for distributed hydrologic modeling by Freeze and Harlan [1969]. The physically based models generally include adherence to continuity in flux and head, which allows the possibility of flow in either direction (i.e., infiltration and exfiltration). Physically based models also implement a more detailed representation of wetting front dynamics [e.g., Garrote and Bras, 1995; Ivanov et al., 2004], which may improve simulations of infiltration and surface runoff during heavy rainfall. The best path forward is not immediately apparent—for example, Maxwell and Kollet [2008a] illustrate some of the difficulties of applying the top-down approach to estimate the large-scale infiltration flux. There is clearly an opportunity to use the physically based methods to explicitly simulate exfiltration, overland flow, and re-infiltration of surface runoff, though in the foreseeable future it may be necessary to parameterize some of these processes in order to maintain computational efficiency and tractability. We discuss these issues in the benchmarking discussion (section 4).

A1.2. The Bottom Boundary Condition for Soil Hydrology

The bottom boundary condition in equation (A1) is given as

$$q(z=z_u) = \begin{cases} c_d K_i & \text{flux boundary condition} \\ -K_{sat} \frac{-\psi(\theta_i)}{z_u - z_i} + K_{sat} & \text{head boundary condition} \end{cases} \quad (A7)$$

where z_u is the depth of the unsaturated zone (m), which is the depth of the water table for the head boundary condition, z_i is the depth of the lowest soil layer (m), K_i is the hydraulic conductivity of the lowest soil layer (m s^{-1}), K_{sat} is the saturated hydraulic conductivity (m s^{-1}), θ_i is the volumetric liquid water content of the lowest soil layer, and c_d is a parameter that controls the rate of flow at the lower boundary.

The key differences in the lower boundary condition are as follows:

1. The flux boundary condition is used in most land models (Table 2), but with important differences in the specification of the c_d parameter. The different approaches include (a) a zero-flux lower boundary, i.e., $c_d=0$, used in LM3 [Milly et al., 2014]; (b) a free drainage lower boundary, i.e., $c_d=1$, used in VIC [Liang et al., 1996], CLM [Oleson et al., 2010], ORCHIDEE [Campoy et al., 2013], and TESSEL [ECMWF, 2014]; and (c) restricted vertical drainage, i.e., $c_d < 1$ as used in the Noah model [Ek et al., 2003] and CABLE [Wang et al., 2011].
2. The head boundary condition, i.e., moving lower boundary defined by the depth of the water table, is now used in LEAF [Miguez-Macho et al., 2007] and MATSIRO [Koirala et al., 2014]. This is an effective way of separating the “unsaturated” zone from the “saturated” zone. However, the flux parameterization in equation (A2), i.e., the moisture-based form of Richards’ equation, as used in LEAF and MATSIRO, can only simulate unsaturated flow and this separation of the saturated and unsaturated zones complicates representing shallow groundwater dynamics such as perched water tables. A variant of this boundary condition, used in PAWS+CLM [Shen and Phanikumar, 2010; Shen et al., 2013], is a noniterative coupling scheme between saturated groundwater flow and the unsaturated zone. With this method, the water table simulated by the saturated zone is consistent with the soil moisture profile. This class of methods can dynamically describe return flow, regional groundwater circulation, groundwater discharge, and saturation excess runoff [see also Camporese et al., 2009; Camporese et al., 2010].

The choice of the bottom boundary condition, along with the depth of the unsaturated zone, can have a large impact on the vertical soil moisture profile and land-atmosphere fluxes [e.g., Zeng and Decker, 2009; Gochis et al., 2010; Campoy et al., 2013]. The free drainage lower boundary condition that is still used in many models assumes spatially uniform soil depth [Ek et al., 2003] and “no bedrock anywhere” [ECMWF, 2014]. These representations do not consider the upward capillary flow or the vertical fluxes arising from

negative potentiometric gradient due to evapotranspiration-induced dryness in the vadose zone. The free drainage lower boundary condition hence effectively neglects the interactions between surface water and groundwater that can be key drivers of land-atmosphere fluxes.

Improvements in land model simulations of soil moisture dynamics are possible through improving simulations of groundwater dynamics (see section A3), which involves more sophisticated representation of the flux at the bottom of the vadose zone. This will require spatially variable datasets of bedrock depth [Tesfa *et al.*, 2009] as well as datasets of permeability and deeper sediments below the depth covered by soil data [Fan *et al.*, 2015].

A2. Root Water Uptake

Root water uptake, represented by the evapotranspiration sink term S_{et} in equation (A1), often represents a large flux of water from the subsurface, and as such has long been recognized as an important term in hydrologic models [e.g., Feddes *et al.*, 1974]. Substantial evidence has accumulated that roots can be adaptive and dynamic [e.g., Harper *et al.*, 1991] and that roots can be shaped by local variations in soil water, oxygen, and nutrient status [e.g., Hodge, 2004]. Additionally, the presence of a shallow groundwater may profoundly influence root structure and dynamics, the latter in turn shaping land hydrology and regulating water, energy, and biogeochemical pools and fluxes [Norby and Jackson, 2000]. This new body of knowledge is directly relevant to understanding ecosystem response-feedback to a rapidly changing global environment, and to improving global model capabilities to predict the possible trajectories of the coevolution of the ecosystems and the physical world [Fan, 2015].

As documented in Table 2, root water uptake is represented in most land models using a macroscopic approach described by Feddes *et al.* [2001]. In this approach, the root water uptake for a given soil layer j is given as

$$S_{et,j} = \frac{f_{roots,j} \beta_{v,j}}{\bar{\beta}_v} \frac{Q_{trans}^{veg}}{L_{vap} \rho_{liq} \Delta z_j} \quad (A8)$$

where Q_{trans}^{veg} ($W m^{-2}$) is the transpiration latent-heat flux, $\beta_{v,j}$ is the soil water stress factor for the j th soil layer, $\bar{\beta}_v$ is the total water availability stress factor, $f_{roots,j}$ is the fraction of roots in the j th soil layer, Δz_j is the depth of the j th soil layer (m), and L_{vap} ($J kg^{-1}$) and ρ_{liq} ($kg m^{-3}$) are, respectively, the latent heat of vaporization and the intrinsic density of liquid water. The soil water stress factor in equation (A8) is typically parameterized as a function of volumetric liquid water content [e.g., de Rosnay *et al.*, 2002; Best *et al.*, 2011; Wang *et al.*, 2011]

$$\beta_{v,j} = \frac{\theta_j - \theta_{wlt}}{\theta_{crit} - \theta_{wlt}} \quad \text{for } \theta_{wlt} < \theta_j < \theta_{crit} \quad (A9)$$

where θ_{crit} and θ_{wlt} define respectively the soil moisture content when plants become stressed and the residual soil moisture content (note $\beta_{v,j}=0$ for $\theta_j < \theta_{wlt}$ and $\beta_{v,j}=1$ for $\theta_j > \theta_{crit}$). The total water availability stress factor is

$$\bar{\beta}_v = \sum_j f_{roots,j} \beta_{v,j} \quad (A10)$$

which is used in the parameterizations of stomatal conductance. An important point here is that equation (A8) does not account for the hydraulic gradients between soil and roots.

The vertical root distribution is typically parameterized as a simple time-invariant (but spatially variable) function [de Rosnay and Polcher, 1998]

$$R(z) = e^{-cz} \quad (A11)$$

where $R(z)$ defines the fraction of roots below depth z and the parameter c is fit for different vegetation types. Jackson *et al.* [1996] compile a database of 250 different root studies to estimate the vertical root distribution for 11 biomes, and these vertical root distributions have been used to estimate rooting parameters for vegetation classes that are commonly used in land models [Zeng *et al.*, 1998; Zeng, 2001]. Variants of equation (A11) are used in CABLE [Wang *et al.*, 2011], CLM [Oleson *et al.*, 2010], TESSEL [ECMWF, 2014], and ORCHIDEE [d'Orgeval *et al.*, 2008].

The typical land model approach to simulate root water uptake as described here has several limitations. First, parameterizing the soil stress function based only on soil moisture does not represent the hydraulic gradient

between soils and plants, which is a critical driver of evapotranspiration. Other modeling approaches explicitly simulate the hydraulic gradient throughout the soil-plant-atmosphere continuum [Baldocchi and Meyers, 1998; Williams *et al.*, 2001; Manoli *et al.*, 2014] and these approaches have recently been shown to provide substantial benefits in land models [Hickler *et al.*, 2006; Bonan *et al.*, 2014]. A limitation of this approach to date is that it is based on setting a minimum canopy xylem pressure, and so it can underpredict drought responses when scaling up to larger areas [Powell *et al.*, 2013]. An alternative is to model the soil-plant hydraulic continuum using both the hydraulic properties of soil and cavitation in plant xylem represented with s-shaped curves representing the distinct changes in root, stem, and leaf hydraulic conductances with declining xylem pressure [Sperry *et al.*, 1998]. This approach has been used to extend the TREES model [Mackay *et al.*, 2003] to accurately predict root water uptake in response to drought [McDowell *et al.*, 2013].

A second limitation is that the root profiles in the current generation of land models are time-invariant, which contrasts with the natural system where roots respond dynamically to changes in available energy and water [Schenk and Jackson, 2002]. Based on recent developments, there is an opportunity here to implement dynamic root growth models in land models, e.g., based on optimality principles [Schymanski *et al.*, 2008]. Such models can utilize optimal rooting strategies following directly from soil-rhizosphere-plant hydraulic theory, which show that deeper roots are important for survival during drought [Lai and Katul, 2000], the coevolution of root to leaf area ratios ensure sufficient, yet not inefficient, water uptake by roots [Ewers *et al.*, 2000; Sperry *et al.*, 2002; Zea-Cabrera *et al.*, 2006], and competition for water among roots of cooccurring plants [Domec *et al.*, 2012; Quijano *et al.*, 2012] to more directly link biophysical and hydrologic processes and improve simulations of root water uptake and evapotranspiration. Indeed, evidence of coordination between plant hydraulic traits on a global scale [Manzoni *et al.*, 2013] should enable constraining future root water uptake models for use in land surface models.

A3. Groundwater Dynamics

There is increasing evidence that groundwater dynamics have an important impact on weather and climate [Maxwell and Kollet, 2008b]. A compilation of water table depth observations suggests that the groundwater is sufficiently shallow to influence the root-zone soil water over notable portions of the land area [Fan *et al.*, 2013], and a data-model synthesis of groundwater-surface interactions in the Amazon suggests that groundwater plays an important role in regulating surface fluxes [Miguez-Macho and Fan, 2012a,b], and these processes may be underrepresented in most current land models

To date, five main approaches have been used to simulate groundwater dynamics:

1. No explicit representation of groundwater dynamics, as in the Noah model [Ek *et al.*, 2003], CABLE [Wang *et al.*, 2011], ORCHIDEE [Koirala *et al.*, 2014], and TESSEL [ECMWF, 2014]. In this approach, runoff is simply the sum of surface runoff and drainage from the bottom of the soil profile [Boone *et al.*, 2004].
2. A base flow bucket below the soil profile, as used in VIC [Liang *et al.*, 1996]. In this approach, drainage from the soil profile flows into a “conceptual bucket” and nonlinear storage-discharge relationships are used to calculate base flow. There is no upward (capillary) flow from the bucket to the soil profile, hence the “saturated” storage has no impact on soil moisture dynamics. Similar approaches are used in the Total Runoff Integrating Pathways (TRIP) model [Alkama *et al.*, 2010; Decharme *et al.*, 2010; Decharme *et al.*, 2012]. However, VIC-GW [Liang *et al.*, 2003; Leung *et al.*, 2011] allows for two-way soil-water table interactions in the vertical direction.
3. Application of general TOPMODEL concepts, where base flow from the soil profile is parameterized based on a statistical distribution of water table depth, as used in the Catchment model [Koster *et al.*, 2000], JULES [Gedney and Cox, 2003; Best *et al.*, 2011], MATSIRO [Yeh and Eltahir, 2005a,b; Koirala *et al.*, 2014], and CLM [Niu *et al.*, 2007; Oleson *et al.*, 2010]. This is accomplished either by using a source-sink term in Richards’ equation, i.e., the S_{ff} term in equation (A1) [Gedney and Cox, 2003; Niu *et al.*, 2007], or by representing the water table as a moving lower boundary condition for the soil profile [Koster *et al.*, 2000; Yeh and Eltahir, 2005a,b; Koirala *et al.*, 2014].
4. The grid-to-grid (or column-to-column) lateral flux computed using Darcy’s Law, as used in LEAF [Miguez-Macho *et al.*, 2007; Fan and Miguez-Macho, 2011] and LM3 [Milly *et al.*, 2014; Subin *et al.*, 2014].
5. Coupling a complete integrated hydrology model with the biophysical components of a land model [Maxwell and Miller, 2005; Maxwell *et al.*, 2011; Shi *et al.*, 2013].

As noted above the *raison d'être* of land models is to provide the lower boundary condition for the atmosphere, so the interest here is the extent to which the different model implementations of groundwater affect soil moisture dynamics and land-atmosphere fluxes [Maxwell *et al.*, 2007; Maxwell and Kollet, 2008b]. Interestingly, with the notable exception of the Catchment model [Koster *et al.*, 2000], none of the TOPMODEL implementations represent the impact of subgrid variability in water table depth on soil moisture dynamics. Some more recent model implementations do explicitly represent the impact of spatial variability in water table depth, either through calculating the lateral flux from grid-to-grid [Fan and Miguez-Macho, 2011; Miguez-Macho and Fan, 2012a,b; Shi *et al.*, 2014; Maxwell *et al.*, 2015] or by calculating the lateral flux among a sequence of tiles in a subgrid hillslope [Subin *et al.*, 2014].

The key challenge is to explicitly represent the impact of the spatial variability in water table depth on soil moisture dynamics and land-atmosphere fluxes across a hierarchy of spatial scales. At the current and projected near-future scales over which these land models will be applied, this necessarily requires simulating both large-scale “among-grid” and the smaller-scale “within-grid” groundwater dynamics. The large-scale “among-grid” dynamics can be represented using a 2-D (vertically integrated) groundwater flow equation (Dupuit-Forchheimer approximation) [Fan and Miguez-Macho, 2011; Miguez-Macho and Fan, 2012a,b] or full 3-D implementation of the mixed form of Richards' equation [Maxwell *et al.*, 2015]. The smaller-scale “within-grid” dynamics can be represented by using the subgrid distribution of water table depth as the lower boundary condition for different subgrid tiles (e.g., where the different tiles are defined as areas with distinctive topographic convergence), or through extending the same large-scale, among-grid groundwater flow model to finer grids, without subgrid characterization at all (see section 3.2). The hillslope width function introduced by Fan and Bras [1998] is one example of a subgrid landscape configuration which imparts characteristic hydrologic responses in hillslope runoff formulations [Troch *et al.*, 2003; Hilberts *et al.*, 2004; Bogaart and Troch, 2006; Carrillo *et al.*, 2011]. Additionally, variable resolution models, such as tRIBS [Ivanov *et al.*, 2004; Vivoni *et al.*, 2004; Vivoni *et al.*, 2005] provide another means of representing different mechanisms of hydrologic complexity based on landform criteria, and such variable resolution approaches are currently being developed for broader earth system applications as well [Skamarock *et al.*, 2012]. At this point, it is unclear which approach will be most effective, and systematic comparison of these different approaches will be necessary to identify the best path to improve representation of groundwater dynamics in ESMs. We expand on this point in the benchmarking discussion (section 4).

A4. Stream-Aquifer-Land Interactions

Only a subset of models reviewed here explicitly represents groundwater dynamics, and a much smaller subset of models explicitly represents two-way stream-aquifer interactions. One example of the latter is the LEAF model, which incorporates river elevation as part of the 2-D vertically, integrated groundwater flow equation, and allows river and floodwater to infiltrate through sediments in the flood plain [Miguez-Macho *et al.*, 2007; Miguez-Macho and Fan, 2012a] that are an important source for groundwater recharge in many parts of the world [e.g., Taylor *et al.*, 2013]. CLM also allows for reinfiltration of flooded waters, but without explicitly linking river dynamics with groundwater flow processes [Oleson *et al.*, 2010].

It is well known in the groundwater modeling community that when groundwater is explicitly represented, streams and water bodies present critically important boundary conditions that strongly control the water table surface [Harbaugh *et al.*, 2005]. However, most of the models reviewed here simulate groundwater dynamics using a kinematic approximation [Liang *et al.*, 1994; Koster *et al.*, 2000; Oleson *et al.*, 2010; Best *et al.*, 2011; Koirala *et al.*, 2014], and hence only simulate one-way flow from the aquifer to the stream. The widespread disregard of stream-aquifer interactions in land models contrasts strongly with the modeling approaches used in integrated hydrologic models (e.g., ParFlow [Kollet and Maxwell, 2006], PIHM and FIHM [Qu and Duffy, 2007; Kumar *et al.*, 2009], HydroGeoSphere [Therrien *et al.*, 2010], and PAWS+CLM [Shen *et al.*, 2013]).

Explicitly representing the two-way exchange of water between aquifers and rivers is critical in order to both provide boundary conditions to the groundwater flow system and to provide estimates of base flow, which is necessary to adequately simulate riparian ponding features (wetlands) and biogeochemical cycles. In the future, a more integrated representation of the terrestrial hydrologic cycle is desired. This requires the following modeling advances: (1) stream routing should move from source-to-sink schemes to reach-by-reach (or high resolution, gridded) routing schemes—the diffusive wave equation (section A.5) is a

favorable approach due to its simplicity and stability; (2) the channel reaches need to interact with the land grid cells—stream-aquifer interaction is dynamic depending on flow stage, as well as the phase of the flood wave passage (i.e., whether or not the channel flow is rising or falling), requiring physically based representation or subgrid parameterization of groundwater head and river stage; and (3) important channel geometries, including channel width and bankfull depth, need to be provided or inferred from available datasets. While these conditions appear challenging, several hydrologic models have implemented these schemes [Downer and Ogden, 2004; Qu and Duffy, 2007; Shen and Phanikumar, 2010], and parsimonious representations of these processes have already been implemented in some land models [Miguez-Macho et al., 2007; Miguez-Macho and Fan, 2012a,b].

A5. Channel/Floodplain Routing

The routing of water through channels and floodplains is a critical component of ESMs because it provides the freshwater flux to the oceans. Reliable simulations of channel/floodplain routing are also important for coupled simulations of groundwater dynamics (as described in section A4) and to enable detailed evaluation/improvement of the terrestrial hydrologic cycle in land models (see section 4). In many flat areas near-stem streams such as the Amazon, mid-stream Yangtze River, the Sudd, and the Okavango delta, channel-land exchange is a major control of the ecosystems of the floodplains and nearby regions [Fan and Miguez-Macho, 2011].

Three main approaches have been used for horizontal routing of runoff through river networks:

1. Source-to-sink methods, which use an impulse response function to calculate the travel time from individual grid boxes (sources) to a specific point on the river network (a sink) [Lohmann et al., 1996; Nijssen et al., 2001]. These methods therefore estimate the lumped response for all grid boxes above a desired sink (e.g., above a gauging station), assuming the runoff routing processes are linear and stationary [Li et al., 2013]. The source-to-sink approach is used in the VIC model [Nijssen et al., 2001], and has been applied as a postprocessing step for multiple land models [Lohmann et al., 1998a, 2004; Xia et al., 2012a, 2012b].
2. Empirical storage-outflow relationships, which calculate the flow in a given reach as a linear or nonlinear function of reach storage. Linear reach storage-outflow relationships are used in ORCHIDEE [Ngo-Duc et al., 2007; Guimberteau et al., 2012] and CLM [Swenson et al., 2012], and nonlinear storage-outflow relationships are used in LM3 [Milly et al., 2014]. For example, in CLM

$$Q_R = v \frac{S_R}{d} \tag{A12}$$

where Q_R is the outflow from a given reach (m s^{-1}), v is the flow velocity (m s^{-1}), computed as a function of gridcell-average slope, S_R is the reach storage (m), and d is the stream distance (m), given as the distance among adjacent grid cells. These empirical storage-outflow relations are in the same class of models as the empirical Manning equation, implemented recently in CLM [Li et al., 2013, 2015]

$$Q_R = \frac{\sqrt{\beta}}{n} k R_h^{2/3} \tag{A13}$$

where β is the channel slope, n is the Manning's roughness coefficient, k is a conversion factor, and R_h is the hydraulic radius (m), defined as the wetted area (m^2) divided by the wetted perimeter (m); with $R_h = f(S_R)$. Empirical storage-outflow methods assume that the gravity force dominates over all others [Li et al., 2013].

3. The third approach used is 1-D diffusive wave models, in which water surface slope, instead of riverbed slope as in the kinematic wave method above, drives the flow, thus accounting for the backwater effect in flat river reaches. These models are used in TESSEL [Yamazaki et al., 2011; Pappenberger et al., 2012; Yamazaki et al., 2012], LEAF [Miguez-Macho and Fan, 2012b], and LM3 [Milly et al., 2014]. In LM3, the 1-D diffusive wave models are only used in reaches where the channel slope is below some specified threshold.

These 1-D channel routing models are more efficient and have lower data requirements than the 2-D and 3-D hydraulic models used in local-scale studies [Wu, 2008], and 1-D routing models are thus more suitable for use in global land models. In contrast to other hydrologic processes where developments in the hydrologic sciences have immediate applicability in land models, the global-scale applicability of complex

hydraulic models is clearly rather limited. As such, we recommend further development and refinement of 1-D channel routing models in land models. In practice, this will mean shifting to models that explicitly represent the physical characteristics of rivers and floodplains [Li *et al.*, 2013]. This will require more widespread implementation of diffusive wave models in order to simulate downstream controls on flow (backwater effects) [Miguez-Macho and Fan, 2012a; Pappenberger *et al.*, 2012; Yamazaki *et al.*, 2013]. It may also require implementing a multiscale modeling approach within various hydrologic components of ESMs [Ivanov *et al.*, 2004; Vivoni *et al.*, 2004; Vivoni *et al.*, 2005; Qu and Duffy, 2007; Kumar *et al.*, 2009] in order to resolve how complex landscape morphology affects hydraulic connectivity and intermittent channel flow.

A key model development need is to improve methods to estimate physical river characteristics (e.g., channel slope, roughness, and hydraulic geometry) and model parameters (e.g., the flow velocity parameter used in the simpler parameterizations). This is a challenge for all flow routing models—for example, the method to estimate the flow velocity parameter has recently been shown to be very important in linear storage-outflow models [Swenson *et al.*, 2012; Li *et al.*, 2015]. Many recent advances have gradually enabled us to address these challenges. River bed elevations extracted using a high-resolution DEM and a forward moving average filter in PAWS+CLM algorithm agree well with the groundwater table, permitting a highly efficient solver for the diffusive wave equation [Shen *et al.*, 2014]. Globally-available, 1/8° resolution river flow direction, accumulation and slope hydrography datasets, e.g., HydroSHEDS [Lehner *et al.*, 2008] and DRT [Wu *et al.*, 2012], have emerged. Remote-sensing data sets and the application of scaling laws provides global estimates of recharge [Gleason and Smith, 2014] and water depths [Mersel *et al.*, 2013]. The next generation remote-sensing products (e.g., the Surface Water and Ocean Topography, SWOT, expected to launch in 2020) will further expand our ability to characterize stream geometries and discharges [e.g., Getirana *et al.*, 2013; Pavelsky *et al.*, 2014; Pedinotti *et al.*, 2014; Allen and Pavelsky, 2015].

Acknowledgments

This paper is produced as part of a new CUAHSI initiative to improve the representation of hydrologic processes in Earth System Models. Support from the National Science Foundation, through CUAHSI cooperative agreement (NSF-EAR-0753521) and an INSPIRE grant (NSF-EAR-1528298), is gratefully acknowledged.

References

- Abramowitz, G. (2012), Towards a public, standardized, diagnostic benchmarking system for land surface models, *Geosci. Model Dev.*, *5*, 819–827, doi:10.5194/gmd-5-819-2012.
- Abramowitz, G., R. Leuning, M. Clark, and A. Pitman (2008), Evaluating the performance of land surface models, *J. Clim.*, *21*, 5468–5481.
- Adam, J. C., J. C. Stephens, S. H. Chung, M. P. Brady, R. D. Evans, C. E. Kruger, B. K. Lamb, M. Liu, C. O. Stöckle, and J. K. Vaughan (2014), Bio-Earth: Envisioning and developing a new regional earth system model to inform natural and agricultural resource management, *Clim. Change*, *129*, 555–571.
- Alcamo, J., P. Döll, T. Henrichs, F. Kaspar, B. Lehner, T. Röscher, and S. Siebert (2003), Development and testing of the WaterGAP 2 global model of water use and availability, *Hydrol. Sci. J.*, *48*, 317–337.
- Alkama, R., B. Decharme, H. Douville, M. Becker, A. Cazenave, J. Sheffield, A. Voldoire, S. Tyteca, and P. Le Moigne (2010), Global evaluation of the ISBA-TRIP continental hydrological system. Part I: Comparison to GRACE terrestrial water storage estimates and in situ river discharges, *J. Hydrometeorol.*, *11*, 583–600.
- Allen, G. H., and T. M. Pavelsky (2015), Patterns of river width and surface area revealed by the satellite-derived North American River Width (NARWidth) data set, *Geophys. Res. Lett.*, *42*, 395–402, doi:10.1002/2014GL062764.
- Avisar, R., and R. A. Pielke (1989), A parameterization of heterogeneous land surfaces for atmospheric numerical models and its impact on regional meteorology, *Mon. Weather Rev.*, *117*, 2113–2136.
- Baldocchi, D., and T. Meyers (1998), On using eco-physiological, micrometeorological and biogeochemical theory to evaluate carbon dioxide, water vapor and trace gas fluxes over vegetation: A perspective, *Agric. For. Meteorol.*, *90*, 1–25.
- Balsamo, G., P. Viterbo, A. Beljaars, B. van den Hurk, M. Hirschi, A. K. Betts, and K. Scipal (2009), A revised hydrology for the ECMWF model: Verification from field site to terrestrial water storage and impact in the integrated forecast system, *J. Hydrometeorol.*, *10*, 623–643, doi:10.1175/2008JHM1068.1.
- Balsamo, G., F. Pappenberger, E. Dutra, P. Viterbo, and B. van den Hurk (2011), A revised land hydrology in the ECMWF model: A step towards daily water flux prediction in a fully-closed water cycle, *Hydrol. Processes*, *25*, 1046–1054, doi:10.1002/hyp.7808.
- Barnett, T. P., J. C. Adam, and D. P. Lettenmaier (2005), Potential impacts of a warming climate on water availability in snow-dominated regions, *Nature*, *438*, 303–309.
- Best, M. J., et al. (2011), The Joint UK Land Environment Simulator (JULES), model description—Part 1: Energy and water fluxes, *Geosci. Model Dev.*, *4*, 677–699, doi:10.5194/gmd-4-677-2011.
- Beven, K. (1993), Prophecy, reality and uncertainty in distributed hydrological modeling, *Adv. Water Resour.*, *16*, 41–51, doi:10.1016/0309-1708(93)90028-E.
- Beven, K. (2001), How far can we go in distributed hydrological modelling?, *Hydrol. Earth Syst. Sci.*, *5*, 1–12.
- Beven, K. (2007), Towards integrated environmental models of everywhere: Uncertainty, data and modelling as a learning process, *Hydrol. Earth Syst. Sci.*, *11*, 460–467.
- Beven, K. (2012), Causal models as multiple working hypotheses about environmental processes, *C. R. Geosci.*, *344*, 77–88, doi:10.1016/j.crte.2012.01.005.
- Beven, K., and J. Freer (2001), A dynamic TOPMODEL, *Hydrol. Processes*, *15*, 1993–2011, doi:10.1002/hyp.252.
- Beven, K., and P. Germann (1981), Water-flow in soil macropores. 2. A combined flow model, *J. Soil Sci.*, *32*, 15–29.
- Beven, K., and P. Germann (1982), Macropores and water-flow in soils, *Water Resour. Res.*, *18*, 1311–1325, doi:10.1029/WR018i005p01311.
- Beven, K. J., and H. L. Cloke (2012), Comment on “Hyperresolution global land surface modeling: Meeting a grand challenge for monitoring Earth’s terrestrial water” by Eric F. Wood *et al.*, *Water Resour. Res.*, *48*, W01801, doi:10.1029/2011WR010982.

- Beven, K. J., and M. J. Kirkby (1979), A physically based, variable contributing area model of basin hydrology, *Hydrol. Sci. J.*, *24*(1), 43–69, doi:10.1080/02626667909491834.
- Beven, K. J., P. Smith, I. Westerberg, and J. Freer (2012), Comment on “Pursuing the method of multiple working hypotheses for hydrological modeling” by M. P. Clark et al., *Water Resour. Res.*, *48*, W11801, doi:10.1029/2012WR012282.
- Blyth, E., D. Clark, R. Ellis, C. Huntingford, S. Los, M. Pryor, M. Best, and S. Sitch (2011), A comprehensive set of benchmark tests for a land surface model of simultaneous fluxes of water and carbon at both the global and seasonal scale, *Geosci. Model Dev.*, *4*, 255–269.
- Bogaart, P., and P. Troch (2006), Curvature distribution within hillslopes and catchments and its effect on the hydrological response, *Hydrol. Earth Syst. Sci.*, *10*, 925–936.
- Bogaart, P. W., D. E. Rupp, J. S. Selker, and Y. Velde (2013), Late-time drainage from a sloping Boussinesq aquifer, *Water Resour. Res.*, *49*, 7498–7507, doi:10.1002/2013WR013780.
- Bonan, G., M. Williams, R. Fisher, and K. Oleson (2014), Modeling stomatal conductance in the earth system: Linking leaf water-use efficiency and water transport along the soil–plant–atmosphere continuum, *Geosci. Model Dev.*, *7*, 2193–2222.
- Bonan, G. B., S. Levis, L. Kergoat, and K. W. Oleson (2002), Landscapes as patches of plant functional types: An integrating concept for climate and ecosystem models, *Global Biogeochem. Cycles*, *16*(2), doi:10.1029/2000GB001360.
- Boone, A., and P. J. Wetzel (1996), Issues related to low resolution modeling of soil moisture: Experience with the PLACE model, *Global Planet. Change*, *13*, 161–181, doi:10.1016/0921-8181(95)00044-5.
- Boone, A., F. Habets, J. Noilhan, D. Clark, P. Dirmeyer, S. Fox, Y. Gusev, I. Haddeland, R. Koster, and D. Lohmann (2004), The Rhone-Aggregation land surface scheme intercomparison project: An overview, *J. Clim.*, *17*, 187–208.
- Boucher, O., G. Myhre, and A. Myhre (2004), Direct human influence of irrigation on atmospheric water vapour and climate, *Clim. Dyn.*, *22*, 597–603.
- Camporese, M., C. Paniconi, M. Putti, and P. Salandin (2009), Ensemble Kalman filter data assimilation for a process-based catchment scale model of surface and subsurface flow, *Water Resour. Res.*, *45*, W10421, doi:10.1029/2008WR007031.
- Camporese, M., C. Paniconi, M. Putti, and S. Orlandini (2010), Surface-subsurface flow modeling with path-based runoff routing, boundary condition-based coupling, and assimilation of multisource observation data, *Water Resour. Res.*, *46*, W02512, doi:10.1029/2008WR007536.
- Campoy, A., A. Ducharme, F. Cheruy, F. Hourdin, J. Polcher, and J. Dupont (2013), Response of land surface fluxes and precipitation to different soil bottom hydrological conditions in a general circulation model, *J. Geophys. Res. Atmos.*, *118*, 10,725–10,739, doi:10.1002/jgrd.50627.
- Carrillo, G., P. Troch, M. Sivapalan, T. Wagener, C. Harman, and K. Sawicz (2011), Catchment classification: Hydrological analysis of catchment behavior through process-based modeling along a climate gradient, *Hydrol. Earth Syst. Sci.*, *15*, 3411–3430.
- Celia, M. A., E. T. Bouloutas, and R. L. Zarba (1990), A general mass-conservative numerical solution for the unsaturated flow equation, *Water Resour. Res.*, *26*, 1483–1496, doi:10.1029/90WR00196.
- Chaney, N. W., J. K. Roundy, J. E. Herrera-Estrada, and E. F. Wood (2014), High-resolution modeling of the spatial heterogeneity of soil moisture: Applications in network design, *Water Resour. Res.*, *51*, 619–638, doi:10.1002/2013WR014964.
- Chen, F., and R. Avissar (1994), Impact of land-surface moisture variability on local shallow convective cumulus and precipitation in large-scale models, *J. Appl. Meteorol.*, *33*, 1382–1401.
- Chen, F., and J. Dudhia (2001), Coupling an advanced land surface-hydrology model with the Penn State-NCAR MM5 modeling system. Part I: Model implementation and sensitivity, *Mon. Weather Rev.*, *129*, 569–585, doi:10.1175/1520-0493(2001)129<0569:CAALSH>2.0.CO;2.
- Chen, F., K. Mitchell, J. Schaake, Y. Xue, H. L. Pan, V. Koren, Q. Y. Duan, M. Ek, and A. Betts (1996), Modeling of land surface evaporation by four schemes and comparison with FIFE observations, *J. Geophys. Res.*, *101*, 7251–7268.
- Clapp, R. B., and G. M. Hornberger (1978), Empirical equations for some soil hydraulic properties, *Water Resour. Res.*, *14*, 601–604.
- Clark, D. B., and N. Gedney (2008), Representing the effects of subgrid variability of soil moisture on runoff generation in a land surface model, *J. Geophys. Res.*, *113*, D10111, doi:10.1029/2007JD008940.
- Clark, M. P., A. G. Slater, D. E. Rupp, R. A. Woods, J. A. Vrugt, H. V. Gupta, T. Wagener, and L. E. Hay (2008), Framework for Understanding Structural Errors (FUSE): A modular framework to diagnose differences between hydrological models, *Water Resour. Res.*, *44*, W00B02, doi:10.1029/2007WR006735.
- Clark, M. P., D. E. Rupp, R. A. Woods, H. J. Tromp-van Meerveld, N. E. Peters, and J. E. Freer (2009), Consistency between hydrological models and field observations: Linking processes at the hillslope scale to hydrological responses at the watershed scale, *Hydrol. Processes*, *23*, 311–319, doi:10.1002/hyp.7154.
- Clark, M. P., D. Kavetski, and F. Fenicia (2011), Pursuing the method of multiple working hypotheses for hydrological modeling, *Water Resour. Res.*, *47*, W09301, doi:10.1029/2010WR009827.
- Clark, M. P., D. Kavetski, and F. Fenicia (2012), Reply to comment by K. Beven et al. on “Pursuing the method of multiple working hypotheses for hydrological modeling”, *Water Resour. Res.*, *48*, W11802, doi:10.1029/2012WR012547.
- Clark, M. P., et al. (2015a), A unified approach to process-based hydrologic modeling. Part 1: Modeling concept, *Water Resour. Res.*, *51*, 2498–2514, doi:10.1002/2015WR017198.
- Clark, M. P., et al. (2015b), A unified approach for process-based hydrologic modeling: Part 2. Model implementation and example applications, *Water Resour. Res.*, *51*, 2515–2542, doi:10.1002/2015WR017200.
- Cox, P. M., R. A. Betts, C. B. Bunton, R. L. H. Essery, P. R. Rowntree, and J. Smith (1999), The impact of new land surface physics on the GCM simulation of climate and climate sensitivity, *Clim. Dyn.*, *15*, 183–203, doi:10.1007/s003820050276.
- Dai, Y., R. E. Dickinson, and Y.-P. Wang (2004), A two-big-leaf model for canopy temperature, photosynthesis, stomatal conductance, *J. Clim.*, *17*, 2281–2299, doi:10.1175/1520-0442(2004)017<2281:ATMFACT>2.0.CO;2.
- De Rooij, G. H. (2010), Comments on “Improving the Numerical Simulation of Soil Moisture-Based Richards Equation for Land Models with a Deep or Shallow Water Table”, *J. Hydrometeorol.*, *11*, 1044–1050.
- de Rosnay, P., and J. Polcher (1998), Modelling root water uptake in a complex land surface scheme coupled to a GCM, *Hydrol. Earth Syst. Sci.*, *2*, 239–255.
- de Rosnay, P., M. Bruen, and J. Polcher (2000), Sensitivity of surface fluxes to the number of layers in the soil model used in GCMs, *Geophys. Res. Lett.*, *27*, 3329–3332, doi:10.1029/2000GL011574.
- de Rosnay, P., J. Polcher, M. Bruen, and K. Laval (2002), Impact of a physically based soil water flow and soil-plant interaction representation for modeling large-scale land surface processes, *J. Geophys. Res.*, *107*(D11), doi:10.1029/2001JD000634.
- Decharme, B., R. Alkama, H. Douville, M. Becker, and A. Cazenave (2010), Global evaluation of the ISBA-TRIP continental hydrological system. Part II: Uncertainties in river routing simulation related to flow velocity and groundwater storage, *J. Hydrometeorol.*, *11*, 601–617.

- Decharme, B., R. Alkama, F. Papa, S. Faroux, H. Douville, and C. Prigent (2012), Global off-line evaluation of the ISBA-TRIP flood model, *Clim. Dyn.*, *38*, 1389–1412.
- Dirmeyer, P. A., R. D. Koster, and Z. C. Guo (2006), Do global models properly represent the feedback between land and atmosphere?, *J. Hydrometeorol.*, *7*, 1177–1198, doi:10.1175/JHM532.1.
- Dolman, J. A., and D. Gregory (1992), The parametrization of rainfall interception in GCMs, *Q. J. R. Meteorol. Soc.*, *118*, 455–467.
- Domec, J. C., J. Ogée, A. Noormets, J. Jouangy, M. Gavazzi, E. Treasure, G. Sun, S. G. McNulty, and J. S. King (2012), Interactive effects of nocturnal transpiration and climate change on the root hydraulic redistribution and carbon and water budgets of southern United States pine plantations, *Tree Physiol.*, *32*, 707–723, doi:10.1093/treephys/tps018.
- Dooge, J. C. I. (1986), Looking for hydrologic laws, *Water Resour. Res.*, *22*, 465–585, doi:10.1029/WR022i09Sp00465.
- d'Orgeval, T., J. Polcher, and P. de Rosnay (2008), Sensitivity of the West African hydrological cycle in ORCHIDEE to infiltration processes, *Hydrol. Earth Syst. Sci.*, *12*, 1387–1401.
- Douville, H. (2004), Relevance of soil moisture for seasonal atmospheric predictions: Is it an initial value problem?, *Clim. Dyn.*, *22*, 429–446.
- Downer, C. W., and F. L. Ogden (2004), GSSHA: Model to simulate diverse stream flow producing processes, *J. Hydrol. Eng.*, *9*, 161–174.
- Drewniak, B., J. Song, J. Prell, V. Kotamarthi, and R. Jacob (2013), Modeling agriculture in the community land model, *Geosci. Model Dev.*, *6*, 495–515.
- Ducharne, A., R. D. Koster, M. J. Suarez, M. Stieglitz, and P. Kumar (2000), A catchment-based approach to modeling land surface processes in a general circulation model: 2. Parameter estimation and model demonstration, *J. Geophys. Res.*, *105*, 24,823–24,838, doi:10.1029/2000JD900328.
- Dunne, J. P., J. G. John, A. J. Adcroft, S. M. Griffies, R. W. Hallberg, E. Shevliakova, R. J. Stouffer, W. Cooke, K. A. Dunne, and M. J. Harrison (2012), GFDL's ES2 global coupled climate-carbon Earth System Models. Part I: Physical formulation and baseline simulation characteristics, *J. Clim.*, *25*, 6646–6665.
- Eagleson, P. S. (1986), The emergence of global-scale hydrology, *Water Resour. Res.*, *22*, 65–145.
- ECMWF (2014), *IFS Documentation—Cy40r1 Operational Implementation, 22 November 2013. Part IV: Physical Processes*, 190 pp., European Centre for Medium-Range Weather Forecasts, Reading, U. K.
- Ek, M. B., K. E. Mitchell, Y. Lin, E. Rogers, P. Grunmann, V. Koren, G. Gayno, and J. D. Tarpley (2003), Implementation of Noah land surface model advances in the National Centers for Environmental Prediction operational mesoscale Eta model, *J. Geophys. Res.*, *108*(D22), 8851, doi:10.1029/2002JD003296.
- Entekhabi, D., and P. S. Eagleson (1989), Land surface hydrology parameterization for atmospheric general circulation models including subgrid scale spatial variability, *J. Clim.*, *2*, 816–831.
- Essery, R., P. Bunting, J. Hardy, T. Link, D. Marks, R. Melloh, J. Pomeroy, A. Rowlands, and N. Rutter (2008), Radiative transfer modeling of a coniferous canopy characterized by airborne remote sensing, *J. Hydrometeorol.*, *9*, 228–241, doi:10.1175/2007JHM870.1.
- Essery, R. L. H., M. J. Best, R. A. Betts, P. M. Cox, and C. M. Taylor (2003), Explicit representation of subgrid heterogeneity in a GCM land surface scheme, *J. Hydrometeorol.*, *4*, 530–543, doi:10.1175/1525-7541(2003)004<0530:EROSHI>2.0.CO;2.
- Ewers, B., R. Oren, and J. Sperry (2000), Influence of nutrient versus water supply on hydraulic architecture and water balance in Pinus taeda, *Plant Cell Environ.*, *23*, 1055–1066.
- Famiglietti, J. S., and E. F. Wood (1994), Multiscale modeling of spatially variable water and energy balance processes, *Water Resour. Res.*, *30*, 3061–3078, doi:10.1029/94WR01498.
- Fan, Y. (2015), Groundwater in the Earth's critical zone - Relevance to large-scale patterns and processes, *Water Resour. Res.*, *51*, 3052–3069, doi:10.1002/2015WR017037.
- Fan, Y., and R. L. Bras (1998), Analytical solutions to hillslope subsurface storm flow and saturation overland flow, *Water Resour. Res.*, *34*, 921–927.
- Fan, Y., and G. Miguez-Macho (2011), A simple hydrologic framework for simulating wetlands in climate and earth system models, *Clim. Dyn.*, *37*, 253–278, doi:10.1007/s00382-010-0829-8.
- Fan, Y., G. Miguez-Macho, C. P. Weaver, R. Walko, and A. Robock (2007), Incorporating water table dynamics in climate modeling: 1. Water table observations and equilibrium water table simulations, *J. Geophys. Res.*, *112*, D10125, doi:10.1029/2006JD008111.
- Fan, Y., H. Li, and G. Miguez-Macho (2013), Global patterns of groundwater table depth, *Science*, *339*, 940–943.
- Fan, Y., S. Richard, R. Bristol, S. Peters, S. Ingebritsen, N. Moosdorf, A. Packman, T. Gleeson, I. Zaslavsky, and S. Peckham (2015), Digital-Crust—A 4D data system of material properties for transforming research on crustal fluid flow, *Geofluids*, *15*, 372–379.
- Feddes, R., E. Bresler, and S. Neuman (1974), Field test of a modified numerical model for water uptake by root systems, *Water Resour. Res.*, *10*, 1199–1206.
- Feddes, R. A., H. Hoff, M. Bruen, T. Dawson, P. de Rosnay, P. Dirmeyer, R. B. Jackson, P. Kabat, A. Kleidon, and A. Lilly (2001), Modeling root water uptake in hydrological and climate models, *Bull. Am. Meteorol. Soc.*, *82*, 2797–2809.
- Fenicia, F., D. Kavetski, H. H. G. Savenije, M. P. Clark, G. Schoups, L. Pfister, and J. Freer (2014), Catchment properties, function, and conceptual model representation: Is there a correspondence?, *Hydrol. Processes*, *28*, 2451–2467, doi:10.1002/hyp.9726.
- Flato, G. M. (2011), Earth system models: An overview, *WIREs Clim. Change*, *2*, 783–800.
- Foley, J. A., R. DeFries, G. P. Asner, C. Barford, G. Bonan, S. R. Carpenter, F. S. Chapin, M. T. Coe, G. C. Daily, and H. K. Gibbs (2005), Global consequences of land use, *Science*, *309*, 570–574.
- Freer, J. E., H. McMillan, J. J. McDonnell, and K. J. Beven (2004), Constraining dynamic TOPMODEL responses for imprecise water table information using fuzzy rule based performance measures, *J. Hydrol.*, *291*, 254–277, doi:10.1016/j.jhydrol.2003.12.037.
- Freeze, R. A., and R. Harlan (1969), Blueprint for a physically-based, digitally-simulated hydrologic response model, *J. Hydrol.*, *9*, 237–258, doi:10.1016/0022-1694(69)90020-1.
- Garrote, L., and R. L. Bras (1995), A distributed model for real-time flood forecasting using digital representation models, *J. Hydrol.*, *167*, 279–306.
- Gedney, N., and P. M. Cox (2003), The sensitivity of global climate model simulations to the representation of soil moisture heterogeneity, *J. Hydrometeorol.*, *4*, 1265–1275, doi:10.1175/1525-7541(2003)004<1265:TSOGCM>2.0.CO;2.
- Getirana, A. C., A. Boone, D. Yamazaki, and N. Mognard (2013), Automatic parameterization of a flow routing scheme driven by radar altimetry data: Evaluation in the Amazon basin, *Water Resour. Res.*, *49*, 614–629, doi:10.1002/wrcr.20077.
- Giorgi, F., and R. Avissar (1997), Representation of heterogeneity effects in earth system modeling: Experience from land surface modeling, *Rev. Geophys.*, *35*, 413–437, doi:10.1029/97RG01754.
- Gleason, C. J., and L. C. Smith (2014), Toward global mapping of river discharge using satellite images and at-many-stations hydraulic geometry, *Proc. Natl. Acad. Sci. U. S. A.*, *111*, 4788–4791.
- Gochis, D. J., E. R. Vivoni, and C. J. Watts (2010), The impact of soil depth on land surface energy and water fluxes in the North American Monsoon region, *J. Arid Environ.*, *74*, 564–571.

- Gochis, D. J., W. Yu, and D. N. Yates (2013), *The WRF-Hydro Model Technical Description and User's Guide, Version 1.0.*, 120 pp., National Center for Atmospheric Research, Boulder, Colo.
- Govindaraju, R., M. Kavvas, and S. Jones (1990), Approximate analytical solutions for overland flows, *Water Resour. Res.*, *26*, 2903–2912.
- Grant, L., M. Seyfried, and J. McNamara (2004), Spatial variation and temporal stability of soil water in a snow-dominated, mountain catchment, *Hydrol. Processes*, *18*, 3493–3511.
- Guimberteau, M., G. Drapeau, J. Ronchail, B. Sultan, J. Polcher, J.-M. Martinez, C. Prigent, J.-L. Guyot, G. Cochonneau, and J. Espinoza (2012), Discharge simulation in the sub-basins of the Amazon using ORCHIDEE forced by new datasets, *Hydrol. Earth Syst. Sci.*, *16*, 911–935.
- Gupta, H. V., T. Wagener, and Y. Q. Liu (2008), Reconciling theory with observations: Elements of a diagnostic approach to model evaluation, *Hydrol. Processes*, *22*, 3802–3813, doi:10.1002/hyp.6989.
- Gupta, H. V., M. P. Clark, J. A. Vrugt, G. Abramowitz, and M. Ye (2012), Towards a comprehensive assessment of model structural adequacy, *Water Resour. Res.*, *48*, W08301, doi:10.1029/2011WR011044.
- Haddeland, I., D. P. Lettenmaier, and T. Skaugen (2006), Effects of irrigation on the water and energy balances of the Colorado and Mekong river basins, *J. Hydrol.*, *324*, 210–223.
- Hahmann, A. N., and R. E. Dickinson (2001), A fine-mesh land approach for general circulation models and its impact on regional climate, *J. Clim.*, *14*, 1634–1646.
- Hansson, K., J. Simunek, M. Mizoguchi, L. C. Lundin, and M. T. van Genuchten (2004), Water flow and heat transport in frozen soil: Numerical solution and freeze-thaw applications, *Vadose Zone J.*, *3*, 693–704.
- Harbaugh, A. W., E. R. Banta, and M. C. Hill (2005), MODFLOW-2000, The US Geological Survey modular ground-water model: User guide to modularization concepts and the ground-water flow process, *U.S. Geol. Surv. Open File Rep.*, *00–92*, 121 pp.
- Harper, J., M. Jones, and N. Sackville Hamilton (1991), The evolution of roots and the problems of analysing their behaviour, in *Plant Root Growth: An Ecological Perspective*, edited by D. Atkinson, Blackwell Scientific Publications, Oxford, U. K.
- Hickler, T., I. C. Prentice, B. Smith, M. T. Sykes, and S. Zaehle (2006), Implementing plant hydraulic architecture within the LPJ Dynamic Global Vegetation Model, *Global Ecol. Biogeogr.*, *15*, 567–577, doi:10.1111/j.1466-822X.2006.00254.x.
- Hilberts, A., E. Van Loon, P. Troch, and C. Paniconi (2004), The hillslope-storage Boussinesq model for non-constant bedrock slope, *J. Hydrol.*, *291*, 160–173.
- Hodge, A. (2004), The plastic plant: Root responses to heterogeneous supplies of nutrients, *New Phytol.*, *162*, 9–24.
- Huang, H. Y., and S. A. Margulis (2009), On the impact of surface heterogeneity on a realistic convective boundary layer, *Water Resour. Res.*, *45*, W04425, doi:10.1029/2008WR007175.
- Huang, H. Y., and S. A. Margulis (2013), Impact of soil moisture heterogeneity length scale and gradients on daytime coupled land-cloudy boundary layer interactions, *Hydrol. Processes*, *27*, 1988–2003.
- Huntington, T. G. (2006), Evidence for intensification of the global water cycle: Review and synthesis, *J. Hydrol.*, *319*, 83–95.
- Hurrell, J. W., M. Holland, P. Gent, S. Ghan, J. E. Kay, P. Kushner, J.-F. Lamarque, W. Large, D. Lawrence, and K. Lindsay (2013), The community earth system model: A framework for collaborative research, *Bull. Am. Meteorol. Soc.*, *94*, 1339–1360.
- Ivanov, V. Y., E. R. Vivoni, R. L. Bras, and D. Entekhabi (2004), Catchment hydrologic response with a fully distributed triangulated irregular network model, *Water Resour. Res.*, *40*, W11102, doi:10.1029/2004WR003218.
- Jackson, R., J. Canadell, J. Ehleringer, H. Mooney, O. Sala, and E. Schulze (1996), A global analysis of root distributions for terrestrial biomes, *Oecologia*, *108*, 389–411.
- Kirchner, J. W., R. P. Hooper, C. Kendall, C. Neal, and G. Leavesley (1996), Testing and validating environmental models, *Sci. Total Environ.*, *183*, 33–47.
- Klemes, V. (1983), Conceptualization and scale in hydrology, *J. Hydrol.*, *65*, 1–23, doi:10.1016/0022-1694(83)90208-1.
- Koirala, S., P. J. F. Yeh, Y. Hirabayashi, S. Kanae, and T. Oki (2014), Global-scale land surface hydrologic modeling with the representation of water table dynamics, *J. Geophys. Res. Atmos.*, *119*, 75–89, doi:10.1002/2013JD020398.
- Kollet, S. J., and R. M. Maxwell (2006), Integrated surface-groundwater flow modeling: A free-surface overland flow boundary condition in a parallel groundwater flow model, *Adv. Water Resour.*, *29*, 945–958, doi:10.1016/j.advwatres.2005.08.006.
- Koren, V., J. Schaake, K. Mitchell, Q. Y. Duan, F. Chen, and J. Baker (1999), A parameterization of snowpack and frozen ground intended for NCEP weather and climate models, *J. Geophys. Res.*, *104*, 19,569–19,585, doi:10.1029/1999JD900232.
- Koster, R. D., and P. C. D. Milly (1997), The interplay between transpiration and runoff formulations in land surface schemes used with atmospheric models, *J. Clim.*, *10*, 1578–1591, doi:10.1175/1520-0442(1997)010<1578:TIBTAR>2.0.CO;2.
- Koster, R. D., and M. J. Suarez (1992), Modeling the land surface boundary in climate models as a composite of independent vegetation stands, *J. Geophys. Res.*, *97*, 2697–2715, doi:10.1029/91JD01696.
- Koster, R. D., M. J. Suarez, A. Ducharme, M. Stieglitz, and P. Kumar (2000), A catchment-based approach to modeling land surface processes in a general circulation model: 1. Model structure, *J. Geophys. Res.*, *105*, 24,809–24,822, doi:10.1029/2000JD900327.
- Koster, R. D., et al. (2006), GLACE: The Global Land-Atmosphere Coupling Experiment. Part I: Overview, *J. Hydrometeorol.*, *7*, 590–610, doi:10.1175/JHM510.1.
- Koster, R. D., et al. (2011), The second phase of the Global Land-Atmosphere Coupling Experiment: Soil moisture contributions to subseasonal forecast skill, *J. Hydrometeorol.*, *12*, 805–822, doi:10.1175/2011JHM1365.1.
- Kowalczyk, E., Y. Wang, R. Law, H. Davies, J. McGregor, and G. Abramowitz (2006), *The CSIRO Atmosphere Biosphere Land Exchange (CABLE) Model for Use in Climate Models and as an Offline Model*, 37 pp., Commonwealth Scientific and Industrial Research Organization, Aspendale, Victoria, Australia.
- Kraucunas, I., L. Clarke, J. Dirks, J. Hathaway, M. Hejazi, K. Hibbard, M. Huang, C. Jin, M. Kintner-Meyer, and K. K. van Dam (2014), Investigating the Nexus of climate, energy, water, and land at decision-relevant scales: The Platform for Regional Integrated Modeling and Analysis (PRIMA), *Clim. Change*, *129*, 573–588.
- Kuczera, G., and M. Mroczkowski (1998), Assessment of hydrologic parameter uncertainty and the worth of multiresponse data, *Water Resour. Res.*, *34*, 1481–1489.
- Kuczera, G., B. Renard, M. Thyer, and D. Kavetski (2010), There are no hydrological monsters, just models and observations with large uncertainties!, *Hydrol. Sci. J.*, *55*, 980–991, doi:10.1080/02626667.2010.504677.
- Kumar, M., C. J. Duffy, and K. M. Salvage (2009), A second-order accurate, finite volume-based, integrated hydrologic modeling (FIHM) framework for simulation of surface and subsurface flow, *Vadose Zone J.*, *8*, 873–890.
- Lai, C., and G. Katul (2000), The dynamic role of root-water uptake in coupling potential to actual transpiration, *Adv. Water Resour.*, *23*, 427–439.
- Landry, C. C., K. A. Buck, M. S. Raleigh, and M. P. Clark (2014), Mountain system monitoring at Senator Beck Basin, San Juan Mountains, Colorado: A new integrative data source to develop and evaluate models of snow and hydrologic processes, *Water Resour. Res.*, *50*, 1773–1788, doi:10.1002/2013WR013711.

- Lawrence, D. M., et al. (2011), Parameterization improvements and functional and structural advances in Version 4 of the Community Land Model, *J. Adv. Model. Earth Syst.*, *3*, M03001, doi:10.1029/2011MS000045.
- Lee, D. H., and L. M. Abriola (1999), Use of the Richards equation in land surface parameterizations, *J. Geophys. Res.*, *104*, 27,519–27,526.
- Lehner, B., K. Verdin, and A. Jarvis (2008), New global hydrography derived from spaceborne elevation data, *Eos Trans. AGU*, *89*, 93–94.
- Leng, G., M. Huang, Q. Tang, W. J. Sacks, H. Lei, and L. R. Leung (2013), Modeling the effects of irrigation on land surface fluxes and states over the conterminous United States: Sensitivity to input data and model parameters, *J. Geophys. Res. Atmos.*, *118*, 9789–9803, doi:10.1002/jgrd.50792.
- Leng, G., M. Huang, Q. Tang, H. Gao, and L. R. Leung (2014), Modeling the effects of groundwater-fed irrigation on terrestrial hydrology over the conterminous United States, *J. Hydrometeorol.*, *15*, 957–972.
- Leonard, L., and C. J. Duffy (2014), Automating data-model workflows at a level 12 HUC scale: Watershed modeling in a distributed computing environment, *Environ. Modell. Software*, *61*, 174–190.
- Leung, L. R., M. Huang, Y. Qian, and X. Liang (2011), Climate–soil–vegetation control on groundwater table dynamics and its feedbacks in a climate model, *Clim. Dyn.*, *36*, 57–81.
- Li, H., M. S. Wigmosta, H. Wu, M. Huang, Y. Ke, A. M. Coleman, and L. R. Leung (2013), A physically based runoff routing model for land surface and earth system models, *J. Hydrometeorol.*, *14*, 808–828.
- Li, H.-Y., L. R. Leung, A. Getirana, M. Huang, H. Wu, Y. Xu, J. Guo, and N. Voisin (2015), Evaluating global streamflow simulations by a physically-based routing model coupled with the Community Land Model, *J. Hydrometeorol.*, *16*, 948–971, doi:10.1175/JHM-D-14-0079.1.
- Liang, X., D. P. Lettenmaier, E. F. Wood, and S. J. Burges (1994), A simple hydrologically based model of land-surface water and energy fluxes for General Circulation Models, *J. Geophys. Res.*, *99*, 14,415–14,428, doi:10.1029/94JD00483.
- Liang, X., E. F. Wood, and D. P. Lettenmaier (1996), Surface soil moisture parameterization of the VIC-2L model: Evaluation and modification, *Global Planet. Change*, *13*, 195–206, doi:10.1016/0921-8181(95)00046-1.
- Liang, X., Z. Xie, and M. Huang (2003), A new parameterization for surface and groundwater interactions and its impact on water budgets with the variable infiltration capacity (VIC) land surface model, *J. Geophys. Res.*, *108*(D16), 8613, doi:10.1029/2002JD003090.
- Lohmann, D., R. Nolte-Holube, and E. Raschke (1996), A large-scale horizontal routing model to be coupled to land surface parametrization schemes, *Tellus, Ser. A*, *48*, 708–721.
- Lohmann, D., et al. (1998a), The Project for Intercomparison of Land-surface Parameterization Schemes (PILPS) phase 2(c) Red-Arkansas River basin experiment: 3. Spatial and temporal analysis of water fluxes, *Global Planet. Change*, *19*, 161–179, doi:10.1016/s0921-8181(98)00046-0.
- Lohmann, D., E. Raschke, B. Nijssen, and D. P. Lettenmaier (1998b), Regional scale hydrology: I. Formulation of the VIC-2L model coupled to a routing model, *Hydrol. Sci. J.*, *43*, 131–141, doi:10.1080/02626669809492107.
- Lohmann, D., K. E. Mitchell, P. R. Houser, E. F. Wood, J. C. Schaake, A. Robock, B. A. Cosgrove, J. Sheffield, Q. Duan, and L. Luo (2004), Streamflow and water balance intercomparisons of four land surface models in the North American Land Data Assimilation System project, *J. Geophys. Res.*, *109*, D07S91, doi:10.1029/2003JD003517.
- Luo, L. F., et al. (2003), Effects of frozen soil on soil temperature, spring infiltration, and runoff: Results from the PILPS 2(d) experiment at Valdai, Russia, *J. Hydrometeorol.*, *4*, 334–351, doi:10.1175/1525-7541(2003)4<334:EOFSOS>2.0.CO;2.
- Luo, Y., J. Randerson, G. Abramowitz, C. Bacour, E. Blyth, N. Carvalhais, P. Ciais, D. Dalmonech, J. Fisher, and R. Fisher (2012), A framework of benchmarking land models, *Biogeosci.*, *9*, 3857–3874.
- Mackay, D. S., D. E. Ahl, B. E. Ewers, S. Samanta, S. T. Gower, and S. N. Burrows (2003), Physiological tradeoffs in the parameterization of a model of canopy transpiration, *Adv. Water Resour.*, *26*, 179–194.
- Mahrt, L. (1987), Grid-averaged surface fluxes, *Mon. Weather Rev.*, *115*, 1550–1560, doi:10.1175/1520-0493(1987)115<1550:GASF>2.0.CO;2.
- Mahrt, L. (2000), Surface heterogeneity and vertical structure of the boundary layer, *Boundary Layer Meteorol.*, *96*, 33–62.
- Manabe, S. (1969), Climate and the ocean circulation: I. The atmospheric circulation and the hydrology of the earth's surface, *Mon. Weather Rev.*, *97*, 739–774.
- Manabe, S., J. Smagorinsky, and R. F. Strickler (1965), Simulated climatology of a general circulation model with a hydrologic cycle, *Mon. Weather Rev.*, *93*, 769–798.
- Manoli, G., S. Bonetti, J.-C. Domec, M. Putti, G. Katul, and M. Marani (2014), Tree root systems competing for soil moisture in a 3D soil–plant model, *Adv. Water Resour.*, *66*, 32–42.
- Manzoni, S., G. Vico, A. Porporato, and G. Katul (2013), Biological constraints on water transport in the soil–plant–atmosphere system, *Adv. Water Resour.*, *51*, 292–304, doi:10.1016/j.advwatres.2012.03.016.
- Marble, J., and J. A. Lough (1997), The storage and aging of continental runoff in large reservoir systems of the world, *Ambio*, *26*, 210–219.
- Maxwell, R. M. (2010), Infiltration in arid environments: Spatial patterns between subsurface heterogeneity and water-energy balances, *Vadose Zone J.*, *9*, 970–983, doi:10.2136/vzj2010.0014.
- Maxwell, R. M., and S. J. Kollet (2008a), Quantifying the effects of three-dimensional subsurface heterogeneity on Hortonian runoff processes using a coupled numerical, stochastic approach, *Adv. Water Resour.*, *31*, 807–817, doi:10.1016/j.advwatres.2008.01.020.
- Maxwell, R. M., and S. J. Kollet (2008b), Interdependence of groundwater dynamics and land-energy feedbacks under climate change, *Nat. Geosci.*, *1*, 665–669, doi:10.1038/ngeo315.
- Maxwell, R. M., and N. L. Miller (2005), Development of a coupled land surface and groundwater model, *J. Hydrometeorol.*, *6*, 233–247, doi:10.1175/JHM422.1.
- Maxwell, R. M., F. K. Chow, and S. J. Kollet (2007), The groundwater–land–surface–atmosphere connection: Soil moisture effects on the atmospheric boundary layer in fully-coupled simulations, *Adv. Water Resour.*, *30*, 2447–2466, doi:10.1016/j.advwatres.2007.05.018.
- Maxwell, R. M., J. K. Lundquist, J. D. Mirocha, S. G. Smith, C. S. Woodward, and A. F. Tompson (2011), Development of a coupled groundwater–atmosphere model, *Mon. Weather Rev.*, *139*, 96–116.
- Maxwell, R. M., et al. (2014), Surface–subsurface model intercomparison: A first set of benchmark results to diagnose integrated hydrology and feedbacks, *Water Resour. Res.*, *50*, 1531–1549, doi:10.1002/2013WR013725.
- Maxwell, R. M., L. E. Condon, and S. J. Kollet (2015), A high resolution simulation of groundwater and surface water over most of the continental US with the integrated hydrologic model ParFlow v3, *Geosci. Model Dev.*, *8*, 923–937, doi:10.5194/gmdd-7-7317-2014.
- McDonnell, J., et al. (2007), Moving beyond heterogeneity and process complexity: A new vision for watershed hydrology, *Water Resour. Res.*, *43*, W07301, doi:10.1029/2006WR005467.
- McDowell, N. G., et al. (2013), Evaluating theories of drought-induced vegetation mortality using a multimodel-experiment framework, *New Phytol.*, *200*, 304–321, doi:10.1111/nph.12465.

- Mendoza, P., M. Clark, M. Barlage, B. Rajagopalan, L. Samaniego, G. Abramowitz, and H. V. Gupta (2015), Are we unnecessarily constraining the agility of complex process-based models?, *Water Resour. Res.*, *51*, 716–728, doi:10.1002/2014WR015820.
- Mersel, M. K., L. C. Smith, K. M. Andreadis, and M. T. Durand (2013), Estimation of river depth from remotely sensed hydraulic relationships, *Water Resour. Res.*, *49*, 3165–3179, doi:10.1002/wrcr.20176.
- Miguez-Macho, G., and Y. Fan (2012a), The role of groundwater in the Amazon water cycle: 1. Influence on seasonal streamflow, flooding and wetlands, *J. Geophys. Res.*, *117*, D15113, doi:10.1029/2012JD017539.
- Miguez-Macho, G., and Y. Fan (2012b), The role of groundwater in the Amazon water cycle: 2. Influence on seasonal soil moisture and evapotranspiration, *J. Geophys. Res.*, *117*, D15114, doi:10.1029/2012JD017540.
- Miguez-Macho, G., Y. Fan, C. P. Weaver, R. Walko, and A. Robock (2007), Incorporating water table dynamics in climate modeling: 2. Formulation, validation, and soil moisture simulation, *J. Geophys. Res.*, *112*, D13108, doi:10.1029/2006JD008112.
- Miller, C. T., C. Abhishek, and M. W. Farthing (2006), A spatially and temporally adaptive solution of Richards' equation, *Adv. Water Resour.*, *29*, 525–545, doi:10.1016/j.advwatres.2005.06.008.
- Milly, P., and K. A. Dunne (2011), On the hydrologic adjustment of climate-model projections: The potential pitfall of potential evapotranspiration, *Earth Interact.*, *15*, 1–14.
- Milly, P. C. D., S. L. Malyshev, E. Shevliakova, K. A. Dunne, K. L. Findell, T. Gleeson, Z. Liang, P. Philipps, R. J. Stouffer, and S. Swenson (2014), An enhanced model of land water and energy for global hydrologic and earth-system studies, *J. Hydrometeorol.*, *15*, 1739–1761, doi:10.1175/JHM-D-13-0162.1.
- Mizumura, K. (2006), Analytical solutions of nonlinear kinematic wave model, *J. Hydrol. Eng.*, *11*, 539–546.
- Mizumura, K., and Y. Ito (2010), Analytical solution of nonlinear kinematic wave model with time-varying rainfall, *J. Hydrol. Eng.*, *16*, 736–745.
- Mizumura, K., and Y. Ito (2011), Influence of moving rainstorms on overland flow of an open book type using kinematic wave, *J. Hydrol. Eng.*, *16*, 926–934.
- Moore, R., and R. Clarke (1981), A distribution function approach to rainfall runoff modeling, *Water Resour. Res.*, *17*, 1367–1382, doi:10.1029/WR017i005p01367.
- Nazemi, A., and H. Wheeler (2015a), On inclusion of water resource management in Earth system models—Part 1: Problem definition and representation of water demand, *Hydrol. Earth Syst. Sci.*, *19*, 33–61.
- Nazemi, A., and H. Wheeler (2015b), On inclusion of water resource management in Earth system models—Part 2: Representation of water supply and allocation and opportunities for improved modeling, *Hydrol. Earth Syst. Sci.*, *19*, 63–90.
- Nearing, G. S., and H. V. Gupta (2014), The quantity and quality of information in hydrologic models, *Water Resour. Res.*, *51*, 524–538, doi:10.1002/2014WR015895.
- Ngo-Duc, T., K. Laval, G. Ramillien, J. Polcher, and A. Cazenave (2007), Validation of the land water storage simulated by Organising Carbon and Hydrology in Dynamic Ecosystems (ORCHIDEE) with Gravity Recovery and Climate Experiment (GRACE) data, *Water Resour. Res.*, *43*, W04427, doi:10.1029/2006WR004941.
- Nijssen, B., G. M. O'Donnell, D. P. Lettenmaier, D. Lohmann, and E. F. Wood (2001), Predicting the discharge of global rivers, *J. Clim.*, *14*, 3307–3323, doi:10.1175/1520-0442(2001)014<3307:PTDOGR>2.0.CO;2.
- Nijssen, B., et al. (2003), Simulation of high latitude hydrological processes in the Torne-Kalix basin: PILPS phase 2(e)—2: Comparison of model results with observations, *Global Planet. Change*, *38*, 31–53, doi:10.1016/S0921-8181(03)00004-3.
- Nimmo, J. R. (2010), Theory for source-responsive and free-surface film modeling of unsaturated flow, *Vadose Zone J.*, *9*, 295–306.
- Niu, G.-Y., and Z. L. Yang (2006), Effects of frozen soil on snowmelt runoff and soil water storage at a continental scale, *J. Hydrometeorol.*, *7*, 937–952, doi:10.1175/JHM538.1.
- Niu, G.-Y., Z. L. Yang, R. E. Dickinson, and L. E. Gulden (2005), A simple TOPMODEL-based runoff parameterization (SIMTOP) for use in global climate models, *J. Geophys. Res.*, *110*, D21106, doi:10.1029/2005JD006111.
- Niu, G.-Y., Z. L. Yang, R. E. Dickinson, L. E. Gulden, and H. Su (2007), Development of a simple groundwater model for use in climate models and evaluation with Gravity Recovery and Climate Experiment data, *J. Geophys. Res.*, *112*, D07103, doi:10.1029/2006JD007522.
- Niu, G.-Y., et al. (2011), The community Noah land surface model with multiparameterization options (Noah-MP): 1. Model description and evaluation with local-scale measurements, *J. Geophys. Res.*, *116*, D12109, doi:10.1029/2010JD015139.
- Niu, G.-Y., C. Paniconi, P. A. Troch, R. L. Scott, M. Durcik, X. Zeng, T. Huxman, and D. C. Goodrich (2014), An integrated modelling framework of catchment-scale ecohydrological processes: 1. Model description and tests over an energy-limited watershed, *Ecohydrology*, *7*, 427–439, doi:10.1002/eco.1362.
- Noh, J.-H., S.-R. Lee, and H. Park (2011), Prediction of cryo-SWCC during freezing based on pore-size distribution, *Int. J. Geomech.*, *12*, 428–438, doi:10.1061/(ASCE)GM.1943-5622.0000134.
- Norby, R. J., and R. B. Jackson (2000), Root dynamics and global change: Seeking an ecosystem perspective, *New Phytol.*, *147*, 3–12.
- Oleson, K. W., et al. (2010), Technical description of version 4.0 of the Community Land Model, *NCAR Tech. Note NCAR/TN-478+STR*, National Center for Atmospheric Research, Boulder, Colo.
- Painter, S. L. (2011), Three-phase numerical model of water migration in partially frozen geological media: Model formulation, validation, and applications, *Comput. Geosci.*, *15*, 69–85.
- Panday, S., and P. S. Huyakorn (2004), A fully coupled physically-based spatially-distributed model for evaluating surface/subsurface flow, *Adv. Water Resour.*, *27*, 361–382.
- Paniconi, C., P. A. Troch, E. E. van Loon, and A. G. Hilberts (2003), Hillslope storage Boussinesq model for subsurface flow and variable source areas along complex hillslopes: 2. Intercomparison with a three dimensional Richards equation model, *Water Resour. Res.*, *39*(11), 1317, doi:10.1029/2002WR001730.
- Pappenberger, F., E. Dutra, F. Wetterhall, and H. Cloke (2012), Deriving global flood hazard maps of fluvial floods through a physical model cascade, *Hydrol. Earth Syst. Sci.*, *16*, 4143–4156.
- Parker, J., R. Lenhard, and T. Kuppasamy (1987), A parametric model for constitutive properties governing multiphase flow in porous media, *Water Resour. Res.*, *23*, 618–624.
- Parlange, J.-Y., C. Rose, and G. Sander (1981), Kinematic flow approximation of runoff on a plane: An exact analytical solution, *J. Hydrol.*, *52*, 171–176.
- Pau, G., G. Bisht, and W. Riley (2014), A reduced-order modeling approach to represent subgrid-scale hydrological dynamics for land-surface simulations: Application in a polygonal tundra landscape, *Geosci. Model Dev.*, *7*, 2091–2105.
- Pavelsky, T. M., M. T. Durand, K. M. Andreadis, R. E. Beighley, R. C. Paiva, G. H. Allen, and Z. F. Miller (2014), Assessing the potential global extent of SWOT river discharge observations, *J. Hydrol.*, *519*, 1516–1525.
- Pedinotti, V., A. Boone, S. Ricci, S. Biancamaria, and N. Mognard (2014), Assimilation of satellite data to optimize large-scale hydrological model parameters: A case study for the SWOT mission, *Hydrol. Earth Syst. Sci.*, *18*, 4485–4507.

- Perrin, C., C. Michel, and V. Andreassian (2003), Improvement of a parsimonious model for streamflow simulation, *J. Hydrol.*, *279*, 275–289, doi:10.1016/S0022-1694(03)00225-7.
- Pitman, A. (2003), The evolution of, and revolution in, land surface schemes designed for climate models, *Int. J. Climatol.*, *23*, 479–510.
- Pitman, A., A. Henderson-Sellers, and Z. Yang (1990), Sensitivity of regional climates to localized precipitation in global models, *Nature*, *346*, 734–737.
- Poff, N. L., J. D. Allan, M. B. Bain, J. R. Karr, K. L. Prestegard, B. D. Richter, R. E. Sparks, and J. C. Stromberg (1997), The natural flow regime, *BioScience*, *47*, 769–784.
- Pokhrel, Y., N. Hanasaki, S. Koirala, J. Cho, P. J.-F. Yeh, H. Kim, S. Kanae, and T. Oki (2012), Incorporating anthropogenic water regulation modules into a land surface model, *J. Hydrometeorol.*, *13*, 255–269.
- Powell, T. L., et al. (2013), Confronting model predictions of carbon fluxes with measurements of Amazon forests subjected to experimental drought, *New Phytol.*, *200*, 350–365, doi:10.1111/nph.12390.
- Qu, Y. Z., and C. J. Duffy (2007), A semidiscrete finite volume formulation for multiprocess watershed simulation, *Water Resour. Res.*, *43*, W08419, doi:10.1029/2006WR005752.
- Quijano, J. C., P. Kumar, D. T. Drewry, A. Goldstein, and L. Misson (2012), Competitive and mutualistic dependencies in multispecies vegetation dynamics enabled by hydraulic redistribution, *Water Resour. Res.*, *48*, W05518, doi:10.1029/2011WR011416.
- Reba, M. L., D. Marks, M. Seyfried, A. Winstral, M. Kumar, and G. Flerchinger (2011), A long-term data set for hydrologic modeling in a snow-dominated mountain catchment, *Water Resour. Res.*, *47*, W07702, doi:10.1029/2010WR010030.
- Riley, W., and C. Shen (2014), Characterizing coarse-resolution watershed soil moisture heterogeneity using fine-scale simulations, *Hydrol. Earth Syst. Sci.*, *18*, 2463–2483.
- Rupp, D. E., and J. S. Selker (2005), Drainage of a horizontal Boussinesq aquifer with a power law hydraulic conductivity profile, *Water Resour. Res.*, *41*, W11422, doi:10.1029/2005WR004241.
- Rupp, D. E., and J. S. Selker (2006), On the use of the Boussinesq equation for interpreting recession hydrographs from sloping aquifers, *Water Resour. Res.*, *42*, W12421, doi:10.1029/2006WR005080.
- Sacks, W. J., B. I. Cook, N. Buenning, S. Levis, and J. H. Helkowski (2009), Effects of global irrigation on the near-surface climate, *Clim. Dyn.*, *33*, 159–175.
- Samaniego, L., R. Kumar, and S. Attinger (2010), Multiscale parameter regionalization of a grid-based hydrologic model at the mesoscale, *Water Resour. Res.*, *46*, W05523, doi:10.1029/2008WR007327.
- Schaake, J. C., V. I. Koren, Q. Y. Duan, K. Mitchell, and F. Chen (1996), Simple water balance model for estimating runoff at different spatial and temporal scales, *J. Geophys. Res.*, *101*, 7461–7475, doi:10.1029/95JD02892.
- Schaeffli, B., and H. V. Gupta (2007), Do Nash values have value?, *Hydrol. Processes*, *21*, 2075–2080.
- Schenk, H. J., and R. B. Jackson (2002), Rooting depths, lateral root spreads and below-ground/above-ground allometries of plants in water-limited ecosystems, *J. Ecol.*, *90*, 480–494.
- Schymanski, S., M. Sivapalan, M. Roderick, J. Beringer, and L. Hutley (2008), An optimality-based model of the coupled soil moisture and root dynamics, *Hydrol. Earth Syst. Sci.*, *12*, 913–932.
- Seibert, J., and J. J. McDonnell (2002), On the dialog between experimentalist and modeler in catchment hydrology: Use of soft data for multicriteria model calibration, *Water Resour. Res.*, *38*(11), 1241, doi:10.1029/2001WR000978.
- Sellers, P., R. Dickinson, D. Randall, A. Betts, F. Hall, J. Berry, G. Collatz, A. Denning, H. Mooney, and C. Nobre (1997), Modeling the exchanges of energy, water, and carbon between continents and the atmosphere, *Science*, *275*, 502–509.
- Shen, C., and M. S. Phanikumar (2010), A process-based, distributed hydrologic model based on a large-scale method for surface–subsurface coupling, *Adv. Water Resour.*, *33*, 1524–1541.
- Shen, C., J. Niu, and M. S. Phanikumar (2013), Evaluating controls on coupled hydrologic and vegetation dynamics in a humid continental climate watershed using a subsurface–land surface processes model, *Water Resour. Res.*, *49*, 2552–2572, doi:10.1002/wrcr.20189.
- Shen, C., J. Niu, and K. Fang (2014), Quantifying the effects of data integration algorithms on the outcomes of a subsurface–land surface processes model, *Environ. Modell. Software*, *59*, 146–161.
- Shi, Y., K. J. Davis, C. J. Duffy, and X. Yu (2013), Development of a coupled land surface hydrologic model and evaluation at a critical zone observatory, *J. Hydrometeorol.*, *14*, 1401–1420.
- Shi, Y., K. J. Davis, F. Zhang, and C. J. Duffy (2014), Evaluation of the parameter sensitivities of a coupled land surface hydrologic model at a critical zone observatory, *J. Hydrometeorol.*, *15*, 279–299.
- Shuttleworth, W. J. (1988), Macrohydrology—The new challenge for process hydrology, *J. Hydrol.*, *100*, 31–56.
- Simunek, J., N. J. Jarvis, M. T. van Genuchten, and A. Gardenas (2003), Review and comparison of models for describing non-equilibrium and preferential flow and transport in the vadose zone, *J. Hydrol.*, *272*, 14–35, doi:10.1016/S0022-1694(02)00252-4.
- Skamarock, W. C., J. B. Klemp, M. G. Duda, L. D. Fowler, S.-H. Park, and T. D. Ringler (2012), A multiscale nonhydrostatic atmospheric model using centroidal Voronoi tessellations and C-grid staggering, *Mon. Weather Rev.*, *140*, 3090–3105.
- Smits, K. M., V. V. Ngo, A. Cihan, T. Sakaki, and T. H. Illangasekare (2012), An evaluation of models of bare soil evaporation formulated with different land surface boundary conditions and assumptions, *Water Resour. Res.*, *48*, W12526, doi:10.1029/2012WR012113.
- Sperry, J., U. Hacke, R. Oren, and J. Comstock (2002), Water deficits and hydraulic limits to leaf water supply, *Plant Cell Environ.*, *25*, 251–263.
- Sperry, J. S., F. R. Adler, G. S. Campbell, and J. P. Comstock (1998), Limitation of plant water use by rhizosphere and xylem conductance: Results from a model, *Plant Cell Environ.*, *21*, 347–359.
- Stöckle, C. O., A. R. Kemanian, R. L. Nelson, J. C. Adam, R. Sommer, and B. Carlson (2014), CropSyst model evolution: From field to regional to global scales and from research to decision support systems, *Environ. Modell. Software*, *62*, 361–369.
- Subin, Z., P. Milly, B. Sulman, S. Malyshev, and E. Shevliakova (2014), Resolving terrestrial ecosystem processes along a subgrid topographic gradient for an earth-system model, *Hydrol. Earth Syst. Sci. Discuss.*, *11*, 8443–8492.
- Swenson, S., and D. Lawrence (2012), A new fractional snow-covered area parameterization for the Community Land Model and its effect on the surface energy balance, *J. Geophys. Res.*, *117*, D21107, doi:10.1029/2012JD018178.
- Swenson, S., and D. Lawrence (2014), Assessing a dry surface layer-based soil resistance parameterization for the Community Land Model using GRACE and FLUXNET-MTE data, *J. Geophys. Res. Atmos.*, *119*, 10,299–10,312, doi:10.1002/2014JD022314.
- Swenson, S., D. Lawrence, and H. Lee (2012), Improved simulation of the terrestrial hydrological cycle in permafrost regions by the Community Land Model, *J. Adv. Model. Earth Syst.*, *4*, M08002, doi:10.1029/2012MS000165.
- Takata, K., S. Emori, and T. Watanabe (2003), Development of the minimal advanced treatments of surface interaction and runoff, *Global Planet. Change*, *38*, 209–222, doi:10.1016/S0921-8181(03)00030-4.
- Taylor, R. G., B. Scanlon, P. Döll, M. Rodell, R. Van Beek, Y. Wada, L. Longuevergne, M. Leblanc, J. S. Famiglietti, and M. Edmunds (2013), Ground water and climate change, *Nat. Clim. Change*, *3*, 322–329.

- Tesfa, T. K., D. G. Tarboton, D. G. Chandler, and J. P. McNamara (2009), Modeling soil depth from topographic and land cover attributes, *Water Resour. Res.*, *45*, W10438, doi:10.1029/2008WR007474.
- Therrien, R., R. McLaren, E. Sudicky, and S. Panday (2010), *HydroGeoSphere: A Three-Dimensional Numerical Model Describing Fully-Integrated Subsurface and Surface Flow and Solute Transport*, Groundwater Simul. Group, Univ. of Waterloo, Waterloo, Ont., Canada.
- Tocci, M. D., C. Kelley, and C. T. Miller (1997), Accurate and economical solution of the pressure-head form of Richards' equation by the method of lines, *Adv. Water Resour.*, *20*, 1–14.
- Troch, P. A., C. Paniconi, and L. Emiel van (2003), Hillslope-storage Boussinesq model for subsurface flow and variable source areas along complex hillslopes: 1. Formulation and characteristic response, *Water Resour. Res.*, *39*(11), 1316, doi:10.1029/2002WR001728.
- Troch, P. A., A. Berne, P. Bogaart, C. Harman, A. G. Hilberts, S. W. Lyon, C. Paniconi, V. Pauwels, D. E. Rupp, and J. S. Selker (2013), The importance of hydraulic groundwater theory in catchment hydrology: The legacy of Wilfried Brutsaert and Jean-Yves Parlange, *Water Resour. Res.*, *49*, 5099–5116, doi:10.1002/wrcr.20407.
- van den Hurk, B., M. Best, P. Dirmeyer, A. Pitman, J. Polcher, and J. Santanello (2011), Acceleration of land surface model development over a decade of GLASS, *Bull. Am. Meteorol. Soc.*, *92*, 1593–1600.
- Van Genuchten, M. T. (1980), A closed-form equation for predicting the hydraulic conductivity of unsaturated soils, *Soil Sci. Soc. Am. J.*, *44*(5), 892–898, doi:10.2136/sssaj1980.03615995004400050002x.
- Vanderborght, J., R. Kasteel, M. Herbst, M. Javaux, D. Thiery, M. Vanclooster, C. Mouvet, and H. Vereecken (2005), A set of analytical benchmarks to test numerical models of flow and transport in soils, *Vadose Zone J.*, *4*, 206–221.
- VanderKwaak, J. E., and K. Loague (2001), Hydrologic-response simulations for the R-5 catchment with a comprehensive physics-based model, *Water Resour. Res.*, *37*, 999–1013, doi:10.1029/2000WR900272.
- Vaze, J., D. Post, F. Chiew, J.-M. Perraud, N. Viney, and J. Teng (2010), Climate non-stationarity—validity of calibrated rainfall—runoff models for use in climate change studies, *J. Hydrol.*, *394*, 447–457.
- Verant, S., K. Laval, J. Polcher, and M. De Castro (2004), Sensitivity of the continental hydrological cycle to the spatial resolution over the Iberian Peninsula, *J. Hydrometeorol.*, *5*, 267–285.
- Vivoni, E. R., V. Y. Ivanov, R. L. Bras, and D. Entekhabi (2004), Generation of triangulated irregular networks based on hydrological similarity, *J. Hydrol. Eng.*, *9*, 288–302, doi:10.1061/(ASCE)1084-0699(2004)9:4(288).
- Vivoni, E. R., V. Teles, V. Y. Ivanov, R. L. Bras, and D. Entekhabi (2005), Embedding landscape processes into triangulated terrain models, *Int. J. Geogr. Inf. Sci.*, *19*, 429–457, doi:10.1080/13658810512331325111.
- Voisin, N., H. Li, D. Ward, M. Huang, M. Wigmosta, and L. Leung (2013a), On an improved sub-regional water resources management representation for integration into earth system models, *Hydrol. Earth Syst. Sci.*, *17*, 3605–3622.
- Voisin, N., L. Liu, M. Hejazi, T. Tesfa, H. Li, M. Huang, Y. Liu, and L. Leung (2013b), One-way coupling of an integrated assessment model and a water resources model: Evaluation and implications of future changes over the US Midwest, *Hydrol. Earth Syst. Sci.*, *17*, 4555–4575.
- Wagener, T., M. Sivapalan, P. Troch, and R. Woods (2007), Catchment classification and hydrologic similarity, *Geogr. Compass*, *1*, 901–931.
- Walko, R. L., et al. (2000), Coupled atmosphere-biophysics-hydrology models for environmental modeling, *J. Appl. Meteorol.*, *39*, 931–944, doi:10.1175/1520-0450(2000)039<0931:CABHMF>2.0.CO;2.
- Wang, Y.-P., and R. Leuning (1998), A two-leaf model for canopy conductance, photosynthesis and partitioning of available energy. I: Model description and comparison with a multi-layered model, *Agric. For. Meteorol.*, *91*, 89–111, doi:10.1016/S0168-1923(98)00061-6.
- Wang, Y.-P., E. Kowalczyk, R. Leuning, G. Abramowitz, M. R. Raupach, B. Pak, E. van Gorsel, and A. Luhar (2011), Diagnosing errors in a land surface model (CABLE) in the time and frequency domains, *J. Geophys. Res.*, *116*, G01034, doi:10.1029/2010JG001385.
- Weiler, M. (2005), An infiltration model based on flow variability in macropores: Development, sensitivity analysis and applications, *J. Hydrol.*, *310*, 294–315.
- Western, A. W., R. B. Grayson, G. Blöschl, G. R. Willgoose, and T. A. McMahon (1999), Observed spatial organization of soil moisture and its relation to terrain indices, *Water Resour. Res.*, *35*, 797–810.
- Wigmosta, M. S., and D. P. Lettenmaier (1999), A comparison of simplified methods for routing topographically driven subsurface flow, *Water Resour. Res.*, *35*, 255–264, doi:10.1029/1998WR900017.
- Williams, M., B. E. Law, P. M. Anthoni, and M. H. Unsworth (2001), Use of a simulation model and ecosystem flux data to examine carbon–water interactions in ponderosa pine, *Tree Physiol.*, *21*, 287–298.
- Wood, E. F., D. P. Lettenmaier, and V. G. Zartarian (1992), A land surface hydrology parameterization with sub grid variability for general circulation models, *J. Geophys. Res.*, *97*, 2717–2728, doi:10.1029/91JD01786.
- Wood, E. F., and Coauthors (2012), Reply to comment by Keith J. Beven and Hannah L. Cloke on "Hyperresolution global land surface modeling: Meeting a grand challenge for monitoring Earth's terrestrial water", *Water Resour. Res.*, *48*, W01802, doi:10.1029/2011WR011202.
- Wu, H., J. S. Kimball, H. Li, M. Huang, L. R. Leung, and R. F. Adler (2012), A new global river network database for macroscale hydrologic modeling, *Water Resour. Res.*, *48*, W09701, doi:10.1029/2012WR012313.
- Wu, W. (2008), *Computational River Dynamics*, CRC Press, Leiden, Netherlands.
- Xia, Y., K. Mitchell, M. Ek, B. Cosgrove, J. Sheffield, L. Luo, C. Alonge, H. Wei, J. Meng, and B. Livneh (2012a), Continental-scale water and energy flux analysis and validation for North American Land Data Assimilation System project phase 2 (NLDAS-2): 2. Validation of model-simulated streamflow, *J. Geophys. Res.*, *117*, D03110, doi:10.1029/2011JD016051.
- Xia, Y., K. Mitchell, M. Ek, J. Sheffield, B. Cosgrove, E. Wood, L. Luo, C. Alonge, H. Wei, and J. Meng (2012b), Continental-scale water and energy flux analysis and validation for the North American Land Data Assimilation System project phase 2 (NLDAS-2): 1. Intercomparison and application of model products, *J. Geophys. Res.*, *117*, D03109, doi:10.1029/2011JD016048.
- Yamazaki, D., S. Kanae, H. Kim, and T. Oki (2011), A physically based description of floodplain inundation dynamics in a global river routing model, *Water Resour. Res.*, *47*, W04501, doi:10.1029/2010WR009726.
- Yamazaki, D., H. Lee, D. E. Alsdorf, E. Dutra, H. Kim, S. Kanae, and T. Oki (2012), Analysis of the water level dynamics simulated by a global river model: A case study in the Amazon River, *Water Resour. Res.*, *48*, W09508, doi:10.1029/2012WR011869.
- Yamazaki, D., G. A. Almeida, and P. D. Bates (2013), Improving computational efficiency in global river models by implementing the local inertial flow equation and a vector-based river network map, *Water Resour. Res.*, *49*, 7221–7235, doi:10.1002/wrcr.20552.
- Yeh, P. J., and E. A. Eltahir (2005a), Representation of water table dynamics in a land surface scheme. Part I: Model development, *J. Clim.*, *18*, 1861–1880.
- Yeh, P. J., and E. A. Eltahir (2005b), Representation of water table dynamics in a land surface scheme. Part II: Subgrid variability, *J. Clim.*, *18*, 1881–1901.
- Yilmaz, K. K., H. V. Gupta, and T. Wagener (2008), A process-based diagnostic approach to model evaluation: Application to the NWS distributed hydrologic model, *Water Resour. Res.*, *44*, W09417, doi:10.1029/2007WR006716.

- Yu, X., C. Duffy, D. C. Baldwin, and H. Lin (2014), The role of macropores and multi-resolution soil survey datasets for distributed surface–subsurface flow modeling, *J. Hydrol.*, *516*, 97–106.
- Zea-Cabrera, E., Y. Iwasa, S. Levin, and I. Rodríguez-Iturbe (2006), Tragedy of the commons in plant water use, *Water Resour. Res.*, *42*, W06D02, doi:10.1029/2005WR004514.
- Zektser, S., H. A. Loáiciga, and J. Wolf (2005), Environmental impacts of groundwater overdraft: Selected case studies in the southwestern United States, *Environ. Geol.*, *47*, 396–404.
- Zeng, X. (2001), Global vegetation root distribution for land modeling, *J. Hydrometeorol.*, *2*, 525–530.
- Zeng, X., and M. Decker (2010), Reply, *J. Hydrometeorol.*, *11*, 1051–1054.
- Zeng, X., Y. J. Dai, R. E. Dickinson, and M. Shaikh (1998), The role of root distribution for climate simulation over land, *Geophys. Res. Lett.*, *25*, 4533–4536.
- Zeng, X. B., and M. Decker (2009), Improving the numerical solution of soil moisture-based Richards equation for Land Models with a deep or shallow water table, *J. Hydrometeorol.*, *10*, 308–319, doi:10.1175/2008JHM1011.1.
- Zeng, Y., Z. Su, L. Wan, and J. Wen (2011), Numerical analysis of air-water-heat flow in unsaturated soil: Is it necessary to consider airflow in land surface models?, *J. Geophys. Res.*, *116*, D20107, doi:10.1029/2011JD015835.