

This is the accepted version of the following article: Nadarajah, N. and Teunissen, P. 2014. Instantaneous GPS/Galileo/QZSS/SBAS Attitude Determination: A Single-Frequency (L1/E1) Robustness Analysis under Constrained Environments. Navigation: Journal of the Institute of Navigation. 61 (1): pp. 65-75, which has been published in final form at <http://doi.org/10.1002/navi.51>

# Instantaneous GPS/Galileo/QZSS/SBAS Attitude

## Determination: A Single-Frequency (L1/E1)

### Robustness Analysis under Constrained Environments

N. Nadarajah<sup>1</sup> and P. J. G. Teunissen<sup>1,2</sup>

<sup>1</sup>*GNSS Research Centre, Curtin University, Perth, Australia*

<sup>2</sup>*Department of Remote Sensing and Geosciences, Delft University of Technology, Delft, The Netherlands*

#### ABSTRACT

The augmentation of new global navigation satellite systems (GNSS) and regional navigation satellite systems (RNSS) to existing GPS enhances the availability of satellite based positioning, navigation, and timing (PNT) solutions. A combined GNSS constellation will significantly increase the number of visible satellites and thus will improve the geometry of observed satellites, enabling improvements in PNT solution availability, reliability, and accuracy. Among existing systems, the European Galileo system, the Japanese quasi-zenith satellite system (QZSS), and satellite based augmented system (SBAS) share at least one frequency (L1/E1) with GPS. In this contribution, we analyse the robustness of pure single-frequency carrier-phase attitude determination using these four systems under constrained environments.

The successful resolution of the integer carrier phase ambiguities is the key to precise attitude determination using multiple GNSS antennas mounted on a platform. Making use of the known baseline length of rigidly fixed antennas, the constrained Least-squares AMBiguity Decorrelation Adjustment (C-LAMBDA) method yields high integer resolution success rates. In this contribution we analyse the performance of the C-LAMBDA method and compare it to the standard LAMBDA method using single-frequency data from four systems (GPS/Galileo/QZSS/SBAS) under constrained environments. Our analyses include robustness studies of C-LAMBDA method under various satellite deprived environments such as satellite outage, open-pit and urban canyon environments using real data consisting of L1/E1 observations from GPS, Galileo, QZSS, GAGAN, and MSAS collected for ten days at Curtin University, Australia. The results demonstrate the enhanced robustness that four systems bring to single-epoch single-frequency attitude determination.

**Keywords:** GPS, Galileo, QZSS, SBAS, single-frequency attitude determination, C-LAMBDA

## 1 INTRODUCTION

2 Single-frequency positioning, navigation, and timing (PNT) using global navigation satellite systems (GNSS) is of interest  
3 for low-cost applications such as navigating unmanned aerial vehicles (UAVs). Augmenting new GNSS and regional navi-  
4 gation satellite systems (RNSS) to existing GPS enhances the availability of PNT solutions. Among existing systems, the  
5 European Galileo system, the Japanese quasi-zenith satellite system (QZSS), and satellite based augmentation system (SBAS),  
6 which includes the US WAAS, the European EGNOS, the Japanese MSAS, and the Indian GAGAN, share at least L1/E1 frequency  
7 with GPS. In this contribution, we analyse the robustness of pure single-frequency (L1/E1) instantaneous attitude determi-  
8 nation under constrained environments using current constellations of the above systems.

9 GNSS attitude determination is a rich field of current studies, with a wide variety of challenging (terrestrial, sea, air and  
10 space) applications [1–9]. Carrier phase integer ambiguity resolution is the key to fast and high-precision GNSS positioning  
11 and attitude determination. Once this has been done successfully, the carrier phase data will act as very precise pseudo range  
12 data, thus making very precise positioning and attitude determination possible. Recent attitude determination methods make  
13 use of the popular LAMBDA method, see e.g. [10–13], as this method is known to be efficient and known to maximize  
14 the ambiguity success rate [14–17]. However, the standard LAMBDA method has been developed for unconstrained GNSS  
15 models. The method is therefore not necessarily optimal for the GNSS attitude determination problem, for which often the  
16 baseline length is provided as well. The Constrained (C-) LAMBDA method [18–22] makes use of this information and  
17 finds the optimal nonlinear constrained integer least-squares solution. This paper demonstrates the effectiveness of the C-  
18 LAMBDA method compared to the standard LAMBDA method in resolving integer ambiguities for attitude determination  
19 using pure single-frequency observations from multi-GNSS, consisting of GPS, Galileo, QZSS, and SBAS.

20 Analyses of PNT solutions using dual system (GPS with one of the other systems) have been reported in various studies. The  
21 performance of the combined GPS-Galileo PNT solutions has been analyzed in [23–27]. The benefit of augmenting GPS  
22 with QZSS is demonstrated in [28]. Beyond the intended functionality, which is to broadcast GNSS error corrections, SBAS  
23 has been proven to contribute to PNT [29–31]. In this contribution, we analyze the performance of combined four-system  
24 attitude determination using real data from identical receivers. Since intersystem biases (ISBs) [26, 32] vanish between  
25 receivers of same type [25, 29], we consider intersystem double differencing, which uses a single pivot satellite for all four  
26 systems and yields a higher level of redundancy than system-specific differencing. In the case of mixed receiver attitude  
27 determination, however, non-zero ISBs must be corrected to retain the advantage of intersystem double differencing [25].

28 In this contribution we concentrate on single-epoch, i.e. instantaneous, attitude determination, as this is the most challeng-  
29 ing for integer ambiguity resolution. Moreover, when successful, it has the additional benefit of making the solutions insensitive  
30 to cycle slips. Our analyses consist of a robustness study of the C-LAMBDA method under different constrained environ-  
31 ments, such as open-pit tracking, the presence of satellite outages, and urban canyon applications. We simulate satellite outages,  
32 open-pit masking, and the urban canyon effect using real data<sub>2</sub> consisting of L1/E1 observations from GPS, Galileo, QZSS,

1 GAGAN, and MSAS, collected for ten days at Curtin University, Perth, Australia. We analyse the corresponding performance  
 2 of the C-LAMBDA method and demonstrate the enhanced robustness of multi-GNSS, single-epoch single-frequency attitude  
 3 determination under such constrained environments. This study is believed to be the first four-system attitude determination anal-  
 4 ysis. This contribution is organized as follows: Section “GNSS-Based Attitude Determination” describes the functional and stochas-  
 5 tic model for GPS/Galileo/QZSS/SBAS observations. It also describes the C-LAMBDA method using the quadratically constrained  
 6 GNSS model for attitude determination. Section “Real-Data Analysis” presents the results of attitude determination reveal-  
 7 ing improved performance of combined system. Finally, Section “Conclusions” contains the summary and conclusions of  
 8 this contribution.

## 9 GNSS-BASED ATTITUDE DETERMINATION

10 In this section we present our attitude determination method using the single frequency combined GPS/Galileo/QZSS/SBAS  
 11 system. First we describe the functional and stochastic model for the combined observations and then we present the steps  
 12 for solving the baseline constrained, mixed-integer attitude model.

### 13 GPS/Galileo/QZSS/SBAS Observations

Let us consider two identical GPS/Galileo/QZSS/SBAS receivers  $r$  and 1 with identical antennas forming a short baseline and collecting observations at L1-frequency. Double differencing is used to eliminate satellite/receiver clock errors and instrumental hardware delays. When combining common frequency observations from multiple systems, one can perform either system-specific double differencing [33] or inter-system double differencing [34,35]. In the latter case, which yields a higher level of redundancy than the former, one should, however, take into account the inter-system bias (ISB) due to system specific hardware delays, more so when mixed receiver types are used. In this work, we consider identical receivers/antennas for which ISBs are known to be absent [25,29]. Also, since attitude determination is based on short baselines, the differential atmospheric delays can be neglected [36]. Hence, the double differenced (DD) pseudo-range and carrier-phase observations for satellite pairs  $1_1$ - $s_\Phi$  of GNSS system pairs  $1$ - $\Phi$  with a single pivot satellite, denoted as  $p_{1r}^{1_1 s_\Phi}$  and  $\phi_{1r}^{1_1 s_\Phi}$  respectively, are given as [25, 27]

$$E\left(p_{1r}^{1_1 s_\Phi}\right) = \rho_{1r}^{1_1 s_\Phi}, \quad s_\Phi = \begin{cases} 2, \dots, m_\Phi & \text{for } \Phi = 1 \\ 1, \dots, m_\Phi & \text{otherwise} \end{cases} \quad (1)$$

$$E\left(\phi_{1r}^{1_1 s_\Phi}\right) = \rho_{1r}^{1_1 s_\Phi} + \lambda N_{1r}^{1_1 s_\Phi}, \quad (2)$$

14 where  $E(\cdot)$  denotes the expectation operator,  $\rho_{1r}^{1_1 s_\Phi}$  is the DD topocentric distance,  $\lambda$  is the wave length,  $N_{1r}^{1_1 s_\Phi}$  is the  
 15 time-invariant *integer* DD carrier-phase ambiguity, and  $m_\Phi$  is the number of satellites from system  $\Phi$ . For simplicity of  
 16 formulation, we assume that satellites are ordered such that first  $m_1$  satellites are of system 1, next  $m_2$  satellites are of

1 system 2, and so on ( $\sum_{\Phi=1}^M m_{\Phi} = m + 1$ , the number of tracked satellites), where  $M$  is the number of systems.

2 The linearized DD observation equations corresponding to (1) and (2), read

$$\text{E}\left(\Delta p_{1r}^{1s\Phi}\right) = g_r^{1s\Phi T} b, \quad (3)$$

$$\text{E}\left(\Delta \phi_{1r}^{1s\Phi}\right) = g_r^{1s\Phi T} b + \lambda N_{1r}^{1s\Phi}, \quad (4)$$

3 where  $\Delta p_{1r}^{1s\Phi}$  and  $\Delta \phi_{1r}^{1s\Phi}$  are the observed-minus-computed code and phase observations,  $b$  is the baseline vector containing  
 4 relative position components, and  $g_r^{1s\Phi}$  is the geometry vector given as  $g_r^{1s\Phi} = e_r^{11} - e_r^{s\Phi}$  with  $e_r^{s\Phi}$  the unit line-of-sight vector  
 5 between receiver-satellite pair  $r - s_{\Phi}$ . The vectorial forms of the DD observation equations read

$$\text{E}(y_p) = G_r b \quad (5)$$

$$\text{E}(y_{\phi}) = G_r b + \lambda z \quad (6)$$

with

$$y_p = \left[ \Delta p_{1r}^{1121}, \dots, \Delta p_{1r}^{11m1}, \Delta p_{1r}^{1112}, \dots, \Delta p_{1r}^{11m2}, \dots, \right. \\ \left. \Delta p_{1r}^{111M}, \dots, \Delta p_{1r}^{11mM} \right]^T \quad (7)$$

$$y_{\phi} = \left[ \Delta \phi_{1r}^{1121}, \dots, \Delta \phi_{1r}^{11m1}, \Delta \phi_{1r}^{1112}, \dots, \Delta \phi_{1r}^{11m2}, \dots, \right. \\ \left. \Delta \phi_{1r}^{111M}, \dots, \Delta \phi_{1r}^{11mM} \right]^T \quad (8)$$

$$G_r = \left[ g_r^{1121}, \dots, g_r^{11m1}, g_r^{1112}, \dots, g_r^{11m2}, \dots, \right. \\ \left. g_r^{111M}, \dots, g_r^{11mM} \right]^T \quad (9)$$

$$z = \left[ N_{1r}^{1121}, \dots, N_{1r}^{11m1}, N_{1r}^{1112}, \dots, N_{1r}^{11m2}, \dots, \right. \\ \left. N_{1r}^{111\eta}, \dots, N_{1r}^{11mM} \right]^T \quad (10)$$

6 For the stochastic modelling (e.g. thermal noise, multipath), we apply elevation dependent weighting [37]. That is, the  
 7 standard deviation of the undifferenced observable  $\zeta$  can be written as

$$\sigma_{\zeta}(\theta) = \sigma_{\zeta_0} \left( 1 + a_{\zeta_0} \exp\left(\frac{-\theta}{\theta_{\zeta_0}}\right) \right) \quad (11)$$

8 where  $\theta$  is the elevation angle of the corresponding satellite, and  $\sigma_{\zeta_0}$ ,  $a_{\zeta_0}$ , and  $\theta_{\zeta_0}$  are model parameters. We further assume  
 9 that the receivers have similar characteristics and that the observation noise standard deviations can be decomposed as

1 follows:

$$\begin{aligned}
\sigma_{\phi_r^{s\Phi}} &= \sigma_r \sigma_{\phi_0}^\Phi v^{s\Phi} \\
\sigma_{p_r^{s\Phi}} &= \sigma_r \sigma_{p_0}^\Phi v^{s\Phi} \\
v^{s\Phi} &= \left(1 + a_0 \exp\left(\frac{-\theta^{s\Phi}}{\theta_0}\right)\right)
\end{aligned} \tag{12}$$

2 where  $\sigma_r$  is the receiver, and  $\sigma_{\phi_0}^\Phi$  and  $\sigma_{p_0}^\Phi$  are observation dependent weightings.

### 3 The GPS/Galileo/QZSS/SBAS Constrained Baseline Model

4 When combining the single-epoch linearized DD GNSS code and phase observation equations of (5) and (6), we obtain the  
5 mixed integer model of observation equations:

$$\begin{aligned}
E(y) = Az + Gb, \quad & z \in \mathbb{Z}^m \quad \text{with } m = \sum_{\Phi=1}^M m_\Phi - 1 \\
& b \in \mathbb{R}^3
\end{aligned} \tag{13}$$

6 where  $y = [y_\phi^T, y_p^T]^T$  is the  $2m \times 1$  vector of linearized (observed-minus-computed) DD carrier-phase and pseudorange  
7 observations,  $z$  is the  $m \times 1$  vector of unknown DD integer ambiguities,  $b$  is  $3 \times 1$  vector of unknown baseline parameters,  
8  $G = e_2 \otimes G_r$  is the  $2m \times 3$  geometry matrix with  $e_n$  the  $n \times 1$  vector of 1's and  $\otimes$  denoting the Kronecker product [38, 39],  
9  $A = [\lambda I_m, 0^T]^T$  is the  $2m \times m$  design matrix with  $I_n$  the identity matrix of size  $n$ .

10 To construct the stochastic model for the observations in (13), consider the undifferenced observations reading as

$$\zeta = [\zeta_1^T, \zeta_2^T]^T \tag{14}$$

11 where  $\zeta_r = [\phi_r^T, p_r^T]^T$ ,  $\phi_r = [\phi_r^{1T}, \dots, \phi_r^{MT}]^T$ ,  $\phi_r^\Phi = [\phi_r^{1\Phi}, \dots, \phi_r^{m\Phi}]^T$ ,  $p_r = [p_r^{1T}, \dots, p_r^{MT}]^T$ ,  $p_r^\Phi = [p_r^{1\Phi}, \dots, p_r^{m\Phi}]^T$ , and  $p_r^{s\Phi}$   
12 and  $\phi_r^{s\Phi}$  are the undifferenced code and phase observations for  $r - s_\Phi$  receiver-satellite pair. Using the noise characteristics  
13 of (12) and assuming the observables to be mutually uncorrelated, the dispersion matrix of the observation vector  $\zeta$  can be  
14 written as

$$D(\zeta) = Q_r \otimes \text{blockdiag}(Q_\phi, Q_p) \tag{15}$$

where  $D(\cdot)$  denotes the dispersion operator,  $Q_r = \text{diag}[\sigma_1^2, \sigma_2^2]$ ,  $Q_\phi = \text{blockdiag}(Q_\phi^1, \dots, Q_\phi^M)$ ,  $Q_\phi^\Phi = (\sigma_{\phi_0}^\Phi)^2 \text{diag}[(v^{1\Phi})^2, \dots, (v^{m\Phi})^2]$ ,  
 $Q_p = \text{blockdiag}(Q_p^1, \dots, Q_p^M)$ , and  $Q_p^\Phi = (\sigma_{p_0}^\Phi)^2 \text{diag}[(v^{1\Phi})^2, \dots, (v^{m\Phi})^2]$  are the co-factor matrices. Using the DD op-

erator  $\mathcal{D}^T = D_1^T \otimes I_2 \otimes D_m^T$ , the dispersion matrix of the DD observations can be written as

$$\begin{aligned} D(y) &= Q_{yy} = D(\mathcal{D}^T \zeta) \\ &= (\sigma_1^2 + \sigma_2^2) I_2 \otimes D_m^T \text{blockdiag}(Q_\phi, Q_p) I_2 \otimes D_m \end{aligned} \quad (16)$$

1 with  $D_n^T = [-e_n, I_n]$  the differencing matrix.

2 The DD observation equations of (13) form, together with the dispersion matrix of (16), a *mixed-integer* Gauss-Markov  
3 model with unknown integer vector  $z \in \mathbb{Z}^m$  and unknown baseline vector  $b \in \mathbb{R}^3$ . This model can be strengthened with the  
4 known baseline length. With the inclusion of the baseline length constraint, we obtain the GNSS compass model [19,20]

$$\begin{aligned} E(y) &= Az + Gb \quad \|b\| = l, z \in \mathbb{Z}^m, b \in \mathbb{R}^3 \\ D(y) &= Q_{yy} \end{aligned} \quad (17)$$

5 where  $l$  is the known baseline length and  $\|\cdot\|$  denotes the unweighted norm. Hence, the baseline is thus now constrained to  
6 lie on a sphere with radius  $l$  ( $\mathbb{S}_l = \{b \in \mathbb{R}^3 \mid \|b\| = l\}$ ). Our objective is to solve for  $b$  in a least-squares sense, thereby taking  
7 the integer constraints on  $z$  and the quadratic constraint on vector  $b$  into account. Hence, the least-squares minimization  
8 problem that will be solved reads

$$\min_{z \in \mathbb{Z}^m, b \in \mathbb{S}_l} \|y - Az - Gb\|_{Q_{yy}}^2 \quad (18)$$

9 with  $\|\cdot\|_Q^2 = (\cdot)^T Q^{-1}(\cdot)$ . It is a quadratically constrained (mixed) integer least-squares (QC-ILS) problem [18], for which  
10 no closed-form solution is available. In the following sections, we describe the method for solving (18).

## 11 The Ambiguity Resolved Attitude

12 We now describe the steps for computing the integer ambiguity resolved attitude angles.

### 13 The real-valued float solution

14 The float solution is defined as the solution of (18) without the constraints. When we ignore the integer constraints on  $z$  and  
15 the quadratic constraint on  $b$ , the float solutions  $\hat{z}$  and  $\hat{b}$ , and their variance-covariance matrices are obtained as follows:

$$\begin{bmatrix} Q_{\hat{z}\hat{z}} & Q_{\hat{z}\hat{b}} \\ Q_{\hat{b}\hat{z}} & Q_{\hat{b}\hat{b}} \end{bmatrix}^{-1} \cdot \begin{bmatrix} \hat{z} \\ \hat{b} \end{bmatrix} = \begin{bmatrix} A^T \\ G^T \end{bmatrix} Q_{yy}^{-1} y \quad (19)$$

1 with

$$\begin{bmatrix} Q_{\hat{z}\hat{z}} & Q_{\hat{z}\hat{b}} \\ Q_{\hat{b}\hat{z}} & Q_{\hat{b}\hat{b}} \end{bmatrix} = \left( \begin{bmatrix} A^T \\ G^T \end{bmatrix} Q_{yy}^{-1} \begin{bmatrix} A & G \end{bmatrix} \right)^{-1}$$

2 The  $z$ -constrained solution of  $b$  and its variance-covariance matrix can be obtained from the float solution as follows

$$\hat{b}(z) = \hat{b} - Q_{\hat{b}\hat{z}} Q_{\hat{z}\hat{z}}^{-1} (\hat{z} - z) \quad (20)$$

$$\begin{aligned} Q_{\hat{b}(z)\hat{b}(z)} &= Q_{\hat{b}\hat{b}} - Q_{\hat{b}\hat{z}} Q_{\hat{z}\hat{z}}^{-1} Q_{\hat{z}\hat{b}} \\ &= (G^T Q_{yy}^{-1} G)^{-1} \end{aligned} \quad (21)$$

Using the above estimators, the original problem in (18) can be decomposed as [20]

$$\begin{aligned} \min_{z \in \mathbb{Z}^m, b \in \mathbb{S}_l} \|y - Az - Gb\|_{Q_{yy}}^2 &= \\ = \|\hat{e}\|_{Q_{yy}}^2 + \min_{z \in \mathbb{Z}^m} \left( \|\hat{z} - z\|_{Q_{\hat{z}\hat{z}}}^2 + \min_{b \in \mathbb{S}_l} \|\hat{b}(z) - b\|_{Q_{\hat{b}(z)\hat{b}(z)}}^2 \right) \end{aligned} \quad (22)$$

3 with  $\hat{e} = y - A\hat{z} - G\hat{b}$  being the vector of least-squares residuals. Note that the first term on the right hand side of (22) does  
4 not depend on the unknown parameters  $z$  and  $b$  and is therefore constant.

## 5 The integer ambiguity resolution

6 Based on the orthogonal decomposition (22), the quadratic constrained integer minimization can be formulated as:

$$\check{z} = \arg \min_{z \in \mathbb{Z}^m} C(z) \quad (23)$$

7 with ambiguity objective function

$$C(z) = \|\hat{z} - z\|_{Q_{\hat{z}\hat{z}}}^2 + \|\hat{b}(z) - \check{b}(z)\|_{Q_{\hat{b}(z)\hat{b}(z)}}^2 \quad (24)$$

8 where

$$\check{b}(z) = \arg \min_{b \in \mathbb{S}_l} \|\hat{b}(z) - b\|_{Q_{\hat{b}(z)\hat{b}(z)}}^2 \quad (25)$$



1 The cost function  $C(z)$  is the sum of two coupled terms: the first weighs the distance from the float ambiguity vector  $\hat{z}$  to the  
2 nearest integer vector  $z$  in the metric of  $Q_{\hat{z}\hat{z}}$ , while the second weighs the distance from the conditional float solution  $\hat{b}(z)$  to  
3 the nearest point on the sphere  $\mathbb{S}_l$  in the metric of  $Q_{\hat{b}(z)\hat{b}(z)}$ .  
4 Unlike with the standard LAMBDA method [40], the search space of the above minimization problem is non-ellipsoidal due  
5 to the presence of the second term in the ambiguity objective function  $C(z)$ . Moreover, its solution requires the computation  
6 of a nonlinear constrained least-squares problem (25) for every integer vector in the search space. In the C-LAMBDA  
7 method, this problem is mitigated through the use of easy-to-evaluate bounding functions [20, 41]. Using these bounding  
8 functions, two strategies, namely the *Expansion* and the *Search and Shrink* strategies, were developed, see e.g. [18, 42].  
9 These techniques avoid the computation of (25) for every integer vector in the search space, and compute the integer  
10 minimizer  $\check{z}$  in an efficient manner.

### 11 **The ambiguity resolved attitude**

12 For a single baseline,  $b$  is related to the Euler-angles  $\xi = [\psi, \theta]^T$ , with  $\psi$  the heading and  $\theta$  the elevation, as  $b(\xi) =$   
13  $lu(\xi)$ , where  $u(\xi) = [c_\theta c_\psi, c_\theta s_\psi, -s_\theta]^T$  with  $s_\alpha = \sin(\alpha)$  and  $c_\alpha = \cos(\alpha)$ . The sought-for attitude angles  $\xi(\check{z})$  are the  
14 reparametrized solution of (25). Using a first order approximation, the formal variance-covariance matrix of the ambiguity  
15 resolved, least-squares estimated heading and elevation angles is given by

$$Q_{\xi\xi} \approx \frac{1}{l^2} \left( J_{u,\xi}(\check{\xi})^T Q_{\hat{b}(z)\hat{b}(z)}^{-1} J_{u,\xi}(\check{\xi}) \right)^{-1} \quad (26)$$

16 with Jacobian matrix

$$J_{u,\xi}(\xi) = \begin{bmatrix} -s_\psi c_\theta & -c_\psi s_\theta \\ c_\psi c_\theta & -s_\psi s_\theta \\ 0 & -c_\theta \end{bmatrix} \quad (27)$$

17 As the results in the next section show, this first order approximation works well. This is due to the fact that the ambiguity  
18 resolved solution is driven by the high precision of the carrier phase observables.

### 19 **REAL-DATA ANALYSIS**

20 In this section the performance analyses of GPS/Galileo/QZSS/SBAS attitude determination using real data are presented.  
21 The data was collected from two TRM59800.00-SCIS antennas mounted on the roof of the Bentley campus building 402 of  
22 Curtin University in Perth, Australia. As shown in Figure 1(a), they form a short baseline ( $l = 8.418$  m, Figure 1(b)).  
23 These antennas are connected to two TRIMBLE NETR9 GNSS receivers continuously tracking all available GNSS satellites.

(a)      (b)  
 An-      An-  
 tenna    tenna  
 setup    ge-  
           om-  
           e-  
           try

**Figure 1.** Curtin GNSS antennas used for the real data campaign

System (Frequency)	Code $\sigma_{p_0}^{\phi}$ [cm]	Phase $\sigma_{\phi_0}^{\phi}$ [mm]
GPS (L1), Galileo (E1), and QZSS (L1)	20	1
SBAS (L1)	240	7

**Table 1.** Elevation dependent stochastic model parameters (cf., equation 12) for undifferenced observables with  $\sigma_r = 1$  for  $r = 1, 2$ ,  $a_{p_0} = a_{\phi_0} = 5$  and  $\epsilon_{p_0} = \epsilon_{\phi_0} = 20$

1 The stochastic model parameters of the elevation dependent model (11) for the receivers are reported in Table 1. The large  
 2 parameter values for SBAS are due to the narrower transmitted signal bandwidth (2.2 MHz) compared to that of other sys-  
 3 tems (e.g., 20 MHz for GPS) [29, 43].  
 4 We considered data from Curtin’s stations for ten days from June 9 to 18, 2013 with a sampling interval of 30 seconds.  
 5 Figure 2 shows the GPS/Galileo/QZSS/SBAS satellite visibility for June 9 (the skyplots, the number of satellites, and the  
 6 PDOP values) demonstrating improved satellite visibility of the combined system.

We consider two performance measures for our analyses; the first one is the empirical instantaneous ambiguity success

(a)(b)(c)  
 Skyplot  
 Number  
 of  
 satellites  
 (GPS/Galileo/  
 QZSS/SBAS)  
 and  
 PDOP  
 values  
 (GPS/Galileo/  
 QZSS/SBAS)  
 J1,  
 GAGAN:  
 S27  
 and  
 S28,  
 and  
 MSAS:  
 S29  
 and  
 S37)

**Figure 2.** Satellite visibility of GPS, Galileo, QZSS, and SBAS (GAGAN+MSAS) constellations on June 9, 2013 for  $10^\circ$  elevation cut-off

Systems (PDOP)	Success Fraction		Angular Standard deviation [deg]	
	LAMBDA	C-LAMBDA	Heading	Elevation
GPS (2.00)	0.85	0.99	0.01 (0.02)	0.04 (0.04)
GPS/Galileo (1.87)	0.92	1.00	0.01 (0.01)	0.03 (0.03)
GPS/QZSS (1.87)	0.94	1.00	0.01 (0.01)	0.03 (0.03)
GPS/GAGAN (1.72)	0.93	1.00	0.01 (0.02)	0.04 (0.04)
GPS/MSAS (1.87)	0.95	1.00	0.01 (0.02)	0.04 (0.04)
GPS/SBAS (1.63)	0.98	1.00	0.01 (0.01)	0.04 (0.04)
GPS/Galileo/QZSS/SBAS (1.50)	<b>1.00</b>	1.00	0.01 (0.01)	0.03 (0.03)
Galileo/QZSS/SBAS (5.75)/0.88	0.07	0.34	0.07 (0.07)	0.25 (0.20)

**Table 2.** Instantaneous ambiguity success fractions (relative frequencies) and angular accuracy measured by empirical and formal (given in brackets) angular standard deviations. SBAS consists of two GAGAN and two MSAS satellites. For the combined Galileo/QZSS/SBAS constellation, only a fraction of epochs (given in emphasized text) was processed due to the poor satellite geometry (PDOP > 100)

fraction (relative frequency), which is defined as

$$\text{success fraction} = \frac{\text{number of correctly fixed epochs}}{\text{total number of epochs}} \quad (28)$$

1 where the true ambiguities are computed using known antenna coordinates in WGS84 as the antennas used are part of Curtin's  
2 permanent stations. However, only length information is used for C-LAMBDA processing. The second performance mea-  
3 sure is the ambiguity fixed angular estimation accuracy, which is given by the formal and empirical standard deviations of  
4 attitude angular estimates.

5 Table 2 summarizes the benefits of augmenting different systems. Augmenting GPS with one or more systems improves  
6 ambiguity resolution. Especially with C-LAMBDA, instantaneous ambiguity resolution is possible (indicated in blue text)  
7 for the scenario considered (Figure 1). Furthermore, SBAS significantly contributes to improved ambiguity resolution  
8 even though it has less precise observations than that of other systems (Table 1). Although augmentation significantly  
9 improves ambiguity resolution and thus the ability to achieve instantaneous results, augmenting GPS with one or more  
10 systems does not significantly improve the ambiguity-fixed angular accuracy. This is understandable as any ambiguity-fixed  
11 solution is driven by the highly precise carrier-phase data. Also note that combining L1/E1-observations from non-GPS  
12 satellites does not yet offer continuous attitude solution (indicated in emphasized text) due to the poor satellite geometry  
13 with current Galileo and QZSS constellations, which are under development. By combining all four systems, one can  
14 achieve instantaneous single-frequency attitude determination even with the unconstrained LAMBDA method (indicated in  
15 bold text) for the scenario considered (Figure 1). With this clear indication of benefits from augmenting multiple system,  
16 we further analyse the performance of the augmented system under various satellite deprived environments in the following  
17 sections and compare with that of GPS-only solutions.

Number of GPS satellites (PDOP)	Success Fraction		Angular Standard deviation [deg]	
	LAMBDA	C-LAMBDA	Heading	Elevation
0 (5.75)/0.88	0.07	0.34	0.07 (0.07)	0.25 (0.20)
2 (3.07)	0.25	0.73	0.03 (0.04)	0.08 (0.12)
4 (2.23)	0.67	0.97	0.02 (0.02)	0.06 (0.06)
6 (1.81)	0.96	<b>1.00</b>	0.02 (0.02)	0.04 (0.04)
8 (1.56)	1.00	1.00	0.01 (0.01)	0.03 (0.03)
10 (1.51)	1.00	1.00	0.01 (0.01)	0.03 (0.03)

**Table 3.** Instantaneous single-frequency ambiguity success fractions (relative frequencies) and angular accuracy measured by empirical and formal (given in brackets) angular standard deviations for simulated GPS satellite outage. For some cases, a fraction of epochs (given in emphasized text) were processed due to a poor satellite geometry for positioning (PDOP > 100)

Number of SBAS satellites (PDOP)	Success Fraction		Angular Standard deviation [deg]	
	LAMBDA	C-LAMBDA	Heading	Elevation
0 (2.00)	0.85	0.99	0.01 (0.02)	0.04 (0.04)
1 (1.92)	0.91	<b>1.00</b>	0.01 (0.02)	0.04 (0.04)
2 (1.87)	0.95	<b>1.00</b>	0.01 (0.02)	0.04 (0.04)
3 (1.81)	0.97	<b>1.00</b>	0.01 (0.01)	0.04 (0.04)
4 (1.63)	0.98	<b>1.00</b>	0.01 (0.01)	0.04 (0.04)

**Table 4.** The contribution SBAS: Instantaneous single-frequency ambiguity success fractions (relative frequencies) and and angular accuracy measured by empirical and formal (given in brackets) angular standard deviations for the augmentation of GPS with different number of SBAS satellites

## 1 Satellite Outages

2 We simulated this satellite deprived environment by arbitrarily removing a number of visible GPS satellites. Note that,  
3 arbitrary removal of satellites over long period (ten days) enables us to evaluate average performance. Table 3 reports the  
4 LAMBDA and C-LAMBDA ambiguity success fractions for single-frequency processing and ambiguity resolved attitude  
5 angular accuracy (angular standard deviation). The benefits of using C-LAMBDA are highlighted using bold text. For the  
6 scenario considered (Figure 1), the C-LAMBDA method on average offers instantaneous attitude solution with all visible  
7 satellites from current non-GPS constellations and with as few as six GPS satellites, while LAMBDA method on average  
8 requires at least eight GPS satellites together with all visible satellites from current non-GPS constellations to achieve  
9 instantaneous solution. The formal standard deviations (terms in brackets) are well in line with the empirical standard  
10 deviations confirming the assumed stochastic model parameters in Table 1. A slight degradation of the angular accuracy  
11 with the number of satellites can be observed.

12 We also analysed the contribution of SBAS system for instantaneous attitude determination by augmenting GPS with different  
13 number of SBAS satellites. Table 4 summarizes the contribution of SBAS satellites highlighting benefits of using C-LAMBDA  
14 method (indicated using bold text). With C-LAMBDA processing, single-frequency user can achieve instantaneous attitude  
15 determination by augmenting GPS L1-observations with that of as few as one SBAS satellite for the scenario considered (Fig-  
16 ure 1). This is an interesting boost for single-frequency users, as at least one SBAS satellite (from WAAS, EGNOS, MSAS, and  
17 GAGAN) is uninterruptedly visible almost anywhere in the world enabling instantaneous attitude determination, which is im-  
18 mune to cycle slips.

Elevation Cut-off [deg]	GPS only			GPS+Galileo+QZSS+SBAS		
	PDOP	LAMBDA	C-LAMBDA	PDOP	LAMBDA	C-LAMBDA
10	2.00	0.85	0.99	1.50	<b>1.00</b>	<b>1.00</b>
20	3.13	0.56	0.93	2.36	0.96	<b>1.00</b>
30	6.64 (0.94)	0.25	0.75	3.52	0.82	0.98
40	12.65 (0.65)	0.08	0.56	7.70 (0.90)	0.45	0.86
50	21.35 (0.23)	0.02	0.46	16.37 (0.26)	0.23	0.74

**Table 5.** Instantaneous ambiguity success fractions (relative frequencies) for the real data with simulated open-pit using elevation masking; For some cases, a fraction of epochs (given in brackets) were processed due to a lack of sufficient visible satellites for positioning (requires at least four satellites) or due to a poor satellite geometry (PDOP > 100)

Elevation cut-off [deg]	GPS only		GPS+Galileo+QZSS+SBAS	
	Heading	Elevation	Heading	Elevation
10	0.01 (0.02)	0.04 (0.04)	0.01 (0.01)	0.03 (0.03)
20	0.02 (0.02)	0.04 (0.04)	0.01 (0.01)	0.04 (0.04)
30	0.02 (0.02)	0.06 (0.06)	0.02 (0.02)	0.06 (0.06)
40	0.03 (0.04)	0.11 (0.12)	0.03 (0.03)	0.11 (0.13)
50	0.04 (0.04)	0.17 (0.18)	0.03 (0.03)	0.15 (0.15)

**Table 6.** Empirical and formal (given in brackets) angular standard deviations [deg] of the ambiguity fixed attitude angles for single-frequency data with simulated open-pit using elevation masking

## 1 Open-pit Problem

2 We simulated this constrained environment using elevation angle masking. Table 5 reports the ambiguity resolution success  
3 fractions for single-frequency processing with different elevation angle maskings. The benefit, improved availability of  
4 attitude solutions, of using a combined system is highlighted (in bold text).

5 Note that, for large elevation masking angles, a fraction of epochs (given in brackets) were processed due to a lack of  
6 sufficient visible satellites for positioning (requires at least four satellites) or due to a poor satellite geometry (PDOP > 100).

7 For the scenario considered (Figure 1), the *single-frequency* C-LAMBDA processing of a combined system enables the  
8 availability of instantaneous attitude solutions for an open-pit with up to 20 deg elevation masking, while it is not possible  
9 for GPS-only processing even with 10 degree elevation masking.

10 The angular accuracies (standard deviations) of the single frequency processing are reported in Table 6. As shown, increas-  
11 ing elevation masking degrades both ambiguity resolution and the angular accuracy. But note that the combined system an-  
12 gular accuracy for a 20 degree mask angle is the same as that of GPS for only a 10 degree mask angle.

## 13 Urban Canyon

14 In this section we analyze the robustness of the C-LAMBDA method under an urban canyon effect, which is a well-  
15 known problem depriving GNSS based navigation solutions in urban environments [44–47]. We simulate the urban canyon  
16 blockage effect using a simple model, where we have two buildings as shown in Figure 3 placed symmetrically with respect  
17 to the attitude platform on an urban road. The blockage is defined by three angles:  $\gamma_0$  the azimuth of the center of the  
18 first building (defining the direction of the road),  $\alpha_0$  the elevation at the center of the building (defining the height of the  
19 buildings), and  $\beta_0$  the azimuth angle (defining the width of the buildings). For example, in the case of  $\gamma_0 = 90^\circ$ ,  $\alpha_0 = 60^\circ$ ,

**Figure 3.** Simulated urban canyon: Buildings on both sides of an urban road blocking satellite visibility; Angle  $\gamma_0$  defines the direction of the road, while angles  $\alpha_0$  and  $\beta_0$  define the height and the width of the buildings, respectively.

$\alpha_0$ (deg)	$\beta_0$ (deg)	GPS only		GPS+Galileo+QZSS+SBAS	
		LAMBDA	C-LAMBDA	LAMBDA	C-LAMBDA
20	20	0.80	0.99	0.99	<b>1.00</b>
	40	0.67	0.96	0.98	<b>1.00</b>
	60	0.55	0.90	0.95	<b>1.00</b>
	80	0.50 (0.99)	0.86 (0.99)	0.93	0.99
40	20	0.75	0.99	0.99	<b>1.00</b>
	40	0.43	0.85	0.93	<b>1.00</b>
	60	0.21 (0.87)	0.70 (0.87)	0.69 (0.99)	0.94 (0.99)
	80	0.14 (0.81)	0.58 (0.81)	0.58 (0.93)	0.92 (0.93)
60	20	0.72	0.98	0.99	<b>1.00</b>
	40	0.26 (0.99)	0.68 (0.99)	0.86	0.99
	60	0.03 (0.52)	0.39 (0.52)	0.17 (0.55)	0.68 (0.55)
	80	0.00 (0.13)	0.14 (0.13)	0.02 (0.14)	0.37 (0.14)
80	20	0.72	0.98	0.99	<b>1.00</b>
	40	0.23 (0.98)	0.66 (0.98)	0.83	0.98
	60	0.02 (0.45)	0.36 (0.45)	0.14 (0.46)	0.58 (0.46)
	80	0.00 (0.02)	0.27 (0.02)	0.00 (0.02)	0.40 (0.02)

**Table 7.** Instantaneous single-frequency ambiguity success fractions (relative frequencies) and the average computation time [sec] (given in brackets) for simulated urban canyon (Figure 3); For some cases, only a fraction of epochs (given in brackets) were processed due to the absence of sufficient satellites for positioning (requires at least four satellites) or due to a poor satellite geometry for positioning (PDOP > 100)

1 and  $\beta_0 = 60^\circ$ , the model represents two buildings with a height of 9 meters and a width of 17 meters on both sides of a  
2 ten-meter wide road in the North-South direction. Urban canyons can also introduce multi-path effects [46] and sometimes  
3 other types of interferences [48] that are not considered in this contribution. The robustness of the C-LAMBDA method  
4 against multi-path effects has already been studied and demonstrated in [49, 50] using a simulation study.

5 We considered the urban canyon along a road in North-South direction ( $\gamma_0 = 90^\circ$ ). This corresponds to the worst case  
6 deprivation due to a lack of visible satellites towards the South direction in Perth, Australia (South polar region). Table 7  
7 summarizes the ambiguity resolution success fraction for the simulated urban canyon scenario demonstrating the benefits  
8 (highlighted using bold text) of augmenting systems. Note that, for large values of  $\alpha_0$  and  $\beta_0$ , only a fraction of epochs  
9 (given in brackets) were processed due to the absence of sufficient satellites for positioning (requires at least four satellites)  
10 or due to a poor satellite geometry (PDOP > 100). For almost all other cases of combined system with the scenario  
11 considered (Figure 1), instantaneous ambiguity resolution is possible due to the exploitation of the geometry constraints in  
12 the C-LAMBDA method. The corresponding angular accuracies (standard deviations) are reported in Table 8, showing that  
13 empirical values are in line with formal values (given in brackets). A combined system processing not only improves the  
14 success fraction, but also slightly improves the angular accuracies. Both the ambiguity resolution success fraction and the  
15 angular accuracy, however, degrade as the effect of the urban canyon increases (i.e., angles  $\alpha_0$  and  $\beta_0$  increase).

$\alpha_0$ (deg)	$\beta_0$ (deg)	GPS only		GPS+Galileo+QZSS+SBAS	
		Heading	Elevation	Heading	Elevation
20	20	0.02 (0.02)	0.04 (0.04)	0.01 (0.01)	0.03 (0.03)
	40	0.02 (0.02)	0.04 (0.04)	0.02 (0.02)	0.04 (0.04)
	60	0.02 (0.02)	0.04 (0.04)	0.02 (0.02)	0.04 (0.04)
	80	0.02 (0.02)	0.05 (0.04)	0.02 (0.02)	0.04 (0.04)
40	20	0.02 (0.02)	0.04 (0.04)	0.01 (0.01)	0.04 (0.03)
	40	0.02 (0.02)	0.05 (0.06)	0.02 (0.02)	0.05 (0.05)
	60	0.03 (0.03)	0.05 (0.06)	0.03 (0.03)	0.05 (0.05)
	80	0.03 (0.03)	0.06 (0.06)	0.03 (0.03)	0.05 (0.05)
60	20	0.02 (0.02)	0.04 (0.04)	0.01 (0.01)	0.04 (0.04)
	40	0.02 (0.02)	0.06 (0.07)	0.02 (0.02)	0.05 (0.05)
	60	0.09 (0.10)	0.10 (0.11)	0.07 (0.07)	0.08 (0.08)
	80	* (*)	* (*)	* (*)	* (*)
80	20	0.02 (0.02)	0.04 (0.04)	0.01 (0.01)	0.04 (0.04)
	40	0.02 (0.03)	0.07 (0.07)	0.02 (0.02)	0.05 (0.06)
	60	0.10 (0.11)	0.12 (0.12)	0.08 (0.08)	0.10 (0.10)
	80	* (*)	* (*)	* (*)	* (*)

**Table 8.** Empirical and formal (given in brackets) angular standard deviations [deg] of the ambiguity fixed attitude angles for simulated urban canyon (Figure 3); \* refers to the cases with not enough samples to compute reliable statistics.

## 16 CONCLUSIONS

17 In this contribution we analysed the performance of the C-LAMBDA method for instantaneous attitude determination using  
18 single-frequency (L1/E1) observations from GPS/Galileo/QZSS/SBAS. Using real data from a rooftop experiment, we  
19 demonstrated that through any of the given augmentations of GPS, instantaneous single-frequency attitude determination is  
20 achieved with the C-LAMBDA method. We also demonstrated that such is even possible with the unconstrained LAMBDA  
21 method, at least in the Asia-Pacific region, when all four systems are combined in a mild multipath environment. We further  
1 analysed the performance of single-frequency attitude determination under various satellite deprived environments. The  
2 C-LAMBDA method offers instantaneous attitude solution with all visible satellites from current non-GPS constellations  
3 and with as few as six GPS satellites, while the LAMBDA method requires at least eight GPS satellites together with all  
4 visible satellites from current non-GPS constellations to achieve instantaneous solution.

5 The *single-frequency* C-LAMBDA processing of a combined system enables the availability of instantaneous attitude solu-  
6 tions for an open-pit with up to 20 degree elevation masking, while it is not possible for GPS-only processing even with 10  
7 degree elevation masking. We also showed that the use of a combined constellation significantly improves the attitude so-  
8 lution availability under satellite masking effect in urban environment. Overall, this study demonstrated the realization of instan-  
9 taneous attitude determination by combining single-frequency (L1/E1) observations from all available systems in a mild mul-  
1 tipath environment.

## 2 ACKNOWLEDGEMENTS

3 This work has been executed in the framework of the Positioning Program Project 1.01 “New carrier phase processing  
4 strategies for achieving precise and reliable multi-satellite, multi-frequency GNSS/RNSS positioning in Australia” of the  
5 Cooperative Research Centre for Spatial Information (CRC-SI) and the Australian Space Research Program GARADA

6 project on SAR Formation Flying. The second author P. J. G. Teunissen is the recipient of an Australian Research Council  
7 Federation Fellowship (project number FF0883188). All this support is gratefully acknowledged.

## 8 REFERENCES

- 9 [1] G. Lu, "Development of a GPS multi-antenna system for attitude determination," Ph.D. dissertation, Department of  
10 Geomatics Engineering, University of Calgary, Calgary, Alberta, Canada, 1995.
- 11 [2] C.-H. Tu, K. Tu, F.-R. Chang, and L.-S. Wang, "GPS compass: A novel navigation equipment," *Aerospace and*  
12 *Electronic Systems, IEEE Transactions on*, vol. 33, no. 3, pp. 1063–1068, July 1997.
- 13 [3] P. Montgomery, I. Y. Bar-Itzhack, and J. Garrick, "Algorithm for attitude determination using GPS," in *Proceedings*  
14 *Guidance, Navigation and Control Conference*, 1999.
- 15 [4] T. Bell, "Error analysis of attitude measurement in robotic ground vehicle position determination," *Navigation, Journal*  
16 *of The Institute of Navigation*, vol. 47, no. 4, pp. 289–296, Winter 2000.
- 17 [5] A. Caporali, "Basic direction sensing with GPS," *GPS World*, vol. 12, no. 3, p. 44, 2001.
- 18 [6] K. J. Park and J. L. Crassidis, "Attitude determination methods using pseudolite signal phase measurements," *Naviga-*  
19 *tion, Journal of The Institute of Navigation*, vol. 53, no. 2, pp. 121–133, Summer 2006.
- 20 [7] J. Pinchin, C. Hide, D. Park, and X. Chen, "Precise kinematic positioning using single frequency GPS receivers and  
21 an integer ambiguity constraint," in *Position, Location and Navigation Symposium, 2008 IEEE/ION*, May 2008, pp.  
22 600–605.
- 23 [8] P. Jurkowski, P. Henkel, and C. Guenther, "GPS based attitude determination with statistical and deterministic baseline  
24 a priori Information," in *Proceedings of the 2012 International Technical Meeting of The Institute of Navigation*,  
25 Newport Beach, CA, USA, January 30 – February 1 2012, pp. 1164–1213.
- 26 [9] K. Q. Chiang, M. L. Psiaki, S. P. Powell, R. J. Miceli, and B. W. O'Hanlon, "GPS-based attitude determination for a  
27 spinning rocket," in *Proceedings of 25th International Technical Meeting of the Satellite Division of The Institute of*  
28 *Navigation*, Nashville, TN, USA, September 17–21 2012.
- 1 [10] Furuno, "Model SC-120: Satellite compass," <http://www.furunousa.com/products/default.aspx>, 2003, [Online; ac-  
2 cessed: 28-March-2013].
- 3 [11] R. Monikes, J. Wendel, and G. F. Trommer, "A modified LAMBDA method for ambiguity resolution in the presence  
4 of position domain constraints," in *Proceedings of the 18th International Technical Meeting of the Satellite Division*  
5 *of The Institute of Navigation (ION GNSS 2005)*, September 2005, pp. 81–87.



- 6 [12] L. V. Kuylen, P. Nemry, A. Simsky, and J. Lorga, "Comparison of attitude performance for multi-antenna receivers,"  
7 *European Journal of Navigation*, vol. 4, no. 2, 2006.
- 8 [13] B. Wang, L. Miao, S. Wang, and J. Shen, "A constrained LAMBDA method for GPS attitude determination," *GPS*  
9 *Solutions*, vol. 13, no. 2, pp. 97–107, March 2009.
- 10 [14] P. J. G. Teunissen, P. De Jonge, and C. Tiberius, "Performance of the LAMBDA method for fast GPS ambiguity  
11 resolution," *Navigation*, vol. 44, no. 3, pp. 373–383, 1997.
- 12 [15] P. J. G. Teunissen, "An optimality property of the integer least-squares estimator," *Journal of Geodesy*, vol. 73, pp.  
13 587–593, 1999.
- 14 [16] D. B. Cox and J. D. W. Brading, "Integration of LAMBDA ambiguity resolution with Kalman filter for relative  
15 navigation of spacecraft," *Navigation, Journal of The Institute of Navigation*, vol. 47, no. 3, pp. 205–210, Fall 2000.
- 16 [17] S. Verhagen and P. J. G. Teunissen, "New global navigation satellite system ambiguity resolution method compared to  
17 existing approaches," *Journal of Guidance, Control, and Dynamics*, vol. 29, no. 4, pp. 981–991, 2006.
- 18 [18] C. Park and P. J. G. Teunissen, "A new carrier phase ambiguity estimation for GNSS attitude determination systems,"  
19 in *Proceedings of International Symposium on GPS/GNSS*, Tokyo, Japan, 15–18 November 2003, pp. 283–290.
- 20 [19] P. J. G. Teunissen, "The LAMBDA method for the GNSS compass," *Artificial Satellites*, vol. 41, no. 3, pp. 89–103,  
21 2006.
- 22 [20] —, "Integer least-squares theory for the GNSS compass," *Journal of Geodesy*, vol. 84, no. 7, pp. 433–447, 2010.
- 23 [21] P. J. G. Teunissen, G. Giorgi, and P. J. Buist, "Testing of a new single-frequency GNSS carrier phase attitude determi-  
24 nation method: Land, ship and aircraft experiments," *GPS Solutions*, vol. 15, no. 1, pp. 15–28, 2011.
- 25 [22] G. Giorgi, P. J. G. Teunissen, S. Verhagen, and P. J. Buist, "Testing a new multivariate GNSS carrier phase attitude  
26 determination method for remote sensing platforms," *Advances in Space Research*, vol. 46, no. 2, pp. 118 – 129, 2010.
- 27 [23] J. Hahn and E. Powers, "GPS and Galileo timing interoperability," in *Proceedings of GNSS 2004*, Rotterdam, the  
28 Netherlands, May 2004.
- 1 [24] B. Bonhoure, C. Boulanger, and J. Marechal, "Long term and multi-receiver GPS/GIOVE mixed PVT experimenta-  
2 tion," in *Proceedings of the 23rd International Technical Meeting of The Satellite Division of the Institute of Navigation*  
3 (*ION GNSS 2010*), Portland, OR, September 2010, pp. 3309–3319.
- 4 [25] D. Odijk and P. Teunissen, "Characterization of between-receiver GPS-Galileo inter-system biases and  
5 their effect on mixed ambiguity resolution," *GPS Solutions*, pp. 1–13, 2012. [Online]. Available: <http://dx.doi.org/10.1007/s10291-012-0298-0>

- 7 [26] D. Odijk, P. J. G. Teunissen, and L. Huisman, "First results of mixed GPS+GIOVE single-frequency RTK in Australia,"  
8 *Journal of Spatial Sciences*, vol. 57, no. 1, pp. 3–18, June 2012.
- 9 [27] N. Nadarajah, P. J. G. Teunissen, and N. Raziq, "Instantaneous GPS-Galileo attitude determination: single-frequency  
10 performance in satellite-deprived environments," *IEEE Transactions on Vehicular Technology*, vol. 62, no. 7, 2013.
- 11 [28] F. Wu, N. Kubo, and A. Yasuda, "Performance evaluation of GPS augmentation using Quasi-Zenith Satellite System,"  
12 *Aerospace and Electronic Systems, IEEE Transactions on*, vol. 40, no. 4, pp. 1249–1260, 2004.
- 13 [29] L. Wanninger and S. Wallstab-Freitag, "Combined processing of GPS, GLONASS, and SBAS code phase and carrier  
14 phase measurements," in *Proceedings of the 20th International Technical Meeting of the Satellite Division of The  
15 Institute of Navigation (ION GNSS 2007)*, 2007, pp. 2196–2201.
- 16 [30] A. Boriskin, D. Kozlov, and G. Zyryanov, "L1 RTK system with fixed ambiguity: What SBAS ranging brings," in  
17 *Proceedings of the 20th International Technical Meeting of the Satellite Division of The Institute of Navigation (ION  
18 GNSS 2007)*, 2007, pp. 2196–2201.
- 19 [31] L. Wanninger, "The future is now - GPS + GLONASS + SBAS = GNSS," *GPS World*, vol. July, pp. 42–48, 2008.
- 20 [32] R. Dach, S. Lutz, M. Meindl, S. Schaer, P. Steigenberger, and G. Beutler, "Combining the observations from different  
21 GNSS," in *Proceedings of EGU General Assembly 2010*, Vienna, Austria, 2-7 May 2010, p. 8985.
- 22 [33] S. Verhagen and P. Joosten, "Algorithms for design computations for integrated GPS-Galileo," in *Proceedings of the  
23 European Navigation Conference (ENC-GNSS 2003)*, 2003.
- 24 [34] O. Julien, P. Alves, M. E. Cannon, and W. Zhang, "A tightly coupled GPS/GALILEO combination for improved  
25 ambiguity resolution," in *Proceedings of the European Navigation Conference (ENC-GNSS03)*, 2003, pp. 1–14.
- 26 [35] O. Julien, M. Cannon, P. Alves, and G. Lachapelle, "Triple frequency ambiguity resolution using GPS/Galileo," *Euro-  
27 pean Journal of Navigation*, vol. 2, no. 2, pp. 51–57, 2004.
- 28 [36] P. J. G. Teunissen and A. Kleusberg, *GPS for Geodesy*, 2nd ed. Springer, 1998.
- 1 [37] H.-J. Euler and C. Goad, "On optimal filtering of GPS dual frequency observations without using orbit information,"  
2 *Journal of Geodesy*, vol. 65, pp. 130–143, 1991.
- 3 [38] D. A. Harville, *Matrix Algebra From A Statisticians Perspective*. New York: Springer, 1997.
- 4 [39] J. R. Magnus and H. Neudecker, *Matrix differential calculus with applications in statistics and econometrics*. New  
5 York: Wiley, 1995.

- 6 [40] P. J. G. Teunissen, "The least-squares ambiguity decorrelation adjustment: a method for fast GPS integer ambiguity  
7 estimation," *Journal of Geodesy*, vol. 70, pp. 65–82, 1995.
- 8 [41] N. Nadarajah, P. J. G. Teunissen, and G. Giorgi, "GNSS attitude determination for remote sensing: On the bounding  
9 of the multivariate ambiguity objective function," in *Proceedings of International Association of Geodesy Symposia*  
10 *(IAGS-2011)*, Melbourne, Australia, 28 June - 7 July 2011.
- 11 [42] G. Giorgi, P. J. G. Teunissen, and P. J. Buist, "A search and shrink approach for the baseline constrained LAMBDA  
12 method: Experimental results," in *Proceedings of International Symposium on GPS/GNSS*, A. Yasuda, Ed., Tokyo,  
13 Japan, 11–14 November 2008, pp. 797–806.
- 14 [43] R. E. Phelts, T. Walter, P. Enge, D. M. Akos, K. Shallberg, and T. Morrissey, "Range biases on the WAAS geostationary  
15 satellites," in *Proceedings of the 2004 National Technical Meeting of The Institute of Navigation*, San Diego, CA,  
16 January 2004, pp. 110–120.
- 17 [44] M. Tsakiri, M. Stewart, T. Forward, D. Sandison, and J. Walker, "Urban fleet monitoring with GPS and GLONASS,"  
18 *The Journal of Navigation*, vol. 51, no. 03, pp. 382–393, 1998.
- 19 [45] I. Ballester-Grpide, E. Herriz-Monseco, A. Juez-Muoz, M. M. Romay-Merino, and T. W. Beech, "Future GNSS  
20 constellation performances inside urban environments," in *Proceedings of the 13th International Technical Meeting*  
21 *of the Satellite Division of The Institute of Navigation (ION GPS 2000)*, Salt Lake City, UT, September 2000, pp.  
22 2436–2445.
- 23 [46] D. Aloï and O. Korniyenko, "Comparative performance analysis of a Kalman filter and a modified double exponential  
24 filter for GPS-Only position estimation of automotive platforms in an urban-canyon environment," *Vehicular Technol-*  
25 *ogy, IEEE Transactions on*, vol. 56, no. 5, pp. 2880–2892, sept. 2007.
- 26 [47] S. Ji, W. Chen, X. Ding, Y. Chen, C. Zhao, and C. Hu, "Potential benefits of GPS/GLONASS/Galileo integration in an  
27 urban canyon - Hong Kong," *The Journal of Navigation*, vol. 63, no. 04, pp. 681–693, 2010.
- 28 [48] E. Bertran and J. Delgado-Penin, "On the use of GPS receivers in railway environments," *Vehicular Technology, IEEE*  
29 *Transactions on*, vol. 53, no. 5, pp. 1452 – 1460, sept. 2004.
- 1 [49] G. Giorgi, "GNSS carrier phase-based attitude determination estimation and applications," Ph.D. dissertation, Delft  
2 University of Technology, December 2011.
- 3 [50] N. Nadarajah and P. J. G. Teunissen, "Instantaneous GPS/BeiDou/Galileo attitude determination: A single-frequency  
4 robustness analysis under constrained environments," in *Proceedings of The Institute of Navigation Pacific PNT 2013*,  
5 Honolulu, Hawaii, 22–25 April 2013, pp. 1088–1103.