INTRODUCTION TO THE EXPLICIT FINITE ELEMENT METHOD FOR NONLINEAR TRANSIENT DYNAMICS

SHEN R. WU and LEI GU



A JOHN WILEY & SONS, INC., PUBLICATION

CONTENTS

| PREF | PREFACE | | |
|---------------|--|-----|--|
| PART | I FUNDAMENTALS | ° 1 | |
| 1 INT | FRODUCTION | 3 | |
| 1.1 | Era of Simulation and Computer Aided Engineering | 3 | |
| - 5. v | 1.1.1 A World of Simulation | 3 | |
| | 1.1.2 Evolution of Explicit Finite Element Method | 4 | |
| , | 1.1.3 Computer Aided Engineering (CAE)—Opportunities | | |
| : | and Challenges | 5 | |
| 1.2 | Preliminaries | 6 | |
| | 1.2.1 Notations | 6 | |
| | 1.2.2 Constitutive Relations of Elasticity | 8 | |
| 2 FR | AMEWORK OF EXPLICIT FINITE ELEMENT METHOD | | |
| FO | R NONLINEAR TRANSIENT DYNAMICS | 11 | |
| 2.1 | Transient Structural Dynamics | 11 | |
| 2.2 | Variational Principles for Transient Dynamics | 13 | |
| | 2.2.1 Hamilton's Principle | 13 | |
| ۂ+ | 2.2.2 Galerkin Method | 15 | |

viii CONTENTS

| | 2.3 | Finite | Element Equations and the Explicit Procedures | 15 |
|------------|------|--------|--|------|
| | | 2.3.1 | Discretization in Space by Finite Element | 16 |
| | | 2.3.2 | System of Semidiscretization | 19 |
| | | 2.3.3 | Discretization in Time by Finite Difference | 19 |
| | | 2.3.4 | Procedure of the Explicit Finite Element Method | - 20 |
| | 2.4 | Main | Features of the Explicit Finite Element Method | 21 |
| | | 2.4.1 | Stability Condition and Time Step Size | 22 |
| | | 2.4.2 | Diagonal Mass Matrix | 23 |
| | | 2.4.3 | Corotational Stress | 24 |
| | 2.5 | Asses | sment of Explicit Finite Element Method | 24 |
| | | 2.5.1 | About the Solution of the Elastodynamics | 24 |
| | | 2.5.2 | A Priori Error Estimate of Explicit Finite Element | |
| | | | Method for Elastodynamics | 25 |
| * | | 2.5.3 | About the Diagonal Mass Matrix | 30 |
| PA | RT | II E | LEMENT TECHNOLOGY | 37 |
| 3 | | | DE SHELL ELEMENT (REISSNER-MINDLIN | |
| | PLA | ATE TH | IEORY) | 39 |
| | 3.1 | Funda | amentals of Plates and Shells | 40 |
| | | 3.1.1 | Characteristics of Thin-walled Structures | 40 |
| | | 3.1.2 | Resultant Equations | 42 |
| | | 3.1.3 | Applications to Linear Elasticity | 44 |
| ¥ | | 3.1.4 | Kirchhoff-Love Theory | 46 |
| 1. | | 3.1.5 | Reissner-Mindlin Plate Theory | 47 |
| ž. | 3.2 | Linea | r Theory of R-M Plate | 47 |
| .} | | 3.2.1 | Helmholtz Decomposition for R-M Plate | 48 |
| | | 3.2.2 | Load Scaling for Static Problem of R-M Plate | 48 |
| 1. | | 3.2.3 | Load Scaling and Mass Scaling for Dynamic Problem of R-M Plate | 49 |
| | | 3.2.4 | Relation between R-M Theory and K-L Theory | 50 |
| | 3.3 | | polation for Four-node R-M Plate Element | 52 |
| | | 3.3.1 | Variational Equations for R-M Plate | 52 |
| | | 3.3.2 | Bilinear Interpolations | 52 |
| <i>f</i> · | , | 3.3.3 | Shear Locking Issues of R-M Plate Element | 55 |
| | 3.4 | | ced Integration and Selective Reduced Integration | 56 |
| V. 5 | ٠. ١ | 3.4.1 | Reduced Integration | 56 |
| | | ~ | | |

| | | CONTENTS | ix |
|-----|--------|--|----------------------|
| • | 3.4.2 | Selective Reduced Integration | 57 |
| } - | 3.4.3 | Nonlinear Application of Selective Reduced | |
| | | Integration—Hughes-Liu Element | 58 |
| 3.5 | Pertur | bation Hourglass Control—Belytschko-Tsay Element | 60 |
| | 3.5.1 | Concept of Hourglass Control | 61 |
|) · | 3.5.2 | Four-node Belytschko-Tsay Shell Element—Perturbation Hourglass Control | 63 |
| | 3.5.3 | Improvement of Belytschko-Tsay Shell Element | 68 |
| • | 3.5.4 | About Convergence of Element using Reduced Integration | 70 |
| 3.6 | - | cal Hourglass Control—Belytschko–Leviathan) Element | 71 |
| | 3.6.1 | Constant and Nonconstant Contributions | 71 |
| | 3.6.2 | · · · · · · · · · · · · · · · · · · · | 72 |
| | 3.6.3 | Physical Hourglass Control by One-point Integration | 73 |
| | 3.6.4 | Drill Projection | 73 74 |
| | 3.6.5 | Improvement of B-L (QPH) Element | 7 4 76 |
| 3.7 | | Projection Method—Bathe–Dvorkin Element | 76 |
| 5.1 | 3.7.1 | Projection of Transverse Shear Strain | 76 |
| | 3.7.2 | Convergence of B-D Element | 78 |
| 3.8 | | sment of Four-node R-M Plate Element | 80 |
| 5.0 | 3.8.1 | Evaluations with Warped Mesh and Reduced Thickness | 80 |
| | 3.8.2 | About the Locking-free Low Order Four-node R-M | 00 |
| | 3.0.2 | Plate Element | 85 |
| THE | REE-NO | ODE SHELL ELEMENT (REISSNER-MINDLIN | |
| PL/ | TE TH | EORY) | 88 |
| 4.1 | Funda | mentals of a Three-node C^0 Element | 89 |
| | 4.1.1 | Transformation and Jacobian | 89 |
| | 4.1.2 | Numerical Quadrature for In-plane Integration | 91 |
| | 4.1.3 | Shear Locking with C^0 Triangular Element | 91 |
| 4.2 | | nposition Method for C^0 Triangular Element One-point Integration | 92 |
| | 4.2.1 | A C^0 Element with Decomposition of Deflection | 92 |
| | 4.2.2 | A C^0 Element with Decomposition of Rotations | 96 |
| 4.3 | | ete Kirchhoff Triangular Element | 97 |
| 4.4 | | sment of Three-node R-M Plate Element | 102 |
| | 4.4.1 | Evaluations with Warped Mesh and Reduced Thickness | 102 |
| | 4.4.2 | About the Locking-free Low Order Three-node R-M | 105 |
| | | Plate Element | 103 |

| 5 | EIG | HT-NO | DE SOLID ELEMENT | 107 |
|-------|-----|---------|---|-----|
| | 5.1 | Triline | ear Interpolation for the Eight-node Hexahedron Element | 107 |
| 1 | 5.2 | | ng Issues of the Eight-node Solid Element | 111 |
| | 5.3 | One-p | oint Reduced Integration and the Perturbed | |
| • | | Hourg | lass Control | 113 |
| | 5.4 | Assun | ned Strain Method and Selective/Reduced Integration | 115 |
| | 5.5 | Assun | ned Deviatoric Strain | 118 |
| • ' | 5.6 | An En | hanced Assumed Strain Method | 118 |
| | 5.7 | Taylo | Expansion of Assumed Strain about the Element Center | 120 |
| | 5.8 | Evalua | ation of Eight-node Solid Element | 123 |
| 6 | TW | O-NOD | E ELEMENT | 128 |
| | 6.1 | Truss | and Rod Element | 128 |
|).·. | 6.2 | Timos | shenko Beam Element | 129 |
| ij, | 6.3 | Spring | g Element | 131 |
| ٠, | | 6.3.1 | One Degree of Freedom Spring Element | 131 |
| r), s | | 6.3.2 | Six Degrees of Freedom Spring Element | 132 |
| Ţŗ | | 6.3.3 | Three-node Spring Element | 133 |
| | 6.4 | Spot V | Weld Element | 134 |
| 1. | | 6.4.1 | Description of Spot Weld Separation | 134 |
| | | 6.4.2 | Failure Criterion | 135 |
| | | 6.4.3 | Finite Element Representation of Spot Weld | 137 |
| | | | | |
| P/ | ART | ill N | MATERIAL MODELS | 139 |
| 7 | MA | TERIA | L MODEL OF PLASTICITY | 141 |
| ξ. | 7.1 | Funda | amentals of Plasticity | 142 |
| 1 2 | | 7.1.1 | Tensile Test | 142 |
| | | 7.1.2 | Hardening | 144 |
| ં. ૡ | • | 7.1.3 | Yield Surface | 145 |
| | | 7.1.4 | Normality Condition | 150 |
| | | 7.1.5 | Strain Rate Effect/Viscoplasticity | 152 |
| | 7.2 | Const | itutive Equations | 153 |
| | | 7.2.1 | Relations between Stress Increments and | |
| | | | Strain Increments | 153 |
| į | | 7.2.2 | Constitutive Equations for Mises Criterion | 157 |
| | | 7.2.3 | Application to Kinematic Hardening | 158 |

| | | | CONTENTS | хi |
|--------------|-----|-------|--|-----|
| | 7.3 | Softw | are Implementation | 159 |
| : ' | | 7.3.1 | Explicit Finite Element Procedure with Plasticity | 160 |
| | | 7.3.2 | | 160 |
| | | 7.3.3 | A Generalized Plane Stress Model | 163 |
| - , 1 | | 7.3.4 | Stress Resultant Approach | 164 |
| | 7.4 | Evalu | ation of Shell Elements with Plastic Deformation | 169 |
| 8 | COI | UNITA | UM MECHANICS MODEL OF DUCTILE DAMAGE | 175 |
| ٠ | 8.1 | Conce | ept of Damage Mechanics | 175 |
| ا <u>س</u> ؤ | 8.2 | Gurso | on's Model | 177 |
| | | 8.2.1 | Damage Variables and Yield Function | 178 |
| | | 8.2.2 | Constitutive Equation and Damage Growth | 179 |
| | 8.3 | Chow | 's Isotropic Model of Continuum Damage Mechanics | 180 |
| 4.7 | | 8.3.1 | Damage Effect Tensor | 181 |
| | | 8.3.2 | Yield Function and Constitutive Equation | 183 |
| | | 8.3.3 | Damage Growth | 185 |
| | | 8.3.4 | Application to Plates and Shells | 187 |
| | | 8.3.5 | Determination of Parameters | 188 |
| t | 8.4 | Chow | 's Anisotropic Model of Continuum Damage Mechanics | 189 |
| 9 | МО | DELS | OF NONLINEAR MATERIALS | 192 |
| • | 9.1 | Visco | elasticity | 192 |
| ri. | | 9.1.1 | Spring-Damper Model | 192 |
| | | 9.1.2 | A General Three-dimensional Viscoelasticity Model | 196 |
| | 9.2 | Polyn | ner and Engineering Plastics | 197 |
| | | 9.2.1 | Fundamental Mechanical Properties of Polymer Materials | 197 |
| | | 9.2.2 | A Temperature, Strain Rate, and Pressure Dependent | 100 |
| | | 000 | Constitutive Relation | 198 |
| | 0.2 | 9.2.3 | A Nonlinear Viscoelastic Model of Polymer Materials | 199 |
| | 9.3 | Rubbe | | 200 |
| , . | | 9.3.1 | Mooney–Rivlin Model of Rubber Material | 200 |
| • | | 9.3.2 | Blatz-Ko Model | 202 |
| | 0.4 | 9.3.3 | Ogden Model | 203 |
| | 9.4 | Foam | · · | 203 |
| | | 9.4.1 | A Cap Model Combining Volumetric Plasticity and Pressure Dependent Deviatoric Plasticity | 205 |
| ٠. | | 9.4.2 | A Model Consisting of Polymer Skeleton and Air | 205 |
| 4. | | 9.4.2 | A Phenomenological Uniaxial Model | 203 |

| | | 9.4.4 | Hysteresis Behavior | 208 |
|--------|-------|--------|---|-----|
| | | 9.4.5 | Dynamic Behavior | 209 |
| | 9.5 | Honey | comb | 209 |
| i,.,, | | 9.5.1 | Structure of Hexagonal Honeycomb | 210 |
| . : : | | 9.5.2 | Critical Buckling Load | 210 |
| ejî. Î | | 9.5.3 | A Phenomenological Material Model of Honeycomb | 211 |
| | | 9.5.4 | Behavior of Honeycomb under Complex Loading Conditions | 213 |
| | 9.6 | Lamina | ated Glazing | 214 |
| | | 9.6.1 | Application of J-integral | 214 |
| | | 9.6.2 | Application of Anisotropic Damage Model | 215 |
| 1. | | 9.6.3 | A Simplified Model with Shell Element for the Laminated Glass | 216 |
| PA | RT IV | / CO | NTACT AND CONSTRAINT CONDITIONS | 219 |
| 10 | THR | EE-DIM | ENSIONAL SURFACE CONTACT | 221 |
| | 10.1 | Examp | les of Contact Problems | 221 |
| | | 10.1.1 | Uniformly Loaded String with a Flat Rigid Obstacle | 222 |
| | | 10.1.2 | Hertz Contact Problem | 225 |
| | | 10.1.3 | Elastic Impact of Two Balls | 226 |
| | | 10.1.4 | Impact of an Elastic Rod on the Flat Rigid Obstacle | 228 |
| | | 10.1.5 | Impact of a Vibrating String to the Flat Rigid Obstacle | 231 |
| | 10.2 | Descri | ption of Contact Conditions | 233 |
| | | 10.2.1 | Contact with a Smooth Rigid Obstacle—Signorini's Problem | 233 |
| | | 10.2.2 | Contact between Two Smooth Deformable Bodies | 237 |
| | | | Coulomb's Law of Friction | 240 |
| | | 10.2.4 | | 242 |
| • | | 10.2.5 | Domain Contact | 242 |
| | 10.3 | | onal Principle for the Dynamic Contact Problem | 243 |
| | | 10.3.1 | Variational Formulation for Frictionless Dynamic Contact Problem | 243 |
| | , | 10.3.2 | Variational Formulation for Frictional Dynamic Contact Problem | 247 |
| | | 10.3.3 | Variational Formulation for Domain Contact | 250 |

| | | | CONTENTS | XIII |
|----------|------|---------|--|------|
| 4. 2. | 10.4 | Penalty | Method and the Regularization of Variational Inequality | 252 |
| ; :: · | | 10.4.1 | Concept of Penalty Method | 252 |
| | | 10.4.2 | Penalty Method for Nonlinear Dynamic Contact Problem | 256 |
| | | 10.4.3 | Explicit Finite Element Procedure with Penalty | |
| | | | Method for Dynamic Contact | 258 |
| 11 | | | PROCEDURES FOR THREE-DIMENSIONAL | 261 |
| | | | | 201 |
| | 11.1 | | act Algorithm with Slave Node Searching Segment | 262 |
| | | | Global Search | 263 |
| | | | Bucket Sorting Method | 264 |
| | | | Local Search | 266 |
| | | | Penalty Contact Force | 268 |
| | 11.2 | | act Algorithm with Master Segment Searching | 200 |
| | | Slave N | | 272 |
| | | 11.2.1 | Global Search with Bucket Sorting Based | |
| | | | on Segment's Capture Box | 272 |
| | | 11.2.2 | Local Search with the Projection of Slave Point | 273 |
| | 11.3 | Method | of Contact Territory and Defense Node | 273 |
| | | 11.3.1 | Global Search with Bucket Sorting Based on Segment's Territory | 274 |
| | | 11.3.2 | Local Search in the Territory | 274 |
| | | 11.3.3 | Defense Node and Contact Force | 275 |
| | 11.4 | Pinball | Contact Algorithm | 277 |
| | | 11.4.1 | The Pinball Hierarchy | 277 |
| | | 11.4.2 | Penalty Contact Force | 278 |
| | 11.5 | Edge (I | Line Segment) Contact | 279 |
| | | 11.5.1 | Search for Line Contact | 279 |
| | | 11.5.2 | Penalty Contact Force of Edge-to-Edge Contact | 281 |
| | 11.6 | Evaluat | tion of Contact Algorithm with Penalty Method | 282 |
| 12 | KINE | MATIC | CONSTRAINT CONDITIONS | 289 |
| | 12.1 | Rigid V | Vall | 289 |
| | | 12.1.1 | A Stationary Flat Rigid Wall | 290 |
| • | | 12.1.2 | A Moving Flat Rigid Wall | 291 |
| | | 12.1.3 | Rigid Wall with a Curved Surface | 293 |

| - | | |
|------|----------|--|
| xiv. | CONTENTS | |

15

1

. 757. - 245. - 247.

> > 4.

| INDEX | | | | |
|-----------------|--|-----|--|--|
| REFERENCES | | | | |
| 12.4 | Application Examples with Constraint Conditions | 300 | | |
| 3.1 12.3 | Explicit Finite Element Procedure with Constraint Conditions | 298 | | |
| 12.2 | Rigid Body | 296 | | |