

6-22-2004

## Laser-Assisted Fabrication of NMR Resonators

William W. Brey  
*Florida State University*

Susan D. Allen  
*Florida State University, allens17@erau.edu*

Follow this and additional works at: <https://commons.erau.edu/db-mechanical-engineering>



Part of the [Mechanical Engineering Commons](#)

---

### Scholarly Commons Citation

Brey, W. W., & Allen, S. D. (2004). Laser-Assisted Fabrication of NMR Resonators. , (). Retrieved from <https://commons.erau.edu/db-mechanical-engineering/10>

This Patent is brought to you for free and open access by the College of Engineering at Scholarly Commons. It has been accepted for inclusion in Mechanical Engineering - Daytona Beach by an authorized administrator of Scholarly Commons. For more information, please contact [commons@erau.edu](mailto:commons@erau.edu).



US006751847B1

(12) **United States Patent**  
**Brey et al.**

(10) **Patent No.:** **US 6,751,847 B1**  
(45) **Date of Patent:** **Jun. 22, 2004**

(54) **LASER-ASSISTED FABRICATION OF NMR RESONATORS**

(75) Inventors: **William W. Brey**, Tallahassee, FL (US); **Susan D. Allen**, Tallahassee, FL (US)

(73) Assignee: **FSU Research Foundation, Inc.**, Tallahassee, FL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 180 days.

(21) Appl. No.: **09/707,126**

(22) Filed: **Nov. 6, 2000**

**Related U.S. Application Data**

(60) Provisional application No. 60/163,402, filed on Nov. 4, 1999.

(51) **Int. Cl.**<sup>7</sup> ..... **H01F 7/06**

(52) **U.S. Cl.** ..... **29/606**; 29/602.1; 29/847; 324/318; 324/319; 336/183

(58) **Field of Search** ..... 29/605, 606, 602.1, 29/25.42, 847, 610.1, 611, 612, 592.1, 600, 601, 602.01, 603.01, 603.13, 603.15, 603.16, 603.25, 324, 322, 422; 324/319, 318; 336/223, 182, 183, 186, 188, 187

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,086,184 A	*	4/1963	Nichols	.....	336/60
3,699,550 A	*	10/1972	Spain	.....	365/136
3,735,293 A	*	5/1973	Breitenbach	.....	333/237
3,864,648 A	*	2/1975	McVickers	.....	333/163
3,911,332 A	*	10/1975	Kunkel	.....	361/270

4,368,407 A	*	1/1983	Wroblewski	.....	315/291
4,694,283 A		9/1987	Reeb		
4,845,586 A	*	7/1989	Blickstein	.....	391/292
4,870,742 A	*	10/1989	Roloff	.....	29/33 S
4,885,539 A	*	12/1989	Roemer et al.	.....	324/318
5,084,311 A	*	1/1992	Liu et al.	.....	428/35.8
5,172,389 A	*	12/1992	Horiuchi et al.	.....	372/87
5,276,398 A		1/1994	Withers et al.		
5,367,261 A	*	11/1994	Frederick	.....	324/318
5,466,480 A		11/1995	Zhou et al.		
5,565,778 A		10/1996	Brey et al.		
5,594,342 A		1/1997	Brey et al.		
5,619,140 A		4/1997	Brey et al.		
5,650,670 A	*	7/1997	Thaxter	.....	307/106
5,681,006 A	*	10/1997	Herd et al.	.....	243/447.1
5,932,492 A	*	8/1999	Hahm et al.	.....	438/737
6,087,832 A		7/2000	Doty		
6,097,188 A		8/2000	Sweedler et al.		
6,118,274 A		9/2000	Roffmann et al.		
6,221,297 B1	*	4/2001	Lanoue et al.	.....	264/219

**FOREIGN PATENT DOCUMENTS**

JP 362229904 A \* 10/1987 ..... 29/602.1

\* cited by examiner

*Primary Examiner*—I Cuda Rosenbaum

*Assistant Examiner*—Marc Jimenez

(74) *Attorney, Agent, or Firm*—Senniger, Powers, Leavitt & Roedel

(57) **ABSTRACT**

A detection coil for use in nuclear resonance magnetic (NMR) spectroscopy and a method of manufacture thereof. At least two film layers of material are deposited on an outer surface of a cylindrical tube of dielectric material. The layers are patterned to form a solenoid on the tube. At least one of the deposited materials is a conductor.

**17 Claims, 5 Drawing Sheets**

