

Abstract Submitted
for the DFD14 Meeting of
The American Physical Society

Maximizing the efficiency of a flexible propulsor using experimental optimization¹ DANIEL QUINN, Princeton University, GEORGE LAUDER, Harvard University, ALEXANDER SMITS, Princeton University, Monash University — Experimental gradient-based optimization is used to maximize the propulsive efficiency of a heaving and pitching flexible panel. Optimum and near-optimum conditions are studied via direct force measurements and Particle Image Velocimetry (PIV). The net thrust and power are found to scale predictably with the frequency and amplitude of the leading edge, but the efficiency shows a complex multimodal response. Optimum pitch and heave motions are found to produce nearly twice the efficiencies of optimum heave-only motions. Efficiency is globally optimized when (1) the Strouhal number is within an optimal range that varies weakly with amplitude and boundary conditions; (2) the panel is actuated at a resonant frequency of the fluid-propulsor system; (3) heave amplitude is tuned such that trailing edge amplitude is maximized while flow along the body remains attached; and (4) the maximum pitch angle and phase lag are chosen so that the effective angle of attack is minimized.

¹This work was supported by the Office of Naval Research under MURI grant number N00014-08-1-0642 (Program Director Dr. Bob Brizzolara), and the National Science Foundation under Grant DBI 1062052 (PI Lisa Fauci) and Grant EFRI-0938043 (PI George Lauder).

Daniel Quinn
Princeton University

Date submitted: 30 Jul 2014

Electronic form version 1.4