



Document details

< Back to results | 1 of 1

Export Download Print E-mail Save to PDF Add to List More... >

[Full Text](#) View at Publisher

Journal of Thermal Analysis and Calorimetry
2020

Maximum temperature analysis in a Li-ion battery pack cooled by different fluids

(📄 Article in press ?)

(Open Access)

Mokashi, I.^{a,b} ✉, Khan, S.A.^a, Abdullah, N.A.^a, Bin Azami, M.H.^a, Afzal, A.^c ✉ 👤 👤

^aDepartment of Mechanical Engineering, International Islamic University Malaysia, Kuala Lumpur, Malaysia

^bDepartment of Mechanical Engineering, Bearys Institute of Technology, (Affiliated to Visvesvaraya Technological University), Mangaluru, India

^cDepartment of Mechanical Engineering, P. A. College of Engineering (Affiliated to Visvesvaraya Technological University), Mangaluru, India

Abstract

↕ View references (54)

The use of Li-ion battery in electric vehicles is becoming extensive in the modern-day world owing to their high energy density and longer life. But there is a concern of proper thermal management to have consistent performance. Therefore, proper cooling mechanism to have a good life and reliability on the battery system is necessary. The main objective of this analysis is to assess the maximum temperature that causes thermal runaway when the battery pack is cooled by several fluids. Five categories of coolants are passed over the heat-generating battery pack to extract the heat and keep the temperature in the limit. Different kinds of gases, conventional oils, thermal oils, nanofluids, and liquid metals are adopted as coolants in each category. This analysis is a novel study which considers different categories of coolant and conjugate heat transfer condition at the battery pack and coolant interface. In each group of coolant, five types of fluids are selected and analyzed to obtain the least maximum temperature of battery. The flow Reynolds number (Re), heat generation (Q_{gen}), and conductivity ratio (Cr) are other parameters considered for the analysis. The Nusselt number for air and water as coolant with increase in Re is studied separately at the end. The maximum temperature is found to increase with Q_{gen} and decrease for Re and Cr . Thermal oils, nanofluids, and liquid metals are found to provide maximum temperature in the same range of 0.62 to 0.54. At the same time, gases have nearly the same effect at different values of Re and Cr . © 2020, Akadémiai Kiadó, Budapest, Hungary.

SciVal Topic Prominence 📄

Topic: Battery Pack | Lifepo4 | Thermal Management

Prominence percentile: 99.863 📄

Author keywords

Conductivity ratio Conjugate Coolants Heat generation Li-ion battery Maximum temperature

Indexed keywords

Engineering controlled terms:

Battery Pack Coolants Heat generation Heat transfer Inclusions Liquid metals Metal analysis Reynolds equation Reynolds number Thermal management (electronics)

Engineering uncontrolled terms

Conductivity ratio Conjugate heat transfer Consistent performance Conventional oil Cooling mechanism High energy densities Maximum temperature Thermal runaways

Metrics 📄 View all metrics >



PlumX Metrics ↕

Usage, Captures, Mentions, Social Media and Citations beyond Scopus.

Cited by 0 documents

Inform me when this document is cited in Scopus:

[Set citation alert >](#)

[Set citation feed >](#)

Related documents

Effect of spacing on thermal performance characteristics of Li-ion battery cells

Afzal, A. , Mohammed Samee, A.D. , Abdul Razak, R.K. (2019) *Journal of Thermal Analysis and Calorimetry*

Thermal management for high power lithium-ion battery by minichannel aluminum tubes

Lan, C. , Xu, J. , Qiao, Y. (2016) *Applied Thermal Engineering*

Comparison of different cooling methods for lithium ion battery cells

Chen, D. , Jiang, J. , Kim, G.-H. (2016) *Applied Thermal Engineering*

View all related documents based on references

Find more related documents in Scopus based on:

Authors > Keywords >

ISSN: 13886150
CODEN: JTACF
Source Type: Journal
Original language: English

DOI: 10.1007/s10973-020-10063-9
Document Type: Article
Publisher: Springer Netherlands

References (54)

[View in search results format >](#)

All [Export](#) [Print](#) [E-mail](#) [Save to PDF](#) [Create bibliography](#)

-
- 1 Xu, X.M., He, R.
Review on the heat dissipation performance of battery pack with different structures and operation conditions

(2014) *Renewable and Sustainable Energy Reviews*, 29, pp. 301-315. Cited 44 times.
doi: 10.1016/j.rser.2013.08.057
[View at Publisher](#)
-
- 2 Liu, Z., Wang, Y., Zhang, J., Liu, Z.
Shortcut computation for the thermal management of a large air-cooled battery pack

(2014) *Applied Thermal Engineering*, 66 (1-2), pp. 445-452. Cited 57 times.
http://www.elsevier.com/aps/find/journaldescription.cws_home/630/description#description
doi: 10.1016/j.applthermaleng.2014.02.040
[View at Publisher](#)
-
- 3 Wang, T., Tseng, K.J., Zhao, J., Wei, Z.
Thermal investigation of lithium-ion battery module with different cell arrangement structures and forced air-cooling strategies

(2014) *Applied Energy*, 134, pp. 229-238. Cited 205 times.
<http://www.elsevier.com/inca/publications/store/4/0/5/8/9/1/index.htm>
doi: 10.1016/j.apenergy.2014.08.013
[View at Publisher](#)
-
- 4 Srinivasan, V., Wang, C.Y.
Analysis of electrochemical and thermal behavior of Li-ion cells

(2003) *Journal of the Electrochemical Society*, 150 (1), pp. A98-A106. Cited 289 times.
doi: 10.1149/1.1526512
[View at Publisher](#)
-
- 5 Spotnitz, R., Franklin, J.
Abuse behavior of high-power, lithium-ion cells

(2003) *Journal of Power Sources*, 113 (1), pp. 81-100. Cited 564 times.
doi: 10.1016/S0378-7753(02)00488-3
[View at Publisher](#)
-

- 6 Kelly, K.J., Mihalic, M., Zolot, M.
Battery usage and thermal performance of the Toyota Prius and Honda Insight during chassis dynamometer testing
(2002) *Proceedings of the Annual Battery Conference on Applications and Advances*, 2002-January, art. no. 986408, pp. 247-252. Cited 60 times.
ISBN: 0780371321
doi: 10.1109/BCAA.2002.986408
[View at Publisher](#)
-
- 7 Wu, M.-S., Liu, K.H., Wang, Y.-Y., Wan, C.-C.
Heat dissipation design for lithium-ion batteries
(2002) *Journal of Power Sources*, 109 (1), pp. 160-166. Cited 175 times.
doi: 10.1016/S0378-7753(02)00048-4
[View at Publisher](#)
-
- 8 Verma, P., Maire, P., Novák, P.
A review of the features and analyses of the solid electrolyte interphase in Li-ion batteries
(2010) *Electrochimica Acta*, 55 (22), pp. 6332-6341. Cited 1544 times.
doi: 10.1016/j.electacta.2010.05.072
[View at Publisher](#)
-
- 9 Guo, G., Long, B., Cheng, B., Zhou, S., Xu, P., Cao, B.
Three-dimensional thermal finite element modeling of lithium-ion battery in thermal abuse application
(2010) *Journal of Power Sources*, 195 (8), pp. 2393-2398. Cited 170 times.
doi: 10.1016/j.jpowsour.2009.10.090
[View at Publisher](#)
-
- 10 Bandhauer, T.M., Garimella, S., Fuller, T.F.
A critical review of thermal issues in lithium-ion batteries
(2011) *Journal of the Electrochemical Society*, 158 (3), pp. R1-R25. Cited 796 times.
doi: 10.1149/1.3515880
[View at Publisher](#)
-
- 11 Moharana, M.K., Singh, P.K., Khandekar, S.
Optimum nusselt number for simultaneously developing internal flow under conjugate conditions in a square microchannel
(2012) *Journal of Heat Transfer*, 134 (7), art. no. 071703. Cited 26 times.
doi: 10.1115/1.4006110
[View at Publisher](#)
-
- 12 Kim, G.-H., Pesaran, A., Spotnitz, R.
A three-dimensional thermal abuse model for lithium-ion cells
(2007) *Journal of Power Sources*, 170 (2), pp. 476-489. Cited 342 times.
doi: 10.1016/j.jpowsour.2007.04.018
[View at Publisher](#)
-

- 13 Chen, S.C., Wan, C.C., Wang, Y.Y.
Thermal analysis of lithium-ion batteries
(2005) *Journal of Power Sources*, 140 (1), pp. 111-124. Cited 386 times.
doi: 10.1016/j.jpowsour.2004.05.064
[View at Publisher](#)
-
- 14 Hatchard, T.D., MacNeil, D.D., Basu, A., Dahn, J.R.
Thermal Model of Cylindrical and Prismatic Lithium-Ion Cells
(2001) *Journal of the Electrochemical Society*, 148 (7), pp. A755-A761. Cited 242 times.
doi: 10.1149/1.1377592
[View at Publisher](#)
-
- 15 Smith, K., Wang, C.-Y.
Power and thermal characterization of a lithium-ion battery pack for hybrid-electric vehicles
(2006) *Journal of Power Sources*, 160 (1), pp. 662-673. Cited 423 times.
doi: 10.1016/j.jpowsour.2006.01.038
[View at Publisher](#)
-
- 16 Sun, H., Wang, X., Tossan, B., Dixon, R.
Three-dimensional thermal modeling of a lithium-ion battery pack
(2012) *Journal of Power Sources*, 206, pp. 349-356. Cited 101 times.
doi: 10.1016/j.jpowsour.2012.01.081
[View at Publisher](#)
-
- 17 Doh, C.-H., Kim, D.-H., Kim, H.-S., Shin, H.-M., Jeong, Y.-D., Moon, S.-I., Jin, B.-S., (...), Veluchamy, A.
Thermal and electrochemical behaviour of C/Li_xCoO₂ cell during safety test
(2008) *Journal of Power Sources*, 175 (2), pp. 881-885. Cited 76 times.
doi: 10.1016/j.jpowsour.2007.09.102
[View at Publisher](#)
-
- 18 Chiu, K.-C., Lin, C.-H., Yeh, S.-F., Lin, Y.-H., Chen, K.-C.
An electrochemical modeling of lithium-ion battery nail penetration
(2014) *Journal of Power Sources*, 251, pp. 254-263. Cited 71 times.
doi: 10.1016/j.jpowsour.2013.11.069
[View at Publisher](#)
-
- 19 Pesaran, A.A.
Battery thermal models for hybrid vehicle simulations
(2002) *Journal of Power Sources*, 110 (2), pp. 377-382. Cited 256 times.
doi: 10.1016/S0378-7753(02)00200-8
[View at Publisher](#)
-
- 20 Chalise, D., Shah, K., Prasher, R., Jain, A.
Conjugate Heat Transfer Analysis of Thermal Management of a Li-Ion Battery Pack
([Open Access](#))
(2018) *Journal of Electrochemical Energy Conversion and Storage*, 15 (1), art. no. 011008. Cited 12 times.
<http://electrochemical.asmedigitalcollection.asme.org/journal.aspx>
doi: 10.1115/1.4038258
[View at Publisher](#)
-

- 21 Fan, L., Khodadadi, J.M., Pesaran, A.A.
A parametric study on thermal management of an air-cooled lithium-ion battery module for plug-in hybrid electric vehicles

(2013) *Journal of Power Sources*, 238, pp. 301-312. Cited 214 times.
doi: 10.1016/j.jpowsour.2013.03.050

[View at Publisher](#)

- 22 Zolot, M., Pesaran, A.A., Mihalic, M.
Thermal evaluation of Toyota prius battery pack

(2002) *SAE Technical Papers*. Cited 36 times.
<http://papers.sae.org/>
doi: 10.4271/2002-01-1962

[View at Publisher](#)

- 23 Zolot, M.D., Kelly, K., Pesaran, A., Keyser, M., Mihalic, M., Hieronymus, A.
Thermal evaluation of the honda insight battery pack

(2001) *Proceedings of the Intersociety Energy Conversion Engineering Conference*, 2, pp. 923-928. Cited 28 times.

- 24 Choi, Y.S., Kang, D.M.
Prediction of thermal behaviors of an air-cooled lithium-ion battery system for hybrid electric vehicles

(2014) *Journal of Power Sources*, 270, pp. 273-280. Cited 66 times.
doi: 10.1016/j.jpowsour.2014.07.120

[View at Publisher](#)

- 25 Wang, T., Tseng, K.J., Zhao, J.
Development of efficient air-cooling strategies for lithium-ion battery module based on empirical heat source model

(2015) *Applied Thermal Engineering*, 90, art. no. 6832, pp. 521-529. Cited 75 times.
<http://www.journals.elsevier.com/applied-thermal-engineering/>
doi: 10.1016/j.applthermaleng.2015.07.033

[View at Publisher](#)

- 26 Yang, N., Zhang, X., Li, G., Hua, D.
Assessment of the forced air-cooling performance for cylindrical lithium-ion battery packs: A comparative analysis between aligned and staggered cell arrangements

(2015) *Applied Thermal Engineering*, 80, pp. 55-65. Cited 130 times.
<http://www.journals.elsevier.com/applied-thermal-engineering/>
doi: 10.1016/j.applthermaleng.2015.01.049

[View at Publisher](#)

- 27 Xu, X.M., He, R.
Research on the heat dissipation performance of battery pack based on forced air cooling

(2013) *Journal of Power Sources*, 240, pp. 33-41. Cited 87 times.
doi: 10.1016/j.jpowsour.2013.03.004

[View at Publisher](#)

- 28 Zhao, J., Rao, Z., Huo, Y., Liu, X., Li, Y.
Thermal management of cylindrical power battery module for extending the life of new energy electric vehicles

(2015) *Applied Thermal Engineering*, 85, pp. 33-43. Cited 97 times.
<http://www.journals.elsevier.com/applied-thermal-engineering/>
doi: 10.1016/j.applthermaleng.2015.04.012

[View at Publisher](#)

- 29 Mohammadian, S.K., Rassoulinejad-Mousavi, S.M., Zhang, Y.
Thermal management improvement of an air-cooled high-power lithium-ion battery by embedding metal foam

(2015) *Journal of Power Sources*, 296, art. no. 21497, pp. 305-313. Cited 62 times.
doi: 10.1016/j.jpowsour.2015.07.056

[View at Publisher](#)

- 30 Jilte, R.D., Kumar, R., Ahmadi, M.H., Chen, L.
Battery thermal management system employing phase change material with cell-to-cell air cooling

(2019) *Applied Thermal Engineering*, 161, art. no. 114199. Cited 19 times.
<http://www.journals.elsevier.com/applied-thermal-engineering/>
doi: 10.1016/j.applthermaleng.2019.114199

[View at Publisher](#)

- 31 Jilte, R.D., Kumar, R., Ahmadi, M.H.
Cooling performance of nanofluid submerged vs. nanofluid circulated battery thermal management systems

(2019) *Journal of Cleaner Production*, 240, art. no. 118131. Cited 15 times.
<https://www.journals.elsevier.com/journal-of-cleaner-production>
doi: 10.1016/j.jclepro.2019.118131

[View at Publisher](#)

- 32 Dincer, I., Hamut, H., Javani, N.
(2017) *Thermal management of electric vehicle battery systems*. Cited 45 times.
Wiley, Hoboken

- 33 Karimi, G., Li, X.
Thermal management of lithium-ion batteries for electric vehicles

(2013) *International Journal of Energy Research*, 37 (1), pp. 13-24. Cited 169 times.
doi: 10.1002/er.1956

[View at Publisher](#)

- 34 Richter, F., Vie, P.J.S., Kjelstrup, S., Burheim, O.S.
Measurements of ageing and thermal conductivity in a secondary NMC-hard carbon Li-ion battery and the impact on internal temperature profiles

(2017) *Electrochimica Acta*, 250, pp. 228-237. Cited 29 times.
<http://www.journals.elsevier.com/electrochimica-acta/>
doi: 10.1016/j.electacta.2017.07.173

[View at Publisher](#)

- 35 Panchal, S., Dincer, I., Agelin-Chaab, M., Fraser, R., Fowler, M.
Thermal modeling and validation of temperature distributions in a prismatic lithium-ion battery at different discharge rates and varying boundary conditions
(2016) *Applied Thermal Engineering*, 96, pp. 190-199. Cited 108 times.
<http://www.journals.elsevier.com/applied-thermal-engineering/>
doi: 10.1016/j.applthermaleng.2015.11.019
View at Publisher
-
- 36 Yu, K., Yang, X., Cheng, Y., Li, C.
Thermal analysis and two-directional air flow thermal management for lithium-ion battery pack
(2014) *Journal of Power Sources*, 270, pp. 193-200. Cited 84 times.
doi: 10.1016/j.jpowsour.2014.07.086
View at Publisher
-
- 37 Richter, F., Kjelstrup, S., Vie, P.J.S., Burheim, O.S.
Thermal conductivity and internal temperature profiles of Li-ion secondary batteries
(2017) *Journal of Power Sources*, 359, pp. 592-600. Cited 25 times.
doi: 10.1016/j.jpowsour.2017.05.045
View at Publisher
-
- 38 Fakoor Pakdaman, M., Akhavan-Behabadi, M.A., Razi, P.
An experimental investigation on thermo-physical properties and overall performance of MWCNT/heat transfer oil nanofluid flow inside vertical helically coiled tubes
(2012) *Experimental Thermal and Fluid Science*, 40, pp. 103-111. Cited 142 times.
doi: 10.1016/j.expthermflusci.2012.02.005
View at Publisher
-
- 39 Shahrul, I.M., Mahbubul, I.M., Saidur, R., Sabri, M.F.M.
Experimental investigation on Al₂O₃-W, SiO₂-W and ZnO-W nanofluids and their application in a shell and tube heat exchanger
(2016) *International Journal of Heat and Mass Transfer*, 97, pp. 547-558. Cited 50 times.
<http://www.journals.elsevier.com/international-journal-of-heat-and-mass-transfer/>
doi: 10.1016/j.ijheatmasstransfer.2016.02.016
View at Publisher
-
- 40 Chavan, D., Pise, A.T.
Experimental investigation of convective heat transfer augmentation using Al₂O₃/water nanofluid in circular pipe
(2015) *Heat and Mass Transfer/Waerme- und Stoffuebertragung*, 51 (9), pp. 1237-1246. Cited 8 times.
<http://www.springer.com/sgw/cda/frontpage/0,11855,1-40109-70-1034617-0,00.html>
doi: 10.1007/s00231-014-1491-1
View at Publisher
-
- 41 Akhavan-Behabadi, M.A., Shahidi, M., Aligoodarz, M.R., Ghazvini, M.
Experimental investigation on thermo-physical properties and overall performance of MWCNT-water nanofluid flow inside horizontal coiled wire inserted tubes
(2017) *Heat and Mass Transfer/Waerme- und Stoffuebertragung*, 53 (1), pp. 291-304. Cited 8 times.
<http://www.springer.com/sgw/cda/frontpage/0,11855,1-40109-70-1034617-0,00.html>
doi: 10.1007/s00231-016-1814-5
View at Publisher

- 42 Afzal, A., Nawfal, I., Mahbul, I.M., Kumbar, S.S.
An overview on the effect of ultrasonication duration on different properties of nanofluids

(2019) *Journal of Thermal Analysis and Calorimetry*, 135 (1), pp. 393-418. Cited 18 times.
<http://www.springer.com/sgw/cda/frontpage/0,11855,1-40109-70-35752391-0,00.html>
doi: 10.1007/s10973-018-7144-8

[View at Publisher](#)

- 43 Afzal, A., Khan, S.A., Ahamed Saleel, C.
Role of ultrasonication duration and surfactant on characteristics of ZnO and CuO nanofluids

(2019) *Materials Research Express*, 6 (11), art. no. 1150D8. Cited 4 times.
<https://iopscience.iop.org/article/10.1088/2053-1591/ab5013/pdf>
doi: 10.1088/2053-1591/ab5013

[View at Publisher](#)

- 44 Afzal, A., Samee, A.M., Razak, R.A.
Experimental thermal investigation of CuO–W nanofluid in circular minichannel
(2017) *Model Meas Control B*, 86 (2), pp. 335-344. Cited 17 times.

- 45 Afzal, A., Samee, A.D.M., Razak, R.K.A.
Comparative thermal performance analysis of water, engine coolant oil and MWCNT-W nanofluid in a radiator

(2018) *Modelling, Measurement and Control B*, 87 (1), pp. 1-6. Cited 8 times.
http://www.iieta.org/Journals/MMC/MMC_B
doi: 10.18280/mmc_b.870101

[View at Publisher](#)

- 46 Ali, H.M., Babar, H., Shah, T.R., Sajid, M.U., Qasim, M.A., Javed, S.
Preparation techniques of TiO₂ nanofluids and challenges: A review (Open Access)

(2018) *Applied Sciences (Switzerland)*, 8 (4), art. no. 587. Cited 58 times.
<http://www.mdpi.com/2076-3417/8/4/587/pdf>
doi: 10.3390/app8040587

[View at Publisher](#)

- 47 Sajid, M.U., Ali, H.M.
Thermal conductivity of hybrid nanofluids: A critical review

(2018) *International Journal of Heat and Mass Transfer, Part A* 126, pp. 211-234. Cited 156 times.
<http://www.journals.elsevier.com/international-journal-of-heat-and-mass-transfer/>
doi: 10.1016/j.ijheatmasstransfer.2018.05.021

[View at Publisher](#)

- 48 Sajid, M.U., Ali, H.M.
Recent advances in application of nanofluids in heat transfer devices: A critical review

(2019) *Renewable and Sustainable Energy Reviews*, 103, pp. 556-592. Cited 141 times.
<https://www.journals.elsevier.com/renewable-and-sustainable-energy-reviews>
doi: 10.1016/j.rser.2018.12.057

[View at Publisher](#)

- 49 Babar, H., Ali, H.M.
Airfoil shaped pin-fin heat sink: Potential evaluation of ferric oxide and titania nanofluids

(2019) *Energy Conversion and Management*, 202, art. no. 112194. Cited 26 times.
<https://www.journals.elsevier.com/energy-conversion-and-management>
doi: 10.1016/j.enconman.2019.112194

[View at Publisher](#)

- 50 Arshad, W., Ali, H.M.
Graphene nanoplatelets nanofluids thermal and hydrodynamic performance on integral fin heat sink

(2017) *International Journal of Heat and Mass Transfer*, 107, pp. 995-1001. Cited 89 times.
<http://www.journals.elsevier.com/international-journal-of-heat-and-mass-transfer/>
doi: 10.1016/j.ijheatmasstransfer.2016.10.127

[View at Publisher](#)

- 51 Arshad, W., Ali, H.M.
Experimental investigation of heat transfer and pressure drop in a straight minichannel heat sink using TiO₂ nanofluid

(2017) *International Journal of Heat and Mass Transfer*, 110, pp. 248-256. Cited 114 times.
<http://www.journals.elsevier.com/international-journal-of-heat-and-mass-transfer/>
doi: 10.1016/j.ijheatmasstransfer.2017.03.032

[View at Publisher](#)

- 52 Afzal, A., Mohammed Samee, A.D., Abdul Razak, R.K., Ramis, M.K.
Thermal management of modern electric vehicle battery systems (MEVBS)

(2020) *Journal of Thermal Analysis and Calorimetry*. Cited 3 times.
<http://www.springer.com/sgw/cda/frontpage/0,11855,1-40109-70-35752391-0,00.html>
doi: 10.1007/s10973-020-09606-x

[View at Publisher](#)

- 53 Afzal, A., Mohammed Samee, A.D., Abdul Razak, R.K., Ramis, M.K.
Effect of spacing on thermal performance characteristics of Li-ion battery cells

(2019) *Journal of Thermal Analysis and Calorimetry*, 135 (3), pp. 1797-1811. Cited 15 times.
<http://www.springer.com/sgw/cda/frontpage/0,11855,1-40109-70-35752391-0,00.html>
doi: 10.1007/s10973-018-7664-2

[View at Publisher](#)

- 54 Samee AD, M., Afzal, A., Razak RK, A., Ramis, M.K.
Effect of Prandtl number on the average exit temperature of coolant in a heat-generating vertical parallel plate channel: A conjugate analysis

(2018) *Heat Transfer - Asian Research*, 47 (4), pp. 603-619. Cited 10 times.
<http://www.interscience.wiley.com/jpages/1099-2871>
doi: 10.1002/htj.21330

[View at Publisher](#)

✉ Mokashi, I.; Department of Mechanical Engineering, International Islamic University Malaysia, Kuala Lumpur, Malaysia; email:mokashi782@gmail.com

✉ Afzal, A.; Department of Mechanical Engineering, P. A. College of Engineering (Affiliated to Visvesvaraya Technological University), Mangaluru, India; email:asif.afzal86@gmail.com

© Copyright 2020 Elsevier B.V., All rights reserved.

About Scopus

[What is Scopus](#)
[Content coverage](#)
[Scopus blog](#)
[Scopus API](#)
[Privacy matters](#)

Language

[日本語に切り替える](#)
[切换到简体中文](#)
[切换到繁體中文](#)
[Русский язык](#)

Customer Service

[Help](#)
[Contact us](#)

ELSEVIER

[Terms and conditions ↗](#) [Privacy policy ↗](#)

Copyright © Elsevier B.V. All rights reserved. Scopus® is a registered trademark of Elsevier B.V.

We use cookies to help provide and enhance our service and tailor content. By continuing, you agree to the use of cookies.

 RELX