Person-job fit estimation from candidate profile and related recruitment history with Co-Attention Neural Networks

Ziyang Wang^a, Wei Wei^{a,*}, Chenwei Xu^{a,d}, Jun Xu^b, Xian-Ling Mao^c

^aSchool of Computer Science and Technology, Huazhong University of Science and Technology, China ^bGaoling School of Artificial Intelligence, Renmin University of China ^cSchool of Computer, Beijing Institute of Technology ^dState Grid Jiangsu Electric Power Co., Ltd. Information & Telecommunication Branch, China

Abstract

Existing online recruitment platforms depend on automatic ways of conducting the person-job fit, whose goal is matching appropriate job seekers with job positions. Intuitively, the previous successful recruitment records contain important information, which should be helpful for the current person-job fit. Existing studies on person-job fit, however, mainly focus on calculating the similarity between the candidate resumes and the job postings on the basis of their contents, without taking the recruiters' experience (*i.e.*, historical successful recruitment records) into consideration. In this paper, we propose a novel neural network approach for person-job fit, which estimates person-job fit from candidate profile and related recruitment history with co-attention **n**eural **n**etworks (named PJFCANN). Specifically, given a target resume-job post pair, PJFCANN generates local semantic representations through co-attention neural networks and global experience representations via graph neural networks. The final matching degree is calculated by combining these two representations. In this way, the historical successful recruitment records are introduced to enrich the features of resumes and job postings and strengthen the current matching process. Extensive experiments conducted on a large-scale recruitment dataset verify the effectiveness of PJFCANN compared with several state-of-the-art baselines. The codes are released at: https://github.com/CCIIPLab/PJFCANN.

Preprint submitted to Journal of LATEX Templates

^{*}Corresponding author

Email address: weiw@hust.edu.cn (Wei Wei)

1. Introduction

With the rapid development of the Internet, online recruitment platforms have also expanded rapidly. According to a recent report from BuisnessOfApps¹, by the end of the year 2019, there will be 660 million users spread over 200 countries and 20 million jobs listed on LinkedIn. The large numbers of job candidates and job postings on the Internet cost the recruiters a lot of effort to find a suitable job. According to SHRM's report², by the end of the year 2018, recruiters need to averagely spend 36 days and 4,400 dollars for filling a job position with the right talent. Therefore, it has become an essential task that automatically matches jobs with suitable candidates, called "Person-Job Fit".

Due to its high practical value, Person-job fit has received increasing research interest [37, 24, 29, 41, 27]. Among these researches, a typical approach is to convert the task to a supervised text matching problem, which aims at calculating the matching degree based on the text content of job postings and resumes. More recently, with the extensive application of deep learning invariant fields, end-to-end neural networks have been proposed to understand semantic representations for calculating the matching degrees, including CNN-based model [44], RNN-based model [30] and the model combining RNN and CNN [4].

Despite significant progress in person-to-job matching, existing methods only focus on modeling the textual semantic information of target resumes and job postings. However, extensive experience gained from past successful recruits is also essential, further supporting current recruiting. For example, seasoned recruiters typically evaluate hiring from two perspectives when considering a candidate's suitability for a job. On the one hand, recruiters consider whether the context of the resume (*e.g.*, experience and skills) fits the context of the job posting (*e.g.*, competency requirements). On the other hand, the experience of historically successful recruitment can be used to guide current recruitment. The historical records can show which experiences are more

https://www.businessofapps.com/data/linkedin-statistics/

²https://www.shrm.org/hr-today/trends-and-forecasting/

research-and-surveys/documents/2017-talent-acquisition-benchmarking.pdf

important for the current job posting and which abilities requirements are more in line with the current resume. Therefore, we propose a novel perspective to model both the text semantic matching and the experience of recruiters for person-job fit.

Inspired by the success of graph neural network (*i.e.*, GNN) based methods [36, 35] in the recommendation system, we apply GNN to incorporate the recruiters' experience into person-job fit problem. Specifically, by finding out all related historical successful records, we first obtain the related resumes and job postings. Then, two graphs are constructed for each recruitment, where the obtained resumes and job postings are treated as the nodes of graphs. Based on the graph we build, GNN can capture the relations between the current item node and the related historical item nodes and generate node embedding vectors correspondingly. Finally, the latent node representation is used to generate the global embedding, which is considered as the hidden features of experiences gained from the historical recruitment records.

Our model presents a novel perspective on modeling in the person-job fit task. To the best of our knowledge, we are the first to model the experience of recruiters by introducing graph neural networks into the person-job fit task. We evaluate our proposed model on a large-scale real-world data set, and extensive experiment results have demonstrated the effectiveness of our model.

2. Problem Formulation

In this paper, we focus on improving the accuracy of the person-job fit task, which aims at measuring the matching degree between the job description posted by a company and the resume submitted by an employee.

In this work, we use the experience of historical successful job applications to guide the current job application. For this purpose, we introduce the "historical successful recruitment record". We will define the "historical successful recruitment record" and the task of person-job fit, respectively. Important notations and their corresponding definitions are shown in Table 1.

Following [30] [4], we use J to denote a **job posting** which have m ability requirements (e.g., C++ programming and Data Mining skills, Team Work, Communication

Table 1: Notations and Definitions.

Notation	Definition
$J = \{j_1, j_2,, j_m\}$	A job posting which contains <i>m</i> ability requirements.
$j_l = \{j_{l,1}, j_{l,2},, j_{l,o_l}\}$	An ability requirement j_l which contains o_l words.
$R = \{r_1, r_2,, r_n\}$	A resume which have n pieces of experience.
$r_k = \{r_{k,1}, r_{k,2}, \dots, r_{k,o_k}\}$	A piece of experience r_k which contains o_k words.
$P = \{p_1, p_2,, p_k\}$	k job applications in the total set of job applications P .
Y	The recruitment result of this job application.
$p_i = (J_i, R_i, Y_i)$	A job application which consists of a job posting J , a
	resume R and a recruitment result Y .
P_h	The set of historically successful recruitment records.

Skill and Sincerity). Moreover, each ability requirement j_l is assumed to contain o_l words.

Similarly, we use R to denote a **resume** which have n pieces of experience (*e.g.*, education experiences, competition experiences, research paper publications and job experiences). Moreover, each piece of the experience r_k is assumed to contain o_k words.

We use P to indicate the total set of job applications along this line. Each p_i in P indicates a job application composed by a J-R pair, and a label Y indicates the recruitment result of this job application, *i.e.*, Y = 1 means the resume successfully passed the job description request, and the candidate entered the interview session. While Y = 0 means the failed one. Thus, p_i can be denoted as $p_i = (J_i, R_i, Y_i)$. Significantly, the same J may exist in many different job applications, and so does R. However, the same J-R pair has one and only one in P.

Next, we use P_h to indicate the set of historically successful recruitment records, which is used as an experience to guide a new job application. Thus, P_h is a subset of P with each label Y in P_h is equal to 1. We define $P_h = \{(J, R, Y) \mid (J, R, Y) \in P \text{ and } Y = 1\}$, where $P_h \subset P$.

Finally, we give the definition of the person-job fit task. Given a target set P_t , $P_t \subset P$ and a historical successful recruitment record set P_h , where $P_h \cap P_t = \emptyset$. The goal of the person-job fit task is to learn a predictive model M. Under the guidance of P_h , M predicts a label \hat{Y} for each J-R pair in P_t by calculating the matching degree




Figure 1: An illustration of the proposed PJFCANN, which consists of three parts: Self-Semantic Representation, Historical Recruitment Experience Representation and Person-Job Fit Label Prediction.

between each J and R in P_t .

$$\hat{M} = \arg\min_{M} loss(M(\hat{Y}|P_h, P_t), Y)$$
(1)

3. THE PROPOSED MODEL

In this section, we will illustrate the details of our model. As shown in Figure 1, PJFCANN consists of three parts, namely *self-semantic representation*, *historical recruitment experience guidance* and *person-job fit label prediction*.

3.1. Self-Semantic Representation

Self-semantic representation aims at calculating the semantic similarity between job postings and resumes. As we mentioned in the introduction, it is unreasonable to only consider job postings and resume as simple text.

After obtaining the documents of users' requirements and experience, it is essential to use a neural network to extract the textual features from documents. A simple way is to use a recurrent neural network (RNN). However, RNN mainly focuses on short sentences while dealing with long-form documents. Thus we choose mashRNN [18], which learns the document representations from multiple abstraction levels of the document structure and is capable of dealing with the long-form document. Compared with

LSTM and GRU, mashRNN learns a more comprehensive semantic representation of the entire document via the information in different structure levels.

$$\mathbf{h}_{j,i} = \mathrm{mashRNN}(\mathbf{E}_{i}^{J}),$$

$$\mathbf{h}_{r,i} = \mathrm{mashRNN}(\mathbf{E}_{i}^{R}),$$
(2)

where \mathbf{E}_{i}^{J} and \mathbf{E}_{i}^{R} denote the matrix of word vectors for the *i*-th requirement in job posting and the *i*-th experience in resume, respectively. $\mathbf{h}_{j,i} \in \mathcal{R}^{d}$ and $\mathbf{h}_{r,i} \in \mathcal{R}^{d}$ are the output of mashRNN and can be regarded as the semantic feature representation of the *i*-th ability requirement in job posting and the *i*-th experience in resume, respectively. *d* is the dimension of the vectors.

After generating the feature vector, we calculate the matching degree between each requirement and each experience. To capture the semantic similarity between job postings and resumes, co-attention neural networks are employed to quantify the matching contributions of each candidate experience to a specific ability requirement.

Here we use an attention-based relation score $\eta_{l,k}$ to quantify the matching contribution of each ability requirement J_k to each candidate experience R_l , which can be calculated as follows,

$$e_{l,k} = \mathbf{v}_{1}^{\mathrm{T}} \tanh(\mathbf{W}_{1}\mathbf{h}_{r,l} + \mathbf{U}_{1}\mathbf{h}_{j,k}),$$

$$\eta_{l,k} = \frac{\exp(e_{l,k})}{\sum_{k=1}^{m} \exp(e_{l,k})},$$

$$\mathbf{h}_{l}^{J} = \sum_{k=1}^{m} \eta_{l,k}\mathbf{h}_{j,k},$$
(3)

where $\mathbf{W}_1 \in \mathcal{R}^{d \times d}$ and $\mathbf{U}_1 \in \mathcal{R}^{d \times d}$, $\mathbf{v}_1 \in \mathcal{R}^{d \times 1}$ are trainable parameters and $\mathbf{h}_l^J \in \mathcal{R}^d$ is the learnt semantic feature representation of ability requirement. Similar to relation score $\eta_{l,k}$, we can also obtain the relation score $\epsilon_{k,l}$ to quantify the matching contribution of each candidate experience R_l to the each ability requirement \mathbf{J}_k as follows,

$$e_{k,l} = \mathbf{v}_{2}^{\mathrm{T}} \tanh(\mathbf{W}_{2}\mathbf{h}_{j,k} + \mathbf{U}_{2}\mathbf{h}_{r,l}),$$

$$\epsilon_{k,l} = \frac{exp(e_{k,l})}{\sum_{l=1}^{n} exp(e_{k,l})},$$

$$\mathbf{h}_{k}^{R} = \sum_{l=1}^{n} \epsilon_{k,l}\mathbf{h}_{r,l},$$
(4)

where $\mathbf{W}_2 \in \mathcal{R}^{d \times d}$, $\mathbf{U}_2 \in \mathcal{R}^{d \times d}$ and $\mathbf{v}_2 \in \mathcal{R}^{d \times 1}$ are trainable parameters and $\mathbf{h}_k^R \in \mathcal{R}^d$ is the learnt semantic feature representation of experience.

Then we add another attention layer to learn the importance of each representation of requirement \mathbf{h}_l^J and each representation of experience \mathbf{h}_k^R respectively. Specifically, we calculate the importance ζ_l of each requirement representation \mathbf{h}_l^J to generate the final local job posting vector \mathbf{H}_{local}^J as follows,

$$c_l^J = \mathbf{v}_{\zeta}^{\mathrm{T}} \tanh(\mathbf{W}_3 \mathbf{h}_l^J + \mathbf{b}_3),$$

$$\zeta_l = \frac{exp(c_l^J)}{\sum_{l=1}^n exp(c_l^J)},$$

$$\mathbf{H}_{local}^J = \sum_{l=1}^n \zeta_l \mathbf{h}_l^J,$$
(5)

where $\mathbf{v}_{\zeta}^{\mathrm{T}} \in \mathcal{R}^{d \times 1}$, $\mathbf{W}_{3} \in \mathcal{R}^{d \times d}$ and $\mathbf{b}_{3} \in \mathcal{R}^{d}$ are trainable parameters. $\mathbf{H}_{local}^{J} \in \mathcal{R}^{d}$ are the obtained local semantic vectors of job postings. And we can also calculate the importance μ_{k} of each candidate experience \mathbf{h}_{k}^{R} to generate the final local resume vector H_{local}^{R} as follows,

$$c_k^R = \mathbf{v}_{\mu}^{\mathrm{T}} \tanh(\mathbf{W}_4 \mathbf{h}_k^R + \mathbf{b}_4),$$

$$\mu_k = \frac{exp(c_k^R)}{\sum_{k=1}^m exp(c_k^R)},$$

$$\mathbf{H}_{local}^R = \sum_{k=1}^m \mu_k \mathbf{h}_k^R,$$
(6)

where $\mathbf{v}_{\mu}^{\mathrm{T}} \in \mathcal{R}^{d \times 1}$, $\mathbf{W}_{4} \in \mathcal{R}^{d \times d}$ and $\mathbf{b}_{4} \in \mathcal{R}^{d}$ are trainable parameters. $\mathbf{H}_{local}^{R} \in \mathcal{R}^{d}$ are the obtained local semantic vectors of resumes.

3.2. Historical Recruitment Experience Representation

In this part, we focus on modeling the experience of recruiters to guide the current recruitment by using historical successful recruitment records P_h . We illustrate the details of *building graph matrix, learning the node embedding* and *modeling the experience of recruiters.*

3.2.1. Building Graph Matrix

For each recruitment, we build two undirected graphs, named **Graph J-J** and **Graph R-R**, respectively. As from Figure 1, Graph J-J $G_J = (V_J, E_J)$ contains the




Figure 2: An illustration of the GNN cell. In the GNN cell, we first aggregate the neighbor nodes to generate the neighbor representation \mathbf{a}_t , then the new target representation \mathbf{g}_t is obtained based on the neighbor representation \mathbf{a}_t and original target representation \mathbf{g}_{t-1} .

historical job postings and current job posting J_c as nodes and the set of edges E_J representing their relations. Similarly, Graph R-R $G_R = (V_R, E_R)$ contains the historical hired Resumes and current Resume R_c as nodes and the set of edges E_R representing their relations. We described the details of constructing the Graph J-J as follows and the construction process of Graph R-R is similar.

For the current recruitment pair (J_c, R_c) , the first step to build Graph J-J is to find all job postings related to J_c . The search strategy is finding a set of job posting J_r where $J_i \in J_r$ meet the condition $(J_i, R_c, 1) \in P_h$. After searching, each $J_i \in J_r$ is marked as the related job postings of current job posting J_c .

The second step is calculating the edge weight to construct an adjacency matrix for each graph. First, we consider J_c and the related job postings $[J_1, J_2, ..., J_q]$ found by search strategy as different single nodes, we first obtain the representations based on BiLSTM with attention mechanism [42] and then use the *cosine similarity function* to calculate the similarity between two nodes to construct the adjacency matrix A^J ,

$$\mathbf{A}^{J}[1][2] = cosine\left(BiLSTM(J_{1}), BiLSTM(J_{2})\right)\right),\tag{7}$$

where BiLSTM denotes the BiLSTM with attention mechanism from [42] and cosine denotes the cosine similarity function. Note that we compute edge weight for every two nodes in the graph, which means the constructed graph is a complete graph.

3.2.2. Learning Node embedding on Graph Matrix

After building the graph matrix, we get two matrices A^J and A^R , which consider each job posting in Graph J-J and each resume in Graph R-R as a single node. As shown in Figure 2, the node representations are learnt by the update functions of GNN cell as follows:

$$\mathbf{a}_{i}^{t} = \mathbf{A}_{i}([\mathbf{g}_{0}^{t-1}, \dots, \mathbf{g}_{n}^{t-1}]^{\mathrm{T}}\mathbf{H}^{t} + \mathbf{b}^{t}),$$

$$\mathbf{z}_{i}^{t} = \sigma(\mathbf{W}_{z}^{t}\mathbf{a}_{t}^{t} + \mathbf{M}_{z}^{t}\mathbf{g}_{i}^{t-1}),$$

$$\mathbf{r}_{i}^{t} = \sigma(\mathbf{W}_{r}^{t}\mathbf{a}_{t}^{t} + \mathbf{M}_{r}^{t}\mathbf{g}_{i}^{t-1}),$$

$$\tilde{\mathbf{g}}_{t}^{t} = \tanh(\mathbf{W}_{h}^{t}\mathbf{a}_{t}^{t} + \mathbf{M}_{h}^{t}(\mathbf{r}_{i}^{t} \odot \mathbf{g}_{i}^{t-1})),$$

$$\mathbf{g}_{i}^{t} = (1 - \mathbf{z}_{i}^{t}) \odot \mathbf{g}_{i}^{t-1} + \mathbf{z}_{i}^{t} \odot \tilde{\mathbf{g}}_{i}^{t},$$
(8)

where $[g_0^t, \ldots, g_n^t] \in \mathbb{R}^{d \times n}$ is the list of node vectors in current label graph matrix at layer $t, A_i \in \mathbb{R}^{1 \times n}$ is *i*-th row of the matrix corresponding to node *i*. H^t, W_z^t, M_z^t , $W_r^t, M_r^t, W_h^t, M_h^t \in \mathbb{R}^{d \times d}$ and $b^t \in \mathbb{R}^d$ are the parameters to learn. $z^t \in \mathbb{R}^d$ and $r^t \in \mathbb{R}^d$ are the reset and update gates respectively. \odot is element-wise multiplication. $\sigma(\cdot)$ is the logistic function. Note that we construct a trainable job posting embedding matrix $\mathbf{H}^{GJ} \in \mathbb{R}^{|J| \times d}$ and resume embedding matrix $\mathbf{H}^{GR} \in \mathbb{R}^{|R| \times d}$ here. And the initial representations of the nodes (*i.e.*, \mathbf{g}^0) are obtained by looking up the embedding matrices \mathbf{H}^{GJ} and \mathbf{H}^{GR} .

After feeding two matrices into the respective gated graph neural network, we obtain the representations of all nodes in Graph J-J and Graph R-R, respectively, which are denoted as \mathbf{g}^J and \mathbf{g}^R , respectively. Among these, \mathbf{g}_0^J and \mathbf{g}_0^R indicate the representation of input job posting and resume (*i.e.*, J and R in the Figure 1), respectively.

3.2.3. Modeling the Experience of recruiters

After getting the final node vectors in Graph J-J and Graph R-R, we further extract more high-level representations for modeling the experience of recruiters. The recruiter knows precisely which ability in resumes he successfully passed is a strong match for this job posting and which requirement in job postings has a high matching degree with this resume. We define the two experiences above as relation J-R and R-J, respectively.

Relation J-R focuses on enhancing the modeling of candidate abilities. First, we apply the soft-attention mechanism to map the job postings (*i.e.*, historical successful

recruitment records for the current resume) embeddings to Graph R-R vector space.

$$\alpha_{i} = \mathbf{v}_{j}^{\mathrm{T}} \sigma(\mathbf{W}_{j} \mathbf{g}_{i}^{J} + \mathbf{c}),$$

$$\mathbf{V}_{R} = \sum_{i=1}^{q} \alpha_{i} \mathbf{g}_{i}^{J},$$
(9)

where \mathbf{g}_i^J denotes each node vector in the Graph J-J, parameters $\mathbf{v}_j \in \mathcal{R}^{d \times 1}$ and $\mathbf{W}_j \in \mathcal{R}^{d \times d}$ denotes the trainable parameters. $\mathbf{V}_R \in \mathcal{R}^d$ denotes the representation of job postings in Graph R-R vector space. It estimates the outstanding skills that recruiters have valued in past successful hires. We use another attention mechanism to estimate the matching degree between each job posting and \mathbf{V}_R .

$$f_t^R = \mathbf{v}_\beta^{\mathrm{T}} \tanh(\mathbf{W}_\beta \mathbf{V}_R + \mathbf{U}_\beta \mathbf{g}_t^J),$$

$$\beta_t = \frac{exp(f_t^R)}{\sum_{t=0}^q exp(f_t^R)},$$

$$\mathbf{e}^J = \sum_{t=0}^q \beta_t \mathbf{g}_t^J,$$
(10)

where $\mathbf{v}_{\beta} \in \mathcal{R}^{d \times 1}$, $\mathbf{W}_{\beta} \in \mathcal{R}^{d \times d}$ and $\mathbf{U}_{\beta} \in \mathcal{R}^{d \times d}$ are the parameters to be learned during the training processing. The attention score β can be seen as the matching degree between requirements in job postings and ability in current resume. \mathbf{e}^{J} denotes the experience from relation J-R.

Finally, we concatenate the job posting representation \mathbf{g}_0^J from Graph J-J with the experience representation e^J from relation J-R and consider the output as the global vector of the resume.

$$\mathbf{H}_{global}^{J} = \tanh(\mathbf{W}_{J}[\mathbf{g}_{0}^{J}; \mathbf{e}^{J}] + \mathbf{b}_{J}), \tag{11}$$

where $\mathbf{W}_J \in \mathcal{R}^{d \times 2d}$ and $\mathbf{b}_J \in \mathcal{R}^d$ are the parameters to learn.

Relation R-J focus on modeling the recruiter's personal preferences. First we apply the soft-attention mechanism to map presentation of the resumes (*i.e.*, historical successful recruitment records for the current job posting) embeddings to Graph J-J vector space.

$$\gamma_i = \mathbf{q}_r^{\mathrm{T}} \sigma(\mathbf{W}_r \mathbf{g}_i^R + \mathbf{c}),$$

$$\mathbf{V}_J = \sum_{i=1}^p \alpha_i \mathbf{g}_i^R,$$
(12)

where \mathbf{g}_i^R denotes each node vector in the Graph R-R, parameters $\mathbf{q}_r \in \mathcal{R}^{d \times 1}$ and $\mathbf{W}_r \in \mathcal{R}^{d \times d}$ denotes the trainable parameters. \mathbf{V}_J denotes the representation of resumes in Graph J-J vector space, and estimates the outstanding skills that recruiters have valued in past successful hires. We use another attention mechanism to estimate the matching degree between each resume and \mathbf{V}_J .

$$f_t^J = \mathbf{v}_{\delta}^{\mathrm{T}} tanh(\mathbf{W}_{\delta} \mathbf{V}_J + \mathbf{U}_{\delta} \mathbf{g}_t^R),$$

$$\delta_t = \frac{exp(f_t^J)}{\sum_{t=0}^{q} exp(f_t^J)},$$

$$e^R = \sum_{t=0}^{p} \delta_t g_t^R,$$
(13)

where $\mathbf{v}_{\delta} \in \mathcal{R}^{d \times 1}$, $\mathbf{W}_{\delta} \in \mathcal{R}^{d \times d}$ and $\mathbf{U}_{\delta} \in \mathcal{R}^{d \times d}$ are the parameters to be learned during the training processing. The attention score δ can be seen as the matching degree between requirements in job postings and ability in current resume. \mathbf{e}^{R} denotes the experience from relation R-J. Finally, we concatenate the resume representation from Graph R-R \mathbf{g}_{0}^{R} with the experience representation from relation R-J \mathbf{e}^{R} , and consider the output as the global information vector of the current resume.

$$\mathbf{H}_{global}^{R} = \tanh(\mathbf{W}_{R}[\mathbf{g}_{0}^{R}; \mathbf{e}^{R}] + \mathbf{b}_{R}), \qquad (14)$$

where $\mathbf{W}_R \in \mathcal{R}^{d \times 2d}$ and $\mathbf{b}_R \in \mathcal{R}^d$ are the parameters to learn.

3.3. Person-Job Fit Label Prediction

After we get the local semantic vectors \mathbf{H}_{local}^{J} , \mathbf{H}_{local}^{R} and the global information vectors \mathbf{H}_{global}^{J} , \mathbf{H}_{global}^{R} , we first concatenate the local vectors and the global vectors. Then, a comparison mechanism is applied based on a fully connected network to measure the matching degree between the job posting and the resume. Finally, we send the

Table 2: Statistics of the dataset

Statistics	Values
job postings number	21661
resumes number	2437
# of successful applications	12112
# of failed applications	38354
Average words per job posting	359.44
Average words per resume	53.51

output **D** of the fully connected network into a logistic function to get the predicted label \tilde{y} .

$$\begin{aligned} \mathbf{H}^{J} &= [\mathbf{H}_{local}^{J}; \mathbf{H}_{global}^{J}], \\ \mathbf{H}^{R} &= [\mathbf{H}_{local}^{R}; \mathbf{H}_{global}^{R}], \\ \mathbf{D} &= \tanh(\mathbf{W}_{d}[\mathbf{H}^{J}; \mathbf{H}^{R}; \mathbf{H}^{J} - \mathbf{H}^{R}] + \mathbf{b}_{d}), \\ \hat{Y} &= \sigma(\mathbf{W}_{y}\mathbf{D} + \mathbf{b}_{y}), \end{aligned}$$
(15)

where $\mathbf{W}_d \in \mathcal{R}^{d_2 \times 6d}$, $\mathbf{b}_d \in \mathcal{R}^{d_2}$, $\mathbf{W}_y \in \mathcal{R}^{1 \times d_2}$, $\mathbf{b}_y \in \mathcal{R}^1$ are the parameters to learn and $\hat{Y} \in [0, 1]$ is the prediction result. $\sigma(\cdot)$ is the logistic sigmoid function. To optimize our model, we adopt the binary cross-entropy loss over the entire training data as the total loss.

4. Experiments

In this section, we first introduce the data set and detailed experimental settings. Then, we report the performances of our model and baseline methods, followed by the analysis of the results.

4.1. Experimental Settings

We introduce the details in our experiment setting, including the data set, word embedding, settings of PJFCANN, and settings of the training stage.

• **Dataset.** We evaluate our model on a large real-world data set provided by an online recruitment company. To protect the privacy of users, all private information is anonymously processed.




Figure 3: The words distribution of resume and job posting.

In this dataset, for a particular pair of a job posting and a resume, three labels are marking the relation between the job posting and the resume, namely "browsed", "delivered" and "satisfied". The label "browsed" means whether the user has been browsed this job posting online, the label "delivered" means whether the user has delivered his resume to this job posting online, the label "satisfied" indicates whether the user matches this job after interviews. Each label's value is chosen in $\{0, 1\}$ where 1 means yes and 0 means no. We mark the "satisfied" pairs as the successful applications and mark those pairs which are marked "delivered" but not marked "satisfied" as failed applications.

The data set consists of 4465 user resumes, 269534 job postings, total pair number is 6971621. There are 31696 pairs marked "satisfied", 150930 pairs marked "delivered", 310521 pairs marked "browsed". According to the word distribution shown in Figure 3, we consider those resumes whose word number is less than 15 as incomplete resumes and those job postings whose word number is less than 50 as incomplete job postings. To ensure the quality of experiments, those incomplete resumes and job postings are removed. We also set the maximum number of words in job postings without successful applications are also removed. Statistics of the pruned data are summarized in Table 2.

According to the recruitment acceptance rates, there are many more failed applications than successful ones, which leads to a typical imbalanced situation. Therefore,




Figure 4: An illustration of the split of dataset

we randomly select some failed applications to keep up with the same number of successful applications.

Because the model needs to use external data to build the graph, for fairness, we divide the data set as follows (Figure 4). For baseline methods, we first divide the data set into 10 pieces. In each piece, the number of successful and failed applications is equal. And we randomly select 9 pieces of the training set, the left 1 piece in the testing set. For PJFCANN, to be fair, we construct the Historical Recruitment Results P_h only from the training set. We randomly select 5 pieces from the 9 pieces training set and consider the successful applications in the 5 pieces as P_h . The left 4 pieces are used for training, the 1 pieces testing set is still used for testing. In the training set, 10% is used for validation, and 90% is used for training. The reason for dividing the piece of P_h and training is that we found this ratio is optimal. The experiment about the effect of P_h 's size is in subsection 5.4.

• **Experimental parameter setting.** We used the GloVe³ to pre-train the word embedding, and used the pre-trained word embedding results to initialize the embedding layer weights. We set the dimension of word embedding as 200.

Following [18] [36], we set the dimension of hidden state in mashRNN as 1024 and the dimension of hidden state output by mashRNN d is set to 200. The dimension of hidden state after fully connected network d_2 is set to 512. And the number of GNN

³https://nlp.stanford.edu/projects/glove/

layers is set to 1.

We optimize the model by using Adam [21] algorithm, and we set batch size as 16 for training and add the dropout layer with the probability of 0.5 to prevent overfitting. All parameters are initialized using a Gaussian distribution with a mean of 0 and a standard deviation of 0.1. The initial learning rate is set to 0.1 and will decay by 0.1 after every 2 epochs. The L2 penalty is set to 10^{-5} . The model is trained on a server with 6-cores CPU@3.20GHz, 32GB RAM, and a GeForce GTX 1080 GPU.

We adopt the four most commonly used evaluation metrics, which are *Accuracy*, *Precision*, *Recall* and *F1* score respectively.

4.2. Baseline Methods

We select some state-of-the-art supervised models as baseline methods, and we compare our model PJFCANN with these baseline methods to verify the effect of our model.

• **Classic Supervise Learning Methods.** Following [30], we implement two classic supervise learning methods, *Random Forests* (RF) and *Gradient Boosting Decision Tree* (GBDT). we construct the representation by using the *Bag-of-words vectors* as the input features.

• **DSSM**[16] utilizes the deep neural network (DNN) to learn dense feature representation on job posting and resume respectively, and calculates the semantic similarity of the feature representation pair.

• **RE2**[38] is a general-purpose text-matching framework. The two text sequences are symmetrically processed before the prediction layer, and all parameters except those in the prediction layer are shared between the two sequences. We consider the resume text and the job posting text as two sequences respectively.

• **PJFNN**[44] proposes a bipartite Convolutional Neural Networks to effectively learn the joint representation of resumes and job postings.

• **BERT**[7] is a language representation model which can be fine-tuned on the semantic textual similarity task. We consider the resume text and the job posting text as two sequences respectively and we fine-tuned the model based on $BERT_{BASE}$.

• **BPJFNN**[30] is a simplified version of APJFNN. It considers resumes and job postings as two single sequences and applies Bi-LSTMs to learn the semantic representation of each word in the two sequences.

• **APJFNN**[30] considers each experience in resume and each requirement in job postings as a sequence, and it applies four hierarchical ability-aware attention strategies based on BPJFNN to learn a word-level semantic representation for both job requirements and resumes.

• SCLPJF[4] consists of *Single Domain part* and *Domain Adaptation part*. In the Single Domain part, it first utilizes RNN to encode the sequence, and then model global semantic interactions between sequence representations of a resume and job postings. In the Domain Adaptation part, it utilizes the SCL algorithm to learn transferable match patterns and components from a domain with sufficient labeled data to a domain without sufficient labeled data. Because our dataset did not have a domain label and can not support the Domain Adaptation part, we only compare our model with SCLPJF's Single Domain part.

• **MV-CoN**[3] consist of *text-based matching model* and *relation-based matching model*. The text-based matching model is implemented by BERT and Transformer architecture. The relation-based matching model builds a job-resume relation graph and uses GNN to aggregate each node's representation. A co-teaching mechanism is used to reduce the influence of noise in training data.

• **PJFCANN** (w/o GNN) is a variant of PJFCANN, which removes the H_{global} part and only uses the H_{local} part. Without the H_{global} part, PJFCANN (w/o GNN) can not obtain the graph information (*i.e.*, historical success recruitment records).

4.3. Overall Results

The performance is shown in Table 3, clearly that our model outperformed all the baselines with a significant margin.

The performance of classic supervised models (*i.e.*, RF and GBDT) are not satisfactory, which is because they use the Bag-of-Words vectors to characterize the semantic features, whose representation ability is somehow limited compared with pre-trained

Methods	Accuracy	Precision	Recall	F1
RF	0.6646	0.6783	0.6261	0.6512
GBDT	0.6807	0.6923	0.6507	0.6708
DSSM	0.6723	0.6830	0.6431	0.6624
RE2	0.7115	0.7074	0.7215	0.7144
PJFNN	0.6938	0.6927	0.6969	0.6948
BERT	0.7123	0.7084	0.7215	0.7149
BPJFNN	0.7107	0.7051	0.7246	0.7147
APJFNN	0.7415	0.7364	0.7523	0.7443
SCLPJF (Single Domain)	0.7146	0.7123	0.7200	0.7161
MV-CoN	0.7496	0.7733	0.7063	0.7383
PJFCANN (w/o GNN)	0.7353	0.7361	0.7338	0.7349
PJFCANN	0.8076	0.7994	0.8215	0.8103

Table 3: Performance of PJFCANN and baselines.

word vectors. Besides, the results also show that the deep learning methods can capture the semantic features better than classic supervised models.

Then we can observe that DSSM does not perform well over four metrics because it fails to capture the sequential properties in the textual information. RE2 and PJFNN obtain better performance than DSSM. However, they use convolutional neural networks to get the semantic features from the long-document sentences, which is still insufficient to capture sequential information in the sentences.

Compared our model PJFCANN with BERT, PJFNN, BPJFNN, SCLPJF, and MV-CoN, it shows that our model outperforms baseline methods over four metrics. This is because these methods only focus on the textual information of current job and resume, while not fully use of the historical successful recruitment records. Although MV-CoN creates a job-resume graph based on the category labels at the bottom layer and keywords, it still suffers from two limits. Firstly, the job-resume graph based on the category labels and keywords is sparsity, which can only provide limited information. Secondly, the category labels may not exist in many real scenes, and the reliability of keywords needs to be judged due to the complexity of jobs and resumes. Unlike MV-CoN, our method uses the historical successful recruitment database to construct the job-resume graph, which is more dense and reliable.

Compared with all baselines above, our model had two main advantages. In the




Figure 5: The effect of P_h 's size and H_{global} 's dimension to the model

first point, our model not only learn the local representation from the text semantic information but also learn the global representation from the historical successful recruitment records. And the second point, our model had the ability to reference the experience of the recruiter, by introducing GNN, our model used the historical experience to represent the current resume and job posting, the attention mechanism help to model the recruiter's preferences and the candidate's abilities. The results indicates that our novel perspective improves the performance of the Person-Job Fit task. Furthermore, by comparing PJFCANN and PJFCANN (w/o GNN), we can observe that PJFCANN outperforms PJFCANN w/o GNN significantly, where the average improvements of PJFCANN are 10.16% over PJFCANN w/o GNN in terms of four metrics. The result demonstrates the importance of historical success recruitment records P_h and the superiority of our GNN module.

4.4. Effect of P_h 's Size

As we mention before, we divide the dataset into 10 pieces, randomly selected 9 pieces for training set, the left 1 pieces for testing set. And we randomly selected 5 pieces from the 9 pieces training set and consider the successful applications in the 5 pieces as P_h , the left 4 pieces is used for training. It is obviously that the size of P_h and the size of training set affect the result predicted by PJFCANN.

Therefore, we test the effect of P_h 's size on the model. The results are shown in Figure 5, where the X-axis denotes the ratio of the dimension of H_{global} to the dimension of concatenation vector H ($H = concat(H_{global}; H_{local})$), the Y-axis denotes the ratio of P_h 's size to training set's size, the Z-axis denotes the accuracy tested on current model. Both the X-axis and the Y-axis's range are from 0 to 1 (including 0 and 1). The larger value of the X-axis is, the greater proportion of the vector generated by GNN in the final vector representation means that the historical experience has a greater impact on current recruitment. The larger value of the Y-axis is, the greater proportion of the historical successful recruitment records P_h 's size in the total training set's size means that there is more data to build the graph and less data to train text semantics.

We analyze the result from four perspectives, as shown in Figure 5, when x and y are both small, which means the recruiter is more focused on match text semantics of the current recruitment, the accuracy is around 68%. When x and y are both big, the recruiter pays most attention to getting guidance from the historically successful recruitment records, the accuracy is around 63%. This phenomenon indicates that there are limitations to modeling person-job fit tasks only from text semantics or historical recruiter's experience.

However, when x is extensive and y is small, the recruiter shows more attention to match the text semantics of the current recruitment without enough semantic training data. The accuracy is very low and only around 35%. When x is small, and y is extensive, the recruiter pays the most attention to get guidance from the historical successful recruitment records without enough records data, the accuracy is also very low and only around 42%.

The highest accuracy happens when x is about 0.2 and y is about 0.6, which shows that the best results could be obtained when the semantic characteristics of the text are

Table 4: Effect of the similarity function.

Similarity function	Accuracy	Precision	Recall	F1
PJFCANN (mean+word2vec)	0.6315	0.6359	0.6154	0.6255
PJFCANN (tf-idf+word2vec)	0.6539	0.6793	0.6323	0.6549
PJFCANN (WMD)	0.6461	0.6513	0.6292	0.6401
PJFCANN (SIF+word2vec)	0.7207	0.7151	0.7338	0.7243
PJFCANN (CNN)	0.7615	0.7537	0.7769	0.7651
PJFCANN (BiLSTM)	0.7684	0.7722	0.7615	0.7668
PJFCANN (BiLSTM+attention)	0.8031	0.7949	0.8169	0.8057

considered together with the historical experience.

4.5. Effect of the Encoder for Similarity Function

As we mention in section 4.2, to get each value in the final matrix, we need a similarity function to calculate the similarity between two resumes or job postings when building a graph. Therefore, we test the effect of the different encoder of similarity functions on the model. The similarity function can be divided into two categories: *unsupervised* and *supervised*.

• Unsupervised. We evaluate 4 unsupervised methods, namely *mean*, *tf-idf*, *smooth inverse frequency(SIF)*[1] and *Word Mover's Distance (WMD)*[22]. First, we use a word vector to represent each word in the sentence, then we obtain the corresponding sentence embedding according to the different weights of the methods. Finally, we calculate the difference between the embeddings due to the similarity.

• **Supervised.** The supervised methods differ from unsupervised methods and require pretraining. For fairness, we train the supervised model based on the training set we split in subsection 5.1.

For resume, we generate the resume pairs from the applications with the same job posting, and we label the successful application resume pair 1 indicates the high semantic similarity and label the failed application resume pair 0. we did the same label step with job posting pairs. The ratio of the training set to the valid set is 4:1.

We evaluate 3 supervised methods which are all end-to-end models based on *CNN*, *BiLSTM* and *BiLSTM+attention* respectively. We use two encoders to generate two hidden representations from the two input sequences, respectively, then treat softmax's output as the value of similarity.

Table 5: The comparison of inference latency.

Methods	Latency (s)
BPJFNN	1.624
APJFNN	2.872
MV-CoN	3.928
PJFCANN (w/o GNN)	1.826
PJFCANN	2.622

The testing results are shown in Table 4. The supervised methods are better than the unsupervised methods. This phenomenon may indicate that word vectors are not enough to characterize the semantic features of the recruitment textural data. The representation after neural network's fine-tune can capture more accurate semantic information. The method based on BiLSTM + attention works best, which may indicate the attention strategies can capture the critical information in more detail and improve the performance with a better estimation of matching results.

4.6. Inference Efficiency Comparison

The inference efficiency is essential for job-resume problem in real-world scenes. Thus we conduct experiments here to evaluate the inference efficiency of our method. Specifically, we compare the inference latency (*i.e.*, the time cost for the inference of test data) between our method PJFCANN with selected representative methods. The evaluation is conducted on a server with 6-cores CPU@3.20GHz, 32GB RAM, a GeForce GTX1080 GPU, and batch size of 32.

The results are shown in Table 5, it can be observed that the inference efficiency of our method is competitive by comparing with other representative baselines. In this work, we use gate graph neural network to model the historical success records, and the number of layers is set to 1. The inference latency of PJFCANN is higher than PJFCANN (w/o GNN), which demonstrates that GNN is more time-complex and needs to cost more time in inference. However, the inference latency of PJFCANN is still lower than APJFNN and MV-CoN, which demonstrates the superiority of our model.




Figure 6: An illustrative example for showing the effect of historical records.

4.7. Case Study

To further show the importance of historical success recruitment records, in Figure 6 we present some case studies for understanding the working mechanism from a qualitative perspective.

Form case 6a, we can observe that it is hard to directly compute the matching degree between job posting J and resume R. The job posting J focus on "human resources specialist" and "administrative management" ability. However, it is difficult to directly capture the correlation between these requirements and the content on the candidate resume R. By incorporating the historical success recruitment records of job posting J and resume R, we can easily find the correlation between resume R2 and candidate resume R (*e.g.*, Education, training and management ability). Thus the model can capture the match signals by incorporating the information of resume R2 into job posting J via GNNs. Similar observation can also be observed from the case 6b. The cases show that using simple text semantic matching is inadequate, and the historical success recruitment records are significant for job-resume matching.

5. Related Work

Our work involves research in two direction: namely *Recruitment Research*, *Deep learning in Text Mining*.

5.1. Recruitment Research

The research on recruitment has never been stopped. With the big open-source data of online recruitment, more and more research task on recruitment analysis has emerged. [33] [43] research the recruitment market trend over time and when to make appropriate job recommendations to a user. [5] [25] research the company profiling to build an in-depth understanding of the company's fundamental characteristics. [12] [17] analyze the differences in job requirements between technical recruitment and non-technical recruitment. [37] propose a data-driven approach for modeling the popularity of job skills based on the analysis of large-scale recruitment data.

The person-job fit [31] which focuses on improving the matching degree between employers' skills and job requirements, is one striking task of recruitment analysis. Early research treats person-job fit as a recommendation problem. Malinowski *et al.* [27] argue that a match between a candidate and a job needs to be bilateral and apply two distinct recommendation systems to improve the matching degree. Following this idea, Lee *et al.* [24] introduces a comprehensive job recommendation problem as a supervised machine learning problem and use naive Bayes hybrid classifier to model it. [8, 15, 26, 41] add different collaborative filtering algorithm into the recommendation system for job seeking and use it on the recruiting website. [40] apply the Generalized Linear Mixed Model into the job recommendation system.

Recent research begins to analyze the person-job fit task from another angle. [44] treat the task as a classification problem and propose an end-to-end model for matching text semantic between resumes and job postings based on Convolutional Neural Network(CNN). Following this idea, [30] keep applying BiLSTMs and Attention mechanism instead of CNN and obtain a better result. Based on this model, [4] add the

Structural Correspondence Learning(SCL) algorithm to solve the problem of unbalanced data in different job categories. MV-coN [3] integrates both text- and relationbased matching models into a unified approach for the job-resume matching, where the relation graph is built based on category and keywords information. However, relying solely on category and keyword information to build graphs may not be reliable enough and will introduce much noise.

Unlike previous works, our proposed PJFCANN leverages the experience of historical success recruitment records to guide the current recruitment, which is necessary and reliable information to enrich the features of resumes and job postings.

5.2. Text Mining with Neural Network

Generally, the study of person-job fit based on textual information can be grouped into the tasks of text mining, which is highly related to Natural Language Processing (NLP) technologies, such as text classification [20] [39], text similarity [11] [20] [32] and reading comprehension [2] [14] Recently, due to the advanced performance and flexibility of deep learning, more and more researchers try to leverage deep learning to solve the text mining problems. Compared with traditional methods that largely depend on the effective human-designed representations and input features (e.g., word n-gram [34], parse trees [6] and lexical features [28]), the deep learning-based approaches can learn effective models for large-scale textural data without labor-intensive feature engineering. Among various deep learning models, Convolutional Neural Network (CNN) [23] and Recurrent Neural Network (RNN) [10] are two representative and widelyused architectures, which can provide effective ways for NLP problems from different perspectives. Specifically, CNN efficiently extracts local semantics and hierarchical relationships in textural data. For instance, as one of the representative works in this field, Kalchbrenner et al. [19] proposed a Dynamic Convolutional Neural Network (DCNN) for modeling sentences, which obtained remarkable performance in several text classification tasks. Furthermore, Kim et al. have shown the power of CNN on a wide range of NLP tasks, even only using a single convolutional layer [20]. From then on, CNN-based approaches have attracted much more attention on many NLP tasks. For example, in [13], He et al. used CNN to extract semantic features from multiple

levels of granularity for measuring the sentence's similarity. Dong et al. introduced a multi-column CNN for addressing the Question Answering problem [9].

6. Conclusions

In this paper, we propose a novel **P**erson-**J**ob-**F**it with **Co**-**A**ttention **N**eural **N**etwork (PJFCANN) model in which the matching degree between the job postings and resumes are predicted based on not only their context but also the related successfully matched job postings and resumes in history, which reflects the recruiters' experiences in a large extent. Specifically, given a target resume-job post pair, PJFCANN first generates the local semantic representations based on a Recurrent Neural Network (RNN). At the same time, PJFCANN generates the global experience representations for the pair based on a Graph Neural Network (GNN). Therefore, the final matching degree is calculated based on the concatenation of these two representations. In this way, the recruiters' experiences are naturally utilized in the matching process. To test the performances of the proposed PJFCANN, extensive experiments were conducted on a large-scale recruitment data set from a commercial online recruitment company. The results verified the effectiveness of PJFCANN compared with several state-of-the-art baselines.

For future work, more prior knowledge information (*e.g.*, knowledge graph) can be incorporated to enhance the ability of text feature learning. And a promising direction is to design more robust ways of graph construction, which can break our dependence on historical data and incorporate more semantic information. Moreover, it is significant to improve the efficiency of the person-job fit (i.e., to implement an online detection system).

7. Acknowledgments

This work was supported in part by the National Natural Science Foundation of China under Grant No.61602197 and Grant No.61772076.

References

- Sanjeev Arora, Yingyu Liang, and Tengyu Ma. 2016. A simple but tough-to-beat baseline for sentence embeddings. (2016).
- [2] Jonathan Berant, Vivek Srikumar, Pei-Chun Chen, Abby Vander Linden, Brittany Harding, Brad Huang, Peter Clark, and Christopher D Manning. 2014. Modeling biological processes for reading comprehension. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. 1499–1510.
- [3] Shuqing Bian, Xu Chen, Wayne Xin Zhao, Kun Zhou, Yupeng Hou, Yang Song, Tao Zhang, and Ji-Rong Wen. 2020. Learning to Match Jobs with Resumes from Sparse Interaction Data using Multi-View Co-Teaching Network. In *Proceedings* of the 29th ACM International Conference on Information & Knowledge Management. 65–74.
- [4] Shuqing Bian, Wayne Xin Zhao, Yang Song, Tao Zhang, and Ji-Rong Wen. 2019. Domain Adaptation for Person-Job Fit with Transferable Deep Global Match Network. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP). 4812–4822.
- [5] Yu Cheng, Yusheng Xie, Zhengzhang Chen, Ankit Agrawal, Alok Choudhary, and Songtao Guo. 2013. Jobminer: A real-time system for mining job-related patterns from social media. In *Proceedings of the 19th ACM SIGKDD international conference on Knowledge discovery and data mining*. ACM, 1450–1453.
- [6] Colin Cherry and Chris Quirk. 2008. Discriminative, syntactic language modeling through latent svms. *Proceeding of Association for Machine Translation in the America (AMTA-2008)* (2008).
- [7] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. arXiv preprint arXiv:1810.04805 (2018).

- [8] Mamadou Diaby, Emmanuel Viennet, and Tristan Launay. 2013. Toward the next generation of recruitment tools: an online social network-based job recommender system. In 2013 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining (ASONAM 2013). IEEE, 821–828.
- [9] Li Dong, Furu Wei, Ming Zhou, and Ke Xu. 2015. Question answering over freebase with multi-column convolutional neural networks. In *Proceedings of the* 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers). 260–269.
- [10] Jeffrey L Elman. 1990. Finding structure in time. *Cognitive science* 14, 2 (1990), 179–211.
- [11] Wael H Gomaa and Aly A Fahmy. 2013. A survey of text similarity approaches. International Journal of Computer Applications 68, 13, 13–18.
- [12] Christopher G Harris. 2017. Finding the Best Job Applicants for a Job Posting: A Comparison of Human Resources Search Strategies. In 2017 IEEE International Conference on Data Mining Workshops (ICDMW). IEEE, 189–194.
- [13] Hua He, Kevin Gimpel, and Jimmy Lin. 2015. Multi-perspective sentence similarity modeling with convolutional neural networks. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*. 1576–1586.
- [14] Karl Moritz Hermann, Tomas Kocisky, Edward Grefenstette, Lasse Espeholt, Will Kay, Mustafa Suleyman, and Phil Blunsom. 2015. Teaching machines to read and comprehend. In *Advances in neural information processing systems*. 1693–1701.
- [15] Wenxing Hong, Siting Zheng, and Huan Wang. 2013. Dynamic user profile-based job recommender system. In 2013 8th International Conference on Computer Science & Education. IEEE, 1499–1503.
- [16] Po-Sen Huang, Xiaodong He, Jianfeng Gao, Li Deng, Alex Acero, and Larry Heck. 2013. Learning deep structured semantic models for web search using

clickthrough data. In Proceedings of the 22nd ACM international conference on Information & Knowledge Management. ACM, 2333–2338.

- [17] Faizan Javed, Phuong Hoang, Thomas Mahoney, and Matt McNair. 2017. Largescale occupational skills normalization for online recruitment. In *Twenty-Ninth IAAI Conference*.
- [18] Jyun-Yu Jiang, Mingyang Zhang, Cheng Li, Michael Bendersky, Nadav Golbandi, and Marc Najork. 2019. Semantic text matching for long-form documents. In *The World Wide Web Conference*. 795–806.
- [19] Nal Kalchbrenner, Edward Grefenstette, and Phil Blunsom. 2014. A convolutional neural network for modelling sentences. arXiv preprint arXiv:1404.2188 (2014).
- [20] Yoon Kim. 2014. Convolutional neural networks for sentence classification. arXiv preprint arXiv:1408.5882 (2014).
- [21] Diederik P Kingma and Jimmy Ba. 2014. Adam: A method for stochastic optimization. arXiv preprint arXiv:1412.6980 (2014).
- [22] Matt Kusner, Yu Sun, Nicholas Kolkin, and Kilian Weinberger. 2015. From word embeddings to document distances. In *International conference on machine learning*. 957–966.
- [23] Yann LeCun, Léon Bottou, Yoshua Bengio, Patrick Haffner, et al. 1998. Gradientbased learning applied to document recognition. *Proc. IEEE* 86, 11 (1998), 2278– 2324.
- [24] Danielle H Lee and Peter Brusilovsky. 2007. Fighting information overflow with personalized comprehensive information access: A proactive job recommender. In *Third International Conference on Autonomic and Autonomous Systems (ICAS'07)*. IEEE, 21–21.
- [25] Hao Lin, Hengshu Zhu, Yuan Zuo, Chen Zhu, Junjie Wu, and Hui Xiong. 2017. Collaborative company profiling: insights from an employee's perspective. In *Thirty-First AAAI Conference on Artificial Intelligence*.

- [26] Yao Lu, Sandy El Helou, and Denis Gillet. 2013. A recommender system for job seeking and recruiting website. In *Proceedings of the 22nd International Conference on World Wide Web*. ACM, 963–966.
- [27] Jochen Malinowski, Tobias Keim, Oliver Wendt, and Tim Weitzel. 2006. Matching people and jobs: A bilateral recommendation approach. In *Proceedings of the* 39th Annual Hawaii International Conference on System Sciences (HICSS'06), Vol. 6. IEEE, 137c–137c.
- [28] Prem Melville, Wojciech Gryc, and Richard D Lawrence. 2009. Sentiment analysis of blogs by combining lexical knowledge with text classification. In Proceedings of the 15th ACM SIGKDD international conference on Knowledge discovery and data mining. ACM, 1275–1284.
- [29] Ioannis Paparrizos, B Barla Cambazoglu, and Aristides Gionis. 2011. Machine learned job recommendation. In *Proceedings of the fifth ACM Conference on Recommender Systems*. ACM, 325–328.
- [30] Chuan Qin, Hengshu Zhu, Tong Xu, Chen Zhu, Liang Jiang, Enhong Chen, and Hui Xiong. 2018. Enhancing person-job fit for talent recruitment: An abilityaware neural network approach. In *The 41st International ACM SIGIR Conference on Research & Development in Information Retrieval*. ACM, 25–34.
- [31] Tomoki Sekiguchi. 2004. Person-organization fit and person-job fit in employee selection: A review of the literature. *Osaka keidai ronshu* 54, 6, 179–196.
- [32] Aliaksei Severyn and Alessandro Moschitti. 2015. Learning to rank short text pairs with convolutional deep neural networks. In *Proceedings of the 38th international ACM SIGIR conference on research and development in information retrieval*. ACM, 373–382.
- [33] Jian Wang, Yi Zhang, Christian Posse, and Anmol Bhasin. 2013. Is it time for a career switch? In Proceedings of the 22nd international conference on World Wide Web. ACM, 1377–1388.

- [34] Sida Wang and Christopher D Manning. 2012. Baselines and bigrams: Simple, good sentiment and topic classification. In *Proceedings of the 50th annual meeting of the association for computational linguistics: Short papers-volume 2*. Association for Computational Linguistics, 90–94.
- [35] Xiang Wang, Xiangnan He, Meng Wang, Fuli Feng, and Tat-Seng Chua. 2019. Neural Graph Collaborative Filtering. arXiv preprint arXiv:1905.08108 (2019).
- [36] Shu Wu, Yuyuan Tang, Yanqiao Zhu, Liang Wang, Xing Xie, and Tieniu Tan. 2019. Session-based recommendation with graph neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 33. 346–353.
- [37] Tong Xu, Hengshu Zhu, Chen Zhu, Pan Li, and Hui Xiong. 2018. Measuring the popularity of job skills in recruitment market: A multi-criteria approach. In *Thirty-Second AAAI Conference on Artificial Intelligence*.
- [38] Runqi Yang, Jianhai Zhang, Xing Gao, Feng Ji, and Haiqing Chen. 2019. Simple and effective text matching with richer alignment features. *arXiv preprint arXiv:1908.00300* (2019).
- [39] Yiming Yang and Jan O Pedersen. 1997. A comparative study on feature selection in text categorization. In *Icml*, Vol. 97. 35.
- [40] XianXing Zhang, Yitong Zhou, Yiming Ma, Bee-Chung Chen, Liang Zhang, and Deepak Agarwal. 2016. Glmix: Generalized linear mixed models for large-scale response prediction. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. ACM, 363–372.
- [41] Yingya Zhang, Cheng Yang, and Zhixiang Niu. 2014. A research of job recommendation system based on collaborative filtering. In 2014 Seventh International Symposium on Computational Intelligence and Design, Vol. 1. IEEE, 533–538.
- [42] Peng Zhou, Wei Shi, Jun Tian, Zhenyu Qi, Bingchen Li, Hongwei Hao, and Bo Xu. 2016. Attention-based bidirectional long short-term memory networks for relation classification. In *Proceedings of the 54th annual meeting of the association for computational linguistics (volume 2: Short papers)*. 207–212.

- [43] Chen Zhu, Hengshu Zhu, Hui Xiong, Pengliang Ding, and Fang Xie. 2016. Recruitment market trend analysis with sequential latent variable models. In Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. ACM, 383–392.
- [44] Chen Zhu, Hengshu Zhu, Hui Xiong, Chao Ma, Fang Xie, Pengliang Ding, and Pan Li. 2018. Person-Job Fit: Adapting the Right Talent for the Right Job with Joint Representation Learning. ACM Transactions on Management Information Systems (TMIS) 9, 3 (2018), 12.