Physics of Multiantenna Systems and Broadband Processing

Tapan K. Sarkar Magdalena Salazar-Palma Eric L. Mokole

With Contributions from:

Santana Burintramart
Jeffrey T. Carlo
Wonsuk Choi
Arijit De
Debalina Ghosh
Seunghyeon Hwang
Jinhwan Koh
Raúl Fernández Recio
Mary Taylor
Nuri Yilmazer
Yu Zhang



A JOHN WILEY & SONS, INC., PUBLICATION

Contents

| Preface . | | | • | • | • | • | | • | xv |
|-----------|------|------------|----------|----------|-----------|-----------|---|--------|-----|
| Acknowl | edgr | nents | • | | | • | | | xxi |
| Chapter | 1 | What Is an | n Antei | nna and | How Do | oes It Wo | ork? | | 1 |
| | 1.0 | Summa | rv | | | | | | 1 |
| | 1.1 | | | | | | ions | | |
| | 1.2 | | | | | | uations | | |
| | | 1.2.1 | Farada | ay's Lav | v | | | | 4 |
| | | 1.2.2 | Gener | alized A | mpère's | Law | | ••••• | 7 |
| | | 1.2.3 | | | | | ectrostatio | | |
| | | 1.2.4 | | | | | agnetosta | | |
| | | 1.2.5 | | | | | • | | |
| | 1.3 | | | | | | | | 10 |
| | 1.4 | | | | | | Point Sou | | |
| | | | a in Fre | quency | and in Ti | me Dom | ain | •••••• | 15 |
| | | 1.4.1 | | | | | Sources | | |
| | | | 1.4.1. | | | | ncy Dom | | |
| | | | 1.4.1 | | | | | | |
| | | | 1.4.1. | | | | omain of | | |
| | | 1.4.2 | Dagan | | | | Receiver | | |
| | 1.5 | ~ | | | | | nite-Size | | 10 |
| | 1.5 | | | | | | l in Time. | | 20 |
| | | 1.5.1 | | | | | Structur | | |
| | | 1.5.1 | | | | | | | |
| | | 1.5.2 | | | | | Structur | | |
| | | 1.0.2 | | | | | | | |
| | | 1.5.3 | | | | | ed Recei | | 21 |
| | | | | | | | ansient Ir | | |
| | | | Field. | | | | | | 21 |
| | 1.6 | Conclus | | | | | | | |
| | | Referen | ces | | | | ••••• | | 23 |
| Chapter | 2 | Fundamer | itals of | Antenr | ıa Theor | v in the | Frequenc | ev | |
| Chapter | - | Domain | 10015 01 | AMICHI | I Heor | j m ene . | - request | -, | 25 |
| | 2.0 | Summa | ry | | | | | | 25 |
| | 2.1 | | | | | | | | |
| | 2.2 | | | | | | | | |

| | 2.3 | Field Radiated by a Small Circular Loop | 30 |
|---------|-----|---|-----|
| | 2.4 | Field Produced by a Finite-Sized Dipole | 32 |
| | 2.5 | Radiation Field from a Linear Antenna | |
| | 2.6 | Near- and Far-Field Properties of Antennas | 36 |
| | | 2.6.1 What Is Beamforming Using Antennas | 36 |
| | | 2.6.2 Use of Spatial Antenna Diversity | 43 |
| | 2.7 | The Mathematics and Physics of an Antenna Array | 46 |
| | 2.8 | Propagation Modeling in the Frequency Domain | 49 |
| | 2.9 | Conclusion | 57 |
| | | References | 57 |
| Chapter | 3 | Fundamentals of an Antenna in the Time Domain | 59 |
| | 3.0 | Summary | 59 |
| | 3.1 | Introduction | |
| | 3.2 | UWB Input Pulse | 61 |
| | 3.3 | Travelling-Wave Antenna | 62 |
| | 3.4 | Reciprocity Relation Between Antennas | 63 |
| | 3.5 | Antenna Simulations | 65 |
| | 3.6 | Loaded Antennas | 65 |
| | | 3.6.1 Dipole | 65 |
| | | 3.6.2 Bicones | 71 |
| | | 3.6.3 TEM Horn | 74 |
| | | 3.6.4 Log-Periodic | 78 |
| | | 3.6.5 Spiral | 80 |
| | 3.7 | Conventional Wideband Antennas | 83 |
| | | 3.7.1 Volcano Smoke | 83 |
| | | 3.7.2 Diamond Dipole | 85 |
| | | 3.7.3 Monofilar Helix | 86 |
| | | 3.7.4 Conical Spiral | 88 |
| | | 3.7.5 Monoloop | 90 |
| | | 3.7.6 Quad-Ridged Circular Horn | 91 |
| | | 3.7.7 Bi-Blade with Century Bandwidth | 93 |
| | | 3.7.8 Cone-Blade | 94 |
| | | 3.7.9 Vivaldi | |
| | | 3.7.10 Impulse Radiating Antenna (IRA) | 97 |
| | | 3.7.11 Circular Disc Dipole | 99 |
| | | 3.7.12 Bow-Tie | 100 |
| | | 3.7.13 Planar Slot | 101 |
| | 3.8 | Experimental Verification of the Wideband Responses | |
| | | from Antennas | 102 |
| | 3.9 | Conclusion | 108 |
| | | References | 109 |
| Chapter | | A Look at the Concept of Channel Capacity from a | |
| | | Maxwellian Viewpoint | 113 |

CONTENTS vii

| | 4.0 | | • | 113 |
|---------|-----|---------|-------------|---------------------------------------|
| | 4.1 | | | 114 |
| | 4.2 | | | y and Its Evolution117 |
| | 4.3 | | | tions for the Channel Capacity118 |
| | 4.4 | | | ent of a Waveform124 |
| | 4.5 | | | les Illustrating the Relevance of the |
| | | Maxwe | llian Physi | cs in Characterizing the Channel |
| | | Capacit | | 130 |
| | | 4.5.1 | | Versus Unmatched Receiving Dipole |
| | | | Antenna | with a Matched Transmitting Antenna |
| | | | | g in Free Space131 |
| | | 4.5.2 | | irective Versus Nondirective Matched |
| | | | Transmit | ting Antennas Located at Different |
| | | | Heights a | above the Earth for a Fixed Matched |
| | | | Receiver | Height above Ground133 |
| | | | 4.5.2.1 | Transmitting Horn Antenna at a |
| | | | | Height of 20 m135 |
| | | | 4.5.2.2 | Transmitting Dipole Antenna at a |
| | | | | Height of 20 m136 |
| | | | 4.5.2.3 | Orienting the Transmitting Horn or |
| | | | | the Dipole Antenna Located at a |
| | | | | Height of 20 m Towards the |
| | | | | Receiving Antenna137 |
| | | | 4.5.2.4 | The Transmitting Horn and Dipole |
| | | | | Antenna Located at a Height of 2 m |
| | | | | above Ground137 |
| | | | 4.5.2.5 | Transmitting Horn and Dipole |
| | | | | Antenna Located Close to the |
| | | | | Ground but Tilted Towards the Sky 138 |
| | | | 4.5.2.6 | Channel Capacity as a Function of |
| | | | | the Height of the Transmitting |
| | | | | Dipole Antenna from the Earth139 |
| | | | 4.5.2.7 | Presence of a Dielectric Wall |
| | | | | Interrupting the Direct Line-of-sight |
| | | | | Between Transmitting and Receiving |
| | | | | Antennas141 |
| | | | 4.5.2.8 | Increase in Channel Capacity when |
| | | | | Matched Receiving Antenna Is |
| | | | | Encapsulated by a Dielectric Box143 |
| | 4.6 | | | 146 |
| | 4.7 | | | of Entropy and Its Evolution148 |
| | | Referen | ces | 164 |
| ~• | _ | | | |
| Chapter | | | nput-Mul | tiple-Output (MIMO) Antenna |
| | | Systems | | 167 |

viii PHYSICS OF MULTIANTENNA SYSTEMS & BROADBAND PROCESSING

| | 5.0 | Summar | y | 167 |
|---------|------|-----------|---|-----|
| | 5.1 | Introduc | tion | 168 |
| | 5.2 | Diversity | y in Wireless Communications | 168 |
| | | 5.2.1 | Time Diversity | 169 |
| | | 5.2.2 | Frequency Diversity | 170 |
| | | 5.2.3 | Space Diversity | |
| | 5.3 | Multiant | enna Systems | 172 |
| | 5.4 | Multiple | -Input-Multiple-Output (MIMO) Systems | 173 |
| | 5.5 | | Capacity of the MIMO Antenna Systems | |
| | 5.6 | | Known at the Transmitter | |
| | | 5.6.1 | Water-filling Algorithm | 179 |
| | 5.7 | Channel | Unknown at the Transmitter | 180 |
| | | 5.7.1 | Alamouti Scheme | 180 |
| | 5.8 | Diversity | y-Multiplexing Tradeoff | 182 |
| | 5.9 | MIMO Ü | Under a Vector Electromagnetic Methodology | 183 |
| | | 5.9.1 | MIMO Versus SISO | |
| | 5.10 | More Ap | opealing Results for a MIMO system | 189 |
| | | 5.10.1 | Case Study: 1 | 189 |
| | | 5.10.2 | Case Study: 2 | 190 |
| | | 5.10.3 | Case Study: 3 | 191 |
| | | 5.10.4 | Case Study: 4 | 194 |
| | | 5.10.5 | Case Study: 5 | |
| | 5.11 | Physics | of MIMO in a Nutshell | 199 |
| | | 5.11.1 | Line-of-Sight (LOS) MIMO Systems with | |
| | | | Parallel Antenna Elements Oriented Along the | |
| | | | Broadside Direction | 200 |
| | | 5.11.2 | Line-of-Sight MIMO Systems with Parallel | |
| | | | Antenna Elements Oriented Along the Broadside | |
| | | | Direction | 202 |
| | | 5.11.3 | Non-line-of-Sight MIMO Systems with Parallel | |
| | | | Antenna Elements Oriented Along the Broadside | |
| | | | Direction | 204 |
| | 5.12 | Conclus | ion | 206 |
| | | Reference | ces | 207 |
| | | | | |
| Chapter | | | Output Energy Filter in Multiantenna Systems | |
| | fo | r Adapti | ve Estimation | 209 |
| | 6.0 | Summar | у | 209 |
| | 6.1 | Various | Forms of the Optimum Filters | 210 |
| | | 6.1.1 | Matched Filter (Cross-correlation filter) | 211 |
| | | 6.1.2 | A Wiener Filter | 212 |
| | | 6.1.3 | An Output Energy Filter (Minimum Variance | |
| | | | Filter) | 213 |
| | | 6.1.4 | Example of the Filters | |
| | | | | |

CONTENTS ix

| | 6.2 | Direct | Data Domain Least Squares Approaches to | |
|---------|-------------------------------|--|---|---|
| | | | ve Processing Based on a Single Snapshot of Data . | 215 |
| | | 6.2.1 | Eigenvalue Method | |
| | | 6.2.2 | Forward Method | |
| | | 6.2.3 | Backward Method | 221 |
| | | 6.2.4 | Forward-Backward Method | |
| | | 6.2.5 | Real Time Implementation of the Adaptive | |
| | | | Procedure | 224 |
| | 6.3 | Direct D | ata Domain Least Squares Approach to Space- | |
| | | | Adaptive Processing | 226 |
| | | 6.3.1 | Two-Dimensional Generalized Eigenvalue | |
| | | | Processor | 230 |
| | | 6.3.2 | Least Squares Forward Processor | |
| | | 6.3.3 | Least Squares Backward Processor | |
| | | 6.3.4 | Least Squares Forward-Backward Processor | |
| | 6.4 | Applica | ation of the Direct Data Domain Least Squares | |
| | | | ques to Airborne Radar for Space-Time Adaptive | |
| | | | sing | 238 |
| | 6.5 | | sion | |
| | | Refere | nces | 247 |
| | | | | |
| Chapter | 7 | Minimun | Norm Property for the Sum of the Adaptive | |
| • | | | n Adaptive or in Space-Time Processing | 249 |
| | 7.0 | Summe | ary | 249 |
| | 7.1 | | action | |
| | 7.2 | | of the Direct Data Domain Least Squares | 250 |
| | 7.2 | | ach | 251 |
| | 7.3 | | of Space-Time Adaptive Processing Based on the | |
| | 7.5 | | Method | |
| | 7.4 | | um Norm Property of the Adaptive Weights at the | 200 |
| | | Minim | | |
| | | | | |
| | | DOA o | of the SOI for the 1-D Case and at Doppler | 255 |
| | 7.5 | DOA o Freque | of the SOI for the 1-D Case and at Doppler ncy and DOA for STAP | |
| | 7.5 7.6 | DOA o Freque Numer | of the SOI for the 1-D Case and at Doppler | 258 |
| | | DOA o Freque Numer Conclu | of the SOI for the 1-D Case and at Doppler ncy and DOA for STAP | 258 273 |
| | | DOA o Freque Numer Conclu | of the SOI for the 1-D Case and at Doppler ncy and DOA for STAP ical Examples | 258 273 |
| Chapter | 7.6 | DOA of Freque Numer Conclu Referen | of the SOI for the 1-D Case and at Doppler ncy and DOA for STAP ical Examples | 258 273 |
| Chapter | 7.6 8 | DOA of Freque Numer Conclu Referen | of the SOI for the 1-D Case and at Doppler ncy and DOA for STAP ical Examples nces al Weights in Adaptive and Space-Time | 258 273 |
| Chapter | 7.6 8 | DOA of Freque Numer Conclu Referen Using Res | of the SOI for the 1-D Case and at Doppler ncy and DOA for STAP ical Examples sion nces al Weights in Adaptive and Space-Time g | 258 273 274 |
| Chapter | 7.6 8 8.0 | DOA of Freque Numer Conclu Referer Using Res Processin | of the SOI for the 1-D Case and at Doppler ncy and DOA for STAP ical Examples sion nces al Weights in Adaptive and Space-Time g ary | 258 273 274 275 275 |
| Chapter | 7.6 8 8.0 8.1 | DOA of Freque Numer Conclu Referen Using Res Processin Summa Introdu | of the SOI for the 1-D Case and at Doppler ncy and DOA for STAP | 258 273 274 275 275 |
| Chapter | 7.6 8 8.0 | DOA of Freque Numer Conclu Referen Using Res Processin Summa Introdu Formul | of the SOI for the 1-D Case and at Doppler ncy and DOA for STAP | 258 273 274 275 275 |
| Chapter | 7.6 8 8.0 8.1 | DOA of Freque Numer Conclu Referen Using Res Processin Summa Introdu Formul | of the SOI for the 1-D Case and at Doppler ncy and DOA for STAP | 258 273 274 275 275 275 |

x PHYSICS OF MULTIANTENNA SYSTEMS & BROADBAND PROCESSING

| | | 8.2.3. Forward-Backward Method | 282 |
|---------|-------|--|------|
| | 8.3 | Simulation Results for Adaptive Processing | 283 |
| | 8.4 | Formulation of an Amplitude-only Direct Data Domain | |
| | | Least Squares Space-Time Adaptive Processing | 289 |
| | | 8.4.1 Forward Method | |
| | | 8.4.2 Backward Method | 291 |
| | | 8.4.3 Forward-Backward Method | 292 |
| | 8.5 | Simulation Results | 292 |
| | 8.6 | Conclusion | 299 |
| | | References | |
| Chapter | 9 P | hase-Only Adaptive and Space-Time Processing | 303 |
| | 9.0 | Summary | 303 |
| | 9.1 | Introduction | |
| | 9.2 | Formulation of the Direct Data Domain Least Squares | |
| | | Solution for a Phase-Only Adaptive System | 304 |
| | | 9.2.1 Forward Method | |
| | | 9.2.2 Backward Method | |
| | | 9.2.3 Forward-Backward Method | |
| | 9.3 | Simulation Results | |
| | 9.4 | Formulation of a Phase-Only Direct Data Domain Least | |
| | · · · | Squares Space-Time Adaptive Processing | .318 |
| | | 9.4.1 Forward Method | |
| | | 9.4.2 Backward Method | |
| | | 9.4.3 Forward-Backward Method | 318 |
| | 9.5 | Simulation Results | |
| | 9.6 | Conclusion | |
| | 9.0 | References | |
| | | | |
| Chapter | 10 Si | imultaneous Multiple Adaptive Beamforming | 323 |
| | 10.0 | Summary | |
| | 10.1 | Introduction | 323 |
| | 10.2 | Formulation of a Direct Data Domain Approach for | |
| | | Multiple Beamforming | |
| | | 10.2.1 Forward Method | 324 |
| | | 10.2.2 Backward Method | 327 |
| | | 10.2.3 Forward-Backward Method | 328 |
| | 10.3 | Simulation Results | 328 |
| | 10.4 | Formulation of a Direct Data Domain Least Squares | |
| | | Approach for Multiple Beamforming in Space-Time | |
| | | Adaptive Processing | 332 |
| | | 10.4.1 Forward Method | 332 |
| | | 10.4.2 Backward Method | |
| | | 10.4.3 Forward-Backward Method | |

CONTENTS xi

| | 10.5 | Simulation Results | .338 |
|---------|------|--|------|
| | 10.6 | Conclusion | |
| | | References | |
| | | | |
| Chapter | | erformance Comparison Between Statistical-Based and | |
| | | Pirect Data Domain Least Squares Space-Time Adaptive | |
| | P | rocessing Algorithms | 347 |
| | 11.0 | Summary | .347 |
| | 11.1 | Introduction | .347 |
| | 11.2 | Description of the Various Signals of Interest | |
| | | 11.2.1 Modeling of the Signal-of-Interest | |
| | | 11.2.2 Modeling of the Clutter | 349 |
| | | 11.2.3 Modeling of the Jammer | .350 |
| | | 11.2.4 Modeling of the Discrete Interferers | |
| | 11.3 | Statistical-Based STAP Algorithms | |
| | | 11.3.1 Full-Rank Optimum STAP | |
| | | 11.3.2 Reduced-Rank STAP (Relative Importance of | |
| | | the Eigenbeam Method) | 352 |
| | | 11.3.3 Reduced-Rank STAP (Based on the Generalized | |
| | | Sidelobe Canceller) | 353 |
| | 11.4 | Direct Data Domain Least Squares STAP Algorithms | |
| | 11.5 | Channel Mismatch | |
| | 11.6 | Simulation Results | .357 |
| | 11.7 | Conclusion | 368 |
| | | References | 368 |
| | | | |
| Chapter | | pproximate Compensation for Mutual Coupling Using | |
| | tl | ne In Situ Antenna Element Patterns | 371 |
| | 12.0 | Summary | 371 |
| | 12.1 | Introduction | |
| | 12.2 | Formulation of the New Direct Data Domain Least | |
| | | Squares Approach Approximately Compensating for the | |
| | | Effects of Mutual Coupling Using the In Situ Element | |
| | | Patterns | 373 |
| | | 12.2.1 Forward Method | 373 |
| | | 12.2.3 Backward Method | |
| | | 12.2.4 Forward-Backward Method | 377 |
| | 12.3 | Simulation Results | 378 |
| | 12.4 | Reason for a Decline in the Performance of the Algorithm | |
| | | When the Intensity of the Jammer Is Increased | .386 |
| | 12.5 | Conclusion | |
| | | References | 386 |

| Chapter | | gnal Enhancement Through Polarization Adaptivity on ransmit in a Near-Field MIMO Environment | 389 |
|---------|--------------|---|-----|
| | 13.0 | Summary | 389 |
| | 13.1 | Introduction | 389 |
| | 13.2 | Signal Enhancement Methodology Through Adaptivity on Transmit | 391 |
| | 13.3 | Exploitation of the Polarization Properties in the | |
| | | Proposed Methodology | 395 |
| | 13.4 | Numerical Simulations | |
| | | 13.4.1 Example 1 | |
| | | 13.4.2 Example 2 | |
| | | 13.4.3 Example 3 | |
| | 13.5 | Conclusion | |
| | | References | 411 |
| Chapter | | irection of Arrival Estimation by Exploiting Unitary ransform in the Matrix Pencil Method and Its | |
| | | omparison with ESPRIT | 413 |
| | 14.0 | Summary | |
| | 14.1 | Introduction | |
| | 14.2 | The Unitary Transform | |
| | 14.3 | 1-D Unitary Matrix Pencil Method Revisited | |
| | 14.4 | Summary of the 1-D Unitary Matrix Pencil Method | |
| | 14.5 | The 2-D Unitary Matrix Pencil Method | 419 |
| | | 14.5.1 Pole Pairing for the 2-D Unitary Matrix Pencil Method | |
| | | 14.5.2 Computational Complexity | 426 |
| | | 14.5.3 Summary of the 2-D Unitary Matrix Pencil Method | 426 |
| | 14.6 | Simulation Results Related to the 2-D Unitary Matrix | |
| | | Pencil Method | |
| | 14.7 | The ESPRIT Method | |
| | 14.8 | Multiple Snapshot-Based Matrix Pencil Method | 432 |
| | 14.9 | Comparison of Accuracy and Efficiency Between | |
| | | ESPRIT and the Matrix Pencil Method | |
| | 14.10 | Conclusion | |
| | | References | 436 |
| Chapter | | OA Estimation Using Electrically Small Matched ipole Antennas and the Associated Cramer-Rao Bound | 439 |
| | | • | 420 |
| | 15.0 15.1 | SummaryIntroduction | |
| | 15.1 | DOA Estimation Using a Realistic Antenna Array | |
| | 13.2 | 15.2.1 Transformation Matrix Technique | |
| | | | |

CONTENTS xiii

| | 15.3 | Cramer-F | Rao Bound for DOA Estimation | 444 |
|---------|------|------------|---|-----|
| | 15.4 | DOA Est | imation Using 0.1 λ Long Antennas | 445 |
| | 15.5 | DOA Est | imation Using Different Antenna Array | |
| | | | ations | |
| | 15.6 | | on | |
| | • | Referenc | es | 462 |
| Chapter | | | ntional Least Squares Optimization for DOA | |
| | E | stimation | Using Arbitrary-Shaped Antenna Arrays | 463 |
| | 16.0 | | <i></i> | |
| | 16.1 | | ion | |
| | 16.2 | | odeling | |
| | 16.3 | | ed DOA Estimation | |
| | 16.4 | | ventional Least Squares Optimization | |
| | 16.5 | | on Results | |
| | | | An Array of Linear Uniformly Spaced Dipoles | 468 |
| | | | An Array of Linear Non-uniformly Spaced | |
| | | | Dipoles | 470 |
| | | | An Array Consisting of Mixed Antenna | |
| | | | Elements | 471 |
| | | | An Antenna Array Operating in the Presence of | |
| | | | Near-Field Scatterers | 472 |
| | | | Sensitivity of the Procedure Due to a Small | |
| | | | Change in the Operating Environment | 473 |
| | | | Sensitivity of the Procedure Due to a Large | |
| | | | Change in the Operating Environment | |
| | | | An Array of Monopoles Mounted Underneath an | |
| | | | Aircraft | 4/6 |
| | | | A Non-uniformly Spaced Nonplanar Array of | 455 |
| | 166 | | Monopoles Mounted Under an Aircraft | |
| | 16.6 | | on | |
| | | Referenc | es | 479 |
| Chapter | | | Direction of Arrival Estimations Using the | |
| | N | Iatrix Pen | cil Method | 481 |
| | 17.0 | Summary | 7 | 481 |
| | 17.1 | | ion | |
| | 17.2 | Brief Ov | erview of the Matrix Pencil Method | 482 |
| | 17.3 | Problem | Formulation for Simultaneous Estimation of | |
| | | DOA and | I the Frequency of the Signal | 488 |
| | 17.4 | | Rao Bound for the Direction of Arrival and | |
| | | Frequenc | y of the Signal | 494 |
| | 17.5 | | Using Isotropic Point Sources | |
| | 17.6 | Example | Using Realistic Antenna Elements | 512 |
| | | | | |

xiv PHYSICS OF MULTIANTENNA SYSTEMS & BROADBAND PROCESSING

| | 17.7 | Conclusion | |
|---------|------|--|-----|
| Chapter | | DAPTIVE PROCESSING OF BROADBAND IGNALS | 523 |
| | 18.0 | Summary | 523 |
| | 18.1 | Introduction | |
| | 18.2 | Formulation of a Direct Data Domain Least Squares | |
| | | Method for Adaptive Processing of Finite Bandwidth | |
| | | Signals Having Different Frequencies | 524 |
| | | 18.2.1 Forward Method for Adaptive Processing of | |
| | | Broadband Signals | 524 |
| | | 18.2.2 Backward Method | 529 |
| | | 18.2.3 Forward-Backward Method | 529 |
| | 18.3 | Numerical Simulation Results | 530 |
| | 18.4 | Conclusion | 535 |
| | | References | 535 |
| Chapter | D | ffect of Random Antenna Position Errors on a Direct eata Domain Least Squares Approach for Space-Time daptive Processing | 537 |
| | 19.0 | Summary | 537 |
| | 19.1 | Introduction | |
| | 19.2 | EIRP Degradation of Array Antennas Due to Random | |
| | | Position Errors | 540 |
| | 19.3 | Example of EIRP Degradation in Antenna Arrays | 544 |
| | 19.4 | Simulation Results | |
| | 19.5 | Conclusion | 551 |
| | | References | 551 |
| Indov | | | 552 |