

Positive lightning flashes recorded on the Säntis tower from May 2010 to January 2012

Carlos Romero,¹ Farhad Rachidi,¹ Marcos Rubinstein,² Mario Paolone,³ Vladimir A. Rakov,⁴ and Davide Pavanello⁵

Received 1 June 2013; revised 13 October 2013; accepted 3 November 2013; published 5 December 2013.

[1] We analyze currents of 30 positive flashes recorded on the Säntis tower, Switzerland, from May 2010 to January 2012. The currents were classified into two types. Type 1 events exhibit a large, unipolar main pulse with a risetime of tens of microseconds, followed by subsidiary peaks separated by millisecond-scale intervals. The main pulse in three flashes was preceded by a slowly rising ramp lasting several milliseconds and was followed by a relatively steady current with superimposed positive and negative pulses, constituting the first direct evidence of M components of both polarities. In four of the five type 1 flashes, the main current was preceded by pulse bursts, presumably due to attempted negative leaders. Type 2 events are characterized by a millisecond-scale waveform with large, oscillatory pulse trains on its rising portion. These pulse trains are inferred to be due to upward negative stepped leaders. Peak currents of type 2 flashes are associated with the fast pulses. Our positive flashes of both types have a median peak current of 11.1 kA and a median duration of 80 ms, consistent with data recorded in Austria. Our measured median transferred charges are about 6 times larger than those at Switzerland's Monte San Salvatore and in Japan and about 3 times larger than in Austria. Eight type 2 flashes in our data set transported over 500 C of positive charge to ground. Our five type 1 events appear to be similar (except for the pulse duration) to their counterparts examined by Berger et al. (1975). Our type 2 events are “classical” upward flashes.

Citation: Romero, C., F. Rachidi, M. Rubinstein, M. Paolone, V. A. Rakov, and D. Pavanello (2013), Positive lightning flashes recorded on the Säntis tower from May 2010 to January 2012, *J. Geophys. Res. Atmos.*, 118, 12,879–12,892, doi:10.1002/2013JD020242.

1. Introduction

[2] This paper presents an analysis of measured current waveforms associated with positive flashes recorded on the Säntis tower from May 2010 through January 2012. Preliminary analyses of the data were presented in Romero et al. [2011, 2012c]. The overall number of recorded flashes in the considered period was 200, of which 30 were of positive polarity and 3 were classified as bipolar.

[3] Although the incidence of positive lightning flashes is of the order of 10 times lower than that of negative flashes, they are of great interest to the scientific and engineering

communities for the following reasons: First, compared to negative lightning, positive flashes exhibit higher peak currents and they lower more charge to the ground [Rakov, 2003]. Positive lightning is therefore a special concern for engineers responsible for the protection of wind turbines and telecommunication towers. Second, the complex structure of the electromagnetic fields radiated by positive lightning can make these flashes difficult to detect and prone to misclassification by lightning location systems. Third, positive lightning has been shown to be associated with the initiation of sprites [e.g., Saba et al., 2010; Yashunin et al., 2007], hence its importance in the study of transient luminous events in the middle atmosphere.

[4] Furthermore, experimental data on positive lightning are scarce and often controversial [Rakov, 2003].

[5] Only a few studies have been published presenting directly measured currents from positive flashes [e.g., Berger et al., 1975; Diendorfer et al., 2006; Goto and Narita, 1995; Wada et al., 1996]. Most other positive lightning studies are based on distant electric field measurements [e.g., Cooray and Pérez, 1994; Fuquay, 1982; Ishii et al., 1998; Nag and Rakov, 2012], high-speed video optical observations [e.g., Campos et al., 2009; Fleenor et al., 2009; Saba et al., 2009, 2008, 2010], or on a combination of remote field and optical measurements [e.g., Kong et al., 2008].

¹Electromagnetic Compatibility Laboratory, Swiss Federal Institute of Technology (EPFL), Lausanne, Switzerland.

²University of Applied Sciences of Western Switzerland, Yverdon-les-Bains, Switzerland.

³Distributed Energy Systems Laboratory, Swiss Federal Institute of Technology (EPFL), Lausanne, Switzerland.

⁴Department of Electrical and Computer Engineering, University of Florida, Gainesville, Florida, USA.

⁵University of Applied Sciences of Western Switzerland (HES-SO), Sion, Switzerland.

Corresponding author: M. Rubinstein, University of Applied Sciences of Western Switzerland, 1400 Yverdon-les-Bains, Vaud, CH-1400, Switzerland. (marcos.rubinstein@heig-vd.ch)




Figure 1. Monthly distribution of the number of flashes to the Sântis tower. June 2010 to January 2012.

[6] Negative and positive flashes observed on the Sântis tower (see Figure 1) are concentrated in the summer months, with August being the month during which most of the positive flashes occurred (6 events in 2010 and 16 events in 2011).

2. Sântis Tower Experimental Setup

[7] The Sântis tower is a 124 m tall tower sitting on the top of the 2502 m tall mount Sântis located at 47°14'57"N and 9°20'32"E in the Appenzell region in the northeast of Switzerland. The tower has a hollow, metallic inner conical structure of radius 2 m at the base and 1 m at its top. An outer Plexiglas structure has a radius of 3 m at the base and 1.5 m at the top. The structure serves mainly as a telecommunications tower and as a weather station. A decade-long analysis on the lightning incidence to several towers at various locations in Switzerland resulted in the choice of the Sântis tower, which is struck by lightning about 100 times a year, according to the European lightning detection network European Cooperation for Lightning Detection [Romero et al., 2012a].

[8] The Sântis tower has been instrumented using advanced and modern equipment including remote monitoring and control capabilities for accurate measurement of lightning current parameters [Romero et al., 2012b]. The lightning current is measured at two different heights, 24 m and 82 m. At the lower height, we installed two Rogowski coils with different sensitivities, each one with an analog integrator to obtain the current waveform. One of these Rogowski sensors was manufactured by Power Electronic Measurements (PEM) Inc. and the other by ROCOIL. Two more sensors were installed at 82 m. The first one is a PEM Rogowski coil with an analog integrator, while the second

Table 1. Current Peak, Total Transferred Charge, Flash Duration, Average Current, and Action Integral of Positive Flashes Recorded on the Sântis Tower^a

Flash #	Type	Number and Time Tag (dd.mm.yy hh:mm)	Pulse Peak (kA)	Flash Peak (kA)	Flash Charge Q (C)	Flash Duration Δt (ms)	Average Current Q/ Δt (kA)	Action Integral (× 10 ⁶ A ² s)
1	1	21.07.2010 19:05	42.7	-	280.9	111	2.6	1.7
2	1	21.07.2010 19:31	18.2	-	84	51	1.6	0.295
3	2	01.08.2010 20:00	0.9	0.4	2.7	15	0.2	0.001
4	2	01.08.2010 20:02	2.4	2.1	16.7	77	0.2	0.013
5	2	01.08.2010 20:06	1	0.6	6.8	40	0.2	0.003
6	2	15.08.2010 14:34	13.2	9.1	189.1	55	3.4	0.798
7	2	15.08.2010 14:37	3.6	3.4	134.8	83	1.6	0.21
8	2	30.08.2010 04:42	6.5	4.9	153.4	68	2.3	0.366
9	2	01.05.2011 12:36	11.9	5.4	8.3	9	0.9	0.024
10	2	20.05.2011 15:29	21.7	9.6	30.2	12	2.5	0.219
11	2	22.05.2011 23:48	11.1	3.3	31.4	17	1.8	0.058
12	2	26.05.2011 17:53	2	1.6	19.5	60	0.3	0.013
13	1	26.05.2011 18:00	16.3	-	14.8	15	1	0.056
14	1	26.05.2011 18:03	31.5	-	41.1	40	1	0.135
15	2	06.06.2011 10:36	12.4	5.8	80.6	100	0.8	0.116
16	2	08.07.2011 01:06	12	11.8	899.6	370	2.4	4.001
17	1	03.08.2011 11:51	92.7	-	404.2	50	8	4.185
18	2	03.08.2011 12:16	4.1	1.4	15	25	0.6	0.013
19	2	27.08.2011 05:43	11.1	10.8	853.3	250	3.4	4.787
20	2	27.08.2011 06:00	6.5	4.1	363.9	300	1.2	0.602
21	2	27.08.2011 06:02	5.2	5.1	460	270	1.7	0.994
22	2	27.08.2011 06:30	25.9	25	913.3	260	3.5	7.193
23	2	27.08.2011 06:37	12.8	9.8	15	15	1	0.02
24	2	27.08.2011 06:46	22.2	14.8	902	200	4.5	7.097
25	2	27.08.2011 06:47	11	10.5	701.8	210	3.3	3.905
26	2	27.08.2011 06:48	10.4	8.8	537.7	240	2.2	2.342
27	2	27.08.2011 06:50	12	8.8	700.9	250	2.8	3.319
28	2	27.08.2011 08:38	9.3	8.8	184.7	170	1.1	0.662
29	2	27.08.2011 08:47	8.1	3.5	225.7	165	1.4	0.424
30	2	05.01.2012 17:21	9.2	8.2	512.5	165	3.1	2.799
		Min:	0.9	0.4	2.7	9	0.2	0.001
		Median:	11.1	5.8	169.1	80	1.7	0.395
		Max:	92.7	25	913.3	370	4.5	7.193

^aPulse peak and flash peak currents are defined in Zhou et al. [2012] and illustrated in Figure 8.




Figure 2. Measured current waveforms associated with type 1 positive flashes. (a) Flash #1, (b) flash #2, (c) flash #13, (d) flash #14, and (e) flash #17. Flash IDs refer to Table 1. Note that waveforms are presented on different time scales.

one is a multigap magnetic loop (B-Dot) sensor specially designed to measure the lightning current derivative [Romero *et al.*, 2012a]. The analog outputs of the sensors are relayed to a digitizing system by means of A/D–D/A 12 bit fiber optic links characterized by an overall bandwidth from DC to 25 MHz. The maximum current measurable with the PEM Rogowski coils is 120 kA, and the maximum current derivative measurable with the B-Dot sensor is 400 kA/ μ s. The PEM Rogowski coil located at 82 m is characterized by a

frequency response ranging from 50 mHz to 2.4 MHz, while the upper frequency limit of the B-Dot sensor is about 20 MHz (for more details, see Romero *et al.* [2012a]). The measurement window for each flash is 1.2 s with a 0.25 s pretrigger and a sampling rate of 100 MHz. The current waveforms were obtained by combining the outputs of the PEM Rogowski coil and the multigap B-dot sensor (both located at 82 m), using a procedure detailed in Romero *et al.* [2013]. The procedure effectively merges the low-




Figure 3. Type 1 current waveform associated with a positive flash recorded on 21 July 2010, 19:05 (flash#1). (a) Current waveform for the entire flash displayed on a 200 ms time scale. (b) Expanded view of the initial portion of the current (blue) and current derivative (red) records displayed on a 22 ms time scale. (c) Expanded view of the fastest pulse occurring at about 120 ms, displayed on a 4 μ s time scale.




Figure 4. (a) Type 1 overall current waveform associated with a positive flash recorded on 21 July 2010,19:31 (flash #2). (b) Expanded view of the main pulse. (c) Expanded view of the current waveform showing zero crossings due to two positive-polarity pulses at about 169 and 171 ms. (d) Expanded view of current derivative of the fastest oscillatory pulse occurring at about 120 ms.




Figure 5. Type 2 current waveform associated with a positive flash recorded on 30 August 2010 at 04:42 (flash #8). (a) Overall flash record (140 ms full scale), (b) initial part of the current record between 119.9 and 120.5 ms, (c) current derivative record between 119.9 and 120.5 ms (600 μ s full scale), and (d) expanded view of the time derivative of the fastest pulse (occurring at about 120 ms).




Figure 6. Type 2 current waveform of a positive flash recorded on 15 August 2010 at 14:37 (flash#7). (a) Overall current record (250 ms full scale). (b) Expanded view of the initial rising portion (6 ms full time scale). (c) Expanded view of the current derivative of the first fast pulse (9 μ s full time scale).

frequency contents from the PEM Rogowski coil and the high-frequency contents of the multigap B-dot sensor (beyond 1 MHz or so) to obtain a current waveform covering a wider frequency band than does either of the individual sensors (see also *Romero et al.* [2012b]).

[9] The status and settings of each pair of sensors can be monitored and changed by means of a control system

designed and built using National Instruments CompactRIO modules linked via fiber optic links using 100Base-FX Ethernet. A local server running, monitoring, and storage tasks is housed in a shielded control room several tens of meters from the base of the tower. The server and the front end station are connected to the Internet over a router and a standard **digital subscriber line** link, allowing remote




Figure 7. Type 2 current waveform of a positive flash recorded on 1 August 2010 at 20:02 (flash#4). (a) Overall flash current record (160 ms full scale). (b) Portion of the current record between 129 and 134 ms (5 ms full scale).




Figure 8. Illustration of the pulse peak current and flash peak current for two measured waveforms of type 2. (a) Flash #7, 15 August 2010 at 14:37. (b) Flash#11, 22 May 2011 at 23:48. Both current peaks are measured with respect to zero level.

maintenance, monitoring, and control of the overall measurement system. More details on the measurement system installed on the Sântis tower can be found in *Romero et al.* [2012a, 2012b].




Figure 9. Pulse peak current cumulative frequency distribution.

3. Data

[10] Table 1 presents values of the current pulse and flash peaks, total transferred charge, flash duration, and action integral for the recorded positive flashes. Pulse peak and flash peak currents are defined in *Zhou et al.* [2012] (they will be discussed in section 4.1).

[11] The observed current waveforms were classified into two types, as described in the following section. Note that, throughout this paper, negative current polarity indicates positive charge transfer to ground. All flashes examined in this paper appeared to be of upward type, although all five type 1 flashes could be viewed as downward flashes with very long upward connecting leaders.

3.1. Classification of Current Waveforms Associated With Positive Flashes

3.2. Type 1

[12] Five of the 30 recorded positive flashes were characterized by the presence of a large unipolar current pulse with characteristics similar to those measured by Berger and coworkers [*Berger, 1977, Figure 18; Berger et al., 1975,*




Figure 10. Pulse peak current histogram. The MLE (maximum-likelihood estimation) of the probability distribution function (PDF, broken green line) is also shown. N is the sample size and GM is the geometrical mean.

Figure 11]. Figure 2 presents current waveforms associated with all these five flashes. The risetime of the pulses was a few tens of microseconds for four of the five cases and about $380 \mu\text{s}$ for the fifth flash (flash #1). In four of the five cases, namely, flashes #2, 13, 14, and 17, the main pulse exhibited structure after the main peak in the form of subsidiary peaks separated by times of the order of 1 ms. As can be seen from Figure 2, in three flashes (#1, 2, 13), the main pulse was preceded by a clearly discernible initial slowly rising ramp lasting a few milliseconds [Romero *et al.*, 2011], and it was followed by a steady current that contained pulses of both polarities (not well resolved in Figure 2), whose shapes are characteristic of M components. Several milliseconds to several tens of milliseconds prior to the start of the initial slowly rising ramp, a train of damped oscillatory pulses separated by several milliseconds and characterized by the highest current steepnesses of the flash can be observed in three of the flashes (#2, 13, 14). Note also that flash 1 exhibits a single burst of pulses (at about 120 ms), with characteristics similar to those observed in flashes 2, 13, and 14. Note that the peak current derivative associated with the main pulse occurring at about 128.6 ms is below the noise level (which in this case is about $2 \text{ kA}/\mu\text{s}$).

[13] In Figure 3a, we show the overall waveform for a type 1 flash recorded on 21 July 2010 at 19:05 (flash #1), also seen in Figure 2a. Figure 3b shows initial portions of current and current derivative records on an expanded time scale. The peak value of the main pulse is 42.7 kA , its 10–90% risetime

is about $380 \mu\text{s}$, and the total charge transferred to ground is 281 C. It can be seen that the highest pulse steepness (maximum current derivative) occurs about 3 ms prior to the initial slowly rising portion of the current. This activity prior to the main pulse might be associated with the streamer corona at the onset of the upward negative leader, or it may be induced in the tower by cloud discharges.

[14] Figure 3c shows, on a $4 \mu\text{s}$ time scale, the fastest of these current pulses (which occurred at a time of about 120 ms), where the time derivative of the current measured by the B-dot sensor is also shown. It can be seen that the current and the current derivative exhibit an oscillatory behavior with a frequency of about 2.3 MHz, which corresponds to a wavelength of about 130 m at the speed of light.

[15] Figure 4a presents another type 1 positive flash corresponding to Figure 2b, recorded on the same day (21 July) at 19:31. The initial, slowly rising portion lasts about 10 ms, at the end of which the current has reached a value of 1 kA. The peak value of the main pulse is 18.2 kA , its 10–90% risetime is about $20 \mu\text{s}$, and the total charge transferred to ground is 84 C. An expanded view of the main current pulse along with the corresponding current derivative record is shown, on a 4 ms time scale, in Figure 4b, in which the relatively slow subsidiary peaks are visible after the initial peak.

[16] Positive and negative (relative to the steady background current) M component-like pulses are seen during the steady current (between 150 and 180 ms), in Figure 4c. It is worth noting that flash #2 can be viewed as bipolar, with




Figure 11. Current waveform associated with a type 1 positive flash that occurred on 3 August 2011 at 11:51 (flash #17), displayed on a 10 ms time scale. The pulse peak of this waveform is 93 kA , the largest in our data set.




Figure 12. Cumulative frequency distribution of transferred charge (N = 30).

polarity reversals due to M component-like pulses occurring between 168 and 172 ms. The occurrence of M components in positive flashes was recently reported by Campos *et al.* [2009] who analyzed the luminosity-versus-time profiles obtained using a high-speed video camera. Our data appear to confirm the findings of Campos and coworkers and, to the best of our knowledge, constitute the first direct evidence of M component-like current pulses of both polarities in positive flashes. Note that some M component-like current waveforms of only one polarity can be seen in the data presented by Goto and Narita [1995] (see their Figure 10).

[17] Bursts of fast pulses can be seen in Figure 4a at about 107 ms, 112 ms, 117 ms, 120 ms, and immediately prior to the initial slow rise of the main pulse. Figure 4d shows an expanded view (10 μ s time scale) of the time derivative of the largest fast current pulse that occurred at about 120 ms. The pulse exhibits oscillations (in this case with a frequency of about 1.7 MHz) that could be associated with the onset of the upward negative leader or induced in the tower by cloud discharges. In the former case, these oscillations can be viewed as being due to attempted negative leader processes similar to those observed to occur prior to the formation of

a sustained upward positive leader in rocket-triggered lightning (see, for example, [Rakov and Uman, 2003, Figure 7.9 and 7.10]). If so, our data constitute the first documented evidence of attempted negative leader process in upward positive lightning.

3.3. Type 2

[18] The second type of observed positive flashes is characterized by a relatively slow (millisecond scale) waveform (see an example shown in Figure 5a) with large, oscillatory pulse trains superimposed on the initial rising portion of the waveform. The initial slow pulse is followed by one or more smaller slow pulses superimposed on a steady current and exhibiting rise and fall times of the order of 10 ms or more (examples are the pulses peaking at around 130 ms and 150 ms in Figure 5a). The pulses superimposed on the rising part of the initial slow waveform have risetimes of the order of microseconds and are separated by time intervals of some tens of microseconds; they are inferred to be due to an upward negative stepped leader [Wada *et al.*, 1996; Rakov, 2003; Diendorfer *et al.*, 2006; Zhou *et al.*, 2012]. The overall peak current of type 2 flashes is typically associated with one of these fast pulses.

[19] Figure 5a presents the overall current waveform associated with a positive flash of the second type recorded on 30 August 2010 with a current peak of 6.5 kA. Figure 5b presents an expanded view of the fast pulses superimposed on the rising portion of the initial slow waveform. These successive pulses are separated by time intervals of about 50 μ s. In Figure 5c, we have plotted, on a 600 μ s time scale, the time derivative of the current measured using the B-dot sensor. It can be seen that the highest steepnesses (in excess of 15 kA/ μ s) are associated with the initial pulses.

[20] Figure 5d presents the time derivative of one of the fast current pulses that occurred at about 120 ms. The pulse exhibits a damped oscillatory behavior, with a frequency of oscillations of about 1.9 MHz, very similar to the frequency of oscillation of the bursts of fast pulses observed in type 1 flashes. These oscillatory pulses are presumably due to the onset of upward negative stepped leader.




Figure 13. Charge histogram. The MLE (maximum-likelihood estimation) PDF (broken green line) is also shown.




Figure 14. Flash #1 that occurred on 21 July 2010, 19:05. This flash was classified as type 1 and transferred to ground 281 C of positive charge. Current (left scale) is shown in blue and charge (right scale) in green.

[21] Another example of overall current waveform associated with the second type is shown in Figure 6a. Again, this current is characterized by an initial phase with fast pulses superimposed on the rising part of the first slow pulse. The slow portion of the waveform in this flash has a relatively low peak value of 3.4 kA and a risetime of 12 ms. Figure 6b shows an expanded view of the initial rising part of the first slow pulse, in which the multiple fast pulses are clearly discernible. The time derivative of the first fast pulse is shown on an expanded time scale in Figure 6c.

[22] Figure 7 shows the current associated with another positive flash classified as type 2, recorded on 1 August 2010 (flash #4). The main slow pulse in this waveform is preceded by bursts of fast pulses that can be seen at about 107 ms, 118 ms, and 120 ms. At about 129 ms, the current exhibits a relatively slow waveform with oscillatory pulse trains superimposed on its initial rising portion (see Figure 7b). In this case, a second slow waveform, peaking at about 180 ms and lasting about 15 ms, appears after about 40 ms interval. Figure 7b shows details of the waveform in the time window of 129 ms to 134 ms, where fast repetitive

pulses are clearly noticeable in the rising portion of the first relatively slow pulse. Note that no fast pulses are seen in the second slow waveform. Also note that this behavior (absence of fast pulses) is very similar to that of subsidiary slow pulses in the flashes shown in Figure 5 (peaking at 132 ms and 150 ms) and Figure 6 (peaking at 175 ms).

4. Statistical Analysis of Positive Flashes

[23] Table 1 summarizes the values of peak current, charge, duration, and action integral associated with the recorded positive flash current waveforms. In this section, we present the statistics associated with the salient parameters (derivable from current records) of these positive flashes, with reference to available data obtained at other instrumented towers.

4.1. Peak Current

[24] *Zhou et al.* [2012] defined two parameters associated with the current peak: (1) the “pulse peak current” which is the difference between the maximum current value of the




Figure 15. Flash #22 that occurred on 27 August 2011, 6:30. This flash was classified as type 2 and transferred to ground 913 C of positive charge. Current (left scale) is shown in blue and charge (right scale) in green.




Figure 16. Cumulative frequency distribution of flash duration (N = 30).

flash and the no-current (zero) level and (2) the “flash peak current” which is the maximum of the underlying slowly varying current and the no-current (zero) level. These two definitions are illustrated in Figure 8 for two different flashes of type 2. The underlying slow waveform, used for measuring the flash peak current, was obtained by applying a 1 kHz low-pass filter to the waveforms. Note that the distinction between pulse and flash peaks is only needed for flashes of type 2 (only pulse peaks are given for type 1 flashes in Table 1).

[25] Figure 9 presents the cumulative frequency distribution of pulse peak currents for all 30 events combined, and Figure 10 presents the corresponding histogram. Although the overall shape of the histogram is indicative of a log-normal distribution, some deviations are observed both for very low and for very high values. These could be due in part to the small sample size. Note that the highest peak currents are associated with type 1 flashes.

[26] The maximum measured value of the peak current during the entire period of observation is 92.7 kA (see Figure 11). It was measured in flash #17 that occurred on 3 August 2011 at 11:51. This flash was classified as type 1. Note that in this case the main pulse had considerable fine structure and was followed within a few milliseconds by more structure in the form of relatively fast pulses superimposed on steady current. Many of these pulses have peaks of the order of tens of kiloampere, up to a maximum of 72 kA. The median for the pulse peak current is found to be 11.1 kA (31.5 kA for type 1 and 10.4 kA for type 2).

4.2. Total Transferred Charge

[27] Figures 12 and 13 show respectively the cumulative probability plot and the histogram of the transferred charge. As with the peak current, the histogram and the cumulative probability plots exhibit the overall characteristics of a log-normal distribution with some deviation for the very high and the very low values which can be attributed, at least in part, to the small sample size. The median is found to be 169 C (84 C for type 1 and 185 C for type 2).

[28] An example of a flash transferring a large amount of charge is presented in Figure 14. This is a type 1 flash that transferred 280 C of charge to ground. In this figure, vertical lines show the times corresponding to 10%, 50%, and 90% of the total transferred charge.

[29] It is worth observing that 8 flashes (all of type 2) out of 30 transported to ground positive charge in excess of 500 C (see Table 1). The largest amount of transferred charge in our data set corresponds to flash #22 that occurred on 27 August 2011 and is shown in Figure 15. The amount of charge transferred during this flash (913 C) is close to the highest charge transfer of about 1000 C ever measured for positive and negative winter lightning in Japan [Miyake *et al.*, 1992].

4.3. Flash Duration

[30] Figures 16 and 17 present the cumulative probability plot and the histogram for the flash duration. The median duration is found to be 80 ms (50 ms for type 1 and 100 ms




Figure 17. Flash duration histogram. The MLE (maximum-likelihood estimation) PDF (broken green line) is also shown.




Figure 18. Action integral histogram.

for type 2). Note that type 1 flashes tend to have shorter durations than type 2 flashes.

4.4. Action Integral

[31] The histogram of action integral is presented in Figure 18. The measured values are characterized by a median of $4 \cdot 10^5 \text{ A}^2\text{s}$ ($3 \cdot 10^5 \text{ A}^2\text{s}$ for type 1 and $4.2 \cdot 10^5$

A^2s for type 2) and a maximum value of $7.19 \cdot 10^6 \text{ A}^2\text{s}$. These values are significantly larger than those reported for 10 years of observations at the Gaisberg tower [Zhou et al., 2012], with a median of $1.6 \cdot 10^5 \text{ A}^2\text{s}$ and a maximum of $2 \cdot 10^6 \text{ A}^2\text{s}$. Two thirds of the observed values remain, nevertheless, below $10^6 \text{ A}^2\text{s}$.

4.5. Correlation Between Parameters

[32] Figures 19a and 19b present the pulse peak current as a function of the charge and flash duration, respectively. It can be seen that the correlation between the peak current and the charge/duration is very different for type 1 and type 2 flashes. While the peak currents for type 2 flashes remain below about 25 kA regardless of the transferred charge, the peak current in type 1 flashes tends to increase with increasing transferred charge or duration. It should be noted, however, that the number of type 1 flashes is quite small to draw definitive conclusions.

5. Discussion

[33] Table 2 presents a summary of median values of the pulse peak current, transferred charge, and flash duration for all 30 upward positive events examined in this study and their counterparts from other studies in Switzerland (Monte San Salvatore) [Berger, 1977], Japan [Miki et al., 2010], and Austria (Gaisberg tower) [Zhou et al., 2012]. The sample size is given in the parentheses.

[34] It can be seen that our median values for the peak current and the flash duration are similar to those based on the data obtained recently in Austria.

[35] The amount of transferred charge is substantially larger in our data set, with a median of 169 C, than in other studies. This value is about 6 times as large as those obtained at Monte San Salvatore [Berger, 1977] and in Japan [Miki et al., 2010] and about 3 times larger than the value obtained in Austria [Zhou et al., 2012].

[36] The values for the average current calculated as the ratio of the charge transfer and the flash duration range from 200 A to 4.5 kA (see Table 1). The median value, 1.7 kA, is




Figure 19. (a) Pulse peak current versus transferred charge. (b) Pulse peak current versus flash duration.

Table 2. Comparison of Median Values of Upward Positive Lightning Parameters From Different Studies^a

Study	Peak Current (kA)	Flash Duration (ms)	Charge Transfer (C)	Action Integral ($\times 10^6 \text{A}^2 \text{s}$)
Monte San Salvatore, Switzerland [Berger, 1977]	1.5 (132)	72 (138)	26 (137)	-
Nikaho Kougen Wind Farm, Japan [Miki et al., 2010]	6.5 (16)	40 (16)	30.2 (16)	-
Gaisberg Tower, Austria [Zhou et al., 2012]	11 ^b (26)	82 (26)	58 (26)	0.16 (25)
Säntis Tower, Switzerland (present study)	11.1 ^b (30)	80 (30)	169 (30)	0.4 (30)

^aThe sample size is given in parentheses.

^bPulse peak current, as defined in Zhou et al. [2012] (see Figure 8).

considerably higher than median average currents during the initial stage of upward negative flashes reported by Diendorfer et al. [2009].

[37] The sample of 26 directly measured positive lightning currents analyzed by Berger et al. [1975], commonly used as a primary reference both in lightning research and in lightning protection studies, is apparently based on a mix of (1) discharges initiated as a result of junction between a descending positive leader and an upward connecting negative leader within some tens of meters of the tower top and (2) discharges initiated as a result of a very long (1–2 km) upward negative leader from the tower making contact with an oppositely charged channel inside the cloud [Rakov, 2003]. These two types of positive discharges, which differ by the height above the tower top of the junction between the upward connecting leader and the oppositely charged overhead channel (descending positive leader or positively charged in-cloud discharge channel), are expected to produce very different current waveforms at the tower. Specifically, relatively fast-rising, “microsecond-scale” current waveforms (similar to those produced by negative return strokes in downward lightning) are expected for relatively low junction points, and relatively slow-rising, “millisecond-scale” waveforms are expected for relatively high junction points. The microsecond-scale current waveform is probably a result of processes similar to those in downward negative lightning, whereas the millisecond-scale current is likely to be a result of the M component mode of charge transfer to the ground, although in the latter case, current peaks can be considerably higher than for ordinary M components. The microsecond-scale waveforms of Berger et al. have typical risetimes of less than 10 μs or so. We have not yet

observed positive lightning current waveforms of this type. The millisecond-scale waveforms of Berger et al. have typical risetimes of tens to hundreds of microseconds. Our type 1 positive flashes appear to belong to this latter category (see Table 3). These flashes are apparently characterized by an upward negative leader making connection with an already existing positively charged conducting channel in the cloud and can possibly be viewed as positive downward flashes with very long negative upward connecting leaders. In contrast, type 2 positive flashes do not make contact with an existing channel in the cloud and their currents exhibit much slower (more than a millisecond or so) overall risetimes with superimposed fast pulses characteristic of leader steps. The type 2 flashes are “classical” upward discharges.

[38] The impulse charges for type 1 events are presented in Table 3. Note that the impulse charge is defined here as the integral from the 2 kA point on the rising front to the half-peak value on the tail. The values range from 1.7 C to 32.3 C with a mean value of 15.6 C, which is similar to the median value of 16 C reported by Berger et al. [1975] for the 26 positive flashes discussed above. The latter sample includes both classical downward flashes and those with very long upward connecting leaders. Also presented in Table 3 are the median and geometrical mean values of the peak current, risetime, pulse duration, and action integral, which can be directly compared with Berger et al.’s values. It appears that all the parameters (except for the pulse duration) of our type 1 events are similar to their counterparts reported by Berger et al. [1975].

[39] Cummer and Lyons [2005] examined charge moment changes (QH) in the first 2 ms after the beginning of the

Table 3. Peak Currents, Impulse Charges (the Integral of the Current From the 2 kA Point on the Front to the Half-Peak Value on the Tail), Risetimes (2 kA to Peak), Pulse Durations (2 kA to 50% Value on the Tail), Action Integrals, and Charge Moment Changes (QH in 2 ms) Assuming a Channel Height of 4 km for Type 1 Flashes

Flash #	Peak Current (kA)	Impulse Charge (C) ^a	Risetime $T_{2\text{kA-PEAK}}$ (μs)	Pulse Duration ^c Δt (ms)	Action Integral ($\times 10^6 \text{A}^2 \text{s}$)	Charge Moment Change QH in 2 ms (Ckm) ^b
1	42.7	32.3	580	1.28	1.7	157
2	18.2	13.1	30	1.44	0.295	68.5
13	16.3	3.6	40	0.35	0.056	26
14	31.5	1.7	20	0.07	0.135	45.5
17	92.7	27.3	130	0.99	4.185	143
Median	31.5	13.1	40	0.99	0.295	68.5
GM	32.6	9.3	71.0	0.5	0.4	71.1

^aIntegral of the current from the 2 kA point on the rising front to the half-peak value on the tail.

^bAssuming a channel height of 4 km.

^cMeasured from the 2 kA point on the rising front to the half-peak value on the tail.

return stroke in cloud-to-ground lightning for three night thunderstorms in Colorado, Nebraska, and Kansas High Plains. They found that strokes having charge moments above 600 C km in two storms and 350 C km in the other produced sprites after short delays (<5 ms). (Note that sprites are produced almost exclusively by positive lightning.) Nag and Rakov [2012], who studied downward positive lightning in Florida, estimated charge moment changes (inferred from measured electric fields and assumed channel length of 12 km). Their charge moment changes in 2 ms varied from 74 to 504 C km, with 16% (3 out of 19 strokes) having charge moment changes greater than 350 C km. They concluded that it is likely that the majority of their positive return strokes did not produce detectable sprites. We performed a similar analysis for our five type 1 events (assuming a 4 km channel length) and found charge moment changes in 2 ms varying from 26 to 157 C km (see Table 3), all below the 350 C km “threshold”. Thus, it is likely that our positive events did not produce detectable sprites.

6. Summary

[40] In this paper, an analysis of the current waveforms of positive flashes recorded on the Säntis tower, Switzerland, from May 2010 through January 2012 is presented. The overall number of recorded flashes was 200, of which 30 were of positive polarity (effectively transported positive charge to ground) and 3 were bipolar. The recorded positive flashes were mainly occurring in the summer months, with August being the month during which most of them were observed (6 events in 2010 and 16 events in 2011). The percentage of positive flashes (15%) is considerably larger than in other studies in summer (3% to 6.5%).

[41] The observed current waveforms are classified into two types. The first type (comprising 5 flashes out of the measured 30) is characterized by the presence of a large, unipolar main current pulse with a risetime of a few tens of microseconds for four of the five flashes and about 380 μ s for the fifth one. In four of the five type 1 flashes, the main pulse exhibited structure after its main peak in the form of several subsidiary peaks separated by time intervals of the order of 1 millisecond. The main pulse was preceded, in three of the five flashes, by a clearly discernible initial, slowly rising ramp lasting a few milliseconds, and it was followed by a long steady current with superimposed pulses of both polarities, characteristic of M components. In four of the five flashes of type 1, the main current waveform was preceded by one or several bursts of fast pulses with oscillation frequencies of some MHz, which are presumably due to attempted negative leader processes similar to those observed to occur prior to the formation of a sustained upward positive leader in rocket-triggered lightning.

[42] The second type of observed positive flashes is characterized by a relatively slow waveform with a duration measured in tens of milliseconds with large, oscillatory pulse trains superimposed on the initial rising portion of the waveform. The initial slow pulse is followed by one or more smaller slow pulses superimposed on a steady current and exhibiting rise and fall times of the order of 10 ms or more. The fast pulses have risetimes of the order of microseconds and are probably associated with upward leader steps. The

overall peak current of type 2 flashes is typically associated with one of the fast pulses.

[43] Our data constitute the first direct evidence of M component current pulses of both polarities during steady currents lowering positive charge to ground.

[44] The observed positive flashes (both types combined) are characterized by a median peak current of 11.1 kA and a median flash duration of 80 ms. These values are similar to those based on the data recorded at the Gaisberg tower in Austria. On the other hand, the amount of transferred charge is substantially larger in our data set, with a median value of 169 C (6 times as large as the values obtained at Monte San Salvatore and in Japan and 3 times as large as the value obtained in Austria). Eight flashes out of 30 transported to ground positive charge in excess of 500 C.

[45] The parameters of our 5 type 1 events appear to be similar (except for the pulse duration) to their counterparts for 26 positive lightning events examined by Berger *et al.* [1975], which can be viewed as downward flashes with very long upward connecting leaders. On the other hand, our type 2 events are classical upward flashes.

References

- Berger, K. (1977), The Earth flash, in *Lightning*, edited by R. H. Golde, pp. 119–190, Academic Press, New York.
- Berger, K., R. B. Anderson, and H. Kroninger (1975), Parameters of lightning flashes, *Electra. no.*, 41, 23–37.
- Campos, L. Z. S., M. M. F. Saba, O. Pinto Jr., and M. G. Ballarotti (2009), Waveshapes of continuing currents and properties of M-components in natural positive cloud-to-ground lightning, *Atmos. Res.*, 91(2–4), 416–424.
- Cooray, V., and H. Pérez (1994), Some features of lightning flashes observed in Sweden, *J. Geophys. Res.*, 99(D5), 10,683–10,688.
- Cummer, S. A., and W. A. Lyons (2005), Implications of lightning charge moment changes for sprite initiation, *J. Geophys. Res.*, 110, A04304, doi:10.1029/2004JA010812.
- Diendorfer, G., H. Pichler, and M. Mair (2006), Characteristics of positive upward lightning measured on an instrumented tower, paper presented at 28th International Conference on Lightning Protection (ICLP), Kanazawa, Japan.
- Diendorfer, G., H. Pichler, and M. Mair (2009), Some parameters of negative upward-initiated lightning to the Gaisberg tower (2000–2007), *IEEE Trans. Electromagn. Compat.*, 51(3), 443–452.
- Fleener, S. A., C. J. Biagi, K. L. Cummins, E. P. Krider, and X.-M. Shao (2009), Characteristics of cloud-to-ground lightning in warm-season thunderstorms in the Central Great Plains, *Atmos. Res.*, 91(2–4), 333–352.
- Fuquay, D. (1982), Positive cloud-to-ground lightning in summer thunderstorms, *J. Geophys. Res.*, 87(C9), 7131–7140.
- Goto, Y., and K. I. Narita (1995), Electrical characteristics of winter lightning, *J. Atmos. Terr. Phys.*, 57(5), 449–458.
- Ishii, M., K. Shimizu, J. Hojo, and K. Shinjo (1998), Termination of multiple-stroke flashes observed by electromagnetic field, paper presented at 24th International Conference on Lightning Protection (ICLP), Birmingham, UK.
- Kong, X., X. Qie, and Y. Zhao (2008), Characteristics of downward leader in a positive cloud-to-ground lightning flash observed by high-speed video camera and electric field changes, *Geophys. Res. Lett.*, 35, L05816, doi:10.1029/2007GL032764.
- Miki, M., T. Miki, A. Wada, A. Asakawa, Y. Asuka, and N. Honjo (2010), Observation of lightning flashes to wind turbines, paper presented at 30th International Conference on Lightning Protection (ICLP), Cagliari, Italy.
- Miyake, K., T. Suzuki, and K. Shinjou (1992), Characteristics of winter lightning current on Japan Sea coast, *IEEE Trans. Power Delivery*, 7(3), 1450–1456.
- Nag, A., and V. A. Rakov (2012), Positive lightning: An overview, new observations, and inferences, *J. Geophys. Res.*, 117, D08109, doi:10.1029/2012JD017545.
- Rakov, V. A. (2003), A review of positive and bipolar lightning discharge, *Bull. Am. Meteorol. Soc.*, 84, 767–776.
- Rakov, V. A., and M. A. Uman (2003), *Lightning: Physics and Effects*, Cambridge Univ. Press, New York.

- Romero, C., M. Paolone, F. Rachidi, M. Rubinstein, A. Rubinstein, P. Zweiacker, and C. A. Nucci (2011), Current waveforms associated with positive flashes recorded on the Sântis Tower in summer 2010, paper presented at XI International Symposium on Lightning Protection (SIPDA), Fortaleza, Brazil, October 3–7, 2011.
- Romero, C., M. Paolone, M. Rubinstein, F. Rachidi, A. Rubinstein, G. Diendorfer, W. Schulz, B. Daout, A. Kaelin, and P. Zweiacker (2012a), A system for the measurements of lightning currents at the Sântis tower, *Electr. Power Syst. Res. J.*, *82*(1), 34–43.
- Romero, C., A. Mediano, A. Rubinstein, F. Rachidi, M. Rubinstein, A. Paolone, P. Zweiacker, N. Mora, D. Pavanello, and B. Daout (2012b), Measurement of lightning currents using a combination of Rogowski coils and B-Dot sensors, *J. Lightning Res.*, *4*(1), 71–77.
- Romero, C., M. Rubinstein, F. Rachidi, M. Paolone, V. A. Rakov, D. Pavanello (2012c), Some characteristics of positive and bipolar lightning flashes recorded on the Sântis Tower in 2010 and 2011, 31st International Conference on Lightning Protection (ICLP), Vienna, Austria, September 3–7, 2012.
- Romero, C., F. Rachidi, M. Paolone, and M. Rubinstein (2013), Statistical distributions of lightning currents associated with upward-negative flashes based on the data collected at the Sântis tower in 2010 and 2011, *IEEE Trans. Power Delivery*, *28*(3), 1804–1812.
- Saba, M. M. F., K. L. Cummins, T. A. Warner, E. P. Krider, L. Z. S. Campos, M. G. Ballarotti, O. Pinto Jr., and S. A. Fleenor (2008), Positive leader characteristics from high-speed video observations, *Geophys. Res. Lett.*, *35*, L07802, doi:10.1029/2007GL033000.
- Saba, M. M. F., L. Z. S. Campos, E. P. Krider, and O. Pinto Jr. (2009), High-speed video observations of positive ground flashes produced by intracloud lightning, *Geophys. Res. Lett.*, *36*, L12811, doi:10.1029/2009GL038791.
- Saba, M. M. F., W. Schulz, T. A. Warner, L. Z. S. Campos, C. Schumann, E. P. Krider, K. L. Cummins, and R. E. Orville (2010), High-speed video observations of positive lightning flashes to ground, *J. Geophys. Res.*, *115*, D24201, doi:10.1029/2010JD014330.
- Wada, A., A. Asakawa, and T. Shindo (1996), Characteristics of lightning flash initiated by an upward leader in winter, paper presented at 23rd International Conference on Lightning Protection, Florence, Italy.
- Yashunin, S. A., E. A. Mareev, and V. A. Rakov (2007), Are lightning M components capable of initiating sprites and sprite halos?, *J. Geophys. Res.*, *112*, D10109, doi:10.1029/2006JD007631.
- Zhou, H., G. Diendorfer, R. Thottappillil, H. Pichler, and M. Mair (2012), Characteristics of upward positive lightning flashes initiated from the Gaisberg Tower, *J. Geophys. Res.*, *117*, D06110, doi:10.1029/2011JD016903.