

AD-A119 910

MASSACHUSETTS INST OF TECH CAMBRIDGE LAB FOR INFORMA--ETC F/G 12/1  
ROBUSTNESS OF ADAPTIVE CONTROL ALGORITHMS IN THE PRESENCE OF UN--ETC(U)  
SEP 82 C E ROHRS, L VALAVANI, M ATHANS N00014-82-K-0582  
LIDS-P-1240 NL

UNCLASSIFIED

1 of 1  
40 A  
73010



END  
DATE  
FILMED  
11-82  
DTIC

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS  
BEFORE COMPLETING FORM

1. REPORT NUMBER		2. GOVT ACCESSION NO. AD-A119.910	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Robustness of Adaptive Control Algorithms in the Presence of Unmodeled Dynamics		5. TYPE OF REPORT & PERIOD COVERED Paper	
7. AUTHOR(s) Charles E. Rohrs                      Michael Athans Lena Valavani                         Gunter Stein		6. PERFORMING ORG. REPORT NUMBER LIDS-P-1240	
9. PERFORMING ORGANIZATION NAME AND ADDRESS M.I.T. Laboratory for Information and Decision Systems Cambridge, MA 02139		8. CONTRACT OR GRANT NUMBER(s) ONR/N00014-82-K-0582 (NR 606-003)	
11. CONTROLLING OFFICE NAME AND ADDRESS Office of Naval Research 800 North Quincy St. Arlington, MA 22217		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE September, 1982	
		13. NUMBER OF PAGES 9	
		15. SECURITY CLASS. (of this report) Unclassified	
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	

16. DISTRIBUTION STATEMENT (of this Report)  
Approved for public release: distribution unlimited

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES  
Proc. 21st IEEE Conference on Decision and Control, Orlando, Florida, Dec. 1982.

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

**DTIC**  
**ELECTE**  
**S** OCT 0 5 1982 **D**

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)  
This paper reports the outcome of an exhaustive analytical and numerical investigation of stability and robustness properties of a wide class of adaptive control algorithms in the presence of unmodeled dynamics and output disturbances. The class of adaptive algorithms considered are those commonly referred to as model-reference adaptive control algorithms, self-tuning controllers, and dead-beat adaptive controllers; they have been developed for both continuous-time systems and discrete-time systems. The existing adaptive control algorithms have been proven to be globally asymptotically stable under certain assumptions. the

AD A119910

DTIC FILE COPY

key ones being (a) that the number of poles and zeroes of the unknown plant are known, and (b) that the primary performance criterion is related to good command following. These theoretical assumptions are too restrictive from an engineering point of view. *Real plants always contain unmodeled high-frequency dynamics and small delays, and hence no upper bound on the number of the plant poles and zeroes exists. Also real plants are always subject to unmeasurable output additive disturbances, although these may be quite small.* Hence, it is important to critically examine the stability robustness properties of the existing adaptive algorithms when some of the theoretical assumptions are removed; in particular, their stability and performance properties in the presence of unmodeled dynamics and output disturbances.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
Availability Codes	
Avail and/or	
Dist	Special
<b>A</b>	



ROBUSTNESS OF ADAPTIVE CONTROL ALGORITHMS  
IN THE PRESENCE OF UNMODELED DYNAMICS\*

by

Charles E. Rohrs, Lena Valavani, Michael Athans, and Gunter Stein

Laboratory for Information and Decision Systems  
Massachusetts Institute of Technology, Cambridge, MA, 02139

ABSTRACT

This paper reports the outcome of an exhaustive analytical and numerical investigation of stability and robustness properties of a wide class of adaptive control algorithms in the presence of unmodeled dynamics and output disturbances. The class of adaptive algorithms considered are those commonly referred to as model-reference adaptive control algorithms, self-tuning controllers, and dead-beat adaptive controllers; they have been developed for both continuous-time systems and discrete-time systems. The existing adaptive control algorithms have been proven to be globally asymptotically stable under certain assumptions, the key ones being (a) that the number of poles and zeroes of the unknown plant are known, and (b) that the primary performance criterion is related to good command following. These theoretical assumptions are too restrictive from an engineering point of view. *Real plants always contain unmodeled high-frequency dynamics and small delays, and hence no upper bound on the number of the plant poles and zeroes exists. Also real plants are always subject to unmeasurable output additive disturbances, although these may be quite small.* Hence, it is important to critically examine the stability robustness properties of the existing adaptive algorithms when some of the theoretical assumptions are removed; in particular, their stability and performance properties in the presence of unmodeled dynamics and output disturbances.

A unified analytical approach has been developed and documented in the recently completed Ph.D. thesis by Rohrs [15] that can be used to examine the class of existing adaptive algorithms. It was discovered that all existing algorithms contain an infinite-gain operator in the dynamic system that defines command reference errors and parameter errors; it is argued that such an infinite gain operator appears to be generic to all adaptive algorithms, whether they exhibit explicit or implicit parameter identification. *The practical engineering consequences of the existence of the infinite-gain operator are disastrous.* Analytical and simulation results demonstrate that sinusoidal reference inputs at specific frequencies and/or sinusoidal output disturbances at any frequency (including d.c.) cause the loop gain of the adaptive control system to increase without bound, thereby exciting the (unmodeled) plant dynamics, and yielding an unstable control system. Hence, it is concluded that *none* of the adaptive algorithms considered can be used with confidence in a practical control system design, because *instability will set in with a high probability.*

\*Research support by NASA Ames and Langley Research Centers under grant NASA/NGL-22-009-124, by the U.S. Air Force Office of Scientific Research (AFOSR) under grant AFOSR 77-3281, and by the Office of Naval Research under grant ONR/N00014-82-K-0582(NR 606-003)

Proc. 21st IEEE Conference on Decision and Control, Orlando, Florida, Dec. 1982.

1. INTRODUCTION

Due to space limitations we cannot possibly provide in this paper analytical and simulation evidence of all conclusions outlined in the abstract. Rather, we summarize the basic approach only for a single class of continuous-time algorithms that include those of Monopoli [4], Narendra and Valavani [1], and Feuer and Morse [2]. However, the same analysis techniques have been used to analyze more complex classes of (1) continuous-time adaptive control algorithms due to Narendra, Lin, and Valavani [3], both algorithms suggested by Morse [4], and the algorithms suggested by Egardt [7] which include those of Landau and Silveira [6], and Kreisselmeier [19]; and (2) discrete-time adaptive control algorithms due to Narendra and Lin [22], Goodwin, Ramadge, and Caines [23] (the so-called dead-beat controllers), and those developed in Egardt [17], which include the self-tuning-regulator of Astrom and Wittenmark [18] and that due to Landau [20]. The thesis by Rohrs [15] contains the full analysis and simulation results for the above classes of existing adaptive algorithms.

The end of the 1970's marked significant progress in the theory of adaptive control, both in terms of obtaining global asymptotic stability proofs [1-7] as well as in unifying diverse adaptive algorithms the derivation of which was based on different philosophical viewpoints [8,9].

Unfortunately, the stability proofs of all these algorithms have in common a very restrictive assumption. For continuous-time implementation this assumption is that the number of the poles and zeroes of the plant, and hence its relative degree, i.e., its number of poles minus its number of zeroes, is known. The counterpart of this assumption for discrete-time systems is that the pure delay in the plant is exactly an integer number of sampling periods and that this integer is known.

This restrictive assumption, in turn, is equivalent to enabling the designer to realize for an adaptive algorithm, a positive real error transfer function, on which all stability proofs have heavily hinged to-date [8]. Positive realness implies that the phase of the system cannot exceed  $\pm 90^\circ$  for all frequencies, while it is a well known fact that models of physical systems become very inaccurate in describing actual plant high-frequency phase characteristics. Moreover, for practical reasons, most controller designs need to be based on models which do not contain all of the plant dynamics, in order to keep the complexity of the required adaptive compensator within bounds.

Motivated from such considerations, researchers in the field recently started investigating the robustness of adaptive algorithms to violation of the restrictive (and unrealistic) assumption of exact knowledge of the plant order and its relative degree. Ioannou and Kokotovic [10] obtained error bounds for adaptive

observers and identifiers in the presence of unmodeled dynamics, while such analytical results were harder to obtain for reduced order adaptive controllers. The first such result, obtained by Rohrs *et al* [11], consists of "linearization" of the error equations, under the assumption that the overall system is in its final approach to convergence. Ioannou and Kokotovic [12] later obtained local stability results in the presence of unmodeled dynamics, and showed that the speed ratio of slow versus fast (unmodeled) dynamics directly affected the stability region. Earlier simulation studies by Rohrs *et al* [13] had already shown increased sensitivity of adaptive algorithms to disturbances and unmodeled dynamics, generation of high frequency control inputs and ultimately instability. Simple root-locus type plots for the linearized system in [11] showed how the presence of unmodeled dynamics could bring about instability of the overall system. It was also shown there that the generated frequencies in the adaptive loop depended nonlinearly on the magnitudes of the reference input and output.

The main contribution of this paper is in showing that two operators inherently included in all algorithms considered — as part of the adaptation mechanism — have infinite gain. As a result, two possible mechanisms of instability are isolated and discussed. It is argued, that the destabilizing effects in the presence of unmodeled dynamics can be attributed to either phase — in the case of high frequency inputs — or primarily gain considerations — in the case of unmeasurable output disturbances of any frequency, including d.c., which result in nonzero steady-state errors. The latter fact is most disconcerting for the performance of adaptive algorithms since it cannot be dealt with, given that a persistent disturbance of any frequency can have a destabilizing effect.

Our conclusions that the adaptive algorithms considered cannot be used for practical adaptive control, because the physical system will eventually become unstable, are based upon two facts of life that cannot be ignored in any physical control design: (1) there are always unmodeled dynamics at sufficiently high frequencies (and it is futile to try to model unmodeled dynamics) and (2) the plant cannot be isolated from unknown disturbances (e.g., 60 Hz hum) even though these may be small. Neither of these two practical issues have been included in the theoretical assumptions common to all adaptive algorithms considered, and this is why these algorithms cannot be used with confidence. To avoid exciting unmodeled dynamics, stringent requirements must be placed upon the bandwidth and phase margin of the control loop; no such considerations have been discussed in the literature. It is not at all obvious, nor easy, how to modify or extend the available algorithms to control their bandwidth, much less their phase margin properties.

In Section 2 of this paper proofs for the infinite gain of the operators generic to the adaptation mechanism are given. Section 3 contains the development of two possible mechanisms for instability that arise as a result of the infinite gain operators. Simulation results that show the validity of the heuristic arguments in Section 3 are presented in Section 4. Section 5 contains the conclusions.

## 2. THE ERROR MODEL STRUCTURE FOR A REPRESENTATIVE ADAPTIVE ALGORITHM

The simplest prototype for a model reference adaptive control algorithm in continuous-time has its origins to at least as far back as 1974, in the paper by Monopoli [14]. This algorithm has been proven asymptotically stable only for the case when the relative degree of

the plant is unity or at most two. The algorithms published by Narendra and Valavani [1] and Feuer and Morse [2] reduce to the same algorithm for the pertinent case. This algorithm will henceforth be referred to as CAL (continuous-time algorithm No.1)

The following equations summarize the dynamical equations that describe it; see also Figure 1. The equations presented here pertain to the case where a unity relative degree has been normally assumed. In the equations below  $r(t)$  is the (command) reference input, and  $d(t)=0$ .

Plant: 
$$y(t) = \frac{g_B(s)}{A(s)} [u(t)] \quad (1)$$

Auxiliary Variables: 
$$w_{ui}(t) = \frac{s^{i-1}}{P(s)} [u(t)]; \quad i=1,2,\dots,n-1 \quad (2)$$

$$w_{yi}(t) = \frac{s^{i-1}}{P(s)} [y(t)]; \quad i=1,2,\dots,n \quad (3)$$

$$\underline{w}(t) = \begin{bmatrix} r(t) \\ w_{u1}(t) \\ \vdots \\ w_{un}(t) \end{bmatrix}; \quad \underline{k}(t) = \begin{bmatrix} k_r(t) \\ k_u(t) \\ \vdots \\ k_y(t) \end{bmatrix} \quad (3a)$$

Model: 
$$y_M(t) = \frac{g_M B_M(s)}{A_M(s)} [z(t)] \quad (4)$$

Control Input: 
$$u(t) = \underline{k}^T(t) \underline{w}(t) \quad (5)$$

Output Error: 
$$e(t) = y(t) - y_M(t) \quad (6)$$

Parameter Adjustment Law: 
$$\dot{\underline{k}}(t) = \dot{\underline{k}}(t) = \underline{\Gamma} \underline{w}(t) e(t) \quad (7)$$

Nominal Controlled Plant: 
$$\frac{g^* B^*}{A^*} = \frac{k_r^* g_B P}{AP - AK_u^* - g_p BK_y^*} \quad (8)$$

Error Equation: 
$$e(t) = \left( \frac{g^* B^*}{A^*} - \frac{g_M B_M}{A_M} \right) [r(t)] + \frac{g^* B^*}{A^*} \left( \frac{\underline{k}^T(t) \underline{w}(t)}{k_r^*} \right) \quad (9)$$

In the above equations the following definitions apply:

$$\underline{k}(t) \triangleq \underline{k}^* + \underline{\tilde{k}}(t) \quad (10)$$

where  $\underline{k}^*$  is a constant  $2n$  vector

$$K_u^*(s) \triangleq k_{u(n-1)}^* s^{n-2} + k_{u(n-2)}^* s^{n-3} + \dots + k_{u1}^*$$

where  $k_{ui}^*$  is the  $i$ -th component of  $k_u^*$

$$K_y^*(s) = k_{yn}^* s^{n-1} + k_{y(n-1)}^* s^{n-2} + \dots + k_y^*$$

where  $k_{yi}^*$  is the  $i$ -th component of  $k_y^*$  and the vector  $\underline{k}^*$  componentwise corresponds exactly to the vector  $\underline{k}(t)$  in eqn. (3a). In the preceding equation we have tried to preserve the conventional literature notation [3,4,5,9], with  $P$  representing the characteristic polynomial for the state variable filters and  $\underline{k}(t)$  the parameter

misalignment vector. The quantity  $\frac{q^*B^*}{A^*}$  represents the closed-loop plant transfer function that would result if  $k$  were identically zero, i.e., if a constant control law  $k=k^*$  were used. Under the conventional assumption that the plant relative degree is exactly known and, if  $B_M$  divides  $P$ , then  $k^*$  can be chosen [1], such that

$$\frac{q^*B^*}{A^*} = \frac{q_M^* z^{(-n)}}{A_M^*} \quad (11)$$

If the Relative Degree Assumption is violated,  $\frac{q^*B^*}{A^*}$  can only get as close to  $\frac{q_M^* B_M^*}{A_M^*}$  as the feedback structure of the controller allows. The first term on the right-hand side of eqn. (9) results from such a consideration. Note that if eqn. (11) were satisfied, eqn. (9) reduces to the familiar error equation form that has appeared in the literature [8] for exact modeling. For more details the reader is referred to the literature cited in this section as well as to [15].

Figure 2 represents in block diagram form the combination of parameter adjustment law and error equations described by (7) and (9).

### 3. THE INFINITE GAIN OPERATORS

#### 3.1 Quantitative Proof of Infinite Gain for Operators of CAL

The error system in Fig. 2 consists of a forward linear time-invariant operator representing the nominal controlled plant complete with unmodeled dynamics,  $\frac{q^*B^*}{k^*A^*}$ ,

and a time-varying feedback operator. It is this feedback operator which is of immediate interest. The operator, reproduced in Fig. 3 for the case where  $w$  is a scalar and  $\Gamma=1$ , is parameterized by the function  $w(t)$  and can be represented mathematically as:

$$u(t) = G_w(t) [e(t)] = u_0 + w(t) \int_0^t w(\tau) e(\tau) d\tau \quad (12)$$

In order to make the notion of the gain of the operator  $G_w(t) [\cdot]$  precise, we introduce the following operator theoretic concepts.

**Definition 1:** A function  $f(t)$  from  $[0, \infty)$  to  $R$  is said to be in  $L_{2e}$  if the the truncated norm

$$\|f(t)\|_{L_2}^T \triangleq \left( \int_0^T f^2(\tau) d\tau \right)^{1/2} \quad (13)$$

is finite for all finite  $T$ .

**Definition 2:** The gain of an operator  $G[f(t)]$ , which maps functions in  $L_{2e}$  into functions in  $L_{2e}$  is defined as

$$\|G\| = \sup_{\substack{f(t) \in L_{2e} \\ T \in (0, \infty)}} \frac{\|G[f(t)]\|_{L_2}^T}{\|f(t)\|_{L_2}^T} \quad (14)$$

If there is no finite number satisfying eqn. (14), then  $G$  is said to have infinite gain.

**Theorem 1:** If  $w(t)$  is given by

$$w(t) = b+c \sin \omega t \quad (15)$$

for any positive constants  $b, c, \omega_0$ , the operator of eqn. (12) has infinite gain.

**Proof:** The proof consists of constructing a signal  $e(t)$ , such that

$$\lim_{T \rightarrow \infty} \frac{\|G_w[e(t)]\|_{L_2}^T}{\|e(t)\|_{L_2}^T} \quad (16)$$

is unbounded.

Let  $e(t) = a \sin \omega_0 t$ , with  $a$  an arbitrary positive constant and  $\omega_0$  the same constant as in eqn. (15). These signals produce:

$$w(t)e(t) = ab \sin \omega_0 t + \frac{1}{2} ac - \frac{1}{2} ac \cos 2\omega_0 t \quad (17)$$

$$\begin{aligned} \tilde{k}(t) &\triangleq \tilde{k}_0 + \int_0^t w(\tau)e(\tau) d\tau \\ &= \tilde{k}_0 + \frac{1}{2} act + \frac{ab}{\omega_0} - \frac{ab}{\omega_0} \cos \omega_0 t - \frac{ac}{4\omega_0} \sin 2\omega_0 t \end{aligned} \quad (18)$$

$$\begin{aligned} u(t) &= G_w(t) [e(t)] = u_0 + w(t) \int_0^t w(\tau)e(\tau) d\tau \\ &= u_0 + \frac{1}{2} abct + \frac{ab^2}{\omega_0} + \left( \frac{1}{2} ac^2 t + \frac{abc}{\omega_0} \right) \sin \omega_0 t + \\ &\quad - \left( \frac{ac^2}{8\omega_0} + \frac{ab^2}{\omega_0} \right) \cos \omega_0 t - \frac{3abc}{4\omega_0} \sin 2\omega_0 t + \frac{ac^2}{8\omega_0} \cos 3\omega_0 t \end{aligned} \quad (19)$$

Next, using standard norm inequalities, we obtain from eqn. (19)

$$\begin{aligned} \|u(t)\|_{L_2}^T &\geq \left\| \frac{1}{2} abct + \frac{1}{2} ac^2 t \sin \omega_0 t \right\|_{L_2}^T - \|u_0\|_{L_2}^T \\ &\quad - \left\| \frac{ab^2}{\omega_0} \right\|_{L_2}^T - \left\| \frac{abc}{\omega_0} \sin \omega_0 t \right\|_{L_2}^T - \left\| \left( \frac{ac^2}{8\omega_0} - \frac{ab^2}{\omega_0} \right) \cos \omega_0 t \right\|_{L_2}^T \\ &\quad - \left\| \frac{3abc}{4\omega_0} \sin 2\omega_0 t \right\|_{L_2}^T - \left\| \frac{ac^2}{8\omega_0} \cos 3\omega_0 t \right\|_{L_2}^T \end{aligned} \quad (20)$$

$$> \left\| \frac{1}{2} abct + \frac{1}{2} ac^2 t \sin \omega_0 t \right\|_{L_2}^T - (K_1^T)^{1/2} \quad (21)$$

with

$$\begin{aligned} K_1^T &= u_0^2 + \left( \frac{ab^2}{\omega_0} \right)^2 + \left( \frac{abc}{\omega_0} \right)^2 + \left\{ \frac{ac^2}{8\omega_0} + \frac{ab^2}{\omega_0} \right\}^2 + \\ &\quad + \left\{ \frac{3abc}{4\omega_0} \right\}^2 + \frac{ac^2}{8\omega_0}^2 < \infty \end{aligned} \quad (22)$$

Now

$$\begin{aligned} &\left\| \frac{1}{2} abct + \frac{1}{2} ac^2 t \sin \omega_0 t \right\|_{L_2}^T^2 = \\ &= \int_0^T \left( \frac{a^2 b^2 c^2}{4} t^2 + \frac{a^2 c^4}{4} t^2 \sin^2 \omega_0 t + \frac{a^2 bc^3}{2} t^2 \sin \omega_0 t \right) dt = \end{aligned} \quad (23)$$

$$= \frac{a^2 b^2 c^2}{12} t^3 \Big|_0^T + \frac{a^2 c^4}{4\omega_0^2} \left[ \frac{(\omega_0 t)^3}{6\omega_0} - \left\{ \frac{(\omega_0 t)^2}{4} + \frac{1}{8\omega_0} \right\} \right. \\ \left. - \sin 2\omega_0 t - \frac{t \cos 2\omega_0 t}{4} \right]_0^T + \\ + \frac{a^2 bc^3}{2\omega_0^2} [2\omega_0 t \sin \omega_0 t - (\omega_0 t)^2 - 2] \cos \omega_0 t \Big|_0^T \quad (24)$$

$$> \left( \frac{a^2 b^2 c^2}{12} + \frac{a^2 c^4}{24} \right) T^3 - K_2 T^2 - K_1 T^2 - K_0 \quad (25)$$

where

$$K_2 = \left( \frac{a^2 c^4}{16} \right)^2 + \left( \frac{a^2 bc^3}{2\omega_0} \right)^2 < \infty \quad (26)$$

$$K_1 = \left( \frac{a^2 c^4}{16\omega_0} \right)^2 + \left( \frac{a^2 bc^3}{\omega_0} \right)^2 < \infty \quad (27)$$

$$K_0 = \left( \frac{a^2 c^4}{32\omega_0^3} \right)^2 + \left( \frac{a^2 bc^3}{\omega_0^2} \right)^2 < \infty \quad (28)$$

Combining inequalities (21) and (25) we arrive at:

$$\left( \|u(t)\|_{L_2}^T \right)^2 \geq \left( \frac{a^2 b^2 c^2}{12} + \frac{a^2 c^4}{24} \right) T^3 - K_2 T^2 - K_1 T - K_0 \quad (29)$$

Also,

$$\left\{ \|e(t)\|_{L_2}^T \right\}^2 = a^2 \int_0^T \sin 2\omega_0 t dt \leq a^2 T \quad (30)$$

Therefore,

$$\frac{\|u(t)\|_{L_2}^T}{\|e(t)\|_{L_2}^T} > \left[ \frac{\left( \frac{a^2 b^2 c^2}{12} + \frac{a^2 c^4}{24} \right) T^3 - K_2 T^2 - K_1 T - K_0}{a^2 T} \right]^{1/2} \xrightarrow{T \rightarrow \infty}$$

and, therefore,  $G_w$  for  $w$  as in eqn. (15) has infinite gain.

In addition to the fact that the operator  $G_w(t)$  from  $e(t)$  to  $u(t)$  has infinite gain, the operator  $H_w$ , from  $e(t)$  to  $\tilde{r}(t)$  in Fig. 3 also has infinite gain. This operator is described by:

$$H_w(t)[e(t)] = \tilde{r}_0 + \int_0^t w(\tau)e(\tau)d\tau \quad (31)$$

**Theorem 2:** The operator  $H_w(t)$  with  $w(t)$  given in eqn. (15) has infinite gain.

**Proof:** Choose  $e(t) = a \sin \omega_0 t$  as before.

Then  $\tilde{r}(t) = H_w(t)[e(t)]$  is given by eqn. (18),

Proof of infinite gain for this operator then follows in exactly analogous steps as in Theorem 1 and is, therefore, omitted.

**Remark 1:** Both operators  $G_w$  and  $H_w$  will also have infinite gain for vectors  $w(t)$ , since the operator

infinite gains can arise from any component of the vector  $w(t)$ .

**Remark 2:** The corresponding operators  $G_w$  and  $H_w$  defined for various other adaptive algorithms such as the Narendra, Lin, Valavani [3] and Morse [4] of the model reference type, as well as the algorithms developed by Egardt [9], which include the self-tuning regulators, can also be proven to be infinite gain operators; see Rohrs [15].

**Remark 3:** Infinite gain operators are generically present in adaptive control and are typically represented as in Fig. 4, where  $F(s)$  is a stable diagonal transfer function matrix and  $M$  is (usually) a memoryless map.  $D$  and  $C$  are vectors of various input and output combinations, including filtered versions of said signals. The operator in Fig. 4 can also be proven to be infinite gain (see Rohrs [15]).

### 3.2 Two Mechanisms of Instability

In this section, we use the algorithm CAL to introduce and delineate two mechanisms which may cause unstable behavior in the adaptive system CAL when it is implemented in the presence of unmodeled dynamics and excited by sinusoidal reference inputs or by disturbances. The arguments made for CAL are also valid for other classes of algorithms mentioned in Remarks 2 and 3, *mutatis mutandis*. Since the arguments explaining instability are somewhat heuristic in nature, they are verified by simulation. Representative simulation results are given in Section 4.

#### 3.2.1 The Causes of Possible Instability

In order to demonstrate the infinite gain nature of the feedback operator of the error system of CAL in Section 2, it is assumed that a component of  $w(t)$  has the form

$$w_1(t) = b + c \sin \omega_0 t \quad (32)$$

and that the error has the form

$$e(t) = a \sin \omega_0 t \quad (33)$$

The arguments of Section 2 indicate that, if  $e(t)$  and a component of  $w(t)$  have distinct sinusoids at a common frequency, the operator  $G_w(t)$  of eqn. (12) and the operator  $H_w(t)$  of eqn. (31) will have infinite gains. Two possibilities for  $e(t)$  and  $w(t)$  to have the forms of eqn. (32) and eqn. (33) are now considered.

**Case (1):** If the reference input consists of a sinusoid and a constant, e.g.

$$r(t) = r_1 + r_2 \sin \omega_0 t \quad (34)$$

where  $r_1$  and  $r_2$  are constants, then the plant output  $y(t)$  will contain a constant term and a sinusoid at frequency  $\omega_0$ . Consequently, through eqns. (2), (3) and (31), all components of the vector  $w(t)$  will contain a constant and a sinusoid of frequency  $\omega_0$ .

If the controlled plant matches the model at d.c. but not at the frequency  $\omega_0$ , the output error

$$e(t) = y(t) - y_M(t) \quad (35)$$

will contain a sinusoid at frequency  $\omega_0$ . Thus, the conditions for infinite gain in the feedback path of Figure 1 have been attained.

Case (2): If a sinusoidal disturbance,  $d(t)$ , at frequency  $\omega$  enters the plant output as shown in Fig. 1, the sinusoid will appear in  $w(t)$  through the following equation which replaces eqn. (3) in the presence of an output disturbance

$$w_{yi}(t) = \frac{i-1}{P(s)} [y(t)+d(t)]; i=1,2,\dots,n \quad (36)$$

The following equation replaces eqn. (6) when an output disturbance is present

$$e(t) = y(t) + d(t) - y_M(t) \quad (37)$$

Any sinusoid present in  $d(t)$  will also enter  $e(t)$  through eqn. (37). Thus the signal  $e(t)$  and  $w(t)$  will contain sinusoids of the same frequency and the operators  $H_w(t)$  and  $G_w(t)$  will display an infinite gain.

### 3.2.2 Instability Due to the Gain of the Operator $G_w$ of Equation (12)

The operator  $G_w$  of eqn. (12) is not only an infinite gain operator  $\frac{1}{s}$  but its gain influences the system in such a manner as to allow arguments using linear systems concepts, as outlined below.

Assume, initially, that the error signal is of the form of eqn. (33), i.e., a sinusoid at frequency  $\omega_0$ . Assume also that a component of  $w(t)$  is of the form of eqn. (32), i.e., a constant plus a sinusoid at the same frequency  $\omega_0$  as the input. The output of the infinite gain operator,  $G_w(t)$  of eqn. (12), as given by eqn.

(19), consists of a sinusoid at frequency  $\omega_0$  with a gain which increases linearly with time plus other terms at 0 radians/sec (i.e. d.c.) and other harmonics of  $\omega_0$ ; i.e.  $u(t) = \frac{1}{2} ac^2 t \sin \omega_0 t + \text{other terms.}$

The infinite gain operator manifests its large gain by producing at the output a sinusoid at the same frequency,  $\omega_0$ , as the input sinusoid but with an amplitude increasing with time. By concentrating on the signal at frequency  $\omega_0$  and viewing the operator  $G_w(t)$  as a simple time-increasing gain with no phase shift at the frequency  $\omega_0$  and very small gain at other frequencies, we will be able to come up with a mechanism for instability of the error system of Figure 2, where  $G_w(t)$  consists of the feedback part of the loop.

If the forward path,  $\frac{q^*B^*}{k^*A^*}$ , of the error loop of Figure 2, has less than  $+180^\circ$  phase shift at the frequency  $\omega_0$ , and if the gain of  $G_w(t)$  were indeed small at all other frequencies, then the high gain of  $G_w(t)$  at  $\omega_0$  would not affect the stability of the error loop.

If, however, the forward loop,  $\frac{q^*B^*}{k^*A^*}$ , does have  $180^\circ$  phase shift at  $\omega_0$ , the combination of this phase shift with the sign reversal will produce a positive feedback loop around the operator  $G_w(t)$ , thereby reinforcing the sinusoid at the input of  $G_w(t)$ . The sinusoid will then increase in amplitude linearly with time, as the gain of  $G_w(t)$  grows, until the combined gain of  $G_w(t)$  and  $\frac{q^*B^*}{k^*A^*}$  exceeds unity at the frequency  $\omega_0$ . At this point, the loop itself will become unstable and all

signals will grow without bound very quickly (as the effects of the unstable loop and continually growing gain of  $G_w(t)$  compound.)

Since the infinite gain of  $G_w(t)$  can be achieved at any frequency  $\omega_0$ , if  $\frac{q^*B^*}{k^*A^*}$  has  $+180^\circ$  phase shift at any frequency, the adaptive system is susceptible to instability from either a reference input or a disturbance.

Thus the importance of the Relative Degree Assumption, which essentially allows one to assume that  $\frac{q^*B^*}{k^*A^*}$  is

strictly positive real is seen. The stability proof of CAL hinges on the assumption that  $\frac{q^*B^*}{k^*A^*}$  is strictly positive real and that  $G_w(t)$  is passive, i.e.

$$\int_0^\infty G_w(t) \{e(t)\}e(t)dt \geq 0 \quad (38)$$

Both properties of positive realness and passivity are properties which are independent of the gain of the operator involved. However, it is always the case that, due to the inevitable unmodeled dynamics, only a bound is known on the gain of the plant at high frequencies. Therefore, for a large class of unmodeled dynamics in the plant, including all unmodeled dynamics with relative degree two or greater, the operator,

$\frac{q^*B^*}{k^*A^*}$ , will have  $\pm 180^\circ$  phase shift at some frequency and be susceptible to unstable behavior if subjected to sinusoidal reference inputs and/or disturbances in that frequency range.

### 3.2.3 Instability Due to the Gain of the Operator $H_w$ of Equation (31)

In the previous subsection, the situation was examined where the amplitude of the sinusoidal error  $e(t)$  grew with time due to a positive feedback mechanism in the error loop. In this subsection, we explore the situation where the sinusoidal error,  $e(t)$ , is not at a frequency where it will grow due to the error system but, rather, when there exist persistent steady-state errors. Such a persistent error could arise from either or both of the two mechanisms discussed in Section 3.1.

1) A reference input with a number of frequencies is applied and the controlled plant with unmodeled dynamics cannot match the model in amplitude and phase for all reference input frequencies involved. This will cause a persistent sinusoid in both the error  $e(t)$ , through eqn. (6), and the signals  $w(t)$ , through eqns. (2) and (3), and/or

(2) An output sinusoidal disturbance,  $d(t)$ , enters as shown in Figure 1, causing the persistent sinusoid directly on  $e(t)$ , through eqn. (37), and  $w(t)$  through eqn. (36).

Assume, that through one of the above or any other mechanism that a component of  $w(t)$  contains a sinusoid at frequency  $\omega_0$  as in eqn. (32) and that  $e(t)$  contains a sinusoid of the same frequency. Then the operator  $H_w(t)$  has infinite gain and the norm of the output signal of this operator,  $\tilde{k}(t)$ , increases without bound. The signal,  $\tilde{k}(t)$ , will take the form of eqn. (18), repeated here:

$$\tilde{k}(t) = \tilde{k}_0 + \frac{1}{2} ac t + \frac{ab}{\omega_0} - \frac{ab}{\omega_0} \cos \omega_0 t - \frac{ac}{4\omega_0} \sin 2\omega_0 t$$



From the second term one can see that the parameters of the controller, defined in eqn. (10), i.e.,  $k(t) = k^* + \bar{k}(t)$ , will increase without bound.

If there are any unmodeled dynamics at all, increasing the size of the nominal feedback controller parameters without bound will cause the adaptive system to become unstable. Indeed, since it is the gains of the nominal feedback loop that are unbounded, the system will become unstable for a large class of plants including all those whose relative degree is three or more, even if no unmodeled dynamics are present.

#### 4. SIMULATION RESULTS

In this section the arguments for instability presented in the previous sections are shown to be valid via simulation.

The simulations were generated using a nominally first order plant with a pair of complex unmodeled poles, described by

$$y(t) = \frac{2}{(s+1)} \cdot \frac{229}{(s^2 + 30s + 229)} [u(t)] \quad (39)$$

and a reference model

$$y_M(t) = \frac{3}{s+3} [r(t)] \quad (40)$$

The simulations were all initialized with

$$k_y(0) = -.65; k_r(0) = 1.14 \quad (41)$$

which yield a stable linearization of the associated error equations. For the parameter values of eqn. (41) one finds that

$$\frac{q^*B^*}{A^*} = \frac{527}{s^3 + 31s^2 + 259s + 527} \quad (42)$$

The reference input signal was chosen based upon the discussion of section 3.2.2

$$r(t) = .3 + 1.85 \sin 16.1t, \quad (43)$$

the frequency 16.1 rad/sec. being the frequency at which the plant and the transfer function in (42), i.e.  $\frac{q^*B^*}{k^*A^*}$ , has 180° phase lag. A small d.c. offset was provided so that the linearized system would be asymptotically stable. The relatively large amplitude, 1.85 of the sinusoid in eqn. (43) was chosen so that the unstable behavior would occur over a reasonable simulation time. The adaptation gains were set equal to unity.

##### 4.1 Sinusoidal Reference Inputs

Figure 5 shows the plant output and parameters  $k_r(t)$  and  $k_y(t)$  for the conditions described so far. The amplitude of the plant output at the critical frequency ( $\omega = 16.1$  rad/sec) and the parameters grow linearly with time until the loop gain of the error system becomes larger than unity. At this point in time, even though the parameter values are well within the region of stability for the linearized system, highly unstable behavior results.

Figure 6 shows the results of a simulation, this time

with the reference input

$$r(t) = .3 + 2.0 \sin 8.0t \quad (44)$$

This simulation demonstrates that if the sinusoid input is at a frequency for which the nominal controlled plant does not generate a large phase shift (at  $\omega = 8.0$ , the phase shift of eqn. (42) is  $-133^\circ$ ), the algorithm may stabilize despite the high gain operator.

Similar results were obtained for the algorithms described in [3,4,6,7,9], but are not included here due to space considerations. The reader is referred to [15] for a more comprehensive set of simulation results, in which instability occurs via both the mechanisms described in sections 3.2.2 and 3.2.3, for sinusoidal inputs.

##### 4.2 Simulations with Output Disturbances

The results in this subsection demonstrate that the instability mechanism explained in Section 3.2.2 does indeed occur when there is an additive unknown output disturbance at the wrong frequency, entering the system as shown in Fig. 1. In addition, the instability mechanism of section 3.2.3, which will drive the algorithms unstable when there is a sinusoidal disturbance at any frequency, is also shown to take place. The same numerical example is employed here as well.

##### Instability via the Phase Mechanism of Section 3.2.2

In this case, CAL was driven by a constant reference input

$$r(t) = .3 \quad (45)$$

with a very small output additive disturbance

$$d(t) = 5.59 \times 10^{-6} \sin 16.1t \quad (46)$$

The results are shown in Fig. 7, and instability occurs as predicted. The only surprise may be the minuteness of the disturbance ( $10^{-6}$ ) which will cause instability.

##### Instability via the Gain Increase Mechanism of Section 3.2.3

Figure 8 shows the results of a simulation of CAL that was generated with

$$r=0.3$$

but the disturbance was changed to

$$d(t) = 8.0 \times 10^{-6} \sin 5t \quad (47)$$

At  $\omega = 5$ ,  $\frac{q^*B^*}{k^*A^*}$  of eqn. (42) provides only  $-102^\circ$  phase shift so the sinusoidal error signal of increasing amplitude, which is characteristic of instability via the mechanism of Section 3.2.2, is not seen in Fig. 8. What is seen is that the system becomes unstable by the mechanism of Section 3.2.3. While the output appears to settle down to a steady state sinusoidal error, the  $k_y$  parameter drifts away until the point where the controller becomes unstable. (Only the onset of unstable behavior is shown in Figure 8 in order to maintain scale). We note also that even when the error appeared settled, its value represented a large disturbance amplification rather than disturbance rejection.

The most disconcerting part of this analysis is that none of the systems analyzed have been able to counter this parameter drift for a sinusoidal disturbance at any frequency tried!

Indeed, Figure 9 shows the results of a simulation run with reference input

$$r=0.0 \quad (48)$$

and constant disturbance

$$d = 3.0 \times 10^{-6} \quad (49)$$

The simulation results show that the output gain settles for a long time, again with disturbance amplification, but the parameter  $k_y$  increases in magnitude until instability ensues. Thus the adaptive algorithm shows no ability to act even as a regulator when there are output disturbances.

### 5. CONCLUSIONS

In this paper it was shown, by analytical methods and verified by simulation results, that existing adaptive algorithms as described in [1-4,6,7,19], have imbedded in their adaptation mechanisms infinite gain operators which, in the presence of unmodeled dynamics, will cause:

- instability, if the reference input is a high frequency sinusoid
- disturbance amplification and instability if there is a sinusoidal output disturbance at any frequency including d.c.
- instability, at any frequency of reference inputs for which there is a non-zero steady state error.

While the first problem can be alleviated by proper limitations on the class of permissible reference inputs, the designer has no control over the additive output disturbances which impact his system, or of non-zero steady-state errors that are a consequence of imperfect model matching. Sinusoidal disturbances and inexact matching conditions are extremely common in practice and can produce disastrous instabilities in the adaptive algorithms considered.

Suggested remedies in the literature such as low pass filtering of plant output or error signal [26,7,21] will not work either.

It is shown in [15] that adding the filter to the output of the plant does nothing to change the basic stability problem as discussed in section 3.2. It is also shown in [15] that filtering of the output error merely results in the destabilizing input, being at a lower frequency.

Exactly analogous results were also obtained for discrete-time algorithms as described in [5,17,18,20] and have been reported in [15].

Finally, unless something is done to eliminate the adverse reaction to disturbances-at any frequency-and to nonzero steady-state errors in the presence of unmodeled dynamics, the existing adaptive algorithms cannot be considered as serious practical alternatives to other methods of control.

### 6. REFERENCES

1. K.S. Narendra and L.S. Valavani, "Stable Adaptive Controller Design-Direct Control," IEEE Trans. Autom. Contr., Vol. AC-23, pp. 570-583, Aug. 1978.
2. A. Feuer and A.S. Morse, "Adaptive Control of Single-Input Single-Output Linear Systems," IEEE

Trans. Autom. Contr., Vol. AC-23, pp. 557-570, August 1978.

3. K.S. Narendra, Y.H. Lin and L.S. Valavani, "Stable Adaptive Controller Design, Part II: Proof of Stability," IEEE Trans. Autom. Contr., Vol. AC-25, pp. 440-448, June 1980.
4. A.S. Morse, "Global Stability of Parameter Adaptive Control Systems," IEEE Trans. Autom. Contr., Vol. AC-25, pp. 433-440, June 1980.
5. G.C. Goodwin, P.J. Ramadge, and P.E. Caines, "Discrete-Time Multivariable Adaptive Control," IEEE Trans. Autom. Contr., Vol. AC-25, pp. 449-456, June 1980.
6. I.D. Landau and H.M. Silveira, "A Stability Theorem with Applications to Adaptive Control," IEEE Trans. Autom. Contr., Vol. AC-24, pp. 305-312, April 1979.
7. B. Egardt, "Stability Analysis of Continuous-Time Adaptive Control Systems," SIAM J. of Control and Optimization, Vol. 18, No. 5, pp. 540-557, Sept., 1980.
8. L.S. Valavani, "Stability and Convergence of Adaptive Control Algorithms: A Survey and Some New Results," Proc. of the JACC Conf., San Francisco, CA, August 1980.
9. B. Egardt, "Unification of Some Continuous-Time Adaptive Control Schemes," IEEE Trans. Autom. Contr., Vol. AC-24, No. 4, pp. 588-592, August 1979.
10. P.A. Ioannou and P.V. Kokotovic, "Error Bounds for Model-Plant Mismatch in Identifiers and Adaptive Observers," IEEE Trans. Autom. Contr., Vol. AC-27, pp. 921-927, August 1982.
11. C. Rohrs, L. Valavani, M. Athans and G. Stein, "Analytical Verification of Undesirable Properties of Direct Model Reference Adaptive Control Algorithms," LIDS-P-1122, M.I.T., August 1981; also Proc. 20th IEEE Conference on Decision and Control, San Diego, CA, December 1981.
12. P. Ioannou and P. Kokotovic, "Singular Perturbations on Robust Redesign of Adaptive Control," presented at IFAC Workshop on Singular Perturbations and Robustness of Control Systems, Lake Ohrid, Yugoslavia, July 1982.
13. C. Rohrs, L. Valavani and M. Athans, "Convergence Studies of Adaptive Control Algorithms, Part I: Analysis," Proc. IEEE CDC Conf., Albuquerque, New Mexico, 1980, pp. 1138-1141.
14. R.V. Monopoli, "Model Reference Adaptive Control with an Augmented Error Signal," IEEE Trans. Autom. Contr., Vol. AC-19, pp. 474-484, October 1974.
15. C. Rohrs, Adaptive Control in the Presence of Unmodeled Dynamics, Ph.D. Thesis, Dept. of Elec. Eng. and Computer Science, M.I.T., August 1982.
16. P. Ioannou, Robustness of Model Reference Adaptive Schemes with Respect to Modeling Errors, Ph.D. Thesis, Dept. of Elec. Eng., Univ. of Illinois at Urbana-Champaign, Report DC-53, August 1982.
17. B. Egardt, "Unification of Some Discrete-Time Adaptive Control Schemes," IEEE Trans. Autom. Contr., Vol. AC-25, No. 4, pp. 693-697, August 1980.

"The analysis of Ioannou [16] shows that, if there were no disturbance in this case, the output would converge to zero. Ioannou's work contains no analysis in the presence of disturbances.

18. K.J. Åström and B. Wittenmark, "A Self-Tuning Regulator," *Automatica*, No. 8, pp. 185-199, 1973.
19. G. Kreisselmeier, "Adaptive Control via Adaptive Observation and Asymptotic Feedback Matrix Synthesis," *IEEE Trans. Autom. Contr.*, Vol. AC-25, pp. 717-722, August 1980.
20. I.D. Landau, "An Extension of a Stability Theorem Applicable to Adaptive Control," *IEEE Trans. Autom. Contr.*, Vol. AC-25, pp. 814-817, August 1980.
21. I.D. Landau and R. Lozano, "Unification of Discrete-Time Explicit Model Reference Adaptive Control Designs," *Automatica*, Vol. 17, No. 4, pp. 593-611, July 1981.
22. K.S. Narendra and Y.H. Lin, "Stable Discrete Adaptive Control," *IEEE Trans. Autom. Contr.*, Vol. AC-25, No. 3, pp. 456-461, June 1980.




Figure 1: Controller structure of CAL with additive output disturbance,  $d(t)$ .




Figure 2: Error System for CAL.





Figure 3: Infinite gain operator of CAL.






Figure 7: Simulation of CAL with unmodeled dynamics,  $r(t)=0.3$ , and  $d(t)=5.59 \times 10^{-6} \sin 16.1t$ . (System eventually becomes unstable.)




Figure 9: Simulation of CAL with unmodeled dynamics,  $r(t)=0.0$ , and  $d(t)=3.0 \times 10^{-6}$ . (System eventually becomes unstable.)




Figure 8: Simulation of CAL with unmodeled dynamics,  $r(t)=0.3$ , and  $d(t)=8.0 \times 10^{-6} \sin 5.0t$ . (System eventually becomes unstable.)