

 Open access • Journal Article • DOI:10.1007/S11440-013-0251-6

Soil treatment with organic non-traditional additives for the improvement of earthworks — [Source link](#)

Gaëtan Blanck, Olivier Cuisinier, Farimah Masrouri

Institutions: University of Lorraine

Published on: 01 Dec 2014 - Acta Geotechnica (Springer Berlin Heidelberg)

Topics: Compaction

Related papers:

- [Stabilization Mechanisms of Nontraditional Additives](#)
- [Stabilization of Clay Soils with Nontraditional Additives](#)
- [Physicochemical behavior of tropical laterite soil stabilized with non-traditional additive](#)
- [Analysis of strength development in non-traditional liquid additive-stabilized laterite soil from macro- and micro-structural considerations](#)
- [Effects of Xanthan gum biopolymer on soil strengthening](#)

Share this paper:    

View more about this paper here: <https://typeset.io/papers/soil-treatment-with-organic-non-traditional-additives-for-1rf9cmx078>



HAL
open science

Soil treatment with organic non-traditional additives for the improvement of earthworks

Gaëtan Blanck, Olivier Cuisinier, Farimah Masrouri

► To cite this version:

Gaëtan Blanck, Olivier Cuisinier, Farimah Masrouri. Soil treatment with organic non-traditional additives for the improvement of earthworks. *Acta Geotechnica*, Springer Verlag, 2014, 9 (6), pp.1111–1122. 10.1007/s11440-013-0251-6 . hal-01418290

HAL Id: hal-01418290

<https://hal.univ-lorraine.fr/hal-01418290>

Submitted on 5 Jul 2019

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1 Soil treatment with organic non-traditional additives for the improvement of earthworks

2

3 Gaëtan Blanck^{1,2}, Olivier Cuisinier¹, Farimah Masrouri¹

4 ¹ Laboratoire Environnement, Géomécanique & Ouvrages

5 École Nationale Supérieure de Géologie bâtiment E

6 Rue du Doyen Marcel Roubault - B.P. 40

7 F-54501 VANDOEUVRE-LES-NANCY Cedex

8

9 ² Agence de l'Environnement et de la Maîtrise de l'Énergie

10 20, avenue du Grésillé – BP 90406

11 F-49004 ANGERS Cedex 01

12 gaetan.blanck@univ-lorraine.fr

13 Tél : + 33 (0)3 83 59 63 01

14 Fax : + 33 (0)3 83 59 63 00

15

16

17 Abstract

18 The aim of this study was to characterise the technical and environmental implications of
19 non-traditional treatments of a low-plasticity compacted silt ($PI = 14$) and to investigate their
20 actions both at the micro- and macro-structural scales. Three non-traditional additives
21 derived from industrial vegetal by-products were studied. These additives are classified as an
22 acid solution (AS), an enzymatic solution (ES) and calcium lignosulfonate (LS). The first step
23 was to characterise the effects of these treatments on Proctor compaction, bearing capacity,
24 unconfined compressive strength and stiffness. The index properties of the treated samples
25 were also measured to assess changes in the interaction between soil minerals and the
26 additives. These experimental results showed that the 0.002% ES and 2.0% LS treatments
27 were the most effective at improving the soil dry density and allowing the soil to reach
28 optimum density using 3% less water or 25% less compaction energy. In a second step the
29 mechanisms involved by the treatment were investigated. A microscopic study was
30 conducted including scanning electronic microscopy (SEM) and mercury injection porosity
31 (MIP) tests, measurements of the surface tension of non-traditional additives mixed with
32 water completed the study and demonstrated that the ES treatment has the same surfactant
33 properties as sodium dodecyl sulfate, a common surfactant. Compaction tests confirmed that
34 the behaviours of the soil after ES and sodium dodecyl sulfate treatments were similar.

35 Key words: Soil treatment, non-traditional additives, compaction, bearing capacity, surfactant

36

37 **1. INTRODUCTION**

38 In earthworks, sustainable development will play a larger role in future project design and the
39 assessment of technical solutions by contractors. Currently, the reduction of the
40 environmental impact of earthworks is a growing issue. One of the major challenges facing
41 earthworks companies is the need to use a majority of natural materials extracted within the
42 construction site, including materials with very low geotechnical characteristics. The common
43 industry solution is to use lime, cement or fly ash to improve the soil geotechnical properties;
44 however, sustainable development principles also require a reduction in the consumption of
45 water and non-renewable energies as a way to limit greenhouse gas emissions. In this
46 context, soil treatment with various non-traditional additives has been tested. These additives
47 are diverse in nature and some of them derive from the industrial transformation of
48 renewable raw materials. Due to their organic nature, some products are biodegradable.
49 Thus, the treated soils can recover their untreated composition after the end of the
50 biodegradation process. These products are also beneficial due to their efficiency at low
51 dosages, thereby limiting the environmental impact and cost of their use. Various additives
52 have been tested for improving the compaction of dry soils to avoid dust generation and for
53 increasing the durability of uncovered roads [5, 22, 24, 27]. Additionally, additives have been
54 tested to stabilise erodible soils [33]. Mechanical properties, such as the unconfined
55 compressive strength [23, 28] or the swelling potential of plastic soils [11, 19], have also
56 been studied.

57 Tingle and Santoni [28] listed seven non-traditional categories based on the major active
58 component and classified them as salts, acids, enzymes, lignosulfonates, petroleum
59 emulsions, polymers and tree resins. Acids are low pH aqueous solutions containing
60 sulfonated molecules such as naphthalene or limonene [13]. The presence of proteins in
61 enzymatic solutions was confirmed by Velasquez et al. [32]. Lignosulfonates are organic

62 polymers derived from lignin extracted by the sulfite processing of cellulose in the wood-pulp
63 and paper industries. According to Tingle et al. [30], petroleum emulsions contain asphalt or
64 synthetic iso-alkane fluids suspended in emulsions by a surfactant, polymer emulsions
65 contain vinyl acetates or acrylic copolymers and tree resins are diverse emulsified by-
66 products of the timber and paper industries. Nevertheless, many of these products also
67 include secondary additives such as surfactants or ultraviolet inhibitors, which may react with
68 the soil minerals or modify the soil water properties and thus influence the mechanical
69 behaviour of the treated soils [30]. The emphasis of this study was put on non-traditional
70 additives that would lower the environmental impact of soil treatment in the earthworks
71 industry. Therefore, this study focused on the following products which are derived from the
72 transformation of renewable organic matters: acids, enzymes and lignosulfonates. For each
73 of these categories, a review of the literature concerning the effects on geotechnical
74 properties and suspected mechanisms is presented. Then, geotechnical properties such as
75 compaction, bearing capacity, unconfined compressive strength and stiffness were
76 investigated to define the potential application of these treatments. In the last part, the action
77 of the treatments on the microstructure of the soil was studied by performing scanning
78 electronic microscopy (SEM) and mercury injection porosity (MIP) tests to identify the
79 mechanisms involved by the different products.

80 **2. LITERATURE REVIEW**

81 **2a. Acid solutions**

82 Rauch et al. [20] studied the effects of an acid product on the index properties of three pure
83 clay phases (kaolinite, illite and montmorillonite) and two plastic soils. They concluded that
84 the acid treatment had little effect on soil plasticity, swelling potential and shear strength. The
85 authors explained that the observed modifications were induced by initial differences in
86 properties of the compacted samples. Tingle & Santoni [28] and Santoni et al. [23] tested the

87 application of an acid solution to three soils ranging from non-plastic to highly plastic in
88 nature. They found no change in the unconfined compressive strength. The authors
89 determined that the acid treatment had no effect on the compaction properties of the soils.
90 However, another study [21] showed that changes in the compaction properties of acid-
91 treated soils can occur. Scholen [24] reported in situ studies undertaken by the US Forest
92 Service between 1991 and 1993 which tested the addition of acid solutions. In 1995, no
93 particular failure or degradation of the treated sections was reported. Scholen [24] proposed
94 that acidic non-traditional additives act by altering the electrolyte concentration of the pore
95 fluid, thereby reducing the double layer thickness of clay minerals. Cation exchange was also
96 suspected to occur and to flocculate the clay minerals. Moreover, important lowering of the
97 pH of a soil can also lead to the dissolution of clay minerals [26, 36]. For example, to start the
98 dissolution of kaolinite, the pH values have to be lower than 2 [16, 35]. However, the X-ray
99 diffraction, specific surface area and cation exchange capacity were not modified by the
100 treatments, even for dosages as high as 50% [13, 21]. Scanning electron microscope
101 pictures obtained by Katz et al. [13] showed similar structures for the acid-treated and
102 untreated soils. According to the literature, acid solutions modify the compaction and bearing
103 capacity properties of treated soils without modifying the soil mineralogy.

104 **2b. Enzymatic solutions**

105 For enzymatic treatments, Rauch et al. [20, 21] concluded that most of the variations in the
106 Atterberg limits they observed were insignificant compared to the typical variations of such
107 measurements. Unconfined Compressive Strength (UCS) tests of the treated soils
108 demonstrated modifications from -30 to +80%, depending on the product and soil tested [18,
109 28]. Velasquez et al. [32] mentioned an increase in shear strength resistance of 9 to 39% for
110 two enzymatic treatments but detailed analysis of samples properties showed that
111 modifications can be attributed to differences in water content and dry density after

112 treatment. For some enzymatic solutions, limited changes in the compaction references were
113 found [19, 21]. Tingle and Santoni [28] considered that the modifications in the compaction
114 properties after enzymatic treatments were too small to be significant; however, Velasquez et
115 al. [32] mentioned that samples treated with enzymatic solutions achieved a higher density
116 for the same compaction energy. In two of the three field studies reported by Scholen [24],
117 the treated section of uncovered forest roads showed less degradation than untreated
118 sections. Visser [34] performed in situ California Bearing Ratio (CBR) measurements on four
119 soils ranging from sandy to clayey treated with an enzymatic solution. CBR improvement
120 occurred in 4 cases out of 8. For enzymatic treatment, Scholen [24] hypothesised that
121 enzymes bond the organic matter of the soil with clay minerals. These additional bonds
122 should reduce the water affinity of the clay and limit the swelling potential of the soil.
123 However, Harris et al. [11] showed that the 3-D swelling potential of a plastic clay (PI = 51)
124 was not modified by the addition of 0.07% of an ES treatment. Another stabilisation
125 mechanism was suggested by Velasquez et al. [32], who observed that an ES could have
126 surfactant properties and thus stabilise the soil by improving its compaction ability. This
127 property was confirmed by Berney et al. [4] and Park et al. [17], who showed that the dry
128 density of compacted soils is improved by the addition of surfactants. In conclusion, ES
129 seems to induce compaction modifications, but the stabilisation mechanisms of this family of
130 products remain in question.

131 **2b. Lignosulfonates**

132 The addition of lignosulfonates modified the index properties of treated soils in different
133 ways. Lambe [14] showed that small quantities of calcium lignosulfonate (< 0.5%) reduce the
134 liquid limit of a low-plasticity soil. Gow et al. [10] treated a silty sand with 0.25 to 1.0% of
135 lignosulfonate and observed that the plastic limit was reduced when the dosage increased,
136 but no consistent trend was found for the liquid limit. A maximum improvement in the UCS

137 was observed for the addition of 5% of lignosulfonates [23, 28]. Compaction properties were
138 also affected by the treatment. Gow et al. [10] showed that the optimal water content of a
139 compacted soil was reduced and the maximum dry density increased especially for dosages
140 between 0.5 and 1.5%. CBR values measured for each dosage at optimal water content and
141 maximum dry density were improved in comparison to untreated samples but decreased with
142 increased dosages. In situ evaluations of the mechanical performances of the lignosulfonate
143 treatment are limited. Surdahl et al. [27] mentioned a stiffness improvement of a granular soil
144 after treatment. Lignosulfonates are thought to stabilise the soil by coating together its
145 particles [30, 33]. However, lignosulfonates also have surfactant [31] and dispersive
146 properties [14, 25]. Thus, the stabilisation mechanism of lignosulfonates is not yet well
147 understood.

148 In general, soil treatment with non-traditional additives can improve the engineering
149 properties of soils; however, these results vary depending on the tested products, soil nature
150 and at times, the dosages. According to Rauch et al. [20] the variability of the engineering
151 properties may be due to the modification of the optimal density and water content of
152 compacted soils. Thus, as for traditional treatments such as lime or cement, the addition of
153 chemical additives may induce modifications of maximum dry density and optimal water
154 content, which must be determined for accurate field applications. Moreover, the
155 strengthening mechanisms of non-traditional treatments are not yet well understood and
156 where data are available, no correlations between microscopic and macroscopic
157 observations have been established. Therefore, some experiments were conducted to
158 identify the mechanisms of each additive.

159 **3. MATERIALS AND METHODS**

160 **3a. Non-traditional additives**

161 The acid solution (AS) tested in this study was a concentrated solution of sulfuric acid mixed
162 with D-limonene, a by-product of citrus processing. For this kind of products, typical dosages
163 tested in the literature are comprised between 0.01 and 0.2%. As shown by different authors,
164 UCS, compaction and clay mineralogical properties were not affected by dosage increase
165 [13, 21, and 28]. Thus, a dosage of 0.01% of concentrated product by dry weight of soil was
166 tested in this study (Tab. 1).

167 The tested enzymatic solution (ES) is a biodegradable brown aqueous solution with an acidic
168 pH of 4.6. For this type of product, typical dosages are comprised between 0.002% and
169 0.1%. However, according to Tingle & Santoni [28] and Velasquez et al. [32], the
170 geotechnical properties of soils treated with an enzymatic additive were independent of the
171 dosage. Therefore a dosage of 0.002% was selected.

172 The tested lignosulfonate (LS) was a biodegradable, organic, water soluble calcium salt used
173 in powder form. The insoluble components were less than 0.5%, the moisture content was
174 approximately 7% and the reducing sugar content was approximately 7% by dry weight of
175 product. Experimental results indicated an optimal additive content of 5% [23, 28] for
176 improving the UCS. On the other hand, Gow et al. [10] had demonstrated that maximum
177 density and bearing capacity values were obtained for a dosage of 0.5%. For that reason,
178 three dosages (0.5, 2.0 and 5.0%) were tested.

179 The tested surfactant was a powder with a SDS content of more than 95 % by dry weight.
180 The required quantity of SDS for a 0.01% dosage was diluted in distilled water and then
181 added to the soil during mixing operations.

182 **3b Tested soil**

183 A natural fine-graded silt of low plasticity often encountered in earthworks projects in the
184 Paris Basin was tested in this study (Tab. 2). X-ray diffraction investigations indicated that
185 the main minerals were quartz and calcite (8.0% by weight determined by calcimetry). The
186 <2 µm fraction contains quartz and clay minerals (chlorite, illite, kaolinite and smectites) and
187 the sulphur content of the soil was less than 0.02%.

188 Before testing, the soil was dried at 60°C and pulverised to pass through a 2 mm sieve.
189 Depending on the liquid or solid nature of the treatment product, a specific protocol was
190 followed to ensure the application was representative of field application procedures. For the
191 AS and ES treatments, the initial quantity of water was mixed with the dry soil material to
192 achieve a water content 3% lower than the target moisture content for compaction. The
193 samples were placed in a container at 20°C for 24 hours to reach the equilibrium of moisture
194 content. Then, the additive was mixed with the quantity of water required to obtain the total
195 desired water content and added during the mixing operation. For LS treatment, the soil was
196 directly brought to the desired water content and set aside for 24 hours to equilibrate. Finally,
197 the powder was added to the soil during mixing. For all treatments, a curing time of one hour
198 in sealed containers was chosen before conducting further tests.

199

200 **4. ALTERATION OF GEOTECHNICAL CHARACTERISTICS AFTER TREATMENT**

201 **4a. Index properties**

202 The liquid limit (LL) and plastic limit (PL) of the treated soil were determined (Tab. 3). For the
203 AS, ES and SDS treatments, the Atterberg limits were not modified; however, a reduction in
204 the LL and PL occurred after the addition of lignosulfonate (LS) at dosages of 2.0 and 5.0%.
205 Despite these changes in the consistency limits, the plasticity index remained constant for all
206 tested treatments and dosages.

207 **4b. pH**

208 The pH of the treated soil was determined according to ISO 10390 [12]. Measured values
209 showed that the pH of the AS and ES treated soil was not affected despite the acidic features
210 of both products. This phenomenon might be related to the high dilution of the products
211 combined with the increased buffering capacity of the soil due to the presence of calcium
212 carbonate. In contrast, the addition of the LS treatment reduced the pH by approximately one
213 pH unit for the 5.0% dosage. This action is due both to the acidic carboxylic and sulfonate
214 functions of lignosulfonate and to the high dosages.

215 **4c. Compaction**

216 Compaction tests were performed according to ASTM D 698-91 [1] using a standard Proctor
217 test. After compaction, the instant bearing index (IPI) was measured following the same
218 procedure as for the un-soaked Californian bearing ratio (ASTM D 1883-92 [2]) but without
219 placing surcharge weights. A penetration piston of 49.6 mm diameter is used to apply the
220 load on the compacted soil. The penetration rate was 1.27 mm/min. The compaction and
221 instant bearing index curves are plotted in Fig. 1 for AS and ES treated soil. Fig. 2 shows the
222 results for the addition of LS at 0.5, 2.0 and 5.0%. The optimum water content (w_{opt}) and the
223 maximum dry unit weight (γ_{dmax}) for each treatment are summarised in Tab. 4.

224 Fig. 1 shows that for the AS treatment, no changes in the compaction and IPI curves
225 occurred. After ES treatment, the maximum dry unit weight increased and the optimum water
226 content reduced from 18.2 kN/m³ and 15.5% to 18.6 kN/m³ and 14.5%, respectively. On the
227 dry side of the compaction curve, a maximum increase in the dry unit weight of 0.8 kN/m³
228 was measured. This means that the compaction ability of the treated soil was improved over
229 a range of water contents from 8 to 15.5%. The IPI curve was also affected by the treatment
230 and shifted towards lower water contents. Thus, the bearing capacity of the soil was reduced

231 for water contents in the vicinity of w_{opt} . However, the measured IPI at the respective
232 optimum water content for both ES treated and untreated soil were roughly equal (Tab. 4).
233 Fig. 2 shows that the LS treatment increased the dry unit weight and reduced the optimum
234 water content of the soil for the three dosages. A maximum densification was obtained with
235 the addition of 2.0% LS, which corresponded to a reduction of 2% in the optimum water
236 content (13.5% for 2.0% LS treatment as compared to 15.5% for untreated soil). For this
237 same treatment, dry unit weights were increased on the dry side of the compaction curve and
238 γ_{dmax} increased from 18.2 to 18.5 kN/m³. Despite an improvement in density, the addition of
239 lignosulfonate reduced the IPI at constant water content, and the IPI reduced further with
240 higher doses of LS. If the soil was compacted at w_{opt} to reach the maximum dry density, the
241 IPI measured for the 2.0% LS treatment was 14, compared to a value of 15 measured at w_{opt}
242 for the untreated soil (Tab. 4). These results illustrate the importance of considering the
243 entire compaction curve when assessing the effects of ES and LS treatments.

244 After 0.002% ES and 2.0% LS treatments, an increase in dry unit weight and a reduction in
245 w_{opt} were observed, implying that a minimum dry density may be achieved for lower water
246 contents. For example, the γ_{dmax} of untreated soil may be achieved at 3% lower water
247 content. Moreover, both treatments could also reduce the energy needed to compact the soil
248 to a minimum desired density. An estimation of the potential energy savings was made
249 according to the results and is presented on Figs 3 and 4. These graphs show the
250 compaction and bearing capacity curves for the ES and LS treated soil compacted at 100%
251 and 75% of the standard Proctor energy. For samples compacted on the dry side of the
252 compaction curve, the measured dry unit weights were the same as for untreated soil despite
253 the 25% energy reduction. For the ES and LS treatments, however, the bearing capacity of
254 the soil compacted at 75% of the standard Proctor energy was reduced compared to the
255 untreated soil.

256 **4d. Unconfined compressive strength**

257 To study the evolution of the mechanical behaviour of treated soil, UCS values were
258 determined at 7 and 28 days for samples compacted at their respective w_{opt} and γ_{dmax} after
259 treatment (Tab. 4). Three replicate samples were statically compacted in one layer in a
260 cylindrical mould 100 mm high and 50 mm in diameter. Samples were wrapped in a plastic
261 film, covered by an aluminium sheet and stored in a plastic container at 20°C. Geometrical
262 parameters, sample weight and water content were controlled after the sample compaction
263 and just before testing. The results of the UCS tests at 7 and 28 days are presented in Fig. 5.
264 In comparison with the untreated soil, the resistance of the AS and 2.0% LS treated soil was
265 not significantly modified. The UCS of ES treated soil was slightly improved due to a higher
266 maximum dry unit weight obtained after treatment, but the addition of 0.5 and 5.0% of
267 lignosulfonate reduced the unconfined compressive strength by 20 and 50%, respectively.
268 Moreover, UCS values only displayed minor changes as a function of curing time, implying
269 that the treatments mainly have short term effects. For samples compacted at w_{opt} and γ_{dmax}
270 determined for each treatment after 7 days of curing, the mean modulus for untreated, ES
271 and 2.0% LS treated soils were respectively 13, 15 and 22 MPa (Tab. 5). Samples were also
272 compacted at a target water content of 12.5% and a dry unit weight of 18.5 kN/m³. The
273 results showed that only the 2.0% LS treatment significantly reduced the stiffness of the soil.

274 **4e. Swelling potential and hydraulic conductivity**

275 The determination of one dimensional free swell potential of treated soil was carried out on
276 samples of 70 mm diameter and 15 mm thickness statically compacted in oedometric cells at
277 different initial compaction states. The samples were saturated with distilled water.

278 Fig. 6 shows the one dimensional swelling potential ($\Delta H/H_0$) for untreated, 2.0% LS and ES
279 treated samples. For each treatment, at optimal conditions of compaction, the swelling

280 potentials were not significantly modified. Moreover, when the untreated soil was compacted
281 at the same dry density and initial water content than treated samples, the swelling potentials
282 were of the same order of magnitude. Therefore, it could be concluded that the studied
283 products did not significantly alter the swelling potential of the tested soil.

284 After the stabilisation of swelling, the saturated hydraulic conductivities of the samples were
285 determined (Fig. 7). Treated samples compacted at their respective maximum dry densities
286 showed a small decrease of the hydraulic conductivity. For treated and untreated samples on
287 the dry side of the compaction curves, the hydraulic conductivities were very similar.

288 This section showed that the non-traditional additives led to several modifications of the
289 geotechnical behaviour of the tested material. The modifications did not appear to be time-
290 dependant since no significant modification of unconfined compressive strength occurred
291 over the curing period considered. Nevertheless, a key question is the permanence of the
292 improvement brought by these products over a long period of time. In this context, the
293 interaction mechanisms between the soils particles and the additives were investigated.

294 **5. THE STUDY OF INTERACTION MECHANISMS**

295 **5a. Microstructure of compacted soil**

296 The investigation of the microstructure of compacted soil was conducted using a scanning
297 electron microscope equipped with an energy dispersive X-ray spectrometer (EDS). Images
298 obtained by collecting the secondary electrons were taken at different magnifications
299 between 100 and 10,000x. All samples were compacted at their respective optimum water
300 content and maximum dry unit weight. After compaction, they were wrapped in a plastic film,
301 covered by an aluminium sheet and stored in a plastic container at 20°C for 28 days. Then,
302 samples 2 to 3 cm³ in volume were carefully extracted and freeze-dried to remove the water

303 and minimise sample deformation. Fragments of the freeze-dried samples were extracted
304 and coated with gold before the SEM analyses.

305 To study the organisation of the internal structure of the compacted soil, SEM investigations
306 were conducted with mercury injection porosity (MIP) tests. Tests were conducted on freeze-
307 dried samples compacted at the maximum dry density and optimal water content for each
308 treatment following the same procedure as for SEM preparation. The pore size distribution is
309 obtained by derivation of the injected mercury volume (V_{inj}) function. To compare the four
310 samples, the injected volume was normalised such that the surface under the pore size
311 distribution curve was equal to 1. The void ratio investigated by the mercury (e_{inv}) can be
312 defined as the ratio between the injected volume of mercury and the volume of solids. When
313 e_{inv} is equal to e_{tot} , the entire porosity of the sample is filled by mercury. Thus, the calculated
314 e_{inv} (Tab. 6) reveals that the majority of the existing pores in the samples were filled with
315 mercury during MIP tests.

316 Fig. 8 shows the surface of the untreated soil. The mineralogical nature of the bigger grains,
317 generally measuring 10 to 50 μm , was determined by the EDS. These grains were identified
318 to be quartz associated with smaller clay minerals of 1 to 5 μm diameter. No preferential
319 orientations of the clay minerals were detected. MIP results indicated that the pore size of
320 untreated soil presents a uni-modal distribution with a dominant radius of 0.6 μm .

321 Results obtained by SEM showed a slightly more aggregated structure and a face to edge
322 organisation of clay minerals for the soil treated with 0.01% AS (Fig. 9). Individual clay
323 minerals are less visible but inter-aggregates pores size remained similar after treatment as
324 confirmed by MIP data (Figs 12 and 13). Therefore, the structure of the treated soil was not
325 significantly altered in this case.

326 After 0.002% ES treatment, the same structure as for the untreated soil is observed from the
327 SEM images (Fig. 10). The MIP study (Fig. 12) showed that less mercury was injected in the
328 ES treated sample. This phenomenon is linked with the higher dry unit weight of the ES
329 treated sample, which reduced its total void ratio (e_{tot}) and thus the total injected volume
330 (V_{inj}). This result is associated to a reduction of the amount of pores comprised between
331 3 and 10 μm (Fig. 13).

332 Fig. 11 shows the soil after the addition of 2.0% of lignosulfonate. In the picture, additional
333 structures can be observed. These structures resemble fibres and are probably
334 lignosulfonate associations forming a network between the soil minerals (arrows). Point 1 on
335 Fig. 11 was identified by the EDS to be a clay mineral, but as the fibres were too small to be
336 analysed by the EDS, their exact nature is unknown. The SEM results also showed larger
337 inter-aggregates pores, large clay minerals were organised in face to face structures
338 orientated in the plane of the picture. Compared to untreated samples, MIP results confirmed
339 the increase of the frequency of pores having radii between 0.3 and 5 μm and also showed a
340 reduction of pores with a radius $<0.3 \mu\text{m}$. The increase in larger pores radius might be
341 caused by aggregation of clay mineral and dispersion of the created structure due to
342 adsorption of lignosulfonates molecules. The reduction in intra-aggregates pores may be
343 explained by the clogging of the smallest pores by lignosulfonates.

344 **5b. Comparison of the treatment additives with a common surfactant**

345 Some authors, for example, Velasquez et al. [32] demonstrated that enzymatic solutions
346 could have surfactant properties. As enzymatic solutions, lignosulfonates also have
347 surfactant properties, which could alter the mechanical behaviour of soils [10, 31]. To
348 determine if the tested non-traditional additives have surfactant properties, the surface
349 tension was measured using the Du Noüy ring method [9]. The results were compared with

350 the surface tensions obtained for aqueous solutions of sodium dodecyl sulfate (SDS)
351 (Fig. 14).

352 Similar to SDS, low dosages of the enzymatic solution reduced the surface tension of the
353 water. At a concentration of 1.0 g/L the surface tension was reduced by more than 50%.
354 Lignosulfonate also exhibited surfactant properties, but the additive was less efficient in
355 reducing the surface tension of the solution. At higher concentrations, the surface tension of
356 the LS solution stabilised approximately 42 mN/m. Only the acid additive did not exhibit any
357 surfactant properties.

358 To study the influence of the addition of a surfactant on the compaction behaviour, 0.01% of
359 SDS by dry matter weight was added to the soil (Fig. 15). The required quantity of SDS was
360 first diluted in water, and the same protocol used for liquid non-traditional treatments was
361 followed. The resulting compaction and IPI curves were compared to those obtained after the
362 ES treatment.

363 With regard to the ES treatment, the SDS addition improved the dry unit weight on the dry
364 side of the compaction curve. The IPI curve for the SDS-treated soil was also slightly shifted
365 towards smaller water contents as was observed after the ES-treatment. Thus, the SDS and
366 ES treatments have a similar effect on the mechanical behaviour of soils. This finding implies
367 that both products may utilise the same stabilisation mechanism. Indeed, the reduction of the
368 surface tension of the soil's interstitial water should lower the matrix suction according to the
369 Jurin law.

370 The suction of the treated soil was investigated for the three non-traditional treatments. The
371 filter paper methodology was used to measure matrix suction of compacted soil according to
372 ASTM D 5298-94 [3]. After compaction of two 70 mm diameter for 15 mm thickness samples,
373 three filter papers were inserted between each sample. Thereafter, the samples were kept in

374 sealed container for 7 days to achieve the suction equilibrium. As the calibration curve of the
375 filter paper was known, the measurement of its water content gave the matrix suction of the
376 soil.

377 The results showed that the acid solution (AS) did not change the suction of the soil. This is
378 consistent with the absence of surfactant features of the additive.

379 As ES treatment has surfactant properties, a reduction of the suction could be expected. In
380 this work, the addition of the enzymatic solution (ES) did not lead to suction modifications
381 (Tab. 7). This can be explained by the biodegradability of the additive. An equilibrium period
382 of seven days may allow the additive to be totally degraded before suction measurements.

383 The LS treatment led to an increase in the matrix suction of the soil. As LS is an organic
384 calcium salt, the increase of the suction might be explained by the hygroscopic nature of
385 lignosulfonates.

386 **6. DISCUSSIONS**

387 Herein, the effects, mechanisms and applications of the three studied treatments are
388 discussed.

389 AS treatment did not change geotechnical properties of the soil but small modifications in the
390 clay minerals organisation were observed in SEM pictures (Fig 9). The observed
391 modifications could be due to changes in the ionic composition of the pore fluid after addition
392 of the product since this parameter is known to induce fabric changes according to the
393 literature [6-8, 15, 16]. No particular application was evidenced for AS treatment of the
394 studied soil.

395 Treatment with ES demonstrated an increase in the compaction ability of the soil. The
396 increase in maximum dry density induced small modifications of the UCS, stiffness, swelling

397 potential and permeability of the soil. Moreover, the microstructure of the soil was not
398 modified. Therefore, it can be concluded that the observed hydro-mechanical modifications
399 are mostly related to the effect of treatment on compaction behaviour of the soil. This
400 hypothesis was confirmed by the absence of pH and index properties changes. As shown on
401 the Fig. 15, the compaction behaviour of the ES treated soil is similar to the behaviour
402 observed after a treatment with a surfactant. Results shown on Fig. 3 indicated that treated
403 soil had a smaller bearing capacity than the untreated soil at given water content and dry
404 density. This phenomenon may be explained by the surfactant properties of the ES. Strong
405 modifications of the surface tension for low additive dosages may also explain why the
406 compaction ability of the ES treated soil was improved despite a low dosage (0,002%). As
407 the enzymatic solution is biodegradable, the product has disappeared in a few days. During
408 the degradation stage of the ES product, increase in bearing capacity may be expected and
409 after degradation of the additive, no long term modifications are expected beyond those
410 caused by the initial densification. According to the experimental results, the ES treatment
411 can be used to increase the compaction ability on the dry side of the compaction curve and
412 thus compact the soil at higher densities for lower water contents.

413 LS treatment reduced the pH and modified the pore-fluid composition, thus, the organisation
414 and interactions between soil particles were changed as shown by mechanical results and
415 SEM pictures. Experimental results showed dosage dependent effects on geotechnical
416 characteristics. The 2% amount of lignosulfonate added to the soil also reduced the stiffness
417 and the index properties. This observation is consistent with dispersive properties of
418 lignosulfonates which tend to increase repulsive interactions between soil constituents [5, 14,
419 25]. LS treatment also reduced the friction between the grains of the soil, which facilitate its
420 deformation under loading, and thus explain the observed reduction in bearing capacity
421 (Figs. 2 and 4). However, surfactant properties and suction modification after treatment
422 cannot explain alone why the bearing capacity was reduced by an increase in the

423 lignosulfonate dosage (Fig. 2). This observation is probably due to the formation of an
424 organic film increasing lubrication between the particles after the addition of lignosulfonate
425 [9]. An increase in dosage led to thicker films, reducing the bearing capacity of the LS treated
426 soil by facilitating the deformation under loading. As for ES, addition of the product modified
427 the behaviour of the soil during the compaction. Nevertheless, field and laboratory testing
428 confirmed the ability of lignosulfonate to be leached out of the soil [11, 22, 27]. So, it is to be
429 expected that the soil will recover its initial characteristics after a certain period of time. The
430 uses of LS treatment are similar to those of ES but higher dosages are needed and attention
431 must be paid on bearing capacity which is altered by the treatment.

432 **7. CONCLUSION**

433 This paper presented an experimental multi-scale study of a low-plasticity soil treated with
434 three non-traditional organic products classified as an acid solution, an enzymatic solution
435 and lignosulfonate. Hydro-mechanical investigations including compaction, bearing capacity,
436 UCS, free swelling and hydraulic conductivity tests were conducted. The effect of the
437 treatments on the microstructure of the compacted soil was investigated using SEM and MIP
438 tests. The study also proposed a reflexion on the modification of the interactions between soil
439 particles induced by the treatments. The following conclusions can be drawn based on the
440 obtained results.

- 441 - To evaluate the performances of non-traditional products used for soil treatment, it is
442 important to consider the entire compaction and bearing capacity curves and not only
443 the values obtained at the optimal conditions. In fact, the water content of compacted
444 soil has a strong influence on the dry unit weight obtained after treatment.
- 445 - The ES and LS treatments reduced the optimal water content and increased the dry
446 density of the compacted soil allowing the use of 3% lower water content and a 25%

447 reduction in the compaction energy, required to achieve the same density when
448 compared to untreated soil. Therefore, the treatments can improve the environmental
449 impact of earthwork projects and are particularly well suited for dry soil compaction in
450 areas where the access to water resources is limited.

451 - Before in situ applications, careful laboratory investigations should be conducted to
452 determine if the treatment genuinely improves the soil behaviour; some non-
453 traditional products have little or no impact on the mechanical properties of treated
454 soils. The changes in compaction parameters must be characterised to determine the
455 optimal application conditions in terms of dosage, desired water content and bearing
456 capacity.

457 - Treatments with organic products have showed immediate modification of the
458 compaction parameters; however, no evolution of the resistance of the soil over time
459 was observed. Thus, treatments essentially act through a physical modification of the
460 soil behaviour. Moreover, as AS and ES were added at low dosages and were
461 biodegradable, intrinsic characteristics of the soil are not changed and the long term
462 behaviour of the soil should not be modified. For LS treatment, leaching of the
463 additive can be expected in case of water transfer in the compacted structure.

464 - Some non-traditional products act like surfactants. This property appears to be an
465 important parameter of the effectiveness of non-traditional products when they are
466 used as compaction aids.

467 **ACKNOWLEDGMENTS**

468 The research presented in this paper was funded by the French Environment and Energy
469 Management Agency (ADEME), Egis Géotechnique and DTP Terrassement.

470

471 **REFERENCES**

- 472 1. ASTM D 698-91 (1991) Test method for laboratory compaction characteristics of soil
473 using standard effort.
- 474 2. ASTM D 1883-92 (1992) Standard test method for CBR (Californian Bearing Ratio) of
475 laboratory-compacted soils.
- 476 3. ASTM D 5298-94 (1995) Standard test method for measurement of soil potential
477 (suction) using filter paper.
- 478 4. Berney ES IV, Peters JF, Newman JK, Smith DM (2003) Effect of surfactant on the
479 dry-side compaction of silty sand. *J Transp Res Board* 1819:57-62.
- 480 5. Bolander P, (1999) Laboratory testing of nontraditional additives for stabilization of
481 roads and trail surfaces. *Transp Res Record: J Transp Res Board* 1652:24–31.
- 482 6. Chen J, Anandarajah A, Inyang H (2000) Pore fluid properties and compressibility of
483 kaolinite. *J Geotech and Geoenvironmental Eng* 126(9):798-807
- 484 7. Di Maio C, Santoli L, Schiavone P (2004) Volume change behaviour of clays: the
485 influence of mineral composition, pore fluid composition and stress state. *Mech of*
486 *Mater* 36:435-451
- 487 8. Dong X, Wang Y-H (2008) The effects of the pH-influenced structure on the dielectric
488 properties of kaolinite-water mixtures. *Soil Sci Soc Am J* 72:1532-1541
- 489 9. Du Noüy PL, (1919) A new apparatus for measuring surface tension. *J Gen*
490 *Physiology*, 1(5):521-524

- 491 10. Gow AJ, Davidson DT, Sheeler JB (1961) Relative effects of chlorides,
492 lignosulfonates and molasses on properties of a soil-aggregate mix. Highw Res board
493 Bul, 282:66–83
- 494 11. Harris P, Holdt Jv, Sebesta S, Scullion T (2006) Recommendations for stabilization of
495 high-sulfate soils in Texas. Transp Res Record: J Transp Res Board 1952:71–79
- 496 12. ISO 10390 (2005) Soil quality – Determination of pH
- 497 13. Katz LE, Rauch AF, Liljestrang HM, Harmon JS, Shaw KS, Albers H (2001)
498 Mechanisms of soil stabilization with liquid ionic stabilizer. Transp Res Record: J
499 Transp Res Board 1757:50–57
- 500 14. Lambe TW (1956) Improvement of soil properties with dispersants. Boston Soc Civil
501 Eng J, 41(2):184-207
- 502 15. Mitchell JK (1993) Fundamentals of soil behavior. John Wiley & Sons, New York
- 503 16. Palomino AM, Santamarina C (2005) Fabric map for kaolinite: effects of pH and ionic
504 concentration on behavior. Clays and Clay Minerals 53(3):211-223
- 505 17. Park J, Vipulanandan C, Kim J, Myoung Hak Oh (2006) Effects of surfactants and
506 electrolyte solutions on the properties of soil. Environ Geology 49(7):213-220
- 507 18. Parsons RL, Milburn JP (2003) Engineering Behavior of Stabilized Soils. Transp Res
508 Record : J Transp Res Board 1837:20–29
- 509 19. Rajendran D, Lytton RL (1997) Reduction of sulfate swell in expansive clay subgrade
510 in the Dallas district. Res Rep TX-98/3929-1, Texas Transportation Institute, College
511 Station

- 512 20. Rauch AF, Harmon JS, Katz LE, HM Liljestrand (2002) Measured effects of liquid soil
513 stabilizers on engineering properties of clay. Transp Res Record: J Transp Res Board
514 1787:33–41
- 515 21. Rauch AF, Katz LE, Liljestrand HM (2003) An analysis of the mechanisms and
516 efficacy of three liquid chemical soil stabilizers: volume 1. Rep FHWA/TX-03/1993-1,
517 Center for transportation research, University of Texas, Austin
- 518 22. Sanders TG, Addo JQ (1993) Effectiveness and environmental impact of road dust
519 suppressants. Dep of Civ Eng, Colorado State University.
- 520 23. Santoni RL, Tingle JS, Webster SL (2002) Stabilization of silty sand with
521 nontraditional additives. Transp Res Record: J Transp Res Board, 1787:61–70
- 522 24. Scholen DE (1995) Stabilizer mechanisms in nonstandard stabilizers. Conf Proc 6: 6th
523 Int Conf on Low-Volume Roads, Vol.2, TRB Natl Res Council, Washington, D.C.,
524 pp. 252–260
- 525 25. Sjöström E., (1993), “Wood chemistry, fundamentals and applications” second ed,
526 293 p.
- 527 26. Sokolovich VE (1973) Acid as chemical stabilizers of clay soils. Scientific Research
528 Institute of Foundations, 4:22-23
- 529 27. Surdahl RW, Woll JH, Marquez HR (2007) Stabilization and dust control at the
530 Buenos Aires national wildlife refuge, Arizona. Transp Res Record: J Transp Res
531 Board 1989:312 – 321
- 532 28. Tingle JS, Santoni RL (2003) Stabilization of clay soils with nontraditional additives.
533 Transp Res Record: J Transp Res Board 1819:72–84

- 534 29. Tingle JS, Larson SL, Weiss CA, Newman JK, Peters JF, Tardy B, Berney ES (2004)
535 Constitutive analyses of nontraditional stabilization additives. Technical Report ERDC
536 TR-04-5, US Army Engineer Research and Development Center, Vicksburg
- 537 30. Tingle JS, Newman JK, Larson SL, Weiss CA, Rushing JF (2007) Stabilization
538 mechanisms of nontraditional additives. Transp Res Record: J Transp Res Board
539 1989:59–67
- 540 31. Trufanova MV, Parfenova LN, Yarygina ON (2010) Surfactant properties of
541 lignosulfonates. Russ J Appl Chem 83(6):1096–1098
- 542 32. Velasquez RA, Marasteanu MO, Holzalski RM (2006) Investigation of the
543 effectiveness and mechanisms of enzyme products for subgrade stabilization. Int J
544 Pavement Eng 7(3):213–220
- 545 33. Vinod JS, Indraratna B, Mahamud MAA (2010) Stabilisation of an erodible soil using
546 a chemical admixture. Proc Inst Civil Eng: Ground Improvement 163:43-51
- 547 34. Visser AT (2007) Procedure for evaluating stabilization of road materials with
548 nontraditional stabilizers. J Transp Res Board 1989:21–26
- 549 35. Wieland E, Stumm W (1992) Dissolution kinetics of kaolinite in acidic solutions at
550 25°C. Geochimica et Cosmochimica Acta 56:3339-3355
- 551 36. Yeoh NS, Oades JM (1981) Properties of soils and clays after acid treatment. I Clay
552 Minerals. Aust J Soil Res 18(19):147-158
- 553

1 **Tab. 1** Dosages tested for the three non-traditional additives

2

Non-traditional additives	Dosages by dry weight of soil
Acid solution (AS)	0.01%
Enzymatic solution (ES)	0.002%
Calcium lignosulfonate (LS)	0.5 ; 2.0 and 5.0%

3

4

5 **Tab. 2** Properties of the tested soil

6

Property	Low plastic clay
Passing 2 mm (%)	100
Passing 80 µm (%)	87
Passing 2 µm (%)	19
Specific gravity	2.67
Liquid limit (%)	34
Plastic limit (%)	20
Plasticity index	14
pH	9.2

7

8

9 **Tab. 3** Index properties and pH of the treated soil

10

Treatment	pH (+/- 0.1)	PL (%)	LL (%)	PI
Untreated	9.2	20	34	14
0.01% AS	9.2	19	33	14
0.002% ES	9.3	19	33	14
0.5% LS	8.8	19	32	13
2.0% LS	8.4	17	30	13
5.0% LS	8.1	13	27	14
0.01% SDS	9.1	19	34	15

11

12

13

14 **Tab. 4** Geotechnical properties of the treated soil

15

Treatment	w_{opt} (%)	γ_{dmax} (kN/m ³)	IPI at w_{opt}	UCS (MPa)	
				7 days	28 days
Untreated	15.5	18.2	15	0.44	0.46
0.01% AS	15.0	18.3	19	0.40	0.41
0.002% ES	14.5	18.6	14	0.53	0.54
0.5% LS	15.0	18.4	13	0.36	0.40
2.0% LS	13.5	18.5	14	0.45	0.49
5.0% LS	14.0	18.3	5	0.22	0.24

16

17

18

19 **Tab. 5** Deformation modulus at 50% of maximal strength

20

Treatment	w (%)	γ_d (kN/m ³)	E ₅₀ (MPa)	Standard deviation (MPa)
Untreated	15.0	18.2	13	2
	12.5	18.4	56	7
0.002% ES	14.0	18.5	15	1
	12.5	18.3	50	4
2.0% LS	12.7	18.5	22	2

21

22

23

24 **Tab. 6** Total void ratio for the compacted samples and calculated mercury investigated
25 maximum void ratio during the MIP tests

26

Treatment	e_{tot}	e_{inv}	γ_d (kN/m ³)
Untreated	0.47	0.44	18.3
0.01% AS	0.46	0.44	18.3
0.002% ES	0.43	0.42	18.7
2.0% LS	0.44	0.41	18.6

27


28

29 **Tab. 7** Matrix suction of treated soil

30

Treatment	w (%)	γ_d (kN/m ³)	Matrix suction (kPa)
Untreated	14.7	18.0	56
0.01% AS	15.4	18.0	54
0.002% ES	14.7	18.2	58
2.0% LS	15.2	18.2	225

31




1

2 **Fig. 1** Compaction and IPI curves for the untreated, 0.01% AS and 0.002% ES treated soil

3

4

5




6

7 **Fig. 2** Compaction and IPI curves for the LS treatment at 0.5, 2.0 and 5.0%

8

9

10




12

13 **Fig. 3** Compaction and IPI curves of the ES treatment at 75 and 100% of the standard
 14 Proctor energy

15

16




17

18 **Fig. 4** Compaction and IPI curves of the 2.0% LS treatment at 75% and 100% of the
 19 standard Proctor energy

20

21


22



23

24 **Fig. 5** Unconfined compressive strength at 7 and 28 days for the studied non-traditional
 25 treatments compacted at their respective optimum Proctor

26




27

28 **Fig. 6** One-dimensional free swelling potential for the ES and LS treatments at different initial
 29 compaction states

30

31




33


34 **Fig. 7** Hydraulic conductivity coefficient for the ES and LS treatments in different initial
 35 compaction states

36

37




40 **Fig. 8** SEM image of the untreated soil



45 **Fig. 9** SEM image of the 0.01% AS treated soil

47



48


49 **Fig. 10** SEM image of the 0.002% ES treated soil

50

51

52

53




54


55 **Fig. 11** SEM image of the 2% LS treated soil

56

57



60 **Fig.12** Injection curves for the untreated, 0.01% AS, 0.002% ES and 2.0% LS treated soil




63

64 **Fig. 13** Pore size distribution for the untreated, 0.01% AS, 0.002% ES and 2.0% LS treated

65 soil

66

67




68

69 **Fig. 14** Surface tension of the three non-traditional additives and SDS in aqueous solution

70

71

72



73

74 **Fig. 15** Compaction and IPI curves for 0.01% SDS and 0.002% ES treated soil

75

76