Portland State University

PDXScholar

Civil and Environmental Engineering Faculty Publications and Presentations

Civil and Environmental Engineering

2019

A Study of Sidewalk Autonomous Delivery Robots and Their Potential Impacts on Freight Efficiency and Travel

Dylan Jennings
Portland State University

Miguel A. Figliozzi Portland State University, figliozzi@pdx.edu

Follow this and additional works at: https://pdxscholar.library.pdx.edu/cengin_fac

Part of the Science and Technology Policy Commons, Technology and Innovation Commons, and the Transportation Commons

Let us know how access to this document benefits you.

Citation Details

Jennings, D., and Figliozzi, M. (2019). A Study of Sidewalk Autonomous Delivery Robots and Their Potential Impacts on Freight Efficiency and Travel, Forthcoming 2019 Transportation Research Record.

This Pre-Print is brought to you for free and open access. It has been accepted for inclusion in Civil and Environmental Engineering Faculty Publications and Presentations by an authorized administrator of PDXScholar. Please contact us if we can make this document more accessible: pdxscholar@pdx.edu.

1	A STUDY OF SIDEWALK AUTONOMOUS DELIVERY ROBOTS AND THEIR
2	POTENTIAL IMPACTS ON FREIGHT EFFICIENCY AND TRAVEL
3	
4	
5	
6	Dylan Jennings (1)
7	Student Researcher
8	Transportation Technology and People (TTP) Lab
9	Department of Civil and Environmental Engineering
10	Portland State University
11	PO Box 751—CEE
12	Portland, OR 97207-0751
13	Email: dwj@pdx.edu
14	
15	
16	Miguel Figliozzi (D)
17	Director Transportation Technology and People (TTP) Lab
18	Department of Civil and Environmental Engineering
19	Portland State University
20	PO Box 751—CEE
21	Portland, OR 97207-0751
22	Phone: 503-725-4282
23	Fax: 503-725-5950
24	Email: <u>figliozzi@pdx.edu</u>
25	
26	
27	
28	
29	Please reference as:
30	
31	Jennings, D., and Figliozzi, M. (2019). A Study of Sidewalk Autonomous Delivery Robots and Their
32	Potential Impacts on Freight Efficiency and Travel, Forthcoming 2019 Transportation Research
33	Record.

ABSTRACT

1

2 E-Commerce and package deliveries are growing at a fast pace and there is an increased demand 3 for same-day deliveries. Established delivery companies and new startups are investing in 4 technologies that reduce delivery times and/or increase delivery drivers' productivity. In this 5 context, the adoption of Sidewalk Automated (or Autonomous) Delivery Robots (SADRs) has a 6 growing appeal. SADRs are pedestrian sized robots that deliver items to customers without the 7 intervention of a delivery person. Since SADRs travel on sidewalks they have been the subject of 8 increasing regulation by local agencies in the US. The three research questions that guide this 9 research effort are: (a) What are the limitations imposed by existing regulations in the US, (b) 10 What are the technical capabilities of existing SADRs, and (c) Given the existing capabilities and regulations, what are the time/cost savings and efficiencies that SADRs can bring about? The 11 12 first part of the research discusses current US regulations on SADRs and reviews existing SADR 13 devices and their capabilities. Building on this knowledge, the second half of the research 14 presents a novel model to estimate delivery time and number of customers served utilizing a 15 combination of SADRs and a special delivery van. These results are compared with a baseline 16 (or prevailing) delivery system utilizing only a conventional delivery van-human driver. Results, insights, and potential implications are discussed. The results show that SADRs can provide 17 substantial cost and time savings in some scenarios. Furthermore, the introduction of SADRs 18 19 may significantly reduce on road travel per package delivered.

20 21

22

Keywords: Last mile, delivery, robot, sidewalk, regulation, cost, time, travel, efficiency

INTRODUCTION

According to the United States Census Bureau's Quarterly E-Commerce Report (1), E-Commerce sales in the United States (US) have increased at an average annual rate of 16% in the past two decades. Considering that the amount of time people deem acceptable for delivery times is shortening (2) and E-Commerce sales are consistently increasing, delivery companies are likely to invest in technologies that increase delivery drivers' productivity. Sidewalk Automated,

or Autonomous, Delivery Robots (SADRs) are one of these potential technologies and the focus of this research.

SADRs are pedestrian sized robots that deliver items to customers without the intervention of a delivery person. Since SADRs travel on sidewalks, they have been the subject of increasing regulation by local agencies. The three research questions that guide this research effort are: (a) What are the limitations imposed by existing regulations in the US, (b) What are the technical capabilities of existing SADRs, and (c) Given the existing capabilities and regulations, what are the time/cost efficiencies and savings that SADRs can bring about? Regarding (a), the regulatory review is limited to the US. A global review, though important, is outside the scope of the paper and left as a research task for future research efforts that focus mainly on the regulatory aspects of this new technology.

In the first half of this paper current SADR regulations are discussed as well as a review of current SADR devices and their capabilities. In the second half of this paper a model to study the impact of SADRs in terms of time, cost, and distance traveled is proposed. The research ends with discussion of the results and conclusions. Next section presents the necessary (yet brief) historical background of SADRs and their applications.

BACKGROUND

There are scant academic publications studying SADRs in a delivery context. For example, there is some research about SADRs optimal wayfinding or optimizing the joint scheduling of both trucks and SADRs (3). There are numerous studies related to the mechanical, electrical, or computing design of robots in general. However, as of November 1, 2018 performing a Google Scholar search for the words "Autonomous Delivery Robot characteristics", "Autonomous Delivery Robot regulation", "Sidewalk Delivery Robot", and "Autonomous Delivery Robot efficiency," no published or unpublished research addressing SADRs characteristics, regulation, and relative efficiency was found.

The only publication that is directly related to the topic of this research was authored by Vleeshouwer, Duin, and Verbraeck (4). These authors utilize simulations to study a small bakery robot delivery service. Results show that costs can be reduced significantly but that the occupation of the robot capacity is low and that in the studied scenario robots are not economically feasible. The authors suggest that robots can be feasible if companies scale up or cooperate to increase robot utilization.

Currently, SADRs are mostly used for take-out food deliveries. In March of 2016, Domino's Pizza Inc., a pizza restaurant chain headquartered in the US, unveiled what it claimed to be the world's first autonomous pizza delivery vehicle. The vehicle was nicknamed "DRU" or Domino's Robotic Unit (5). This would be the first of several companies announcing a delivery robot to operate on sidewalks. Starship Technologies, founded in 2014, launched their 40-pound delivery robot in March of 2016 in London and has partnered with Domino's to deliver pizzas (6). At the end of April of 2018, Starship Technologies announced that it will be rolling out its delivery robot services to corporate and academic campuses in the US and Europe. Starship

1 Technologies has already implemented their delivery services at the Intuit campus in Mountain

- 2 View, California, where average delivery times to customers are less than 15 minutes (7).
- 3 Dispatch, a startup company based in San Francisco, announced in April 2016 that it had been
- 4 working on automatic delivery robots since 2015 and had recently received a \$2 million
- 5 investment to continue to expand the company (8). In April of 2017, another San Francisco
- 6 based company called Marble, partnering with Yelp and Eat24, announced that it would be

7 testing its delivery robot (9). In September of 2017, Thyssenkrupp announced that it would

partner with TeleRetail to research the use of delivery robots (10). There are several companies

trying to use SADRs for delivering parcels to customers. Starship Technologies (11) and

Dispatch (12) both have plans to enable the use of SADRs for parcel delivery in the future.

SADRs benefits could include cheaper costs of delivery and faster service, however, there are safety concerns. For example, Norman Yee, the San Francisco City Supervisor, says that SADRs pose a threat to "seniors, children, [and] people with disabilities [who] can't maneuver quickly" (13). Yee also states that he is "trying to prevent some of the things that we did not prevent with other innovations," referring to the abundance of Uber and Lyft drivers in San Francisco causing traffic jams (14). Robert O'Sullivan, the San Francisco police commander, also has concerns about the safety of SADRs, commenting that "if hit by a car, they also have the potential of becoming a deadly projectile" (15). Several community groups in San Francisco have also spoken against SADRs, including the Senior and Disability Action group and Walk SF. "The sidewalks are for walking. That's why they're called side walks," stated the interim executive director of Walk SF (16).

While lawmakers like Norman Yee might dislike the idea of SADRs using sidewalks, Starship Technologies claims that most pedestrians do not mind the robots. In fact, Starship notes that 70% of pedestrians do not pay any attention to the robots, and most of the rest of street-goers react positively to the robots (17). Additionally, Starship Technologies claims that over the tens of thousands of miles of sidewalks their SADRs have travelled, meeting millions of people, there have been zero accidents (15).

There are opposing views regarding SADR deployments and/or utilization on public spaces, hence, regulation is likely to be a key factor that hinders or promotes the utilization of SADRs. Next section discusses the current regulatory environment in the US.

REGULATORY ENVIRONMENT AND SADRS IN THE US

The regulatory review is limited to the US. A global review is outside the scope of the paper and left as a research task for future research efforts that focus just on the regulatory aspects of this new technology. SADRs are still a novel and not widely used technology; only a few states and cities have regulations in place. In alphabetical order, the states which have implemented regulations: Arizona; Florida; Idaho; Ohio; Utah; Virginia; and Wisconsin. Additionally, several cities have adopted regulations: Austin, Texas; San Francisco, California; and Washington DC.

San Francisco is one of the most restrictive places with regulations on SADRs; it requires not only a speed and weight limit, but also requires a permit for each device, with a limit of nine Autonomous Delivery Device permits for the city overall. These permits are valid for up to 180 days, and no more than one permit may be held by one permittee. San Francisco is currently the only place to require permits for SADRs. The device is also required to emit a warning noise to notify pedestrians and cyclists that the device is nearby. Interestingly, despite all the other regulations San Francisco has on SADRs, there is no weight limit for SADRs in San Francisco.

- 1 While San Francisco might be the most restrictive place for SADRs in the US, Arizona might be
- 2 the least restrictive. Like San Francisco, Arizona does not have a defined weight limit for
- 3 SADRs. Arizona requires only that the vehicle is electric, travels at less than 10 mph (16 kph), is
- 4 actively controlled or monitored, follows pedestrian laws, and yields to pedestrians. Arizona
- 5 does not require insurance policies, braking systems, headlight systems, contact information, or a
- 6 serial number plate, as many other places do. A summary of some key regulatory aspects are 7

included in Table 1.

8 9

[TABLE 1]

10 11

Size and Weight Limits

- 12 Washington DC and Florida have unloaded weight limits of 50 pounds. The 50-pound limit
- 13 restricts SADR companies, as many SADRs weigh more than 50 pounds. Starship Technologies'
- 14 SADR weighs 40 pounds unloaded, which provides a competitive advantage in locations with
- 15 low weight limit (18). Other places such as Wisconsin, Ohio, and Idaho have less strict
- 16 regulations, with unloaded weight limits of 80 to 90 pounds. Finally, there are other places where
- 17 weight limitations allow essentially all SADRs currently on the market. These include Utah, with
- 18 an unloaded 150-pound limit, Austin, Texas, with an unloaded 300-pound limit, and Arizona and
- 19 San Francisco, California, with no weight limits.

20 21

Speed Limits

- 22 Almost all places have a speed limit for SADRs of 10 miles per hour, the exception being San
- 23 Francisco with a speed limit of 3 miles per hour.

24 25

SADR Characteristics

- 26 An extensive initial internet search by the authors in March 2018 found that five companies most
- 27 prominently covered in the news as SADR makers. Among them Starship Technologies has
- 28 received ample media coverage, as they are the most widespread SADR company as of
- 29 November 1, 2018. Robby and KiwiBot are two additional SADR companies that have surfaced
- 30 the news since March 2018 (19, 20), however, there is not yet enough information about their
- specifications. Table 2 compares the five SADRs initially found, which lists details found from 31
- 32 various journal sources online about each SADR. Journalists interviewing the companies
- 33 gathered most of the information contained in Table 2.

34 35

[TABLE 2]

36 37 38

METHODOLOGY

39 The efficiency of SADRs will be analyzed utilizing continuous approximations. The notation 40 used is summarized below.

- 42 n =Number of customers served
- 43 l(n) = Average distance a vehicle travels to serve n customers
- 44 k_1 = Routing parameter representing non-Euclidean travel on sidewalks and roads
- 45 ψ = Overlapping factor among SADR service areas
- 46 a =Area of service area where n customers reside

- m = Number of van tours necessary to serve n customers
- d = Distance between the depot and the geometric center of the service area
- 3 r =Radius of the service area
- τ = Total van time necessary to make n deliveries
- s =Average speed of the vehicle
- t_0 = Time it takes to wait for the customer to pick up their order from the vehicle
- t_u = Time it takes the vehicle and/or driver to unload the delivery

When considering how to quantify the efficiency of a SADR, or any transportation vehicle, one of the key numbers to consider is the total distance the vehicle has to travel to make a delivery, or multiple deliveries. The average distance l(n) can be estimated as a function of customer density, number of vehicles, network characteristics and route constraint coefficients, and the distance between the depot and the delivery area (21). The equation used in this paper to calculate the distance traveled to visit n customers is:

$$l(n) = 2md + k_l \sqrt{an} \tag{1}$$

In equation (1), d represents the average distance from the depot or distribution center (DC) to the customer(s) multiplied by two, the number of times the vehicle goes to and from the service or delivery area (SA); k_l is a constant value representing routing constraints in the SA. The service area where customers are located is represented by a. The number of customers or stops is represented by n. For ease of notation and calculations, a circular SADR service area is assumed but the method described herein can be used with other SA shapes. As cities are generally rectangular rather than circular, the k_l routing constraint constant adjusts for this and it is assumed a Manhattan or L2 norm (21).

Taking equation (1) and solving for a results in a formula that can be used to determine the average area a SADR could cover given the maximum l(n) (vehicle range) is known. Assuming a circular service area, the radius r of the SA that a vehicle (or SADR) could serve from the center of the SA is found utilizing equation (2).

$$r = \sqrt{\frac{(l(n) - 2md)^2}{k_l^2 \pi n}} \tag{2}$$

When the DC is located in the center of the SA, and there is no long-haul distance (d=0), the previous equations can be simplified.

Another important number to consider when dealing with last mile deliveries is the time it takes to make n deliveries. A formula to calculate the route duration time accounting not only for driving time but also waiting for the customer and unloading the packages is the following (22):

$$\tau = \frac{1}{s}(l(n)) + (t_0 + t_u)n \tag{3}$$

The first term of equation (3) represents the driving time and the second term of the equation represents the time it takes to park, wait for the customer, and unload the packages.

To estimate the number of SADRs that are necessary to cover an area we utilize the result proven by Kershner (23) that showed that the minimum number of circles to cover an area is approximated by:

$$\frac{\psi a}{\pi (r)^2} \tag{4}$$

where r is the size of the circle that can be covered by a SADR and ψ is a factor that accounts for the overlap among circular SADRs service areas. We assume a low value of $\psi = 1.21$. Finally, it is assumed in the case study (next section) that SADRs are used complementing mothership vans such as the one shown in (Figure 1) below. Note that the terms "mothership van" and "SADR van" have the same meaning in this research.

[FIGURE 1]

2 3

The SADR van can maximize efficiency when d is small by making several tours during a driver's shift. This requires the SADR van (mothership) driver to return to the DC to get more SADRs before picking up the first tour's SADRs. The operation of the SADRs is illustrated in Figure 2. Let's assume that the SADR van drop-offs or picks-up y SADRs per tour. For the sake of simplicity, let's assume that eight SADRs (y = 8) will be dropped off or picked up. Three stages or phases are defined.

- Phase 1, initial delivery, the SADR van (mothership) travels from the DC to the SA and drops off the SADRs (numbered 1-8) at predetermined drop-off/pick-up points along a route.
- Phase 2, intermediate delivery and collection, can be omitted or repeated x times, where x is an integer and $0 \le x$. This phase has several sub phases and to exemplify the operation it is assumed below (2a to 2d) that x = 1.
 - 2a: the SADR van returns to the DC to pick up eight additional SADRs (numbered 9-16).
 - o 2b and 2c: the SADR van drops them (numbered 9-16) off in the SA (2b) while simultaneously picking up (2c) the first batch of SADRs (numbered 1-8).
 - o 2d: the SADR van drops off the first batch of SADRs at the DC (numbered 1-8) and returns.
- Phase 3, the mothership van picks up then final y = 8 SADRs (numbered 1 + xy, y + xy) and ends at the DC.

Assuming current SADRs and realistic values (described in the next section) the following ranges seem feasible: $1 \le y \le 8$ and $0 \le x \le 2$ when y = 8 and assuming 8-hour driver's shifts. The reader should note that there are other potential scenarios or ways where SADRs and vans can be used together. We focus on the proposed scenario because it maximizes the number of deliveries when the SADRs delivery time is longer than the van travel time between drop-off points. This is explained and estimated in the next section.

[FIGURE 2]

CASE STUDY

In the following case study a Starship SADR is utilized because it meets the requirement of all US jurisdictions. The SADR results are later compared to results obtained utilizing conventional delivery vans.

SADR Van Results

It is assumed that the range of a Starship SADR is up to 4 miles (6.4 km). Starship's SADR is designed to carry up to three grocery bags of items. Considering most Amazon packages parcels are less than five pounds (2.3 kg) (24), we assume that one grocery bag is approximately equivalent in size and weight to two packages. Therefore, we assume that the Starship SADR can carry up to six packages and serve up to six customers. Note that the Starship SADR only has one locking chamber; it is assumed that theft is not an issue because SADRs are equipped with cameras, GPS trackers, and sensors to weigh the cargo. It is possible to record what cargo is being removed, when, and where. It is also assumed that s = 2.8 mph (4.5 kph) since it is the speed of the SADR 4 mph (6.4 kph) multiplied by 0.7; the coefficient 0.7 indicates that the SADR is stopped for 30% of the time it is in transit due to waiting at crosswalks, or waiting for pedestrians. We assume a value of 0.7 for k_l as done in previous studies. With these assumptions we find r, τ , and density $\frac{n}{a}$ as detailed in Table 3.

[TABLE 3]

In Table 3 it is assumed that the average distance that the SADR is traveling remains the same and equal to the SADR range, l(n) = 4 miles (6.44 km). It takes 1.56 to 2.23 hours for a SADR to deliver to 1 to 6 customers respectively. We assume for this calculation d = 0 since this is the area around the SADR drop-off/pick-up point.

To estimate the time it takes a mothership van to drop off eight SADRs, its full capacity, and then pick them back up and return to the DC, it is necessary to estimate the number of SADRs that are necessary to cover an area. Assuming 8 SADRs and that each SADR delivers to 6 customers, the radius of the largest circular area that 8 SADRs can cover is $r \cong 2.97$ mi (4.78 km). The value of r = 2.97 mi can be used to estimate the distance $l(n) \cong 10.42mi$ (16.77 km) that a van carrying n = 8 SADRs would have to travel to drop off all of the SADRs.

Assuming that vans travel at an average speed of 25 mph (40.2 kph) in an urban area and are stopped due to traffic signals or congestion 30% of the time, the actual average speed is s = 17.5 mph (28.2 kph). We also assume that at each stop it takes $t_u = 10$ minutes for the driver to park, load a SADR with its delivery items and send the SADR out of the van. Given these assumptions, the total amount of time it takes to drop off 8 SADRs is 1.93 hrs. If it takes 1.93 hours for the mothership driver to drop off all of the SADRs, but it takes each SADR 2.23 hours as seen in (Table 3) to deliver to six customers, then the mothership driver would need to wait 0.30 hours on average for the first SADR they dropped off to be ready to be picked up. Rather than waiting, the driver could (i) make some deliveries in person, i.e. in the conventional way or (ii) go back to the DC to get a second round of SADRs to drop off. The second option (ii) is assumed in this research.

We I examine different values of d from the DC to the SA. We assume that in this segment of the network the van travels faster on freeways or major arterials. We assume an average speed of 55 mph (88.5 kph) but accounting for a 30% stop adjustment time. The average speed to travel to/from DC to the SA is s = 38.5 mph (62.0 kph).

It takes the SADR van driver 3.86 working hours to drop off and pick up the SADRs once in the SA. This time as a function of the distance *d* from the DC to the SA is shown in Table 4; this table assumes a half-hour lunch break in the middle of the shift that 8 SADRs are utilized and that 48 customers are served.

[TABLE 4]

Standard Van Results

We will now examine how many customers a standard van without SADRs can serve in an 8 or 10-hour shift. It is assumed the same SA radius of 2.97 miles (4.78 km) and same travel speeds s = 17.5 mph (28.2 kph). In addition, it is assumed that the driver has to wait an average of $t_0 + t_u = 10$ minutes per customer. This results in the same amount of time $t_0 + t_u = 10$ used for the SADR van to park, load a SADR with its delivery items and send the SADR out of the van (equal times allows for an easier initial comparison).

The SADR-van can serve 48 customers in less than half the time, see for example Table 4 and the row where $d=10\,$ miles. Table 4 indicates that there is clear increase in productivity when a van is complemented by SADRs. The faster delivery time is a bonus as companies are moving to shorter delivery periods, for example Amazon has recently expanded its one-day and same day (two-hour) delivery services (25).

However, the time per delivery $t_0 + t_u$ can be substantially shorter than 10 minutes per customer. For example, a typical UPS delivery truck in a dense urban area can deliver 200–300 pieces and packages and serve on average n = 120 customers (26). Decreasing $t_0 + t_u$ to 5 and 3 minutes produce the following results (see Table 5).

[TABLE 5]

Comparisons

To quantify time savings by using a SADR van over standard vans, we determine the amount of tours, and in turn how many n deliveries, a SADR van could complete in up to a ten-hour shift. Then, we calculate how many conventional ten-hour van shifts and time would be needed to deliver to the same number of customers. Finally, by comparing results time savings for using a SADR van instead of standard vans are estimated (Table 6).

Time savings can also be translated into cost savings. Assuming a vehicle-driver cost for light trucks is \$40 per hour (27), then if a SADR van is an hour more efficient than a standard van there is a cost savings of \$40. However, the SADRs themselves have an operational cost as well. Table 6 below shows the cost savings for each d assuming that SADRs cost \$1 and \$2 per delivery – Starship Technologies has stated their devices will eventually cost \$1 per delivery to operate (28). From Table 6 it can be estimated that each SADR delivery would have to cost around \$3 to 5 per delivery, $t_0 + t_u = 10$, to cost more than a standard van. Based on the results presented in Table 4, we can conclude that using a SADR van can be both more cost and time efficient in some scenarios.

[TABLE 6]

However, the results are reversed when the delivery time per customer is $t_0 + t_u = 3$ minutes for both types of vans. Table 7 below shows no cost savings although SADR delivery vans are more competitive and can make more deliveries especially when d is small.

[TABLE 7]

From Tables 6 and 7 we can draw several observations. SADRs may be more efficient than standard vans when the average delivery time per customer is high. Also, SADRs can be faster and more cost efficient than standard delivery vans when customer density increases. This second finding seems to agree with Vleeshouwer et al. results (4). Finally, the additional cost of using SADRs is small when $d \le 10$ miles and customers may prefer to pay a bit more for faster or time sensitive deliveries if SADR van can deliver faster or more reliably.

It is also important to consider initial investment costs regarding the SADRs. Starship SADR currently costs \$5,500 (29) and there is also the additional cost of the specialized SADR vans. Therefore, there is a significant initial investment cost. A detailed study of investment flows and the financial feasibility of SADRs is left as a future research task.

Finally, from a freight planning and societal perspective, it is important to quantify changes in vehicle miles travelled. Table 8, final column, reports the amount of van travel distance reduction when moving from conventional deliveries to SADR-van deliveries. The travel distance reductions are substantial. Hence, SADRs have a great potential to reduce package related freight travel and associated externalities. However, the reduction of on road travel comes at the expense of new SADR travel on sidewalks and streets. This creates new externalities and potential safety issues as discussed earlier.

[TABLE 8]

CONCLUSIONS

Autonomous Delivery Robots (SADRs) used in conjunction with vans to transport them to service areas could be a viable alternative to standard delivery vehicles. As discussed in the first half of this paper, regulations are likely to play a large role in hindering or promoting SADR usage on a large scale by the parcel delivery industry. Speed, size, and weight limits may greatly decrease SADR effectiveness.

Assuming current SADR characteristics and strict regulation, this research shows that vans complemented by SADRs can significantly reduce delivery times, on-road vehicle miles traveled, and costs when compared to conventional deliveries in some scenarios. The average time spent per customer or delivery may have a major impact on the feasibility and cost efficiency of this new technology.

SADRs can also indirectly reduce the number of on road vehicle miles traveled by delivery vans. Hence, SADRs have great potential to reduce package related freight travel (per unit delivered) in urban areas with the associated benefits in terms of congestion and externalities. However, the reduction of on road travel comes at the expense of new SADR travel on sidewalks and streets. This creates new externalities and potential issues related to pedestrian safety and sidewalk congestion. Additionally, while delivery drivers utilize metered regular parking spots or loading zones in downtown areas, it likely that SADR vans would require more parking space and behave differently than standard delivery vans (e.g. longer parking). Would

the cost structure of SADR deliveries incentivize double parking behavior sometimes found in express package delivery (30)?

Policy makers may need to consider regulations regarding SADR vans such as: How much parking space is required by SADR vans? How long can the SADR van stop to drop off or pick up a SADR? Can the SADR van stop in a metered zone without paying the meter? Where can the SADRs themselves wait; can they idle on the sidewalk or do they need to get out of the way of pedestrians by parking on the street? Is there a limit to how many SADRs are allowed on a sidewalk or block at any given time? Future research efforts should focus on the potentially many new regulatory challenges posed by SADRs.

This research presents novel results and insights regarding SADR-van time, cost, and on road travel efficiency. However, future research efforts should analyze alternative SADR deployments and scenarios as well as a deeper analysis of the tradeoffs and problems generated by shifting freight road traffic to sidewalks. Given the explosive growth of the package delivery industry and the shift towards one-day and same day (even 1-hour) deliveries, these issues are likely to become even more relevant in the near future.

ACKNOWLEDGEMENTS

This research project was funded by the Freight Mobility Research Institute (FMRI), a U.S. DOT University Transportation Center.

AUTHOR CONTRIBUTION STATEMENT: The authors confirm contribution to the paper as follows: study conception and design: M. Figliozzi; data collection: D. Jennings, M. Figliozzi; analysis and interpretation of results: M. Figliozzi, D. Jennings; draft manuscript preparation: D. Jennings, M. Figliozzi. All authors reviewed the results and approved the final version of the manuscript.

REFERENCES

- Quarterly E-Commerce Report 1st Quarter 2018. Publication CB18-74. USCB, U.S.
 Department of Commerce, 2018.
- 5 2. Rogers, K. Higher Demand for Quick Delivery is Creating a Boom in Jobs. *CNBC News*.
- 6 2018. https://www.cnbc.com/2018/05/04/higher-demand-for-quick-delivery-is-creating-a-boom-in-jobs.html. Accessed October 24, 2018.
- Boysen, N., S. Schwerdfeger, and F. Weidinger. Scheduling Last-Mile Deliveries with
 Truck-Based Autonomous Robots. *European Journal of Operational Research*. 2018. DOI: https://doi.org/10.1016/j.ejor.2018.05.058. Accessed July 21, 2018.
- Vleeshouwer, T., Duin, R. V., and Verbraeck, A. Implementatie van autonome bezorgrobots
 voor een kleinschalige thuisbenzorgdienst. *ResearchGate*. 2017,
- https://www.researchgate.net/publication/320451527 Implementatie van autonome bezorgr obots voor een kleinschalige thuisbezorgdienst. Accessed November 1, 2018.
- Domino's Serves Up Pizza Delivery Robot. *The Sydney Morning Herald*.
 https://www.smh.com.au/business/companies/dominos-serves-up-pizza-delivery-robot-20160318-gnlqjc.html. Accessed July 1, 2018.
- Harris-Burland, H. Starship Technologies Launches Pilot Program with Domino's Pizza
 Enterprises. *Starship*. https://www.starship.xyz/press_releases/starship-technologies-launches-pilot-program-with-dominos-pizza-enterprises/. Accessed July 1, 2018.
- 7. Sawers, P. Starship Technologies Launches Autonomous Robot Delivery Services for Campuses. *Venturebeat*. https://venturebeat.com/2018/04/30/starship-technologies-launches-autonomous-robot-delivery-services-for-campuses/. Accessed July 1, 2018.
- 8. Dickey, M. R. Self-driving Delivery Vehicle Startup Dispatch Raises \$2 Million Seed Round Led by Andreessen Horowitz. *Techcrunch*. https://techcrunch.com/2016/04/06/self-driving-delivery-vehicle-startup-dispatch-raises-2-million-seed-round-led-by-andreessen-horowitz/.

 Accessed July 1, 2018.
- Kolodny, L. Marble and Yelp Eat24 Start Robot Food Delivery in San Francisco.
 Techcrunch. https://techcrunch.com/2017/04/12/marble-and-yelp-eat24-start-robot-food-delivery-in-san-francisco/. Accessed July 1, 2018.
- 11. Daimler (2017). Mercedes-Benz Vans invests in Starship Technologies, the world's leading
 manufacturer of delivery robots,
- 36 https://media.daimler.com/marsMediaSite/en/instance/ko/Mercedes-Benz-Vans-invests-in-starship-Technologies-the-worlds-leading-manufacturer-of-delivery-robots.xhtml?oid=15274799, Accessed August 1, 2018
- 12. Carry the Robot Makes a Debut at Menlo College. *Menlo College*.
 40 https://menlo.edu/news/carry-the-robot-makes-a-debut-at-menlo-college/. Accessed July 1, 2018.
- 42 13. Weiner, A. Minor Roadblocks Stand in the Way of Personal Delivery Devices. *The Spoon*.
 43 https://thespoon.tech/minor-roadblocks-stand-in-the-way-of-personal-delivery-devices/.
 44 Accessed July 1, 2018.

- 1 14. Studies Show Uber, Lyft Make Cities' Traffic Congestion Worse. CBS SF Bay Area.
- https://sanfrancisco.cbslocal.com/2018/02/25/studies-show-uber-lyft-make-cities-traffic-congestion-worse/. Accessed July 1, 2018.
- 4 15. Harris, M. 'Our Streets are Made for People': San Francisco Mulls Ban on Delivery Robots.
- 5 *The Guardian*. https://www.theguardian.com/sustainable-business/2017/may/31/delivery-6 robots-drones-san-francisco-public-safety-job-loss-fears-marble. Accessed July 19, 2018.
- 7 16. Zaleski, A. San Francisco to Delivery Robots: Get Off the Damn Sidewalk. *Citylab*.
- 8 https://www.citylab.com/life/2017/05/san-francisco-to-delivery-robots-get-off-the-damn-sidewalk/527460/. Accessed July 19, 2018.
- 10 17. Zhang, B. Personal Delivery Devices to Expand Across Bay Area. *The Campanile*.
- https://thecampanile.org/2017/12/07/personal-delivery-devices-to-expand-across-bay-area/.
 Accessed July 19, 2018.
- 13 18. Glaser, A. A Robot-Delivery Startup Helped Write State Laws that are Locking Out Competition. *Recode*. https://www.recode.net/2017/4/22/15273698/robot-delivery-startup Helped Write State Laws that are Locking Out
- 14 Competition. *Recode*. https://www.recode.net/2017/4/22/15273698/robot-delivery-startup-starship-state-laws-lock-out-competitors. Accessed July 19, 2018.
- 16 19. Robby 2 The Future of Last-Mile Delivery is Here. *Robby.io*. https://robby.io/about.
 17 Accessed November 11, 2018.
- 18 20. Kiwi Food. Delivered. Now. *Kiwicampus*. https://kiwicampus.com/. Accessed November 11, 2018.
- 21. Figliozzi, M. Analysis of the Efficiency of Urban Commercial Vehicle Tours: Data
 Collection, Methodology, and Policy Implications. *Transportation Research Part B: Methodological*, 2007. 41: 1014-1032.
- 22. Figliozzi, M. The Impacts of Congestion on Commercial Vehicle Tour Characteristics and Costs. *Transportation Research Part E*, 2010. 46: 496-506.
- 25 23. Kershner, R. The Number of Circles Covering a Set. *American Journal of Mathematics* 61:
 665-671.
- 24. Pierce, D. Delivery Drones are Coming: Jeff Bezos Promises Half-Hour Shipping with Amazon Prime Air. *The Verge*. https://www.theverge.com/2013/12/1/5164340/delivery-drones-are-coming-jeff-bezos-previews-half-hour-shipping. Accessed July 22, 2018.
- 30 25. Green, D., Amazon bringing 2-hour delivery to Whole Foods is a sneaky change in strategy, 31 and it could mean a big change is coming https://www.businessinsider.com/amazon-2-hour-delivery-whole-foods-is-change-in-strategy-2018-6, Accessed July 26, 2018.
- 26. Figliozzi, M. Lifecycle modeling and assessment of unmanned aerial vehicles (Drones) CO₂e emissions, *Transportation Research Part D: Transport and Environment*, 2017. 57: 251-261.
- 27. Outwater, M., and M. Kitchen. Value of Time for Travel Forecasting and Benefit Analysis.
 Puget Sound Regional Council. https://www.psrc.org/sites/default/files/valueoftimememo-updated.pdf.
 27. Outwater, M., and M. Kitchen. Value of Time for Travel Forecasting and Benefit Analysis.
 Puget Sound Regional Council. https://www.psrc.org/sites/default/files/valueoftimememo-updated.pdf.
 28. 2018.
- 28. Meek, A. The Robots are Coming (to Deliver Your Groceries). *BGR*.
- 39 <u>https://bgr.com/2017/01/31/robot-delivery-pizza-starship-technologies/</u>. Accessed July 26, 2018.
- 29. Condliffe, J. Why Sidwalk Delivery Robots Still Need Safety Drivers. *Technologyreview*.
- https://www.technologyreview.com/the-download/610107/why-sidewalk-delivery-robots-still-need-safety-drivers-too/. Accessed November 14, 2018.
- 44 30. Figliozzi, M. A. & Tipagornwong, C. (2017). Impact of Last Mile Parking Availability on
- Commercial Vehicle Costs and Operations. Supply Chain Forum: an International Journal, 18:2, 60-68

FIGURES

1 2

3 4

5

6 7

8 9 Vans & Robots
Minister Betti Vinini, G STABBIO

FIGURE 1 A Mercedes Benz Van Outfitted for Use with Starship Technologies' SADRs Source Daimler (11)

Phase 2a Phase 1 Phase 2b Pick up more DC DC DC **SADRs** Phase 2c Phase 2d Phase 3 Dropoff DC DC DC SADRs Legend: Distribution Center Motion of SADR Van **SADR Dropoff Point SADR Van End Location SADR Pickup Point SADR Van Start Location**

FIGURE 2 SADR Van Operation

TABLES

TABLE 1 Regulations on Sidewalk Autonomous Delivery Robots

	REQUIRED							
State or City		Yield on	Insurance	Braking	Lights (at	Legislation		
when code	was enacted	sidewalk	policy	system	night)	8		
Arizona	3/28/2018	Yes, ped. only	No	No	No	Publication HB 2422. State of Arizona		
Florida	7/1/2017	Yes	Yes	No	No	Publication SB 460. The Florida Senate		
Idaho	7/1/2017	Not specified	No	No	No	Publication HB 204. Idaho State Affairs Committee		
Ohio	9/29/2017	Yes, ped. only	Yes	Yes	Yes	Publication 4511.513. Ohio General Assembly		
Utah	3/19/2018	Yes, ped. only	Yes	Yes	Yes	Publication HB 217. Utah General Session		
Virginia	2/24/2017	Yes, ped. only	Yes	Yes	Yes	Publication 46.2- 908.1. Virginia Code		
Wisconsin	6/21/2017	Yes	No	Yes	Yes	Publication SB 148. Wisconsin Legislature		
Austin, Texas	7/20/2017	Yes	Yes	No	No	City Council Resolution No. 20170810-012. Austin City Council		
San Francisco	12/22/17 revised 3/29/18	Yes, ped. and cyclists	No, but must pay for damages caused by device	No	No	Publication 244-17. City and County of San Francisco, Board of Supervisors		
Washingt on D.C.	9/15/2016	Yes	No	No	No	Publication Chapter 15C. § 50-1551 to 50-1555. Council of the District of Columbia		

TABLE 2 Specifications for Studied SADRs

•	Weight (lbs)	Speed	Capacity	Capacity	Range (mi)
		(mph)	(lbs)	(chambers)	
Starship	40	4	40	1	4
Technologies	10	7	40	1	Т
Domino's DRU	Unknown	12	21 (approx.)	4*	12
Dispatch's	Unknown,				
Carry	but it				12 hr
	requires two	4	100	4	battery, up
	people to lift				to 48 miles
	the device				
Thyssenkrupp's	60	35	77	1	10
TeleRetail	00	33	//	1	10
Marble	80	4	Unknown	1	Unknown
Robby	60	Unknown	Unknown	1	20
KiwiBot	Unknown	Unknown	Unknown	1	Unknown

*NOTE: Domino's Robotic Unit has 4 compartments but they are all accessible at the same time

TABLE 3 SADR Service Area Radius and Tour Time - $t_0 + t_u = 10$

THE E SHER SELVICE HELE RELEASE AND TOUR TIME OF THE							
Customers	Radius of the	Time (hours)	Customer density				
served (n)	SA (mi) r	(au)	$(customers/mi^2)(n/a)$				
2	1.92	1.70	0.17				
3	1.86	1.83	0.28				
4	1.61	1.96	0.49				
5	1.44	2.10	0.77				
6	1.32	2.23	1.10				

TABLE 4 Shift Lengths varying with d and $t_0 + t_u = 10$ (all vehicles)

		Conventional Van					
	SADR-van	8 Hour Shif	ft Constraint	10 Hour Shift Constraint			
d (miles)	Shift Length (hours) (z) for n = 48	Customers served (n)	Shift Length (hours)	Customers served (n)	Shift Length (hours)		
0	3.86	40	8.00	50	9.82		
5	4.12	38	7.89	49	9.90		
10	4.38	37	7.97	48	9.98		
20	4.90	34	7.93	45	9.95		
30	5.42	31	7.90	42	9.92		
40	5.94	29	7.86	39	9.89		
50	6.46	25	7.82	36	9.86		
60	6.98	23	7.96	33	9.83		

1 2

TABLE 5 Shift Lengths varying with d and $t_0 + t_u$

		Conventional Van, 10 Hour Shift Constraint					
	SADR-van	$t_0 + t_u = $	5 minutes	$t_0 + t_u = 3$ minutes			
d	Shift Length	Customers Shift		Customers	Shift Length		
(miles)	(hours) (z) for n = 48	served (n)	Length (hours)	served (n)	(hours)		
0	3.86	95	9.97	149	9.96		
5	4.12	92	9.95	144	9.99		
10	4.38	89	9.92	139	9.95		
20	4.90	84	9.97	131	10.00		
30	5.42	78	9.92	122	9.98		
40	5.94	73	9.96	113	9.97		
50	6.46	67	9.90	104	9.94		
60	6.98	62	9.94	96	9.98		

TABLE 6 Time and Cost Savings SADR Van vs. Standard Vans, $t_0 + t_n = 10$ (all vehicles)

d (mi)	SADRs used	Customers served (n)	Time Savings Using SADRs (hours)	Daily Cost Savings SADRs w/\$1 Cost per delivery	Savings per delivery w/\$1 Cost	Cost Savings SADRs w/\$2 Cost per delivery	Savings per delivery w/\$2 Cost
0	16*	96*	11.13	\$349	\$3.64	\$253.38	\$2.64
5	16 [*]	96*	11.16	\$350	\$3.65	\$254.24	\$2.65
10	16*	96*	11.20	\$352	\$3.67	\$256.00	\$2.67
20	16*	96*	11.43	\$361	\$3.76	\$265.07	\$2.76
30	8	48	5.92	\$189	\$3.93	\$140.69	\$2.93
40	8	48	6.23	\$201	\$4.19	\$153.29	\$3.19
50	8	48	6.69	\$219	\$4.57	\$171.47	\$3.57
60	8	48	7.32	\$245	\$5.10	\$196.73	\$4.10

*NOTE: The SADR van can maximize efficiency in areas with small *d* values by making two tours in a ten-hour shift as described in (Figure 2). Therefore, it can serve 96 customers utilizing 16 SADRs instead of 8.

TABLE 7 Time and Cost Savings SADR Van vs. Standard Vans, $t_0 + t_u = 3$ (all vehicles)

d (mi)	SADRs used	Customer s served (n)	Time Savings Using SADRs (hours)	Cost Savings SADRs w/\$1 Cost per delivery	Savings per delivery w/\$1 Cost	Cost Savings SADRs w/\$2 Cost per delivery	Savings per delivery w/\$2 Cost
0	32*	192*	4.65	(\$5.83)	(\$0.03)	(\$197.83)	(\$1.03)
5	24*	144*	2.23	(\$54.80)	(\$0.38)	(\$198.80)	(\$1.38)
10	24*	144*	0.99	(\$104.48)	(\$0.73)	(\$248.48)	(\$1.73)
20	16*	96*	-1.04	(\$137.67)	(\$1.43)	(\$233.67)	(\$2.43)
30	8	48	-1.41	(\$104.54)	(\$2.18)	(\$152.54)	(\$3.18)
40	8	48	-2.14	(\$133.80)	(\$2.79)	(\$181.80)	(\$3.79)
50	8	48	-2.83	(\$161.29)	(\$3.36)	(\$209.29)	(\$4.36)
60	8	48	-3.47	(\$186.80)	(\$3.89)	(\$234.80)	(\$4.89)

*NOTE: The SADR van can maximize efficiency in areas with small *d* values by making multiple tours in a tenhour shift as described in (Figure 2). Therefore, it can deliver many deliveries, using more than 8 SADRs.

TABLE 8 Distance traveled to serve the same number of customers and $t_0 + t_u = 10$ (all vehicles)

d (miles)	On-road distance traveled by SADR van (miles)	On-sidewalk distance Traveled by SADRs (miles)	On-road distance traveled by Standard vans (miles)	% on-road van travel distance reduction
0*	41.5	64	50.1	17%
5*	61.5	64	70.1	12%
10*	81.5	64	91.0	10%
20^{*}	121.5	64	138.0	12%
30	80.8	32	95.9	16%
40	100.8	32	126.8	21%
50	120.8	32	162.8	26%
60	140.8	32	205.4	31%

*NOTE: The SADR van can maximize efficiency in areas with small d values by making two tours in a ten-hour shift as described in (Figure 2). Therefore, it can serve 96 customers utilizing 16 SADRs instead of 8.