SUPERSONIC VELOCITY IN GASES AND VAPOURS.

PART II. SUPERSONIC SATELLITES IN VAPOURS.

By S. K. Kulkarni Jatkar.

INTRODUCTION.

In Part I (This Journal, 1938, 21A, 245-71) the major satellites in a supersonic interferometer have been shown to be due to the interference between the main sound beam and the diffracted waves which are reflected by the walls of the tube. In fact, the phenomena is very similar to the wave interference which is observed in connection with radio signal fading. It is well known that fading of the wireless signals is due to interference between the direct 'ray' and that reflected from the Heaviside layer, or between two reflected rays coming from different parts of the Heaviside layer. The different reflections reach the receiver by different paths with phase shifts among themselves, the resulting signal being zero or very strong according to the difference in phase. The striking resemblance between the curves for radio signal fading and those which are obtained in the supersonic interferometer has already been pointed out by the author, which led him to suggest that the periodic signal fading, its dependance on wavelength and its pronounced peakiness with associated 'satellites' depend upon the regular movement of the Heaviside layer alone (Proc. Ind. Sci. Congress, 1930, p. 104) (Electrotechnics, 1938, No. 11, 84-6).

The use of screens suggested by Eucken and Becker (Z. Phys. Chem., 1934, Abt. B., 27, 219) is only a partial remedy as shown in Part I. Lining the walls of the tube with sound-absorbing material, if such a material could be found for high frequencies, may also simplify the interference curves.

A far more serious complication, however, is due to shift of phase in front of the oscillator, in the main sound beam. The wave theory shows that the region near the radiator, is full of changes of phase and intensity, which may produce complicated reactions of the waves returned by the reflector, on the oscillator which is used to detect the phase of the reflected waves.

The apparatus used and the experimental procedure followed by Grabau, Kneser, Eucken and Becker, Zülkhe, Richards and several others, are not calculated to overcome the various complications. W. T. Richards reports having encountered startling irregularities, which he ascribes to the fact that the waves generated by piezoelectric or magnetostriction oscillators, are not plain or purely sinusoidal to any high degree of approximation, due to the various parts of the surface of the oscillator not vibrating in phase with each other. This factor may, however, produce only damping of the quartz plate which should otherwise oscillate as a whole, although the sensitivity of different portions of the radiating face to the pressure changes may vary, as found by the author.

As shown in Part I the 'satellites' observed in the supersonic interferometer in air and other gases were only apparatus effects, and disappeared when experiments were made using a resonance method in narrow tubes. Two difficulties arise in regard to the use of narrow One is the somewhat uncertain correction for the effect of tubes. viscosity and heat conduction by the walls of the tube for different gases and vapours, and the other is the decreased sensitiveness of the quartz oscillator to the reaction of the resonating tube, and the consequent difficulty in carrying out measurements in gases and vapours which showed strong absorption. It was found by the author that, in the case of carbon disulphide, in spite of the increased density, the absorption was so pronounced that, measurements could not be taken for more than a few wave-lengths near the crystal at 50 Khz., and no measurements whatever could be made at 100 Khz, and above, even near the source. In the case of vapours of methylene dichloride and ethyl acetate, measurements could not be obtained above 126 Khz. It was, therefore, necessary to examine the 'wave form' obtained in various vapours in wide tubes, to find out if reliable measurements could be obtained from the position of the major peaks, on the assumption that they correspond to integral number of half wavelengths. It was found, however, that these peaks showed variation of phase and intensity at different positions of the reflector on the axis of the crystal oscillator, which made the observed values of wavelengths unreliable. It has been shown in this paper, by reproductions of the numerous records, that only narrow tube method can be used for accurate determinations of velocity. The decreased sensitivity is offset to some extent by the increased reaction due to higher density of the vapours.

EXPERIMENTAL.

The apparatus used has already been described in Part I (*loc. cit.*). In Fig. 1, curves 1 and 2 represent the variation of the anode current of the valve oscillator for different positions of the

reflector in ethyl ether vapour, at 95 Khz. Curve 1 was produced when the oscillations were weak and the curve 2, when oscillations were strong, the increased reaction in curve 1 being due to more favourable valve characteristic, as explained in Part I. Tube diameter was 7.5 cms. and reflector, 5 cms. in all the curves.

Curve 3 represents two records (slightly displaced from each other on purpose), showing the anode current variation in air at 50 Khz. in the same tube, with two different anode couplings.

Curve 4 shows the same variation in steam at 110°.

Curve 5 shows the interferometer curve for ethyl alcohol vapour.

Curve 6 shows the record of the interferometer for ethyl ether.

Curve 7 shows the record of the interferometer for methyl alcohol vapour.

The following tables give the results of some of the typical measurements at 50 Khz.

Fig. 1,	Curve	4.
---------	-------	----

Steam.

Fig. 1, Curve 5.

Ethyl alcohol.

n	Observed value	Calculated value	Difference	n	Observed value	Calculated value	Difference
1	5.80	4.90	0 • 90	2	6-25	6.00	- 0.25
3	13.40	14.70	+ 1.30	7	22.65	21.00	- 1-65
5	24-30	24.50	+0.20	18	55-60	54.00	- 1.60
6	29.70	29.40	- 0.30	21	65+60	63-00	- 2.60
8	40.05	39-20	- 0.85	29	98.40	96-00	- 2.40
12	58-85	58-80	- 0.05	24	104-40	102.00	-2.40
14	6S+85	68-60	- 0.25	95	106.00	105-00	- 1.00
16	78.50	78-40	- 0 • 10	30	107.00	108-00	- 1.00
17	83-20	83.30	+0.30	30	107-00	100 00	
20	97.05	98-00	+ 0.95				
23	112.25	112.70	+0.45				
24	115-65	117.60	+ 1.95				
28	128-40	127-40	+ 1-00				

Fig. 1, Curve 6.

Ethyl ether.

Fig. 1, Curve 7.

Methul	alcohol
212 0010310	111000000

n	Observed value	Calculated value	Difference	n	Observed value	Calculated value	Difference
1	2.60	2.22	- 0.38	1	3.60	3-30	- 0-30
2	4.90	4.44	- 0 • 46	2	5.70	6-60	+0.90
12	26.90	26.64	0 •26	3	10.00	9.90	0 • 10
22	48.60	48-84	+0.24	4	13.85	13.20	~ 0.65
23	51.95	51-06	- 0.89	5	17-50	16.50	- 1.00
24	53-30	53.28	- 0.02	6	21.10	19.80	- 1.30
29	64.20	64.38	+ 0.18	7	24.75	23.10	- 1.65
3 0	67+45	66-60	- 0.85	10	31.60	33.00	+ 1.40
32	71.80	71.04	- 0.76	11	34.70	36-30	+1.60
33	74.05	73-26	- 0.79	12	38-25	39-60	+ 1.35
38	84.70	84.36	0 • 34	13	40 • 95	42.90	+ 1.95
40	89.40	88.80	- 0.60	15	48-30	49.50	+ 1.20
42	93-23	93.24	+ 0.01	17	55.05	56.10	+ 1.05
49	107.65	108-78	+ 1.13	20	65.10	66.00	+ 0.90
51	114.30	113.22	1.08	21	67.95	69-30	+ 1.35
53	117.95	117.66	— 0·29	22	71.10	72.60	+ 1.50
55	122.45	122.10	-0.35	23	74.50	75.90	+ 1.40
	Lessen and the second s			25	82.50	82-50	0
				26	86-30	85.80	- 0.50
				29	92.00	95-70	+ 0 • 10
				30	99.15	99.00	- 0.15
				31	101.10	102-30	+ 0.60
				33	109.40	108.90	- 0.50

The above tables show the screw readings for the principal peaks obtained in Fig. 1, along with the calculated values given in the second column on the assumption of an average wave-length. The last column shows the deviations of the observed from the calculated values. The values obtained for the deviations, if plotted against

Fig. 2.

¢

distance, abundantly prove that the principal peaks shown in the Pierce interferometer are not integral numbers of half wavelengths apart. Any simplification of the resonance curves obtained by change in the valve circuits, which has been advocated by many workers in this field, can only be due to decreased sensitivity.

At 95 Khz. the use of 4 cm. tube with a reflector of the same size gave better results than a tube of 8 cm. and a reflector of 5 cm. (see Figs. 2 and 4, Part I). The following table shows some of the typical results for the average half wave-length in air at 95 Khz.

Temp. C.°	λ/2 mm.	Temp. C.°	$\lambda/2$ mm.
19.5	1.858	99.5	2.104
22.0	1.860	,,	2.100
23.5	1.853	,,	2.095
24.5	1.871	.,	2.094

The following table gives typical values of the velocity of sound in gases and vapours as determined by the Pierce interferometer.

		Temp. C.°	50 Khz. meters	95 Khz meters
Steam		110	497	
Ethyl alcohol		90	266	
Ethyl ether	••	90	222	
Methyl alcohol		90	343.5	
Air		25	345	345
Carbon dioxide		25	270	268
Methyl ether		25	255	256

The values are appreciably different from those found in 1 cm. tube given at the end of the paper. It is evident that no reliance can be placed on these measurements.

In Fig. 2, curve A shows the reaction-distance pattern obtained for ethyl alcohol vapour in a tube 1 cm. diameter at 50 Khz. The experiment has been repeated thrice in succession, the third curve being reproduced only for the corresponding middle portion, to show that the results are reproducible. Curve B represents 'the standing wave system' in acctone vapour under the same circumstances. Curve C shows the same phenomena in benzene vapour. Curve D is for chloroform vapour. Curve E shows two repeated patterns for methyl alcohol. Curve F shows duplicate sets of results obtained for air.

The slip produced in the records in the duplicate curves is due to the recording paper, the corresponding screw readings having shown reproducibility within 0.05 of a mm.

In the following tables are given, the results of measurements of wave-lengths of some typical vapours at 97.1° in a tube 1 cm. in diameter at 49.42 Khz. The measurements were done by recording the screw readings for the maximum anode current for individual peaks, the results being given for equal number $(n\lambda 2)$ of successive intervals of half wave-lengths.

Methyl .	Alcohol	Ethyl.	Alcohol	Ethyl	Ether
	30 X/2		40 λ/2		60 λ/2
35—5	101-05	411	108.95	622	124.55
366	101.05	422	$108 \cdot 85$	633	$124 \cdot 40$
377	100.80	43-3	108.70	644	124.60
388	100-80	444	108-10	655	124 • 40
399	101.00	455	108-25	66-6	124.50
4010	101.05	466	108.35	67 - 7	124.20
	100+96		108.53]24• 4 4
$\lambda/2 = 3$	363 mm.	$\lambda/2 = 2$	-713 mm.	$\lambda/2 = 2$.074mm.
n == 332.4 m./sec.		v == 268 • 2 m./sec.		v = 204.9 m./sec.	

.

Temp. 97.1°.

Methyl	ether.
--------	--------

```
Acctone.
```

,

Tem	ւթ. 25°	Temp	o. 97+5°	49.4 Tem	2 Khz. p. 97•1°	94+5 Temj	7 Khz. 5. 97•1°
	50 $\lambda/2$		40 $\lambda/2$		$10 \lambda/2$		$100 \lambda/2$
51-1	123.25	44-4	110.20	11-1	24.55	1011	127-25
52-2	123.05	455	110.65	122	24.80	102-2	127-12
533	123.05	46-6	109.95	133	24.60	1033	126.98
54 - 4	123.03	477	110.25	144	24.50	1044	127.06
55-5	123.30	48-8	109.25	15-5	24.25	105-5	126.98
566	$123 \cdot 20$			16-6	24+30		
57-7	123.10			177	94.25		
58 - 8	123.01			19 9	24.95		
	123 • 12		110.06	10 0	24.20		
$\lambda/2 =$	2.462	$\lambda/2 =$	2.751	15	24.50		
	er) (9		15 10	20-10	24.50		107 00
-1 0	31 A/2	1 10	40 A/2		24•45		127-08
51-0	126-15	1 - 40	123.60	A/2 =	= 2 • 445	$\lambda/2 =$	- 1-271
52-1	126.50	2-47	123 • 70		Mean 20 $\lambda/2$		Mean 20 $\lambda/2$
55-4	126+45	3-48	123.60	120	48.442	1-20	25.496
		449	123 • 80	2140	48.628	21-40	25.602
		550	123-40	41-60	48.450	4160	25-458
	126 • 38	-	123.63	6180	48·273	6180	25.128
$\lambda/2 =$	2 • 478	$\lambda/2 =$	2.747			81-100	25.390
	Mean $8 \lambda/2$		50 $\lambda/2$	l	48.448	01 100	25.419
18	20.08	500	136.95) 19 -	2.499) (2 -	1.971
9-16	19.75	51-1	137-05	Mean $\lambda/2$	= 2.433 mm.	$M_{can}\lambda/2$	== 1.271 mm.
17-24	19-80	522	136.80	Velocity	$= n\lambda$	Velocity	$= n\lambda$
2532	19-40			;	240 •5 m./sec.		240 •4 m./sec.
3340	19.90	1		· ······			
	19.77		136-93				
$\lambda/2 =$	2.477	λ/2 -=	2.738				
Mean $\lambda/2 =$	= 2·472 mm.	Mean $\lambda/2 =$	= 2·745 mm.				
Velocity ==	nλ 245 •1 m./sec.	Velocity == 2	= nλ 271·3 m·/sec.				

Benze	me 97-1°	Chlorofor	m 97·l°	Acctone ?	Femp. 134°	Benzene	Temp. 134°
	60 $\lambda/2$		$_{30} \lambda/2$		50 λ/2		60 λ/2
65 - 5	121 - 75	344	51.70	511	127-53	611	128-62
66—6	121.55	355	51.75	52 - 2	127.33	62-2	128.72
677	121.40	366	51.70	533	127.10	633	129.05
688	121.40	37-7	51.70	544	127-25	64-4	128.97
699	121-30	38-8	5 1.70	55-5	127.47	655	128.80
70-10	121.35	39—9	51.65	566	127.62	666	129.50
	121-46		51.70	57-7	127+40	677	129.00
$\lambda/2 = 2$.	024 nim.	$\lambda/2 = 1$.	723 mm.	588	127.68	688	129.12
$v = 200 \cdot$	I m./see.	v = 170	3 m./sec.		127 • 42		128.92
		<u> </u>		$\lambda/2 =$	2 • 548 mm.	$\lambda/2 =$	2 · 1 49 mm.
				Velocity =	= nλ 250 · 5 m./sec.	Velocity =	- nλ 213.9 m./sec.

2107.

50 Khz.

Temp. 24.2 °C.		Temp.	23 • 8° C.	Temp. 97 · 1° C.	
3	2 λ/2		32 λ/2		$32 \lambda/2$
331 1	11.45	33-1	111.40	32-0	126.35
34-2 1	11-65	342	111.48	331	125.90
353 1	11-65	353	111.63	34—2	126.00
364 1	11-63	364	111.50	353	125.98
37-5 1	11.60	37-5	111.55	36-4	126.15
386 1	11.60	386	111.54	375	$126 \cdot 15$
1	11.60		111.52		126.088
$\lambda/2 = 3.490$	mm.	$\lambda/2 = 3$	485 mm.	$\lambda/2 = 3.940 \text{ mm}.$	
$v = 345 \cdot 3 \text{ m}.$	/see.	v = 344	8 m./sec.	v = 389	4 m./sec.

463

Carbon tetrachloride Temp. 97.1°		Propyl ether Temp. 97·1°		Steam 134°	
	80 λ/2		70 λ/2		$20 \lambda/2$
9111	116-60	700	131.05	20-0	100-05
9212	116.55	71-1	130.85	211	100.20
93—-13	116.55	72-2	131.45	222	99-10
)414	116.60	733	131-20	23-3	99-45
9515	116.50			244	99.95
9616	116.50			255	100.25
9717	116-45			266	99-35
98-18	116.42			27-7	99.75
				288	100.40
	116.52		131-14		99 •9 44
$\lambda/2 = 1.4565 \text{ mm}.$		$\lambda/2 = 1.8734 \text{ mm}.$		$\lambda/2 = 4.9972 \text{ mm}.$	
v == 144.0 m./sec.		v == 185.2 m,/sec.		v == 492.0 m./sec.	

It will be seen from curve A that the portion, where there is slight irregularity, shows an inverted peak. But there is apparently no phase shift. The wave-length is 5.42 mm. in ethyl alcohol.

In curve B for acetone, the wave-length is 4.89 mm., and there are three inverted peaks.

In curve C for benzene, where the wave-length is 4.05 mm. there are at least two regions of complicated wave form. The measurements, however, show that there is no phase shift, as could be found by noting the differences between the calculated and observed readings.

In the curve D for chloroform vapour, in which the wave-length is 3.4 mm., the tendency to show complexity is apparent with diminished wave-length.

In curve E for methyl alcohol, the improvement of the wave-form is due to the increased wave-length which is 6.72 mm.

In curve F for air, the wave-length is 7.0 mm. at 25° C. The further improvement in the wave-form with the increased wave-length is quite clearly shown.

It will be shown in a subsequent communication that at higher temperatures, when the wave-length becomes 8 mm. the correction for the diameter of the tube is appreciable, as the wave-length is comparable with the diameter of the tube.

As the wave-lengths in vapours are lower and as further experiments were done at higher frequencies, a tube of 5 mm. diameter was used for subsequent experiments. Although the reaction was enormously decreased, there was no difficulty in getting reliable measurements by adjusting the power in the oscillator and the position of the valve characteristic, so as to get maximum anode reaction,

SUMMARY.

Further evidence regarding the complexity of the wave-form in the Pierce interferometer in vapours, has been brought forth by reproduction of the typical records, which show variations of intensity and phase, due to diffraction effects. The anomalous results obtained are thus due to experimental method, rather than to any characteristic of the physical situation, such as complexity of the molecule and its structure, and the attendant absorption and dispersion.

As a result of many experiments, only the narrow tube method has been found to be satisfactory for accurate determination of velocity. The following table shows the values of the velocity of sound in meters/sec. at 49.42 Khz. in a few typical gases and vapours in 1 cm, brass tube, at 685 mm.

				25°	97·1°	134°
Steam		••	• ·			492-0
Air	•••			345.0	389+4	
Methyl alcohol					332 • 4	
Methyl ether				245.1	271-3	
Ethyl alcohol					268-2	•••
Acetone			.]		240.5	250.5
Ethyl ether			(204+9	••
Benzene					200.1	214-0
Propyl ether	••				185.0	
('hloroform					170-3	
('arbon tetrachloride					144.0	

Department of General Chemistry. Indian Institute of Science,

[Received, 25-10-1938.]

Bangalore (India).