

SURFACE WAVES IN FIBRE-REINFORCED ANISOTROPIC SOLID ELASTIC MEDIA UNDER THE INFLUENCE OF GRAVITY

M. SETHI*

Govt. Polytechnic, Faculty of Science
Hoshiarpur, INDIA
E-mail: munishsethi76@gmail.com

K.C. GUPTA

College of Pharmacy and Technical Education
Faculty of Mathematics
Sangrur, INDIA

D. GUPTA and MANISHA

Maharishi Markandeshwar University
Faculty of Mathematics, Research Scholar
Mullana, INDIA

The aim of the present paper is to investigate surface waves in an anisotropic, elastic solid medium under the influence of gravity. First, a theory of generalised surface waves was developed and then it was employed to investigate particular cases of waves, viz., Stoneley and Rayleigh, Love type. The wave velocity equations were obtained for different cases and they are in well agreement with the corresponding classical result, when the effect of gravity, viscosity as well as parameters for fibre-reinforcement of the material medium are ignored.

Key words: fibre-reinforced medium, surface waves, viscosity, Rayleigh waves, gravity.

1. Introduction

The propagation of surface waves in homogeneous and non-homogeneous elastic media is of considerable importance in earth-quake engineering and seismology on account of occurrence of non-homogeneities in the earth crust, as the earth is made up of different layers. As a result, the theory of surface waves was developed by Stoneley (1924), Bullen (1965), Ewing *et al.* (1957), Hunters (1970) and Jeffreys (1970).

The effect of gravity on wave propagation in an elastic solid medium was first considered by Bromwich (1898), who treated the force of gravity as a type of body force. Love (1965) extended the work of Bromwich and investigated the influence of gravity on superfacial waves and showed that the Rayleigh wave velocity is affected by the gravity field. Sezawa (1927) studied the dispersion of elastic waves propagated on curved surfaces.

The transmission of elastic waves through a stratified solid medium was studied by Thomson. Haskell (1953) studied the dispersion of surface waves in multilayered media. The monograph of Ewing *et al.* (1957) is a comprehensive study of elastic waves.

Biot (1965) studied the influence of gravity on Rayleigh waves, assuming the force of gravity to create a type of initial stress of a hydrostatic nature and the medium to be incompressible. Taking into

* To whom correspondence should be addressed

account the effect of initial stresses and using Biot's theory of incremental deformations, Dey modified the work of Jones (1964). De and Sengupta (1974) studied many problems of elastic waves and vibrations under the influence of gravity field. Sengupta and Acharya (1979) studied the influence of gravity on the propagation of waves in a thermoelastic layer. Brunelle (1973) studied the surface wave propagation under initial tension or compression. Wave propagation in a thin two-layered laminated medium with stress couples under initial stresses was studied by Roy (1984). Roy and Sengupta investigated the rotatory vibration of a general viscoelastic solid sphere and also the radial vibration of a general viscoelastic solid sphere. The details can be found in the work of Eringen and Sahubi (1975). Datta (1986) studied the effect of gravity on the Rayleigh wave propagation in a homogeneous, isotropic elastic solid medium. Goda (1992) studied the effect of inhomogeneity and anisotropy on Stoneley waves. Recently Abd-Alla and Ahmed (1996) studied the Rayleigh waves in an orthotropic thermoelastic medium under gravity field and initial stress.

In most previous investigations, the effect of reinforcement has been neglected. The idea of continuous self-reinforcement at every point of an elastic solid was introduced by Belfield *et al.* (1983). The characteristic property of a reinforced concrete member is that its components, namely concrete and steel, act together as a single anisotropic unit as long as they remain in the elastic condition, i.e., the two components are bound together so that there can be no relative displacement between them.

In this paper, the authors study the propagation of surface waves in anisotropic, fibre-reinforced solid media under the influence of gravity. Biot's theory of incremental deformations is used to obtain the wave velocity equation for Stoneley, Rayleigh and Love waves. These equations are in complete agreement with the corresponding classical results in the absence of gravity and fibre-reinforced parameters of the material medium.

2. Formulation of the problem

Let M_1 and M_2 be two fibre-reinforced elastic anisotropic semi-infinite solid media. They are perfectly welded in contact to prevent any relative motion or sliding before and after the disturbances and to ensure that the continuity of displacement, stress etc. hold good across the common boundary surface. The mechanical properties of M_1 are different from those of M_2 . These media extend to an infinite great distance from the origin and are separated by a plane horizontal boundary and M_2 is to be taken above M_1 .

Let $Oxyz$ be a set of orthogonal Cartesian co-ordinates and let O be any point on the plane boundary and Oz points vertically downward to the medium M_1 . We consider the possibility of a type of wave travelling in the direction Ox , in such a manner that the disturbance is largely confined to the neighbourhood of the boundary and at any instant, all particles in any line parallel to the y -axis have equal displacements. It follows from these two assumptions that the wave is a surface wave and all partial derivatives with respect to y are zero.

Further let us assume that u, v, w are the components of displacements at any point (x, y, z) at any time t . It is also assumed that the gravitational field generates a hydrostatic initial stress which is produced by a slow process of creep where the shearing stresses tend to become small or vanish after a long period of time.

The equilibrium equation of the initial stress is in the form

$$\frac{\partial \tau}{\partial x} = 0, \quad \frac{\partial \tau}{\partial z} + \rho g = 0.$$

The dynamical equations of motion for a three-dimensional elastic solid medium under the influence of initial stress and gravity (Biot 1965, pp. 44-45, 273-281) are

$$\frac{\partial \tau_{11}}{\partial x} + \frac{\partial \tau_{12}}{\partial y} + \frac{\partial \tau_{13}}{\partial z} + \rho g \frac{\partial w}{\partial x} = \rho \frac{\partial^2 u}{\partial t^2}, \quad (2.1a)$$

$$\frac{\partial \tau_{12}}{\partial x} + \frac{\partial \tau_{22}}{\partial y} + \frac{\partial \tau_{23}}{\partial z} + \rho g \frac{\partial w}{\partial y} = \rho \frac{\partial^2 v}{\partial t^2}, \quad (2.1b)$$

$$\frac{\partial \tau_{13}}{\partial x} + \frac{\partial \tau_{23}}{\partial y} + \frac{\partial \tau_{33}}{\partial z} - \rho g \left(\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} \right) = \rho \frac{\partial^2 w}{\partial t^2} \quad (2.1c)$$

where ρ is the density of the material medium, g is the acceleration due to gravity and $\tau_{ij} = \tau_{ji} \forall i, j$ are the stress components.

The constitutive equations for a fibre-reinforced linearly elastic anisotropic medium with respect to a preferred direction \mathbf{a} are (Belfield *et al.*, 1983)

$$\begin{aligned} \tau_{ij} = & \lambda e_{kk} \delta_{ij} + 2\mu_T e_{ij} + \alpha (a_k a_m e_{km} \delta_{ij} + e_{kk} a_i a_j) + \\ & + 2(\mu_L - \mu_T)(a_i a_k e_{kj} + a_j a_k e_{ki}) + \beta (a_k a_m e_{km} a_i a_j) \end{aligned} \quad (2.2)$$

where $e_{ij} = \frac{1}{2}(u_{i,j} + u_{j,i})$ are components of strain; $\alpha, \beta, (\mu_L - \mu_T)$ are reinforced anisotropic elastic parameters; λ, μ_T are elastic parameters; $\mathbf{a} = (a_1, a_2, a_3)$, $a_1^2 + a_2^2 + a_3^2 = 1$. If \mathbf{a} has components that are $(1, 0, 0)$ so that the preferred direction is the x -axis, (2) simplifies, as given below

$$\begin{aligned} \tau_{11} = & (\lambda + 2\alpha + 4\mu_L - 2\mu_T + \beta)e_{11} + (\lambda + \alpha)e_{22} + (\lambda + \alpha)e_{33}, \\ \tau_{22} = & (\lambda + \alpha)e_{11} + (\lambda + 2\mu_T)e_{22} + \lambda e_{33}, \\ \tau_{33} = & (\lambda + \alpha)e_{11} + \lambda e_{22} + (\lambda + 2\mu_T)e_{33}, \\ \tau_{23} = & 2\mu_T e_{23}, \\ \tau_{13} = & 2\mu_L e_{13}, \\ \tau_{12} = & 2\mu_L e_{12}. \end{aligned} \quad (2.3)$$

Introducing Eqs (2.2), (2.3) in (2.1a), (2.1b), (2.1c), the equations of motion become

$$(\lambda + 2\alpha + 4\mu_L - 2\mu_T + \beta) \frac{\partial^2 u}{\partial x^2} + (\alpha + \lambda + \mu_L) \frac{\partial^2 w}{\partial x \partial z} + \mu_L \frac{\partial^2 u}{\partial z^2} + \rho g \frac{\partial w}{\partial x} = \rho \frac{\partial^2 u}{\partial t^2}, \quad (2.4)$$

$$(\mu_L - \mu_T) \frac{\partial^2 v}{\partial x^2} + \mu_T \left(\frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial z^2} \right) v = \rho \frac{\partial^2 v}{\partial t^2}, \quad (2.5)$$

$$\mu_L \frac{\partial^2 w}{\partial x^2} + (\alpha + \lambda + \mu_L) \frac{\partial^2 u}{\partial x \partial z} + (\lambda + 2\mu_T) \frac{\partial^2 w}{\partial z^2} + \rho g \frac{\partial w}{\partial y} - \rho g \left(\frac{\partial u}{\partial x} \right) = \rho \frac{\partial^2 w}{\partial t^2}. \quad (2.6)$$

To examine dilatational and rotational disturbances, we introduce two displacement potentials ϕ and ψ by the relations

$$u = \frac{\partial\phi}{\partial x} - \frac{\partial\psi}{\partial z}, \quad \omega = \frac{\partial\phi}{\partial z} + \frac{\partial\psi}{\partial x}. \quad (2.7)$$

The component v is associated with a purely distortional movement. We note that ϕ , ψ and v are associated with P waves, SV waves and SH waves, respectively. The symbols have their usual significance. Now using Eq.(2.7) in Eqs (2.4), (2.5) we obtain the following wave equation in M_I satisfied by ϕ and ψ as

$$(\lambda + 2\alpha + 4\mu_L - 2\mu_T + \beta) \frac{\partial^2\phi}{\partial x^2} + (\alpha + \lambda + 2\mu_L) \frac{\partial^2\phi}{\partial z^2} + \rho g \frac{\partial\psi}{\partial x} = \frac{\partial^2\phi}{\partial t^2}, \quad (2.8)$$

$$(\alpha + 3\mu_L + \beta - 2\mu_T) \frac{\partial^2\psi}{\partial x^2} + \mu_L \frac{\partial^2\psi}{\partial z^2} - \rho g \frac{\partial\phi}{\partial x} = \frac{\partial^2\psi}{\partial t^2}, \quad (2.9)$$

$$(\mu_L - \mu_T) \frac{\partial^2 v}{\partial x^2} + \mu_T \left(\frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial z^2} \right) v = \rho \frac{\partial^2 v}{\partial t^2}, \quad (2.10)$$

and similar relations in M_2 with $\rho, \lambda, \alpha, \mu_L, \beta$ replaced by $\rho', \lambda', \alpha', \mu'_L, \beta'$.

3. Solution of the problem

Now our main objective is to solve Eqs (2.8), (2.9), (2.10). We seek the solution of Eqs (2.8), (2.9), (2.10) in the following forms

$$(\phi, \psi, v) = [F(z), G(z), H(z)] e^{i\omega(x-ct)}. \quad (3.1)$$

Using Eq.(3.1) in Eqs (2.8), (2.9), and (2.10) we get a set of differential equations for the medium M_I as follows

$$\begin{aligned} \frac{d^2 F}{dz^2} + h_I^2 F + f_I^2 G &= 0, \\ \frac{d^2 G}{dz^2} + l_I^2 G - m_I^2 F &= 0, \\ \frac{d^2 H}{dz^2} + K_I^2 H &= 0 \end{aligned} \quad (3.2)$$

where

$$h_I^2 = \frac{\omega^2 (C^2 - A_I)}{A_2}; \quad f_I^2 = \frac{gI\omega}{A_2},$$

$$l_1^2 = \frac{\omega^2 (C^2 - A_3)}{A_4}; \quad m_1^2 = \frac{i\omega g}{A_4}; \quad K_1^2 = \frac{\omega^2 (C^2 - A_4)}{A_5},$$

$$A_1 = \frac{\lambda + 2\alpha + 4\mu_L - 2\mu_T + \beta}{\rho}, \quad A_2 = \frac{\lambda + \alpha + 2\mu_L}{\rho}, \quad A_3 = \frac{\alpha + 3\mu_L + \beta - 2\mu_T}{\rho},$$

$$A_4 = \frac{\mu_L}{\rho}, \quad A_5 = \frac{\mu_T}{\rho},$$

and those for the medium M_2 are given by

$$\frac{d^2 F}{dz^2} + h_1'^2 F + f_1'^2 G = 0,$$

$$\frac{d^2 G}{dz^2} + l_1'^2 G - m_1'^2 F = 0, \quad (3.3)$$

$$\frac{d^2 H}{dz^2} + K_1'^2 H = 0$$

where

$$h_1'^2 = \frac{\omega^2 (C^2 - A_1')}{A_2'}, \quad f_1'^2 = \frac{gi\omega}{A_2'}, \quad l_1'^2 = \frac{\omega^2 (C^2 - A_3')}{A_4'},$$

$$m_1'^2 = \frac{i\omega g}{A_4'}, \quad K_1'^2 = \frac{\omega^2 (C^2 - A_4')}{A_5'},$$

$$A_1' = \frac{\lambda' + 2\alpha' + 4\mu_L' - 2\mu_T' + \beta'}{\rho'}, \quad A_2' = \frac{\lambda' + \alpha' + 2\mu_L'}{\rho'}, \quad A_3' = \frac{\alpha' + 3\mu_L' + \beta' - 2\mu_T'}{\rho'},$$

$$A_4' = \frac{\mu_L'}{\rho'}, \quad A_5' = \frac{\mu_T'}{\rho'}.$$

Equations (3.2) and (3.3) must have exponential solutions in order that F, G, H will describe surface waves, they must become vanishingly small as $z \rightarrow \infty$.

Hence for the medium M_1

$$\phi(x, z, t) = [Ae^{-p_1 z} + Be^{-p_2 z}] e^{i\omega(x-ct)},$$

$$\psi(x, z, t) = [Ce^{-p_3 z} + De^{-p_2 z}] e^{i\omega(x-ct)}, \quad (3.4)$$

$$v(x, z, t) = Ee^{-K_1 z + i\omega(x-ct)},$$

and for the medium M_2

$$\begin{aligned}\phi(x, z, t) &= [A'e^{-p_1'z} + B'e^{-p_2'z}]e^{i\omega(x-ct)}, \\ \psi(x, z, t) &= [C'e^{-p_1'z} + D'e^{p_2'z}]e^{i\omega(x-ct)}, \\ v(x, z, t) &= E'e^{-K_1'z+i\omega(x-ct)}\end{aligned}\quad (3.5)$$

where p_j, p_j' ($j=1, 2$) are roots of the equations

$$p^4 + (l_1^2 + h_1^2)p^2 + h_1^2l_1^2 + m_1^2f_1^2 = 0, \quad (3.6)$$

and
$$p'^4 + (l_1'^2 + h_1'^2)p'^2 + h_1'^2l_1'^2 + m_1'^2f_1'^2 = 0. \quad (3.7)$$

For the media M_1 and M_2 respectively, we take into consideration the real roots of Eq.(3.6) and Eq.(3.7). The constants A, B and A', B' are related with C, D and C', D' in Eqs (3.4) and (3.5) by means of first Eqs in (3.2) and (3.3).

Equating the co-efficients of $e^{-p_1'z}, e^{-p_2'z}, e^{p_1'z}, e^{p_2'z}$ to zero after substituting Eqs (3.4) and (3.5) in the first Eqs in (3.2) and (3.3) respectively, we get

$$C = \gamma_1 A, \quad D = \gamma_2 B, \quad C' = \gamma_1' A', \quad D' = \gamma_1' B'$$

where
$$\gamma_j = -\frac{[p_j^2 + h_j^2]}{f_j^2} \quad \text{and} \quad \gamma_j' = -\frac{[p_j'^2 + h_j'^2]}{f_j'^2} \quad [j = 1, 2]. \quad (3.8)$$

4. Boundary conditions

The boundary conditions for the problem are:

(i) The displacement components at the boundary surface between the media M_1 and M_2 must be continuous at all times and positions.

i.e.,
$$[u, v, w]M_1 = [u, v, w]M_2 \quad \text{at} \quad z=0 \quad \text{respectively.}$$

(ii) The stress components τ_{31}, τ_{32} and τ_{33} must be continuous at the boundary $z=0$.

i.e.,
$$[\tau_{31}, \tau_{32}, \tau_{33}]M_1 = [\tau_{31}, \tau_{32}, \tau_{33}]M_2 \quad \text{at} \quad z=0 \quad \text{respectively,}$$

where

$$\tau_{31} = \mu_L \left(2 \frac{\partial^2 \phi}{\partial x \partial z} + \frac{\partial^2 \psi}{\partial x^2} - \frac{\partial^2 \psi}{\partial z^2} \right),$$

$$\tau_{33} = \lambda \nabla^2 \phi + \alpha \left(\frac{\partial^2 \phi}{\partial x^2} - \frac{\partial^2 \psi}{\partial x \partial z} \right) + 2\mu_T \left(\frac{\partial^2 \phi}{\partial z^2} + \frac{\partial^2 \psi}{\partial x \partial z} \right), \tag{4.1}$$

$$\tau_{32} = \mu_T \frac{\partial v}{\partial z}$$

where ∇^2 is the two dimensional Laplacian operator given by

$$\nabla^2 \equiv \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial z^2}.$$

Applying the boundary conditions (i) and (ii), we have

$$A(I - i\beta_1\gamma_1) + B(I - i\beta_2\gamma_2) - A'(i\beta'_1\gamma'_1 + I) - B'(i\beta'_2\gamma'_2 + I) = 0, \tag{4.2a}$$

$$E = E', \tag{4.2b}$$

$$A(\gamma_1 + i\beta_1) + B(\gamma_2 + i\beta_2) + A'(-\gamma'_1 + i\beta'_1) + B'(-\gamma'_2 + i\beta'_2) = 0, \tag{4.2c}$$

$$\begin{aligned} \mu_L \left[(2i\beta_1 + \gamma_1 + \beta_1^2\gamma_1)A + (2i\beta_2 + \gamma_2 + \beta_2^2\gamma_2)B \right] = \\ = \mu'_L \left[(-2i\beta'_1 + \gamma'_1 + \beta_1'^2\gamma'_1)A' + (-2i\beta'_2 + \gamma'_2 + \beta_2'^2\gamma'_2)B' \right], \end{aligned} \tag{4.2d}$$

$$\mu_T [-K_1 E] = \mu'_T [-K'_1 E'], \tag{4.2e}$$

$$\begin{aligned} A \left[\lambda(\beta_1^2 - I) + 2\mu_T(\beta_1^2 - i\beta_1\gamma_1) + \alpha(-I + i\beta_1\gamma_1) \right] + \\ + B \left[\lambda(\beta_2^2 - I) + 2\mu_T(\beta_2^2 - i\beta_2\gamma_2) + \alpha(-I + i\beta_2\gamma_2) \right] = \\ = A' \left[\lambda'(\beta_1'^2 - I) + 2\mu'_T(\beta_1'^2 - i\beta_1'\gamma'_1) + \alpha'(-I - i\beta_1'\gamma'_1) \right] + \\ + B' \left[\lambda'(\beta_2'^2 - I) + 2\mu'_T(\beta_2'^2 - i\beta_2'\gamma'_2) + \alpha'(-I - i\beta_2'\gamma'_2) \right] \end{aligned} \tag{4.2f}$$

where

$$\beta_j = \frac{p_j}{\omega}, \quad \beta'_j = \frac{p'_j}{\omega}, \quad j = 1, 2.$$

From Eqs (4.2b) and (4.2e), we have $E = E' = 0$. Thus there is no propagation of displacement v . Hence SH-waves are decoupled in this case.

Finally, eliminating the constants A, B, A', B' from Eqs (4.2a), (4.2c), (4.2d) and (4.2f), we get

$$\det(a_{ij}) = 0, \quad i, j = 1, 2, 3, 4 \tag{4.3}$$

where

$$\begin{aligned}
a_{11} &= (I - i\beta_1\gamma_1), & a_{12} &= I - i\beta_2\gamma_2, & a_{13} &= -(i\beta_1'\gamma_1' + I), & a_{14} &= -(i\beta_2'\gamma_2' + I), \\
a_{21} &= \gamma_1 + i\beta_1, & a_{22} &= \gamma_2 + i\beta_2, & a_{23} &= -\gamma_1' + i\beta_1', & a_{24} &= -\gamma_2' + i\beta_2', \\
a_{31} &= \mu_L \left[(2i\beta_1 + \gamma_1 + \beta_1^2\gamma_1) \right], & a_{32} &= \mu_L \left[2i\beta_2 + \gamma_2 (I + \beta_2^2) \right] \mu_L, \\
a_{33} &= - \left[-2i\beta_1' + \gamma_1' (I + \beta_1'^2) \right] \mu_L', & a_{34} &= - \left[-2i\beta_2' + \gamma_2' (I + \beta_2'^2) \right] \mu_L', \\
a_{41} &= \left[\lambda (\beta_1^2 - I) + 2\mu_T (\beta_1^2 - i\beta_1\gamma_1) + \alpha (-I + i\beta_1\gamma_1) \right], \\
a_{42} &= \left[\lambda (\beta_2^2 - I) + 2\mu_T (\beta_2^2 - i\beta_2\gamma_2) + \alpha (-I + i\beta_2\gamma_2) \right], \\
a_{43} &= - \left[\lambda' (\beta_1'^2 - I) + 2\mu_T' (\beta_1'^2 - i\beta_1'\gamma_1') + \alpha' (-I - i\beta_1'\gamma_1') \right], \\
a_{44} &= \left[\lambda' (\beta_2'^2 - I) + 2\mu_T' (\beta_2'^2 - i\beta_2'\gamma_2') + \alpha' (-I - i\beta_2'\gamma_2') \right].
\end{aligned} \tag{4.4}$$

From Eq.(4.3), we get the velocity of surface waves in common boundary between two fibre-reinforced elastic anisotropic semi-infinite solid media under the influence of gravity. Since the wave velocity c obtained from Eq.(4.3) depends on the particular value of ω which indicates the dispersion of the general wave form and on the gravity field.

5. Particular cases

Stoneley waves: are the generalised form of Rayleigh waves in which we assume that the waves are propagated along the common boundary of two semi-infinite media M_1 and M_2 . Therefore Eq.(4.3) determines the wave velocity equation for Stoneley waves in anisotropic fibre-reinforced solid elastic media under the influence of gravity.

Clearly, from Eq.(4.3) it is follows that wave velocity of Stoneley waves depends upon the parameters for fibre-reinforcement of the material medium, gravity and the densities of both media. The wave velocity Eq.(4.3) for Stoneley waves under the present circumstances depends on the particular value of ω and creates a dispersion of a general wave form.

Equation (4.3), of course, is in complete agreement with the corresponding classical result, when the effect of gravity and parameters for fibre-reinforcement are ignored.

Rayleigh waves: To investigate the possibility of Rayleigh waves in anisotropic fibre-reinforced elastic media, we replace medium M_2 by vacuum. Since the boundary $z = 0$ is adjacent to vacuum, it is free from surface traction. So the stress boundary condition in this case may be expressed as

$$\tau_{31} = 0, \quad \tau_{33} = 0 \quad \text{on} \quad z = 0.$$

Thus Eqs (4.2d) and (4.2f) reduce to

$$\left(2i\beta_1 + \gamma_1 + \beta_1^2\gamma_1 \right) A + \left(2i\beta_2 + \gamma_2 + \beta_2^2\gamma_2 \right) B = 0, \tag{5.1a}$$

$$\begin{aligned}
 &A\left[\lambda\left(\beta_1^2 - I\right) + 2\mu_T\left(\beta_1^2 - i\beta_1\gamma_1\right) + \alpha(-I + i\beta_1\gamma_1)\right] + \\
 &+ B\left[\lambda\left(\beta_2^2 - I\right) + 2\mu_T\left(\beta_2^2 - i\beta_2\gamma_2\right) + \alpha(-I + i\beta_2\gamma_2)\right].
 \end{aligned}
 \tag{5.1b}$$

Eliminating A and B from Eqs (5.1a) and (5.1b), we have

$$\begin{aligned}
 &\left[2i\beta_1 + \gamma_1\left(\beta_1^2 + I\right)\right]\left[\lambda\left(\beta_2^2 - I\right) + 2\mu_T\left(\beta_2^2 - i\beta_2\gamma_2\right) + \alpha(-I + i\beta_2\gamma_2)\right] + \\
 &-\left[2i\beta_2 + \gamma_2\left(\beta_2^2 + I\right)\right]\left[\lambda\left(\beta_1^2 - I\right) + 2\mu_T\left(\beta_1^2 - i\beta_1\gamma_1\right) + \alpha(-I + i\beta_1\gamma_1)\right] = 0.
 \end{aligned}
 \tag{5.2}$$

Equation (5.2) is the wave velocity equation for Rayleigh waves in a fibre-reinforced solid elastic medium under the influence of gravity.

From Eq.(5.2), we see that Rayleigh waves depend on the gravity and the parameters for fibre-reinforcement of the material medium.

In the absence of gravity, this equation is in complete agreement with the corresponding classical result (Sengupta and Acharya, 1979).

Again in the absence of gravity and writing $\mu_L = \mu_L - \mu_T + \mu_T$ and making α, β and $|\mu_L - \mu_T|$ all tend to zero, Eq.(5.2) reduces to the following form

$$\left(2 - \frac{\rho c^2}{\mu_T}\right)^2 = 4\left(I - \frac{\rho c^2}{\lambda + 2\mu_T}\right)^{1/2}\left(I - \frac{\rho c^2}{\mu_T}\right)^{1/2},
 \tag{5.3}$$

which gives the wave velocity equation for Rayleigh waves in an isotropic elastic medium.

Love waves: To investigate the possibility of Love waves in a fibre-reinforced elastic solid media, we replace medium M_2 which is obtained by two horizontal plane surfaces at a distance H -apart, while M_1 remains infinite.

For the medium M_1 , the displacement component v remains same as in general case given by Eq.(3.4).

For the medium M_2 , we preserve the full solution, since the displacement component along y -axis, i.e., v no longer diminishes with increasing the distance from the boundary surface of the two media.

Thus,
$$v' = E' \exp\left\{K_3' z + i\omega(x - ct)\right\} + F' \exp\left\{-K_3' z + i\omega(x - ct)\right\}.
 \tag{5.4}$$

In this case, the boundary conditions are

- (i) v and τ_{32} are continuous at $z = 0$
- (ii) $\tau'_{32} = 0$ at $z = -H$.

Applying boundary conditions (i) and (ii) and using Eqs (3.4), (4.1) and Eq.(5.4), we get

$$E = E' + F',
 \tag{5.5}$$

$$-p_3(\mu_T)E = (\mu_T')\left[K_3' E' - K_3 F'\right],
 \tag{5.6}$$

$$K_3' E' e^{-K_3' H} - K_3' F' e^{K_3' H} = 0. \quad (5.7)$$

On eliminating the constant E , E' and F' from Eqs (5.5), (5.6) and (5.7)

$$\tanh(K_3' H) = \frac{K_3(\mu_T)}{K_3'(\mu_T')}. \quad (5.8)$$

Thus Eq.(5.8) gives the wave velocity equation for Love waves in a fibre-reinforced elastic solid medium under the influence of gravity. Clearly, fibre-reinforcement plays a vital role in the propagation of Love waves whereas the presence of gravitational field cannot influence the same. Moreover, the thickness of the fibre-reinforced layer has a pronounced effect on the propagation of Love waves.

If gravity and parameters for fibre-reinforcement of material medium are not considered, Eq.(5.8) is in complete agreement with the corresponding classical result of Bullen.

6. Discussion and conclusions

In the light of the above analysis, the following conclusions can be made.

1. The present study reveals the effects of elasticity, gravity and fibre-reinforcement parameters on the wave velocity equations corresponding to Stoneley waves, Rayleigh waves and Love waves. The results of this analysis are useful in circumstances where these effects cannot be neglected.
2. Rayleigh wave velocity is modulated to a considerable extent by the presence of gravity and fibre-reinforcement parameters. Further, it is noted that due to the presence of gravity wave velocity Eq.(5.2) depends on the particular value of ω which indicates the dispersion of the general wave form. It can also be noted that when ω is large and as a consequence the wave-length is small, the effect of gravity is sufficiently small. Again if ω is small and the wave-length is large, the effect of gravity has a significant effect on wave velocity. The results are in complete agreement with the corresponding classical results when fibre-reinforcement parameters and gravitational fields are neglected.
3. It is noted from Eq.(5.8) that gravity cannot influence Love wave propagation. Frequency (ω), thickness of the layer (H) and fibre-reinforcement parameters have a salient influence on Love wave propagation. If gravity and parameters for fibre-reinforcement of the material medium are neglected, the dispersion equation is in complete agreement with the corresponding classical result.
4. It is noted that the wave velocity equation of Stoneley waves is very similar to the corresponding problem in the classical theory of elasticity. Here also waves are dispersed due to the presence of gravity, frequency and fibre-reinforcement parameters. Also, the wave velocity equation of this generalized type of surface waves under the influence of gravity in anisotropic fibre-reinforced elastic solid media is in complete agreement with the corresponding classical results when gravity and parameters for fibre-reinforcement of the material medium, are neglected.

Further, the solution of the wave velocity equation for Stoneley waves cannot be determined by easy analytical methods. However, we can apply numerical techniques to solve this equation by choosing suitable values of physical constants for both media M_1 and M_2 .

Nomenclature

- e_{ij} $i,j = 1,2,3$, – strain components
 g – acceleration due to gravity
 $\alpha, \beta, (\mu_L - \mu_T)$ – reinforced anisotropic elastic parameters
 λ, μ_T – elastic parameters

ϕ, ψ and v – associated with P waves. SV waves and SH waves

ρ – density of the material medium

$\tau_{ij}, j=1, 2, 3$ – stress components

$\nabla^2 \equiv \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial z^2}$ – Laplacian operator

References

- Abd-Alla A.M. and Ahmed S.M. (1996): *Rayleigh waves in an orthotropic thermoelastic medium under gravity field and initial stress.* – J. Earth, Moon Planets, vol.75, pp.185-197.
- Belfield A.J., Rogers T.G. and Spencer A.J.M. (1983): *Stress in elastic plates reinforced by fibers lying in concentric circles.* – J. Mech. Phys. Solids 31 : 25.
- Biot M.A. (1965): *Mechanics of Incremental Deformations.* – J. Willey.
- Bland D.R. (1960): *The theory of linear viscoelasticity.* – (London: Pergamon)(Monograph on the subject contains many cases of stress analysis.
- Bromwich T.J. (1898): *On the influence of gravity on elastic waves, and, in particular, on the vibrations of an elastic globe.* – Proc. London Math. Soc., vol.30, pp.98-120.
- Brunelle E.J. (1973): *Surface wave propagation under initial tension or compression.* – Bull. Seismol. Soc. Am. 63. pp.1895-1899.
- Bullen K.E. (1965): *Theory of Seismology.* – Cambridge University Press.
- Chattopadhyay A. and Venkateswarlu R.L.K. (1998): *Stresses produced in a fibre-reinforced half-space due to a moving load.* – Bull. Cal. Math. Soc., vol.90, pp.337-342.
- Chattopadhyay A., Gupta S., Sharma V.K. and Kumari P. (2010): *Propagation of G-type seismic waves in viscoelastic medium.* – Int. J. of Appl. Math. and Mech., vol.6, No.9, pp.63-75.
- Chattopadhyay A., Gupta S., Sharma V.K. and Kumari P. (2010): *Effect of point source and heterogeneity on the propagation of SH- waves.* – Int. J. of Appl. Math. and Mech., vol.6, No.9, pp.76-89.
- Datta B.K. (1986): *Some observation on interactions of Rayleigh waves in an elastic solid medium with the gravity field.* – Rev. Roumaine Sci. Tech. Ser. Mec. Appl., vol.31, pp.369-374.
- De S.K. and Sengupta P.R. (1974): *Influence of gravity on wave propagation in an elastic layer.* – J. Acoust. Soc. Am., vol.55, pp.919-921.
- Eringen A.C. and Sahubi E.S. (1975): *Linear Theory of Elastodynamics.* – New York, London: Academic Press, vol.2.
- Ewing W.M., Jardetzky W.S. and Press F. (1957): *Elastic waves in layered media.* – New York: McGraw-Hill.
- Flugge W. (1967): *Viscoelasticity.* – London: Blaisdel.
- Goda M.A. (1992): *The effect of inhomogeneity and anisotropy on Stoneley waves.* – Acta Mech., vol.93, No.1-4, pp.89-98.
- Haskell N.A. (1953): *The dispersion of surface waves in multilayered media.* – Bull. Seis. Soc. Amer., vol.43, pp.17-34.
- Hunter S.C. (1970): *Viscoelastic waves*, Progress in solid mechanics, I. (ed: Sneddon IN and Hill R) Cambridge University Press.
- Jeffreys H. (1970): *The Earth.* – Cambridge University Press.
- Jones J.P. (1964): *Wave propagation in a two layered medium.* – J. Appl. Mechanics, pp.213-222.
- Lamb H. (1926): *On waves in elastic plate.* – Proc. R. Soc.(London) A93. pp.114-128.
- Love A.E.H. (1965): *Some Problems of Geodynamics.* – London: Cambridge University Press.
- Paria G. (1960): *Love waves in granular medium.* – Bull. Calcutta. Math. Soc., vol.52, No.4, pp.195-203.

- Roy P.P. (1984): *Wave propagation in a thin two layered medium with stress couples under initial stresses*. – Acta Mechanica, vol.54. pp.1-21.
- Sengupta P.R. and Acharya D. (1979): *The influence of gravity on the propagation of waves in a thermoelastic layer*. – Rev. Romm. Sci. Technol. Mech. Appl., Tome 24, pp.395-406.
- Sezawa K. (1927): *Dispersion of elastic waves propagated on the surface of stratified bodies and on curved surfaces*. – Bull. Earthq. Res. Inst. Tokyo, vol.3, pp.1-18.
- Sharma J.N. and Kaur D. (2010): *Rayleigh waves in rotating thermoelastic solids with voids*. – Int. J. of Appl. Math. and Mech., vol.6, No.3, pp.43-61.
- Stoneley R. (1924): *Waves at the surface of separation of two solids*. – Proc. R. Soc. A 806. pp.416-428.
- Voigt W. (1887): Abh. Gesch. Wiss, vol.34.

Received: September 11, 2011

Revised: July 25, 2012