

**SUSTAINABLE MANUFACTURING : OPTIMIZATION OF ELECTRICAL ENERGY
CONSUMPTION IN PLASTIC INJECTION MOLDING PROCESS**

By

NUR ANIS OTHMAN

Thesis Submitted to

Othman Yeop Abdullah Graduate School of Business,

Universiti Utara Malaysia,

in Partial Fulfillment of the Requirement for the Master of Sciences (Management)



Othman Yeop Abdullah
Graduate School of Business
Universiti Utara Malaysia

PERAKUAN KERJA DISERTASI
(*Certification of Dissertation*)

Saya, mengaku bertandatangan, memperakukan bahawa
(*I, the undersigned, certified that*)
NUR ANIS BT OTHMAN (815594)

Calon untuk Ijazah Sarjana
(*Candidate for the degree of*)
MASTER OF SCIENCE (MANAGEMENT)

telah mengemukakan didertasi yang bertajuk
(*has presented his/her dissertation of the following title*)

**SUSTAINABLE MANUFACTURING: OPTIMIZATION OF ELECTRICAL ENERGY CONSUMPTION IN
PLASTIC INJECTION MOLDING PROCESS**

Seperti yang tercatat di muka surat tajuk dan kulit disertasi
(*as it appears on the title page and front cover of the dissertation*)

Bahawa disertasi tersebut boleh diterima dari segi bentuk serta kandungan dan meliputi bidang ilmu dengan memuaskan.
(*that the dissertation acceptable in the form and content and that a satisfactory knowledge of the field is covered by the dissertation*).

Nama Penyelia : **DR. MOHAMAD FARIZAL RAJEMI**
(Name of Supervisor)

Tandatangan :
(Signature)

Tarikh : **22 JUNE 2015**
(Date)

PERMISSION TO USE

In presenting this dissertation/project paper in partial fulfillment of the requirements for a Post Graduate degree from the Universiti Utara Malaysia (UUM), I agree that the Library of this university may make it freely available for inspection. I further agree that permission for copying this dissertation/project paper in any manner, in whole or in part, for scholarly purposes may be granted by my supervisor(s) or in their absence, by the Dean of Othman Yeop Abdullah Graduate School of Business where I did my dissertation/project paper. It is understood that any copying or publication or use of this dissertation/project paper parts of it for financial gain shall not be allowed without my written permission. It is also understood that due recognition shall be given to me and to the UUM in any scholarly use which may be made of any material in my dissertation/project paper.

Request for permission to copy or to make other use of materials in this dissertation/project paper in whole or in part should be addressed to:

Dean of Othman Yeop Abdullah Graduate School of Business

Universiti Utara Malaysia

06010 UUM Sintok

Kedah Darul Aman

ABSTRACT

This research discussed the optimization energy consumption in injection molding process to meet energy efficiency in production and get an optimal parameter setting. Injection molding is one of the techniques used in producing plastic product by injecting plastic materials molten by heat into a mold and then cooling and solidifying. It is a very complex process due to various parameters that must be considered. At this time, the industry manufacturer plastic consumes high electrical energy to produce plastic product. This in turn will release carbon dioxide gas which can have adverse effects on the environment. In this research, the all-electric injection molding machine is used because of this machine proven consume less energy compare with hydraulic and hybrid machine. Hence, this gives an advantage to the manufacturer to reduce the energy consumption from the optimization process. To optimal setting up of injection molding process, variables play a very important role in reducing electrical energy consumption to produce product. The variables involved to control settings are holding pressure, injection pressure, injection speed, mold open/close speed and screw rotation speed. Furthermore, this research presents a simple and efficient way to optimize parameter setting in injection molding process by using Taguchi experimental method and signal-to-noise ratio. With using both methods, optimal parameter settings can be achieved. In this research, an orthogonal array (OA) and signal-to-noise (S/N) ratio are employed to conduct optimization of injection molding parameter. As a result, optimization in injection molding can create the better process parameter settings which can not only reduce electrical energy consumption but, be more robust and also enhance the stability of injection process. In addition, this in turn will contribute towards sustainable manufacturing processes and reducing the carbon dioxide emissions.

Keywords: Injection molding machine, optimization, parameter setting, Taguchi Method, sustainable manufacturing

ABSTRAK

Kajian ini membincangkan penggunaan tenaga yang optimum dalam proses pengacuan suntikan untuk memenuhi kecekapan tenaga dalam pengeluaran dan dapat mengoptimumkan penetapan parameter. Pengacuan suntikan adalah salah satu teknik yang digunakan dalam menghasilkan produk plastik dengan menyuntik bahan plastik lebur dengan haba ke dalam acuan dan kemudian menyejuk dan memejal. Ia adalah satu proses yang sangat kompleks kerana pelbagai parameter yang perlu dipertimbangkan. Pada masa ini, pengeluar industri plastik menggunakan tenaga elektrik yang tinggi untuk menghasilkan produk plastik. Ini seterusnya akan membebaskan gas karbon dioksida yang boleh memberi kesan buruk kepada alam sekitar. Dalam kajian ini, semua-elektrik mesin pengacuan suntikan digunakan kerana mesin ini terbukti menggunakan tenaga yang kurang berbanding dengan mesin hidraulik dan hibrid. Oleh itu, ini memberi kelebihan kepada pengeluar untuk mengurangkan penggunaan tenaga melalui proses pengoptimuman. Tetapan optimum daripada pembolehubah proses pengacuan suntikan memainkan peranan yang amat penting dalam mengurangkan penggunaan tenaga elektrik untuk menghasilkan produk. Pembolehubah yang terlibat untuk mengawal tetapan ialah memegang tekanan, tekanan suntikan, kelajuan suntikan, acuan terbuka kelajuan / rapat dan skru kelajuan putaran. Tambahan pula, kajian ini membentangkan satu cara mudah dan berkesan untuk mengoptimumkan tetapan parameter dalam proses pengacuan suntikan dengan menggunakan kaedah eksperimen Taguchi dan isyarat-kepada-hingar. Dengan menggunakan kedua-dua kaedah ini, tetapan parameter yang optimum dapat dicapai. Dalam kajian ini, pelbagai ortogon (OA) dan isyarat-kepada-hingar (S / N) digunakan untuk menjalankan pengoptimuman pengacuan suntikan parameter. Hasilnya, pengoptimuman dalam pengacuan suntikan boleh membina proses tetapan parameter yang lebih baik yang bukan sahaja boleh mengurangkan penggunaan tenaga elektrik tetapi, menjadi lebih mantap dan juga meningkatkan kestabilan proses suntikan. Di samping itu, ini seterusnya akan menyumbang kepada proses pembuatan yang mampan dan mengurangkan pengeluaran karbon dioksida.

Kata kunci: Suntikan mesin pengacuan, pengoptimuman, tetapan parameter, Taguchi Kaedah, pembuatan mampan

ACKNOWLEDGEMENT

I would like to thank Allah for His love and blessing that make me move forward to complete this dissertation.

The dissertation could not have been accomplished without support, guidance and assistance from many individuals. First of all, this special gratitude goes to my supervisor, Dr. Mohd. Farizal Rajemi for his guidance, valuable suggestion, patience, commences encouragement and advice that he has given me to complete of this dissertation. I am deeply indebted for his time, passion, dedication, support and assist me to give the right path to write a dissertation, and that was the essential thing that I have learn from him.

Next, the special thank you goes to the people that frequently give courage which is my beloved mother Cik Halimah @ Aklimah Yaacob. And also, my family members and fiancé always give me motivation and support to finish my dissertation. This study would not have been possible without support from my best friends Ana and Hani. I am grateful for these friends who have screamed, cried and laughed with me throughout this journey.

Last but not least, also thanks to my colleagues and course mates that assist me through this research paper with their support, advice, and motivated me along this way.

TABLE OF CONTENTS

CERTIFICATION OF DISSERTATION	II
PERMISSION TO USE.....	III
ABSTRACT	IV
ABSTRAK	V
ACKNOWLEDGEMENT.....	VI
TABLE OF CONTENTS	VII
LIST OF TABLES.....	IX
LIST OF FIGURES.....	X
LIST OF ABBREVIATIONS.....	XI
CHAPTER ONE.....	1
INTRODUCTION	1
1.1 Introduction to the Study	1
1.2 Background of the Problem	4
1.3 Problem Statement	8
1.4 Research Objectives	9
1.5 Research Questions	10
1.6 Significance of the Study.....	10
1.7 Scope of Study	12
1.8 Definition of Key Terms.....	13
1.9 Organization of Remaining Chapters	15
CHAPTER TWO.....	17
LITERATURE REVIEW	17
2.1 Introduction.....	17
2.2 Plastic Injection Molding Process.....	17
2.3 Definition and Conceptualization of Optimization Energy	20
2.4 Sustainable Manufacturing	22
2.5 Research Model / Framework.....	24
2.6 Definition of Variables	26
CHAPTER THREE.....	29
RESEARCH METHODOLOGY.....	29
3.1 Introduction.....	29
3.2 Research Design.....	29

3.2.1 Identify Control Factors and Control Variables	33
3.2.2 Development Parameter Setting Orthogonal Array (OA).....	34
3.2.3 Identify a Signal to Noise Ratio (S/ N).....	37
3.3. Data Collection Procedures	39
3.4 Data Analysis Techniques	42
CHAPTER FOUR	44
ANALYSIS OF RESULT AND DISCUSSION	44
4.1 Introduction.....	44
4.2 Distribution of Energy	44
4.3 Energy Map.....	49
4.4 Optimization Parameter Setting	54
4.5 Discussion	60
CHAPTER FIVE	63
CONCLUSION.....	63
5.1 Introduction.....	63
5.2 Recapitulation of the Study.....	63
5.3 Summary of Results	64
5.4 Limitation of Study	66
5.5 Suggestions for Future Research.....	66
5.6 Conclusion	67
REFERENCES	68
APPENDICES	71
Appendix A: Calculation Distribution of Energy	71
Appendix B: Calculation Electrical Energy Map.....	72
Appendix C: Calculation Optimization Parameter Setting.....	73

LIST OF TABLES

Table	Page
Table 3.1 Process Parameter Factors and Levels	36
Table 3.2 Taguchi Orthogonal Array (OA) Matrix Table	36
Table 3.3 Orthogonal Array L ₁₈ Smaller-the-Better	37
Table 4.1 Injection Molding Parameter and Their Levels	55
Table 4.2 Experimental Plan Using L ₁₈ Orthogonal Array	56
Table 4.3 Experimental Results for Total Energy and S/N Ratio	57
Table 4.4 Response Table for Signal to Noise Ratio	58
Table 4.5 Optimum Setting Table	59
Table 4.6 Recommended Setting	60

LIST OF FIGURES

Figure	Page
Figure 1.1 Profile of the Plastic Products Industry by Manufacturing Process, 2009	4
Figure 1.2 Electricity Consumption in Malaysia by Sector (%), in the Year 2011	5
Figure 1.3 Electricity Consumption in Malaysia by Sector (%), in the Year 2012	6
Figure 1.4 Electricity Consumption in Malaysia by Sector (%), in the Year 2013	6
Figure 2.1 Complete Cycle of Injection Molding Process	18
Figure 2.2 Model Nissei NEX 500 All Electric Injection Molding Machine	20
Figure 2.3 Share of Energy Consumption in Representative Injection Molding Process	21
Figure 2.4 Theoretical Frameworks for Electrical Energy Consumption.....	25
Figure 3.1 Steps Applied for Taguchi Optimization Process	32
Figure 3.2 Control Factors and Control Variables in Injection Molding Parameter Setting	34
Figure 3.3 Kyoritsu KEW 5020 Current Logger	41
Figure 4.1 Amount of Current and Time in Injection Molding Processes	46
Figure 4.2 Distribution of Electrical Energy Consumption in Injection Molding	48
Figure 4.3 The Injection Speed and Holding Pressure Parameter	50
Figure 4.4 Electrical Powers [kW] for Each Setting	51
Figure 4.5 Electrical Energy Map for Each Setting	52
Figure 4.6 Electrical Energy Usages for 1000 Shots.....	53
Figure 4.7 Response Graph of S/N Ratio	59

LIST OF ABBREVIATIONS

Abbreviations

ANN	Artificial Neural Networks
ABC	Artificial Bee Colony Algorithm
CO ₂	Carbon Dioxide
GDP	Gross Domestic Product
GHG	Greenhouse Gas
GWh	Gigawatt Hour
IMM	Injection Molding Machine
kWh	Kilowatt-hour
MSD	Mean Square Deviation
OA	Orthogonal Array
ROI	Return of Investment
S/N	Signal to Noise Ratio

CHAPTER ONE

INTRODUCTION

1.1 Introduction to the Study

Electricity is the main source for daily life and now it is classified as primary human need. In Malaysia, 90% of electricity generation is divided into two sources in which 60% is from gas and 30% from coal, while the rest of 10% is from hydro and oil (Bakar, 2011). Electricity is used in various sectors including domestic, industrial, enterprise, agriculture and education and so on. In this country, the electricity demand has recorded an increase of 6.1% per year (Consumer Research and Resource Centre, 2012). The electrical energy is generated almost every day to meet the needs of users in daily life. Demand for electricity in Peninsular Malaysia in 2010 continued to increase over 2009 of 7.8% from 94.748 in 2009 to 102.139 GWh (Energy Commission Report Malaysia, 2010). The sources used to generate electricity are based on oil, gas and coal which cannot be renewed due to the shortage of these resources.

Electricity is the most important element in an operating system of a residential or commercial building. Some of the systems within a building include lighting system, air conditioning system, motor equipment systems, communication systems, production systems and etc. The absence of electricity causes the system to stop its work as well as affect the activity of users in various sectors to do their work effectively.

The contents of
the thesis is for
internal user
only

References

- Allwood J. (2005) What is sustainable manufacturing? Sustainability: What are the issues? In: Sustainable Manufacturing Seminar Series
- Bakar, A. R. (2011). Kementerian Tenaga, Teknologi Hijau dan Air. Retrieved from http://www.kettha.gov.my/portal/index.php?r=kandungan/parlimen_view&menu1_id=5&menu2_id=19&parlimen_id=392#.VVQhvbmqkp
- Chen, W. C., Fu, G. L., Tai, P. H., & Deng, W. J. (2009). Process parameter optimization for MIMO plastic injection molding via soft computing. *Expert Systems with Applications: An International Journal*, 36(2), 1114-1122
- Chen, W. C., Liou, P. H., & Chou, S. C. (2014). An integrated parameter optimization system for MIMO plastic injection molding using soft computing. *The International Journal of Advanced Manufacturing Technology*, 73(9-12), 1465-1474
- Chiang, K. T., & Chang, F. P. (2006). Application of grey-fuzzy logic on the optimal process design of an injection-molded part with a thin shell feature. *International Communications in Heat and Mass Transfer*, 33(1), 94–101. <http://doi.org/10.1016/j.icheatmasstransfer.2005.08.006>
- Damir G., Maja, R., & Mladen Š. (2012a). Energy Efficient Injection Moulding of Polymers. *Issn 2067-3809*, 103–108
- Damir G., Maja, R., & Mladen Š. (2012b). Processing parameters influencing energy efficient injection moulding of plastics and rubbers. *Kategorizirani Radovi*, 33, 112–117
- Department of Statistics, Malaysia. (2013). Annual Gross Domestic Product. [Report]. 124.
- Dufloy, J. R., Sutherland, J. W., Dornfeld, D., Herrmann, C., Jeswiet, J., Kara, S., ... Kellens, K. (2012). Towards energy and resource efficient manufacturing: A processes and systems approach. *CIRP Annals - Manufacturing Technology*, 61(2), 587–609. <http://doi.org/10.1016/j.cirp.2012.05.002>
- Energy Commission. (2010). Electricity Supply Industry in Malaysia–Performance and Statistical Information. *Energy Commission: Putrajaya, Malaysia*.
- Energy Commission. (2011). Electricity Supply Industry in Malaysia–Performance and Statistical Information. *Energy Commission: Putrajaya, Malaysia*.
- Energy Commission. (2012). Electricity Supply Industry in Malaysia–Performance and Statistical Information. *Energy Commission: Putrajaya, Malaysia*.
- Energy Commission. (2013). Electricity Supply Industry in Malaysia–Performance and Statistical Information. *Energy Commission: Putrajaya, Malaysia*.

- Fei, N. C., Mehat, N. M., & Kamaruddin, S. (2013). Practical Applications of Taguchi Method for Optimization of Processing Parameters for Plastic Injection Moulding: A Retrospective Review. *ISRN Industrial Engineering*, 2013, 1–11. <http://doi.org/10.1155/2013/462174>
- Galarraga, I., Abadie, L. M., & Ansuategi, A. (2013). Efficiency, effectiveness and implementation feasibility of energy efficiency rebates: The “Renove” plan in Spain. *Energy Economics*, 40. <http://doi.org/10.1016/j.eneco.2013.09.012>
- Guo, Y., Loenders, J., Duflou, J., & Lauwers, B. (2012). Optimization of energy consumption and surface quality in finish turning. In *Procedia CIRP* (Vol. 1, pp. 512–517). <http://doi.org/10.1016/j.procir.2012.04.091>
- Huang, M. C., & Tai, C. C. (2001). Effective factors in the warpage problem of an injection-molded part with a thin shell feature. *Journal of Materials Processing Technology*, 110(1), 1–9. [http://doi.org/10.1016/S0924-0136\(00\)00649-X](http://doi.org/10.1016/S0924-0136(00)00649-X)
- Kanungo, a., & Swan, E. (2008). All Electric Injection Molding Machines: How Much Energy Can You Save? *30th Industrial Energy Technology Conference*, 1–12. Retrieved from <http://txspace.di.tamu.edu/handle/1969.1/87974>
- Karna, S. K. (2012). *IJEMS An Overview on Taguchi Method*, 1(June), 1–7.
- Kent R., (2008). *Energy Management in Plastic Processing*, Plastic Information Direct, Bristol.
- Madan, J., Mani, M., & Lyons, K. W. (2013). Characterizing Energy Consumption of the Injection Molding Process. *Volume 2: Systems; Micro and Nano Technologies; Sustainable Manufacturing*, V002T04A015. <http://doi.org/10.1115/MSEC2013-1222>
- Market Watch 2012, The Malaysian Plastic Industry. *Trade Fairs in Malaysia 2012, PWTC, Kuala Lumpur*.
- Market Watch 2011, The Malaysian Plastic Industry. *Trade Fairs in Malaysia 2010/2011, PWTC and KLCC, Kuala Lumpur*.
- Mathivanan, D., Nouby, M., & Vidhya, R. (2010). Minimization of sink mark defects in injection molding process – Taguchi approach. *International Journal of Engineering, Science and Technology*, 2(2), 13–22. <http://doi.org/10.4314/ijest.v2i2.59133>
- Mativenga, P. T., & Rajemi, M. F. (2011). Calculation of optimum cutting parameters based on minimum energy footprint. *CIRP Annals - Manufacturing Technology*, 60(1), 149–152. <http://doi.org/10.1016/j.cirp.2011.03.088>
- Nalbant, M., Gökkaya, H., & Sur, G. (2007). Application of Taguchi method in the optimization of cutting parameters for surface roughness in turning. *Materials and Design*, 28(4), 1379–1385. <http://doi.org/10.1016/j.matdes.2006.01.008>

- Ng, C. F., Kamaruddin, S., Siddiquee, a. N., & Khan, Z. a. (2011). Experimental investigation on the recycled hdpe and optimization of injection moulding process parameters via taguchi method. *International Journal of Mechanical and Materials Engineering*, 6(1), 81–91.
- Pah, T., & Syed, R. (2013). Kesedaran Mengenai Penjimatan Tenaga Elektrik dan Kelestarian Alam Sekitar, 2, 977–990.
- Rajemi, M. F., Mativenga, P. T., & Aramcharoen, A. (2010). Sustainable machining: Selection of optimum turning conditions based on minimum energy considerations. *Journal of Cleaner Production*, 18(10-11), 1059–1065.
<http://doi.org/10.1016/j.jclepro.2010.01.025>
- Rashi A. Yadav, S. V. Joshi & N., K., Kamble (2012). Recent methods for optimization of plastic injection molding process - A Literature Review [Journal]. *International Journal of Scientific & Engineering Research* 3(8).
- S. Kamaruddin, Zahid A. Khan & S. H. Foong (2010). Application of Taguchi method in the optimization of injection moulding parameters for manufacturing products from plastic blend. *IACSIT International Journal of Engineering and Technology*, 2(6), 574-580.
- Sekaran, U. (2000). *Research methods for business: A skill-building approach* (3rd ed.). US: John Wiley & Son. Inc.
- Thiriez, a., & Gutowski, T. (2006). An Environmental Analysis of Injection Molding. *Proceedings of the 2006 IEEE International Symposium on Electronics and the Environment*, 2006., 195–200. <http://doi.org/10.1109/ISEE.2006.1650060>
- World Commission on Environment and Development. (1987). Report of the World Commission on Environment and Development: Our Common Future (The Brundtland Report). *Medicine, Conflict and Survival*, 4(1), 300.
<http://doi.org/10.1080/07488008808408783>
- Wu, C. H., & Liang, W. J. (2005). Effects of geometry and injection-molding parameters on weld-line strength. *Polymer Engineering & Science*, 45(7), 1021-1030.
- Yadav, A. J., Dravid, S. V., & Rajput, V. D. (2012). Taguchi technique in optimization of injection molding process parameters for manufacturing plastic parts. *Proceeding of the NCNTE-2012*, 24-25.