Temperature-Pressure Phase Relationships in Niobium Pentoxide

J. L. Waring, R. S. Roth, and H. S. Parker

Institute for Materials Research, National Bureau of Standards, Washington, D.C. 20234

(July 23, 1973)

A pressure-temperature (P-T) section of the phase equilibrium diagram for Nb_2O_5 has been determined. Four single phase regions, $H\cdot Nb_2O_5$, $B\cdot Nb_2O_5$, and two $L\cdot Nb_2O_5$ areas, were characterized by x-ray powder diffraction data. The superstructure of $L\cdot Nb_2O_5$ was indexed on the basis of similarities to the known superstructures of $L\cdot Ta_2O_5$ and confirmed with single crystal electron diffraction data. The correct unit cell is orthorhombic with a=6.168, b=29.312, c=3.938 Å, with the b axis 8 times the subcell $(8\times3.664$ Å).

Key words: Niobium pentoxide; phase relationships; pressure; temperature.

1. Introduction

Niobium pentoxide has been reported to occur in at least eight different polymorphic forms under varying experimental conditions. The polymorphs of Nb₂O₅ and their structural relationships to each other have been discussed by A. D. Wadsley and S. Andersson [1].1 These authors postulated that some of the various modifications should have stability fields in the relevant ranges of the pressure-temperature (P-T) phase diagram. They put forward a "not impossible" phase diagram (fig. 1) based on no experimental evidence. S. Tamura [2] reported a temperaturepressure diagram (fig. 2) for Nb₂O₅ postulating the boundaries between H-Nb2O5 and L-Nb2O5 and B-Nb₂O₅ and L-Nb₂O₅ based on experiments utilizing an opposed piston apparatus. H-Nb₂O₅ is the stable polymorph which occurs at high temperatures and atmospheric pressure, L-Nb₂O₅ is the metastable polymorph formed during precipitation and B-Nb₂O₅ is the high pressure form [1]. In the present study only these three previously reported phases were found to occur in the system at the temperatures and pressures studied.

In this study, it was necessary to determine which of the multitude of possible polymorphs represent equilibrium phases and which represent metastable phases. The Nb₂O₅ specimens were equilibrated in an apparatus which is capable of heating materials in a uniform temperature zone up to about 1400 °C and 150,000 psi² isostatic pressure in an environment free of contaminants.




FIGURE 1. Tentative temperature-pressure phase diagram for various Nb₂O₅ modifications (taken from Wadsley and Andersson [1] and modified according to present notation).

2. Sample Preparation

The Nb₂O₅ used in this investigation was found by spectrographic analysis to contain less than about 0.01 percent Si, 0.001 percent Ca and Mg. The presence of As, Cu, and Ta was questionable. The starting materials were prepared as follows: The Nb₂O₅ (low temperature form) was dried at 130 °C for 19 h. Portions of the dried material were sealed in 5 mm O.D. × 25 mm long Pt tubes and heated to 1450 °C for 60 h to form H-Nb₂O₅, the high temperature polymorph. This material was reannealed in air at 1000 °C for 1 h to minimize any slight reduction which may have occurred. The B-polymorph of Nb₂O₅ was formed by heating the high temperature modification (H-Nb₂O₅)

¹ Figures in brackets indicate the literature references at the end of this paper.

 $^{^2}$ The use of psi, bar, and kbar follows the current common practice of workers in the field. Note that 1 bar=10^5 N/m² (or pascal)=10^6 dyn/cm²=0.9869 atm=14.504 psi. The accepted international standard (SI) unit of pressure is the pascal or newton per meter squared.




Figure 2. Pressure/temperature/structure relationships for Nb₂O₅ (after Tamura [2]).

at 900 °C for 19 h at about 70,500 psi. For some experiments, LiNbO $_3$ or distilled H_2O was added to increase crystallinity and to determine if such impurities affect the equilibrium phase assemblage.

3. Apparatus

An internally heated pressure system similar to that described by Yoder [3] was used in this investigation. A block diagram of the apparatus is shown in figure 3. An air operated, two stage compressor (labeled A) supplies argon gas to the system at pressure to 30,000 psi. For higher initial pressures the valve (labeled B) is closed and the moving piston of an intensifier (labeled C) is advanced against the head of gas which has filled the vessel. The intensifier piston is advanced by hydraulic pressure supplied by an air driven oil compressor. The differential ratio of the intensifier is 5:1 thus providing a maximum pressure of 150,000 psi. The valve (labeled D) isolates the pressure vessel during a run. Pressures of up to 150,000 psi can be obtained in a few minutes provided the system is tight. Since a minimum of 16 h was needed to achieve equilibrium in most of the samples studied, at least in the lower P-T range, particular attention had to be paid to obtaining a relatively leak free system. Experimental results were discarded if a pressure drop greater than 500 psi occurred during a run.

3.1. Pressure Measurement

The pressure was determined as a function of the change in resistance of a "seasoned" manganin wire coil when measured with a dc Carey-Foster Bridge [4]. The resistance of the manganin coils was approximately equal to $120\,\Omega$ and the coils were calibrated by the supplier against a dead weight gage. Two coils were used for a comparison measurement. One coil acted as a pressure sensor and the other served as a




Figure 3. Schematic block diagram of pressure-temperature apparatus having a working range up to 1400 °C and 150,000 p.s.i.

dummy gage for temperature compensation. A least squares fit by computer analysis of the correction data for the manganin coils used in this study has shown that the resistance-pressure curve in the range 0–150,000 psi can be described best by a parabolic equation of the type $R = B_0 + B_1P + B_2P^2$ where $B_0 = 1.20357$, $B_1 = 1.9926470 \times 10^{-5}$ and $B_2 = 8.0085893 \times 10^{-13}$. Errors in absolute pressure may be as much as 20 bar at 150,000 psi due to uncertainties in the pressure scale [3].

3.2 Temperature Measurement

The temperature was measured with a Pt-Pt10 percent Rh thermocouple. Bell [5] has shown that the effect of pressure on Pt-10 percent Rh thermocouples at the pressures attained in this work are within the limits of error in the temperature measurement. For this reason no correction for pressure has been applied to the temperature measurements. The temperatures reported can be considered accurate to at least ± 20 °C. Yoder [3] reported the results of probing the thermal gradient of his system with a thermocouple. A zone of even heating ±5 °C was found to exist over a distance of about 5 cm. As our system is nearly identical, this time consuming process was not repeated.

4. Phase Equilibria

A P-T phase equilibrium diagram for Nb_2O_5 (fig. 4) has been constructed from the x-ray data given in table 1. These data were obtained from specimens quenched (thermocouple indicates cooling to ambient temperature in less than a minute) by turning off the electrical power to the furnace and then reducing the pressure. Equilibrium was considered to have been approached when the x-ray powder diffraction patterns of specimens successively heated for longer times and/or at higher temperatures and/or pressures (quenched to ambient temperature and pressure) showed no significant change. X-ray diffraction powder patterns were made using a high angle record-




FIGURE 4. Pressure-temperature (P-T) phase equilibrium diagram for Nb₂O₅.

Dot dash curves - delineate phase boundaries which could not be determined. Dashed curve - delineates phase boundaries where reversibility was not established.

○ - L-Nb₂O₅ +- H-Nb₂O₅ ◇ - B-Nb₂O₅

Symbols refer to phases interpreted as equilibrium (see table 1 for experimental data).

ing Geiger counter diffractometer and nickel-filtered copper radiation with the Geiger counter scanning the 2θ angular range at $1/4^{\circ}$ $2\theta/\min$ and the radiation being recorded on the chart at 1° $2\theta/\mathrm{in}$. The unit cell dimensions reported are estimated to be accurate within about two standard deviations.

The phase diagram can be described as consisting of four single phase regions in the temperature-pressure range investigated. They are designated H-Nb₂O₅, L-Nb₂O₅, B-Nb₂O₅ and L'-Nb₂O₅. In a previous study the N-form of Nb₂O₅ was synthesized at atmospheric pressure with the addition of LiNbO₃ [6]. However, in the present study this phase was found to transform to B-Nb₂O₅ at 800 °C and 64,000 psi and may be considered to become unstable with increasing pressure. No other polymorphs of Nb₂O₅ have been found to occur in this study.

4.1. H-Nb₂O₅ (High Temperature Form)

The crystal structure of the high temperature form of $\mathrm{Nb_2O_5}$ (H- $\mathrm{Nb_2O_5}$) was reported by Gatehouse and Wadsley [7]. The structure consists of infinite chains of 3×5 blocks of octahedra at one level and isolated blocks of 3×4 octahedra at the next level with tetrahedral positions at the block junctions. This phase, with a reported x-ray density of 4.55 [8], was found to occur at the highest temperature and lowest pressure (fig. 4). All experiments conducted in the P-T range lower than that given in table 1 and figure 4 showed no change in the starting material. Therefore, the low temperature boundary of the H- $\mathrm{Nb_2O_5}$ field could not be determined because equilibrium could not be achieved in this portion of the system in laboratory time.

Table 1. Temperature-Pressure Experimental Data for $\mathrm{Nb_2O_E}$.

for No ₂ 0 ₅ .					
Heat T	reatment <u>a/b</u> /		X-ray Diffraction Analyses [©]		
Temp °C	Time hr	Pressure psi			
600	144	103,000	1 + + + + L 1 + + + + + + + + + + + + + + + + + + +		
700	1	89,000	'L → L + <u>tr H</u> {H → H + L {L → L		
700	168	108,500	H + L + <u>tr H</u> L → L		
730	72	66, 200	B + B		
746	22	101,100	$\begin{cases} H + \overline{L} + \underline{H} + \underline{tr} B \\ L + L + \underline{tr} H \text{ and } B \end{cases}$		
750	48	63,100	{H → B L → B		
750	96	77,200	{H + L + H L + L + tr B B + B		
750	64	82,400	B + B		
750	16	89,400	{H + L + <u>tr.H</u> L + L		
750	127	107,200	B + B		
751	168	108,000	lH → [
775	115	47,500	H - H L - L + tr H B - B + tr H		
775	24	54,760	1 + B + tr H		
775	43	66,540	H + B + tr L L + B + L		
800	19	64,000	L + L + tr B		
800	21	82,000	L + L + tr B H + B + <u>tr L</u>		
800	68	92,000	L + B + L		
800	24	105,000	H + B + L L + B + L (H + B + L		
800	19	118,000	L + L + H		
850	120	48,700	H - H L - L + H		
850	144	51,400	H + B + tr.H L + B + L		
875	24	56,000	{H + H L + B + L		
900 900	112 19	47,500 68,000	L + L + tr H		
900	16	70,400	1H - B + H L - B + C		
900	16	82,500	H + B + tr L L + B + L		
900	36	104,000	1H + B + <u>tr L</u>		
950	17	48,300	L + L + H		
951	64	70,600	H - B + L L - L + <u>tr B</u>		
965	64	75,000	H + L		
995	65	79,160	{H - L L - L		
000	19	60,000	L + L		
000	16	65,200	B + L {H - L + B L - B + tr H		
000	48	98,000			
050	16	53,000	1L + B + L		
050 050	192 16	60,750 75,500	H - L H - L		
050	16	100,000	jH + L		
100	16	77,700	H + I		
150	289	46,600	{H - H L - L + tr H		
150	144	60,600	{H + H {L → H		
150	113	69,500	IH - L		

a/ The starting materials were prepared as follows: L-Nb₂O₅ - dried at 130°C for 19 hours, H-Nb₂O₅ - calcined at 1450°C for 60 hours in large sealed Pt tube and reannealed in air at 1000°C for one hour. B-Nb₂O₅ - H-Nb₂O₅ was heated at 900°C for 19 hours in a series of small Pt tubes at a pressure of 70,500 psi.

Table 2. Indexed X-ray Diffraction Powder Pattern for B-Nb₂0₅ (CuK_{\pi} radiation)<u>a</u>/

hk i. b/	d _{obs}	20 _{obs}	20 calc	1 <u>c</u> /	
200 111 111 400 311 002 311 020 402 021	6.16 3.644 3.315 3.077 2.982 2.6868 2.5034 2.4422 2.3480	14.37 24.42 26.87 28.99 29.94 33.32 35.84 36.77 38.30	14.38 24.41 26.87 28.99 29.94 33.33 36.77 38.31 (40.54)	14 79 64 100 81 43 31 11 7	
511 510 221 600 420 511 602 022 402 113 313 711 422	2.2218 2.1980 2.1667 2.0518 1.9133 1.8879 1.8827 1.8068 1.8057 1.7233 1.7081 1.7028 1.6920	40.57 41.02 41.65 44.10 47.48 48.16 48.30 50.47 50.50 53.10 53.79 54.16	40.55 40.59 41.03 41.65 44.11 47.49 48.18 48.30 50.46 50.52 53.10 53.59 53.81 54.14	14 12 7 17 29 7 7 43 36 10 21 57 29	
130 1137 620 137 800 802 337 622 711 602 422 313 331 713 004 820 822 604	1.6143 1.5710 1.5604 1.5382 1.5150 1.4947 1.4915 1.4831 1.4577 1.4512 1.4378 1.4217 1.3965 1.3433 1.3013	57.00 58.72 59.16 60.10 61.12 62.04 62.19 62.58 63.80 64.10 64.79 65.62 66.95 69.98 72.59 73.50	57.001 58.73 59.15 60.09 61.11 62.05 62.20 62.60 63.78 64.10 64.79 65.62 66.93 69.99 72.56 73.49 73.52	7 6 6 13 6 9 14 26 4 7 6 14 7	

a/ Specimen heated to 900°C for 19 hrs at 70,500 psi in a sealed Pt tube and quenched.

4.2. B-Nb₂O₅

The existence of B-Nb₂O₅ was first reported by Laves, Petter and Wulf [9] who described it as zeta-Nb₂O₅. Schäfer, Schulte, and Gruehn [10] formed several new phases from the reaction Nb₂O₅(s)+3NbX₅(g) \rightleftharpoons 5NbOX₃(g) X=Cl, Br, or I. One of the new phases formed in this reaction was called B and is the same phase which Laves named zeta. In this paper, the B-nomenclature is used. The stability field of B is shown in figure 4. B-Nb₂O₅ is thus the medium temperature, high pressure polymorph of Nb₂O₅. B-Nb₂O₅ has not been previously synthesized by pressure equilibrium conditions below about 30 kbar [2], but was found to form under equilibrium conditions in the present work at pressures as low as 3.5 kbar.

 b^{\prime} All specimens were quenched in sealed Pt tubes. Some specimens were heated at appropriate temperatures in Au tubes and it was found that for Nb_2O_5 the experimental results were the same for both the Pt and Au tubes.

The phases identified are given in the order of the amount present at room temperature. The phases are not necessarily those present at the temperature and pressure to which the specimen was heated.

H = high temperature-low pressure polymorph of Nb_20_5

L-Nb₂O₅ = represents both L-Nb₂O₅ and L'Nb₂O₅ which occur experimentally in two different portions of the system separated by the field of B-Nb₂O₅. The x-ray patterns of the specimens prepared in these two fields are identical except for degree of crystallinity.

B = intermediate temperature and high pressure polymorph of $\mathrm{Nb}_2\mathrm{O}_5$.

The phase(s) underlined have been interpreted as non-equilibrium under the specified temperature-pressure conditions.

 $[\]frac{b^{\prime}}{a} \begin{array}{l} \text{Indexed on the basis of a monoclinic unit cell} \\ \frac{a=12.744\pm0.001\text{\AA}}{and}, \frac{b=4.8845\pm0.0006\text{\AA}}{b=105^{\circ}1.9^{\circ}\pm0.5^{\circ}1.8$

Observed intensity, peak height.

This phase can be transformed reversibly, B-Nb₂O₅ \leftrightarrows L-Nb₂O₅ and B-Nb₂O₅ \rightleftarrows H-Nb₂O₅. However, B-Nb₂O₅ would not revert to L-Nb₂O₅ at the low temperature boundary (L'). This phase has been indexed after Laves, Petter, and Wulf [9] on the basis of a monoclinic unit cell. The parameters, a=12.744, b=4.884, c=5.563 Å, and $\beta=105^{\circ}1.9'$, were refined by least squares analyses from the indexed x-ray powder pattern given in table 2.

4.3. L-Nb₂O₅ (Low Temperature Form)

a. Stability

The low temperature form of Nb_2O_5 (L- Nb_2O_5) was first reported by Brauer [11]. This is the apparently metastable form obtained when the material is precipitated from solution and crystallized at low temperatures. When heated this phase will gradually change to poorly formed $H\text{-}Nb_2O_5$, which becomes more crystalline with increasing time and temperature. Once $H\text{-}Nb_2O_5$ is formed it does not revert to $L\text{-}Nb_2O_5$ at atmospheric

pressure at any temperature.

The only oxide known to stabilize L-Nb₂O₅ at a temperature in excess of 1000 °C at ambient pressure is Sb₂O₄ [12]. However, both F⁻ and (OH)⁻ probably also can be incorporated into this structure type [13, 14] which may also result in stabilization. Apparently L-Nb₂O₅ has a stability field at higher pressures and temperatures, as postulated by Wadsley and Andersson [1] and by Tamura [2]. In the present work, H-Nb₂O₅ was transformed to L-Nb₂O₅ and in turn L-Nb₂O₅ was transformed to H-Nb₂O₅ (see table 1). In figure 4, L-Nb₂O₅ is shown to occur as both the low temperature-high pressure and high temperature-high pressure (L'-Nb₂O₅) forms of Nb₂O₅ (see discussion sec. 5).

b. Structure

Numerous attempts to index the x-ray powder diffraction pattern of L-Nb₂O₅ have been reported in the literature. All such previous attempts were based on very limited powder data. Frevel and Rinn [15] first indexed L-Nb₂O₅ with a monoclinic unit cell and the orthorhombic subcell was indicated by Holser [16] to be similar to that of Ta₂O₅ and U₃O₈. An orthorhombic unit cell for L-Nb₂O₅ was proposed by Zvinchuck [17] with a b axis approximately 12 times the subcell. Terao [18] also showed an orthorhombic subcell and postulated a monoclinic supercell for L-Nb₂O₅ very similar to that of Frevel and Rinn [15]. From selected area electron diffraction of oxidized thin films, Spyridelis, Delavignette, and Amelinckx [19] reported that "in niobium pentoxide the spacing between the superlattice spots in the linear group is somewhat larger than in tantalum pentoxide corresponding to a smaller long spacing in direct space (which varies from 20 to 30 Å)". The authors stated that although the specimen temperature is difficult to estimate on beam heating they felt that sufficient specimen heating had occurred so that they were observing diffraction data taken from

a specimen of H-Nb₂O₅. Subsequently, precharacterized specimens of H-Nb₂O₅ were examined by Allpress, Sanders and Wadsley [20] by electron diffraction and found to be much different from the films described by Spyridelis et al. [19]. They concluded that, "in our opinion these films are much more likely to consist of low-temperature T-Nb₂O₅ (L-Nb₂O₅) or an oxygendeficient phase, or a mixture of phases closely related to it."

With increased temperature and pressure L-Nb₂O₅ was found in the present work to become more crystalline and a number of superstructure lines become clearly evident in the x-ray diffraction pattern. This pattern is very similar to that of the phase $15\text{Ta}_2\text{O}_5 \cdot 2\text{WO}_3$, the smallest unit cell found for the L-Ta₂O₅ (L-Nb₂O₅) type phases [21, 22, 23]. The crystal structure of $15\text{Ta}_2\text{O}_5 \cdot 2\text{WO}_3$ has been reported by Stephenson and Roth [24] and the x-ray diffraction powder pattern was indexed on the basis of an orthorhombic unit cell with a=6.175, b=29.29, and c=3.874 Å with the aid of intensities obtained from single crystal diffractometer data. For this composition, the b-axis is eight times the subcell $(b=3.661\times8=29.29$ Å).

In the present work all of the lines of the powder pattern of L-Nb₂O₅ can be indexed on the basis of an orthorhombic cell with $a=6.168\pm.001$, $b=29.312\pm.001$ and $c=3.936\pm.001$ A, with a and c similar to the values previously reported for the subcell. As is the case with $15\text{Ta}_2\text{O}_5 \cdot 2\text{WO}_3$, the b axis exhibits a multiplicity of 8 times the subcell and the true b axis is $b=3.664\times8=29.312\pm.001$ Å. The indexed x-ray diffraction powder pattern for L-Nb₂O₅ is given in table 3.3

Selected area electron diffraction patterns of L-Nb₂O₅ were made by J. G. Allpress, CSIRO, Melbourne, Australia, from a specimen heated to 1000 °C at 70,000 psi for 19 h. These patterns confirm that the correct unit cell is dimensionally orthorhombic with the parameters derived from the powder data. A typical example of diffraction from the hkO plane is shown in figure 5. It can be seen in this diffraction pattern that there is a multiplicity of 8 along the b axis.

For a phase with m=8 the ideal composition is $M_{16}O_{42}$ [21, 23, 24]. The compound $15Ta_2O_5 \cdot 2WO_3$ has the formula Ta₁₅WO_{40.5} for eight subcells whereas the low temperature form of Nb₂O₅ would correspond to Nb₁₆O₄₀ with two oxygen ions missing and would have a slightly different ordering scheme. Since the crystal structure of 15Ta₂O₅ · 2WO₃ has been reported from single crystal data [24] it is possible to calculate the intensities of the x-ray diffraction powder pattern of this material. The Fortran program used for the computation was developed by Smith [25] and modified by Evans [26]. The calculated integrated intensities of the powder pattern agree quite well with those published for the observed powder data [22]. The integrated intensities for the L-Nb₂O₅ powder pattern were calculated utilizing the same coordinates. The

³ B. Nolander and R. Norin (Acta Chem. Scand. **26** 3814 (1972)) have also indexed a powder pattern of "T·Nb₂O₅" with the unit cell: a=6.170, b=29.25, c=3.928 Å.

Table 3. Indexed X-Ray Diffraction Powder Pattern for $L-Nb_20_{\frac{1}{5}} \; (\text{CuK}_\alpha \; \text{radiation}) \underline{a}/$

	2 3	2 3			
hki <u>b</u> /	d _{obs}	^{2⊕} obs	20 _{calc}	I _{obs} c/	$I_{calc} \underline{d}$
130	5.217	16.98	16.98	5	6
060	4.886	18.14	18.14	1	2
001	3.934	22.58	22.57	88	100
170			25.70		3
180	3.151	28.30	28,31	100	82
200	3.085	28.92	28.93	44	33
210	3.0680	29.08	29.09	15	22
190			31.03		<1
250	2.7298	32.78	32.78	5	1
260	2.6078	34.36	34.36	3 1	2
171	2.6080	34.46	34.46	48	36
181	2.4597 2.4278	36.50 37.00	36.50 37.00	21	14
211	2.4200	37.12	37.13	10	9
2,10,0	2.1250	42.51	42.51	3	i
1,13,0	2.1177	42.66	42.66	4	ż
320			44.46		ĩ
2,11,0	2.1534	44.91	44.92	6	1
330	2.0128	45.00	45.02	6	3
1,14,0	1.9828	45.72	45.72	1	2
002	1.9689	46.06	46.08	24	19
1,13,1	1.8646	48.80	48.79	6	2
370			49.34		2
0,16,0	1.8322	49.72	49.73	16	8
321	1.8084	50.42	50.41	1	1
380	1.7931	50.88	150.881	23	12
331 1			'50.90' 52.60		1
3711			154.961		
182	1.6693	54.96	154.96	24	20
0,16,1	1.6603	55.27	55.26	23	12
202	1.6592	55.32	55.32	23	12
2,15,0	1.6507	55.63	55.63	3	2
381	1.6316	56.34	56.34	15	9
391	1 5750		57.94		1
2,16,0	1.5750	58.56	58.56	10	6 1
400 410	1.5420	59.94 60.04	59.93 60.03	4	1
3,13,0	1.5195	60.92	60.93	3	<1
450	1.4912	62.20	62.19	ĭ	<1
460			63.18	- 12	1
3,14,0			63.34		1
2,16,1	1.4622	63.58	63.57	9	5
401	1.4351	64.92	64.89	4	1
332	1.4070	66.38	66.39	3	1
372			69.80		1
0,16,2	1.3409	70.12	70.12	5	4
382	1.3255	71.06	71.06	8	6
003	1777	71.90	777		2

a/ Specimen heated to 700°C at 108,500 psi for 168 hours in a sealed Pt tube and quenched.

following assumptions were made for the calculation: space group Pm was chosen, and the z coordinates were fixed either at 0 or 1/2. Oxygen number 21 (notation of [24]) was found to be absent 3 out of 4 times in two unit cells of $15Ta_2O_5 \cdot 2WO_3$ and assumed to be completely absent in Nb_2O_5 . The calculated peak intensities of L-Nb₂O₅ [25] (given in table 3) were found to be in good agreement with those observed in the x-ray powder diffraction pattern and to agree within experimental error with those calculated for $15Ta_2O_5 \cdot 2WO_3$. The L-Nb₂O₅ specimen from which these computations were made was heated at 700 °C for




Figure 5. Selected area electron diffraction photograph of the hk0 plane of a crystal of L-Nb₂O₅ taken from a specimen heated to 1000 °C at 70,000 psi for 19 hours.

The superstructure of 8 times the subcell is clearly evident, as marked on the lower margin.

168 h at 108,500 psi. Since crystals in this specimen were too small for single crystal x-ray diffraction studies, an attempt was made to grow single crystals of low Nb₂O₅ under pressure by the addition of H₂O. The resulting material was still very fine grained and unsuitable for single crystal x-ray diffraction studies. The x-ray powder pattern was indexed on the basis of a similar orthorhombic cell with the b axis multiplicity of 8 and slightly different unit cell dimensions, a = 6.199 Å, $b = 3.640 \times 8 = 29.124$ Å, and c = 3.938 Å.

5. Discussion

In figure 4 L-Nb₂O₅ and L'-Nb₂O₅ are shown to occur in two different portions of the system, separated by the field of B-Nb₂O₅. The x-ray diffraction patterns of specimens prepared in these two fields are identical except for degree of crystallinity. There are at least two possible interpretations of the data.

The first possibility is that an unknown high temperature phase may be postulated to cool metastably through the B-field and then transform to a stable phase of the L-Nb₂O₅ type. The low temperature form of Nb₂O₅ may possibly go through an infinite series of structurally subtle transitions of the sort reported for L-Ta₂O₅ [21, 24] involving a change in the multiplicity of the b axis. This type of transition would involve a

 $[\]frac{b'}{a=6.199 \text{\AA}}$, b=29.124Å, and c=3.938Å.

⁰ Observed intensity peak heights

d/ Calculated peak intensity using Fortran program described by D. Smith [25] and modified by E. Evans [26] (based on assumptions given in text).

change in vacancy ordering and therefore in density. The structure of this original high temperature phase is, or course unknown, but may be postulated as being similar to H-Ta₂O₅ (previously found for Nb₂O₅ only from melted specimens containing some ZrO₂ [27]).

The second possibility is that a high temperaturehigh pressure polymorph may be assumed to be a phase of the L-Nb₂O₅ type which, on cooling through the B-field metastably, goes through a series of transitions to the m=8 phase at atmospheric temperature and pressure. In the first case L-Nb₂O₅ is the stable phase only in the low temperature-high pressure region. In the second case L-Nb₂O₅ is stable only in the high temperature-high pressure region and the B-polymorph is stable to ambient temperature at high pressures. Either case is equally possible even if the m=8 phase is maintained at all temperatures and pressures. The correct situation could only be solved by a high resolution high pressure-high temperature (above 900 °C) x-ray study. Unfortunately such an apparatus was not available.

The authors wish to express their thanks to J. G. Allpress, CSIRO, Melbourne, Australia, for the electron diffraction examination, to H. Yoder and G. Speicher of the Geophysical Laboratory, Carnegie Institute of Washington for their many helpful comments during the course of this work, and to J. Filliben of the National Bureau of Standards for his help in the mathematical computation involved in the pressure measurement. The writers are especially indebted to instrument maker L. Schneider of NBS for his assistance in repairing and modifying the equipment.

6. References

- [1] Wadsley, A. D., and Andersson, S., Perspectives in Structural Chemistry Vol. III, p. 1, edited by J. D. Dunitz and J. A. Ibers (John Wiley and Sons, New York, 1970).
- Tamura, S., J. Mater. Sci. 7 298 (1972).
- Yoder, H. S., Jr., Trans. Amer. Geophy. Union 31 827 (1950).
 Laus, F. A., Electrical Measurements, (McGraw-Hill, New York, 1938).

- [5] Bell, P. M., Boyd, F. R., Jr., and England, J. L., Accurate Characterization of the High-Pressure Environment, Nat. Bur. Stand. (U.S.), Spec. Publ. 326, p. 63, edited by E. C. Lloyd (1971).
- [6] Roth, R. S., Parker, H. S., Brower, W. S., and Waring, J. L., Fast Ion Transport in Solids, Solid State Batteries and Devices, sponsored by Advanced Study Institute, Belgirate, Italy (1972). Edited by W. vanGool (North Holland Publishing Co., Amsterdam, Holland, 1973), p. 217.
- [7] Gatehouse, B. M., and Wadsley, A. D., Acta Cryst. 17 1545 (1964).
- [8] Holzberg, F., Reisman, A., Berry, M., and Berkenbilt, M., J. Am. Chem. Soc. 81 3182 (1959).
- [9] Laves, F., Petter, W., and Wulf, H., Naturwissenschaften 51 633 (1964).
- [10] Schäfer, H., Schulte, F., and Gruehn, R., Angew. Chem. 76 536 (1964).
- [11] Brauer, G., Z. anorg. allgem Chem. 248 1 (1941).
- [12] Roth, R. S., and Waring, J. L., Amer. Min. 48 1348 (1963).
- [13] Andersson, S., and Aström, Acta Chemica Scan. 18 2233 (1964).
- [14] Jahnberg, L., and Andersson, S., Acta Chemica Scan. 21 615 (1967).
- [15] Frevel, L. K., and Rinn, H. N., Anal. Chem. 27 1329 (1955).
 [16] Holser, W. T., Acta Cryst. 9 196 (1956).
- Zvinchuck, R. A., Crystallography C.C.C.R. 3 744 (1958).
- [18] Terao, N., Japanese Journal of Applied Physics 2 156 (1963). [19] Spyridelis, J. S., Delavignette, P., and Amelinckx, S., Phys.
- stat. sol. 19 683 (1967). [20] Allpress, J. G., Sanders, J. V., and Wadsley, A. D., Phys. stat. sol. 25 544 (1968).
- [21] Roth, R. S., and Waring, J. L., J. Res. Nat. Bur. Stand. (U.S.), 74A (Phys. and Chem.), No. 4, 485-493 (July-Aug. 1970).
- [22] Roth, R. S., Waring, J. L., and Parker, H. S., J. Solid State Chem. 2 445 (1970).
- [23] Roth, R. S., and Stephenson, N. C., The Chemistry of Extended Defects in Non-Metallic Solids, p. 167, Edited by L. Eyring and M. O'Keeffe, (North Holland Publishing Co., Amsterdam, 1970).
- [24] Stephenson, N. C., and Roth, R. S., Acta Cryst. B27 1110 (1971).
- [25] Smith, D. K., A. Revised Program for Calculating Powder Diffraction Patterns, Lawrence Radiation Laboratory, Livermore, Calif.
- [26] Personal communication, E. Evans, National Bureau of Standards (1973).
- [27] Roth, R. S., Waring, J. L., Brower, W. S., and Parker, H. S., NBS Special Publ. 364, p. 183, Proceedings of 5th Materials Research Symposium, Edited by R. S. Roth and S. J. Schneider (1972).

(Paper 77A6-793)