

Textile Waste Water and the advanced Oxidative Treatment Process, an Overview

FagbenroOluwakemi Kehinde¹, Hamidi Abdul Aziz²

P.G. Student, School of Civil Engineering, Engineering Campus, Universiti Sains Malaysia (USM),
14300 Nibong Tebal, Penang, Malaysia¹

Professor, School of Civil Engineering, Engineering Campus, Universiti Sains Malaysia (USM), 14300 NibongTebal,
Penang, Malaysia²

ABSTRACT: Sustainability of the environment has become a focus; hence the need for improvement and monitoring of textile waste water discharges, for which major concern is color. Color in textile dyeing and finishing effluents is as a result of large amounts of dye stuffs left during the dyeing stages and inefficient dyeing processes often resulting in unfixed forms. Waste water from Textile and dyeing industries contain many pollutants, making it high in organic and inorganic chemical content, total organic carbon (TOC), chemical oxygen demand (COD), and especially, strong color. It is thus difficult to be degraded by the conventional methods; hence the use of the advanced oxidation processes (AOPs). The advanced oxidative process is certainly not a very new treatment method as it has been studied and used extensively; however, hope remains for possible improvement, hence this review. AOPs are being researched more with a view to improve on the treatability of effluents and the hope to use the method for the complete mineralization of dyes. Although they are very effective in complete mineralization of pollutants, AOPs may be very expensive when used solely.

KEYWORDS: AOPs, Textile waste water, H₂O₂, UV, Color.

1. INTRODUCTION

The importance of Textile industries in the manufacture of clothes and clothing materials cannot be over emphasized. But as good as they are, their existence also signifies a very crucial environmental issue, bothering on waste water discharges. According to [1], the textile industry is very important because its materials are used in varying ways including clothes for wearing. Products are however affected by the styles in clothing wears, changes with the season and the trends in fashion.

Dyes and colors are known to have a long history and constitute an important component in our daily lives. Natural plants and insect sources were initially used by the dye industry and then rapidly turned to synthetic manufacturing processes. The Synthetic dyes are considered a major part of our lives.[2, 3].Several of the synthetic dyes, especially azo dyes, were found to be toxic, carcinogenic and mutagenic and are thus banned throughout the world, [4, 5]. Their use and manufacture have however continued until today because of their low cost, ease of synthesis and other desirable properties [4, 6].Azo dyes are considered the largest group of dyes and or industrial colorants which currently represents 60-70% share in the worlds dye market [7-9]. The bonds are resistant to breakdown, hence, they exhibit the potential for persistence and accumulation in the environment, [4].

The textile industries extensively use synthetic dyes in the dyeing and printing process, [4]generating a very large quantity of complex chemical substances which remained as unused materials in the wastewater from various stages of textile processing[3, 10-12].

Also, the use of dyes by the textile industry has however grown steadily because they react well with fibers and their color is stable. Literatures have discussed dyes more, because of their high solubility in water and as effluents

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 8, August 2014

containing environmentally problematic compounds [13] in [14] that are visible in small quantities due to their brilliance,[15].

Table 1: Textile Processes.

Textile production involves the combination of the following processes;

Sizing;	it is the process in which cotton yarns are transformed to woven fabrics by the application of starch, modified starch, polyvinyl acetate, carboxymethylcellulose and gums.
Weaving;	the process converts yarns into fabrics in a dry operation, although, looms using water jet to insert the weft yarn-in- between the warp may be used instead.
Desizing;	this process removes the substances previously applied to the yarn in the sizing process.
Scouring;	this is done to remove natural waxes, pectins, spinning oils, and other non-cellulosic components, using hot alkaline solution (usually caustic soda or soda ash). The process involves the removal of both natural and applied substance to synthetic and natural materials. However, scouring intensity depends on the material type.
Bleaching;	the whiteness of cotton and other fibers, is increased by the removal of the natural yellowish coloring in this process.
Mercerizing;	the process is applied only in pure cotton fabrics that are treated by a concentrated caustic soda bath and a final acid wash for neutralization.
Fulling/milling;	the process mates and shrinks the fabrics to make denser, it is however restricted only to woolen fabrics and some worsted fabrics.
Dyeing;	the process adds Color to the fabric, and it includes printing.
Finishing;	finishing agents are used in this process for softening, cross-linking and waterproofing of both natural and synthetic textiles to improve specific properties of their finished fabrics.

[19-23]

The dyeing process in the textile processing generates much concern, as it uses an average of ten times more water for the preparation, dye washing, and rinsing stages [16]. Table 1.0 shows a list of most commonly used processes involved in textile fabric productions.

Textile dyeing and finishing generates the largest quantity of waste water as water is used for the cleaning of raw material and in many flushing stages in the wet production [17, 18]. 10-15% dyes are lost in effluent during the dyeing process [4]. The traditional textile finishing industry consumes about 100 liters of water to process about 1 Kg of textile material while the new closed-loop technologies such as the reuse of microbial or enzymatic treatment of dyeing effluents could help in reducing this enormous water pollution[4].

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 8, August 2014

Table 2: Textile Waste Water Characteristics.

Characteristics	Units	Value
Color	Pt.Co./ADMI	(50-2,500)
pH		(6.95-11.8)
Temperature (T)	°C	(21-62)
Chemical oxygen demand (COD)	mg ^l ⁻¹	(150-30,000)
Biological oxygen demand (BOD)	mg ^l ⁻¹	(80-6,000)
Total suspended solids (TSS)	mg ^l ⁻¹	(15-8,000)
Total Dissolved solids (TDS)	mg ^l ⁻¹	(2,900-3,100)
Total Solids (TS)	mg ^l ⁻¹	(6000-7000)
Total Kjeldahl Nitrogen	mg ^l ⁻¹	(70-80)
Oil and Grease	mg ^l ⁻¹	(5-5,500)
Total alkalinity (as CaCO ₃)	mg ^l ⁻¹	(17-22)

Essentially, pollution due to effluent from textile industry has increased during the recent years and has become a great concern to a healthy environment. These waste waters are generally characterized by high content of dyestuff, salts, Biological Oxidation Demand (BOD), Chemical Oxygen Demand (COD), suspended solid (SS), heat, color, fluctuating pH, and the presence of metal ions, [4, 19]. Typical textile waste water characteristics are shown in Table 2.0.

This review focuses on the progress and limitation of the advanced oxidative processes involving only Ultra Violet (UV) light and Hydrogen peroxide (H₂O₂) in the treatment of textile waste water in particular.

This review however, focuses on the progress of Ultra Violet (UV) light and Hydrogen peroxide (H₂O₂), in the advanced oxidative processes, for the treatment of textile waste water in particular.

II. TREATMENT PROCESSES

There exists various techniques for the treatment of industrial effluents including textile waste water which are broadly categorized into physical, chemical and biological methods [27], or a combination of the methods such as the physico-chemical and electrochemical methods.

Table 3: Treatment Processes.

CATEGORIES	TREATMENT METHOD	REFERENCES
Physical Method	Adsorption	[29-32]
	Ion exchange	[33, 34]
	Membrane filtration	[15, 35-37]
Chemical method	Coagulation/Flocculation	[38-40]
	Advanced Oxidative processes (AOP): UV (Photochemical), H ₂ O ₂ , Ozonation based processes.	[25, 41-45]
Biological Methods	Aerobic, Anaerobic, Biofilm-based, Fungal Metabolic activities.	[35, 46-49]

Although Table 3 highlights the three basic category of treatment methods, a number of treatment technologies evolve thereof and are so much interrelated that a technique may be a part of two methods. Typically, adsorption can be physical or chemical, depending on the existing bonds formed in the process.

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 8, August 2014

III. ADVANCED OXIDATION PROCESSES (AOPS).

The advanced oxidative process is certainly not a very new treatment method as it has been studied extensively, but of course there is yet room for development of the process and the need to attain higher efficiencies,[50].

AOPs are generally considered as the set of chemical processes for the treatment of water and waste water by the reactions with hydroxyl radical (OH[•]) in oxidation. The AOPs are processes based on the generation and utilization of reactive species such as hydroxyl radicals (OH[•]), which is one of the strongest inorganic oxidants (E⁰=8V). The hydroxyl radicals oxidize a broad range of organic pollutants rapidly and non- selectively, [5, 51-53]. Hydroxyl radicals are very unstable and highly reactive because of their oxidation potential, [18].

AOPs include also, both photocatalytic (involving Ultra violet light or Ultra Sound) and non-photocatalytic (dark) processes. AOPs emerge as an important destructive method for eliminating most of the organic and inorganic pollutants including reactive dyes. They have been used to enhance the biotreatability of wastewaters containing various organic compounds that are non-biodegradable and/or toxic to common microorganisms, hence AOPs in this sense are pretreatment methods, (Josmaria,L. et.al.2012)[3, 54, 55].

More commonly, and in a more practical sense though, AOP refers to the treatment processes involving UV light, Ultrasound, Ozone (O₃) and hydrogen peroxide (H₂O₂) either singly, serially or in combination with or without catalysts, such as metal ions or semiconductors,[53, 56], such as in the equations below .

- A. Photolysis (UV or VUV).
- B. Hydrogenperoxide (H₂O₂).
 - H₂O₂ + UV(i)
 - Fenton: H₂O₂+Fe²⁺/Fe³⁺.(ii)
 - Fentonlike reagents(iii)
 - Photo-Fenton: H₂O₂+Fe²⁺/Fe³⁺ + UV(iv)
- C. Ozone (O₃) .
 - Ozonation; O₃, O(v)
 - Photo-Ozonation: O₃+UV(vi)
 - Ozonation +Catalysis; O₃+ H₂O₂, O₃+ Fe²⁺/Fe³⁺(vii)
- D. Heterogeneous catalysis +UV and Photocatalysis.
[57]

The advanced oxidative processes (AOPs) are being researched more with a view to improve on the treatability of effluents and the hope to use the method for the complete mineralization of pollutants such as dyes to CO₂, water, and inorganic compounds. However, AOPs will be very expensive when used solely, [10, 17,58].

Because of the aforementioned problematic nature of dyeing effluents and due to the varying composition of the effluent, [28], also, as dye effluents are hardly biodegradable and are not very responsive to conventional physical and chemical treatment methods in singleton, and resulting in a simple transfer of pollutant from one phase to another rather than destroying them, which consequently leads to secondary pollution (Dongfang, Z. and Feng Z. 2012), therefore, the need arises for an effective treatment method for these waste water.

AOPs are therefore expected to be carefully monitored during operation, to avoid a partial oxidation of organic contaminants which may result in the formation of intermediates that are more toxic than the parent compounds as with the conventional treatment methods, [54, 58].

3.1 Ultraviolet (UV)

Ultraviolet (UV) radiation is considered as an essential element in photochemical oxidation for which the emitted wavelength plays a significant role. Such AOPs are mostly used to degrade compounds that absorb UV radiation within the corresponding range of the spectrum,[58].

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 8, August 2014

Ultraviolet (UV) have shown positive results for disinfection and removal of pathogens like estrogen 17 α -ethinylestradiol (EE2), [59]. The effectiveness of ultraviolet (UV) reacting singly or in combination with other item/method can be dependent on several factors such as pH and initial concentration, [60].

UV is sometimes enhanced in an AOP created by the addition of H₂O₂ to UV to destroy certain pathogens, and organic pollutants in water, [61].

Also, the UV/H₂O₂-based processes have shown better performance with removal efficiencies higher than 80% for all investigated parameters obtained when it was integrated with the biological treatment, thereby meeting the discharge limits while no biodegradability enhancement was shown when the process was used as an end treatment, [62].

3.2 Hydrogen Peroxide (H₂O₂).

H₂O₂, can be used in various applications because of the different ways in which it functions selectively, and because it has no gaseous release nor chemical residues as found with other chemical oxidants, [53].

However, negligible effects were observed in the presence of H₂O₂ alone, compared to the Fenton-mediated decoloration, [63]. Also, H₂O₂ alone (i.e., without UV power) proved ineffective as for both mineralizing and biodegradability enhancing agent and that the only reactive species was essentially the hydroxyl free radical OH \cdot , [62].

The effect of operating conditions was observed when measuring via a spectrophotometer at the visible maximum absorption, it was found that the rate of decolorization increased with the initial dosage of H₂O₂ up to a maximum and beyond which decoloration was inhibited, [64].

3.3 UV/ H₂O₂ Processes.

The formation of the hydroxyl radical in the UV/ H₂O₂ is based on the photo dissociation of H₂O₂ by UV radiation in the range of 200-280nm,[50, 58].

In the H₂O₂/UV process, the pH has shown to be a significant factor in dye discoloration and the process is also more effective in acidic media,[19].

In a related treatment of textile dyeing wastewater, all the processes tested, using solar advanced oxidation processes contributed to an effective decolorization and mineralization, but the most efficient process was the solar-photo-Fenton[45, 65]. The first case had an optimum catalyst concentration of 60mg Fe²⁺L⁻¹, leading to 98.5 % decolorization and 85.5 % mineralization after less than 0.1 and 5.8 kJ UVL⁻¹, respectively. A final wastewater with a COD below 250 mg O₂L⁻¹ was achieved using the combination of a solar-photo-Fenton reaction with a biological process, which required a photo-treatment of 0.5 kJUVL⁻¹, consuming 7.5 mM H₂O₂, resulting in 58.4 % of mineralization. The second case; using H₂O₂, with an optimum catalyst concentration of 100 mg Fe²⁺L⁻¹ leading to 98% decolorisation and 89% mineralization after 7.2 and 49.1 kJUVL⁻¹, respectively.

In an experiment [66], where the effect of ultrasound(US) and UV energies introduced into the Fenton like system were compared, 3 h after reaction, the removal rates of RB5, EDTA for, Total Organic Carbon(TOC), and Chemical Oxygen Demand (COD) were 100%, 96.5%, 68.6% and 92.2%, respectively. US showed a significant synergistic effect on the degradation and mineralization of both RB5 and EDTA, while UV did not achieve any improvement.

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 8, August 2014

IV.CONCLUSION

UV has shown positive results for disinfection and removal of pathogens and organic pollutants in water and waste water. The effectiveness of UV reacting singly or in combination with other methods is found to be dependent on factors which include especially, pH and initial concentration.

The UV/H₂O₂-based processes have shown better performance with removal efficiencies higher than 80% for the investigated parameters obtained when it was integrated with the biological treatment, thereby meeting the discharge limits while no- biodegradability enhancement was shown when the process was used as an end treatment.

The formation of the hydroxyl radical in the UV/ H₂O₂ process is based on the photo dissociation of H₂O₂ by UV radiation in the range of 200-280nm and H₂O₂ is variously applied because it has no gaseous release or chemical residues as found with other chemical oxidants.

REFERENCES

1. Sultana, Z., et al., Study on implementation of effluent treatment plants for safe environment from textile waste. 2013.
2. Rauf, M. and S.S. Ashraf, Radiation induced degradation of dyes—an overview. *Journal of hazardous materials*, **166**(1): p. 6-16, 2009.
3. Divya, N., A. Bansal, and A.K. Jana. Nano-Photocatalysts in the Treatment of Colored Wastewater—A Review. in *Materials Science Forum*, Trans Tech Publ. , 2013.
4. Shah, M., et al., Microbial degradation of Textile Dye (Remazol Black B) by *Bacillus* spp. ETL-2012. *J Bioremed Biodeg*, **4**(180): p. 2, 2013.
5. Salman Ashraf, S., M. Rauf, and F.H. Abdullah, A hands-on approach to teaching environmental awareness and pollutant remediation to undergraduate chemistry students. *Research in Science & Technological Education*, **30**(2): p. 173-184, 2012.
6. Bafana, A., S.S. Devi, and T. Chakrabarti, Azo dyes: past, present and the future. *Environmental Reviews*, **19**(NA): p. 350-371, 2011.
7. Mahne, D., Combination of constructed wetland and TiO₂ photocatalysis for textile wastewater treatment. Unpublished Doctoral Thesis. Univerza v Novi Gorici, podiplomski študij, 2012.
8. Wu, H., et al., Decolourization of the azo dye Orange G in aqueous solution via a heterogeneous Fenton-like reaction catalysed by goethite. *Environmental technology*, **33**(14): p. 1545-1552, 2012.
9. Singh, K. and S. Arora, Removal of synthetic textile dyes from wastewaters: a critical review on present treatment technologies. *Critical Reviews in Environmental Science and Technology*, **41**(9): p. 807-878, 2011.
10. Verma, A.K., R.R. Dash, and P. Bhunia, A review on chemical coagulation/flocculation technologies for removal of colour from textile wastewaters. *Journal of environmental management*, **93**(1): p. 154-168, 2012.
11. Yonar, T., et al., Decolorisation of textile effluent using homogeneous photochemical oxidation processes. *Coloration technology*, **121**(5): p. 258-264, 2005.
12. Cheung, W., Y. Szeto, and G. McKay, Enhancing the adsorption capacities of acid dyes by chitosan nano particles. *Bioresource technology*, **100**(3): p. 1143-1148, 2009.
13. Papić, S., et al., Decolorization and mineralization of commercial reactive dyes by using homogeneous and heterogeneous Fenton and UV/Fenton process. *J Hazard Mater*, **164**: p. 1137-1145, 2009.
14. Guimaraes, J.R., M. Guedes Maniero, and R. Nogueira de Araújo, A comparative study on the degradation of RB-19 dye in an aqueous medium by advanced oxidation processes. *Journal of environmental management*, **110**: p. 33-39, 2012.
15. Robinson, T., et al., Remediation of dyes in textile effluent: a critical review on current treatment technologies with a proposed alternative. *Bioresource technology*, **77**(3): p. 247-255, 2001.
16. Agustina, T. and H. Ang, Decolorization and Mineralization of CI Reactive Blue 4 and CI Reactive Red 2 by Fenton Oxidation Process. *International Journal*, **3**(3), 2012.
17. Oller, I., S. Malato, and J. Sánchez-Pérez, Combination of advanced oxidation processes and biological treatments for wastewater decontamination—a review. *Science of the total environment*, **409**(20): p. 4141-4166, 2011.
18. Mahamuni, N.N. and Y.G. Adewuyi, Advanced oxidation processes (AOPs) involving ultrasound for waste water treatment: a review with emphasis on cost estimation. *Ultrasonics Sonochemistry*, **17**(6): p. 990-1003, 2010.
19. Kalra, S.S., et al. Advanced Oxidation Processes for Treatment of Textile and Dye Wastewater: A Review. in *2nd International Conference on Environmental Science and Development*. 2011.
20. Ngai, E., et al., Decision support and intelligent systems in the textile and apparel supply chain: An academic review of research articles. *Expert Systems with Applications*, **41**(1): p. 81-91, 2014.
21. Correia, V.M., T. Stephenson, and S.J. Judd, Characterisation of textile wastewaters—a review. *Environmental Technology*, **15**(10): p. 917-929, 1994.
22. Babu, B.R., et al., Textile technology. *Technology*, 1995.
23. dos Santos, A.B., F.J. Cervantes, and J.B. van Lier, Review paper on current technologies for decolourisation of textile wastewaters: perspectives for anaerobic biotechnology. *Bioresource Technology*, **98**(12): p. 2369-2385, 2007.
24. Al-Kdasi, A., et al., Treatment of textile wastewater by advanced oxidation processes—a review. *Global nest: the Int. J.*, **6**(3): p. 222-230, 2004

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 8, August 2014

25. Franco, M.S. and E.B. Azevedo, Color removal of Remazol® dye baths wastewater by UV/H₂O₂ does not decrease TOC, BOD/COD, and toxicity of the effluent. *Desalination and Water Treatment*, (ahead-of-print): p. 1-8, 2013.
26. Sarayu, K. and S. Sandhya, Current technologies for biological treatment of textile wastewater—a review. *Applied biochemistry and biotechnology*, **167**(3): p. 645-661, 2012.
27. Anjaneyulu, Y., N.S. Chary, and D.S.S. Raj, Decolorization of industrial effluents—available methods and emerging technologies—a review. *Reviews in Environmental Science and Bio/Technology*, **4**(4): p. 245-273, 2005.
28. Bisschops, I. and H. Spanjers, Literature review on textile wastewater characterisation. *Environmental technology*, **24**(11): p. 1399-1411, 2003.
29. Bhatnagar, A. and M. Sillanpää, Utilization of agro-industrial and municipal waste materials as potential adsorbents for water treatment—a review. *Chemical Engineering Journal*, **157**(2): p. 277-296, 2010.
30. Lim, S.-L., W.-L. Chu, and S.-M. Phang, Use of *Chlorella vulgaris* for bioremediation of textile wastewater. *Bioresource technology*, **101**(19): p. 7314-7322, 2010.
31. Gupta, V., et al., A comparative investigation on adsorption performances of mesoporous activated carbon prepared from waste rubber tire and activated carbon for a hazardous azo dye—Acid Blue 113. *Journal of hazardous materials*, **186**(1): p. 891-901, 2011.
32. Mahmoodi, N.M., et al., Adsorption of textile dyes on Pine Cone from colored wastewater: Kinetic, equilibrium and thermodynamic studies. *Desalination*, **268**(1): p. 117-125, 2011.
33. Syafalni, S., et al., Treatment of Dye Wastewater Using Granular Activated Carbon and Zeolite Filter. *Modern Applied Science*, **6**(2): p. p37, 2012.
34. Ahmad, A., A. Idris, and B. Hameed, Color and COD reduction from cotton textile processing wastewater by activated carbon derived from solid waste in column mode. *Desalination and Water Treatment*, **41**(1-3): p. 224-231, 2012.
35. Ahmad, A.L., W.A. Harris, and B.S. Ooi, Removal of dye from wastewater of textile industry using membrane technology. *Jurnal Teknologi*, **36**(1): p. 31-44, 2012.
36. Liu, C., et al., Fouling and structural changes of Shirasu porous glass (SPG) membrane used in aerobic wastewater treatment process for microbubble aeration. *Journal of Membrane Science*, 2012.
37. Ciardelli, G., L. Corsi, and M. Marcucci, Membrane separation for wastewater reuse in the textile industry. *Resources, conservation and recycling*, **31**(2): p. 189-197, 2001.
38. Harrelkas, F., et al., Treatment of textile dye effluents using coagulation–flocculation coupled with membrane processes or adsorption on powdered activated carbon. *Desalination*, **235**(1): p. 330-339, 2009.
39. Tatsi, A., et al., Coagulation–flocculation pretreatment of sanitary landfill leachates. *Chemosphere*, **53**(7): p. 737-744, 2003.
40. Golob, V., A. Vinder, and M. Simonič, Efficiency of the coagulation/flocculation method for the treatment of dyebath effluents. *Dyes and pigments*, **67**(2): p. 93-97, 2005.
41. Arslan-Alaton, I., T. Olmez-Hanci, and S. Shayin, H₂O₂/UV-C treatment of textile preparation wastewater: kinetic investigation on alternative combinations of commercial textile preparation auxiliaries. *Environmental technology*, **33**(13): p. 1531-1537, 2012.
42. Hammami, S., et al., Comparative mineralization of textile dye indigo by photo-Fenton process and anodic oxidation using boron-doped diamond anode. *Desalination and Water Treatment*, **45**(1-3): p. 297-304, 2012.
43. Bahmani, M., et al., The photocatalytic degradation and kinetic analysis of BTEX components in polluted wastewater by UV/H₂O₂-based advanced oxidation. *Desalination and Water Treatment*, (ahead-of-print): p. 1-9, 2013.
44. Garcia, J.C., et al., Toxicity assessment of textile effluents treated by advanced oxidative process (UV/TiO₂ and UV/TiO₂/H₂O₂) in the species *Artemia salina* L. *Environmental monitoring and assessment*, **185**(3): p. 2179-2187, 2013.
45. Soares, P.A., et al., Insights into real cotton-textile dyeing wastewater treatment using solar advanced oxidation processes. *Environmental Science and Pollution Research*, p. 1-14, 2013.
46. Işık, M. and D.T. Sponza, Anaerobic/aerobic treatment of a simulated textile wastewater. *Separation and Purification Technology*, **60**(1): p. 64-72, 2008.
47. Khouni, I., B. Marrot, and R.B. Amar, Treatment of reconstituted textile wastewater containing a reactive dye in an aerobic sequencing batch reactor using a novel bacterial consortium. *Separation and Purification Technology*, **87**: p. 110-119, 2012.
48. Lotito, A.M., et al., Effective aerobic granular sludge treatment of a real dyeing textile wastewater. *International Biodeterioration & Biodegradation*, **69**: p. 62-68, 2012.
49. Kim, M., et al., Recalcitrant organic matter removal from textile wastewater by an aerobic cell-immobilized pellet column. *Water Science & Technology*, **67**(9): p. 2124-2131, 2013.
50. Vilhunen, S. and M. Sillanpää, Recent developments in photochemical and chemical AOPs in water treatment: a mini-review. *Reviews in Environmental Science and Bio/Technology*, **9**(4): p. 323-330, 2010.
51. Chakrabarti, S. and B.K. Dutta, Photocatalytic degradation of model textile dyes in wastewater using ZnO as semiconductor catalyst. *Journal of Hazardous Materials*, **112**(3): p. 269-278, 2004.
52. Dokuzoğlu, Z. and U. Alkan, Biotreatability enhancement of aqueous Reactive Black 5 by hydrogen peroxide/ultraviolet advanced oxidation process. *Coloration Technology*, **126**(5): p. 308-314, 2010.
53. Chitra, S., et al., Degradation of 1, 4-dioxane using advanced oxidation processes. *Environmental Science and Pollution Research*, **19**(3): p. 871-878, 2012.
54. Rizzo, L., Bioassays as a tool for evaluating advanced oxidation processes in water and wastewater treatment. *Water research*, **45**(15): p. 4311-4340, 2011.
55. Chan, S.H.S., et al., Recent developments of metal oxide semiconductors as photocatalysts in advanced oxidation processes (AOPs) for treatment of dye waste-water. *Journal of Chemical Technology and Biotechnology*, **86**(9): p. 1130-1158, 2011.
56. Abreu, P.d., et al., Photocatalytic Oxidation Process (UV/H₂O₂/ZnO) in the treatment and sterilization of dairy wastewater—doi: 10.4025/actascitechnol.v35i1.11132. *Acta Scientiarum. Technology*, **35**(1): p. 75-81, 2012.
57. Pera-Titus, M., et al., Degradation of chlorophenols by means of advanced oxidation processes: a general review. *Applied Catalysis B: Environmental*, **47**(4): p. 219-256, 2004.

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 3, Issue 8, August 2014

58. Poyatos, J., et al., Advanced oxidation processes for wastewater treatment: state of the art. *Water, Air, and Soil Pollution*, **205**(1-4): p. 187-204, 2010.
59. Madsen, H.T. and E.G. Sogaard, Case study of treatment of waste water for 17 α -ethinylestradiol and microorganisms with UV and photocatalysis in an on-going process of introducing AOP techniques in the Danish water sector. *Water Practice and Technology*, **7**(4), 2012.
60. Wang, D., J.R. Bolton, and R. Hofmann, Medium pressure UV combined with chlorine advanced oxidation for trichloroethylene destruction in a model water. *water research*, **46**(15): p. 4677-4686, 2012.
61. Bounty, S., R. Rodriguez, and K.G. Linden, Inactivation of Adenovirus Using Low-Dose UV/H₂O₂ based Advanced Oxidation. *Water research*, 2012.
62. Del Moro, G., et al., Comparison of UV/H₂O₂ based AOP as an end treatment or integrated with biological degradation for treating landfill leachates. *Chemical Engineering Journal*, 2013.
63. Alshamsi, F.A., et al., Comparative efficiencies of the degradation of Crystal Violet using UV/hydrogen peroxide and Fenton's reagent. *Dyes and pigments*, **74**(2): p. 283-287, 2007.
64. Aleboyeh, A., H. Aleboyeh, and Y. Moussa, "Critical" effect of hydrogen peroxide in photochemical oxidative decolorization of dyes: Acid Orange 8, Acid Blue 74 and Methyl Orange. *Dyes and Pigments*, **57**(1): p. 67-75, 2003.
65. Vilar, V.J., et al., Treatment of textile wastewaters by solar-driven advanced oxidation processes. *Solar Energy*, **85**(9): p. 1927-1934, 2011.
66. Zhou, T., et al., Rapid decolorization and mineralization of simulated textile wastewater in a heterogeneous Fenton like system with/without external energy. *Journal of hazardous materials*, **165**(1): p. 193-199, 2009.