

## The flow rate of granular materials through an orifice

C. Mankoc · A. Janda · R. Arévalo · J. M. Pastor ·  
I. Zuriguel · A. Garcimartín · D. Maza

Published online: 2 October 2008  
© Springer-Verlag 2008

### Erratum to: Granular Matter (2007) 9:407–414 DOI 10.1007/s10035-007-0062-2

In [1], we failed to indicate that when different bead diameters are used the flow rate  $W_b$  must be rescaled by the factor  $(\sqrt{d_p})^{-1}$ . Thus the expression for the flow rate used along the article is  $W_b = W/(m_b \sqrt{d_p})$ . The values of  $W_b$  presented in the manuscript, and in particular those displayed in Fig. 2, were obtained in this way. We thank E. Rame [2] for pointing this oversight to us.

### References

1. Mankoc, C., Janda, A., Arévalo, R., Pastor, J.M., Zuriguel, I., Garcimartín, A., Maza, D.: The flow rate of granular materials through an orifice. *Granul. Matter* **9**, 407–414 (2007)
2. Rame, E.: NASA Glenn Research Center, private communication

---

The online version of the original article can be found under  
doi:10.1007/s10035-007-0062-2.

C. Mankoc · A. Janda · R. Arévalo · J. M. Pastor · I. Zuriguel ·  
A. Garcimartín (✉) · D. Maza  
Departamento de Física y Matemática Aplicada,  
Facultad de Ciencias, Universidad de Navarra,  
31080 Pamplona, Spain  
e-mail: angel@fisica.unav.es