



*Citation for published version:*

Greetham, DV, Charlton, N & Poghosyan Hopes, A 2020, Total Positive Influence Domination on Weighted Networks. in H Cherifi, S Gaito, J Mendes, E Moro & L Rocha (eds), *Complex Networks and Their Applications VIII : Volume 1 Proceedings of the Eighth International Conference on Complex Networks and Their Applications COMPLEX NETWORKS 2019*. Studies in Computational Intelligence, vol. 881, Springer, pp. 325-336.  
[https://doi.org/10.1007/978-3-030-36687-2\\_27](https://doi.org/10.1007/978-3-030-36687-2_27)

*DOI:*

[10.1007/978-3-030-36687-2\\_27](https://doi.org/10.1007/978-3-030-36687-2_27)

*Publication date:*

2020

*Document Version*

Peer reviewed version

[Link to publication](#)

This is a post-peer-review, pre-copyedit version of an article published in International Conference on Complex Networks and Their Applications. The final authenticated version is available online at:  
[https://doi.org/10.1007/978-3-030-36687-2\\_27](https://doi.org/10.1007/978-3-030-36687-2_27)

**University of Bath**

**Alternative formats**

If you require this document in an alternative format, please contact:  
[openaccess@bath.ac.uk](mailto:openaccess@bath.ac.uk)

**General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

**Take down policy**

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# Total positive influence domination on weighted networks

Danica Vukadinović Greetham<sup>1</sup>, Nathaniel Charlton<sup>2</sup>, and Anush Poghosyan<sup>3</sup>

<sup>1</sup> Knowledge Media Institute, The Open University, UK  
dvg27@open.ac.uk

<sup>2</sup> billiejoecharlton@gmail.com

<sup>3</sup> University of Bath, UK  
A.Poghosyan.Hopes@bath.ac.uk

**Abstract.** We are proposing two greedy and a new linear programming based approximation algorithm for the total positive influence dominating set problem in weighted networks. Applications of this problem in weighted settings include finding: a minimum cost set of nodes to broadcast a message in social networks, such that each node has majority of neighbours broadcasting that message; a maximum trusted set in bitcoin network; an optimal set of hosts when running distributed apps etc. Extensive experiments on different generated and real networks highlight advantages and potential issues for each algorithm.

**Keywords:** domination sets, total positive influence, vertex-weighted networks, network communities

## 1 Introduction

In complex networks, one often wants to control or support a dynamic process unfolding on the network. For instance, it is beneficial to have a support community for a social network intervention to work on an individual (see e.g. [13]), so that change affirmative messages can come from multiple sources. For this reason, an intervention designer might want to identify a support subset of the whole social network, which will form the basis for intervention. In media and communication, conflicting messages often travel through the network. Identifying the minimum set of nodes that can broadcast a particular message, so that each node hears that message from majority of its neighbours would be useful (one can assume that a ‘broadcasting’ cost is associated to each node). In distributed systems, each node often has a cost assigned of running a distributed app. Then, the aim is to find the most cost effective subset of nodes in order to offer some resilience guarantees to all users - for example, that each node has at least  $\alpha * 100\%$  of its neighbourhood running the app.

In graph theory, a set of nodes such that all the other, or indeed all the nodes are connected to that set is called a *dominating set*. The related optimisation problem of finding a dominating set of minimum size is NP-complete

[12]. From the 1950s onward, different variants of this problem have been investigated. Based on problems in ad-hoc communications networks,  $k$ -domination was explored where each node not in the dominating set needs to have at least  $k$  neighbours in the dominating set. Similarly, two versions, *positive influence dominating set* where all nodes not in the dominating set  $D$  have to have at least half of its neighbourhood in  $D$  (or all nodes for the *total* version) were proposed. A generalised version, for any percentage of neighbourhood:  $\alpha$  domination (where each node, except those in dominating set, needs to have at least  $\alpha * 100$  percent of its neighbours in the dominating set) is proposed in [9]. Finally,  $\alpha$ -rate domination is defined in [11] where nodes in the dominating set are included in the requirement, and the constraint is imposed on the closed neighbourhood (neighbours and the node itself). Again, finding minimum cardinalities of  $\alpha$  and  $\alpha$ -rate dominating sets is NP-complete. In this work, we propose and experimentally analyse three new algorithms for the total positive influence dominating set problems on weighted networks, thus looking into a more general problem.

In the next section we give preliminaries and a quick overview of the relevant previous work. In Section 3, we present two greedy algorithm variants based on different strategies for node selection. In Section 4, an algorithm that exploits the network's community structure is proposed. We analyse the results obtained from different algorithms ran on families of random generated graphs and real-world networks in Section 5. Finally, we discuss our results and give some pointers to future work in Section 6.

## 2 Preliminaries

Let  $G(V, E)$ , where  $V$  is a set of nodes, and  $E$  is the set of edges between them, be a simple, undirected graph (network) with non-negative weights on the nodes, defined by a function

$$w : V \rightarrow \mathbb{R}^+ \cup \{0\}.$$

We denote with  $w_v$  the weight of a node  $v$ .

Let  $d_v$  denote a degree (a number of connections) for each  $v \in V$ . The neighbourhood  $N(v)$  of  $v$  is a set of all adjacent nodes to  $v$ , thus

$$N(v) = \{w | vw \in E.\}$$

Obviously,  $d_v = |N(v)|$ .

A total positive influence domination set (TPIDS)  $D$  is a subset of  $V$  such that for each  $v \in V$  at least  $\lceil \alpha |N(v)| \rceil$  nodes in  $N(v)$  are in  $D$ , for  $\alpha = \frac{1}{2}$ . We relax the last assumption and discuss the problem when  $\alpha \in (0, 1)$  instead. The weight of  $D$  is  $W_D = \sum_{v \in D} w_v$ . We want to find the minimum weight TPIDS (MWTPIDS).

For each  $v_i \in V$ ,  $1 \leq i \leq n$  let the variable  $x_i$  has the following meaning:  $x_i = 1$  if  $v_i$  is contained in MWTPIDS and  $x_i = 0$  otherwise. We consider the following linear programming relaxation  $LP$  of an integer program  $IP$  that

describes MWTPIDS (see [27]):

$$\begin{aligned}
 \min \quad & \sum_{i=1}^n w_i x_i \\
 \text{s.t.} \quad & \sum_{v_j \in N(v_i)} x_j \geq \lceil \alpha |N(v_i)| \rceil, \quad \forall v_i \in V \\
 & 0 \leq x_i \leq 1, \quad \forall 1 \leq i \leq n.
 \end{aligned} \tag{1}$$

The *LP 1* is polynomial-time solvable and we can compute an optimal solution  $\{\bar{x}_i\}_{1 \leq i \leq n}$ . If we denote with  $IP_{OPT}$  an optimal solution of the corresponding integer program IP we have that

$$IP_{OPT} \geq \sum_{i=1}^n w_i \bar{x}_i. \tag{2}$$

## 2.1 Previous work

Due to their suitability to a wide range of applications in networks design and control, variants of domination problems have been studied thoroughly. This includes a study of corresponding computational complexities for different variants and development of exact and approximation algorithms (e.g. [17], [1], [26]). The widely explored variants include the basic dominating set problem and its weighted version where weights are on nodes. The minimum weighted dominating set problem is one of the classic NP-hard optimisation problems in network theory [12]. A generalisation of the domination set problem on node-weighted networks, where the direct connections are replaced with shortest paths corresponding to some measure  $f$  defined on the nodes of a network, was explored in [5]. The authors have used randomised rounding to prove the approximation ratio of  $O(\log \Delta')$  for their algorithm, where  $\Delta'$  is the maximum cardinality of the sets of nodes that can be dominated by any single node through the defined shortest paths. Molnar et al. [22] proposed probabilistic dominating set selection strategies for large heterogeneous non-weighted graphs and explored how the structure of networks influences performances of degree dependent probabilistic method based approximation algorithms and greedy algorithms.

Another generalisation, the  $\alpha$ -domination problem, was introduced by Dunbar et al. in [9], where each node not in the dominating set is required to have at least  $\alpha * 100$  percents of neighbours in the dominating set. Similarly, the concept of  $\alpha$ -rate domination [11] requires each node in the network to have at least  $\alpha * 100$  percents of the closed neighbourhood in the dominating set. Both the  $\alpha$  and  $\alpha$ -rate domination problems are proven to be NP-complete. New upper bounds and randomised algorithms for finding the  $\alpha$  and  $\alpha$ -rate domination sets in terms of a parameter  $\alpha$  and network node degrees on undirected simple finite graphs are provided by using the probabilistic method in [10] and [11].

Wang et al. [28] investigated the propagation of influence in the context of social networks. They introduced new variants of domination such as the

positive influence dominating set (PIDS) and total positive influence dominating set (TPIDS). Actually, the definitions of PIDS is equivalent to  $\alpha$ -dominating set problem for a special case when  $\alpha = 1/2$ . Dinh et al. [8] have generalised PIDS and TPIDS by allowing any  $0 < \alpha < 1$ , presenting a linear time exact algorithm for trees, and approximation algorithms for minimum PIDS and TPIDS within a factor  $\ln \Delta + O(1)$ , where  $\Delta$  is the maximum degree of the network

A new greedy algorithm for minimum TPIDS is proposed in [7] and compared with two previous greedy strategies, noting that for PIDS and TPIDS different strategies are needed. Minimum TPIDS (as defined here, although the authors are calling it PIDS) is presented as an integer linear program in [21]. In [27], the alpha-rate domination on node-weighted networks is investigated. An algorithm based on randomised rounding of linear programming formulation of the problem is given, with a proof of its approximation ratio to be  $\log_2 \Delta(G)$ , where  $\Delta$  is the maximum degree of the network. With a slight modification, this algorithm can be applied to MWTIPDS, but for large networks, solving LP takes time [18]. Here we contribute with three fast alternatives and compare the quality of results for different network types.

### 3 Greedy algorithms

In this section, we consider two greedy techniques for solving the minimum weighted total positive influence dominating set problem. The Algorithm 1 below describes a generic greedy algorithm to find MWTIPDS, where we assign a cost function  $g$  (defined on the next page) to all nodes according to their weight and degree, and select the nodes with minimal cost to be in the dominating set.

---

#### Algorithm 1 Greedy algorithms for MWTIPDS

---

**Require:** A network  $G$ , a real number  $\alpha$ ,  $0 < \alpha \leq 1$

**Ensure:** A low weight TPIDS  $D$  of  $G$

```

1: Initialize  $D = \emptyset$ ; { Form a set  $D \subseteq V(G)$  }
2: for all nodes  $v \in G \setminus D$  do
3:   compute  $c_v$ ; assign  $g(v) := w_v/c_v$ 
4: end for
5: while  $\exists v \in V(G)$  s.t.  $r > 0$ ,  $r := \lceil \alpha |N(v)| \rceil - |N(v) \cap D|$  do
6:   sort  $g(v)$ 
7:   for  $k \leq r$  do
8:     add  $\arg \min_v g(v)$  to  $D$  { Add smallest  $r$  nodes according to  $g$  }
9:   end for
10:  for all nodes  $v \in G \setminus D$  do
11:    recompute  $g(v)$  { Repeat 2-4 }
12:  end for
13: end while
14: return  $D$ ; {  $D$  is a low-weight  $\alpha$ -rate dominating set }

```

---

As expected with a greedy process, this does not necessarily yield the optimal solution. We consider and implement two different strategies of cost computation, that determines the nodes added to the dominating set. Those are:

- S1*:  $c_v = d_v - n$ , where  $n$  is the number of  $v$ 's neighbours that are in  $D$  or dominated, and the cost  $g(v) = \frac{w_v}{c_v}$ , thus the nodes with large degree (discounting for neighbours that are already in domination set or dominated), but smaller weight are picked up first;
- S2*:  $c_v = \sum_{u \in N(v) \setminus D \cup S} w_u$ ,  $g(v) = \frac{w_v}{c_v}$  ( $S$  are the dominated nodes), hence the nodes with smaller weight and large neighbourhood weight are picked up first (again, we discount for neighbours already in  $D$  or dominated).

The first strategy *S1* tries to balance minimising weight with the minimising the size of a dominating set. The second strategy *S2* is based on reasoning that it should be beneficial to take 'light' nodes with 'heavy' neighbourhoods as then less heavy neighbours will be needed in the dominating set. In both cases when we calculate cost-functions, we are not considering nodes already in dominating set or dominated.

Since we may need to browse through all the neighbours of nodes in  $V$ , in total it can take  $O(n^2)$  steps to calculate domination rate for each node  $v \in V(G)$ . Then computing and sorting a cost function  $g$  for each node can take  $O(n^2)$  steps in the worst case. This needs to be recomputed in each loop iteration, hence, in total, the set  $D$  can be computed in  $O(n^3)$  steps.

## 4 An algorithm using community structure - RRWC

As the range and size of a network determine the size of the linear programme that needs to be solved, we investigated the so called block separability strategy. Our problem in its linear programming form 1, similar to the one in [27], when there is a genuine community structure in the network, can benefit from block separability (see [4]). The community structure here means that almost all the edges belonging to the nodes inside a community are toward the nodes in the same community and only very few are to the nodes in other communities. Therefore, the cost function can be (approximately) separated across the communities, the adjacency matrix is (approximately) block-diagonal, so we can solve LPs similar to those in 1 separately for each community (note that this can be done in parallel). Firstly, we split a network into communities, then we solve a linear programme for each of communities, and use randomised rounding inside communities. Finally, we check if all the nodes are  $\alpha$  dominated, and if not, we add a required number of nodes to the final solution. We implemented this algorithm in Python using NetworkX, and the module Community<sup>4</sup> that deploys the Louvain method of community detection given in [2].

We will denote this algorithm **AlgRRWC** and it is presented below, see Algorithm 2 (RRWC stands for *randomised rounding with communities*).

<sup>4</sup> <http://perso.crans.org/aynaud/communities/>

---

**Algorithm 2** Algorithm RRWC for MWTPIDS

---

**Require:** A network  $G$ , a real number  $\alpha$ ,  $0 < \alpha \leq 1$   
**Ensure:** A low weight TPIDS  $D$  of  $G$

- 1: Initialize  $D = \emptyset$ ; violation = 1
- 2: Split  $G$  into communities  $C_1, \dots, C_k$ ;
- 3: **for all**  $C_i$  **do**
- 4:   **while** no-of-runs  $< \lceil \log_2 \Delta(G) \rceil$  and violation == 1 **do**
- 5:     solve LP;  $x = \text{lp.result}$ ;
- 6:     **for all**  $x_i$  **do**
- 7:        $r = \text{random.uniform}(0, 0.5)$
- 8:       **if**  $r < x_i$  **then**
- 9:         add  $x_i$  to  $D$
- 10:      **end if**
- 11:     **end for**
- 12:     **for all**  $x_i$  **do**
- 13:       **if**  $|D \cap N(v_i)| < \lceil \alpha * N(v_i) \rceil$  **then**
- 14:         violation = 1
- 15:       **else**
- 16:         violation = 0
- 17:       **end if**
- 18:     **end for**
- 19:     no-of-run++
- 20:   **end while**
- 21: **end for**
- 22: **for all** node  $v \in G$  **do**
- 23:   **if**  $r = \lceil \alpha * |N(v)| \rceil - |D \cap N(v)| \geq 0$  **then**
- 24:     add the first lightest  $r$  neighbours not already in  $D$  to  $D$
- 25:   **end if**
- 26: **end for**
- 27: **return**  $D$ ; {  $D$  is a low-weight  $\alpha$ -rate dominating set }

---

## 5 Results

We have applied our algorithms on three real-life networks obtained from Facebook and Bitcoin Alpha. In addition, to thoroughly test advantages and potential issues for each algorithm, we created three types of random networks and several graph colouring benchmark random graphs. All experiments were run on a MacBookPro, MacOS High Sierra 10.13.6 with Intel Core i7 at 3.5GHz and 16GB of RAM.

### 5.1 Real-life networks

Firstly, two publicly available Facebook networks from network repository were obtained [25]. The first one, socfb-mich67 (fb1) is quite dense without obvious community structure, while the other one, socfb-nips-eg (fb2) is relatively sparse connecting different ego-nets. The largest connected component is extracted in each case and a random integer from 1 to 10 is assigned as a weight to each node.

We also used a real network from [19], Bitcoin-alpha network ‘who-trusts-whom network of people who trade using Bitcoin on a platform called Bitcoin Alpha’. This is a directed network with integer edge weights from  $-10$  (total distrust) to  $+10$  (total trust). Pre-processing was needed, in order to have positive weights only, and to turn maximisation into minimisation problem. We added 10 to each edge score, and then calculated the node weights  $w_v$  in following way: for each node  $v$ ,  $W_v$  denoted the sum of all incoming edges’ weights, then

$$w_v = 1 - \frac{W_v}{\max_{v \in V}(W_v)},$$

so that all weights are between 0 and 1. We then converted the edges to undirected. In this way, a minimum weight (most trusted) set of nodes is obtained, such that each node had at least  $\alpha$  neighbours in that set.

**Table 1.** Real-world network statistics:  $V$  denotes the number of nodes,  $E$  the number of edges,  $\Delta$  the max degree,  $\delta_{avg}$  the average degree, Comms the number of communities detected by Louvain algorithm and  $w_{avg}$  is the average node weight.

| network      | V    | E     | $\Delta$ | $\delta_{avg}$ | Comms | $W_{avg}$ |
|--------------|------|-------|----------|----------------|-------|-----------|
| fb1          | 3745 | 81901 | 419      | 43.74          | 9     | 5.46      |
| fb2          | 2888 | 2981  | 769      | 2.06           | 8     | 5.48      |
| bitcoinalpha | 3775 | 14120 | 511      | 7.48           | 22    | 0.98      |

## 5.2 Random networks

We have generated three different types of random networks, with 10 networks of each type. They all had a similar number of nodes and edges and were created using methods from the NetworkX [14] package.

We also used some of random graphs from DIMACS graph colouring benchmarks [24] and [23]. Weights were assigned uniformly at random from integers between 1 and 10 (including the boundaries).

**Random networks, ER type** Often used as a benchmark, our first type, ER network, Erdős-Rényi model[3] is obtained by choosing uniformly at random from a family  $\mathcal{G}(n, m)$  of all possible networks on  $n$  nodes with  $m$  edges [3] resulting in a small diameter, high clustering coefficient and no genuine community structure. We used `dense_gnm_random_graph` method from NetworkX with parameters  $n = 500, m = 5000$  to create those networks and denote them with ER.

**Preferential attachment - high clustering networks, PN type** We used another NetworkX method `powerlaw_cluster_graph` to create networks that



result in approximate power-law degree distribution and high average clustering (we used parameters  $n = 500$ ,  $m = 10$  random edges for each node, 0.8 for probability of triangles)[15] again without genuine community structure. These networks are denoted with  $PN$ .

**Planted  $l$ -partition networks, PLP type** Additionally, we have created networks that consisted of several interlinked modules or communities (in our case 5 communities with equal sizes of 100). In these networks (also called planted  $l$ -partition graphs [6]) nodes in the same community or subgraph are interconnected with higher probability, in our case  $p_{in} = 0.18$  (this value provides each community similar to other types of networks density), and nodes of different communities are connected with much smaller probability, in our case  $p_{out} = 0.0001$ . We used `random_partition_graph` NetworkX method. This results in networks having recognisable modular or block structure - with a lot of links inside those 5 communities and only few links between different communities.

**Graph colouring benchmark random graphs** We have also downloaded three random networks of different density: dsjc250-5 (an ER graph, but using  $\mathcal{G}(n, p)$  family of all graphs with  $n$  nodes and a probability of an edge between any two nodes  $p$  with  $n = 250$  and  $p = 0.5$ ) from [16] again without community structure, quite dense; r250-1 from [24] geometric random graph formed by randomly placing 250 vertices in a unit square, then putting edges between any two vertices that are within 0.1 distance of each other also from [16], relatively sparse with (local neighbourhoods) community structure.; fpsol2-i-3 from [23] from [20] register allocation graphs - a conflict graph of variables, with an edge between the two if they are active in the same range of code, with density between the other two, and some community structure. The weights for all the networks listed above were created by picking uniformly a random number from 1 to 10. The descriptive statistics for these networks are given in Table 2.

### 5.3 Comparison

We used Gurobi<sup>5</sup>, a state-of-the art commercial mathematical programming solver through its Python interface, to obtain the exact IP solutions for smaller networks. AlgRR from [27], slightly adapted to MWTPIDS, which considers the whole adjacency matrix inside a linear program, was used for larger networks. We can see from Table 3 that, as expected, AlgRRWC performs well for networks with well defined community structure (PLP graphs, fpsol2-i-3, and fb2 graph). It is much faster than AlgRR (times given include the computation of communities), in some instances three orders of magnitude, providing solutions of similar order to AlgRR and sometimes outperforming it. Comparing two greedy algorithms we observe that no simple winner between the two emerges. AlgG\_S1

<sup>5</sup> <https://www.gurobi.com>

performs better than AlgG\_S2 and AlgRRWC on ER and r250 graphs, while AlgG\_S2 is better on PN and dsjc250-5 graphs. For real networks, they are competitive with AlgRRWC only on bitcoin network for higher threshold where both perform identically. Overall AlgRRWC times and results are competitive with two greedy algorithms, and therefore, AlgRRWC is recommended as a much faster alternative to AlgRR for larger networks.

**Table 2.** Average statistics (from a sample of 10) for random generated networks and three random networks from DIMACS graph colouring benchmarks;  $V$  denotes the number of nodes,  $E$  the number of edges,  $\Delta$  the max degree,  $\delta_{avg}$  the average degree, Comms the number of communities detected by Louvain algorithm and  $w_{avg}$  is the average node weight.

| network             | V   | E      | $\Delta$ | $\delta_{avg}$ | Comms | $W_{avg}$ |
|---------------------|-----|--------|----------|----------------|-------|-----------|
| ER-500-5000         | 500 | 5000   | 34.9     | 20             | 10.1  | 5.48      |
| PLC-500-10-0.8      | 500 | 4874.3 | 143.5    | 19.5           | 8.4   | 5.46      |
| PP5-100-0.18-0.0001 | 500 | 4417.7 | 30.5     | 17.67          | 5     | 5.44      |
| dsjc250-5-rw.gexf   | 250 | 15668  | 147      | 125.34         | 6     | 5.53      |
| r250-1-rw.gexf      | 250 | 867    | 13       | 6.94           | 14    | 5.34      |
| fpsol2-i-3-rw.gexf  | 363 | 8688   | 346      | 47.87          | 4     | 5.55      |

## 6 Conclusions

Finding the set of minimum weight in a network such that each node has at least  $\alpha$  percentage of its neighbours in that set can be applied to different control and intervention problems in distributed computing and social networks. Until now, up to our knowledge, the weighted version of total positive influence domination problem did not receive much attention. Our contributions consist of two greedy strategies and a novel linear programming based algorithm for this problem. We thoroughly test all proposed algorithms on a diverse set of random and real-life networks with different structures.

Splitting linear programming formulation over communities and patching up a solution offers much faster solution, when compared with the whole network linear program AlgRR, and as expected, produces sometime even better solutions when networks have relatively well defined community structure. Two greedy strategies, one choosing nodes by sorting them according to their ratio of degree and weight and the other of choosing 'lighter' nodes with 'heavier' neighbourhood, seem to be perform better than AlgRRWC only for ER and PN graphs of moderate size, but with inferior solutions. For real-life networks with community structure AlgRRWC is viable and much faster alternative to AlgRR.

It would be interesting to explore if conditioning of matrices used in linear programming formulation can speed up solutions significantly and to see how

**Table 3.** Alpha-rate domination sets’ average sizes (#), average weights (W) and average running times (T) for AlgG\_S1, AlgG\_S2, AlgRRWC and AlgRR for three different types of networks (with a sample of 10 networks for each type) and three random networks from DIMACS graph-colouring benchmark set. In bold is given the best result of the three new algorithms, and a star denotes when AlgRRWC is better than AlgRR. For smaller networks Gurobi can be treated as a ground truth.

| network     | $\alpha$ | AlgG_S1 |               |         | AlgG_S2 |               |         | AlgRRWC |               |         | AlgRR  |        |         |
|-------------|----------|---------|---------------|---------|---------|---------------|---------|---------|---------------|---------|--------|--------|---------|
|             |          | #       | W             | Time(s) | #       | W             | Time(s) | #       | W             | Time(s) | #      | W      | Time(s) |
| ER-500-5000 | 0.25     | 293.7   | <b>1095.3</b> | 0.50    | 300.4   | 1142.5        | 0.81    | 269.3   | 1227.9        | 0.49    | 224    | 742    | 22.10   |
| ER-500-5000 | 0.50     | 401.1   | 1894.8        | 0.36    | 400.2   | <b>1893</b>   | 0.50    | 386.9   | 1968.9        | 0.47    | 339.2  | 1467.7 | 20.56   |
| ER-500-5000 | 0.75     | 472.3   | <b>2467.2</b> | 0.26    | 472.3   | 2467.9        | 0.31    | 471.3   | 2543.9        | 0.40    | 458.7  | 2386   | 22.61   |
| PN-500      | 0.25     | 214.3   | 698.1         | 0.41    | 201.4   | <b>689.1</b>  | 0.46    | 234.3   | 1261.8        | 0.56    | 137.7  | 428.8  | 18.49   |
| PN-500      | 0.50     | 364.5   | 1615.3        | 0.39    | 343.7   | <b>1527.1</b> | 0.34    | 353.7   | 1877.7        | 0.60    | 265.2  | 1047   | 17.16   |
| PN-500      | 0.75     | 471.5   | 2450.3        | 0.24    | 471.1   | <b>2444</b>   | 0.20    | 464.5   | 2552.4        | 0.56    | 419.1  | 2093.1 | 15.35   |
| PLP-5-100   | 0.25     | 318.9   | 1282.2        | 0.53    | 322.2   | 1297.8        | 0.89    | 217.2   | <b>723.3*</b> | 0.40    | 216.8  | 730.9  | 26.43   |
| PLP-5-100   | 0.50     | 403.9   | 1902.2        | 0.38    | 398.7   | 1868.8        | 0.62    | 338.1   | <b>1454.5</b> | 0.41    | 336    | 1430.6 | 17.20   |
| PLP-5-100   | 0.75     | 477.7   | 2500.3        | 0.24    | 477.4   | 2498.5        | 0.36    | 455.2   | <b>2348*</b>  | 0.39    | 458.7  | 2386   | 13.77   |
|             |          | AlgG_S1 |               |         | AlgG_S2 |               |         | AlgRRWC |               |         | Gurobi |        |         |
| dsjc250-5   | 0.25     | 84      | 203           | 0.35    | 83      | <b>199</b>    | 0.47    | 85      | 227           | 0.57    | 73     | 166    | 6.41    |
| dsjc250-5   | 0.5      | 148     | 521           | 0.24    | 146     | <b>509</b>    | 0.33    | 156     | 602           | 0.54    | 136    | 459    | 42.80   |
| dsjc250-5   | 0.75     | 208     | 989           | 0.24    | 203     | <b>949</b>    | 0.26    | 220     | 1116          | 0.51    | 196    | 888    | 903.45  |
| r250-1      | 0.25     | 226     | 1096          | 0.16    | 227     | 1106          | 0.15    | 141     | <b>675</b>    | 0.27    | 95     | 305    | 1.58    |
| r250-1      | 0.5      | 230     | <b>1136</b>   | 0.11    | 239     | 1226          | 0.11    | 230     | 1264          | 0.28    | 150    | 576    | 1.88    |
| r250-1      | 0.75     | 244     | <b>1276</b>   | 0.06    | 244     | <b>1276</b>   | 0.06    | 247     | 1330          | 0.19    | 208    | 1013   | 1.96    |
| fpsol2-i-3  | 0.25     | 110     | 403           | 0.15    | 113     | 405           | 0.15    | 109     | <b>251</b>    | 0.46    | 94     | 183    | 3.41    |
| fpsol2-i-3  | 0.5      | 197     | 774           | 0.12    | 196     | 772           | 0.13    | 198     | <b>693</b>    | 1.04    | 184    | 577    | 3.22    |
| fpsol2-i-3  | 0.75     | 287     | 1333          | 0.15    | 281     | 1303          | 0.15    | 283     | <b>1285</b>   | 0.41    | 274    | 1198   | 3.32    |

**Table 4.** Alpha-rate domination sets’ sizes (#), weights(W) and running times(T) for AlgG\_S1, AlgG\_S2, AlgRRWC and AlgRR for real-world networks and  $\alpha = 0.25, 0.5, 0.75$  respectively.

| Graph        | $\alpha$ | AlgG_S1 |                |         | AlgG_S2 |                |         | AlgRRWC |                |         | AlgRR |         |          |
|--------------|----------|---------|----------------|---------|---------|----------------|---------|---------|----------------|---------|-------|---------|----------|
|              |          | #       | W              | Time(s) | #       | W              | Time(s) | #       | W              | Time(s) | #     | W       | Time(s)  |
| fb1          | 0.25     | 3638    | 19366          | 43.59   | 3653    | 19516          | 64.09   | 2207    | <b>13681</b>   | 70.22   | 1001  | 3327    | 14294.23 |
| fb1          | 0.5      | 3642    | 19406          | 34.75   | 3645    | 19436          | 39.93   | 2882    | <b>16771</b>   | 50.52   | 1841  | 7607    | 8036.35  |
| fb1          | 0.75     | 3725    | 20236          | 16.99   | 3738    | 20366          | 16.92   | 3575    | <b>19977</b>   | 40.87   | 2692  | 13112   | 7709.50  |
| fb2          | 0.25     | 1007    | 2236           | 2.34    | 1007    | 2236           | 1.30    | 876     | <b>1760</b>    | 1.49    | 824   | 1612    | 123.14   |
| fb2          | 0.5      | 1691    | 5742           | 1.21    | 1691    | 5742           | 0.66    | 1619    | <b>5353</b>    | 1.33    | 1572  | 5266    | 1218.46  |
| fb2          | 0.75     | 2221    | <b>9601</b>    | 0.55    | 2221    | <b>9601</b>    | 0.26    | 2292    | 10184          | 1.29    | 2296  | 10222   | 1393.59  |
| bitcoinalpha | 0.25     | 3195    | 3137.63        | 45.69   | 2978    | 2921.14        | 27.96   | 2777    | <b>2733.91</b> | 38.33   | 1361  | 1315.90 | 8332.39  |
| bitcoinalpha | 0.5      | 3388    | <b>3330.19</b> | 24.40   | 3388    | <b>3330.19</b> | 18.51   | 3681    | 3626.38        | 51.62   | 974   | 931.70  | 23303.20 |
| bitcoinalpha | 0.75     | 3772    | <b>3713.49</b> | 4.74    | 3772    | <b>3713.49</b> | 3.23    | 3775    | 3716.49        | 30.89   | 2252  | 2199.55 | 3714.60  |

combination of matrix rank, density and block-models structure influences the quality and time of solutions. Also, further investigation of how skewed weight

distributions affect different algorithms is needed. We hope that our results will be helpful for network analysts in many different applications across social and communication networks. Python code and networks will be made available on GitHub<sup>6</sup>.

## References

1. Ambühl, C., Erlebach, T., Mihalák, M., Nunkesser, M.: Constant-factor approximation for minimum-weight (connected) dominating sets in unit disk graphs. In: Díaz, J., Jansen, K., Rolim, J.D.P., Zwick, U. (eds.) *Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques*. pp. 3–14. Springer Berlin Heidelberg, Berlin, Heidelberg (2006)
2. Blondel, V., Guillaume, J., Lambiotte, R., Mech, E.: Fast unfolding of communities in large networks. *J. Stat. Mech* p. P10008 (2008)
3. Bollobás, B.: *Random Graphs*. Cambridge University Press, second edn. (2001), <http://dx.doi.org/10.1017/CB09780511814068>, cambridge Books Online
4. Boyd, S., Parikh, N., Chu, E., Peleato, B., Eckstein, J.: Distributed optimization and statistical learning via the alternating direction method of multipliers. *Foundations and Trends in Machine Learning* 3(1), 1–122 (2011), <http://dx.doi.org/10.1561/22000000016>
5. Chen, N., Meng, J., Rong, J., Zhu, H.: Approximation for dominating set problem with measure functions. *Computing and Informatics* 23, 37–49 (2004)
6. Condon, A., Karp, R.: Algorithms for graph partitioning on the planted partition model. *Random Struct. Algor.* 18, 116–140 (2001)
7. Dhawan, A., Rink, M.: Positive influence dominating set generation in social networks. In: *2015 International Conference on Computing and Network Communications (CoCoNet)*. pp. 112–117 (Dec 2015)
8. Dinh, T., Shen, Y., Nguyen, D., Thai, M.: On the approximability of positive influence dominating set in social networks. *Journal of Combinatorial Optimization* 27(3), 487–503 (2014), <http://dx.doi.org/10.1007/s10878-012-9530-7>
9. Dunbar, J., Hoffman, D., Laskar, R., Markus, L.:  $\alpha$ -domination. *Discrete Math.* 211, 11–26 (2000)
10. Gagarin, A., Poghosyan, A., Zverovich, V.: Randomized algorithms and upper bounds for multiple domination in graphs and networks. *Discrete Applied Mathematics* 161(4-5), 604 – 611 (2013), <http://www.sciencedirect.com/science/article/pii/S0166218X11002423>
11. Gagarin, A., Poghosyan, A., Zverovich, V.E.: Upper bounds for alpha-domination parameters. *Graphs and Combinatorics* 25(4), 513–520 (2009)
12. Garey, M.R., Johnson, D.S.: *Computers and Intractability: A Guide to the Theory of NP-Completeness*. W. H. Freeman & Co., New York, NY, USA (1979)
13. Greaves, C., Reddy, P., Sheppard, K.: Supporting behaviour change for diabetes prevention. In: Schwarz, P., Reddy, P., Greaves, C., Dunbar, J., J., S. (eds.) *Diabetes Prevention in Practice*. pp. 19–29. Dresden: Tumaini Institute for Prevention Management (2010)
14. Hagberg, A., Schult, D., Swart, P.: Exploring network structure, dynamics, and function using networkx. In: *Proceedings of the 7th Python in Science Conference (SciPy2008)*, Pasadena, CA USA. pp. 11–15 (August 2008)

<sup>6</sup> <https://github.com/dvgreetham/domset/>

15. Holme, P., Kim, B.J.: Growing scale-free networks with tunable clustering. *Phys. Rev. E* 65, 026107 (2002)
16. Johnson, D.S., Aragon, C.R., McGeoch, L.A., Schevon, C.: Optimization by simulated annealing: An experimental evaluation; part ii, graph coloring and number partitioning. *Operations Research* 39, 378–406 (1991)
17. Klasing, R., Laforest, C.: Hardness results and approximation algorithms of  $k$ -tuple domination in graphs. *Inf. Process. Lett.* 89(2), 75–83 (Jan 2004), <http://dx.doi.org/10.1016/j.ipl.2003.10.004>
18. Lee, Y.T., Sidford, A.: Efficient inverse maintenance and faster algorithms for linear programming. In: 2015 IEEE 56th Annual Symposium on Foundations of Computer Science. pp. 230–249 (Oct 2015)
19. Leskovec, J., Krevl, A.: SNAP Datasets: Stanford large network dataset collection. <http://snap.stanford.edu/data> (Jun 2014)
20. Lewandowski, G., Condon, A.: Experiments with parallel graph coloring heuristics and applications of graph coloring (1994)
21. Lin, G., Guan, J., Feng, H.: An ilp based memetic algorithm for finding minimum positive influence dominating sets in social networks. *Physica A: Statistical Mechanics and its Applications* 500, 199 – 209 (2018), <http://www.sciencedirect.com/science/article/pii/S0378437118302218>
22. Molnár, Jr., F., Derzsy, N., Czabarka, E., Székely, L., Szymanski, B.K., Korniss, G.: Dominating scale-free networks using generalized probabilistic methods. *Scientific Reports* 4(6308) (2014), <http://www.nature.com/srep/2014/140909/srep06308/full/srep06308.html>
23. Nguyen, T.H.: Graph coloring benchmark instances. <https://turing.cs.hbg.psu.edu/txn131/graphcoloring.html> (accessed 14 Oct 2018)
24. Porumbel, D.: DIMACS graphs: Benchmark instances and best upper bounds. <http://www.info.univ-angers.fr/pub/porumbel/graphs/> (2011)
25. Rossi, R.A., Ahmed, N.K.: The network data repository with interactive graph analytics and visualization. In: Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence (2015), <http://networkrepository.com>
26. Vazquez-Araujo, F., Dapena, A., Souto-Salorio, M.J., Castro, P.M.: Calculation of the connected dominating set considering vertex importance metrics. *Entropy* 20(2) (2018), <http://www.mdpi.com/1099-4300/20/2/87>
27. Vukadinovic Greetham, D., Poghosyan, A., Charlton, N.: Weighted alpha-rate dominating sets in social networks. In: Tenth International Conference on Signal-Image Technology and Internet-Based Systems (SITIS), Marrakech, Morocco. pp. 369–375 (November 23-27 2014)
28. Wang, F., Du, H., Camacho, E., Xu, K., Lee, W., Shi, Y., Shan, S.: On positive influence dominating sets in social networks. *Theoretical Computer Science* 412(3), 265 – 269 (2011), <http://www.sciencedirect.com/science/article/pii/S0304397509007221>