Supporting Information for PCCP

Ultrafast Internal Conversion in a Low Band Gap Polymer for Photovoltaics: Experimental and Theoretical Study

Daniele Fazzi,^{a*} Giulia Grancini,^{b*} Margherita Maiuri,^b Daniele Brida,^b Giulio Cerullo,^b and Guglielmo Lanzani^{a,b}

a Center for Nano Science and Technology @ PoliMi, Istituto Italiano di Tecnologia, Via Pascoli 70/3, 20133 Milano, Italy.

bDipartimento di Fisica, Politecnico di Milano, Piazza L. da Vinci, 32, 20133 Milano, Italy

Corresponding authors: daniele.fazzi@iit.it; giulia.grancini@mail.polimi.it

S1) DFT (CAM-B3LYP, B3LYP and wB97XD/6-31G**) total energy for CPDTBT₄ in its ground state singlet (S0) and triplet (T1) state.

S2) Evaluation of the vertical excited state energies for CPDTBT₁₋₄ with: ZINDO/S calculations on AM1 optimized geometries and TD-CAMB3LYP calculations on CAM-B3LYP optimized geometries.

S3) Calculated TD-CAM-B3LYP/6-31G** Franck-Condon (FC) factors for S0 \rightarrow S1 transition for CPDTBT₁.

S4) Calculated TD-CAM-B3LYP/6-31G** Franck-Condon (FC) factors for S0→S2 transition for CPDTBT₁.

S5) Bond length differences as evaluated at the (TD)-CAMB3LYP/6-31G** level for optimized structures in S0, S1 and S2 states. Oligomer CPDTBT₄.

S6) Evaluation of the non radiative adiabatic excited state $S2 \rightarrow S1$ transition rate following the energy gap-law equation.

S7) TDDFT relaxed potential energy profiles as evaluated at the TDB3LYP and TDwB97X/6-31G** level for S0, S1, S2 and T1.

S8) Excited state energies for CPDTBT4 as evaluated with TDCAM-B3LYP, TDwB97XD, TDB3LYP/6-31G**

S9) TDDFT excited state energy variations as evaluated by displacing the nuclear geometry of CPDTB₄ along the most Raman active mode (ECC-mode)

S10) PCM (SCRF) TDDFT excited state energies for PCPDTBT_{1,4} oligomers

S1) DFT (CAM-B3LYP, B3LYP and wB97XD/6-31G**) total energy for CPDTBT₄ in its ground state singlet (S0) and triplet (T1) state:

S₀: CPDTBT₄ flat geometry (CAM-B3LYP/6-31G^{**}) = -7830.95572666 Ha S₀: CPDTBT₄ distorted geometry (CAM-B3LYP/6-31G^{**}) = -7830.95622708 Ha S₀: CPDTBT₄ distorted geometry (wB97XD/6-31G^{**}) = -7831.51193128 Ha S₀: CPDTBT₄ distorted geometry (B3LYP/6-31G^{**}) = -7832.72377798 Ha

T₁: CPDTBT₄ (UCAM-B3LYP/6-31G**) = -7830.91916325 Ha

S2) Evaluation of the vertical excited state energies for CPDTBT₁₋₄ with: ZINDO/S calculations on AM1 optimized geometries and TD-CAMB3LYP calculations on CAM-B3LYP optimized geometries.



TD-CAMB3LYP

S3) Calculated TD-CAM-B3LYP/6-31G** Franck-Condon (FC) factors for S0 \rightarrow S1 transition for CPDTBT₁.

| Freq | FC |
|----------------|--------|
| (cm-1) | |
| 26.6 | 0.0000 |
| 41.1 | 0.0000 |
| 74.8 | 0.0965 |
| 85.0 | 0.0000 |
| 105.3 | 0.0000 |
| 127.8 | 0.0000 |
| 158.3 | 0.4548 |
| 160.2 | 0.0000 |
| 198.4 | 0.0000 |
| 207.2 | 0.2858 |
| 224.6 | 0.0000 |
| 246.8 | 0.0000 |
| 257.4 | 0.2959 |
| 260.6 | 0,0000 |
| 284.0 | 0.0410 |
| 305.2 | 0.0410 |
| 319 5 | 0.2723 |
| 380 3 | 0.0000 |
| 396.7 | 0.0000 |
| JJ0.7 Л10 Л | 0.0000 |
| 413.4 | 0.0000 |
| 443.4 150 Q | 0.0033 |
| 430.8 | 0.0233 |
| 401.0 | 0.1903 |
| 501 6 | 0.0000 |
| 501.0 | 0.0000 |
| 550.5 | 0.0013 |
| 540.2 | 0.0000 |
| 576.9 | 0.1090 |
| 607.0 | 0.0149 |
| 024.7 | 0.0000 |
| 038.5 | 0.0407 |
| 6/8.6 | 0.0333 |
| 694.1 | 0.0305 |
| 696.1 | 0.0000 |
| 702.5 | 0.1282 |
| /11.3 | 0.0000 |
| 724.6 | 0.0000 |
| /65.0 | 0.0000 |
| 770.8 | 0.0000 |
| /96.2 | 0.1414 |
| 808.2 | 0.0208 |
| 818.7 | 0.0001 |
| 840.4 | 0.0304 |
| 882.3 | 0.0000 |
| 883.3 | 0.0008 |
| 909.6 | 0.0000 |
| 912.3 | 0.0017 |
| 922.7 | 0.0000 |
| 954.6 | 0.0015 |
| 965.5 | 0.0000 |

| 970.8 | 0.0000 |
|--------|--------|
| 1007.0 | 0.0001 |
| 1011.9 | 0.0022 |
| 1045.8 | 0.0000 |
| 1106.6 | 0.0024 |
| 1122.6 | 0.0004 |
| 1134.5 | 0.0004 |
| 1168.3 | 0.0000 |
| 1194.8 | 0.0000 |
| 1201.8 | 0.0187 |
| 1209.6 | 0.0128 |
| 1226.5 | 0.0001 |
| 1275.3 | 0.0092 |
| 1296.6 | 0.0008 |
| 1354.4 | 0.0620 |
| 1384.8 | 0.0504 |
| 1396.3 | 0.0280 |
| 1410.5 | 0.0489 |
| 1423.3 | 0.0000 |
| 1430.2 | 0.0136 |
| 1443.4 | 0.0001 |
| 1450.4 | 0.0140 |
| 1472.2 | 0.0733 |
| 1487.2 | 0.0302 |
| 1503.0 | 0.0299 |
| 1503.1 | 0.0002 |
| 1506.3 | 0.0000 |
| 1521.9 | 0.0002 |
| 1524.6 | 0.0019 |
| 1536.5 | 0.1015 |
| 1551.6 | 0.0126 |
| 1567.0 | 0.0577 |
| 1592.1 | 0.2575 |
| 1626.1 | 0.0467 |
| 3072.5 | 0.0000 |
| 3075.4 | 0.0000 |
| 3149.4 | 0.0000 |
| 3153.4 | 0.0000 |
| 3162.9 | 0.0000 |
| 3164.1 | 0.0000 |
| 3210.4 | 0.0000 |
| 3227.1 | 0.0000 |
| 3243.3 | 0.0000 |
| 3251.0 | 0.0000 |
| 3272.2 | 0.0000 |
| 3287.8 | 0.0000 |

S4) Calculated TD-CAM-B3LYP/6-31G** Franck-Condon (FC) factors for S0 \rightarrow S2 transition for CPDTBT₁.

Freq FC (cm-1) 17.2 0.0000 34.2 0.0000 73.2 0.0000 75.5 0.0335 108.1 0.0000 124.5 0.0000 143.6 0.0000 157.3 0.2922 183.2 0.0000 205.8 0.1181 216.5 0.0000 234.3 0.0000 256.9 0.0687 271.0 0.0000 276.8 0.1701 299.2 0.2493 317.5 0.3180 365.8 0.0000 379.2 0.0000 438.0 0.0510 438.1 0.0000 448.7 0.0171 471.8 0.0000 490.7 0.0000 497.2 0.0092 531.8 0.2130 539.9 0.0000 570.7 0.1016 608.2 0.0125 620.1 0.0495 624.4 0.0000 661.7 0.0000 676.6 0.0786 683.7 0.0000 690.9 0.1016 700.2 0.0275 724.2 0.0000 727.5 0.0000 785.2 0.0059 806.7 0.0000 823.8 0.0192 842.8 0.0005 867.4 0.0217 895.7 0.0543 911.6 0.0000 917.6 0.0168 932.2 0.0000 945.1 0.0016 946.7 0.0000 957.8 0.0000

| 988.5 | 0.0083 |
|--------|--------|
| 991.8 | 0.0000 |
| 1001.8 | 0.0175 |
| 1034.9 | 0.0000 |
| 1097.7 | 0.0001 |
| 1112.8 | 0.0000 |
| 1134.6 | 0.0090 |
| 1167.4 | 0.0001 |
| 1185.0 | 0.0800 |
| 1185.1 | 0.0005 |
| 1207.0 | 0.0315 |
| 1239.5 | 0.0064 |
| 1273.3 | 0.0001 |
| 1284.5 | 0.0124 |
| 1326.4 | 0.0098 |
| 1341.2 | 0.0026 |
| 1369.2 | 0.1315 |
| 1390.0 | 0.0000 |
| 1407.9 | 0.0688 |
| 1417.5 | 0.0000 |
| 1438.0 | 0.0065 |
| 1442.9 | 0.0079 |
| 1465.5 | 0.1037 |
| 1481.8 | 0.0105 |
| 1501.6 | 0.0000 |
| 1502.9 | 0.0000 |
| 1509.7 | 0.0041 |
| 1516.0 | 0.0200 |
| 1517.7 | 0.0064 |
| 1530.3 | 0.0094 |
| 1553.4 | 0.0001 |
| 1581.8 | 0.0389 |
| 1608.3 | 0.3855 |
| 1659.4 | 0.0059 |
| 3064.2 | 0.0000 |
| 3068.1 | 0.0000 |
| 3139.1 | 0.0000 |
| 3143.8 | 0.0000 |
| 3160.7 | 0.0000 |
| 3162.3 | 0.0000 |
| 3215.1 | 0.0000 |
| 3231.9 | 0.0000 |
| 3245.1 | 0.0000 |
| 3250.3 | 0.0000 |
| 3271.1 | 0.0000 |
| 3286.0 | 0.0000 |

S5) Bond length differences as evaluated at the (TD)-CAMB3LYP/6-31G** level for optimized structures in S0, S1 and S2 states. Oligomer CPDTBT₄.



R(S1) - R(S0) optimized geometries



S6) Evaluation of the non radiative adiabatic S2 \rightarrow S1 excited state transition rate, following the energy gap-law equation.

Non radiative decay rate [G. Lanzani, et. al., Phys. Rev. Lett., 2001, 87, 187402]:

 $k_{nr} = A^{ij} \exp(-\Delta E^{ij}/B^{ij})$

where:

A is the pre-exponential factor related to the electronic coupling between states *i* and *j*; ΔE^{ij} is the adiabatic energy (zero point energy) difference between states *i* and *j*; B^{ij} is related to the relaxation energy for the $i \rightarrow j$ transition.

For CPDTBT₄ we have:

 $\begin{array}{l} \Delta E \; (S_1 \text{-} S_0) = 1.67 \; \text{eV} \\ \Delta E \; (S_2 \text{-} S_1) = 0.35 \; \text{eV} \\ \text{B, expressed in terms of effective frequency:} \\ \omega_M \; (S_1 \text{-} S_0) \; \text{as evaluated by FC factors calculated for } S_1 \rightarrow S_0 \; \text{transition (see $\mathbf{S3})} = 1618 \text{cm}^{-1} \\ \omega_M \; (S_2 \text{-} S_1) \; \text{as evaluated by FC factors calculated for } S_2 \rightarrow S_1 \; \text{transition (see list below reported)} = 1410 \text{cm}^{-1} \end{array}$

The ratio between $S_1 \rightarrow S_0$ and $S_2 \rightarrow S_1$ for non radiative rate transitions is expressed as:

 $k_{nr} (S_1 \rightarrow S_0) / k_{nr} (S_2 \rightarrow S_1) = A^{1-0} expt(-\Delta E^{1-0}/B^{1-0}) / A^{2-1} expt(\Delta E^{2-1}/B^{2-1})$

by considering, in a first approximation, $A^{1-0} = A^{2-1}$, we have:

 $k_{nr} (S_1 \rightarrow S_0) / k_{nr} (S_2 \rightarrow S_1) = 0.00179$

By knowing (see manuscript): $k_{nr}(S_1 \rightarrow S_0) = 5.95 \times 10^9 \text{ s}^{-1}$ (determined by knowing the quantum yield and the radiative decay rate $k_{nr}(S_1 \rightarrow S_0)$)

we have:

 $k_{nr} (S_2 \rightarrow S_1) = 3.36 \times 10^{12} \text{ s}^{-1}$

hence

 $\tau_{nr}(S_2 \rightarrow S_1) = 300 fs$

FC factors evaluated for the $S_2 \rightarrow S_1$ transition (CPDTBT₁)

Freq FC (cm⁻¹) -2.8 0.0000 -1.8 0.0000 0.6 0.0000 1.2 0.0000 3.8 0.0000

| 5.3 C | 0.0000 |
|-------------------|---------|
| 26.6 | 0.0000 |
| 41 1 | 0.0000 |
| 41.1 | 0.0000 |
| 74.8 | 0.0168 |
| 85.0 | 0.0000 |
| 405.0 | 0.0000 |
| 105.3 | 0.0000 |
| 127.8 | 0.0000 |
| 100 | 0.0172 |
| 120.2 | 0.0175 |
| 160.2 | 0.0000 |
| 108 / | 0 0000 |
| 150.4 | 0.0000 |
| 207.2 | 0.0314 |
| 224.6 | 0.0000 |
| 246.0 | 0.0000 |
| 246.8 | 0.0000 |
| 257.4 | 0.1048 |
| 260 6 | 0 0000 |
| 200.0 | 0.0000 |
| 284.0 | 0.0312 |
| 305.2 | 0.0012 |
| 240 5 | 0.0012 |
| 319.5 | 0.0499 |
| 389.3 | 0.0000 |
| 206 7 | 0 0000 |
| 390.7 | 0.0000 |
| 419.4 | 0.0000 |
| 443.4 | 0.0037 |
| | 0.0057 |
| 450.8 | 0.0010 |
| 481.6 | 0.2498 |
| 102 0 | 0.0000 |
| 492.0 | 0.0000 |
| 501.6 | 0.0000 |
| 520.2 | 0 1824 |
| 550.5 | 0.1024 |
| 548.2 | 0.0000 |
| 578.9 | 0.0143 |
| co 7 0 | 0.02.02 |
| 607.0 | 0.0222 |
| 624.7 | 0.0000 |
| 628 5 | 0.0025 |
| 030.5 | 0.0025 |
| 678.6 | 0.0016 |
| 694.1 | 0.0026 |
| 001.1 | 0.0020 |
| 696.1 | 0.0000 |
| 702.5 | 0.0020 |
| 711 2 | 0 0000 |
| /11.5 | 0.0000 |
| 724.6 | 0.0000 |
| 765.0 | 0 0000 |
| 705.0 | 0.0000 |
| //0.8 | 0.0000 |
| 796.2 | 0.0104 |
| 000 2 | 0 0127 |
| 000.2 | 0.0157 |
| 818.7 | 0.0019 |
| 840.4 | 0.0065 |
| 002.2 | 0.0000 |
| 882.3 | 0.0000 |
| 883.3 | 0.0051 |
| 909 6 | 0 0000 |
| 505.0 | 0.0000 |
| 912.3 | 0.0003 |
| 922.7 | 0.0000 |
| 0546 | 0 0002 |
| 954.0 | 0.0002 |
| 965.5 | 0.0000 |
| 970.8 | 0.0000 |
| 1007.0 | 0.0007 |
| 1007.0 | 0.0007 |
| 1011.9 | 0.0093 |
| 104⊑ 0 | 0 0000 |
| 1043.0 | 0.0000 |
| 1106.6 | 0.0033 |
| 1122 6 | 0.0000 |
| 1124 5 | 0.0000 |
| 1134.5 | 0.0026 |
| 1168.3 | 0.0002 |
| 110/ 0 | 0.0000 |
| 1194.0 | 0.0000 |
| 1201.8 | 0.0078 |
| 1209 6 | 0 0002 |
| 1205.0 | 0.0002 |
| 1226.5 | 0.0436 |
| 1275.3 | 0.0017 |
| 1206 0 | 0.0027 |
| 1290.0 | 0.0027 |
| 1354.4 | 0.0665 |
| 1384 9 | 0 0086 |
| 104.0 | |
| 1205 5 | 0.0000 |
| 1396.3 | 0.0080 |

| 1423.3 | 0.0000 | |
|--------|--------|--|
| 1430.2 | 0.0466 | |
| 1443.4 | 0.0029 | |
| 1450.4 | 0.0117 | |
| 1472.2 | 0.0073 | |
| 1487.2 | 0.0136 | |
| 1503.0 | 0.0051 | |
| 1503.1 | 0.0000 | |
| 1506.3 | 0.0000 | |
| 1521.9 | 0.0050 | |
| 1524.6 | 0.0037 | |
| 1536.5 | 0.0009 | |
| 1551.6 | 0.0039 | |
| 1567.0 | 0.0030 | |
| 1592.1 | 0.0085 | |
| 1626.1 | 0.0000 | |
| 3072.5 | 0.0000 | |
| 3075.4 | 0.0001 | |
| 3149.4 | 0.0000 | |
| 3153.4 | 0.0000 | |
| 3162.9 | 0.0000 | |
| 3164.1 | 0.0000 | |
| 3210.4 | 0.0000 | |
| 3227.1 | 0.0000 | |
| 3243.3 | 0.0000 | |
| 3251.0 | 0.0000 | |
| 3272.2 | 0.0000 | |
| 3287.8 | 0.0000 | |
| | | |

S7) TDDFT relaxed potential energy profiles as evaluated at the TDB3LYP and TDwB97X/6-31G** level for S0 (red circles), S1 (blue), S2 (purple) and T1 (green).





| | TDCAMB3LYP | TDwB97XD | TDB3LYP |
|----------------|-----------------|-----------------|------------------|
| S0 → S1 | 2.06 (f = 3.78) | 2.36 (f = 3.70) | 1.31 (f = 3.31) |
| S0 → S2 | 2.36 (f = 0.23) | 2.62 (f = 0.21) | 1.57 (f = 0.05) |
| S0→S3 | 2.60 (f = 0.12) | 2.83 (f = 0.13) | 1.71 (f = 0.14) |
| S0 → S4 | 2.93 (f = 0.19) | 3.17 (f = 0.20) | 1.73 (f = 0.004) |
| S0→S8 | 3.61 (f = 0.56) | 3.82 (f = 0.92) | |

S8) Excited state energies for CPDTBT₄ as evaluated with TDCAM-B3LYP, TDwB97XD, TDB3LYP/6-31G**

S9) TDDFT (CAM-B3LYP/6-31G^{**}) excited state energy variations as evaluated by displacing the nuclear geometry of CPDTB₄ along the most Raman active mode (ECC-mode)



S10) PCM (SCRF) TDDFT (CAM-B3LYP/6-31G**) excited state energies for PCPDTBT_{1,4} oligomers (optimized geometries PCM-CAM-B3LYP/6-31G**, cholorobenzene as solvent).

- *n* S0-S1 (*vacuum*) S0-S1 (*chlorobenzene*)
- 1 3.01 (f=0.49) 2.93 (f=0.62)
- 4 2.15 (f=3.70) 2.01 (f=3.93)